

# Documented Code for datatool v2.31

Nicola L. C. Talbot

<http://www.dickimaw-books.com/>

2018-12-07

This is the documented code for the datatool bundle. See [datatool-user.pdf](#) for the main user manual.

# Contents

<b>1</b>	<b>datatool-base.sty</b>	<b>2</b>
1.1	Package Options	2
1.2	Utilities	3
1.2.1	General List Utilities	6
1.2.2	General Token Utilities	15
1.3	Locale Dependent Information	16
1.3.1	Currencies	23
1.4	Floating Point Arithmetic	25
1.5	String Macros	36
1.6	Conditionals	44
1.6.1	Determining Data Types	45
1.6.2	ifthen Conditionals	90
1.7	Loops	97
<b>2</b>	<b>datatool-fp.sty</b>	<b>100</b>
2.1	Comparison Commands	101
2.2	Functions	103
<b>3</b>	<b>datatool-pgfmath.sty</b>	<b>105</b>
3.1	Comparison Commands	105
3.2	Functions	107
<b>4</b>	<b>datatool.sty</b>	<b>110</b>
4.1	Package Declaration	110
4.2	Package Options	110
4.3	Defining New Databases	114
4.4	Accessing Data	132
4.5	Iterating Through Databases	148
4.6	DTLforeach Conditionals	171
4.7	Displaying Database	172
4.8	Editing Databases	180
4.9	Database Functions	185
4.10	Sorting Databases	196
4.11	Saving a database to an external file	206
4.12	Loading a database from an external file	214
4.13	Debugging commands	224

<b>5</b>	<b>datagidx.sty</b>	<b>226</b>
5.1	Default Settings . . . . .	226
5.2	Package Options . . . . .	236
5.3	Glossary/Index Formatting . . . . .	239
5.3.1	Predefined styles . . . . .	250
5.3.2	Location Lists . . . . .	270
5.4	Defining New Glossary/Index Databases . . . . .	276
5.5	Defining New Terms . . . . .	280
5.5.1	Options . . . . .	280
5.5.2	New Terms . . . . .	281
5.5.3	Defining Acronyms . . . . .	295
5.6	Conditionals . . . . .	295
5.7	Unsetting and Resetting . . . . .	296
5.8	Accessing Entry Information . . . . .	298
5.8.1	Using Acronyms . . . . .	311
5.9	Displaying Glossaries, Lists of Acronyms, Indices . . . . .	312
<b>6</b>	<b>databib.sty</b>	<b>322</b>
6.1	Package Declaration . . . . .	322
6.2	Package Options . . . . .	322
6.3	Loading BBL file . . . . .	322
6.4	Predefined text . . . . .	323
6.5	Displaying the bibliography . . . . .	324
6.5.1	ifthen conditionals . . . . .	340
6.6	Bibliography Style Macros . . . . .	344
6.7	Bibliography Styles . . . . .	348
6.8	Multiple Bibliographies . . . . .	367
<b>7</b>	<b>databar.sty</b>	<b>371</b>
<b>8</b>	<b>datapie.sty</b>	<b>393</b>
<b>9</b>	<b>dataplot.sty</b>	<b>406</b>
<b>10</b>	<b>person.sty</b>	<b>432</b>
10.1	Package Declaration . . . . .	432
10.2	Defining People . . . . .	432
10.3	Remove People . . . . .	434
10.4	Conditionals and Loops . . . . .	435
10.5	Predefined Words . . . . .	438
10.6	Displaying Information . . . . .	440
10.7	Extracting Information . . . . .	448
<b>Index</b>		<b>450</b>
<b>Index</b>		<b>450</b>

History	477
Change History	477

# 1 datatool-base.sty

This package provides all the basic commands needed by various packages in the datatool bundle.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool-base}[2018/12/07 v2.31 (NLCT)]
```

Required packages:

```
\RequirePackage{etoolbox}
\RequirePackage{amsmath}
\RequirePackage{xkeyval}
\RequirePackage{xfor}
\RequirePackage{ifthen}
```

Version of required that fixes `\su@IfSubStringInString`

```
\RequirePackage{substr}[2009/10/20]
```

## 1.1 Package Options

**verbose** Define key for package option `verbose`. (This also switches the `fp` messages on/off if `datatool-fp` used.) This boolean may already have been defined if `datatool` has been loaded.

```
\ifundef{\ifdtlverbose}
{
  \define@boolkey{datatool-base.sty}[dtl]{verbose}[true]{}
}%
{}
```

**math** Determine whether to use `fp` or `pgfmath` for the arithmetic commands. The default is to use `fp`.

```
\define@choickey{datatool-base.sty}{math}[\val\nr]{fp,pgfmath}{%
  \renewcommand*\@dtl@mathprocessor{#1}%
}
```

**utf8** Enable UTF-8 support in comparison handlers. This is still a bit experimental, so it needs to be explicitly switched on.

```
\define@boolkey{datatool-base.sty}[@dtl@]{utf8}[true]{}
\ifdef\UTFviii@two@octets
{\booltrue{@dtl@utf8}}%
{\boolfalse{@dtl@utf8}}
```

`\tlenableUTFviii`

```
\newcommand*\dtlenableUTFviii{\booltrue{@dtl@utf8}}
```

`\disableUTFviii`

```
\newcommand*\dtldisableUTFviii{\boolfalse{@dtl@utf8}}
```

`\@mathprocessor`

```
\providecommand*\@dtl@mathprocessor}{fp}
```

Process options:

```
\ProcessOptionsX
```

Load package dealing with numerical processes:

```
\RequirePackage{datatool-\@dtl@mathprocessor}
```

## 1.2 Utilities

```
\dtl@message \dtl@message{<message string>}
```

Displays message only if the verbose option is set.

```
\newcommand*\dtl@message[1]{%
  \ifdtlverbose\typeout{#1}\fi
}
```

`\@dtl@toks`

```
\newtoks\@dtl@toks
```

`\@dtl@tmpcount` Define temporary count register

```
\newcount\@dtl@tmpcount
```

`\dtl@tmplength` Define temporary length register:

```
\newlength\dtl@tmplength
```

```
\dtl@ifsingle \dtl@ifsingle{<arg>}{<true part>}{<>false part>}
```

If there is only one object in *<arg>* (without expansion) do *<true part>*, otherwise do false part.

```
\newcommand*\dtl@ifsingle[3]{%
  \def\@dtl@arg{#1}%
  \ifdefempty{\@dtl@arg}%
  {%
    #3%
  }%
  {%
    \@dtl@ifsingle#1\@nil{#2}{#3}%
  }%
}
```

`\@dtl@ifsingle`

```
\def\@dtl@ifsingle#1#2\@nil#3#4{%
  \def\dtl@sg@arg{#2}%
  \ifdefempty{\dtl@sg@arg}%
  {%
    #3%
  }%
  {%
    #4%
  }%
}
```

`singleorUTFviii` As above but also checks for UTF8.

```
\newcommand{\dtl@ifsingleorUTFviii}[3]{%
  \ifbool{\dtl@utf8}
  {%
    \def\@dtl@arg{#1}%
    \ifdefempty{\@dtl@arg}%
    {%
      #3%
    }%
    {%
      \expandafter\dtl@if@two@octets#1\relax\relax\dtl@end@if@two@octets
      {%
        \dtl@getfirst@UTFviii#1\@nil\end@dtl@getfirst@UTFviii
        \ifdefempty\dtl@rest{#2}{#3}%
      }%
      {%
        \@dtl@ifsingle#1\@nil{#2}{#3}%
      }%
    }%
  }%
  {%
    \dtl@ifsingle{#1}{#2}{#3}%
  }%
}
```

`ifintopenbetween`

```
\dtlifintopenbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}
```

If we're dealing with integers it's more efficient to use TeX's `\ifnum`.

```
\newcommand{\dtlifintopenbetween}[5]{%
  \ifnum#1>#2\relax
```

Greater than minimum value. Is it less than the maximum?

```
\ifnum#1<#3\relax
  #4%
\else
```

```

    #5%
  \fi
\else
  #5%
\fi
}

```

intclosedbetween `\dtlifintclosedbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}`

If we're dealing with integers it's more efficient to use T<sub>E</sub>X's `\ifnum`.

```

\newcommand{\dtlifintclosedbetween}[5]{%
  \dtlifintopenbetween{#1}{#2}{#3}{#4}%
  {%

```

Check end points.

```

  \ifnum#1=#2\relax
    #4%
  \else
    \ifnum#1=#3\relax
      #4%
    \else
      #5%
    \fi
  \fi
}%
}

```

ng@collect@body Need long versions of `'s \collect@body`. These macros are adapted from the macros defined by `amsmath`.

```

\long\def\long@collect@body#1{%
  \@envbody{\@xp#1\@xp{\the\@envbody}}%
  \edef\process@envbody{\the\@envbody\@nx\end{\@currenenvir}}%
  \@envbody\@emptytoks \def\begin@stack{b}%
  \begingroup
  \@xp\let\csname\@currenenvir\endcsname\long@collect@@body
  \edef\process@envbody{\@xp\@nx\csname\@currenenvir\endcsname}%
  \process@envbody
}

```

g@addto@envbody Adapted from `'s \addto@envbody`

```

\long\def\long@addto@envbody#1{%
  \toks@{#1}%
  \edef\dtl@tmp{\the\@envbody\the\toks@}%
  \global\@envbody\@xp{\dtl@tmp}%
}

```



g@collect@@body Adapted from 's \collect@body

```

\long\def\long@collect@@body#1\end#2{%
  \protected@edef\begin@stack{%
    \long@push@begins#1\begin\end \@xp@gobble\begin@stack
  }%
  \ifx\@empty\begin@stack
    \endgroup
    \@checkend{#2}%
    \long@addto@envbody{#1}%
  \else
    \long@addto@envbody{#1\end{#2}}%
  \fi
  \process@envbody
}

```

ong@push@begins Adapted from 's \push@begins

```

\long\def\long@push@begins#1\begin#2{%
  \ifx\end#2\else b\@xp\long@push@begins\fi
}

```

### 1.2.1 General List Utilities

\DTLifinlist `\DTLifinlist{<element>}{<list>}{<>true part>}{<>false part>}`

If *<element>* is contained in the comma-separated list given by *<list>*, then do *<>true part>* otherwise do false part. (Does a one level expansion on *<list>*, but no expansion on *<element>*.)

```

\newcommand*\DTLifinlist}[4]{%
  \def\@dtl@doifinlist##1,#1,##2\end@dtl@doifinlist{%
    \def\@before{##1}%
    \def\@after{##2}%
  }%
  \expandafter\@dtl@doifinlist\expandafter,#2,#1,\@nil
  \end@dtl@doifinlist
  \ifx\@after\@nnil
% not found
    #4%
  \else
% found
    #3%
  \fi
}

```

TLlistskipempty If true, skip empty elements in the list-related commands below.

```

\newif\ifDTLlistskipempty
\DTLlistskipemptytrue

```

`\DTLlistelement`

```
\DTLlistelement{<list>}{<idx>}
```

Does the *<idx>*th element in the list. The index should start from 1 for the first element.

```
\newrobustcmd{\DTLlistelement}[2]{%
```

The `\@for`-loop is scoped in case it's nested.

```
\begingroup
\@dtl@tmpcount=0\relax
\@for\@dtl@element:=#1\do{%
\ifDTLlistskipempty
\ifdefempty{\@dtl@element}%
}%
{%
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@dtl@element\@endfortrue\fi
}%
\else
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@dtl@element\@endfortrue\fi
\fi
}%
\if@endfor \else\@dtl@listelement@outrange{#2}\fi
\endgroup
}
```

`\DTLfetchlistelement`

```
\DTLfetchlistelement{<list>}{<idx>}{<cs>}
```

Fetches the *<idx>*th element in the list and stores in *<cs>*. The index should start from 1 for the first element.

```
\newrobustcmd{\DTLfetchlistelement}[3]{%
```

The `\@for`-loop is scoped in case it's nested.

```
\begingroup
\@dtl@tmpcount=0\relax
\@for\@dtl@element:=#1\do{%
\ifDTLlistskipempty
\ifdefempty{\@dtl@element}%
}%
{%
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@endfortrue\fi
}%
\else
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@endfortrue\fi
\fi
}
```

```

    \fi
  }%
  \if@endfor \else\def\@dtl@element{\@dtl@listelement@outofrange{#2}}\fi
  \edef\x{%
    \endgroup
    \noexpand\def\noexpand#3{\expandonce\@dtl@element}%
  }\x
}

```

ment@outofrange

```

\newcommand{\@dtl@listelement@outofrange}[1]{%
  \PackageWarning{datatool-base}{List index ‘\number#1’ out of range}%
}

```

DTLnumitemsinlist

```
\DTLnumitemsinlist{<list>}{<cmd>}
```

Counts number of non-empty elements in list and stores result in control sequence *<cmd>*.

```

\newrobustcmd{\DTLnumitemsinlist}[2]{%
  \@dtl@tmpcount=0\relax
  \@for\@dtl@element:=#1\do{%
    \ifDTLlistskipempty
      \ifdefempty{\@dtl@element}%
        {}%
        {\advance\@dtl@tmpcount by 1\relax}%
      \else
        \advance\@dtl@tmpcount by 1\relax
      \fi
    }%
  \edef#2{\number\@dtl@tmpcount}%
}

```

\dtl@choplast

```
\dtl@choplast{<list>}{<rest>}{<last>}
```

Chops the last element off a comma separated list, putting the last element in the control sequence *<last>* and putting the rest in the control sequence *<rest>*. The control sequence *<list>* is unchanged. If the list is empty, both *<last>* and *<rest>* will be empty.

```
\newcommand*{\dtl@choplast}[3]{%
```

Set *<rest>* to empty:

```
\let#2\@empty
```

Set *<last>* to empty:

```
\let#3\@empty
```

Iterate through  $\langle list \rangle$ :

```
\@for\@dtl@element:=#1\do{%  
  \ifdefempty{#3}%  
  {%
```

First iteration, don't set  $\langle rest \rangle$ .

```
}%  
{%  
  \ifdefempty{#2}%  
  {%
```

Second iteration, set  $\langle rest \rangle$  to  $\langle last \rangle$  (which is currently set to the previous value:

```
  \expandafter\toks@\expandafter{#3}%  
  \edef#2{\the\toks@}%  
}%  
{%
```

Subsequent iterations, set  $\langle rest \rangle$  to  $\langle rest \rangle, \langle last \rangle$  ( $\langle last \rangle$  is currently set to the previous value):

```
  \expandafter\toks@\expandafter{#3}%  
  \expandafter\@dtl@toks\expandafter{#2}%  
  \edef#2{\the\@dtl@toks,\the\toks@}%  
}%  
}%
```

Now set  $\langle last \rangle$  to current element.

```
  \let#3=\@dtl@element%  
}%  
}
```

$\@dtl@chopfirst$

```
\@dtl@chopfirst{\langle list \rangle}{\langle first \rangle}{\langle rest \rangle}
```

Chops first element off  $\langle list \rangle$  and store in  $\langle first \rangle$ . The remainder of the list is stored in  $\langle rest \rangle$ . ( $\langle list \rangle$  remains unchanged.)

```
\newcommand*\@dtl@chopfirst}[3]{%  
  \let#2=\@empty  
  \let#3=\@empty  
  \@for\@dtl@element:=#1\do{%  
    \let#2=\@dtl@element  
    \@endfortrue  
  }%  
  \if@endfor  
    \let#3=\@forremainder  
  \fi  
  \@endforfalse  
}
```

I made a bit of a blunder here.  $\@dtl@sortlist$  was supposed to work with commands like  $\@dtl@compare$ , but those commands require three arguments, the first being the register in

which to store the result. This contradicts the requirements of `\dtl@sortlist`. The “bug fix” in v2.26 fixed it to work with commands like `\dtl@compare`, but that broke the documented design (which breaks the glossaries package). The other problem is that `\dtl@insertinto` actually sorts in the reverse order. So v2.27 undoes the change from v2.26 to ensure backward compatibility and provides an alternative user-level command `\dlt@sortlist`, that’s designed to work with the three-argument handler commands like `\dtl@compare`.

`\dtl@sortlist` `\dtl@sortlist{<list>}{<criteria cmd>}`

Performs an insertion sort on *<list>*, where *<criteria cmd>* is a macro which takes two arguments *<a>* and *<b>*. *<criteria cmd>* must set the count register `\dtl@sortresult` to either  $-1$  (*<b>* less than *<a>*),  $0$  (*<a>* is equal to *<b>*) or  $1$  (*<b>* is greater than *<a>*.)

```
\newcommand{\dtl@sortlist}[2]{%
\def\@dtl@sortedlist{}%
\@for\@dtl@currentrow:=#1\do{%
\expandafter\dtl@insertinto\expandafter
{\@dtl@currentrow}{\@dtl@sortedlist}{#2}%
\@endforfalse}%
\let#1=\@dtl@sortedlist
}
```

`\dtl@insertinto` `\dtl@insertinto{<element>}{<sorted-list>}{<criteria cmd>}`

Inserts *<element>* into the sorted list *<sorted-list>* according to the criteria given by *<criteria cmd>* (see above.)

```
\newcommand{\dtl@insertinto}[3]{%
\def\@dtl@newsortedlist{}%
\@dtl@insertdonefalse
\@for\dtl@srtelement:=#2\do{%
\if@dtl@insertdone
\expandafter\toks@\expandafter{\dtl@srtelement}%
\edef\@dtl@newstuff{\the\toks@}%
\else
\expandafter#3\expandafter{\dtl@srtelement}{#1}%

\ifnum\dtl@sortresult<0\relax
\expandafter\toks@\expandafter{\dtl@srtelement}%
\@dtl@toks{#1}%
\edef\@dtl@newstuff{\the\@dtl@toks},{\the\toks@}%
\@dtl@insertdone true
\else
\expandafter\toks@\expandafter{\dtl@srtelement}%
```

```

        \edef\@dtl@newstuff{{\the\toks@}}%
    \fi
\fi
\ifdefempty{\@dtl@newsortedlist}%
{%
    \expandafter\toks@\expandafter{\@dtl@newstuff}%
    \edef\@dtl@newsortedlist{\the\toks@}%
}%
{%
    \expandafter\toks@\expandafter{\@dtl@newsortedlist}%
    \expandafter\@dtl@toks\expandafter{\@dtl@newstuff}%
    \edef\@dtl@newsortedlist{\the\toks@,\the\@dtl@toks}%
}%
\@endforfalse
}%
\ifdefempty{\@dtl@newsortedlist}%
{%
    \@dtl@toks{#1}%
    \edef\@dtl@newsortedlist{{\the\@dtl@toks}}%
}%
{%
    \if@dtl@insertdone
    \else
        \expandafter\toks@\expandafter{\@dtl@newsortedlist}%
        \@dtl@toks{#1}%
        \edef\@dtl@newsortedlist{\the\toks@,{\the\@dtl@toks}}%
    \fi
}%
\global\let#2=\@dtl@newsortedlist
}

```

`\dtlsortlist` `\dtlsortlist{<list>}{<criteria cmd>}`

As `\dtl@sortlist` but the `<criteria>` command must take three arguments.

```

\newcommand{\dtl@sortlist}[2]{%
\def\@dtl@sortedlist{}%
\@for\@dtl@currentrow:=#1\do{%
\expandafter\dtlinsertinto\expandafter
{\@dtl@currentrow}{\@dtl@sortedlist}{#2}%
\@endforfalse}%
\let#1=\@dtl@sortedlist
}

```

`\dtlinsertinto` `\dtlinsertinto{<element>}{<sorted-list>}{<criteria cmd>}`

Inserts  $\langle element \rangle$  into the sorted list  $\langle sorted-list \rangle$  according to the criteria given by  $\langle criteria cmd \rangle$ , which should be a command that takes three arguments  $\{\langle reg \rangle\}\{\langle A \rangle\}\{\langle B \rangle\}$ , where  $\langle reg \rangle$  is a count register in which to store the result,  $\langle A \rangle$  is the first element and  $\langle B \rangle$  is the second element to compare.

```

\newcommand{\dtlinsertinto}[3]{%
  \def\@dtl@newsortedlist{}%
  \@dtl@insertdonefalse
  \@for\dtl@srtelement:=#2\do{%
    \expandafter\DTLifSubString\expandafter{\dtl@srtelement}{,}%
    {%
      \expandafter\toks@\expandafter{\dtl@srtelement}%
      \edef\dtl@srtelement{\the\toks@}%
    }%
    {%
      }%
  }
  \if@dtl@insertdone
    \let\@dtl@newstuff\dtl@srtelement
  \else
    \expandafter#3\expandafter\dtl@sortresult
    \expandafter{\dtl@srtelement}{#1}%
    \ifnum\dtl@sortresult>0\relax
      \DTLifSubString{#1}{,}%
      {%
        \@dtl@toks{#1}%
      }%
      {%
        \@dtl@toks{#1}%
      }%
      \expandafter\toks@\expandafter{\dtl@srtelement}%
      \edef\@dtl@newstuff{\the\@dtl@toks,\the\toks@}%
      \@dtl@insertdonetrue
    \else
      \expandafter\toks@\expandafter{\dtl@srtelement}%
      \edef\@dtl@newstuff{\the\toks@}%
      \let\@dtl@newstuff\dtl@srtelement
    \fi
  \fi
  \ifempty{\@dtl@newsortedlist}%
  {%
    \expandafter\toks@\expandafter{\@dtl@newstuff}%
    \edef\@dtl@newsortedlist{\the\toks@}%
  }%
  {%
    \expandafter\toks@\expandafter{\@dtl@newsortedlist}%
    \expandafter\@dtl@toks\expandafter{\@dtl@newstuff}%
    \edef\@dtl@newsortedlist{\the\toks@,\the\@dtl@toks}%
  }%
  \@endforfalse
}%

```

```

\ifdefempty{\@dtl@newsortedlist}%
{%
  \DTLifSubString{#1}{,}%
  {%
    \@dtl@toks{#1}%
  }%
  {%
    \@dtl@toks{#1}%
  }%
  \edef\@dtl@newsortedlist{\the\@dtl@toks}%
}%
{%
  \if@dtl@insertdone
  \else
  \DTLifSubString{#1}{,}%
  {%
    \@dtl@toks{#1}%
  }%
  {%
    \@dtl@toks{#1}%
  }%
  \expandafter\toks@\expandafter{\@dtl@newsortedlist}%
  \edef\@dtl@newsortedlist{\the\toks@,\the\@dtl@toks}%
  \fi
}%
\global\let#2=\@dtl@newsortedlist
}

```

`\edtlininsertinto` `\edtlininsertinto{<element>}{<sorted-list>}{<criteria cmd>}`

First expands *<element>* before inserting into the list.

```

\newcommand*{\edtlininsertinto}[3]{%
  \protected@edef\dtl@srtelement{#1}%
  \expandafter\dtlininsertinto\expandafter{\dtl@srtelement}{#2}{#3}%
}

```

`@dtl@insertdone` Define conditional to indicate whether the new entry has been inserted into the sorted list.

```

\newif\if@dtl@insertdone

```

`\dtl@sortresult` Define `\dtl@sortresult` to be set by comparison macro.

```

\newcount\dtl@sortresult

```

This next command is based on the list iteration exercise given at <http://www.dickimaw-books.com/latex/admin/html/foreachtips.shtml#oxfordcomma> It's designed to format a comma-separated list using `\DTLlistformatsep` between each item except for the last. The separator for the last pair is `\DTLlistformatlastsep` if the list only contains two items or



\DTLlistformatoxford\DTLlistformatlastsep if the list contains three or more items. Each item is formatted according to \DTLlistformatitem.

DTLlistformatsep

```
\newcommand*\DTLlistformatsep}{, }
```

DTLlistformatoxford

```
\newcommand*\DTLlistformatoxford}{}
```

\DTLandname

```
\ifdef\andname
{\newcommand*\DTLandname}{\andname}}
{\newcommand*\DTLandname}{\&}}
```

DTLlistformatlastsep

```
\newcommand*\DTLlistformatlastsep){ \DTLandname\space}
```

DTLlistformatitem

```
\newcommand*\DTLlistformatitem}[1]{#1}
```

DTLformatlist@handler

```
\newcommand*\@dtl@formatlist@handler}[1]{%
  \@dtl@formatlist@itemsep
  \@dtl@formatlist@lastitem
  \renewcommand{\@dtl@formatlist@lastitem}{%
    \renewcommand{\@dtl@formatlist@itemsep}{%
      \DTLlistformatsep
      \renewcommand*\@dtl@formatlist@prelastitemsep}{%
        \DTLlistformatoxford}}%
    \renewcommand{\@dtl@formatlist@prelastitem}{%
      \@dtl@formatlist@prelastitemsep
      \DTLlistformatlastsep}%
    \DTLlistformatitem{#1}%
  }%
}%
```

\DTLformatlist

Formats the comma-separated list supplied in its argument. The unstarred version adds grouping.

```
\newrobustcmd*\DTLformatlist}{%
  \@ifstar{\s@dtlformatlist}{\@dtlformatlist}%
}
```

\s@dtlformatlist

Starred version of \DTLformatlist doesn't add grouping.

```
\newcommand*\s@dtlformatlist}[1]{%
  \def\@dtl@formatlist@itemsep}{%
  \def\@dtl@formatlist@lastitem}{%
  \def\@dtl@formatlist@prelastitem}{%
  \def\@dtl@formatlist@prelastitemsep}{%
}
```

```

\@for\@dtl@formatlist@item:=#1\do{%
  \ifDTLlistskipempty
    \ifdefempty{\@dtl@formatlist@item}%
    {}%
    {\expandafter\@dtl@formatlist@handler\expandafter{\@dtl@formatlist@item}}%
  \else
    \expandafter\@dtl@formatlist@handler\expandafter{\@dtl@formatlist@item}%
  \fi
}%
\@dtl@formatlist@prelastitem\@dtl@formatlist@lastitem
}

```

\@dtlformatlist Unstarred version of \DTLformatlist adds grouping.

```
\newcommand*{\@dtlformatlist}[1]{\s@dtlformatlist{#1}}
```

## 1.2.2 General Token Utilities

```
\@dtl@toks@gput@right@cx{\@dtl@toks@name}{\@dtl@stuff}
```

Globally appends stuff to token register \@dtl@toks@name

```

\newcommand{\@dtl@toks@gput@right@cx}[2]{%
  \def\@dtl@toks@name{#1}%
  \edef\@dtl@stuff{#2}%
  \global\csname\@dtl@toks@name\endcsname\expandafter
  \expandafter\expandafter{\expandafter\the
  \csname\expandafter\@dtl@toks@name\expandafter\endcsname\@dtl@stuff}%
}

```

```
\@dtl@toks@gconcat@middle@cx{\@dtl@toks@name}{\@dtl@before}{\@dtl@stuff}{\@dtl@after}
```

Globally sets token register \@dtl@toks@name to the contents of \@dtl@before concatenated with \@dtl@stuff (expanded) and the contents of \@dtl@after

```

\newcommand{\@dtl@toks@gconcat@middle@cx}[4]{%
  \def\@dtl@toks@name{#1}%
  \edef\@dtl@stuff{#3}%
  \global\csname\@dtl@toks@name\endcsname\expandafter\expandafter
  \expandafter\expandafter\expandafter
  \expandafter\expandafter{\expandafter\expandafter\expandafter
  \the\expandafter\expandafter\expandafter#2%
  \expandafter\@dtl@stuff\the#4}%
}

```

## 1.3 Locale Dependent Information

`@numgrpsepcount` Define count register to count the digits between the number group separators.  
`\newcount\@dtl@numgrpsepcount`

`\@dtl@decimal` The current decimal character is stored in `\@dtl@decimal`.  
`\newcommand*\@dtl@decimal}{.}`

`numbergroupchar` The current number group character is stored in `\@dtl@numbergroupchar`.  
`\newcommand*\@dtl@numbergroupchar}{,}`

`DTLsetnumberchars` `\DTLsetnumberchars{<number group char>}{<decimal char>}`

This sets the decimal character and number group characters.

```
\newcommand*\DTLsetnumberchars[2]{%
  \renewcommand*\@dtl@numbergroupchar{#1}%
  \renewcommand*\@dtl@decimal}{#2}%
  \@dtl@construct@getnums
  \@dtl@construct@stripnumgrpchar{#1}%
}
```

`construct@getintfrac` `\@dtl@construct@getintfrac{<char>}`

This constructs the macros for extracting integer and fractional parts from a real number using the decimal character `<char>`.

`converttodecimal` `\DTLconverttodecimal{<num>}{<cmd>}`

`\DTLconverttodecimal` will convert locale dependent `<num>` a decimal number in a form that can be used in the macros defined in the `fp` package. The resulting number is stored in `<cmd>`. This command has to be redefined whenever the decimal and number group characters are changed as they form part of the command definitions.

```
\edef\@dtl@construct@getintfrac#1{%
  \noexpand\def\noexpand\@dtl@getintfrac##1#1##2\noexpand\relax{%
    \noexpand\@dtl@getintpart{##1}%
    \noexpand\def\noexpand\@dtl@fracpart{##2}%
    \noexpand\ifempty{\noexpand\@dtl@fracpart}
    {%
      \noexpand\def\noexpand\@dtl@fracpart{0}%
    }%
  }%
```

```

\dtl@getfracpart##2\relax
\dtl@choptrailingzeroes{\dtl@fracpart}%
}%
}%
\dtl@getfracpart##1#1\relax{%
\dtl@fracpart{##1}%
}%
\DTLconverttodecimal##1##2{%
\dtl@ifsingle{##1}%
{%
\expandafter\dtl@toks@\expandafter{##1}%
\edef\dtl@tmp{\the\dtl@toks}%
}%
{%
\dtl@tmp{##1}%
}%
\dtl@standardize@currency\dtl@tmp
\ifempty{\dtl@org@currency}%
{%
}%
{%
\let\dtl@currency\dtl@org@currency
}%
\expandafter
\dtl@getintfrac\dtl@tmp#1\relax
\edef##2{\dtl@intpart.\dtl@fracpart}%
}%
}

```

`\dtl@construct@getnums` The following calls the above with the relevant decimal character:

```

\newcommand*\dtl@construct@getnums{%
\expandafter\dtl@construct@getintfrac\expandafter{\dtl@decimal}%
}

```

`\dtl@get@intpart` The following gets the integer part (adjusting for repeating +/- signs if necessary.) Sets `\dtl@intpart`.

```

\newcommand*\dtl@get@intpart}[1]{%
\dtl@tmpcount=1\relax
\def\dtl@intpart{##1}%
\ifx\dtl@intpart\empty
\def\dtl@intpart{0}%
\else
\def\dtl@intpart{}%
\dtl@get@int@part#1.\relax%
\fi
\ifnum\dtl@tmpcount<0\relax
\edef\dtl@intpart{-\dtl@intpart}%
\fi
\dtl@strip@numgrpchar{\dtl@intpart}%
}

```

```
}
```

tl@get@int@part

```
\def\@dtl@get@int@part#1#2\relax{%  
  \def\@dtl@argi{#1}%  
  \def\@dtl@argii{#2}%  
  \ifx\protect#1\relax%  
    \let\@dtl@get@nextintpart=\@dtl@get@int@part  
  \else  
    \expandafter\ifx\@dtl@argi\${%  
      \let\@dtl@get@nextintpart=\@dtl@get@int@part  
    \else  
      \ifx-#1%  
        \multiply\@dtl@tmpcount by -1\relax  
        \let\@dtl@get@nextintpart=\@dtl@get@int@part  
      \else  
        \if\@dtl@argi+%  
          \let\@dtl@get@nextintpart=\@dtl@get@int@part  
        \else  
          \def\@dtl@intpart{#1}%  
          \ifx.\@dtl@argii  
            \let\@dtl@get@nextintpart=\@gobble  
          \else  
            \let\@dtl@get@nextintpart=\@dtl@get@next@intpart  
          \fi  
        \fi  
      \fi  
    \fi  
  \fi  
  \fi  
  \fi  
  \@dtl@get@nextintpart#2\relax  
}
```

et@next@intpart

```
\def\@dtl@get@next@intpart#1.\relax{%  
  \edef\@dtl@intpart{\@dtl@intpart#1}%  
}
```

optrailingzeroes

```
\@dtl@choptrailingzeroes{<cmd>}
```

Chops trailing zeroes from number given by *<cmd>*.

```
\newcommand*{\@dtl@choptrailingzeroes}[1]{%  
  \def\@dtl@tmpcpz{}%  
  \expandafter\@dtl@chop@trailingzeroes#1\@nil%  
  \let#1=\@dtl@tmpcpz  
}
```

@trailingzeroes Trailing zeroes are chopped using a recursive algorithm. \@dtl@tmpcpz needs to be set before using this. (The chopped number is put in this control sequence.)

```
\def\@dtl@chop@trailingzeroes#1#2\@nil{%
  \dtlifnumeq{#2}{0}%
  {%
    \edef\@dtl@tmpcpz{\@dtl@tmpcpz#1}%
    \let\@dtl@chopzeroesnext=\@dtl@gobbletonil
  }%
  {%
    \edef\@dtl@tmpcpz{\@dtl@tmpcpz#1}%
    \let\@dtl@chopzeroesnext=\@dtl@chop@trailingzeroes
  }%
  \@dtl@chopzeroesnext#2\@nil
}
```

No-op macro to end recursion:

dtl@gobbletonil

```
\def\@dtl@gobbletonil#1\@nil{}
```

@truncatedecimal

```
\@dtl@truncatedecimal<cmd>
```

Truncates decimal given by *<cmd>* to an integer (assumes the number is in decimal format with full stop as decimal point.)

```
\newcommand*\@dtl@truncatedecimal}[1]{%
  \expandafter\@dtl@truncatedecimal#1.\@nil#1%
}
```

truncatedecimal

```
\def\@dtl@truncatedecimal#1.#2\@nil#3{%
  \def#3{#1}%
}
```

strip@numgrpchar

```
\@dtl@strip@numgrpchar{<cmd>}
```

Strip the number group character from the number given by *<cmd>*.

```
\newcommand*\@dtl@strip@numgrpchar}[1]{%
  \def\@dtl@stripped{}%
  \edef\@dtl@do@strip@numgrpchar{%
    \noexpand\@dtl@strip@numgrpchar#1\@dtl@numbergroupchar
    \noexpand\relax
  }%
  \@dtl@do@strip@numgrpchar
```

```

    \let#1=\@dtl@stripped
}

```

stripnumgrpchar The following macro constructs \@dtl@strip@numgrpchar.

```

\edef\@dtl@construct@stripnumgrpchar#1{%
  \noexpand\def\noexpand\@dtl@strip@numgrpchar##1#1##2\noexpand\relax{%
    \noexpand\expandafter\noexpand\toks@\noexpand\expandafter
      {\noexpand\@dtl@stripped}%
    \noexpand\edef\noexpand\@dtl@stripped{%
      \noexpand\the\noexpand\toks@
        ##1%
    }%
    \noexpand\def\noexpand\@dtl@tmp{##2}%
    \noexpand\ifx\noexpand\@dtl@tmp\noexpand\@empty
      \noexpand\let\noexpand\@dtl@next=\noexpand\relax
    \noexpand\else
      \noexpand\let\noexpand\@dtl@next=\noexpand\@dtl@strip@numgrpchar
    \noexpand\fi
    \noexpand\@dtl@next##2\noexpand\relax
  }%
}

```

Ldecimaltolocale

```
\DTLdecimaltolocale{<number>}{<cmd>}
```

Define command to convert a decimal number into the locale dependent format. Stores result in *<cmd>* which must be a control sequence.

```

\newcommand*{\DTLdecimaltolocale}[2]{%
  \edef\@dtl@tmpdtl{#1}%
  \expandafter\@dtl@decimaltolocale\@dtl@tmpdtl.\relax
  \dtlifnumeq{\@dtl@fracpart}{0}%
  {%
    \edef#2{\@dtl@intpart}%
  }%
  {%
    \edef#2{\@dtl@intpart\@dtl@decimal\@dtl@fracpart}%
  }%
}

```

decimaltolocale Convert the integer part (store in \@dtl@intpart)

```

\def\@dtl@decimaltolocale#1.#2\relax{%
  \@dtl@decimaltolocaleint{#1}%
  \def\@dtl@fracpart{#2}%
  \ifdefempty\@dtl@fracpart
  {%
    \def\@dtl@fracpart{0}%
  }%
}

```

```

    {%
      \@dtl@decimal@to@localefrac#2\relax
    }%
  }

```

decimal@to@localeint

```

\def\@dtl@decimal@to@localeint#1{%
  \@dtl@tmpcount=0\relax
  \@dtl@countdigits#1.\relax
  \@dtl@numgrpsepcount=\@dtl@tmpcount\relax
  \divide\@dtl@numgrpsepcount by 3\relax
  \multiply\@dtl@numgrpsepcount by 3\relax
  \advance\@dtl@numgrpsepcount by -\@dtl@tmpcount\relax
  \ifnum\@dtl@numgrpsepcount<0\relax
    \advance\@dtl@numgrpsepcount by 3\relax
  \fi
  \def\@dtl@intpart{}%
  \@dtl@decimal@to@localeint#1.\relax
}

```

\@dtl@countdigits Counts the number of digits until #2 is a full stop. (increments \@dtl@tmpcount.)

```

\def\@dtl@countdigits#1#2\relax{%
  \advance\@dtl@tmpcount by 1\relax
  \ifx.#2\relax
    \let\@dtl@countnext=\@gobble
  \else
    \let\@dtl@countnext=\@dtl@countdigits
  \fi
  \@dtl@countnext#2\relax
}

```

decimal@to@localeint

```

\def\@dtl@decimal@to@localeint#1#2\relax{%
  \advance\@dtl@numgrpsepcount by 1\relax
  \ifx.#2\relax
    \edef\@dtl@intpart{\@dtl@intpart#1}%
    \let\@dtl@localeintnext=\@gobble
  \else
    \ifnum\@dtl@numgrpsepcount=3\relax
      \edef\@dtl@intpart{\@dtl@intpart#1\@dtl@numbergroupchar}%
      \@dtl@numgrpsepcount=0\relax
    \else
      \ifnum\@dtl@numgrpsepcount>3\relax
        \@dtl@numgrpsepcount=0\relax
      \fi
      \edef\@dtl@intpart{\@dtl@intpart#1}%
    \fi
    \let\@dtl@localeintnext=\@dtl@decimal@to@localeint
  \fi
}

```



```

\@dtl@localeintnext#2\relax
}

```

`\decimaltolocalefrac` Convert the fractional part (store in `\@dtl@fracpart`). `\@dtl@choptrailingzeroes` was originally used, but this interfered with `\dtlround`. Removing `\@dtl@choptrailingzeroes` caused a 'Number too big' error, so any fractional part over 2147483647 needs to be trimmed. Unfortunately `\ifnum#1>2147483647` also causes the 'Number too big' error, so count the digits, and if the digit count exceeds 9, trim the excess.

```

\def\@dtl@decimaltolocalefrac#1.\relax{%
\count@=0\relax
\@dtl@digitcount#1\relax
\ifnum\count@>9\relax
\@dtl@chopexcessfrac#1000000000\@nil
\else
\def\@dtl@fracpart{#1}%
\fi
}

```

`\@chopexcessfrac` Chop fractional part to just 9 digits.

```

\newcommand*\@dtl@chopexcessfrac[9]{%
\def\@dtl@fracpart{#1#2#3#4#5#6#7#8#9}%
\@dtl@gobbletonil
}

```

`\@dtl@digitcount` Counts the number of digits in #1.

```

\newcommand*\@dtl@digitcount[1]{%
\ifx\relax#1\relax
\let\@dtl@digitcountnext\relax
\else
\advance\count@ by \@ne
\let\@dtl@digitcountnext\@dtl@digitcount
\fi
\@dtl@digitcountnext
}

```

`\decimaltocurrency` `\DTLdecimaltocurrency{<number>}{<cmd>}`

This converts a decimal number into the locale dependent currency format. Stores result in `<cmd>` which must be a control sequence.

```

\newcommand*\DTLdecimaltocurrency[2]{%
\edef\@dtl@tmpdtl{#1}%
\expandafter\@dtl@decimaltolocale\@dtl@tmpdtl.\relax
\dtl@truncatedecimal\@dtl@tmpdtl
\@dtl@tmpcount=\@dtl@tmpdtl\relax
\expandafter\@dtl@toks\expandafter{\@dtl@currency}%
}

```

```

\dtlifnumeq{\@dtl@fracpart}{0}%
{%
  \ifnum\@dtl@tmpcount<0\relax
    \@dtl@tmpcount = -\@dtl@tmpcount\relax
    \edef#2{-\the\@dtl@toks\the\@dtl@tmpcount\@dtl@decimal00}%
  \else
    \edef#2{\the\@dtl@toks\@dtl@intpart\@dtl@decimal00}%
  \fi
}%
{%
  \ifnum\@dtl@tmpcount<0\relax
    \@dtl@tmpcount = -\@dtl@tmpcount\relax
    \ifnum\@dtl@fracpart<10\relax
      \edef#2{%
        -\the\@dtl@toks\number\@dtl@tmpcount
        \@dtl@decimal\@dtl@fracpart0%
      }%
    \else
      \edef#2{%
        -\the\@dtl@toks\number\@dtl@tmpcount
        \@dtl@decimal\@dtl@fracpart
      }%
    \fi
  \else
    \ifnum\@dtl@fracpart<10\relax
      \edef#2{\the\@dtl@toks\@dtl@intpart\@dtl@decimal\@dtl@fracpart0}%
    \else
      \edef#2{\the\@dtl@toks\@dtl@intpart\@dtl@decimal\@dtl@fracpart}%
    \fi
  \fi
}%
}

```

Set the defaults:

```

\@dtl@construct@getnums
\expandafter\@dtl@construct@stripnumgrpchar\expandafter
{\@dtl@numbergroupchar}

```

### 1.3.1 Currencies

`\@dtl@currencies` stores all known currencies.

```

\newcommand*{\@dtl@currencies}{\$, \pounds}

```

`\DTLaddcurrency` `{\langle symbol \rangle}`

Adds `\langle symbol \rangle` to the list of known currencies

```

\newcommand*{\DTLnewcurrencysymbol}[1]{%
  \expandafter\toks@\expandafter{\@dtl@currencies}%
  \@dtl@toks{#1}%
  \edef\@dtl@currencies{\the\@dtl@toks,\the\toks@}%
}

```

If any of the following currency commands have been defined, add them to the list:

```

\AtBeginDocument{%
  \@ifundefined{texteuro}{\DTLnewcurrencysymbol{\texteuro}}%
  \@ifundefined{textdollar}{\DTLnewcurrencysymbol{\textdollar}}%
  \@ifundefined{textstirling}{\DTLnewcurrencysymbol{\textstirling}}%
  \@ifundefined{textyen}{\DTLnewcurrencysymbol{\textyen}}%
  \@ifundefined{textwon}{\DTLnewcurrencysymbol{\textwon}}%
  \@ifundefined{textcurrency}{\DTLnewcurrencysymbol{\textcurrency}}%
  \@ifundefined{euro}{\DTLnewcurrencysymbol{\euro}}%
  \@ifundefined{yen}{\DTLnewcurrencysymbol{\yen}}%
}

```

\@dtl@standardize@currency

```
\@dtl@standardize@currency{<cmd>}
```

Substitutes the first currency symbol found in *<cmd>* with  $\$$ . This is used when testing text to determine if it is currency. The original currency symbol is stored in  $\@dtl@org@currency$ , so that it can be replaced later. If no currency symbol is found,  $\@dtl@org@currency$  will be empty.

```

\newcommand{\@dtl@standardize@currency}[1]{%
  \def\@dtl@org@currency{}%
  \@for\@dtl@thiscurrency:=\@dtl@currencies\do{%
    \expandafter\toks@\expandafter{\@dtl@thiscurrency}%
    \edef\@dtl@dosubs{\noexpand\DTLsubstitute{\noexpand#1}%
      {\the\toks@}{\noexpand\$}}%
    \@dtl@dosubs
    \ifdefempty{\@dtl@replaced}%
      {%
    }%
      {%
        \let\@dtl@org@currency=\@dtl@replaced
        \@endfortrue
      }%
    }%
  \@endforfalse
}

```

\@dtl@currency

\@dtl@currency is set by  $\DTLlocaltodecimal$  and  $\@dtl@checknumerical$ . It is used by  $\DTLdecimaltocurrency$ . Set to  $\$$  by default.

```
\newcommand*{\@dtl@currency}{\$}
```

```
defaultcurrency \DTLsetdefaultcurrency{<symbol>} sets the default currency.
\newcommand*{\DTLsetdefaultcurrency}[1]{%
\renewcommand*{\@dtl@currency}{#1}%
}
```

## 1.4 Floating Point Arithmetic

The commands defined in this section all use the equivalent commands provided by the fp or pgfmath packages, but first convert the decimal number into the required format.

```
\DTLadd \DTLadd{<cmd>}{<num1>}{<num2>}
```

Sets  $\langle cmd \rangle = \langle num1 \rangle + \langle num2 \rangle$

```
\newcommand*{\DTLadd}[3]{%
\DTLconverttodecimal{#2}{\@dtl@numi}%
\DTLconverttodecimal{#3}{\@dtl@numii}%
\dtladd{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
\ifdefempty{\@dtl@replaced}%
{%
\DTLdecimaltolocale{\@dtl@tmp}{#1}%
}%
{%
\DTLdecimaltocurrency{\@dtl@tmp}{#1}%
}%
}
```

```
\DTLgadd Global version
```

```
\newcommand*{\DTLgadd}[3]{%
\DTLadd{\@dtl@tmpii}{#2}{#3}%
\global\let#1=\@dtl@tmpii
}
```

```
\DTLaddall \DTLaddall{<cmd>}{<num list>}
```

Sums all the values in  $\langle num list \rangle$  and stores in  $\langle cmd \rangle$  which must be a control sequence.

```
\newcommand*{\DTLaddall}[2]{%
\def\@dtl@sum{0}%
\@for\dtl@thisval:=#2\do{%
\expandafter\DTLconverttodecimal\expandafter{\dtl@thisval}{\@dtl@num}%
\dtladd{\@dtl@sum}{\@dtl@sum}{\@dtl@num}%
}%
\ifdefempty{\@dtl@replaced}%
}
```

```

    {%
      \DTLdecimaltolocale{\@dtl@sum}{#1}%
    }%
    {%
      \DTLdecimaltocurrency{\@dtl@sum}{#1}%
    }%
  }

```

`\DTLgaddall` `\DTLgaddall{<cmd>}{<num list>}`

Global version

```

\newcommand*{\DTLgaddall}[2]{%
  \DTLaddall{\@dtl@tmpi}{#2}%
  \global\let#1=\@dtl@tmpi
}

```

`\DTLsub` `\DTLsub{<cmd>}{<num1>}{<num2>}`

Sets  $\langle cmd \rangle = \langle num1 \rangle - \langle num2 \rangle$

```

\newcommand*{\DTLsub}[3]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \dtlsub{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}

```

`\DTLgsub` Global version

```

\newcommand*{\DTLgsub}[3]{%
  \DTLsub{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}

```

`\DTLmul` `\DTLmul{<cmd>}{<num1>}{<num2>}`

Sets  $\langle cmd \rangle = \langle num1 \rangle \times \langle num2 \rangle$

```

\newcommand*\DTLmul}[3]{%
  \let\@dtl@thisreplaced=\@empty
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \ifdefempty{\@dtl@replaced}%
  {%
  }%
  {%
    \let\@dtl@thisreplaced=\@dtl@replaced
  }%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \ifdefempty{\@dtl@replaced}%
  {%
  }%
  {%
    \let\@dtl@thisreplaced=\@dtl@replaced
  }%
  \dtlmul{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
  \ifdefempty{\@dtl@thisreplaced}%
  {%
  }%
  \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
  }%
  \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}

```

\DTLgmul Global version

```

\newcommand*\DTLgmul}[3]{%
  \DTLmul{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}

```

\DTLdiv `\DTLdiv{<cmd>}{<num1>}{<num2>}`

Sets  $\langle cmd \rangle = \langle num1 \rangle / \langle num2 \rangle$

```

\newcommand*\DTLdiv}[3]{%
  \let\@dtl@thisreplaced=\@empty
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \ifdefempty{\@dtl@replaced}%
  {%
  }%
  {%
    \let\@dtl@thisreplaced=\@dtl@replaced
  }%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \dtldiv{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
}

```

```

\ifdefempty{\@dtl@thisreplaced}%
{%
  \DTLdecimaltolocale{\@dtl@tmp}{#1}%
}%
{%
  \ifdefequal{\@dtl@thisreplaced}{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}%
}

```

\DTLgdiv Global version

```

\newcommand*\DTLgdiv}[3]{%
  \DTLdiv{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}

```

\DTLabs

```
\DTLabs{<cmd>}{<num>}
```

Sets  $\langle cmd \rangle = \text{abs}(\langle num \rangle)$

```

\newcommand*\DTLabs}[2]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtlabs{\@dtl@tmp}{\@dtl@numi}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}

```

\DTLgabs Global version

```

\newcommand*\DTLgabs}[2]{%
  \DTLabs{\@dtl@tmpii}{#2}%
  \global\let#1=\@dtl@tmpii
}

```

\DTLneg

```
\DTLneg{<cmd>}{<num>}
```

Sets  $\langle cmd \rangle = -\langle num \rangle$

```
\newcommand*\DTLneg}[2]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtlneg{\@dtl@tmp}{\@dtl@numi}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}
```

`\DTLgneg` Global version

```
\newcommand*\DTLgneg}[2]{%
  \DTLneg{\@dtl@tmpii}{#2}%
  \global\let#1=\@dtl@tmpii
}
```

`\DTLsqrt` `\DTLsqrt{ $\langle cmd \rangle$ }{ $\langle num \rangle$ }`

Sets  $\langle cmd \rangle = \text{sqrt}(\langle num \rangle)$

```
\newcommand*\DTLsqrt}[2]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtlroot{\@dtl@tmpi}{\@dtl@numi}{2}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmpi}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmpi}{#1}%
  }%
}
```

`\DTLgsqrt` Global version

```
\newcommand*\DTLgsqrt}[2]{%
  \DTLsqrt{\@dtl@tmpii}{#2}%
  \global\let#1=\@dtl@tmpii
}
```

`\DTLmin` `\DTLmin{ $\langle cmd \rangle$ }{ $\langle num1 \rangle$ }{ $\langle num2 \rangle$ }`

Sets  $\langle cmd \rangle = \text{min}(\langle num1 \rangle, \langle num2 \rangle)$



```

\newcommand*\DTLmin}[3]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \dtlifnumlt{\@dtl@numi}{\@dtl@numii}%
  {%
    \dtl@ifsingle{#2}%
    {\let#1=#2}%
    {\def#1{#2}}%
  }%
  {%
    \dtl@ifsingle{#3}%
    {\let#1=#3}%
    {\def#1{#3}}%
  }%
}

```

\DTLgmin Global version

```

\newcommand*\DTLgmin}[3]{%
  \DTLmin{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}

```

\DTLminall \DTLminall{<cmd>}{<num list>}

Finds the minimum value in *<num list>* and stores in *<cmd>* which must be a control sequence.

```

\newcommand*\DTLminall}[2]{%
  \let\@dtl@min=\@empty
  \@for\dtl@thisval:=#2\do{%
    \expandafter\DTLconverttodecimal\expandafter{\dtl@thisval}{\@dtl@num}%
    \ifdefempty{\@dtl@min}%
    {%
      \let\@dtl@min=\@dtl@num
    }%
    {%
      \dtlmin{\@dtl@min}{\@dtl@min}{\@dtl@num}%
    }%
  }%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@min}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@min}{#1}%
  }%
}

```

```
\DTLgminall \DTLgminall{<cmd>}{<num list>}
```

Global version

```
\newcommand*\DTLgminall}[2]{%
  \DTLminall{\@dtl@tmpi}{#2}%
  \global\let#1=\@dtl@tmpi
}
```

```
\DTLmax \DTLmax{<cmd>}{<num1>}{<num2>}
```

Sets  $\langle cmd \rangle = \max(\langle num1 \rangle, \langle num2 \rangle)$

```
\newcommand*\DTLmax}[3]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \dtlmax{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
  \dtlifnumgt{\@dtl@numi}{\@dtl@numii}%
  {%
    \dtl@ifsingle{#2}%
    {\let#1=#2}%
    {\def#1{#2}}%
  }%
  {%
    \dtl@ifsingle{#3}%
    {\let#1=#3}%
    {\def#1{#3}}%
  }%
}
```

```
\DTLgmax Global version
```

```
\newcommand*\DTLgmax}[3]{%
  \DTLmax{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}
```

```
\DTLmaxall \DTLmaxall{<cmd>}{<num list>}
```

Finds the maximum value in  $\langle num list \rangle$  and stores in  $\langle cmd \rangle$  which must be a control sequence.

```
\newcommand*\DTLmaxall}[2]{%
  \let\@dtl@max=\@empty
  \@for\dtl@thisval:=#2\do{%
```

```

\expandafter\DTLconverttodecimal\expandafter{\dtl@thisval}{\dtl@num}%
\ifdefempty{\@dtl@max}%
{%
  \let\@dtl@max\@dtl@num
}%
{%
  \dtlmax{\@dtl@max}{\@dtl@max}{\@dtl@num}%
}%
}%
\ifdefempty{\@dtl@replaced}%
{%
  \DTLdecimaltolocale{\@dtl@max}{#1}%
}%
{%
  \DTLdecimaltocurrency{\@dtl@max}{#1}%
}%
}

```

`\DTLgmaxall` `\DTLgmaxall{<cmd>}{<num list>}`

Global version

```

\newcommand*\DTLgmaxall}[2]{%
\DTLmaxall{\@dtl@tmpi}{#2}%
\global\let#1=\@dtl@tmpi
}

```

`\DTLmeanforall` `\DTLmeanforall{<cmd>}{<num list>}`

Computes the arithmetic mean of all the values in *<num list>* and stores in *<cmd>* which must be a control sequence.

```

\newcommand*\DTLmeanforall}[2]{%
\def\@dtl@mean{0}%
\def\@dtl@n{0}%
\@for\dtl@thisval:=#2\do{%
\expandafter\DTLconverttodecimal\expandafter{\dtl@thisval}{\dtl@num}%
\dtladd{\@dtl@mean}{\@dtl@mean}{\@dtl@num}%
\dtladd{\@dtl@n}{\@dtl@n}{1}%
}%
\dtldiv{\@dtl@mean}{\@dtl@mean}{\@dtl@n}%
\ifdefempty{\@dtl@replaced}%
{%
  \DTLdecimaltolocale{\@dtl@mean}{#1}%
}%
{%

```

```

    \DTLdecimaltocurrency{\@dtl@mean}{#1}%
  }%
}

```

```
\DTLgmeanforall \DTLgmeanforall{<cmd>}{<num list>}
```

Global version

```

\newcommand*{\DTLgmeanforall}[2]{%
  \DTLmeanforall{\@dtl@tmpi}{#2}%
  \global\let#1=\@dtl@tmpi
}

```

```
DTLvarianceforall \DTLvarianceforall{<cmd>}{<num list>}
```

Computes the variance of all the values in *<num list>* and stores in *<cmd>* which must be a control sequence.

```

\newcommand*{\DTLvarianceforall}[2]{%
  \def\@dtl@mean{0}%
  \def\@dtl@n{0}%
  \let\@dtl@decvals=\@empty
  \@for\@dtl@thisval:=#2\do{%
    \expandafter\DTLconverttodecimal\expandafter{\@dtl@thisval}{\@dtl@num}%
    \ifdefempty{\@dtl@decvals}%
    {%
      \let\@dtl@decvals=\@dtl@num
    }%
    {%
      \expandafter\toks@\expandafter{\@dtl@decvals}%
      \edef\@dtl@decvals{\the\toks@,\@dtl@num}%
    }%
    \dtladd{\@dtl@mean}{\@dtl@mean}{\@dtl@num}%
    \dtladd{\@dtl@n}{\@dtl@n}{1}%
  }%
  \dtldiv{\@dtl@mean}{\@dtl@mean}{\@dtl@n}%
  \def\@dtl@var{0}%
  \@for\@dtl@num:=\@dtl@decvals\do{%
    \dtlsub{\@dtl@diff}{\@dtl@num}{\@dtl@mean}%
    \dtlmul{\@dtl@diff}{\@dtl@diff}{\@dtl@diff}%
    \dtladd{\@dtl@var}{\@dtl@var}{\@dtl@diff}%
  }%
  \dtldiv{\@dtl@var}{\@dtl@var}{\@dtl@n}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@var}{#1}%
  }%
}

```

```

}%
{%
  \DTLdecimaltocurrency{\@dtl@var}{#1}%
}%
}

```

`\DTLgvarianceforall` `\DTLgvarianceforall{<cmd>}{<num list>}`

Global version

```

\newcommand*{\DTLgvarianceforall}[2]{%
  \DTLvvarianceforall{\@dtl@tmpi}{#2}%
  \global\let#1=\@dtl@tmpi
}

```

`\DTLsdforall` `\DTLsdforall{<cmd>}{<num list>}`

Computes the standard deviation of all the values in *<num list>* and stores in *<cmd>* which must be a control sequence.

```

\newcommand*{\DTLsdforall}[2]{%
  \def\@dtl@mean{0}%
  \def\@dtl@n{0}%
  \let\@dtl@decvals=@empty
  \for\@dtl@thisval:=#2\do{%
    \expandafter\DTLconverttodecimal\expandafter{\@dtl@thisval}{\@dtl@num}%
    \ifdefempty{\@dtl@decvals}%
      {%
        \let\@dtl@decvals=\@dtl@num
      }%
    {%
      \expandafter\toks@\expandafter{\@dtl@decvals}%
      \edef\@dtl@decvals{\the\toks@,\@dtl@num}%
    }%
    \dtladd{\@dtl@mean}{\@dtl@mean}{\@dtl@num}%
    \dtladd{\@dtl@n}{\@dtl@n}{1}%
  }%
  \dtldiv{\@dtl@mean}{\@dtl@mean}{\@dtl@n}%
  \def\@dtl@sd{0}%
  \for\@dtl@num:=\@dtl@decvals\do{%
    \dtlsub{\@dtl@diff}{\@dtl@num}{\@dtl@mean}%
    \dtlmul{\@dtl@diff}{\@dtl@diff}{\@dtl@diff}%
    \dtladd{\@dtl@sd}{\@dtl@sd}{\@dtl@diff}%
  }%
  \dtldiv{\@dtl@sd}{\@dtl@sd}{\@dtl@n}%
  \dtlroot{\@dtl@sd}{\@dtl@sd}{2}%
}

```

```

\ifdefempty{\@dtl@replaced}%
{%
  \DTLdecimaltolocale{\@dtl@sd}{#1}%
}%
{%
  \DTLdecimaltocurrency{\@dtl@sd}{#1}%
}%
}

```

`\DTLgdsforall` `\DTLgdsforall{<cmd>}{<num list>}`

Global version

```

\newcommand*\DTLgdsforall[2]{%
  \DTLsforall{\@dtl@tmpi}{#2}%
  \global\let#1=\@dtl@tmpi
}

```

`\DTLround` `\DTLround{<cmd>}{<num>}{<num digits>}`

Sets *<cmd>* to *<num>* rounded to *<num digits>* digits after the decimal character.

```

\newcommand*\DTLround[3]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtlround{\@dtl@tmp}{\@dtl@numi}{#3}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}

```

`\DTLground` Global version

```

\newcommand*\DTLground[3]{%
  \DTLround{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}

```

`\DTLtrunc` `\DTLtrunc{<cmd>}{<num>}{<num digits>}`

Sets *<cmd>* to *<num>* truncated to *<num digits>* digits after the decimal character.

```

\newcommand*\DTLtrunc}[3]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtltrunc{\@dtl@tmp}{\@dtl@numi}{#3}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}

```

`\DTLgtrunc` Global version

```

\newcommand*\DTLgtrunc}[3]{%
  \DTLtrunc{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}

```

`\DTLclip` `\DTLclip{<cmd>}{<num>}`

Sets *<cmd>* to *<num>* with all unnecessary 0's removed.

```

\newcommand*\DTLclip}[2]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtlclip{\@dtl@tmp}{\@dtl@numi}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}

```

`\DTLgclip` Global version

```

\newcommand*\DTLgclip}[3]{%
  \DTLclip{\@dtl@tmpii}{#2}%
  \global\let#1=\@dtl@tmpii
}

```

## 1.5 String Macros

`\DTLinitials` `\DTLinitials{<string>}`

Convert a string into initials. (Any ~ character found is first converted into a space.)

```
\newcommand*{\DTLinitials[1]}{%
  \def\dtl@initialscmd{%
    \dtl@subnohrsp{#1}{\dtl@string}%
    \DTLsubstituteall{\dtl@string}{~}{ }%
    \DTLsubstituteall{\dtl@string}{\ }{ }%
    \DTLsubstituteall{\dtl@string}{\space}{ }%
    \expandafter\dtl@initials\dtl@string{} \@nil%
    \dtl@initialscmd
  }%
}
```

The following substitutes `\protect \nobreakspace { }` with a space. (Note that in this case the space following `\nobreakspace` forms part of the command.)

```
\edef\dtl@construct@subnohrsp{%
```

Define `\@dtl@subnohrsp`

```
\noexpand\def\noexpand\@dtl@subnohrsp##1\noexpand\protect
\expandafter\noexpand\csname nobreakspace \endcsname ##2{%
\noexpand\toks@{##1}%
\noexpand\expandafter\noexpand\@dtl@toks\noexpand\expandafter{%
\noexpand\@dtl@string}%
\noexpand\edef\noexpand\@dtl@string{\noexpand\the\noexpand\@dtl@toks
\noexpand\the\noexpand\toks@}%
\noexpand\def\noexpand\@dtl@tmp{##2}%
\noexpand\ifx\noexpand\@dtl@tmp\noexpand\@nnil
\noexpand\let\noexpand\@dtl@subnohrspnext=\noexpand\relax
\noexpand\else
\noexpand\toks@{ }%
\noexpand\expandafter\noexpand\@dtl@toks\noexpand\expandafter{%
\noexpand\@dtl@string}%
\noexpand\edef\noexpand\@dtl@string{\noexpand\the\noexpand\@dtl@toks
\noexpand\the\noexpand\toks@}%
\noexpand\let\noexpand\@dtl@subnohrspnext=\noexpand\@dtl@subnohrsp
\noexpand\fi
\noexpand\@dtl@subnohrspnext
}%
}
```

Define `\dtl@subnohrsp`

```
\noexpand\def\noexpand\dtl@subnohrsp##1##2{%
\noexpand\def\noexpand\@dtl@string{%
\noexpand\@dtl@subnohrsp ##1\noexpand\protect\expandafter\noexpand
\csname nobreakspace \endcsname \noexpand\@nil
\noexpand\let##2=\noexpand\@dtl@string
}%
}
\dtl@construct@subnohrsp
```

DTLstoreinitials `\DTLstoreinitials{<string>}{<cmd>}`



Convert a string into initials and store in  $\langle cmd \rangle$ . (Any  $\sim$  character found is first converted into a space.)

```

\newcommand*{\DTLstoreinitials}[2]{%
  \def\dtl@initialscmd{%
    \dtl@subnobrsp{#1}\dtl@string}%
  \DTLsubstituteall{\dtl@string}{~}{ }%
  \DTLsubstituteall{\dtl@string}{\ }{ }%
  \DTLsubstituteall{\dtl@string}{\space}{ }%
  \expandafter\dtl@initials\dtl@string} \@nil
  \let#2=\dtl@initialscmd
}

```

$\backslash dtl@initials$

```

\def\dtl@initials#1#2 #3{%
  \dtl@ifsingle{#1}%
  {%
    \ifcat\noexpand#1\relax\relax
      \def\@dtl@donextinitials{\@dtl@initials#2 {#3}}%
    \else
      \def\@dtl@donextinitials{\@dtl@initials#1#2 {#3}}%
    \fi
  }%
  {%
    \def\@dtl@donextinitials{\@dtl@initials{#1}#2 {#3}}%
  }%
  \@dtl@donextinitials
}

```

$\backslash @dtl@initials$

```

\def\@dtl@initials#1#2 #3{%
  \dtl@initialshyphen#2-{\dtl@endhyp
  \expandafter\@dtl@toks\expandafter{\dtl@initialscmd}%
  \toks@{#1}%
  \ifdefempty{\dtl@inithyphen}%
  {%
  }%
  {%
    \edef\dtl@initialscmd{\the\@dtl@toks\the\toks@}%
    \expandafter\@dtl@toks\expandafter{\dtl@initialscmd}%
    \expandafter\toks@\expandafter{\dtl@inithyphen}%
  }%
  \def\dtl@tmp{#3}%
  \ifx\@nnil\dtl@tmp
    \edef\dtl@initialscmd{\the\@dtl@toks\the\toks@\DTLafterinitials}%
    \let\dtl@initialsnext=\@gobble
  \else
    \edef\dtl@initialscmd{\the\@dtl@toks\the\toks@\DTLbetweeninitials}%
    \let\dtl@initialsnext=\dtl@initials
  \fi
}

```

```

\dtl@initialsnext{#3}%
}

```

@initialshyphen

```

\def\dtl@initialshyphen#1-#2#3\dtl@endhyp{%
\def\dtl@inithyphen{#2}%
\ifdefempty{\dtl@inithyphen}%
{%
}%
}%
\edef\dtl@inithyphen{%
\DTLafterinitialbeforehyphen\DTLinitialhyphen#2}%
}%
}

```

DTLafterinitials Defines what to do after the final initial.

```

\newcommand*{\DTLafterinitials}{.}

```

DTLbetweeninitials Defines what to do between initials.

```

\newcommand*{\DTLbetweeninitials}{.}

```

DTLinitialbeforehyphen Defines what to do before a hyphen.

```

\newcommand*{\DTLafterinitialbeforehyphen}{.}

```

DTLinitialhyphen Defines what to do at the hyphen

```

\newcommand*{\DTLinitialhyphen}{-}

```

DTLifAllUpperCase \DTLifAllUpperCase{<string>}{<true part>}{<>false part>}

If *<string>* only contains uppercase characters do *<true part>*, otherwise do *<>false part>*.

```

\newcommand*{\DTLifAllUpperCase}[3]{%
\protected@edef\dtl@tuc{#1}%
\expandafter\dtl@testifuppercase\dtl@tuc\@nil\relax
\if@dtl@condition#2\else#3\fi
}

```

DTLifalluppercase

```

\def\dtl@testifuppercase#1#2{%
\def\dtl@argi{#1}%
\def\dtl@argii{#2}%
\def\dtl@tc@rest{}%
\ifx\dtl@argi\@nnil
\let\dtl@testifuppernext=\@nnil
\else
\ifx#1\protect

```

```

        \let\dtl@testifuppernext=\dtl@testifuppercase
    \else
        \ifx\uppercase#1\relax
            \@dtl@conditiontrue
            \def\dtl@tc@rest{}%
            \let\dtl@testifuppernext=\relax
        \else
            \edef\dtl@tc@arg{\string#1}%
            \expandafter\dtl@test@ifuppercase\dtl@tc@arg\end
            \ifx\dtl@argii\@nnil
                \let\dtl@testifuppernext=\@dtl@gobbletonil
            \fi
        \fi
    \fi
\ifx\dtl@testifuppernext\relax
\edef\dtl@dotestifuppernext{%
\noexpand\dtl@testifuppercase}%
\else
\ifx\dtl@testifuppernext\@nnil
\edef\dtl@dotestifuppernext{#2}%
\else
\expandafter\toks@\expandafter{\dtl@tc@rest}%
\@dtl@toks{#2}%
\edef\dtl@dotestifuppernext{%
\noexpand\dtl@testifuppernext\the\toks@\the\@dtl@toks}%
\fi
\fi
\dtl@dotestifuppernext
}

```

@ifalluppercase

```

\def\dtl@test@ifuppercase#1#2\end{%
\def\dtl@tc@rest{#2}%
\IfSubStringInString{\string\MakeUppercase}{#1#2}%
{%
\@dtl@conditiontrue
\def\dtl@tc@rest{}%
\let\dtl@testifuppernext=\relax
}%
{%
\IfSubStringInString{\string\MakeTextUppercase}{#1#2}%
{%
\@dtl@conditiontrue
\def\dtl@tc@rest{}%
\let\dtl@testifuppernext=\relax
}%
{%
\edef\dtl@uccode{\the\uccode'#1}%

```

```

\edef\dtl@code{\number'#1}%
\ifnum\dtl@code=\dtl@uccode\relax
  \@dtl@conditiontrue
  \let\dtl@testifuppernext=\dtl@testifuppercase
\else
  \ifnum\dtl@uccode=0\relax
    \@dtl@conditiontrue
    \let\dtl@testifuppernext=\dtl@testifuppercase
  \else
    \@dtl@conditionfalse
    \let\dtl@testifuppernext=\@dtl@gobbletonil
  \fi
\fi
}%
}%
}

```

DTLifAllLowerCase `\DTLifAllLowerCase{<string>}{<true part>}{<>false part>}`

If *<string>* only contains lowercase characters do *<true part>*, otherwise do *<>false part>*.

```

\newcommand*{\DTLifAllLowerCase}[3]{%
  \protected@edef\dtl@tlc{#1}%
  \expandafter\dtl@testiflowercase\dtl@tlc\@nil\relax
  \if@dtl@condition#2\else#3\fi
}

```

dtl@testiflowercase

```

\def\dtl@testiflowercase#1#2{%
  \def\dtl@argi{#1}%
  \def\dtl@argii{#2}%
  \ifx\dtl@argi\@nnil
    \let\dtl@testiflowernext=\@nnil
  \else
    \ifx#1\protect
      \let\dtl@testiflowernext=\dtl@testiflowercase
    \else
      \ifx\lowercase#1\relax
        \@dtl@conditiontrue
        \def\dtl@tc@rest{}%
        \let\dtl@testiflowernext=\relax
      \else
        \edef\dtl@tc@arg{\string#1}%
        \expandafter\dtl@testiflowercase\dtl@tc@arg\end
        \ifx\dtl@argii\@nnil
          \let\dtl@testiflowernext=\@dtl@gobbletonil
        \fi
      \fi
    \fi
  \fi
}

```

```

    \fi
  \fi
\fi
\ifx\dtl@testiflowernext\relax
\edef\dtl@dotestiflowernext{%
  \noexpand\dtl@testiflowercase}%
\else
\ifx\dtl@testiflowernext\@nnil
\edef\dtl@dotestiflowernext{#2}%
\else
\expandafter\toks@\expandafter{\dtl@tc@rest}%
\@dtl@toks{#2}%
\edef\dtl@dotestiflowernext{%
  \noexpand\dtl@testiflowernext\the\toks@\the\@dtl@toks}%
\fi
\fi
\dtl@dotestiflowernext
}

```

@ifalllowercase

```

\def\dtl@test@iflowercase#1#2\end{%
\def\dtl@tc@rest{#2}%
\IfSubStringInString{\string\MakeLowercase}{#1#2}%
{%
\@dtl@conditiontrue
\def\dtl@tc@rest{}%
\let\dtl@testiflowernext=\relax
}%
{%
\IfSubStringInString{\string\MakeTextLowercase}{#1#2}%
{%
\@dtl@conditiontrue
\def\dtl@tc@rest{}%
\let\dtl@testiflowernext=\relax
}%
{%
\edef\dtl@lccode{\the\lccode'#1}%
\edef\dtl@code{\number'#1}%
\ifnum\dtl@code=\dtl@lccode\relax
\@dtl@conditiontrue
\let\dtl@testiflowernext=\dtl@testiflowercase
\else
\ifnum\dtl@lccode=0\relax
\@dtl@conditiontrue
\let\dtl@testiflowernext=\dtl@testiflowercase
\else
\@dtl@conditionfalse
\let\dtl@testiflowernext=\@dtl@gobbletonil
\fi
}
}

```

```

    \fi
  }%
}

```

`\DTLsubstitute` `\DTLsubstitute{<cmd>}{<original>}{<replacement>}`

Substitutes first occurrence of *<original>* with *{<replacement>}* within the string given by *<cmd>*

```

\newcommand{\DTLsubstitute}[3]{%
  \expandafter\DTLsplitstring\expandafter
  {#1}{#2}{\@dtl@beforepart}{\@dtl@afterpart}%
  \ifdefempty{\@dtl@replaced}%
  {%
  }%
  {%
  \def#1{%
    \expandafter\@dtl@toks\expandafter{\@dtl@beforepart}%
    \expandafter\toks@\expandafter{#1}%
    \protected@edef#1{\the\toks@\the\@dtl@toks#3}%
    \expandafter\@dtl@toks\expandafter{\@dtl@afterpart}%
    \expandafter\toks@\expandafter{#1}%
    \edef#1{\the\toks@\the\@dtl@toks}%
  }%
}

```

`\DTLsplitstring` `\DTLsplitstring{<string>}{<split text>}{<before cmd>}{<after cmd>}`

Splits string at *<split text>* stores the pre split text in *<before cmd>* and the post split text in *<after cmd>*.

```

\newcommand*\DTLsplitstring[4]{%
  \def\dtl@splitstr##1#2##2\@nil{%
    \def#3{##1}%
    \def#4{##2}%
    \ifdefempty{#4}%
    {%
      \let\@dtl@replaced=\@empty
    }%
    {%
      \def\@dtl@replaced{#2}%
      \dtl@split@str##2\@nil
    }%
  }%
  \def\dtl@split@str##1#2\@nil{%

```

```

\def#4{##1}}%
\dtl@splitstr#1#2\@nil
}

```

DTLsubstituteall `\DTLsubstituteall{<cmd>}{<original>}{<replacement>}`

Substitutes all occurrences of *<original>* with *{<replacement>}* within the string given by *<cmd>*

```

\newcommand{\DTLsubstituteall}[3]{%
\def\@dtl@splitsubstr{%
\let\@dtl@afterpart=#1\relax
\@dtl@dosubstitute{#2}{#3}%
\expandafter\toks@\expandafter{\@dtl@splitsubstr}%
\expandafter\@dtl@toks\expandafter{\@dtl@afterpart}%
\long\edef#1{\the\toks@\the\@dtl@toks}%
}

```

dtl@dosubstitute Recursive substitution macro.

```

\def\@dtl@dosubstitute#1#2{%
\expandafter\DTLsplitstring\expandafter
{\@dtl@afterpart}{#1}{\@dtl@beforepart}{\@dtl@afterpart}%
\expandafter\toks@\expandafter{\@dtl@splitsubstr}%
\expandafter\@dtl@toks\expandafter{\@dtl@beforepart}%
\edef\@dtl@splitsubstr{\the\toks@\the\@dtl@toks}%
\ifdefempty{\@dtl@replaced}%
{%
\let\@dtl@dosubstnext=\@dtl@dosubstitutenooop
}%
{%
\expandafter\toks@\expandafter{\@dtl@splitsubstr}%
\@dtl@toks{#2}%
\edef\@dtl@splitsubstr{\the\toks@\the\@dtl@toks}%
\let\@dtl@dosubstnext=\@dtl@dosubstitute
}%
\@dtl@dosubstnext{#1}{#2}%
}

```

dosubstitutenooop Terminates recursive substitution macro.

```

\def\@dtl@dosubstitutenooop#1#2{}

```

## 1.6 Conditionals

f@dtl@condition

```

\newif\if@dtl@condition

```

## 1.6.1 Determining Data Types

The control sequence `\@dtl@checknumerical` checks the data type of its argument, and sets `\@dtl@datatype` to 0 if the argument is a string, 1 if the argument is an integer or 2 if the argument is a real number. First define `\@dtl@datatype`:

```
\@dtl@datatype
    \newcount\@dtl@datatype
```

```
\@dtl@checknumerical {arg}
```

Checks if *arg* is numerical (includes decimal numbers, but not scientific notation.) Sets `\@dtl@datatype`, as described above.

```
\newcommand{\@dtl@checknumerical}[1]{%
  \@dtl@numgrpsepfalse
  \@dtl@ifsingle{#1}%
  {%
    \expandafter\toks@\expandafter{#1}%
    \edef\@dtl@tmp{\the\toks@}%
  }%
  {%
    \def\@dtl@tmp{#1}%
  }%

  \ifdefempty\@dtl@tmp
  {%
    \@dtl@datatype=0\relax
  }%
  {%
    \@dtl@tmpcount=0\relax
    \@dtl@datatype=0\relax
    \@dtl@numgrpsepcount=2\relax
    \@dtl@standardize@currency\@dtl@tmp
    \ifdefempty{\@dtl@org@currency}%
    {%
    }%
    {%
      \let\@dtl@currency\@dtl@org@currency
    }%
    \expandafter\@dtl@checknumericalstart\@dtl@tmp\@nil\@nil
  }%
  \ifnum\@dtl@numgrpsepcount>-1\relax
  \if@dtl@numgrpsep
    \ifnum\@dtl@numgrpsepcount=3\relax
    \else
      \@dtl@datatype=0\relax
    \fi
```



```

    \fi
  \fi
}

```

\@dtl@protect

```
\newcommand*{\@dtl@protect}{\protect}
```

\@dtl@minus

```
\newcommand*{\@dtl@minus}{-}
```

\@dtl@plus

```
\newcommand*{\@dtl@plus}{+}
```

\@dtl@dollar

```
\newcommand*{\@dtl@dollar}{\$}
```

knnumericalstart Check first character for checknumerical process to see if it's a plus or minus sign.

```

\def\@dtl@checknumericalstart#1#2\@nil\@nil{%
  \def\@dtl@tmp{#1}%
  \ifx\@dtl@tmp\@dtl@protect
    \@dtl@checknumericalstart#2\@nil\@nil\relax
  \else
    \ifx\@dtl@tmp\@dtl@minus
      \def\@dtl@tmp{#2}%
      \ifdefempty{\@dtl@tmp}%
        {%
          \@dtl@datatype=0\relax
        }%
      {%
        \ifnum\@dtl@datatype=0\relax
          \@dtl@datatype=1\relax
        \fi
        \@dtl@checknumericalstart#2\@nil\@nil\relax
      }%
    \else
      \ifx\@dtl@tmp\@dtl@plus
        \def\@dtl@tmp{#2}%
        \ifdefempty{\@dtl@tmp}%
          {%
            \@dtl@datatype=0\relax
          }%
          {%
            \ifnum\@dtl@datatype=0\relax
              \@dtl@datatype=1\relax
            \fi
            \@dtl@checknumericalstart#2\@nil\@nil\relax
          }%
        \else
          \def\@dtl@tmp{#1}%

```

```

\ifx\@dtl@tmp\@dtl@dollar
\def\@dtl@tmp{#2}%
\ifdefempty{\@dtl@tmp}%
{%
\@dtl@datatype=0\relax
}%
{%
\@dtl@datatype=3\relax
\@dtl@checknumericalstart#2\@nil\@nil\relax
}%
\else
\ifdefempty{\@dtl@tmp}%
{%
\@dtl@datatype=0\relax
}%
{%
\ifnum\@dtl@datatype=0\relax
\@dtl@datatype=1\relax
\fi
\@dtl@checknumericalloop#1#2\@nil\@nil\relax
}%
\fi
\fi
\fi
\fi
}

```

`\if@dtl@numgrpsep` The conditional `\if@dtl@numgrpsep` is set the first time `\@dtl@checknumericalloop` encounters the number group separator.

```
\newif\if@dtl@numgrpsep
```

`\if@dtl@digitordecimalsep` Check if argument is either a digit or the decimal separator. Rewrite provided by Bruno Le Floch.

```

\newcommand*\@dtl@ifDigitOrDecimalSep}[3]{%
\ifnum 9<1\noexpand#1\relax
#2%
\else
\expandafter\ifx\@dtl@decimal#1\relax
#2%
\else
#3%
\fi
\fi
}

```

`\@dtl@checknumericalloop` Check numerical loop. This iterates through each character until `\@nil` is reached, or invalid character found. Increments `\@dtl@tmpcount` each time it encounters a decimal character.

```

\def\@dtl@checknumericalloop#1#2\@nil{%
\def\@dtl@tmpcount{#1}%

```

```

\ifx\@nnil\@dtl@tmp\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop%
\else
\@dtl@ifDigitOrDecimalSep{#1}{%
\let\@dtl@chcknumnext=\@dtl@checknumericalloop%
\expandafter\ifx\@dtl@decimal#1\relax
\if@dtl@numgrpsep
\ifnum\@dtl@numgrpsepcount=3\relax
\@dtl@numgrpsepcount=-1\relax
\else
\@dtl@datatype=0\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop
\fi
\else
\@dtl@numgrpsepcount=-1\relax
\fi
\else
\ifnum\@dtl@numgrpsepcount=-1\relax
\else
\advance\@dtl@numgrpsepcount by 1\relax
\fi
\fi
}%
\ifx\@dtl@numbergroupchar\@dtl@tmp\relax
\@dtl@numgrpseptrue
\ifnum\@dtl@numgrpsepcount<3\relax
\@dtl@datatype=0\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop
\else
\@dtl@numgrpsepcount=0\relax
\fi
\else
\@dtl@datatype=0\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop
\fi
}%
\ifx\@dtl@decimal\@dtl@tmp\relax
\ifnum\@dtl@datatype<3\relax
\@dtl@datatype=2\relax
\fi
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount>1\relax
\@dtl@datatype=0\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop%
\fi
\fi
\fi
\@dtl@chcknumnext#2\@nil
}

```

cknumericalnoop End loop  
`\def\@dtl@checknumericalnoop#1\@nil#2{}`

`\DTLifnumerical` `\DTLifnumerical{<arg>}{<true part>}{<false part>}`

Tests the first argument, if its numerical do second argument, otherwise do third argument.

```
\newcommand{\DTLifnumerical}[3]{%
\@dtl@checknumerical{#1}%
\ifnum\@dtl@datatype=0\relax#3\else#2\fi
}
```

`\DTLifreal` `\DTLifreal{<arg>}{<true part>}{<false part>}`

Tests the first argument, if it's a real number (not an integer) do second argument, otherwise do third argument.

```
\newcommand{\DTLifreal}[3]{%
\@dtl@checknumerical{#1}%
\ifnum\@dtl@datatype=2\relax #2\else #3\fi
}
```

`\DTLifint` `\DTLifint{<arg>}{<true part>}{<false part>}`

Tests the first argument, if it's an integer do second argument, otherwise do third argument.

```
\newcommand{\DTLifint}[3]{%
\@dtl@checknumerical{#1}%
\ifnum\@dtl@datatype=1\relax #2\else #3\fi
}
```

`\DTLifstring` `\DTLifstring{<arg>}{<true part>}{<false part>}`

Tests the first argument, if it's a string do second argument, otherwise do third argument.

```
\newcommand{\DTLifstring}[3]{%
\@dtl@checknumerical{#1}%
\ifnum\@dtl@datatype=0\relax #2\else #3\fi
}
```

`\DTLifcurrency`

```
\DTLifcurrency{<arg>}{<true part>}{<false part>}
```

Tests the first argument, if it starts with the currency symbol do second argument, otherwise do third argument.

```
\newcommand{\DTLifcurrency}[3]{%
  \@dtl@checknumerical{#1}%
  \ifnum\@dtl@datatype=3\relax #2\else #3\fi
}
```

`\DTLifcurrencyunit`

```
\DTLifcurrencyunit{<arg>}{<symbol>}{<true part>}{<false part>}
```

This tests if *<arg>* is currency, and uses the currency unit *<symbol>*. If true do third argument, otherwise do fourth argument.

```
\newcommand*\DTLifcurrencyunit[4]{%
  \@dtl@checknumerical{#1}%
  \ifnum\@dtl@datatype=3\relax
    \ifthenelse{\equal{\@dtl@org@currency}{#2}}{#3}{#4}%
  \else
    #4%
  \fi
}
```

`\DTLifcasedatatype`

```
\DTLifcasedatatype{<arg>}{<string case>}{<int case>}{<real case>}
{<currency case>}
```

If *<arg>* is a string, do *<string case>*, if *<arg>* is an integer do *<int case>*, if *<arg>* is a real number, do *<real case>*, if *<arg>* is currency, do *<currency case>*.

```
\newcommand{\DTLifcasedatatype}[5]{%
  \@dtl@checknumerical{#1}%
  \ifcase\@dtl@datatype
    #2% string
  \or
    #3% integer
  \or
    #4% number
  \or
    #5% currency
  \fi
}
```

estbothnumerical

```
\dtl@testbothnumerical{<arg1>}{<arg2>}
```

Tests if both arguments are numerical. This sets the conditional `\if@dtl@condition`.

```
\newcommand*{\dtl@testbothnumerical}[2]{%
  \dtl@ifsingle{#1}{%
    \edef\@dtl@tmp{#1}}{%
    \def\@dtl@tmp{#1}}%
  \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
  \edef\@dtl@firsttype{\number\@dtl@datatype}%
  \dtl@ifsingle{#2}{%
    \edef\@dtl@tmp{#2}}{%
    \def\@dtl@tmp{#2}}%
  \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
  \multiply\@dtl@datatype by \@dtl@firsttype\relax
  \ifnum\@dtl@datatype>0\relax
    \@dtl@conditiontrue
  \else
    \@dtl@conditionfalse
  \fi
}
```

\DTLifnumlt

```
\DTLifnumlt{<num1>}{<num2>}{<true part>}{<false part>}
```

Determines if  $\langle num1 \rangle < \langle num2 \rangle$ . Both numbers need to have the decimal separator changed to a dot to ensure that it works with `\dtlifnumlt`

```
\newcommand*{\DTLifnumlt}[4]{%
  \DTLconverttodecimal{#1}{\@dtl@numi}%
  \DTLconverttodecimal{#2}{\@dtl@numii}%
  \dtlifnumlt{\@dtl@numi}{\@dtl@numii}%
  {%
    #3%
  }%
  {%
    #4%
  }%
}
```

\dtlcompare

```
\dtlcompare{<count>}{<string1>}{<string2>}
```

Compares  $\langle string1 \rangle$  and  $\langle string2 \rangle$ , and stores the result in the count register  $\langle count \rangle$ . The result may be one of:

- 1 if  $\langle string1 \rangle$  is considered to be less than  $\langle string2 \rangle$
- 0 if  $\langle string1 \rangle$  is considered to be the same as  $\langle string2 \rangle$
- 1 if  $\langle string1 \rangle$  is considered to be greater than  $\langle string2 \rangle$

Note that for the purposes of string comparisons, commands within  $\langle string1 \rangle$  and  $\langle string2 \rangle$  are ignored, except for `\space` and `~`, which are both treated as a space (character code 32.) The following examples assume that the count register `\mycount` has been defined as follows:

```
\newcount\mycount
```

**Examples:**

1. `\dtlcompare{\mycount}{Z"oe}{Zoe}\number\mycount`  
produces: -1, since the accent command is ignored.
2. `\dtlcompare{\mycount}{foo}{Foo}\number\mycount`  
produces: 1, since the comparison is case sensitive, however, note the following example:
3. `\dtlcompare{\mycount}{foo}{\uppercase{foo}}\number\mycount`  
which produces: 1, since the `\uppercase` command is ignored.
4. You can “trick” `\dtlcompare` using a command which doesn’t output any text. Suppose you have defined the following command:

```
\newcommand*\noopsort[1]{}
```

then `\noopsort{a}foo` produces the text: foo, however the following

```
\dtlcompare{\mycount}{\noopsort{a}foo}{bar}\number\mycount
```

produces: -1, since the command `\noopsort` is disregarded when the comparison is made, so `\dtlcompare` just compares `{a}foo` with `bar`, and since `a` is less than `b`, the first string is considered to be less than the second string.

5. Note that this also means that:

```
\def\mystr{abc}%
\dtlcompare{\mycount}{\mystr}{abc}\number\mycount
```

produces: -1, since the command `\mystr` is disregarded, which means that `\dtlcompare` is comparing an empty string with the string `abc`.

6. Spaces count in the comparison:

```
\dtlcompare{\mycount}{ab cd}{abcd}\number\mycount
```

produces: -1, but sequential spaces are treated as a single space:

```
\dtlcompare{\mycount}{ab cd}{ab cd}\number\mycount
```

produces: 0.

7. As usual, spaces following command names are ignored, so

```
\dtlcompare{\mycount}{ab\relax cd}{ab cd}\number\mycount
```

produces: -1.

8. ~ and \space are considered to be the same as a space:

```
\dtlcompare{\mycount}{ab cd}{ab~cd}\number\mycount
```

produces: 0.

```
\newcommand*{\dtlcompare}[3]{%
  \dtl@subnohrsp{#2}{\@dtl@argA}%
  \dtl@subnohrsp{#3}{\@dtl@argB}%
  \ifdefempty{\@dtl@argA}%
  {%
    \ifdefempty{\@dtl@argB}%
    {%
      #1=0\relax
    }%
  }%
  {%
    #1=-1\relax
  }%
}%
{%
  \ifdefempty{\@dtl@argB}%
  {%
    #1=1\relax
  }%
  {%
    \DTLsubstituteall{\@dtl@argA}{ }\space }%
    \DTLsubstituteall{\@dtl@argB}{ }\space }%
    \expandafter\dtl@getfirst\@dtl@argA\end@dtl@getfirst
    \let\dtl@firstA=\dtl@first
    \let\dtl@restA=\dtl@rest
    \expandafter\dtl@getfirst\@dtl@argB\end@dtl@getfirst
    \let\dtl@firstB=\dtl@first
    \let\dtl@restB=\dtl@rest
    \expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstA}{%
    \expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstB}{%
    \expandafter\dtl@setcharcode\expandafter{\dtl@firstA}{\dtl@codeA}%
    \expandafter\dtl@setcharcode\expandafter{\dtl@firstB}{\dtl@codeB}%
    \ifnum\dtl@codeA=-1\relax
      \ifnum\dtl@codeB=-1\relax
```



v2.25: added `\expandonce` to prevent non-ASCII characters from being expanded.

```
\edef\dtl@donext{%
  \noexpand\dtlcompare
  {\noexpand#1}{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
\dtl@donext
\else
\edef\dtl@donext{%
  \noexpand\dtlcompare
  {\noexpand#1}%
  {\expandonce\dtl@restA}%
  {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
\fi
\else
\ifnum\dtl@codeB=-1\relax
```

v2.25: added `\expandonce` to prevent non-ASCII characters from being expanded.

```
\edef\dtl@donext{%
  \noexpand\dtlcompare
  {\noexpand#1}%
  {\expandonce\dtl@firstA\expandonce\dtl@restA}%
  {\expandonce\dtl@restB}}%
\dtl@donext
\else
\ifnum\dtl@codeA<\dtl@codeB
#1=-1\relax
\else
\ifnum\dtl@codeA>\dtl@codeB
#1=1\relax
\else
\ifdefempty{\dtl@restA}%
{%
  \ifdefempty{\dtl@restB}%
  {%
    #1=0\relax
  }%
  {%
    #1=-1\relax
  }%
}%
{%
  \ifdefempty{\restB}%
  {%
    #1=1\relax
  }%
  {%
    \protected@edef\dtl@donext{%
      \noexpand\dtlcompare
      {\noexpand#1}{\dtl@restA}{\dtl@restB}}%
    \dtl@donext
```

```

    }%
  }%
  \fi
  \fi
  \fi
\fi
}{%

```

v2.25: added `\expandonce` to prevent non-ASCII characters from being expanded.

```

\edef\dtl@donext{%
  \noexpand\dtlcompare
  {\noexpand#1}%
  {\expandonce\dtl@firstA\expandonce\dtl@restA}%
  {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
}}{%
\edef\dtl@donext{%
  \noexpand\dtlcompare
  {\noexpand#1}%
  {\expandonce\dtl@firstA\expandonce\dtl@restA}%
  {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
}%
}%
}%
}

```

`\if@two@octets` Check if argument starts with `\UTFviii@two@octets`

```

\def\dtl@if@two@octets#1#2\dtl@end@if@two@octets#3#4{%
  \ifbool{\dtl@utf8}
  {%
    \ifx\UTFviii@two@octets#1\relax
    #3%
  \else
  #4%
  \fi
}%
{%
  #4%
}%
}

```

`\getfirst@UTFviii`

```

\def\dtl@getfirst@UTFviii#1#2#3\end@dtl@getfirst@UTFviii{%
  \def\dtl@first{#1#2}%
  \ifx\@nil#3\relax
  \def\dtl@rest{}%
  \else
  \expandafter\def\expandafter\dtl@rest\expandafter{\@dtl@firsttonil#3}%
  \fi
}

```

```
}
```

```
@dtl@firsttonil
```

```
\def\@dtl@firsttonil#1\@nil{#1}
```

```
\dtl@getfirst Gets the first object, and stores in \dtl@first. The remainder is stored in \dtl@rest.
```

```
\def\dtl@getfirst#1#2\end@dtl@getfirst{%  
  \def\dtl@first{#1}%  
  \ifdefempty{\dtl@first}%  
  {%  
    \def\dtl@rest{#2}%  
  }%  
  {%  
    \ifbool{@dtl@utf8}  
    {%  
      \expandafter\dtl@if@two@octets#1#2\relax\dtl@end@if@two@octets  
      {%  
        \dtl@getfirst@UTFviii#1#2\@nil\end@dtl@getfirst@UTFviii  
      }%  
      {%  
        \dtl@ifsingle{#1}{\def\dtl@rest{#2}}{\dtl@getfirst#1#2\end@dtl@getfirst}%  
      }%  
    }%  
    {%  
      \dtl@ifsingle{#1}{\def\dtl@rest{#2}}{\dtl@getfirst#1#2\end@dtl@getfirst}%  
    }%  
  }%  
}%
```

Count registers to store character codes:

```
\newcount\dtl@codeA  
\newcount\dtl@codeB
```

```
\dtl@setcharcode \dtl@setcharcode{<c>}{<count register>}
```

Sets *<count register>* to the character code of *<c>*, or to -1 if *<c>* is a control sequence, unless *<c>* is either `\space` or `~` in which case it sets *<count register>* to the character code of the space character.

```
\newcommand*{\dtl@setcharcode}[2]{%  
  \ifstrempy{#1}%  
  {%
```

Empty argument. Set code to -1.

```
    #2=-1\relax  
  }%  
  {%  
    \ifx\@dtl@wordbreak#1\relax
```

Reached a word break. Set to character code of a space.

```
#2=' \relax
\else
\ifcat\noexpand#1\relax
```

Argument is a control sequence, so set to 0.

```
#2=0\relax
\else
\expandafter\dtl@if@two@octets#1\relax\relax\dtl@end@if@two@octets
{%
```

Argument is a UTF8 character.

```
\dtlsetUTFviiiicharcode{#1}{#2}%
}%
{%
```

Argument is a character, so set to the character code.

```
\dtlsetcharcode{#1}{#2}%
}%
\fi
\fi
}%
}
```

`\dtlsetcharcode` Set the code for the given character. May be redefined by user for non-UTF8 encodings (e.g. Latin-1).

```
\newcommand*\dtlsetcharcode[2]{#2='#1\relax}
```

`\dtlsetlccharcode` Set the lowercase code for the given character. May be redefined by user for non-UTF8 encodings (e.g. Latin-1).

```
\newcommand*\dtlsetlccharcode[2]{#2=\lccode'#1\relax}
```

`\dtlsetUTFviiiicharcode` Default behaviour is to set all UTF8 characters to code 64 (before A). This will need to be redefined according to the relevant alphabet.

```
\newcommand*\dtlsetUTFviiiicharcode[2]{\dtlsetdefaultUTFviiiicharcode{#1}{#2}}
```

`\dtlsetUTFviiilccharcode` Default behaviour is to set all UTF8 characters to code 96 (before a). This will need to be redefined according to the relevant alphabet.

```
\newcommand*\dtlsetUTFviiilccharcode[2]{\dtlsetdefaultUTFviiilccharcode{#1}{#2}}
```

`\dtlsetUTFviiiicharcode` Default codes for some supplemental Latin characters.

```
\newcommand*\dtlsetdefaultUTFviiiicharcode[2]{%
\ifboolexpr
{
test {\ifstrequal{#1}{À}}
or test {\ifstrequal{#1}{Á}}
or test {\ifstrequal{#1}{Â}}
or test {\ifstrequal{#1}{Ã}}
or test {\ifstrequal{#1}{Ä}}
```

```

}%
{%
  #2='A\relax
}%
{%
  \ifstrequal{#1}{Q}%
  {%
    #2='C\relax
  }%
  {%
    \ifboolexpr
    {
      test {\ifstrequal{#1}{E}}
      or test {\ifstrequal{#1}{E}}
      or test {\ifstrequal{#1}{E}}
      or test {\ifstrequal{#1}{E}}
    }%
    {%
      #2='E\relax
    }%
    {%
      \ifboolexpr
      {
        test {\ifstrequal{#1}{I}}
        or test {\ifstrequal{#1}{I}}
        or test {\ifstrequal{#1}{I}}
        or test {\ifstrequal{#1}{I}}
      }%
      {%
        #2='I\relax
      }%
      {%
        \ifstrequal{#1}{N}%
        {%
          #2='N\relax
        }%
        {%
          \ifboolexpr
          {
            test {\ifstrequal{#1}{O}}
            or test {\ifstrequal{#1}{O}}
            or test {\ifstrequal{#1}{O}}
            or test {\ifstrequal{#1}{O}}
            or test {\ifstrequal{#1}{O}}
          }%
          {%
            #2='O\relax
          }%
          {%

```

```

\ifboolexpr
{
  test {\ifstrequal{#1}{Û}}
  or test {\ifstrequal{#1}{Ü}}
  or test {\ifstrequal{#1}{Ū}}
  or test {\ifstrequal{#1}{Ů}}
}%
{%
#2='U\relax
}%
{%
\ifstrequal{#1}{Ÿ}%
{%
#2='Y\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{â}}
  or test {\ifstrequal{#1}{á}}
  or test {\ifstrequal{#1}{à}}
  or test {\ifstrequal{#1}{ã}}
  or test {\ifstrequal{#1}{ä}}
}%
{%
#2='a\relax
}%
{%
\ifstrequal{#1}{ç}%
{%
#2='c\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{è}}
  or test {\ifstrequal{#1}{é}}
  or test {\ifstrequal{#1}{ê}}
  or test {\ifstrequal{#1}{ë}}
}%
{%
#2='e\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{i}}
  or test {\ifstrequal{#1}{í}}
  or test {\ifstrequal{#1}{î}}

```

```

    or test {\ifstrequal{#1}{i}}
  }%
  {%
    #2='i\relax
  }%
  {%
    \ifstrequal{#1}{ñ}%
    {%
      #2='n\relax
    }%
    {%
      \ifboolexpr
      {
        test {\ifstrequal{#1}{ò}}
        or test {\ifstrequal{#1}{ó}}
        or test {\ifstrequal{#1}{ô}}
        or test {\ifstrequal{#1}{õ}}
        or test {\ifstrequal{#1}{ö}}
      }%
      {%
        #2='o\relax
      }%
      {%
        \ifboolexpr
        {
          test {\ifstrequal{#1}{ù}}
          or test {\ifstrequal{#1}{ú}}
          or test {\ifstrequal{#1}{û}}
          or test {\ifstrequal{#1}{ü}}
        }%
        {%
          #2='u\relax
        }%
        {%
          \ifstrequal{#1}{ÿ}%
          {%
            #2='y\relax
          }%
          {%
            #2=64\relax
          }%
        }%
      }%
    }%
  }%
}

```

```

        }%
    }%
}

```

`\Fviiilccharcode` As above but for case-insensitive comparison.

```

\newcommand*\dtlsetdefaultUTFviiilccharcode[2]{%
\ifboolexpr
{
    test {\ifstrequal{#1}{à}}
  or test {\ifstrequal{#1}{á}}
  or test {\ifstrequal{#1}{â}}
  or test {\ifstrequal{#1}{ã}}
  or test {\ifstrequal{#1}{ä}}
  or test {\ifstrequal{#1}{Å}}
  or test {\ifstrequal{#1}{Á}}
  or test {\ifstrequal{#1}{Ã}}
  or test {\ifstrequal{#1}{Ä}}
}%
{%
    #2='a\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{ç}}
  or test {\ifstrequal{#1}{Ç}}
}
{%
    #2='c\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{è}}
  or test {\ifstrequal{#1}{é}}
  or test {\ifstrequal{#1}{ê}}
  or test {\ifstrequal{#1}{ë}}
  or test {\ifstrequal{#1}{È}}
  or test {\ifstrequal{#1}{É}}
  or test {\ifstrequal{#1}{Ê}}
  or test {\ifstrequal{#1}{Ë}}
}%
{%

```



```

#2='e\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{i}}
    or test {\ifstrequal{#1}{i}}
    or test {\ifstrequal{#1}{i}}
    or test {\ifstrequal{#1}{i}}
    or test {\ifstrequal{#1}{I}}
    or test {\ifstrequal{#1}{I}}
    or test {\ifstrequal{#1}{Î}}
    or test {\ifstrequal{#1}{Î}}
}%
{%
#2='i\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{ñ}}
    or test {\ifstrequal{#1}{Ñ}}
}
{%
#2='n\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{ò}}
    or test {\ifstrequal{#1}{ó}}
    or test {\ifstrequal{#1}{ô}}
    or test {\ifstrequal{#1}{ö}}
    or test {\ifstrequal{#1}{ö}}
    or test {\ifstrequal{#1}{Û}}
    or test {\ifstrequal{#1}{Û}}
    or test {\ifstrequal{#1}{Û}}
    or test {\ifstrequal{#1}{Û}}
}%
{%
#2='o\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{ù}}
    or test {\ifstrequal{#1}{ú}}
    or test {\ifstrequal{#1}{û}}
}

```



Argument is a control sequence, so set to 0.

```
#2=0\relax
\else
\expandafter\dtl@if@two@octets#1\relax\relax\dtl@end@if@two@octets
{%
```

Argument is a UTF8 character.

```
\dtlsetUTFviiiiccharcode{#1}{#2}%
}%
{%
```

Argument is a character, so set to the lower case code.

```
\dtlsetlccharcode{#1}{#2}%
}%
```

If the result is zero, which means the character doesn't have a lower case equivalent. So set to the character code.

```
\ifnum#2=0\relax
#2='#1\relax
\fi
\fi
\fi
}%
}
```

`\dtlcompare` `\dtlcompare{<count>}{<string1>}{<string2>}`

As `\dtlcompare` but ignores case.

```
\newcommand*{\dtlcompare}[3]{%
\dtl@subno@brsp{#2}{\@dtl@argA}%
\dtl@subno@brsp{#3}{\@dtl@argB}%
\ifdefempty{\@dtl@argA}%
{%
```

Both are empty, so they are equal.

```
#1=0\relax
}%
{%
```

The first string is empty, but the second isn't. Therefore the first string is less than the second string.

```
#1=-1\relax
}%
}%
{%
```

The second string is empty, but the first isn't. Therefore the first string is greater than the second string.

```
#1=1\relax
}%
{%
```

Identify all word breaks.

```
\dtl@setwordbreaksnohyphens{\@dtl@argA}{\@dtl@wordbreak}%
\let\@dtl@argA\dtl@string
\dtl@setwordbreaksnohyphens{\@dtl@argB}{\@dtl@wordbreak}%
\let\@dtl@argB\dtl@string
```

Get the first object and the remaining text.

```
\expandafter\dtl@getfirst\@dtl@argA\end@dtl@getfirst
\let\dtl@firstA=\dtl@first
\let\dtl@restA=\dtl@rest
\expandafter\dtl@getfirst\@dtl@argB\end@dtl@getfirst
\let\dtl@firstB=\dtl@first
\let\dtl@restB=\dtl@rest
```

Is the first object of *<string1>* a single character or a group?

```
\expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstA}%
{%
```

It's a single character. Is the first object of *<string2>* a single character or a group?

```
\expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstB}%
{%
```

Both are a single character. Get the lower case character code.

```
\expandafter\dtl@setlccharcode\expandafter{\dtl@firstA}{\dtl@codeA}%
\expandafter\dtl@setlccharcode\expandafter{\dtl@firstB}{\dtl@codeB}%
\ifnum\dtl@codeA=-1\relax
\ifnum\dtl@codeB=-1\relax
```

v2.25: added `\expandonce` to prevent non-ASCII characters from being expanded.

```
\edef\dtl@donext{%
\noexpand\dtl@compare{\noexpand#1}%
{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
\dtl@donext
\else
\edef\dtl@donext{%
\noexpand\dtl@compare
{\noexpand#1}%
{\expandonce\dtl@restA}%
{\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
\fi
\else
\ifnum\dtl@codeB=-1\relax
```

v2.25: added `\expandonce` to prevent non-ASCII characters from being expanded.

```
\edef\dtl@donext{%
```

```

        \noexpand\dtlicompare
        {\noexpand#1}%
        {\expandonce\dtl@firstA\expandonce\dtl@restA}%
        {\expandonce\dtl@restB}}%
    \dtl@donext
\else
\ifnum\dtl@codeA<\dtl@codeB
#1=-1\relax
\else
\ifnum\dtl@codeA>\dtl@codeB
#1=1\relax
\else
\ifdefempty{\dtl@restA}%
{%
\ifdefempty{\dtl@restB}%
{%
#1=0\relax
}%
}%
#1=-1\relax
}%
}%
{%
\ifdefempty{\restB}%
{%
#1=1\relax
}%
}%

```

v2.25: added \expandonce to prevent non-ASCII characters from being expanded.

```

        \edef\dtl@donext{%
        \noexpand\dtlicompare
        {\noexpand#1}%
        {\expandonce\dtl@restA}%
        {\expandonce\dtl@restB}}%
    \dtl@donext
    }%
}
\fi
\fi
\fi
\fi
}%
{%

```

The first object in  $\langle string1 \rangle$  is a single character, but the first object in  $\langle string2 \rangle$  isn't a single character. v2.25: added \expandonce to prevent non-ASCII characters from being expanded.

```

\edef\dtl@donext{%
\noexpand\dtlicompare
{\noexpand#1}%

```

```

        {\expandonce\dtl@firstA\expandonce\dtl@restA}%
        {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
    \dtl@donext
  }%
}%
{%

```

Neither object is a single character. v2.25: added \expandonce to prevent non-ASCII characters from being expanded.

```

    \edef\dtl@donext{%
      \noexpand\dtlicompare
      {\noexpand#1}%
      {\expandonce\dtl@firstA\expandonce\dtl@restA}%
      {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
    \dtl@donext
  }%
}%
}%
}

```

ordindexcompare Word breaks come before all other letters of the alphabet.

```

\newcommand*\dtlwordindexcompare[3]{%
  \@dtldictcompare{#1}{#2}{#3}{\@dtl@wordbreak}%
}

```

terindexcompare Word breaks are ignored.

```

\newcommand*\dtlletterindexcompare[3]{%
  \@dtldictcompare{#1}{#2}{#3}{}}%
}

```

@dtldictcompare Word or letter compare. Fourth argument should be \@dtl@wordbreak for word compare or empty for letter compare.

```

\newcommand*\@dtldictcompare[4]{%
  \dtl@subnobsr{#2}{\@dtl@argA}%
  \dtl@subnobsr{#3}{\@dtl@argB}%
  \ifdefempty{\@dtl@argA}%
  {%
    \ifdefempty{\@dtl@argB}%
    {%
      #1=0\relax
    }%
  }%
  {%
    #1=-1\relax
  }%
}%
{%
  \ifdefempty{\@dtl@argB}%
  {%
    #1=1\relax
  }%
}

```

```
}%  
{%
```

Alphabetizing continues until a comma indicates inverted order. This assumes that an actual comma indicates that the comma forms part of the text (e.g. in a title of a play). Inversion commas should be indicated using commands such as `\datatoolpersoncomma`. There are three types of inverted order: people, places and subjects (concepts or objects). We also need to treat parenthetical material in a similar way. Find if the first string has an inverted order.

```
\expandafter\DTLsplitstring\expandafter  
  {\@dtl@argA}{\datatoolpersoncomma}{\@dtl@beforepart}{\@dtl@afterpart}%  
\ifdefempty{\@dtl@replaced}%  
{%  
  \expandafter\DTLsplitstring\expandafter  
    {\@dtl@argA}{\datatoolplacecomma}{\@dtl@beforepart}{\@dtl@afterpart}%  
\ifdefempty{\@dtl@replaced}%  
{%  
  \expandafter\DTLsplitstring\expandafter  
    {\@dtl@argA}{\datatoolsubjectcomma}{\@dtl@beforepart}{\@dtl@afterpart}%  
\ifdefempty{\@dtl@replaced}%  
{%  
  \expandafter\DTLsplitstring\expandafter  
    {\@dtl@argA}{\datatoolparenstart}{\@dtl@beforepart}{\@dtl@afterpart}%  
\ifdefempty{\@dtl@replaced}%  
{%  
  \def\@dtl@A@comma{0}%  
  \let\@dtl@A@before\@dtl@argA  
  \def\@dtl@A@after{}%  
}%  
{%  
  \let\@dtl@A@comma\@dtl@replaced  
  \let\@dtl@A@before\@dtl@beforepart  
  \let\@dtl@A@after\@dtl@afterpart  
}%  
}%  
{%  
  \let\@dtl@A@comma\@dtl@replaced  
  \let\@dtl@A@before\@dtl@beforepart  
  \let\@dtl@A@after\@dtl@afterpart  
}%  
}%  
{%  
  \let\@dtl@A@comma\@dtl@replaced  
  \let\@dtl@A@before\@dtl@beforepart  
  \let\@dtl@A@after\@dtl@afterpart  
}%  
}%  
{%  
  \let\@dtl@A@comma\@dtl@replaced  
  \let\@dtl@A@before\@dtl@beforepart
```

```

\let\@dtl@A@after\@dtl@afterpart
}%

```

Now find if the second string has an inverted order.

```

\expandafter\DTLsplitstring\expandafter
{\@dtl@argB}{\datatoolpersoncomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
\expandafter\DTLsplitstring\expandafter
{\@dtl@argB}{\datatoolplacecomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
\expandafter\DTLsplitstring\expandafter
{\@dtl@argB}{\datatoolsubjectcomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
\expandafter\DTLsplitstring\expandafter
{\@dtl@argB}{\datatoolparenstart}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
\def\@dtl@B@comma{0}%
\let\@dtl@B@before\@dtl@argB
\def\@dtl@B@after{}}%
}%
}%
{\let\@dtl@B@comma\@dtl@replaced
\let\@dtl@B@before\@dtl@beforepart
\let\@dtl@B@after\@dtl@afterpart
}%
}%
{\let\@dtl@B@comma\@dtl@replaced
\let\@dtl@B@before\@dtl@beforepart
\let\@dtl@B@after\@dtl@afterpart
}%
}%
{\let\@dtl@B@comma\@dtl@replaced
\let\@dtl@B@before\@dtl@beforepart
\let\@dtl@B@after\@dtl@afterpart
}%
}%
{\let\@dtl@B@comma\@dtl@replaced
\let\@dtl@B@before\@dtl@beforepart
\let\@dtl@B@after\@dtl@afterpart
}%
}%

```

Get the first letter and find out if it's a letter, digit or symbol.

```

\expandafter\dtl@ifcasechargroup\@dtl@A@before\dtl@end@ifcasechargroup

```



```

{\def\@dtl@A@chargroup{2}}%
{\def\@dtl@A@chargroup{1}}%
{\def\@dtl@A@chargroup{0}}%
\expandafter\dtl@ifcasechargroup\@dtl@B@before\dtl@end@ifcasechargroup
{\def\@dtl@B@chargroup{2}}%
{\def\@dtl@B@chargroup{1}}%
{\def\@dtl@B@chargroup{0}}%

```

Are they in the same group?

```

\ifnum\@dtl@A@chargroup<\@dtl@B@chargroup
#1=-1\relax
\else
\ifnum\@dtl@A@chargroup>\@dtl@B@chargroup
#1=1\relax
\else

```

In the same group. Which group are they in?

```

\ifcase\@dtl@A@chargroup

```

Symbol group v2.25: added \expandonce to prevent non-ASCII characters from being expanded.

```

\edef\dtl@donext{%
\noexpand\dtlcompare
{\noexpand#1}%
{\expandonce\@dtl@A@before}%
{\expandonce\@dtl@B@before}}%
\dtl@donext

```

Number.

```

\or
\ifnum\@dtl@A@before<\@dtl@B@before\relax
#1=-1\relax
\else
\ifnum\@dtl@A@before>\@dtl@B@before\relax
#1=1\relax
\else
#1=0\relax
\fi
\fi
\or

```

Word or phrase.

```

\@dtlwordindexcompare{#1}{\@dtl@A@before}{\@dtl@B@before}
{\dtlicomparewords}{#4}%

```

If they are equal, do we have an inverted order?

```

\ifnum#1=0\relax

```

Temporarily redefine the inversion commas to numbers to make the comparisons easier.

```

\let\@org@dtl@person@comma\datatoolpersoncomma
\let\@org@dtl@place@comma\datatoolplacecomma
\let\@org@dtl@subject@comma\datatoolsubjectcomma
\let\@org@dtl@paren@start\datatoolparenstart

```

People first, then places, then subjects, then no inversion, then parenthetical.

```
\def\datatoolpersoncomma{3}%  
\def\datatoolplacecomma{2}%  
\def\datatoolsubjectcomma{1}%  
\def\datatoolparenstart{-1}%
```

Now compare:

```
\ifnum\@dtl@A@comma>\@dtl@B@comma\relax  
#1=-1\relax  
\else  
\ifnum\@dtl@A@comma<\@dtl@B@comma\relax  
#1=1\relax  
\else
```

They are the same type. First do a reverse case sensitive comparison.

```
\@dtlwordindexcompare{#1}{\@dtl@B@before}{\@dtl@A@before}  
{\dtlcomparewords}{#4}%
```

Are they still equal?

```
\ifnum#1=0\relax
```

So sort on inversion.

```
\@dtlwordindexcompare{#1}{\@dtl@A@after}{\@dtl@B@after}  
{\dtlicomparewords}{#4}%  
\fi  
\fi  
\fi
```

Restore original definitions.

```
\let\datatoolpersoncomma\@org@dtl@person@comma  
\let\datatoolplacecomma\@org@dtl@place@comma  
\let\datatoolsubjectcomma\@org@dtl@subject@comma  
\let\datatoolparenstart\@org@dtl@paren@start  
\fi  
\fi  
\fi  
\fi  
}%  
}%  
}%
```

Need to indicate type of inversion.

toolpersoncomma

```
\newcommand*{\datatoolpersoncomma}{,\space}
```

atoolplacecomma

```
\newcommand*{\datatoolplacecomma}{,\space}
```

oolsubjectcomma

```
\newcommand*{\datatoolsubjectcomma}{,\space}
```

atoolparenstart

```
\newcommand*\datatoolparenstart}{\space}
```

wordindexcompare

```
\@dtlwordindexcompare{<count>}{<cs A>}{<cs B>}{<word comparison handler>}
{<word break replacement>}
```

```
\newcommand*\@dtlwordindexcompare}[5]{%
```

Word or phrase. Replace word breaks.

```
\dtl@setwordbreaks{#2}{#5}%
```

```
\let#2\dtl@string
```

And again for the second string.

```
\dtl@setwordbreaks{#3}{#4}%
```

```
\let#3\dtl@string
```

Now compare both strings.

```
% \@dtl@dict@compare{#1}{#2}{#3}{#4}%
```

```
\edef\@dtl@do@compare{%
```

```
\noexpand#4{\noexpand#1}%
```

```
{\expandonce#2}{\expandonce#3}%
```

```
}%
```

```
\@dtl@do@compare
```

```
}
```

dtl@dict@compare

```
\@dtl@dict@compare{<count>}{<cs A>}{<cs B>}{<word comparison handler>}
```

Now that all the word breaks have been identified with \@dtl@wordbreak compare both strings.

```
\newcommand*\@dtl@dict@compare}[4]{%
```

Are either empty?

```
\ifdefempty{#2}%
```

```
{%
```

A is empty. Is B empty?

```
\ifdefempty{#3}%
```

```
{%
```

Both are empty.

```
#1=0\relax
```

```
}%
```

```
{%
```

A is empty but B isn't

```
#1=-1\relax
}%
}%
{%
```

A isn't empty. Is B empty?

```
\ifdefempty{#3}%
{%
```

B is empty but A isn't.

```
#1=1\relax
}%
{%
```

Neither are empty. Grab first word from A.

```
\expandafter\dtl@grabword#2\@dtl@endgrabword\dtl@A@first\dtl@A@remain
```

Grab first word from B.

```
\expandafter\dtl@grabword#3\@dtl@endgrabword\dtl@B@first\dtl@B@remain
```

Compare A and B.

```
\edef\@dtl@do@compare{%
  \noexpand#4{\noexpand#1}%
  {\expandonce\dtl@A@first}{\expandonce\dtl@B@first}%
}%
\@dtl@do@compare
```

Are they the same?

```
\ifnum#1=0\relax
```

They are, so compare on the next word.

```
\@dtl@dict@compare{#1}{\dtl@A@remain}{\dtl@B@remain}{#4}%
\fi
}%
}%
}
```

`\dtl@grabword` Grab first word from phrase.

```
\def\dtl@grabword#1\@dtl@wordbreak#2\@dtl@endgrabword#3#4{%
  \def#3{#1}%
  \def#4{#2}%
}
```

`\dtlicomparewords`

```
\dtlicomparewords{<count>}{<word A>}{<word B>}
```

This does a case insensitive comparison.

```
\newcommand{\dtlicomparewords}[3]{%
  \dtlicompare{#1}{#2}{#3}%
}
```

```
\dtlcomparewords \dtlcomparewords{<count>}{<word A>}{<word B>}
```

This does a case sensitive comparison.

```
\newcommand{\dtlcomparewords}[3]{%
  \dtlcompare{#1}{#2}{#3}%
}
```

l@setwordbreaks Replace word breaks (space, \space, \, ~ and hyphen -) with the second argument (either \@dtl@wordbreak for letter sort or nothing for word sort). Result is stored in \dtl@string.

```
\newcommand*{\dtl@setwordbreaks}[2]{%
  \expandafter\dtl@subnohrsp\expandafter{#1}{\dtl@string}%
  \DTLsubstituteall{\dtl@string}{~}{#2}%
  \DTLsubstituteall{\dtl@string}{\ }{#2}%
  \DTLsubstituteall{\dtl@string}{\space}{#2}%
  \DTLsubstituteall{\dtl@string}{-}{#2}%
}
```

Now deal with actual spaces.

```
\toks@{#2}%
\edef\dtl@do@setwordbreaks{%
  \noexpand\@dtl@setwordbreaks{\the\toks@}\expandonce\dtl@string\space\noexpand\@nil}%
\def\dtl@string{}%
\dtl@do@setwordbreaks
}
```

l@setwordbreaks

```
\def\@dtl@setwordbreaks#1#2 #3{%
  \def\dtl@tmp{#3}%
  \ifx\@nnil\dtl@tmp
```

Reached end of loop.

```
\let\@dtl@setwordbreaks@next\@gobbletwo
\appto\dtl@string{#2}%
\else
  \let\@dtl@setwordbreaks@next\@dtl@setwordbreaks
  \appto\dtl@string{#2#1}%
\fi
\@dtl@setwordbreaks@next{#1}#3%
}
```

breaksnohyphens As \dtl@setwordbreaks but excludes hyphens.

```
\newcommand*{\dtl@setwordbreaksnohyphens}[2]{%
  \expandafter\dtl@subnohrsp\expandafter{#1}{\dtl@string}%
  \DTLsubstituteall{\dtl@string}{~}{#2}%
  \DTLsubstituteall{\dtl@string}{\ }{#2}%
  \DTLsubstituteall{\dtl@string}{\space}{#2}%
}
```

Now deal with actual spaces.

```
\toks@{#2}%
```

```

\edef\dtl@do@setwordbreaks{%
  \noexpand\@dtl@setwordbreaks{\the\toks@}\expandonce\dtl@string\space\noexpand\@nil}%
\def\dtl@string{%
\dtl@do@setwordbreaks
}

```

\@dtl@wordbreak

```
\newcommand*\@dtl@wordbreak}{ }
```

ifcasechargroup Determine if first character is a letter, a digit or a symbol.

```
\def\dtl@ifcasechargroup#1#2\dtl@end@ifcasechargroup#3#4#5{%
```

Does it start with a UTF8 character?

```
\expandafter\dtl@if@two@octets#1#2\relax\relax\dtl@end@if@two@octets
{%
```

Get the lower case character code.

```

\dtl@getfirst@UTFviii#1#2\@nil\end@dtl@getfirst@UTFviii
\expandafter\dtlsetUTFviii\lcccharcode\expandafter{\dtl@first}{\count@}%
\ifnum\count@<'a\relax #5\else#3\fi
}%
{%
\dtlifcasechargroup{#1}%
{#3}%
{%

```

Starts with a digit. Is the whole thing an integer?

```

\DTLifint{#1#2}
{%
#4%
}%
{%

```

No, it isn't. Consider it a string.

```

#3%
}%
}%
{#5}%
}%
}

```

macro `\dtlifcasechargroup{<char>}{<case letter>}{<case digit>}{<case symbol>}`

```

\newcommand*\dtlifcasechargroup[4]{%
\count@=#1\relax
\dtlifintclosedbetween{\number\count@}{48}{57}%
{%

```

It's a digit.

```
#3%
}%
{%
\dtlifintclosedbetween{\number\count@}{97}{122}%
{%
```

Lower case letter

```
#2%
}%
{%
\dtlifintclosedbetween{\number\count@}{65}{90}%
{%
```

Upper case letter

```
#2%
}%
{%
```

Other

```
#4%
}%
}%
}%
}
```

```
\dtlparsewords \dtlparsewords{<phrase>}{<handler cs>}
```

Iterates through the given phrase. Hyphens are considered word boundaries.

```
\newcommand*{\dtlparsewords}[2]{%
\dtl@subnohrsp{#1}{\dtl@string}%
\DTLsubstituteall{\dtl@string}{~}{ }%
\DTLsubstituteall{\dtl@string}{\ }{ }%
\DTLsubstituteall{\dtl@string}{\space}{ }%
\DTLsubstituteall{\dtl@string}{-}{ }%
\let\dtl@parsewordshandler#2\relax
\edef\dtl@donext{%
\noexpand\@dtl@parse@words\expandonce\dtl@string\space\noexpand\@nil}%
\dtl@donext
}
```

```
dtl@parse@words
```

```
\def\@dtl@parse@words#1 #2{%
\def\dtl@tmp{#2}%
\ifx\@nnil\dtl@tmp
\let\parse@wordshandler=\@gobble
\else
```

```

\let\parse@wordsnext=\@dtl@parse@words
\fi
\dlt@parsewordshandler{#1}%
\parse@wordsnext#2%
}

```

`\DTLifstringlt` `\DTLifstringlt{<string1>}{<string2>}{<true part>}{<false part>}`

String comparison (Starred version ignores case)

```
\newcommand*{\DTLifstringlt}{\@ifstar\@sDTLifstringlt\@DTLifstringlt}
```

Unstarred version

```

\newcommand*{\@DTLifstringlt}[4]{%
\protected@edef\@dtl@tmpcmp{%
\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
\@dtl@tmpcmp
\ifnum\@dtl@tmpcount<0\relax
#3%
\else
#4%
\fi
}

```

Starred version

```

\newcommand*{\@sDTLifstringlt}[4]{%
\protected@edef\@dtl@tmpcmp{%
\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
\@dtl@tmpcmp
\ifnum\@dtl@tmpcount<0\relax
#3%
\else
#4%
\fi
}

```

`\DTLiflt` `\DTLiflt{<arg1>}{<arg2>}{<true part>}{<false part>}`

Does `\DTLifnumlt` if both `<arg1>` and `<arg2>` are numerical, otherwise do `\DTLifstringlt` (unstarred version) or `\DTLifstringlt*` (starred version).

```
\newcommand*{\DTLiflt}{\@ifstar\@sDTLiflt\@DTLiflt}
```

Unstarred version

```

\newcommand*{\@DTLiflt}[4]{%
\dtl@testbothnumerical{#1}{#2}%
\if@dtl@condition

```



```

\DTLifnumlt{#1}{#2}{#3}{#4}%
\else
\@DTLifstringlt{#1}{#2}{#3}{#4}%
\fi
}

```

#### Starred version

```

\newcommand*{\@sDTLiflt}[4]{%
\dtl@testbothnumerical{#1}{#2}%
\if@dtl@condition
\DTLifnumlt{#1}{#2}{#3}{#4}%
\else
\@sDTLifstringlt{#1}{#2}{#3}{#4}%
\fi
}

```

`\DTLifnumgt` `\DTLifnumgt{<num1>}{<num2>}{<true part>}{<>false part>}`

Determines if  $\{<num1>\} > \{<num2>\}$ . Both numbers need to have the decimal separator changed to a dot to ensure that it works with `\dtlifnumgt`

```

\newcommand*{\DTLifnumgt}[4]{%
\DTLconverttodecimal{#1}{\@dtl@numi}%
\DTLconverttodecimal{#2}{\@dtl@numii}%
\dtlifnumgt{\@dtl@numi}{\@dtl@numii}%
{%
#3%
}%
{%
#4%
}%
}

```

`\DTLifstringgt` `\DTLifstringgt{<string1>}{<string2>}{<true part>}{<>false part>}`

String comparison (starred version ignores case)

```

\newcommand*{\DTLifstringgt}{\@ifstar\@sDTLifstringgt\@DTLifstringgt}

```

#### Unstarred version

```

\newcommand*{\@DTLifstringgt}[4]{%
\protected@edef\@dtl@tmpcmp{%
\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
\@dtl@tmpcmp
\ifnum\@dtl@tmpcount>0\relax
#3%
}

```

```

\else
  #4%
\fi
}

```

Starred version

```

\newcommand*\@sDTLifstringgt}[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount>0\relax
    #3%
  \else
    #4%
  \fi
}

```

`\DTLifgt` `\DTLifgt{<arg1>}{<arg2>}{<true part>}{<false part>}`

Does `\DTLifnumgt` if both `<arg1>` and `<arg2>` are numerical, otherwise do `\DTLifstringgt` or `\DTLifstringgt*`.

```

\newcommand*\@DTLifgt{\@ifstar\@sDTLifgt\@DTLifgt}

```

Unstarred version

```

\newcommand*\@DTLifgt}[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumgt{#1}{#2}{#3}{#4}%
  \else
    \@DTLifstringgt{#1}{#2}{#3}{#4}%
  \fi
}

```

Starred version

```

\newcommand*\@sDTLifgt}[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumgt{#1}{#2}{#3}{#4}%
  \else
    \@sDTLifstringgt{#1}{#2}{#3}{#4}%
  \fi
}

```

`\DTLifnumeq` `\DTLifnumeq{<num1>}{<num2>}{<true part>}{<false part>}`

Determines if  $\langle num1 \rangle = \langle num2 \rangle$ . Both numbers need to have the decimal separator changed to a dot to ensure that it works with `\dtlifnumeq`

```
\newcommand*\DTLlifnumeq[4]{%
  \DTLconverttodecimal{#1}{\@dtl@numi}%
  \DTLconverttodecimal{#2}{\@dtl@numii}%
  \dtlifnumeq{\@dtl@numi}{\@dtl@numii}%
  {%
    #3%
  }%
  {%
    #4%
  }%
}
```

`\DTLifstringeq` `\DTLifstringeq{<string1>}{<string2>}{<>true part>}{<>false part>}`

String comparison (starred version ignores case)

```
\newcommand*\DTLifstringeq{\@ifstar\@sDTLifstringeq\@DTLifstringeq}
```

Unstarred version

```
\newcommand*\@DTLifstringeq[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount=0\relax
    #3%
  \else
    #4%
  \fi
}
```

Starred version

```
\newcommand*\@sDTLifstringeq[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount=0\relax
    #3%
  \else
    #4%
  \fi
}
```

`\DTLifeq` `\DTLifeq{<arg1>}{<arg2>}{<>true part>}{<>false part>}`

Does `\DTLifnumeq` if both  $\langle arg1 \rangle$  and  $\langle arg2 \rangle$  are numerical, otherwise do `\DTLifstringeq` or `\DTLifstringeq*`.

```
\newcommand*\@DTLifeq{\@ifstar\@sDTLifeq\@DTLifeq}
```

Unstarred version

```
\newcommand*\@DTLifeq[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \ifdtl@condition
    \DTLifnumeq{#1}{#2}{#3}{#4}%
  \else
    \@DTLifstringeq{#1}{#2}{#3}{#4}%
  \fi
}
```

Starred version

```
\newcommand*\@sDTLifeq[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \ifdtl@condition
    \DTLifnumeq{#1}{#2}{#3}{#4}%
  \else
    \@sDTLifstringeq{#1}{#2}{#3}{#4}%
  \fi
}
```

`\DTLifSubString`

```
\DTLifSubString{<string>}{<sub string>}{<true part>}{<false part>}
```

If  $\langle sub\ string \rangle$  is contained in  $\langle string \rangle$  does  $\langle true\ part \rangle$ , otherwise does  $\langle false\ part \rangle$ .

```
\newcommand*\@DTLifSubString[4]{%
  \protected@edef\@dtl@dotestifsubstring{\noexpand\dtl@testifsubstring
{#1}{#2}}%
  \@dtl@dotestifsubstring
  \ifdtl@condition
    #3%
  \else
    #4%
  \fi
}
```

`testifsubstring`

```
\newcommand*\@dtl@testifsubstring[2]{%
  \dtl@subnohrsp{#1}{\@dtl@argA}%
  \dtl@subnohrsp{#2}{\@dtl@argB}%
}
```

Identify all word breaks.

```
\dtl@setwordbreaksnohyphens{\@dtl@argA}{\@dtl@wordbreak}%
\let\@dtl@argA\dtl@string
\dtl@setwordbreaksnohyphens{\@dtl@argB}{\@dtl@wordbreak}%

```

```

\let\@dtl@argB\dtl@string
\edef\dtl@donext{%
  \noexpand\@dtl@testifsubstring{\expandonce\@dtl@argA}{\expandonce\@dtl@argB}}%
\dtl@donext
}
\newcommand*\@dtl@testifsubstring}[2]{%

\def\@dtl@subs@argA{#1}%
\def\@dtl@subs@argB{#2}%
\ifdefempty{\@dtl@subs@argB}%
{%
  \@dtl@conditiontrue
}%
{%
\ifdefempty{\@dtl@subs@argA}%
{%
  \@dtl@conditionfalse
}%
{%
  \@dtl@teststartswith{#1}{#2}%
  \if@dtl@condition
\else
  \dtl@getfirst#1\end@dtl@getfirst
  \expandafter\dtl@ifsingle\expandafter{\dtl@first}%
  {%
    \expandafter\@dtl@testifsubstring\expandafter{\dtl@rest}{#2}%
  }%
  {%
    \protected@edef\@dtl@donext{\noexpand\@dtl@testifsubstring
      {\expandonce\dtl@first\expandonce\dtl@rest}{\expandonce\@dtl@subs@argB}}%
    \@dtl@donext
  }%
\fi
}%
}%
}

```

\DTLifStartsWith \DTLifStartsWith{<string>}{<substring>}{<>true part>}{<>false part>}

If <string> starts with <substring>, this does <>true part>, otherwise it does <>false part>.

```

\newcommand*\DTLifStartsWith}[4]{%
  \@dtl@conditionfalse
  \protected@edef\@dtl@tmp{\noexpand\dtl@teststartswith{#1}{#2}}%
  \@dtl@tmp
  \if@dtl@condition
  #3%
  \else

```

```

    #4%
    \fi
}

```

```

\dtl@teststartswith{\dtl@teststartswith{\string}\{prefix\}}

```

Tests if *string* starts with *prefix*. This sets `\if@dtl@condition`. First substitute all word breaks with `\dtl@setwordbreaksnohyphen`

```

\newcommand*\dtl@teststartswith[2]{%
  \dtl@subnohrsp{#1}\@dtl@argA}%
  \dtl@subnohrsp{#2}\@dtl@argB}%

```

Identify all word breaks.

```

\dtl@setwordbreaksnohyphens{\@dtl@argA}\@dtl@wordbreak}%
\let\@dtl@argA\dtl@string
\dtl@setwordbreaksnohyphens{\@dtl@argB}\@dtl@wordbreak}%
\let\@dtl@argB\dtl@string
\edef\dtl@donext{%
  \noexpand\dtl@teststartswith{\expandonce\@dtl@argA}\expandonce\@dtl@argB}}%
\dtl@donext
}

```

```

\newcommand*\@dtl@teststartswith[2]{%
  \def\@dtl@argA{#1}%
  \def\@dtl@argB{#2}%
  \ifdefempty{\@dtl@argA}%
  {%
    \ifdefempty{\@dtl@argB}%
    {%
      \@dtl@conditiontrue
    }%
  }%
  {%
    \@dtl@conditionfalse
  }%
}%
{%
  \ifdefempty{\@dtl@argB}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \expandafter\dtl@getfirst\@dtl@argA\end\dtl@getfirst

```

Get the first object and the remaining text.

```

\let\dtl@firstA=\dtl@first
\let\dtl@restA=\dtl@rest
\expandafter\dtl@getfirst\@dtl@argB\end\dtl@getfirst

```

```
\let\dtl@firstB=\dtl@first
\let\dtl@restB=\dtl@rest
```

Is the first object of  $\langle string1 \rangle$  a single character or a group?

```
\expandafter\dtl@ifsingle\expandafter{\dtl@firstA}%
{%
```

It's a single character. Is the first object of  $\langle string2 \rangle$  a single character or a group?

```
\expandafter\dtl@ifsingle\expandafter{\dtl@firstB}%
{%
```

Both are a single character. Get the lower case character code.

```
\expandafter\dtl@setcharcode\expandafter{\dtl@firstA}{\dtl@codeA}%
\expandafter\dtl@setcharcode\expandafter{\dtl@firstB}{\dtl@codeB}%
\ifnum\dtl@codeA=-1\relax
  \ifnum\dtl@codeB=-1\relax
    \protected@edef\dtl@donext{%
      \noexpand\@dtl@teststartswith{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
    \dtl@donext
  \else
    \protected@edef\dtl@donext{%
      \noexpand\@dtl@teststartswith
        {\expandonce\dtl@restA}{\expandonce\dtl@firstB\expandonce\dtl@restB}}%
    \dtl@donext
  \fi
\else
  \ifnum\dtl@codeB=-1\relax
    \protected@edef\dtl@donext{%
      \noexpand\@dtl@teststartswith
        {\expandonce\dtl@firstA\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
    \dtl@donext
  \else
    \ifnum\dtl@codeA=\dtl@codeB
      \protected@edef\dtl@donext{%
        \noexpand\@dtl@teststartswith{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
      \dtl@donext
    \else
      \@dtl@conditionfalse
    \fi
  \fi
\fi
\fi
}%
{%
```

The first object in  $\langle string1 \rangle$  is a single character, but the first object in  $\langle string2 \rangle$  isn't a single character.

```
\protected@edef\dtl@donext{%
  \noexpand\@dtl@teststartswith
    {\expandonce\dtl@firstA\expandonce\dtl@restA}%
    {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
```

```
}%
}%
{%
```

Neither object is a single character.

```
\protected@edef\dtl@donext{%
\noexpand\@dtl@teststartswith
{\expandonce\dtl@firstA\expandonce\dtl@restA}%
{\expandonce\dtl@firstB\expandonce\dtl@restB}}%
}%
}%
}%
}
```

numclosedbetween

```
\DTLifnumclosedbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}
```

Determines if  $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$ .

```
\newcommand*{\DTLifnumclosedbetween}[5]{%
\DTLconverttodecimal{#1}{\@dtl@numi}%
\DTLconverttodecimal{#2}{\@dtl@numii}%
\DTLconverttodecimal{#3}{\@dtl@numiii}%
\DTLifFPclosedbetween{\@dtl@numi}{\@dtl@numii}{\@dtl@numiii}{#4}{#5}%
}
```

stringclosedbetween

```
\DTLifstringclosedbetween{<string>}{<min>}{<max>}{<true part>}{<false
part>}
```

String comparison (starred version ignores case)

```
\newcommand*{\DTLifstringclosedbetween}{%
\ifstar\@sDTLifstringclosedbetween\@DTLifstringclosedbetween
}
```

Unstarred version

```
\newcommand*{\@DTLifstringclosedbetween}[5]{%
\protected@edef\@dtl@tmpcmp{%
\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
\@dtl@tmpcmp
\let\@dtl@dovalue\relax
\ifnum\@dtl@tmpcount<0\relax
\def\@dtl@dovalue{#5}%
\fi
\ifx\@dtl@dovalue\relax
\protected@edef\@dtl@tmpcmp{%
\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
\@dtl@tmpcmp
```



```

\ifnum\@dtl@tmpcount>0\relax
  \def\@dtl@dovalue{#5}%
\else
  \def\@dtl@dovalue{#4}%
\fi
\fi
\@dtl@dovalue
}

```

#### Starred version

```

\newcommand*{\@sDTLifstringclosedbetween}[5]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtl@compare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \let\@dtl@dovalue\relax
  \ifnum\@dtl@tmpcount<0\relax
    \def\@dtl@dovalue{#5}%
  \fi
  \ifx\@dtl@dovalue\relax
    \protected@edef\@dtl@tmpcmp{%
      \noexpand\dtl@compare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
    \@dtl@tmpcmp
    \ifnum\@dtl@tmpcount>0\relax
      \def\@dtl@dovalue{#5}%
    \else
      \def\@dtl@dovalue{#4}%
    \fi
  \fi
  \@dtl@dovalue
}

```

Lifclosedbetween

```
\DTLifclosedbetween{<arg>}{<min>}{<max>}{<true part>}{<false part>}
```

Does `\DTLifnumclosedbetween` if `{<arg>}`, `<min>` and `<max>` are numerical, otherwise do `\DTLifstringclosedbetween` or `\DTLifstringclosedbetween*`.

```

\newcommand*{\DTLifclosedbetween}{%
  \@ifstar\@sDTLifclosedbetween\@DTLifclosedbetween
}

```

#### Unstarred version

```

\newcommand*{\@DTLifclosedbetween}[5]{%
  \dtl@testbothnumerical{#2}{#3}%
  \if@dtl@condition
    \dtl@ifsingle{#1}{%
      \edef\@dtl@tmp{#1}{%
        \def\@dtl@tmp{#1}}%
    \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
  }
}

```

```

\ifnum\@dtl@datatype>0\relax
  \DTLifnumclosedbetween{#1}{#2}{#3}{#4}{#5}%
\else
  \@DTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
\fi
\else
  \@DTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
\fi
}

```

#### Starred version

```

\newcommand*\@sDTLifclosedbetween}[5]{%
  \dtl@testbothnumerical{#2}{#3}%
  \if@dtl@condition
    \dtl@ifsingle{#1}{%
      \edef\@dtl@tmp{#1}{%
        \def\@dtl@tmp{#1}}%
      \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
    }
    \ifnum\@dtl@datatype>0\relax
      \DTLifnumclosedbetween{#1}{#2}{#3}{#4}{#5}%
    \else
      \@sDTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
    \fi
  \else
    \@sDTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
  \fi
}

```

ifnumopenbetween

```
\DTLifnumopenbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}
```

Determines if  $\langle min \rangle < \langle num \rangle < \langle max \rangle$ .

```

\newcommand*\DTLifnumopenbetween}[5]{%
  \DTLconverttodecimal{#1}{\@dtl@numi}%
  \DTLconverttodecimal{#2}{\@dtl@numii}%
  \DTLconverttodecimal{#3}{\@dtl@numiii}%
  \DTLifFPopenbetween{\@dtl@numi}{\@dtl@numii}{\@dtl@numiii}{#4}{#5}%
}

```

stringopenbetween

```
\DTLifstringopenbetween{<string>}{<min>}{<max>}{<true part>}{<false part>}
```

String comparison (starred version ignores case)

```

\newcommand*\DTLifstringopenbetween}{%
  \@ifstar\@sDTLifstringopenbetween\@DTLifstringopenbetween
}

```

Unstarred version:

```
\newcommand*{\@DTLifstringopenbetween}[5]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \let\@dtl@dovalue\relax
  \ifnum\@dtl@tmpcount>0\relax
  \else
    \def\@dtl@dovalue{#5}%
  \fi
  \ifx\@dtl@dovalue\relax
    \protected@edef\@dtl@tmpcmp{%
      \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
    \@dtl@tmpcmp
    \ifnum\@dtl@tmpcount<0\relax
      \def\@dtl@dovalue{#4}%
    \else
      \def\@dtl@dovalue{#5}%
    \fi
  \fi
  \@dtl@dovalue
}
```

Starred version

```
\newcommand*{\@sDTLifstringopenbetween}[5]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \let\@dtl@dovalue\relax
  \ifnum\@dtl@tmpcount>0\relax
  \else
    \def\@dtl@dovalue{#5}%
  \fi
  \ifx\@dtl@dovalue\relax
    \protected@edef\@dtl@tmpcmp{%
      \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
    \@dtl@tmpcmp
    \ifnum\@dtl@tmpcount<0\relax
      \def\@dtl@dovalue{#4}%
    \else
      \def\@dtl@dovalue{#5}%
    \fi
  \fi
  \@dtl@dovalue
}
```

DTLifopenbetween

<code>\DTLifopenbetween{&lt;arg&gt;}{&lt;min&gt;}{&lt;max&gt;}{&lt;true part&gt;}{&lt;false part&gt;}</code>
--

Does `\DTLifnumopenbetween` if  $\langle arg \rangle$ ,  $\langle min \rangle$  and  $\langle max \rangle$  are numerical, otherwise do `\DTLifstringopenbetween` or `\DTLifstringopenbetween*`.

```
\newcommand*\DTLifopenbetween}{%
  \@ifstar\@sDTLifopenbetween\@DTLifopenbetween
}
```

Unstarred version

```
\newcommand*\@DTLifopenbetween}[5]{%
  \dtl@testbothnumerical{#2}{#3}%
  \if@dtl@condition
    \dtl@ifsingle{#1}{%
      \edef\@dtl@tmp{#1}{%
        \def\@dtl@tmp{#1}}%
      \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
      \ifnum\@dtl@datatype>0\relax
        \DTLifnumopenbetween{#1}{#2}{#3}{#4}{#5}%
      \else
        \@DTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
      \fi
    \else
      \@DTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
    \fi
  }
```

Starred version

```
\newcommand*\@sDTLifopenbetween}[5]{%
  \dtl@testbothnumerical{#2}{#3}%
  \if@dtl@condition
    \dtl@ifsingle{#1}{%
      \edef\@dtl@tmp{#1}{%
        \def\@dtl@tmp{#1}}%
      \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
      \ifnum\@dtl@datatype>0\relax
        \DTLifnumopenbetween{#1}{#2}{#3}{#4}{#5}%
      \else
        \@sDTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
      \fi
    \else
      \@sDTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
    \fi
  }
```

`LifFPopenbetween`

```
\DTLifFPopenbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}
```

Determines if  $\langle min \rangle < \langle num \rangle < \langle max \rangle$  where all arguments are in standard fixed point notation. (Command name maintained for backward compatibility.)

```
\let\DTLifFPopenbetween\dtlifnumopenbetween
```

fFPclosedbetween

```
\DTLifFPclosedbetween{<num>}{<min>}{<max>}{<>true part>}{<>false part>}
```

Determines if  $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$ . (Command name maintained for backward compatibility.)

```
\let\DTLifFPclosedbetween\dtlifnumclosedbetween
```

## 1.6.2 ifthen Conditionals

The following commands provide conditionals `\DTLis...` which can be used in `\ifthenelse`.

`\dtl@testlt` Command to test if first argument is less than second argument. If either argument is a string, a case sensitive string comparison is used instead. This sets `\if@dtl@condition`.

```
\newcommand*\dtl@testlt[2]{%
  \DTLiflt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

`\DTLislt` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLislt[2]{%
  \TE@throw\noexpand\dtl@testlt{#1}{#2}\noexpand\if@dtl@condition
}
```

`\dtl@testiclt` Command to test if first argument is less than second argument. If either argument is a string, a case insensitive string comparison is used instead. This sets `\if@dtl@condition`.

```
\newcommand*\dtl@testiclt[2]{%
  \@sDTLiflt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

`\DTLisilt` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisilt[2]{%
  \TE@throw\noexpand\dtl@testiclt{#1}{#2}\noexpand\if@dtl@condition
}
```

`\dtl@testgt` Command to test if first argument is greater than second argument. This sets `\if@dtl@condition`.

```
\newcommand*\dtl@testgt[2]{%
  \DTLifgt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

`\DTLisgt` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisgt[2]{%
  \TE@throw\noexpand\dtl@testgt{#1}{#2}\noexpand\if@dtl@condition
}
```

`\dtl@testicgt` Command to test if first argument is greater than second argument (ignores case). This sets `\if@dtl@condition`.

```
\newcommand*\dtl@testicgt[2]{%
  \@sDTLifgt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

`\DTLisigt` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisigt[2]{%
  \TE@throw\noexpand\dtl@testicgt{#1}{#2}\noexpand\if@dtl@condition
}

```

`\dtl@testeq` Command to test if first argument is equal to the second argument. This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testeq[2]{%
  \DTLlifeq{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLiseq` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLiseq[2]{%
  \TE@throw\noexpand\dtl@testeq{#1}{#2}\noexpand\if@dtl@condition
}

```

`\dtl@testiceq` Command to test if first number is equal to the second number (ignores case). This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testiceq[2]{%
  \@sDTLlifeq{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLisieq` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisieq[2]{%
  \TE@throw\noexpand\dtl@testiceq{#1}{#2}\noexpand\if@dtl@condition
}

```

`\DTLisSubString` Tests if second argument is contained in first argument.

```

\newcommand*\DTLisSubString[2]{%
  \TE@throw\noexpand\dtl@testifsubstring{#1}{#2}%
  \noexpand\if@dtl@condition
}

```

`\DTLisPrefix` Tests if first argument starts with second argument.

```

\newcommand*\DTLisPrefix[2]{%
  \TE@throw\noexpand\dtl@teststartswith{#1}{#2}%
  \noexpand\if@dtl@condition
}

```

`\DTLisinlist` Tests if first argument starts with second argument.

```

\newcommand*\DTLisinlist[2]{%
  \TE@throw\noexpand\dtl@testinlist{#1}{#2}%
  \noexpand\if@dtl@condition
}

```

`\dtl@testinlist`

```

\newcommand*\dtl@testinlist[2]{%
  \DTLifinlist{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

umclosedbetween Command to test if first number lies between second and third numbers. (End points included, all arguments are fixed point numbers in standard format.) This sets `\if@dtl@condition`.

```
\newcommand*\@dtl@testnumclosedbetween}[3]{%
  \DTLifnumclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

Provide conditional command for use in `\ifthenelse`

umclosedbetween

```
\newcommand*\DTLisnumclosedbetween}[3]{%
  \TE@throw\noexpand\@dtl@testnumclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
```

tnumopenbetween Command to test if first number lies between second and third numbers. (End points excluded, all arguments are fixed point numbers in standard format.) This sets `\if@dtl@condition`.

```
\newcommand*\@dtl@testnumopenbetween}[3]{%
  \DTLifnumopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

snumopenbetween Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisnumopenbetween}[3]{%
  \TE@throw\noexpand\@dtl@testnumopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
```

stclosedbetween Command to test if first value lies between second and third values. (End points included, case sensitive.) This sets `\if@dtl@condition`.

```
\newcommand*\@dtl@testclosedbetween}[3]{%
  \DTLifclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

isclosedbetween Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisclosedbetween}[3]{%
  \TE@throw\noexpand\@dtl@testclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
```

sticlosedbetween Command to test if first value lies between second and third values. (End points included, case ignored.) This sets `\if@dtl@condition`.

```
\newcommand*\@dtl@testiclosedbetween}[3]{%
  \@sDTLifclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

`isiclosedbetween` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisiclosedbetween}[3]{%
  \TE@throw\noexpand\dtl@testiclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}

```

`testopenbetween` Command to test if first value lies between second and third values. (End points excluded, case sensitive.) This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testopenbetween}[3]{%
  \DTLifopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`DTLisopenbetween` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisopenbetween}[3]{%
  \TE@throw\noexpand\dtl@testopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}

```

`testiopenbetween` Command to test if first value lies between second and third values. (End points excluded, case ignored.) This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testiopenbetween}[3]{%
  \sDTLifopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`DTLisiopenbetween` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisiopenbetween}[3]{%
  \TE@throw\noexpand\dtl@testiopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}

```

`FPclosedbetween` Keep old command name for backwards compatibility:

```

\let\DTLisFPclosedbetween\DTLisnumclosedbetween

```

`testFPopenbetween` Command to test if first number lies between second and third numbers. (End points excluded, all arguments are fixed point numbers in standard format.) This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testFPopenbetween}[3]{%
  \DTLifFPopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`isFPopenbetween` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisFPopenbetween}[3]{%
  \TE@throw\noexpand\dtl@testFPopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}

```



`\dtl@testFPislt` Command to test if first number is less than second number where both numbers are in standard format. This sets `\if@dtl@condition`.

```
\newcommand*\dtl@testFPislt}[2]{%
  \dtlifnumlt{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \@dtl@conditionfalse
  }%
}
```

`\DTLisFPlt` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisFPlt}[2]{%
  \TE@throw\noexpand\dtl@testFPislt{#1}{#2}%
  \noexpand\if@dtl@condition
}
```

`\dtl@testFPisgt` Command to test if first number is greater than second number where both numbers are in standard format. This sets `\if@dtl@condition`.

```
\newcommand*\dtl@testFPisgt}[2]{%
  \dtlifnumgt{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \@dtl@conditionfalse
  }%
}
```

`\DTLisFPgt` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisFPgt}[2]{%
  \TE@throw\noexpand\dtl@testFPisgt{#1}{#2}%
  \noexpand\if@dtl@condition
}
```

`\dtl@testFPiseq` Command to test if two numbers are equal, where both numbers are in standard decimal format

```
\newcommand*\dtl@testFPiseq}[2]{%
  \dtlifnumeq{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \@dtl@conditionfalse
  }%
}
```

`\DTLisFPeq` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLisFPeq}[2]{%
  \TE@throw\noexpand\dtl@testFPiseq{#1}{#2}%
  \noexpand\if@dtl@condition
}

```

`\dtl@testFPislteq` Command to test if first number is less than or equal to second number where both numbers are in standard format. This sets `\if@dtl@condition`.

```

\newcommand*{\dtl@testFPislteq}[2]{%
  \dtlifnumlt{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \@dtl@conditionfalse
  }%
  \if@dtl@condition
  \else
    \dtl@testFPiseq{#1}{#2}%
  \fi
}

```

`\DTLisFPlteq` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLisFPlteq}[2]{%
  \TE@throw\noexpand\dtl@testFPislteq{#1}{#2}%
  \noexpand\if@dtl@condition
}

```

`\dtl@testFPisgteq` Command to test if first number is greater than or equal to second number where both numbers are in standard format. This sets `\if@dtl@condition`.

```

\newcommand*{\dtl@testFPisgteq}[2]{%
  \dtlifnumgt{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \@dtl@conditionfalse
  }%
  \if@dtl@condition
  \else
    \dtl@testFPiseq{#1}{#2}%
  \fi
}

```

`\DTLisFPgteq` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLisFPgteq}[2]{%
  \TE@throw\noexpand\dtl@testFPisgteq{#1}{#2}%
  \noexpand\if@dtl@condition}

```

`\dtl@teststring` Command to test if argument is a string. This sets `\if@dtl@condition`  
`\newcommand*{\dtl@teststring}[1]{%`  
`\DTLifstring{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}`

`\DTLisstring` Provide conditional command for use in `\ifthenelse`  
`\newcommand*{\DTLisstring}[1]{%`  
`\TE@throw\noexpand\dtl@teststring{#1}\noexpand\if@dtl@condition}`

`\dtl@testnumerical` Command to test if argument is a numerical. This sets `\if@dtl@condition`  
`\newcommand*{\dtl@testnumerical}[1]{%`  
`\DTLifnumerical{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%`  
`}`

`\DTLisnumerical` Provide conditional command for use in `\ifthenelse`  
`\newcommand*{\DTLisnumerical}[1]{%`  
`\TE@throw\noexpand\dtl@testnumerical{#1}\noexpand\if@dtl@condition}`

`\dtl@testint` Command to test if argument is an integer. This sets `\if@dtl@condition`  
`\newcommand*{\dtl@testint}[1]{%`  
`\DTLifint{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}`

`\DTLisint` Provide conditional command for use in `\ifthenelse`  
`\newcommand*{\DTLisint}[1]{%`  
`\TE@throw\noexpand\dtl@testint{#1}\noexpand\if@dtl@condition}`

`\dtl@testreal` Command to test if argument is a real. This sets `\if@dtl@condition`  
`\newcommand*{\dtl@testreal}[1]{%`  
`\DTLifreal{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}`

`\DTLisreal` Provide conditional command for use in `\ifthenelse`  
`\newcommand*{\DTLisreal}[1]{%`  
`\TE@throw\noexpand\dtl@testreal{#1}\noexpand\if@dtl@condition}`

`\dtl@testcurrency` Command to test if argument is a currency. This sets `\if@dtl@condition`  
`\newcommand*{\dtl@testcurrency}[1]{%`  
`\DTLifcurrency{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}`

`\DTLiscurrency` Provide conditional command for use in `\ifthenelse`  
`\newcommand*{\DTLiscurrency}[1]{%`  
`\TE@throw\noexpand\dtl@testcurrency{#1}\noexpand\if@dtl@condition}`

`\dtl@testcurrencyunit` Command to test if argument is a currency with given unit. This sets `\if@dtl@condition`  
`\newcommand*{\dtl@testcurrencyunit}[2]{%`  
`\DTLifcurrencyunit{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}`

`\DTLiscurrencyunit` Provide conditional command for use in `\ifthenelse`  
`\newcommand*{\DTLiscurrencyunit}[2]{%`  
`\TE@throw\noexpand\dtl@testcurrencyunit{#1}{#2}%`  
`\noexpand\if@dtl@condition`  
`}`

## 1.7 Loops

`\dtlbreak` Break out of loop at the end of current iteration.

```
\newcommand*{\dtlbreak}{%
  \PackageError{datatool}{Can't break out of anything}{}%
}
```

`\dtlforint` `\dtlforint<ct>=<start>\to<end>\step <inc>\do{<body>}`

`<ct>` is a count register, `<start>`, `<end>` and `<inc>` are integers. Group if nested or use `\dtlforint`. An infinite loop may result if `<inc>=0` and `<start> ≤ <end>` and `\dtlbreak` isn't used.

```
\long\def\dtlforint#1=#2\to#3\step#4\do#5{%
```

Make a copy of old version of break function

```
\let\@dtl@orgbreak\dtlbreak
\def\@dtl@endloophook{}
```

Setup break function for the loop (sets `<ct>` to `<end>` at the end of the current iteration).

```
\def\dtlbreak{\def\@dtl@endloophook{#1=#3}}%
```

Initialise `<ct>`

```
#1=#2\relax
```

Check if the steps are positive or negative.

```
\ifnum#4<0\relax
```

Counting down

```
\whiledo{\(#1>#3)\TE@or\(#1=#3)}%
{%
  #5%
  \@dtl@endloophook
  \advance#1 by #4\relax
}%
\else
```

Counting up

```
\whiledo{\(#1<#3)\TE@or\(#1=#3)}%
{%
  #5%
  \@dtl@endloophook
  \advance#1 by #4\relax
}%
\fi
```

Restore break function.

```
\let\dtlbreak\@dtl@orgbreak
}
```

l@foreach@level Count register to keep track of global nested loops.

```
\newcount\@dtl@foreach@level
```

```
\dtl@forint \dtl@forint<ct>=<start>\to<end>\step <inc>\do{<body>}
```

*<ct>* is a count register, *<start>*, *<end>* and *<inc>* are integers. An infinite loop may result if *<inc>*=0 and *<start>* ≤ *<end>* and `\dtlbreak` isn't used.

```
\long\def\dtl@forint#1=#2\to#3\step#4\do#5{%
```

Initialise

```
\global#1=#2\relax
```

Increment level counter to allow for nested loops

```
\global\advance\@dtl@foreach@level by 1\relax
```

Set up end loop hook

```
\expandafter\global\expandafter  
\let\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname  
\relax
```

Set up the break function: Copy current definition

```
\expandafter\global\expandafter  
\let\csname @dtl@break@\the\@dtl@foreach@level\endcsname  
\dtlbreak
```

Set up definition for this level (sets *<ct>* to *<end>* at the end of the current iteration).

```
\gdef\dtlbreak{\expandafter  
\gdef\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname{%  
#1=#3}}%
```

check the direction

```
\ifnum#4<0\relax
```

Counting down

```
\whiledo{\(#1>#3)\TE@or\(#1=#3)}%  
{%  
#5%  
\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname  
\global\advance#1 by #4\relax  
}%  
\else
```

Counting up (or 0 increments)

```
\whiledo{\(#1<#3)\TE@or\(#1=#3)}%  
{%  
#5%  
\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname  
\global\advance#1 by #4\relax  
}%  
\fi
```

Restore break function

```
\expandafter\global\expandafter\let\expandafter\dtlbreak
\csname @dtl@break@\the\@dtl@foreach@level\endcsname
```

Decrement level counter

```
\global\advance\@dtl@foreach@level by -1\relax
}
```

`dtlenvgforint` Environment form (contents are gathered, so verbatim can't be used):

```
\newenvironment{dtlenvgforint}[1]%
{
\def\@dtlenvgforint@arg{#1}%
\long@collect@body\@do@dtlenvgforint
}%
{}
\newcommand{\@do@dtlenvgforint}[1]{%
\expandafter\dtlgforint\@dtlenvgforint@arg\do{#1}%
}
```

## 2 datatool-fp.sty

Definitions of fixed-point commands that use the fp package.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool-fp}[2018/12/07 v2.31 (NLCT)]
```

Required packages:

```
\RequirePackage{xkeyval}
\RequirePackage{fp}
\RequirePackage{datatool-base}
```

`verbose` Switch fp messages on or off

```
\define@choicekey{datatool-fp}{verbose}[\val\nr]{true,false}[true]{%
  \ifcase\nr\relax
    \FPmessagestrue
  \or
    \FPmessagesfalse
  \fi
}
\let\ifFPmessages\ifdtlverbose
```

Process package options:

```
\ProcessOptionsX
```

Define commands that are needed before loading datatool-base:

```
\providecommand*\@dtl@mathprocessor}{fp}
```

```
\dtlifnumeq \dtlifnumeq{<num1>}{<num2>}{<true part>}{<false part>}
```

Does *<true part>* if  $\langle num1 \rangle = \langle num2 \rangle$ , otherwise does *<false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\newcommand*\dtlifnumeq[4]{%
  \FPifeq{#1}{#2}%
  #3%
  \else
  #4%
  \fi
}
```

If `verbose` option set, switch on `verbose` for `datatool-base` as well:

```
\let\ifdtlverbose\ifFPmessages
```

## 2.1 Comparison Commands

`\dtlifnumlt` `\dtlifnumlt{<num1>}{<num2>}{<true part>}{<>false part>}`

Does *<true part>* if  $\langle num1 \rangle < \langle num2 \rangle$ , otherwise does *<>false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\newcommand*{\dtlifnumlt}[4]{%
  \FPiflt{#1}{#2}%
  #3%
  \else
  #4%
  \fi
}
```

`\dtlifnumgt` `\dtlifnumgt{<num1>}{<num2>}{<true part>}{<>false part>}`

Does *<true part>* if  $\langle num1 \rangle > \langle num2 \rangle$ , otherwise does *<>false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\newcommand*{\dtlifnumgt}[4]{%
  \FPifgt{#1}{#2}%
  #3%
  \else
  #4%
  \fi
}
```

`ifnumopenbetween` `\dtlifnumopenbetween{<num>}{<min>}{<max>}{<true part>}{<>false part>}`

Determines if  $\langle min \rangle < \langle num \rangle < \langle max \rangle$  where all arguments are in standard fixed point notation.

```
\newcommand*{\dtlifnumopenbetween}[5]{%
  \let\@dtl@dovalue\relax
  \dtlifnumgt{#1}{#2}%
  {}%
  {%
    \def\@dtl@dovalue{#5}%
  }%
  \dtlifnumlt{#1}{#3}%
  {%
    \ifx\@dtl@dovalue\relax
```



```

        \def\@dtl@dovalue{#4}%
    \fi
}%
{%
    \def\@dtl@dovalue{#5}%
}%
\@dtl@dovalue
}

```

numclosedbetween `\dtlifnumclosedbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}`

Determines if  $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$  where all arguments are in standard fixed point notation.

```

\newcommand*\dtlifnumclosedbetween}[5]{%
    \let\@dtl@dovalue\relax
    \dtlifnumgt{#1}{#2}%
    {%
    {%
        \dtlifnumeq{#1}{#2}%
        {%
            \def\@dtl@dovalue{#4}%
        }%
        {%
            \def\@dtl@dovalue{#5}%
        }%
    }%
    }%
    \dtlifnumlt{#1}{#3}%
    {%
        \ifx\@dtl@dovalue\relax
            \def\@dtl@dovalue{#4}%
        \fi
    }%
    {%
        \dtlifnumeq{#1}{#3}%
        {%
            \def\@dtl@dovalue{#4}%
        }%
        {%
            \def\@dtl@dovalue{#5}%
        }%
    }%
    }%
    \@dtl@dovalue
}

```

## 2.2 Functions

`\dtladd` Adds two numbers using fp.

```
\newcommand*\dtladd}[3]{%
  \FPadd{#1}{#2}{#3}%
}
```

`\dtlsub` Subtracts two numbers using fp.

```
\newcommand*\dtlsub}[3]{%
  \FPsub{#1}{#2}{#3}%
}
```

`\dtlmul` Multiplies two numbers using fp.

```
\newcommand*\dtlmul}[3]{%
  \FPmul{#1}{#2}{#3}%
}
```

`\dtldiv` Divides two numbers using fp.

```
\newcommand*\dtldiv}[3]{%
  \FPdiv{#1}{#2}{#3}%
}
```

`\dtlroot` Square root using fp.

```
\newcommand*\dtlroot}[2]{%
  \FProot{#1}{#2}%
}
```

`\dtlround` Rounds using fp.

```
\newcommand*\dtlround}[3]{%
  \FPround{#1}{#2}{#3}%
}
```

`\dtltrunc` Truncates using fp. (Third argument is the number of digits.)

```
\newcommand*\dtltrunc}[3]{%
  \FPtrunc{#1}{#2}{#3}%
}
```

`\dtlclip`

```
\newcommand*\dtlclip}[2]{%
  \FPclip{#1}{#2}%
}
```

`\dtlmin` Minimum of two numbers using fp.

```
\newcommand*\dtlmin}[3]{%
  \FPmin{#1}{#2}{#3}%
}
```

`\dtlmax` Maximum of two numbers using fp.

```
\newcommand*\dtlmax}[3]{%  
  \FPmax{#1}{#2}{#3}%  
}
```

`\dtlabs` Absolute value using fp.

```
\newcommand*\dtlabs}[2]{%  
  \FPabs{#1}{#2}%  
}
```

`\dtlneg` Negative of a value using fp.

```
\newcommand*\dtlneg}[2]{%  
  \FPneg{#1}{#2}%  
}
```

## 3 datatool-pgfmath.sty

Definitions of fixed-point commands that use the pgfmath package.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool-pgfmath}[2018/12/07 v2.31 (NLCT)]
```

Required packages:

```
\RequirePackage{xkeyval}
\RequirePackage{pgfrcs,pgfkeys,pgfmath}
```

Process package options:

```
\ProcessOptionsX
```

Define commands that are needed before loading datatool-base:

```
\providecommand*{\@dtl@mathprocessor}{pgfmath}
```

```
\dtlifnumeq \dtlifnumeq{<num1>}{<num2>}{<true part>}{<>false part>}
```

Does *<true part>* if  $\langle num1 \rangle = \langle num2 \rangle$ , otherwise does *<>false part>*. The numbers must use a full stop as the decimal character and no number group separator. The `\number0` part allows an empty argument to be treated as zero. (`\number` required to prevent a zero prefix indicating an octal number.)

```
\newcommand*{\dtlifnumeq}[4]{%
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \pgfmathifthenelse{\number0#1==\number0#2}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmathresult
}
```

Load base package:

```
\RequirePackage{datatool-base}
```

### 3.1 Comparison Commands

```
\dtlifnumlt \dtlifnumlt{<num1>}{<num2>}{<true part>}{<>false part>}
```

Does  $\langle true\ part\rangle$  if  $\langle num1\rangle < \langle num2\rangle$ , otherwise does  $\langle false\ part\rangle$ . The numbers must use a full stop as the decimal character and no number group separator.

```
\newcommand*\dtlifnumlt}[4]{%
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \pgfmathifthenelse{\number0#1 < \number0#2}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmathresult
}
```

`\dtlifnumgt` `\dtlifnumgt{\langle num1\rangle}{\langle num2\rangle}{\langle true\ part\rangle}{\langle false\ part\rangle}`

Does  $\langle true\ part\rangle$  if  $\langle num1\rangle > \langle num2\rangle$ , otherwise does  $\langle false\ part\rangle$ . The numbers must use a full stop as the decimal character and no number group separator.

```
\newcommand*\dtlifnumgt}[4]{%
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \pgfmathifthenelse{\number0#1 > \number0#2}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmathresult
}
```

`ifnumopenbetween` `\dtlifnumopenbetween{\langle num\rangle}{\langle min\rangle}{\langle max\rangle}{\langle true\ part\rangle}{\langle false\ part\rangle}`

Determines if  $\langle min\rangle < \langle num\rangle < \langle max\rangle$  where all numerical arguments are in standard fixed point notation.

```
\newcommand*\dtlifnumopenbetween}[5]{%
  \def\@dtl@truepart{#4}%
  \def\@dtl@falsepart{#5}%
  \pgfmathifthenelse
    {(\number0#2 < \number0#1) && (\number0#1 < \number0#3)}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmathresult
}
```

`numclosedbetween` `\dtlifnumclosedbetween{\langle num\rangle}{\langle min\rangle}{\langle max\rangle}{\langle true\ part\rangle}{\langle false\ part\rangle}`

Determines if  $\langle min\rangle \leq \langle num\rangle \leq \langle max\rangle$  where all numerical arguments are in standard fixed point notation.

```
\newcommand*\dtlifnumclosedbetween}[5]{%
```

```

\def\@dtl@truepart{#4}%
\def\@dtl@falsepart{#5}%
\pgfmathifthenelse
{(\number0#2 <= \number0#1) && (\number0#1 <= \number0#3)}
{"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
\pgfmathresult
}

```

## 3.2 Functions

`\dtladd` Adds two numbers using PGF math engine.

```

\newcommand*\dtladd}[3]{%
\pgfmathadd{#2}{#3}%
\let#1\pgfmathresult
}

```

`\dtlsub` Subtracts two numbers using PGF math engine.

```

\newcommand*\dtlsub}[3]{%
\pgfmathsubtract{#2}{#3}%
\let#1\pgfmathresult
}

```

`\dtlmul` Multiplies two numbers using PGF math engine.

```

\newcommand*\dtlmul}[3]{%
\pgfmathmultiply{#2}{#3}%
\let#1\pgfmathresult
}

```

`\dtldiv` Divides two numbers using PGF math engine.

```

\newcommand*\dtldiv}[3]{%
\pgfmathdivide{#2}{#3}%
\let#1\pgfmathresult
}

```

`\dtlroot` Square root using PGF math engine.

```

\newcommand*\dtlroot}[2]{%
\pgfmathsqrt{#2}%
\let#1\pgfmathresult
}

```

`\dtlround` Rounds using PGF math engine.

```

\newcommand*\dtlround}[3]{%
\ifnum#3=0\relax
\pgfmathparse{int(round(#2))}%
\let#1\pgfmathresult
\else
\pgfmathparse{int(10^#3)}%
\let\dtl@tmpshift\pgfmathresult

```

Need to be careful not to trigger the dimension too large error, so this is a bit convoluted.

```
\pgfmathparse{int(floor(#2))}%
\let\dtl@int@round\pgfmathresult
\pgfmathparse{int(round((#2-\dtl@int@round) * \dtl@tmpshift))}%
```

This bit is awkward because simply dividing by multiples of 10 in pgfmath can cause rounding errors, so need to employ another method.

```
\@dtl@tmpcount=0\relax
\expandafter\@dtl@countdigits\pgfmathresult.\relax
\advance\@dtl@tmpcount by -#3\relax
\def\@dtl@intpart{}%
\def\@dtl@fracpart{}%
\expandafter\@dtl@gatherintfrac\pgfmathresult\relax
\edef\@dtl@intpart{\number\numexpr\dtl@int@round
+\number0\@dtl@intpart}%
\edef#1{\@dtl@intpart.\@dtl@fracpart}%
\fi
}
```

`\dtl@gatherintfrac`

```
\newcommand*\@dtl@gatherintfrac}[1]{%
\ifx\relax#1\relax
\else
\advance\@dtl@tmpcount by -1\relax
\ifnum\@dtl@tmpcount<0\relax
\edef\@dtl@fracpart{\@dtl@fracpart#1}%
\else
\edef\@dtl@intpart{\@dtl@intpart#1}%
\fi
\expandafter\@dtl@gatherintfrac
\fi
}
```

`\dtltrunc` Truncates using PGF math engine. (Third argument is the number of digits.) This suffers from the same problems as `\dtlround`. Can cause dimension too large error or rounding errors.

```
\newcommand*\dtltrunc}[3]{%
\ifnum#3=0\relax
\pgfmathparse{int(floor(#2))}%
\let#1\pgfmathresult
\else
\pgfmathparse{int(10^#3)}%
\let\dtl@tmpshift\pgfmathresult
```

Need to be careful not to trigger the dimension too large error, so this is a bit convoluted.

```
\pgfmathparse{int(floor(#2))}%
\let\dtl@int@trunc\pgfmathresult
\pgfmathparse{int(floor((#2-\dtl@int@trunc) * \dtl@tmpshift))}%
```

This bit is awkward because simply dividing by multiples of 10 in pgfmath can cause rounding errors, so need to employ another method.

```

\@dtl@tmpcount=0\relax
\expandafter\@dtl@countdigits\pgfmathresult.\relax
\advance\@dtl@tmpcount by -#3\relax
\def\@dtl@intpart{}%
\def\@dtl@fracpart{}%
\expandafter\@dtl@gatherintfrac\pgfmathresult\relax
\edef\@dtl@intpart{\number\numexpr\@dtl@int@trunc
+\number0\@dtl@intpart}%
\edef#1{\@dtl@intpart.\@dtl@fracpart}%
\fi
}

```

`\dtlclip` There isn't a clip in pgfmath as it seems to automatically clip.

```

\newcommand*\dtlclip[2]{%
\edef#1{#2}%
}

```

`\dtlmin` Minimum of two numbers using PGF math engine.

```

\newcommand*\dtlmin[3]{%
\pgfmathmin{#2}{#3}%
\let#1\pgfmathresult
}

```

`\dtlmax` Maximum of two numbers using PGF math engine.

```

\newcommand*\dtlmax[3]{%
\pgfmathmax{#2}{#3}%
\let#1\pgfmathresult
}

```

`\dtlabs` Absolute value using PGF math engine.

```

\newcommand*\dtlabs[2]{%
\pgfmathabs{#2}%
\let#1\pgfmathresult
}

```

`\dtlneg` Negative of a value using PGF math engine.

```

\newcommand*\dtlneg[2]{%
\pgfmathmul{-1}{#2}%
\let#1\pgfmathresult
}

```



## 4 datatool.sty

### 4.1 Package Declaration

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool}[2018/12/07 v2.31 (NLCT)]
```

Load required packages:

```
\RequirePackage{xkeyval}
\RequirePackage{ifthen}
\RequirePackage{xfor}
\RequirePackage{substr}
\RequirePackage{etoolbox}
```

### 4.2 Package Options

`\@dtl@separator` The data separator character (comma by default) is stored in `\@dtl@separator`. This is the separator used in external data files, not in the  $\LaTeX$  code, which always uses a comma separator.

```
\newcommand*{\@dtl@separator}{,}
```

`\DTLsetseparator` `\DTLsetseparator{<char>}`

The sets `\@dtl@separator`, and constructs the relevant macros that require this character to be hardcoded into their definition.

```
\newcommand*{\DTLsetseparator}[1]{%
  \renewcommand*{\@dtl@separator}{#1}%
  \@dtl@construct@lopoffs
}
```

`\DTLsettabseparator` `\DTLsettabseparator` makes it easier to set a tab separator.

```
\gdef\DTLsettabseparator{%
  \catcode'\^^I12
  \DTLsetseparator{^^I}%
}
```

`\DTLmaketabspace`

```
\gdef\DTLmaketabspace{%
  \catcode'\^^I10\relax
}
\endgroup
```

`\@dtl@delimiter` The data delimiter character (double quote by default) is stored in `\@dtl@delimiter`. This is used in external data files, not in the  $\TeX$  code.

```
\begingroup
\catcode'\ "12\relax
\gdef\@dtl@delimiter{"}
\endgroup
```

`\DTLsetdelimiter` `\DTLsetdelimiter{<char>}`

This sets the delimiter.

```
\newcommand*\DTLsetdelimiter[1]{%
\renewcommand*\@dtl@delimiter}{#1}%
\@dtl@construct@lopoffs
}
```

`construct@lopoff` `\@dtl@construct@lopoff<separator char><delimiter char>`

This defines

```
\@dtl@lopoff<first element><sep><rest of list>\to<cmd1><cmd2>
```

for the current separator and delimiter.

```
\edef\@dtl@construct@lopoff#1#2{%
\noexpand\long
\noexpand\def\noexpand\@dtl@lopoff#1##1##2\noexpand\to##3##4{%
\noexpand\ifx#2##1\noexpand\relax
\noexpand\ifstrempy{##1}%
{\noexpand\@dtl@qlopoff#1{##2\noexpand\to##3##4\relax}%
f%
\noexpand\dtl@ifsingle{##1}%
{\noexpand\@dtl@qlopoff#1##1##2\noexpand\to##3##4\relax}%
{\noexpand\@dtl@qlopoff#1{##1}##2\noexpand\to##3##4\relax}%
}%
\noexpand\else
\noexpand\ifstrempy{##1}%
{\noexpand\@dtl@lop@ff#1{##2\noexpand\to##3##4\relax}%
f%
\noexpand\dtl@ifsingle{##1}%
{\noexpand\@dtl@lop@ff#1##1##2\noexpand\to##3##4\relax}%
{\noexpand\@dtl@lop@ff#1{##1}##2\noexpand\to##3##4\relax}%
}%
\noexpand\fi
```

```
}%
}
```

construct@qlopoff

```
\@dtl@construct@qlopoff<separator char><delimiter char>
```

This constructs \@dtl@qlopoff to be used when the entry is surrounded by the current delimiter value.

```
\edef\@dtl@construct@qlopoff#1#2{%
  \noexpand\long
  \noexpand\def\noexpand\@dtl@qlopoff#1#2##1#2#1##2\noexpand\to##3##4{%
    \noexpand\def##4{##1}%
```

Replace any escaped delimiters

```
  \noexpand\DTLsubstituteall{##4}{#2#2}{#2}%
  \noexpand\edef\noexpand\@dtl@dosubs{%
    \noexpand\noexpand\noexpand\DTLsubstituteall{\noexpand\noexpand##4}%
    {\noexpand\expandafter\noexpand\noexpand\noexpand\csname#2\noexpand\endcsname#2}%
    {\noexpand\expandafter\noexpand\noexpand\noexpand\csname#2\noexpand\endcsname}%
  }%
  \noexpand\@dtl@dosubs
  \noexpand\def##3{#1##2}%
}%
}
```

construct@lop@ff

```
\@dtl@construct@lop@ff<separator char>
```

This constructs \@dtl@lop@ff to be used when the entry isn't surrounded by the delimiter.

```
\edef\@dtl@construct@lop@ff#1{%
  \noexpand\long
  \noexpand\def\noexpand\@dtl@lop@ff#1##1#1##2\noexpand\to##3##4{%
    \noexpand\def##4{##1}%
    \noexpand\def##3{#1##2}%
  }%
}
```

construct@lopoffs

```
\@dtl@construct@lopoffs
```

This constructs all the lopoff macros using the given separator and delimiter characters.

```
\newcommand{\@dtl@construct@lopoffs}{%
  \edef\@dtl@chars{\@dtl@separator}\@dtl@delimiter}%
  \expandafter\@dtl@construct@lopoff\@dtl@chars
```

```

\expandafter\@dtl@construct@qlopoff\@dtl@chars
\expandafter\@dtl@construct@lopoff\expandafter{\@dtl@separator}%
}

separator Define separator used in external data files.
\define@key{datatool.sty}{separator}{%
\DTLsetseparator{#1}%
}

delimiter Define delimiter used in external data files.
\define@key{datatool.sty}{delimiter}{%
\DTLsetdelimiter{#1}%
}

verbose
\define@boolkey{datatool.sty}[dtl]{verbose}[true]{}

math Determine whether to use fp or pgfmath for the arithmetic commands. The default is to use
fp.
\define@choicekey{datatool.sty}{math}[\val\nr]{fp,pgfmath}{%
\renewcommand*\@dtl@mathprocessor{#1}%
}
\providecommand*\@dtl@mathprocessor{fp}

dtl@set@options
\newcommand*\@dtl@set@options{}

utf8 Pass to datatool-base
\define@choicekey{datatool.sty}{utf8}{true,false}[true]{%
\renewcommand*\@dtl@set@options{\setbool{\@dtl@utf8}{#1}}%
}

Process package options:
\ProcessOptionsX
Set the defaults:
\@dtl@construct@lopoffs
Load base package:
\RequirePackage{datatool-base}
Set options that depend on datatool-base:
\@dtl@set@options

\DTLpar Many of the commands used by this package are short commands. This means that you can't
use \par in the data. This command needs to be robust so it doesn't get expanded when
written to a file. We also can't just use a synonym for \@@par because it may be used in a
context where \par has a different meaning to \@@par.
\DeclareRobustCommand{\DTLpar}{\par}

```

## 4.3 Defining New Databases

As from v2.0, the internal structure of the database has changed to make it more efficient.<sup>1</sup> The database is now stored in a token register instead of a macro. Each row is represented as:

```
\db@row@elt@w \db@row@id@w <row idx>\db@row@id@end@ <column data> \db@row@id@w
<row idx>\db@row@id@end@ \db@row@elt@end@
```

where *<row idx>* is the row index and *<column data>* is the data for each column in the row.

Each column for a given row is stored as:

```
\db@col@id@w <column idx>\db@col@id@end@ \db@col@elt@w <value>\db@col@elt@end@
\db@col@id@w <column idx>\db@col@id@end@
```

where *<column idx>* is the column index and *<value>* is the entry for the given column and row.

Each row only has an associated index, but columns have a unique identifying key as well as an associated index. Columns also have an associated data type which may be: 0 (column contains strings), 1 (column contains integers), 2 (column contains real numbers), 3 (column contains currency) or *<empty>* (column contains no data). Since the key sometimes has to be expanded, a header is also available in the event that the user wants to use `\DTLdisplaydb` or `\DTLdisplaylongdb` and requires a column header that would cause problems if used as a key. The general column information is stored in a token register where each column has information stored in the form:

```
\db@plist@elt@w \db@col@id@w <index>\db@col@id@end@ \db@key@id@w <key>\db@key@id@end@
\db@type@id@w <type>\db@type@id@end@ \db@header@id@w <type>\db@header@id@end@
\db@col@id@w <index>\db@col@id@end@ \db@plist@elt@end@
```

The column name (*<key>*) is mapped to the column index using `\dtl@ci@<db>@<key>` where *<db>* is the database name.

```
\DTLnewdb \DTLnewdb{<db name>}
```

Initialises a database called *<name>*.

```
\newcommand*{\DTLnewdb}[1]{%
```

Check if there is already a database with this name.

```
\DTLifdbexists{#1}%
{%
  \PackageError{datatool}{Database ‘#1’ already exists}{}%
}%
{%
```

Define new database. Add information message if in verbose mode.

```
\dtl@message{Creating database ‘#1’}%
```

Define token register used to store the contents of the database.

```
\expandafter\newtoks\csname dtldb@#1\endcsname
```

<sup>1</sup>Thanks to Morten Høgholm for the suggestion.

Define token register used to store the column header information.

```
\expandafter\newtoks\csname dtlkeys@#1\endcsname{}}%
```

Define count register used to store the row count.

```
\expandafter\newcount\csname dtlrows@#1\endcsname
```

Define count register used to store the column count.

```
\expandafter\newcount\csname dtlcols@#1\endcsname  
}%  
}
```

```
\DTLcleardb \DTLcleardb{<db name>}
```

Clears the database. (Makes it empty, but still defined.)

```
\newcommand*{\DTLcleardb}[1]{%  
  \DTLifdbexists{#1}%  
  {%  
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do  
    {%  
      \expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined  
    }%  
    \csname dtldb@#1\endcsname{}}%  
    \csname dtlkeys@#1\endcsname{}}%  
    \csname dtlrows@#1\endcsname=0\relax  
    \csname dtlcols@#1\endcsname=0\relax  
  }%  
  {%  
    \PackageError{Can't clear database '#1':  
      database doesn't exist}{-}{-}%  
  }%  
}
```

```
\DTLdeletedb \DTLdeletedb{<db name>}
```

Deletes a database.

```
\newcommand*{\DTLdeletedb}[1]{%  
  \DTLifdbexists{#1}%  
  {%  
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do  
    {%  
      \expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined  
    }%  
    \expandafter\let\csname dtldb@#1\endcsname\undefined  
    \expandafter\let\csname dtlkeys@#1\endcsname\undefined  
  }%  
}
```

```

\expandafter\let\csname dtlrows@#1\endcsname\undefined
\expandafter\let\csname dtlcols@#1\endcsname\undefined
}%
{%
\PackageError{Can't delete database '#1':
database doesn't exist}{-}{-}%
}%
}

```

`\DTLgnewdb` `\DTLgnewdb{<db name>}`

Initialises a database called *<name>*. (Global version.)

```
\newcommand*{\DTLgnewdb}[1]{%
```

Check if there is already a database with this name.

```

\DTLifdbexists{#1}%
{%
\PackageError{datatool}{Database '#1' already exists}{-}%
}%
{%

```

Define new database. Add information message if in verbose mode.

```
\dtl@message{Creating database '#1'}%
```

Define token register used to store the contents of the database.

```
\expandafter\global\expandafter\newtoks\csname dtldb@#1\endcsname
```

Define token register used to store the column header information.

```
\expandafter\global\expandafter\newtoks\csname dtlkeys@#1\endcsname{}
```

Define count register used to store the row count.

```
\expandafter\global\expandafter\newcount\csname dtlrows@#1\endcsname
```

Define count register used to store the column count.

```

\expandafter\global\expandafter\newcount\csname dtlcols@#1\endcsname
}%
}

```

`\DTLgdeletedb` `\DTLgdeletedb{<db name>}`

Deletes a database. (Global version.)

```

\newcommand*{\DTLgdeletedb}[1]{%
\DTLifdbexists{#1}%
{%
\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
{%

```

```

    \expandafter\global\expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined
  }%
  \expandafter\global\expandafter\let\csname dtldb@#1\endcsname\undefined
  \expandafter\global\expandafter\let\csname dtlkeys@#1\endcsname\undefined
  \expandafter\global\expandafter\let\csname dtlrows@#1\endcsname\undefined
  \expandafter\global\expandafter\let\csname dtlcols@#1\endcsname\undefined
}
{
  \PackageError{Can't delete database '#1':
    database doesn't exist}{-}{-}%
}
}
}

```

`\DTLgcleardb` `\DTLgcleardb{<db name>}`

Clears the database. (Global version.)

```

\newcommand*\DTLgcleardb}[1]{%
  \DTLifdbexists{#1}%
  {%
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
    {%
      \expandafter\global\expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined
    }%
    \expandafter\global\csname dtldb@#1\endcsname{-}%
    \expandafter\global\csname dtlkeys@#1\endcsname{-}%
    \expandafter\global\csname dtlrows@#1\endcsname=0\relax
    \expandafter\global\csname dtlcols@#1\endcsname=0\relax
  }%
  {%
    \PackageError{Can't clear database '#1':
      database doesn't exist}{-}{-}%
  }%
}
}

```

`\DTLrowcount` `\DTLrowcount{<db name>}`

The number of rows in the database called <db name>. (Doesn't check if database exists.)

```

\newcommand*\DTLrowcount}[1]{%
  \expandafter\number\csname dtlrows@#1\endcsname
}

```

`\DTLcolumncount` `\DTLcolumncount{<db name>}`



The number of columns in the database called *<db name>*. (Doesn't check if database exists.)

```
\newcommand*\DTLcolumncount}[1]{%
  \expandafter\number\csname dtlcols@#1\endcsname
}
```

`\DTLifdbempty` `\DTLifdbempty{<name>}{<true part>}{<false part>}`

Check if named database is empty (i.e. no rows have been added).

```
\newcommand{\DTLifdbempty}[3]{%
  \DTLifdbexists{#1}%
  {\@DTLifdbempty{#1}{#2}{#3}}%
  {\PackageError{Can't check if database '#1' is empty:
    database doesn't exist}{-}{-}}%
}
```

`\@DTLifdbempty` `\@sDTLifdbempty{<name>}{<true part>}{<false part>}`

Check if named existing database is empty. (No check performed to determine if the database exists.)

```
\newcommand{\@DTLifdbempty}[3]{%
  \expandafter\ifnum\csname dtlrows@#1\endcsname=0\relax
  #2%
  \else
  #3%
  \fi
}
```

`\DTLnewrow` `\DTLnewrow{<db name>}`

Add a new row to named database. The starred version doesn't check for the existence of the database.

```
\newcommand*\DTLnewrow{%
  \@ifstar\@sDTLnewrow\@DTLnewrow
}
```

`\@DTLnewrow` `\@DTLnewrow{<db name>}`

Add a new row to named database. (Checks for the existence of the database.)

```

\newcommand*{\@DTLnewrow}[1]{%
\DTLifdbexists{#1}%
  {\@sDTLnewrow{#1}}%
  {\PackageError{datatool}{Can't add new row to database '#1':
database doesn't exist}{}}%
}

```

`\@sDTLnewrow` `\@DTLnewrow{<db name>}`

Add a new row to named existing database. (No check performed to determine if the database exists.)

```
\newcommand*{\@sDTLnewrow}[1]{%
```

Increment row count.

```
\global\advance\csname dtlrows@#1\endcsname by 1\relax
```

Append an empty row to the database

```

\@dtl@toks@gput@right@cx{dtldb@#1}{%
  \noexpand\db@row@elt@w%
  \noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
  \noexpand\db@row@id@end@%
  \noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
  \noexpand\db@row@id@end@%
  \noexpand\db@row@elt@end@%
}%

```

Display message on terminal and log file if in verbose mode.

```

\dtl@message{New row added to database '#1'}%
}

```

`\dtlcolumnnum` Count register to keep track of column index.

```
\newcount\dtlcolumnnum
```

`\dtlrownum` Count register to keep track of row index.

```
\newcount\dtlrownum
```

`\DTLifhaskey` `\DTLifhaskey{<db name>}<key><true part><false part>`

Checks if the named database *<db name>* has a column with label *<key>*. If column exists, do *<true part>* otherwise do *<false part>*. The starred version doesn't check if the named database exists.

```
\newcommand*{\DTLifhaskey}{\@ifstar\@sDTLifhaskey\DTLifhaskey}
```

```

\@DTLifhaskey Unstarred version of \DTLifhaskey
  \newcommand{\@DTLifhaskey}[4]{%
    \DTLifdbexists{#1}%
    {%
      \@sDTLifhaskey{#1}{#2}{#3}{#4}%
    }%
    {%
      \PackageError{datatool}{Database ‘#1’ doesn’t exist}{-}%
    }%
  }

```

```

\@sDTLifhaskey Starred version of \DTLifhaskey
  \newcommand{\@sDTLifhaskey}[4]{%
    \@ifundefined{dtl@ci@#1@#2}%
    {%
      Key not defined
      #4%
    }%
    {%
      Key defined
      #3%
    }%
  }

```

```

TLgetcolumnindex \DTLgetcolumnindex{<cs>}{<db>}{<key>}

```

Gets index for column with label *<key>* from database *<db>* and stores in *<cs>* which must be a control sequence. Unstarred version checks if database and key exist, unstarred version doesn't perform any checks.

```

\newcommand*{\DTLgetcolumnindex}{%
  \ifstar\@sdtl@getcolumnindex\@dtl@getcolumnindex
}

```

```

@getcolumnindex Unstarred version of \DTLgetcolumnindex
  \newcommand*{\@dtl@getcolumnindex}[3]{%
    Check if database exists.
    \DTLifdbexists{#2}%
    {%
      Database exists. Now check if key exists.
      \@sDTLifhaskey{#2}{#3}%
    }%
  }

```

Key exists so go ahead and get column index.

```
\@sdtl@getcolumnindex{#1}{#2}{#3}%  
}%  
{%
```

Key doesn't exist in named database.

```
\PackageError{datatool}{Database '#2' doesn't contain  
key '#3'}{}%  
}%  
}%  
{%
```

Named database doesn't exist.

```
\PackageError{datatool}{Database '#2' doesn't exist}{}%  
}%  
}
```

@getcolumnindex Starred version of \DTLgetcolumnindex.

```
\newcommand*{\@sdtl@getcolumnindex}[3]{%  
  \expandafter\let\expandafter#1\csname dtl@ci@#2@#3\endcsname  
}
```

\dtlcolumnindex `\dtlcolumnindex{<db>}{<key>}`

Column index corresponding to <key> in database <db>. (No check for existence of database or key.)

```
\newcommand*{\dtlcolumnindex}[2]{%  
  \csname dtl@ci@#1@#2\endcsname  
}
```

Lgetkeyforcolumn `\DTLgetkeyforcolumn{<key cs>}{<db>}{<column index>}`

Gets the key associated with the given column index and stores in <key cs>. Unstarred version doesn't perform checks.

```
\newcommand*{\DTLgetkeyforcolumn}{%  
  \ifstar\@sdtlgetkeyforcolumn\@dtlgetkeyforcolumn}
```

getkeyforcolumn

```
\newcommand*{\@dtlgetkeyforcolumn}[3]{%  
  \DTLifdbexists{#2}%  
  {%
```

Check if index is in range.

```

\ifnum#3<1\relax
  \PackageError{datatool}{Invalid column index \number#3}{%
    Column indices start at 1}%
\else
  \expandafter\ifnum\csname dtlcols@#2\endcsname<#3\relax
    \PackageError{datatool}{Index \number#3\space out of
      range for database ‘#2’}{Database ‘#2’ only has
        \expandafter\number\csname dtlcols@#2\endcsname\space
          columns}%
  \else
    \@sdtlgetkeyforcolumn{#1}{#2}{#3}%
  \fi
\fi
}%
{%
\PackageError{datatool}{Database ‘#2’ doesn’t exists}{}%
}%
}

```

getkeyforcolumn

```
\@sdtlgetkeyforcolumn{<key cs>}{<db>}{<column index>}
```

Gets the key associated with the given column index and stores in <key cs>

```

\newcommand*{\@sdtlgetkeyforcolumn}[3]{%
  \edef\@dtl@dogetkeyforcolumn{\noexpand\@dtl@getkeyforcolumn
    {\noexpand#1}{#2}{\number#3}}%
  \@dtl@dogetkeyforcolumn
}

```

getkeyforcolumn

Column index must be fully expanded before use.

```

\newcommand*{\@dtl@getkeyforcolumn}[3]{%
  \def\@dtl@get@keyforcolumn##1% before stuff
    \db@plist@elt@w% start of block
    \db@col@id@w #3\db@col@id@end@% index
    \db@key@id@w ##2\db@key@id@end@% key
    \db@type@id@w ##3\db@type@id@end@% data type
    \db@header@id@w ##4\db@header@id@end@% header
    \db@col@id@w #3\db@col@id@end@% index
    \db@plist@elt@end@% end of block
    ##5\q@nil{\def#1{##2}}%
  \edef\@dtl@tmp{\expandafter\the\csname dtlkeys@#2\endcsname}%
  \expandafter\@dtl@get@keyforcolumn\@dtl@tmp
    \db@plist@elt@w% start of block
    \db@col@id@w #3\db@col@id@end@ %index
    \db@key@id@w \@nil\db@key@id@end@% key
    \db@type@id@w \db@type@id@end@% data type
}

```

```

        \db@header@id@w \db@header@id@end@% header
        \db@col@id@w #3\db@col@id@end@% index
        \db@plist@elt@end@% end of block
        \q@nil
    }

```

Define some commands to indicate the various data types a database may contain.

```

\DTLunsettype  Unknown data type. (All entries in the column are blank so the type can't be determined.)
                \def\DTLunsettype{}

\DTLstringtype Data type representing strings.
                \def\DTLstringtype{0}

\DTLinttype    Data type representing integers.
                \def\DTLinttype{1}

\DTLrealtype   Data type representing real numbers.
                \def\DTLrealtype{2}

DTLcurrencytype Data type representing currency.
                \def\DTLcurrencytype{3}

```

```

\DTLgetdatatype \DTLgetdatatype{<cs>}{<db>}{<key>}

```

Gets data type associated with column labelled *<key>* in database *<db>* and stores in *<cs>*. Type may be: *<empty>* (unset), 0 (string), 1 (int), 2 (real), 3 (currency). Unstarred version checks if the database and key exist, starred version doesn't.

```

\newcommand*{\DTLgetdatatype}{%
  \ifstar\@sdtlgetdatatype\@dtlgetdatatype
}

```

```

@dtlgetdatatype Unstarred version of \DTLgetdatatype.
                \newcommand*\@dtlgetdatatype}[3]{%

```

Check if database exists.

```

\DTLifdbexists{#2}%
{%

```

Check if key exists in this database.

```

\@sDTLifhaskey{#2}{#3}%
{%

```

Get data type for this database and key.

```

\@sdtlgetdatatype{#1}{#2}{#3}%
}%
{%

```

Key doesn't exist in this database.

```
\PackageError{datatool}{Key '#3' undefined in database '#2'}{-}%  
}%  
}%  
{%
```

Database doesn't exist.

```
\PackageError{datatool}{Database '#2' doesn't exist}{-}%  
}%  
}
```

sdtlgetdatatype Starred version of \DTLgetdatatype. This ensures that the key is fully expanded before begin passed to \@dtl@getdatatype.

```
\newcommand*{\@sdtlgetdatatype}[3]{%  
  \edef\@dtl@dogetdata{\noexpand\@dtl@getdatatype{\noexpand#1}%  
    {\expandafter\the\csname dtlkeys@#2\endcsname}%  
    {\dtlcolumnindex{#2}{#3}}}%  
  \@dtl@dogetdata  
}
```

\@dtl@getdatatype `\@dtl@getdatatype{<cs>}{<data specs>}{<column index>}`

Column index must be expanded.

```
\newcommand*{\@dtl@getdatatype}[3]{%  
  \def\@dtl@get@keydata##1% stuff before  
    \db@plist@elt@w% start of key block  
    \db@col@id@w #3\db@col@id@end@% column index  
    \db@key@id@w ##2\db@key@id@end@% key id  
    \db@type@id@w ##3\db@type@id@end@% data type  
    \db@header@id@w ##4\db@header@id@end@% header  
    \db@col@id@w #3\db@col@id@end@% column index  
    \db@plist@elt@end@% end of key block  
  ##5% stuff afterwards  
  \q@nil{\def#1{##3}}%  
  \@dtl@get@keydata#2\q@nil  
}
```

\@dtl@getprops `\@dtl@getprops{<key cs>}{<type cs>}{<header toks>}{<before toks>}{<after toks>}{<data specs>}{<column index>}`

Column index must be expanded.

```
\newcommand*{\@dtl@getprops}[7]{%  
  \def\@dtl@get@keydata##1% stuff before  
    \db@plist@elt@w% start of key block
```

```

\@db@col@id@w #7\@db@col@id@end@% column index
\@db@key@id@w ##2\@db@key@id@end@% key id
\@db@type@id@w ##3\@db@type@id@end@% data type
\@db@header@id@w ##4\@db@header@id@end@% header
\@db@col@id@w #7\@db@col@id@end@% column index
\@db@plist@elt@end@% end of key block
##5% stuff afterwards
\q@nil{%
  \@def#1{##2}% key
  \@def#2{##3}% data type
  #3={##4}% header
  #4={##1}% before stuff
  #5={##5}% after stuff
}%
\@dtl@get@keydata#6\q@nil
}

```

\@dtl@before

```
\newtoks\@dtl@before
```

\@dtl@after

```
\newtoks\@dtl@after
```

\@dtl@colhead

```
\newtoks\@dtl@colhead
```

\DTLaddcolumn

```
\DTLaddcolumn{<db>}{<key>}
```

Adds a column with given key to given column. No data is added to the column. The starred version doesn't check for the existence of the database.

```

\newcommand*{\DTLaddcolumn}{%
  \@ifstar\@sDTLaddcolumn\@DTLaddcolumn
}
\newcommand{\@DTLaddcolumn}[2]{%
  \DTLifdbexists{#1}%
  {\@dtl@updatekeys{#1}{#2}}}%
  {\PackageError{datatool}{Can't add new column to database '#1':
    database doesn't exist}}}%
}
\newcommand{\@sDTLaddcolumn}[2]{%
  \@dtl@updatekeys{#1}{#2}}}%
}

```

\@dtl@updatekeys

```
\@dtl@updatekeys{<db>}{<key>}{<value>}
```



Adds key to database's key list if it doesn't exist. The value is used to update the data type associated with that key. Key must be fully expanded. Doesn't check if database exists.

```
\newcommand*{\@dtl@updatekeys}[3]{%
```

Check if key already exists

```
\@sDTLifhaskey{#1}{#2}%
{%
```

Key exists, may need to update data type. First get the column index.

```
\expandafter\dtl@columnnum\expandafter
=\dtl@columnindex{#1}{#2}\relax
```

Get the properties for this column

```
\edef\@dtl@dogetprops{\noexpand\@dtl@getprops
{\noexpand\@dtl@key}{\noexpand\@dtl@type}%
{\noexpand\@dtl@colhead}{\noexpand\@dtl@before}%
{\noexpand\@dtl@after}{\the\csname dtlkeys@#1\endcsname}%
{\number\dtl@columnnum}}%
\@dtl@dogetprops
```

Is the value empty?

```
\ifstrempy{#3}%
{%
```

Leave data type as it is

```
}%
{%
```

Make a copy of current data type

```
\let\@dtl@oldtype\@dtl@type
```

Check the data type for this entry (stored in \@dtl@datatype)

```
\@dtl@checknumerical{#3}%
```

If this column currently has no data type assigned to it then use the new type.

```
\ifdefempty{\@dtl@type}%
{%
\edef\@dtl@type{\number\@dtl@datatype}%
}%
{%
```

This column already has an associated data type but it may need updating.

```
\ifcase\@dtl@datatype % string
```

String overrides all other types

```
\def\@dtl@type{0}%
\or % int
```

All other types override int, so leave it as it is

```
\or % real
```

Real overrides int, but not currency or string

```
\ifnum\@dtl@type=1\relax
\def\@dtl@type{2}%
```

```

        \fi
        \or % currency
Currency overrides int and real but not string
        \ifnum\@dtl@type>0\relax
        \def\@dtl@type{3}%
        \fi
        \fi
    }%
Has the data type been updated?
    \ifx\@dtl@oldtype\@dtl@type
No change needed
        \else
Update required
        \@dtl@toks@gconcat@middle@cx{dtlkeys@#1}%
        {\@dtl@before}%
        {%
            \noexpand\db@plist@elt@w% start of key block
            \noexpand\db@col@id@w \the\@dtl@columnnum
            \noexpand\db@col@id@end@% column index
            \noexpand\db@key@id@w #2\noexpand\db@key@id@end@% key id
            \noexpand\db@type@id@w \@dtl@type
            \noexpand\db@type@id@end@% data type
            \noexpand\db@header@id@w \the\@dtl@colhead
            \noexpand\db@header@id@end@% header
            \noexpand\db@col@id@w \the\@dtl@columnnum
            \noexpand\db@col@id@end@% column index
            \noexpand\db@plist@elt@end@% end of key block
        }%
        {\@dtl@after}%
    \fi
} %
}%
{%
Key doesn't exist. Increment column count.
    \expandafter\global\expandafter\advance
    \csname dtlcols@#1\endcsname by 1\relax
    \dtl@columnnum=\csname dtlcols@#1\endcsname\relax
Set column index for this key.
    \expandafter\xdef\csname dtl@ci@#1@#2\endcsname{%
        \number\@dtl@columnnum}%
Get data type for this entry (stored in \@dtl@datatype)
    \ifstrempy{#2}%
    {%
        \edef\@dtl@type{}}% don't know data type yet
    }%

```

```

    {%
      \@dtl@checknumerical{#3}%
      \edef\@dtl@type{\number\@dtl@datatype}%
    }%

```

Append to property list

```

\@dtl@toks@gput@right@cx{dtlkeys@#1}%
{%
  \noexpand\db@plist@elt@w
  \noexpand\db@col@id@w \the\dtlcolumnnum
  \noexpand\db@col@end@
  \noexpand\db@key@id@w #2\noexpand\db@key@end@
  \noexpand\db@type@id@w \@dtl@type
  \noexpand\db@type@end@
  \noexpand\db@header@id@w #2\noexpand\db@header@end@
  \noexpand\db@col@id@w \the\dtlcolumnnum
  \noexpand\db@col@end@
  \noexpand\db@plist@elt@end@
}%
}%
}

```

\DTLsetheader \DTLsetheader{<db>}{<key>}{<header>}

Sets header for column given by <key> in database <db>. Starred version doesn't check for existence of database or key.

```

\newcommand*\@DTLsetheader{\@ifstar\@sDTLsetheader\@DTLsetheader}

```

\@DTLsetheader Unstarred version

```

\newcommand*\@DTLsetheader}[3]{%

```

Check if database exists

```

\DTLifdbexists{#1}%
{%

```

Check if key exists.

```

  \@sDTLifhaskey{#1}{#2}%
  {%
    \@sDTLsetheader{#1}{#2}{#3}%
  }%
  {%
    \PackageError{datatool}{Database '#1' doesn't contain key
      '#2'}{ }%
  }%
}%
{%
  \PackageError{datatool}{Database '#1' doesn't exist}{ }%

```

```
}%
}
```

`\@sDTLsetheader` Starred version

```
\newcommand*\@sDTLsetheader}[3]{%
  \expandafter\dtlcolumnnum\expandafter
  =\dtlcolumnindex{#1}-{#2}\relax
  \@dtl@setheaderforindex{#1}-{\dtlcolumnnum}{#3}%
}
```

`\@dtl@setheaderforindex`

```
\@dtl@setheaderforindex{<db>}{<column index>}{<header>}
```

Sets the header for column given by *<column index>* in database *<db>*. The header must be expanded.

```
\newcommand*\@dtl@setheaderforindex}[3]{%
```

Get the properties for this column

```
\edef\@dtl@dogetprops{\noexpand\@dtl@getprops
  {\noexpand\@dtl@key}{\noexpand\@dtl@type}%
  {\noexpand\@dtl@colhead}{\noexpand\@dtl@before}%
  {\noexpand\@dtl@after}{\the\csname dtlkeys@#1\endcsname}%
  {\number#2}}%
\@dtl@dogetprops
```

Store the header in `\@dtl@toks`

```
\@dtl@colhead={#3}%
```

Reconstruct property list

```
\edef\@dtl@colnum{\number#2}\relax
\@dtl@toks@gconcat@middle@cx{dtlkeys@#1}%
{\@dtl@before}%
{%
  \noexpand\db@plist@elt@w% start of block
  \noexpand\db@col@id@w \@dtl@colnum
  \noexpand\db@col@id@end@% index
  \noexpand\db@key@id@w \@dtl@key\noexpand\db@key@id@end@% key
  \noexpand\db@type@id@w \@dtl@type
  \noexpand\db@type@id@end@% data type
  \noexpand\db@header@id@w \the\@dtl@colhead
  \noexpand\db@header@id@end@% header
  \noexpand\db@col@id@w \@dtl@colnum
  \noexpand\db@col@id@end@% index
  \noexpand\db@plist@elt@end@% end of block
}%
{\@dtl@after}%
}
```

`\expandnewvalue` Expand new value before adding to database

```

\newcommand*\dtlexpandnewvalue{%
  \def\@dtl@setnewvalue##1{\protected@edef\@dtl@tmp{##1}%
  \expandafter\@dtl@toks\expandafter{\@dtl@tmp}}%
}

```

`\noexpandnewvalue` Don't expand new value before adding to database

```

\newcommand*\dtlnoexpandnewvalue{%
  \def\@dtl@setnewvalue##1{\@dtl@toks{##1}}%
}

```

Do this by default:

```
\dtlnoexpandnewvalue
```

`\DTLnewbentry` `\DTLnewbentry{<db name>}{<id>}{<value>}`.

Adds an entry to the last row (adds new row if database is empty) and updates general column information if necessary. The starred version doesn't check if the database exists.

```

\newcommand*\DTLnewbentry{%
  \@ifstar\@sDTLnewbentry\DTLnewbentry
}

```

`\@DTLnewbentry` Unstarred version of `\DTLnewbentry`.

```

\newcommand*\@DTLnewbentry[3]{%
  \DTLifdbexists{#1}%
  {\@sDTLnewbentry{#1}{#2}{#3}}%
  {\PackageError{datatool}{Can't add new entry to database '#1':
  database doesn't exist}{}}%
}

```

`\@sDTLnewbentry` Starred version of `\DTLnewbentry` (doesn't check if the database exists).

```
\newcommand*\@sDTLnewbentry[3]{%
```

Update key list

```
\@dtl@updatekeys{#1}{#2}{#3}%
```

Get the column index

```

\expandafter\dtlcolumnnum\expandafter
=\dtlcolumnindex{#1}{#2}\relax

```

Get the current row:

```

\edef\dtl@dogetrow{\noexpand\dtlgetrow{#1}%
  {\number\csname dtlrows@#1\endcsname}}%
\dtl@dogetrow

```

Check if this row already has an entry for the given column.

```

\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
  {\noexpand\dtl@entry}{\number\dtlcolumnnum}%

```

```

}%
\dtl@dogetentry
\ifx\dtl@entry\dtlnovalue
Store the value of this entry in \@dtl@toks
\@dtl@setnewvalue{#3}%
There are no entries in this row for the given column. Add this entry.
\@dtl@toks@gconcat@middle@cx{dtldb@#1}%
{\dtlbeforerow}%
{%
Start of this row:
\noexpand\db@row@elt@w%
Row ID:
\noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
\noexpand\db@row@id@end@%
Current row so far
\the\dtlcurrentrow
New column: Column ID
\noexpand\db@col@id@w \number\dtlcolumnnum
\noexpand\db@col@id@end@%
Value:
\noexpand\db@col@elt@w \the\@dtl@toks
\noexpand\db@col@elt@end@%
Column ID:
\noexpand\db@col@id@w \number\dtlcolumnnum
\noexpand\db@col@id@end@%
Row ID:
\noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
\noexpand\db@row@id@end@%
End of this row
\noexpand\db@row@elt@end@%
}%
Rest (this should be empty)
{\dtlafterrow}%
Print information message if in verbose mode.
\dtl@message{Added #2\space -> #3\space to database '#1'}%
\else
There's already an entry for the given column in this row
\PackageError{datatool}{Can't add entry with ID '#2' to
current row of database '#1'}{There is already an entry with
this ID in the current row}%
\fi
}

```

```
\DTLifdbexists \DTLifdbexists{<db name>}{<true part>}{<>false part>}
```

Checks if a data base with the given name exists.

```
\newcommand{\DTLifdbexists}[3]{%
  \ifundefined{dtldb@#1}{#3}{#2}}
```

## 4.4 Accessing Data

```
\DTLassign \DTLassign{<db>}{<row idx>}{<assign list>}
```

Assigns values given in *<assign list>* for row *<row idx>* in database *<db>*. (Where *<assign list>* is in the same form as in `\DTLforeach`)

```
\newcommand*\DTLassign[3]{%
  \DTLifdbexists{#1}
  {%
```

Grouped in the event that `\dtlcurrentrow` is already in use. (Assignments in `\@dtl@assign` are global.)

```
  {%
    \dtlgetrow{#1}{#2}%
    \@dtl@assign{#3}{#1}%
  }%
}%
{%
  \PackageError{datatool}{Database ‘#1’ doesn’t exist}{}%
}%
}
```

```
assignfirstmatch \DTLassignfirstmatch{<db>}{<col key>}{<value>}{<assign list>}
```

Applies the assignment list to the first row that has the given value in the given column. (Value must be expanded.)

```
\newcommand*\DTLassignfirstmatch[4]{%
  \dtl@assignfirstmatch{#3}{#1}{#2}{#4}%
}
```

```
assignfirstmatch \xDTLassignfirstmatch{<db>}{<col key>}{<value>}{<assign list>}
```

Applies the assignment list to the first row that has the given value in the given column. (Performs *one level* expansion on *<value>*.)

```
\newcommand*\xDTLassignfirstmatch}[4]{%
  \protected@edef\@dtl@asg@value{\expandonce{#3}}%
  \expandafter\dtl@assignfirstmatch\expandafter
  {\@dtl@asg@value}{#1}{#2}{#4}%
}
```

`ssignfirstmatch` Internal swaps the ordering around so the value is first. (This just makes it easier for `\xDTLassignfirstmatch`

```
\newcommand*\dtl@assignfirstmatch}[4]{%
  \DTLifdbexists{#2}%
  {%
  % Grouped in the event that \cs{dtlcurrentrow} is already in use.
  % (Assignments in \cs{@dtl@assign} are global.)
  % \begin{macrocode}
  {%
```

Get row idx:

```
\dtlgetrowindex{\dtl@asg@rowidx}{#2}{\dtlcolumnindex{#2}{#3}}{#1}%
\ifx\dtl@asg@rowidx\dtlnovalue
  \PackageError{datatool}{No match found for
  \string\DTLassignfirstmatch{#2}{#3}{#1}{#4}}{ }%
\else
  \dtlgetrow{#2}{\dtl@asg@rowidx}%
  \@dtl@assign{#4}{#2}%
\fi
}%
}%
{%
\PackageError{datatool}{Data base ‘#2’ doesn’t exist}{ }%
}%
}
```

```
\@dtl@assign \@dtl@assign{<list>}{<db>}
```

Assigns commands according to the given keys. The current row must be stored in `\dtlcurrentrow`.

```
\newcommand*\@dtl@assign}[2]{%
  \ifstrempy{#1}{ }%
  {%
  \@dtl@assigncmd#1,\@nil\@{#2}%
  }%
}
```



\@dtl@assigncmd

```
\@dtl@assigncmd<cmd>=<id>\@nil
```

```
\def\@dtl@assigncmd#1#2=#3,#4\@#5{%
```

Store database label. (This may already have been done so \edef is used to prevent infinite recursion.)

```
\edef\@dtl@dbname{#5}%
```

get entry for ID given by #3 and store in #2

```
\@sDTLifhaskey{#5}{#3}%
```

```
{%
```

```
\edef\@dtl@dogetentry{%
```

```
\noexpand\dtlgetentryfromcurrentrow
```

```
{\noexpand#1}{\dtlcolumnindex{#5}{#3}}%
```

```
\@dtl@dogetentry
```

Set to null if required

```
\ifdefequal{#1}{\dtlnovalue}%
```

```
{%
```

```
\@dtl@setnull{#1}{#3}%
```

```
}%
```

```
{}%
```

Make it global

```
\global\let#1=#1\relax
```

```
}%
```

```
{%
```

```
\PackageError{datatool}{Can't assign \string#1\space: there  
is no key '#3' in data base '#5'}{}
```

Set to null

```
\global\let#1\DTLstringnull
```

```
}%
```

Recurse?

```
\def\dtl@tmp{#4}%
```

```
\ifx\@nnil\dtl@tmp
```

```
\let\@dtl@next\@dtl@assigncmdnoop
```

```
\else
```

```
\let\@dtl@next\@dtl@assigncmd
```

```
\fi
```

```
\@dtl@next#4\@#5}%
```

```
}
```

l@assigncmdnoop End loop

```
\def\@dtl@assigncmdnoop#1\@#2{}
```

```

\@dtl@setnull \@dtl@setnull{<cmd>}{<id>} sets <cmd> to either \@dtlstringnull or \@dtlnumbernull
depending on the data type for <id>. (Database name should be stored in \@dtl@dbname prior
to use.)
    \newcommand*{\@dtl@setnull}[2]{%
Check if database given by \@dtl@dbname has the required key.
    \@sDTLifhaskey{\@dtl@dbname}{#2}%
    {%
Set to null
    \@dtl@setnull{#1}{#2}%
    }%
    {%
Key not defined in database \@dtl@dbname.
    \global\let#1=\DTLstringnull
    }%
    }
@@dtl@setnull As above, but doesn't check if key exists
    \newcommand*{\@@dtl@setnull}[2]{%
Get the data type associated with this key and store in \@dtl@type.
    \@sdtlgetdatatype{\@dtl@type}{\@dtl@dbname}{#2}%
Check data type.
    \ifnum0\@dtl@type=0\relax
Data type is <empty> or 0, so set to string null.
    \global\let#1=\DTLstringnull
    \else
Data type is numerical, so set to number null.
    \global\let#1=\DTLnumbernull
    \fi
    }
\DTLstringnull String null value:
    \newcommand*{\DTLstringnull}{\@dtlstringnull}
\@dtlstringnull String null value:
    \newcommand*{\@dtlstringnull}{NULL}
\DTLnumbernull Number null value:
    \newcommand*{\DTLnumbernull}{\@dtlnumbernull}
\@dtlnumbernull Number null value:
    \newcommand*{\@dtlnumbernull}{0}

```

`\DTLifnull` `\DTLifnull{<command>}{<true part>}{<>false part>}`

Checks if *<command>* is null (either `\DTLstringnull` or `\DTLnumbernull`) if true, does *<true part>* otherwise does *<>false part>*.

```
\newcommand*\DTLifnull}[3]{%
  \ifx#1\dtlnonvalue
    #2%
  \else
    \ifx#1\DTLstringnull
      #2%
    \else
      \ifx#1\DTLnumbernull
        #2%
      \else
        #3%
      \fi
    \fi
  \fi
}
```

`\DTLifnullorepty` `\DTLifnullorepty{<command>}{<true part>}{<>false part>}`

```
\newcommand*\DTLifnullorepty}[3]{%
  \ifdefempty{#1}{#2}{\DTLifnull{#1}{#2}{#3}}%
}
```

`\@dtlnonvalue`

```
\def\@dtlnonvalue{Undefined Value}
```

`\dtlnonvalue`

```
\def\dtlnonvalue{\@dtlnonvalue}
```

`\DTLgetkeydata` `\DTLgetkeydata{<key>}{<db>}{<col cs>}{<type cs>}{<header cs>}`

Gets data for given key in database *<db>*: the column index is stored in *<col cs>* and data type is stored in *<type cs>*. The unstarred version checks for the existence of the database and key, the starred version doesn't.

```
\newcommand*\DTLgetkeydata{%
  \@ifstar\@sdtlgetkeydata\@dtlgetkeydata
}
```

```

\@dtlgetkeydata  Unstarred version of \DTLgetkeydata
                  \newcommand*{\@dtlgetkeydata}[5]{%
Check if the database exists.
                  \DTLifdbexists{#2}%
                  {%
Check if the given key exists in the database.
                  \@sDTLifhaskey{#2}{#1}%
                  {%
Get the data.
                  \@sdtlgetkeydata{#1}{#2}{#3}{#4}{#5}%
                  }%
                  {%
Key not defined in the given database.
                  \PackageError{datatool}{Key ‘#1’ not defined in database
                  ‘#2’}{}%
                  }%
                  }%
                  {%
Database not defined.
                  \PackageError{datatool}{Database ‘#2’ doesn’t exist}{}%
                  }%
                  }

@sdtlgetkeydata  \@sdtlgetkeydata{<key>}{<db>}{<col cs>}{<type cs>}{<header cs>} Starred verison of \DTLgetkeydata.
                  \newcommand*{\@sdtlgetkeydata}[5]{%
                  \@sdtl@getcolumnindex{#3}{#2}{#1}%
                  \edef\@dtl@dogetkeydata{\noexpand\@dtl@getprops
                  {\noexpand\@dtl@key}{\noexpand#4}{\noexpand\@dtl@colhead}%
                  {\noexpand\@dtl@before}{\noexpand\@dtl@after}%
                  {\expandafter\the\csname dtlkeys@#2\endcsname}%
                  {#3}}%
                  \@dtl@dogetkeydata
                  \edef#5{\the\@dtl@toks}%
                  }

```

```

dtl@gathervalues  \dtl@gathervalues[<label>]{<db name>}{<row toks>}

```

Stores each element of *<row>* in *<db name>* into the command `\@dtl@<label>@<key>`, where *<key>* is the key for that element, and *<label>* defaults to *key*.

```

\newcommand{\dtl@gathervalues}[3][key]{%
\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#2}\do
{%

```

```

\dtlgetentryfromrow{\@dtl@tmp}{\@dtl@col}{#3}%
\ifx\@dtl@tmp\dtlnovalue
  \@dtl@setnull{\@dtl@tmp}{\@dtl@key}%
\fi
\expandafter\let\csname @dtl@#1@\@dtl@key\endcsname\@dtl@tmp
}%
}

```

```
\dtl@g@gathervalues \dtl@g@gathervalues[<label>]{<db name>}{<row toks>}
```

As above but makes global assignments

```

\newcommand{\dtl@g@gathervalues}[3][key]{%
\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#2}\do
{%
\dtlgetentryfromrow{\@dtl@tmp}{\@dtl@col}{#3}%
\ifx\@dtl@tmp\dtlnovalue
  \@dtl@setnull{\@dtl@tmp}{\@dtl@key}%
\fi
\expandafter\global
  \expandafter\let\csname @dtl@#1@\@dtl@key\endcsname\@dtl@tmp
}%
}

```

`\dtlcurrentrow` Define token register to store current row.

```
\newtoks\dtlcurrentrow
```

`\dtlbeforerow` Define token register to store everything before the current row.

```
\newtoks\dtlbeforerow
```

`\dtlafterrow` Define token register to store everything after the current row.

```
\newtoks\dtlafterrow
```

```
\dtlgetrow \dtlgetrow{<db>}{<row idx>}
```

Gets row with index *<row idx>* from database named *<db>* and stores the row in `\dtlcurrentrow`, the preceding rows in `\dtlbeforerow` and the following rows in `\dtlafterrow`. The row index, *<row idx>*, is stored in `\dtlrownum` and the database name, *<db>*, is stored in `\dtldbname`. This assumes that the given row exists.

```

\newcommand*{\dtlgetrow}[2]{%
\dtlrownum=#2\relax
\edef\dtldbname{#1}%
\expandafter\toks@\expandafter=\csname dtldb@#1\endcsname
\edef\@dtl@dogetrow{\noexpand\@dtlgetrow{\the\toks@}{\number#2}}%

```

```

\@dtl@dogetrow
}

```

```

\dtlgetrowforvalue \edtlgetrowforvalue{<db>}{<column idx>}{<value>}

```

A version of `\dtlgetrowforvalue` that expands its arguments.

```

\newcommand{\edtlgetrowforvalue}[3]{%
\protected@edef\@dtl@dogetrowforvalue{%
\noexpand\dtlgetrowforvalue{#1}{#2}{#3}}%
\@dtl@dogetrowforvalue
}

```

```

\DTLfetch \DTLfetch{<db name>}{<column1 name>}{<column1 value>}{<column2 name>}

```

Fetches and displays the value for `<column2 name>` in the first row where the value of `<column1 name>` is `<column1 value>`. Note that all arguments are expanded.

```

\newcommand{\DTLfetch}[4]{%
\edtlgetrowforvalue{#1}{\dtlcolumnindex{#1}{#2}}{#3}%
\dtlgetentryfromcurrentrow{\dtlcurrentvalue}{\dtlcolumnindex{#1}{#4}}%
\dtlcurrentvalue
}

```

```

\dtlgetrowforvalue \dtlgetrowforvalue{<db>}{<column idx>}{<value>}

```

Like `\dtlgetrow`, but gets the row where the entry in column `<column index>` matches `<value>`. Produces an error if row not found.

```

\newcommand*{\dtlgetrowforvalue}[3]{%
\dtlgetrowindex{\dtl@rowidx}{#1}{#2}{#3}%
\ifx\dtl@rowidx\dtlnovalue
\PackageError{datatool}{No row found in database ‘#1’ for
column ‘\number#2’ matching ‘#3’}{%
\else
\dtlrownum=\dtl@rowidx\relax
\edef\dtldbname{#1}%
\expandafter\toks@\expandafter=\csname dtldb@#1\endcsname
\edef\@dtl@dogetrow{\noexpand\dtlgetrow{\the\toks@}{\dtl@rowidx}}%
\@dtl@dogetrow
\fi
}

```

`\@dtlgetrow` `\@dtlgetrow{<data specs>}{<row idx>}`

Gets the row specs from *<data specs>* for row with index *<row idx>* which must be fully expanded.

```
\newcommand*{\@dtlgetrow}[2]{%
  \def\@dtl@getrow##1% before stuff
    \db@row@elt@w% start of the row
      \db@row@id@w #2\db@row@id@end@% row id
        ##2%
      \db@row@id@w #2\db@row@id@end@% row id
    \db@row@elt@end@% end of the row
      ##3% after stuff
    \q@nil{\dtlbeforerow={##1}\dtlcurrentrow={##2}\dtlafterrow={##3}}%
  \@dtl@getrow#1\q@nil
}
```

`\dtlrecombine` `\dtlrecombine`

Recombines database contents from `\dtlbeforerow`, `\dtlcurrentrow` and `\dtlafterrow`

```
\newcommand*{\dtlrecombine}{%
  \@dtl@toks@gconcat@middle@cx{dtldb@\dtldbname}%
  {\dtlbeforerow}%
  {%
```

Start of row tag

```
\noexpand\db@row@elt@w
```

Row number

```
\noexpand\db@row@id@w
  \number\dtlrownum
\noexpand\db@row@id@end@
```

Current row specs:

```
\the\dtlcurrentrow
```

Row number

```
\noexpand\db@row@id@w
  \number\dtlrownum
\noexpand\db@row@id@end@
```

End of row tag

```
\noexpand\db@row@elt@end@
}%
{\dtlafterrow}%
}
```

mbineomitcurrent

```
\dtlrecombineomitcurrent
```

Like \dtlrecombine but omits \dtlcurrentrow

```
\newcommand{\dtlrecombineomitcurrent}{%
```

Decrement row indices in \dtlafterrow:

```
\dtl@decrementrows{\dtlafterrow}{\dtlrownum}
```

Reconstruct database contents by concatenating \dtlbeforerow and \dtlafterrow

```
\csname dtldb@\dtldbname\endcsname=\dtlbeforerow
\@dtl@toks@gput@right@cx{\dtldb@\dtldbname}{\the\dtlafterrow}%
\dtl@message{Removed row \number\dtlrownum\space in database
  '\dtldbname'}%
}
```

\dtlsplitrow

```
\dtlsplitrow{<row specs>}{<col num>}{<before cs>}{<after cs>}
```

Splits the row around the entry given by *<col num>*. The entries before the split are stored in *<before cs>* and the entries after the split are stored in *<after cs>*. *<row specs>* and *<col num>* need to be expanded before use.

```
\newcommand*{\dtlsplitrow}[4]{%
\def\@dtlsplitrow##1%before stuff
\db@col@id@w #2\db@col@id@end@% column id
##2% unwanted stuff
\db@col@id@w #2\db@col@id@end@% column id
##3% after stuff
\q@nil{\def#3{##1}\def#4{##3}}%
\@dtlsplitrow#1\q@nil
}
```

entryincurrentrow

```
\dtlreplaceentryincurrentrow{<new value>}{<col num>}
```

Replaces entry for column *<col num>* in \dtlcurrentrow with *<new value>*

```
\newcommand*{\dtlreplaceentryincurrentrow}[2]{%
```

Split row

```
\edef\@dtl@do@splitrow{\noexpand\dtlsplitrow
{\the\dtlcurrentrow}%
{\number#2}%
{\noexpand\@dtl@before@cs}%
{\noexpand\@dtl@after@cs}}%
\@dtl@do@splitrow
```



Recombine with new value

```
\toks@{#1}%  
\edef\@dtl@stuff{%  
  \expandonce\@dtl@before@cs
```

Begin column index specs:

```
\noexpand\db@col@id@w \number#2\noexpand  
  \noexpand\db@col@id@end@% column id
```

New entry:

```
\noexpand\db@col@elt@w  
  \the\toks@  
  \noexpand\db@col@elt@end@
```

End column index specs:

```
\noexpand\db@col@id@w \number#2\noexpand  
  \noexpand\db@col@id@end@% column id  
\expandonce\@dtl@after@cs  
}%
```

Store in \dtlcurrentrow

```
\expandafter\dtlcurrentrow\expandafter{\@dtl@stuff}%
```

Update column specs

```
\@sdtlgetkeyforcolumn{\@dtl@key}{\dtldbname}{#2}%  
\@dtl@updatekeys{\dtldbname}{\@dtl@key}{#1}%  
\dtl@message{Updated \@dtl@key\space -> #1\space in database  
  '\dtldbname'}%  
}
```

entryincurrentrow

```
\dtlremoveentryincurrentrow{<col idx>}
```

Removes entry for column <col idx> from \dtlcurrentrow.

```
\newcommand*{\dtlremoveentryincurrentrow}[1]{%
```

Split row

```
\edef\@dtl@do@splitrow{\noexpand\dtlsplitrow  
  {\the\dtlcurrentrow}%  
  {\number#1}%  
  {\noexpand\@dtl@before@cs}%  
  {\noexpand\@dtl@after@cs}}%  
\@dtl@do@splitrow
```

Combine row without given column:

```
\edef\@dtl@stuff{%  
  \expandonce\@dtl@before@cs  
  \expandonce\@dtl@after@cs  
}%
```

Store in `\dtlcurrentrow`

```
\expandafter\dtlcurrentrow\expandafter{\@dtl@stuff}%  
\dtl@message{Removed entry from column \number#1\space\space in database  
'\dtldbname'}%  
}
```

`iesincurrentrow`

```
\dtlswapentriesincurrentrow{<col1 num>}{<col2 num>}
```

Swaps columns `<col1 num>` and `<col2 num>` in `\dtlcurrentrow`

```
\newcommand*{\dtlswapentriesincurrentrow}[2]{%  
  \dtlgetentryfromcurrentrow{\@dtl@entryI}{#1}%  
  \dtlgetentryfromcurrentrow{\@dtl@entryII}{#2}%  
  \expandafter\dtlreplaceentryincurrentrow\expandafter  
  {\@dtl@entryII}{#1}%  
  \expandafter\dtlreplaceentryincurrentrow\expandafter  
  {\@dtl@entryI}{#2}%  
}
```

`ryfromcurrentrow`

```
\dtlgetentryfromcurrentrow{<cs>}{<col num>}
```

Gets value for column `<col num>` from `\dtlcurrentrow` and stores in `<cs>`. If not found, `<cs>` is set to `\dtlnovalue`.

```
\newcommand*{\dtlgetentryfromcurrentrow}[2]{%  
  \dtlgetentryfromrow{#1}{#2}{\dtlcurrentrow}%  
}
```

`lgetentryfromrow`

```
\dtlgetentryfromrow{<cs>}{<col num>}{<row toks>}
```

```
\newcommand*{\dtlgetentryfromrow}[3]{%  
  \edef\@dtl@do@getentry{\noexpand\dtlgetentryfromrow  
  {\noexpand#1}{\number#2}{\the#3}}%  
  \@dtl@do@getentry  
}
```

`@getentryfromrow`

```
\dtl@getentryfromrow{<cs>}{<col num>}{<row specs>}
```

```
\newcommand*{\dtl@getentryfromrow}[3]{%  
  \def\dtl@dogetentry##1% before stuff
```

```

\db@col@id@w #2\db@col@id@end@% Column id
\db@col@elt@w ##2\db@col@elt@end@% Value
\db@col@id@w #2\db@col@id@end@% Column id
##3% Remaining stuff
\q@nil{\def#1{##2}}%
\dtl@dogetentry#3%
\db@col@id@w #2\db@col@id@end@%
\db@col@elt@w \@dtlnovalue\db@col@elt@end@%
\db@col@id@w #2\db@col@id@end@%
\q@nil
}

```

entrytocurrentrow

```
\dtlappendentrytocurrentrow{<key>}{<value>}
```

Appends entry to \dtlcurrentrow

```
\newcommand*{\dtlappendentrytocurrentrow}[2]{%
```

Update information about this column (adding new column if necessary)

```
\@dtl@updatekeys{\dtldbname}{#1}{#2}%
```

Get column index and store in \dtlcolumnnum

```
\expandafter\dtlcolumnnum\expandafter
=\dtlcolumnindex{\dtldbname}{#1}\relax
```

Does this row already have an entry with this key?

```
\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
{\noexpand\dtl@entry}{\number\dtlcolumnnum}%
}%
\dtl@dogetentry
\ifx\dtl@entry\dtlnovalue
```

There are no entries in this row for the given key. Expand entry value before storing.

```
\protected@edef\@dtl@tmp{#2}%
\expandafter\@dtl@toks\expandafter{\@dtl@tmp}%
```

Append this entry to the current row.

```
\@dtl@toks@gput@right@cx{dtlcurrentrow}%
{%
```

Begin column index specs:

```
\noexpand\db@col@id@w
\number\dtlcolumnnum
\noexpand\db@col@id@end@
```

New entry:

```
\noexpand\db@col@elt@w
\the\@dtl@toks
\noexpand\db@col@elt@end@
```

End column index specs:

```
\noexpand\db@col@id@w  
  \number\dtlcolumnnum  
\noexpand\db@col@id@end@  
}%
```

Print information to terminal and log file if in verbose mode.

```
\dtl@message{Appended #1\space -> #2\space to database  
  '\dtldbname'}%  
\else
```

There is already an entry in this row for the given key

```
\PackageError{datatool}{Can't append entry to row:  
  there is already an entry for key '#1' in this row}{}%  
\fi  
}
```

entryincurrentrow

```
\dtlupdateentryincurrentrow{<key>}{<value>}
```

Appends entry to \dtlcurrentrow if column with given key doesn't exist, otherwise updates the value.

```
\newcommand*{\dtlupdateentryincurrentrow}[2]{%
```

Update information about this column (adding new column if necessary)

```
\dtl@updatekeys{\dtldbname}{#1}{#2}%
```

Get column index and store in \dtlcolumnnum

```
\expandafter\dtlcolumnnum\expandafter  
  =\dtlcolumnindex{\dtldbname}{#1}\relax
```

Does this row already have an entry with this key?

```
\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow  
  {\noexpand\dtl@entry}{\number\dtlcolumnnum}%  
}%  
\dtl@dogetentry  
\ifx\dtl@entry\dtlnovalue
```

There are no entries in this row for the given key. Expand entry value before storing.

```
\protected@edef\@dtl@tmp{#2}%  
\expandafter\@dtl@toks\expandafter{\@dtl@tmp}%
```

Append this entry to the current row.

```
\@dtl@toks@gput@right@cx{dtlcurrentrow}%  
{%
```

Begin column index specs:

```
\noexpand\db@col@id@w  
  \number\dtlcolumnnum  
\noexpand\db@col@id@end@
```

New entry:

```
\noexpand\db@col@elt@w
  \the\@dtl@toks
\noexpand\db@col@elt@end@
```

End column index specs:

```
\noexpand\db@col@id@w
  \number\dtl@columnnum
\noexpand\db@col@id@end@
}%
```

Print information to terminal and log file if in verbose mode.

```
\dtl@message{Appended #1\space -> #2\space to database
  '\dtldbname'}%
\else
```

There is already an entry in this row for the given key

```
\toks@{#2}%
\edef\do@dtl@replaceincurrentrow{%
  \noexpand\dtl@replaceentryincurrentrow{\the\toks@}{\number\dtl@columnnum}%
}%
\do@dtl@replaceincurrentrow
\fi
}
```

```
\DTLgetvalue \DTLgetvalue{<cs>}{<db>}{<r>}{<c>}
```

Gets the element in row  $\langle r \rangle$ , column  $\langle c \rangle$  from database  $\langle db \rangle$  and stores in  $\langle cs \rangle$ .

```
\newcommand*\DTLgetvalue[4]{%
  \edef\dtl@dogetvalue{\noexpand\dtl@getvalue{\noexpand#1}{#2}%
    {\number#3}{\number#4}}%
  \dtl@dogetvalue
}
```

```
\dtl@getvalue
```

```
\newcommand*\dtl@getvalue[4]{%
  \def\@dtl@getvalue ##1% stuff before row <r>
    \db@row@id@w #3\db@row@id@end@% row <r> id
    ##2% stuff in row <r> before column <c>
    \db@col@id@w #4\db@col@id@end@% column <c> id
    \db@col@elt@w ##3\db@col@elt@end@% value
    ##4% stuff after value
  \q@nil{\def#1{##3}}%
  \toks@=\csname dtldb@#2\endcsname
  \expandafter\@dtl@getvalue\the\toks@% contents of data base
  \db@row@id@w #3\db@row@id@end@%
  \db@col@id@w #4\db@col@id@end@%
```

```

        \db@col@elt@w \@dtlnvalue\db@col@elt@end@% undefined value
    \q@nil
\ifx#1\dtlnvalue
    \PackageError{datatool}{There is no element at (row=#3,\space
        column=#4) in database '#2'}{}%
\fi
}

```

\DTLgetlocation \DTLgetlocation{<row cs>}{<column cs>}{<database>} {<value>}

Assigns <row cs> and <column cs> to the indices of the first entry in <database> that matches <value>.

```

\newcommand*\DTLgetlocation}[4]{%
    \def\@dtl@getlocation##1% stuff before value
        \db@col@elt@w #4\db@col@elt@end@% value
        \db@col@id@w ##2\db@col@id@end@% column id
        ##3% stuff after this column
        \db@row@id@w ##4\db@row@id@end@% row id
        ##5% stuff after row
    \q@nil{\def#1{##4}\def#2{##2}}%
    \toks@=\csname dtldb@#3\endcsname
    \expandafter\@dtl@getlocation\the\toks@% contents of data base
        \db@col@elt@w #4\db@col@elt@end@% value
        \db@col@id@w \@dtlnvalue\db@col@id@end@% undefined column id
        \db@row@id@w \@dtlnvalue\db@row@id@end@% undefined row id
    \q@nil
    \ifx#1\dtlnvalue
        \PackageError{datatool}{There is no element '#4' in database '#3'}{}%
    \fi
}

```

\DTLgetrowindex \DTLgetrowindex{<row cs>}{<database>}{<column index>} {<value>}

Assigns <row cs> to the row index of the first entry in <database> where the entry in <column index> matches <value>.

```

\newcommand*\DTLgetrowindex}[4]{%
    \toks@{#4}%
    \edef\@dtl@dogetrowindex{\noexpand\@dtlgetrowindex{\noexpand#1}{#2}{\number#3}{\the\toks@}}%
    \dtl@dogetrowindex
    \ifx#1\dtlnvalue
        \PackageError{datatool}{There is no element '#4' for column
            \number#3\space in database '#2'}{}%
    \fi
}

```

```
\dtlgetrowindex \dtlgetrowindex{<row cs>}{<database>}{<column index>} {<value>}
```

As above but doesn't produce an error if not found.

```
\newcommand*\dtlgetrowindex[4]{%
  \toks@{#4}%
  \edef\dtl@dogetrowindex{\noexpand\@dtlgetrowindex{\noexpand#1}{#2}{\number#3}{\the\toks@}}%
  \dtl@dogetrowindex
}
```

```
\xdtlgetrowindex \xdtlgetrowindex{<row cs>}{<database>}{<column index>} {<value>}
```

As above but expands the value.

```
\newcommand*\xdtlgetrowindex[4]{%
  \protected@edef\dtl@dogetrowindex{\noexpand\@dtlgetrowindex{\noexpand#1}{#2}{\number#3}{#4}}%
  \dtl@dogetrowindex
}
```

```
\@dtlgetrowindex \@dtlgetrowindex{<row cs>}{<database>}{<column index>} {<value>}
```

Column index must be fully expanded.

```
\newcommand*\@dtlgetrowindex[4]{%
  \def\@dtl@getrowindex##1% stuff before value
    \db@col@elt@w #4\db@col@elt@end@% value
    \db@col@id@w #3\db@col@id@end@% column id
    ##2% stuff after this column
    \db@row@id@w ##3\db@row@id@end@% row id
    ##4% stuff after row
    \q@nil{\def#1{##3}}%
  \toks@=\csname dtldb@#2\endcsname
  \expandafter\@dtl@getrowindex\the\toks@% contents of data base
  \db@col@elt@w #4\db@col@elt@end@% value
  \db@col@id@w #3\db@col@id@end@% column id
  \db@row@id@w \@dtlnovalue\db@row@id@end@% undefined row id
  \q@nil
}
```

## 4.5 Iterating Through Databases

```
\@dtlforeachrow \@dtlforeachrow(<idx cs>,<row cs>)\in{<db>} \do{<body>}
```

Iterates through each row in database. Assigns the current row index to  $\langle idx cs \rangle$  and the row specs to  $\langle row cs \rangle$

```
\long\def\@dtlforeachrow(#1,#2)\in#3\do#4{%
  \edef\dtl@tmp{\expandafter\the\csname dtldb@#3\endcsname}%
  \expandafter\@dtlforeachrow\dtl@tmp
  \db@row@elt@w%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@elt@end@%
  \@@{#1}{#2}{#4}\q@nil
}
```

@dtlforeachrow

```
\long\def\@dtlforeachrow\db@row@elt@w%
\db@row@id@w #1\db@row@id@end@%
#2\db@row@id@w #3\db@row@id@end@%
\db@row@elt@end@#4\@@#5#6#7\q@nil{%
```

Define control sequence given by #5

```
\gdef#5{#1}%
```

Hide the loop body in a macro

```
\gdef\@dtl@loopbody{#7}%
```

Increment level counter to allow for nested loops

```
\global\advance\@dtlforeach@level by 1\relax
```

Check if we have reached the end of the loop

```
\ifx#5\@nnil
  \expandafter\global\expandafter
  \let\csname @dtlforeachnext\the\@dtlforeach@level\endcsname
  =\@dtlforeachnoop
\else
  \gdef#6{#2}%
```

Set up the break function: Make a copy of current break function

```
\expandafter\let
  \csname @dtl@break@\the\@dtlforeach@level\endcsname
  \dtlbreak
```

Setup break function for this level

```
\gdef\dtlbreak{\expandafter\global\expandafter
  \let\csname @dtlforeachnext\the\@dtlforeach@level\endcsname
  =\@dtlforeachnoop}%
```

Initialise

```
\expandafter\global\expandafter
  \let\csname @dtlforeachnext\the\@dtlforeach@level\endcsname
  =\@dtlforeachrow
```

Do body of loop

```
\@dtl@loopbody
```



Restore break function

```
\expandafter\let\expandafter\dtlbreak
\csname @dtl@break@the\@dtl@foreach@level\endcsname
\fi
```

Set up what to do next.

```
\expandafter\let\expandafter\@dtl@foreachnext
\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
```

Decrement level counter.

```
\global\advance\@dtl@foreach@level by -1\relax
```

Repeat loop if necessary.

```
\@dtl@foreachnext#4\@@{#5}{#6}{#7}\q@nil
}
```

dtl@foreachnoop

```
\long\def\@dtl@foreachnoop#1\@@#2\q@nil{}
```

\dtlforeachkey

```
\dtlforeachkey(<key cs>,<col cs>,<type cs>,<header cs>) \in{<db>}\do
{<body>}
```

Iterates through all the keys in database *<db>*. In each iteration, *<key cs>* stores the key, *<col cs>* stores the column index, *<type cs>* stores the data type and *<header cs>* stores the header.

```
\long\def\dtlforeachkey(#1,#2,#3,#4)\in#5\do#6{%
\gdef\@dtl@loopbody{#6}%
\edef\@dtl@keys{\expandafter\the\csname dtlkeys@#5\endcsname}%
\expandafter\@dtl@foreachkey\@dtl@keys
\@db@plist@elt@w%
\@db@col@id@w -1\@db@col@id@end@%
\@db@key@id@w \@db@key@id@end@%
\@db@type@id@w \@db@type@id@end@%
\@db@header@id@w \@db@header@id@end@%
\@db@col@id@w -1\@db@col@id@end@%
\@db@plist@elt@end@%
\@@{\@dtl@updatefkcs{#1}{#2}{#3}{#4}}\q@nil
}
```

@dtl@updatefkcs

```
\newcommand*\@dtl@updatefkcs}[8]{%
\gdef#1{#5}%
\gdef#2{#6}%
\gdef#3{#7}%
\gdef#4{#8}%
}
```

`@dtl@foreachkey` Sets everything globally in case it occurs in a tabular environment Loop body needs to be stored in `\@dtl@loopbody`. #7 indicates an update macro.

```
\long\def\@dtl@foreachkey\db@plist@elt@w%  
\db@col@id@w #1\db@col@id@end@%  
\db@key@id@w #2\db@key@id@end@%  
\db@type@id@w #3\db@type@id@end@%  
\db@header@id@w #4\db@header@id@end@%  
\db@col@id@w #5\db@col@id@end@%  
\db@plist@elt@end@#6\@#7\q@nil{%  
\ifnum#1=-1\relax
```

Terminate loop

```
\let\@dtl@foreachnext\@dtl@foreachnoop  
\else
```

Set up loop variables

```
#7{#2}{#1}{#3}{#4}%
```

Increment level counter to allow for nested loops

```
\global\advance\@dtl@foreach@level by 1\relax
```

Set up the break function

```
\expandafter\let  
\csname @dtl@break@the\@dtl@foreach@level\endcsname  
\dtlbreak  
\gdef\dtlbreak{\expandafter\global\expandafter  
\let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname  
=\@dtl@foreachnoop}%
```

Initialise

```
\expandafter\global\expandafter  
\let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname  
=\@dtl@foreachkey
```

Do body of loop

```
\@dtl@loopbody
```

Set up what to do next

```
\expandafter\let\expandafter\@dtl@foreachnext  
\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
```

Restore break function

```
\expandafter\let\expandafter\dtlbreak  
\csname @dtl@break@the\@dtl@foreach@level\endcsname
```

Decrement level counter

```
\global\advance\@dtl@foreach@level by -1\relax  
\fi
```

Recurse if necessary

```
\@dtl@foreachnext#6\@#7\q@nil  
}
```

```
\dtlforcolumn \dtlforcolumn{<cs>}{<db>}{<key>}{<body>}
```

Iterates through column given by <key> in database <db>. <cs> is assign to the element of the column in the current iteration. Starred version doesn't check if data base exists

```
\newcommand*{\dtlforcolumn}{\@ifstar\@sdtlforcolumn\@dtlforcolumn}
```

```
\@dtlforcolumn
```

```
\newcommand{\@dtlforcolumn}[4]{%
```

Check if data base exists

```
\DTLifdbexists{#2}%
{%
  \DTLifhaskey{#2}{#3}%
  {%
    \@sdtlforcolumn{#1}{#2}{#3}{#4}%
  }%
}
```

key not in data base

```
{%
  \PackageError{datatool}{Database '#2' doesn't contain
    key '#3'}{}%
}%
}%
%
{%
  \PackageError{datatool}{Database '#2' doesn't exist}{}%
}%
}
```

```
\@sdtlforcolumn
```

```
\newcommand{\@sdtlforcolumn}[4]{%
  \toks@{#4}%
  \edef\@dtl@doforcol{\noexpand\dtl@forcolumn{\noexpand#1}%
    {\expandafter\the\csname dtldb#2\endcsname}%
    {\dtlcolumnindex{#2}{#3}}{\the\toks@}}%
  }%
  \@dtl@doforcol%
}
% end{macrocode}
%\end{macro}
%
%\begin{macro}{\dtlforcolumnidx}
%\begin{definition}
%\cs{dtlforcolumnidx}\marg{cs}\marg{db}\marg{col num}\marg{body}
%\end{definition}
% Iterates through the column with index <col num> in database <db>.
% Starred version doesn't check if database exists.
%\changes{2.0}{2009 February 27}{new}
```

```
% \begin{macrocode}
\newcommand*{\dtlforcolumnidx}{%
  \ifstar\@sdtlforcolumnidx\@dtlforcolumnidx
}
```

dtlforcolumnidx

```
\newcommand{\@dtlforcolumnidx}[4]{%
  \DTLifdbexists{#2}%
  {%
    \expandafter\ifnum\csname dtlcols@#2\endcsname<#3\relax
    \PackageError{datatool}{Column index \number#3\space out of
      bounds for database ‘#2’}{Database ‘#2’ only has
      \expandafter\number\csname dtlcols@#2\endcsname\space
      columns}%
    \else
    \ifnum#3<1\relax
    \PackageError{datatool}{Column index \number#3\space out of
      bounds for database ‘#2’}{Indices start from 1}%
    \else
    \@sdtlforcolumnidx{#1}{#2}{#3}{#4}%
    \fi
  \fi
}%
```

data base doesn't exist

```
{%
  \PackageError{datatool}{Database ‘#2’ doesn't exist}{}%
}%
}
```

dtlforcolumnidx

```
\newcommand{\@sdtlforcolumnidx}[4]{%
  \toks@{#4}%
  \edef\@dtl@doforcol{\noexpand\dtl@forcolumn{\noexpand#1}%
    {\expandafter\the\csname dtldb@#2\endcsname}%
    {\number#3}{\the\toks@}}%
  }%
  \@dtl@doforcol
}
```

```
\dtl@forcolumn \dtl@forcolumn{<cs>}{<db specs>}{<col num>}{<body>}
```

<col num> needs to be fully expanded

```
\newcommand{\dtl@forcolumn}[4]{%
```

make a copy of break function

```
\let\@dtl@oldbreak\dtlbreak
```

set up break function

```
\def\dtlbreak{\let\@dtl@forcolnext=\@dtl@forcolnoop}%
```

define loop macro for this column

```
\def\@dtl@forcolumn##1% before stuff
\@db@col@id@w #3\@db@col@id@end@% column index
\@db@col@elt@w ##2\@db@col@elt@end@% entry
\@db@col@id@w #3\@db@col@id@end@% column index
##3% after stuff
\q@nil{%
\def#1{##2}% assign value to <cs>
```

check if end of loop

```
\ifx#1\@nnil
\let\@dtl@forcolnext=\@dtl@forcolnoop
\else
```

do body of loop

```
#4%
\let\@dtl@forcolnext=\@dtl@forcolumn
\fi
```

repeat if necessary

```
\@dtl@forcolnext##3\q@nil
}%
```

do loop

```
\@dtl@forcolumn#2%
\@db@col@id@w #3\@db@col@id@end@%
\@db@col@elt@w \@nil\@db@col@elt@end@%
\@db@col@id@w #3\@db@col@id@end@\q@nil
```

restore break function

```
\let\dtlbreak\@dtl@oldbreak
}
```

@dtl@forcolnoop

```
\def\@dtl@forcolnoop#1\q@nil{}
```

dtlforeachlevel

\DTLforeach can only be nested up to three levels. \dtlforeachlevel keeps track of the current level.

```
\newcount\dtlforeachlevel
```

The counter DTLrow<*n*> keeps track of each row of data during the <*n*> nested \DTLforeach. It is only incremented in the conditions (given by the optional argument) are met.

```
\newcounter{DTLrowi}
\newcounter{DTLrowii}
\newcounter{DTLrowiii}
```

Keep hyperref happy

```
\newcounter{DTLrow}
\def\theHDTLrow{\arabic{DTLrow}}
\def\theHDTLrowi{\theHDTLrow.\arabic{DTLrowi}}
\def\theHDTLrowii{\theHDTLrowi.\arabic{DTLrowii}}
\def\theHDTLrowiii{\theHDTLrowii.\arabic{DTLrowiii}}

\newcount\dtl@rowi
\newcount\dtl@rowii
\newcount\dtl@rowiii

\newtoks\@dtl@curi
\newtoks\@dtl@previ
\newtoks\@dtl@nexti
\newtoks\@dtl@curii
\newtoks\@dtl@previi
\newtoks\@dtl@nextii
\newtoks\@dtl@curiii
\newtoks\@dtl@previii
\newtoks\@dtl@nextiii
```

```
\DTLsaverowcount \DTLsaveastrowcount{<cmd>}
```

Stores the maximum row count for the last `\DTLforeach`.

```
\newcommand*{\DTLsaveastrowcount}[1]{%
\ifnum\dtlforeachlevel>2\relax
\def#1{0}%
\else
\ifnum\dtlforeachlevel<0\relax
\def#1{0}%
\else
\@dtl@tmpcount=\dtlforeachlevel
\advance\@dtl@tmpcount by 1\relax
\edef#1{\expandafter\number
\csname c@DTLrow\romannumeral\@dtl@tmpcount\endcsname}%
\fi
\fi}
```

`DTLenvforeach` Environment form of `\DTLforeach` (contents are gathered, so verbatim can't be used).

```
\newenvironment{DTLenvforeach}[3][\boolean{true}]%
{
\def\@dtlenvforeach@args{[#1]{#2}{#3}}%
\long\collect@body\@do@dtlenvforeach
}%
{}
\newcommand{\@do@dtlenvforeach}[1]{%
\expandafter\@DTLforeach\@dtlenvforeach@args{#1}%
}
```

DTLenvforeach\* Environment form of \DTLforeach\* (contents are gathered, so verbatim can't be used).

```

\newenvironment{DTLenvforeach*}[3][\boolean{true}]%
{
  \def\s@dtlenvforeach@args{[#1]{#2}{#3}}%
  \long@collect@body\@do@sdtlenvforeach
}
{}
\newcommand{\@do@sdtlenvforeach}[1]{%
  \expandafter\@sDTLforeach\s@dtlenvforeach@args{#1}%
}

```

\DTLforeach \DTLforeach[*<conditions>*]{*<db name>*}{*<values>*}{*<text>*}

For each row of data in the database given by *<db name>*, do *<text>*, if the specified conditions are satisfied. The argument *{<values>}* is a comma separated list of *<cmd>=<key>* pairs. At the start of each row, each of the commands in this list are set to the value of the entry with the corresponding key *<key>*. (\gdef is used to ensure \DTLforeach works in a tabular environment.) The database may be edited in the unstarred version, in the starred version the database is read only.

```

\newcommand*{\DTLforeach}{\@ifstar\@sDTLforeach\@DTLforeach}

```

\@DTLforeach \@DTLforeach is the unstarred version of \DTLforeach. The database is reconstructed to allow for rows to be edited. Use the starred version for faster access.

```

\newcommand{\@DTLforeach}[4][\boolean{true}]{%

```

Check database exists

```

\DTLifdbexists{#2}%
{}

```

Keep hyperref happy

```

\refstepcounter{DTLrow}%

```

Make it global (so that it works in tabular environment)

```

\global\c@DTLrow=\c@DTLrow\relax

```

Store database name

```

\xdef\@dtl@dbname{#2}%

```

Increment level and check not exceeded 3

```

\global\advance\dtlforeachlevel by 1\relax
\ifnum\dtlforeachlevel>3\relax
  \PackageError{datatool}{\string\DTLforeach\space nested too
    deeply}{Only 3 levels are allowed}%
\else
  \@DTLifdbempty{#2}%

```

Do nothing if database is empty

```

{}%
{}%

```

Set level dependent information (needs to be global to ensure it works in the tabular environment). Row counter:

```
\expandafter\global
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
= 0\relax
```

Store previous value of \DTLiffirstrow

```
\expandafter\global\expandafter\let%
\csname @dtl@iffirstrow\the\dtlforeachlevel\endcsname
\DTLiffirstrow
```

Define current \DTLiffirstrow

```
\gdef\DTLiffirstrow##1##2{%
\expandafter\ifnum
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
=1\relax
##1%
\else
##2%
\fi}%
```

Store previous value of \DTLiflastrow

```
\expandafter\global\expandafter\let%
\csname @dtl@iflastrow\the\dtlforeachlevel\endcsname
\DTLiflastrow
```

Define current \DTLiflastrow

```
\gdef\DTLiflastrow##1##2{%
\expandafter\ifnum
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
=\csname dtlrows@#2\endcsname\relax
##1%
\else
##2%
\fi}%
```

Store previous value of \DTLifoddrow

```
\expandafter\global\expandafter\let%
\csname @dtl@ifoddrow\the\dtlforeachlevel\endcsname
\DTLifoddrow
```

Define current \DTLifoddrow

```
\gdef\DTLifoddrow##1##2{%
\expandafter\ifodd
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
##1%
\else
##2%
\fi}%
```

Store data base name for current level

```
\expandafter\global\expandafter\let
```



```

\csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
  =\@dtl@dbname

```

Mark it as not read only

```

\expandafter\global\expandafter\let
\csname @dtl@ro@\romannumeral\dtlforeachlevel\endcsname
  = 0\relax

```

Loop through each row. Loop counter given by \dtl@row<level>

```

\dtlgforint
\csname dtl@row\romannumeral\dtlforeachlevel\endcsname
  =1\to\csname dtlrows@#2\endcsname\step1\do
  {%

```

Get current row from the data base

```

\@dtl@tmpcount=
\csname dtl@row\romannumeral\dtlforeachlevel\endcsname
\edef\dtl@dogetrow{\noexpand\dtlgetrow{#2}%
  {\number\@dtl@tmpcount}}%
\dtl@dogetrow

```

Store the current row for this level

```

\expandafter\global
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
  = \dtlcurrentrow

```

Store the previous rows for this level

```

\expandafter\global
\csname @dtl@prev\romannumeral\dtlforeachlevel\endcsname
  = \dtlbeforerow

```

Store the subsequent rows for this level

```

\expandafter\global
\csname @dtl@next\romannumeral\dtlforeachlevel\endcsname
  = \dtlafterrow

```

Assign commands to the required entries

```

\ifx\relax#3\relax
\else
\@dtl@assign{#3}{#2}%
\fi

```

Do the main body of text if condition is satisfied

```

\ifthenelse{#1}%
  {%

```

Increment user row counter

```

\refstepcounter{DTLrow\romannumeral\dtlforeachlevel}%
\expandafter\edef\expandafter\DTLcurrentindex%
\expandafter{%
  \arabic{DTLrow\romannumeral\dtlforeachlevel}}%
#4%

```

Has this row been marked for deletion?

```
\edef\@dtl@tmp{\expandafter\the
\csname @dtl@cur\romannumeral
\dtlforeachlevel\endcsname}%
\ifx\@dtl@tmp\@nnil
```

Row needs to be deleted Decrement row indices for rows with a higher index than this one

```
\expandafter\dtl@decrementrows\expandafter
{\csname @dtl@prev\romannumeral
\dtlforeachlevel\endcsname
}{\csname dtl@row\romannumeral
\dtlforeachlevel\endcsname}%
\expandafter\dtl@decrementrows\expandafter
{\csname @dtl@next\romannumeral
\dtlforeachlevel\endcsname
}{\csname dtl@row\romannumeral
\dtlforeachlevel\endcsname}%
```

Reconstruct data base without this row

```
\edef\@dtl@tmp{%
\expandafter\the
\csname @dtl@prev\romannumeral
\dtlforeachlevel\endcsname
\expandafter\the
\csname @dtl@next\romannumeral
\dtlforeachlevel\endcsname
}%
\expandafter\global\expandafter
\csname dtldb@#2\endcsname\expandafter{\@dtl@tmp}%
```

Decrement the row count for this database:

```
\expandafter\global\expandafter
\advance\csname dtlrows@#2\endcsname by -1\relax
```

Decrement the counter for this loop

```
\expandafter\global\expandafter
\advance\csname dtl@row\romannumeral
\dtlforeachlevel\endcsname by -1\relax
\else
```

Reconstruct data base

```
\@dtl@before=\csname @dtl@prev\romannumeral
\dtlforeachlevel\endcsname
\@dtl@after=\csname @dtl@next\romannumeral
\dtlforeachlevel\endcsname
\@dtl@toks@gconcat@middle@cx{dtldb@#2}%
{\@dtl@before}%
{%
```

This row

```
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \expandafter\number
```

```

        \csname dtl@row\romannumeral
        \dtlforeachlevel\endcsname
\noexpand\db@row@id@end@%
\expandafter\the
        \csname @dtl@cur\romannumeral
        \dtlforeachlevel\endcsname
\noexpand\db@row@id@w \expandafter\number
        \csname dtl@row\romannumeral
        \dtlforeachlevel\endcsname
\noexpand\db@row@id@end@%
\noexpand\db@row@elt@end@%
}%
{\@dtl@after}%
\fi
}%

```

Condition not met so ignore

```

{}%
}%

```

Restore previous value of \DTLiffirstrow

```

\expandafter\global\expandafter\let\expandafter\DTLiffirstrow
\csname @dtl@ifirstrow\the\dtlforeachlevel\endcsname

```

Restore previous value of \DTLiflastrow

```

\expandafter\global\expandafter\let\expandafter\DTLiflastrow
\csname @dtl@iflastrow\the\dtlforeachlevel\endcsname

```

Restore previous value of \DTLifoddrow

```

\expandafter\global\expandafter\let\expandafter\DTLifoddrow
\csname @dtl@ifoddrow\the\dtlforeachlevel\endcsname
}%
\fi

```

Decrement level

```

\global\advance\dtlforeachlevel by -1\relax
}%

```

else part (data base doesn't exist):

```

{%
\PackageError{datatool}{Database '#2' doesn't exist}{}%
}%
}

```

\@sDTLforeach \@sDTLforeach is the starred version of \DTLforeach. The database rows can't be edited.

```

\newcommand{\@sDTLforeach}[4] [\boolean{true}] {%

```

Check database exists

```

\DTLifdbexists{#2}%
{%

```

Keep hyperref happy

```

\refstepcounter{DTLrow}%

```

Make it global (so that it works in tabular environment)

```
\global\c@DTLrow=\c@DTLrow
```

Store database name.

```
\xdef\@dtl@dbname{#2}%
```

Increment level and check not exceeded 3

```
\global\advance\dtlforeachlevel by 1\relax
\ifnum\dtlforeachlevel>3\relax
  \PackageError{datatool}{\string\DTLforeach\space nested too
    deeply}{Only 3 levels are allowed}%
\else
  \@DTLifdbempty{#2}%
```

Do nothing if database is empty

```
{}%
{%
```

Set level dependent information (needs to be global to ensure it works in the tabular environment). Row counter:

```
\expandafter\global
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
= 0\relax
```

Store previous value of \DTLiffirstrow

```
\expandafter\global\expandafter\let%
\csname @dtl@iffirstrow\the\dtlforeachlevel\endcsname
\DTLiffirstrow
```

Define current \DTLiffirstrow

```
\gdef\DTLiffirstrow##1##2{%
\expandafter\ifnum
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
=1\relax
##1%
\else
##2%
\fi}%
```

Store previous value of \DTLiflastrow

```
\expandafter\global\expandafter\let%
\csname @dtl@iflastrow\the\dtlforeachlevel\endcsname
\DTLiflastrow
```

Define current \DTLiflastrow

```
\gdef\DTLiflastrow##1##2{%
\expandafter\ifnum
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
=\csname dtlrows@#2\endcsname\relax
##1%
\else
##2%
\fi}%
```

Store previous value of \DTLifodddrow

```
\expandafter\global\expandafter\let%
\csname @dtl@ifodddrow\the\dtlforeachlevel\endcsname
\DTLifodddrow
```

Define current \DTLifodddrow

```
\gdef\DTLifodddrow##1##2{%
\expandafter\ifodd
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
##1%
\else
##2%
\fi}%
```

Store data base name for current level

```
\expandafter\gdef\csname @dtl@dbname@\romannumeral
\dtlforeachlevel\endcsname{#2}%
```

Mark it as read only

```
\expandafter\global\expandafter\let
\csname @dtl@ro@\romannumeral\dtlforeachlevel\endcsname
= 1\relax
```

Iterate through each row.

```
\@dtlforeachrow(\dtl@thisidx,\dtl@thisrow)\in{#2}\do%
{%
```

Assign row number (not sure if this is needed here)

```
\csname dtl@row\romannumeral\dtlforeachlevel\endcsname
= \dtl@thisidx\relax
```

Store the current row specs for this level

```
\expandafter\global
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
= \expandafter{\dtl@thisrow}%
```

Assign commands to the required entries

```
\ifx\relax#3\relax
\else
```

Need to set \dtlcurrentrow for \@dtl@assign

```
\dtlcurrentrow=\expandafter{\dtl@thisrow}%
\@dtl@assign{#3}{#2}%
\fi
```

Do the main body of text if condition is satisfied

```
\ifthenelse{#1}%
{%
```

Increment user row counter

```
\refstepcounter{DTLrow\romannumeral\dtlforeachlevel}%
\expandafter\edef\expandafter\DTLcurrentindex%
\expandafter{%
```

```

        \arabic{DTLrow\romannumeral\dtlforeachlevel}}}%
    #4%
    }%
Condition not met so ignore
    {}%
    }%
Restore previous value of \DTLiffirstrow
    \expandafter\global\expandafter\let\expandafter\DTLiffirstrow
    \csname @dtl@iffirstrow\the\dtlforeachlevel\endcsname
Restore previous value of \DTLiflastrow
    \expandafter\global\expandafter\let\expandafter\DTLiflastrow
    \csname @dtl@iflastrow\the\dtlforeachlevel\endcsname
Restore previous value of \DTLifoddrow
    \expandafter\global\expandafter\let\expandafter\DTLifoddrow
    \csname @dtl@ifoddrow\the\dtlforeachlevel\endcsname
    }%
    \fi
Decrement level
    \global\advance\dtlforeachlevel by -1\relax
    }%
else part (data base doesn't exist):
    {%
    \PackageError{datatool}{Database '#2' doesn't exist}{}%
    }%
}

```

```
\@dtlifreadonly \@dtlifreadonly{<true part>}{<false part>}
```

Checks if current loop level is read only

```

\newcommand*{\@dtlifreadonly}[2]{%
\expandafter\ifx
\csname @dtl@ro@\romannumeral\dtlforeachlevel\endcsname1\relax

```

Read only

```

    #1%
    \else

```

Not read only

```

    #2%
    \fi
}

```

\DTLappendtorow

```
\DTLappendtorow{<key>}{<value>}
```

Appends entry to current row. (The current row is given by \@dtl@cur<n> where <n> is roman numeral value of \dtlforeachlevel. One level expansion is applied to <value>).

```
\newcommand*{\DTLappendtorow}[2]{%
  \ifnum\dtlforeachlevel=0\relax
    \PackageError{datatool}{\string\DTLappendrow\space can only be
      used inside \string\DTLforeach}{}%
  \else
```

Set \@dtl@thisdb to the current database name:

```
\expandafter\let\expandafter\@dtl@thisdb
  \csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
```

Check this isn't in \DTLforeach\*

```
\@dtlifreadonly
  {%
    \PackageError{datatool}{\string\DTLappendtorow\space can't
      be used inside \DTLforeach*}{The starred version of
      \string\DTLforeach\space is read only}%
  }%
  {%
```

Store current row number in \dtlrownum

```
\dtlrownum=
  \csname dtl@row\romannumeral\dtlforeachlevel\endcsname\relax
```

Update information about this column (adding new column if necessary)

```
\@dtl@updatekeys{\@dtl@thisdb}{#1}{#2}%
```

Get column index and store in \dtlcolumnnum

```
\expandafter\dtlcolumnnum\expandafter
  =\dtlcolumnindex{\@dtl@thisdb}{#1}\relax
```

Set \dtlcurrentrow to the current row

```
\dtlcurrentrow =
  \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
```

Does this row already have an entry with this key?

```
\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
  {\noexpand\dtl@entry}{\number\dtlcolumnnum}%
}%
\dtl@dogetentry
\ifx\dtl@entry\dtlnovalue
```

There are no entries in this row for the given key. Expand entry value before storing.

```
\protected@edef\@dtl@tmp{#2}%
\expandafter\@dtl@toks\expandafter{\@dtl@tmp}%
```

Append this entry to the current row.

```
\@dtl@toks@gput@right@cx{@dtl@cur\romannumeral\dtlforeachlevel}%
{%
  \noexpand\db@col@id@w \number\dtlcolumnnum
  \noexpand\db@col@id@end@
  \noexpand\db@col@elt@w \the\@dtl@toks
  \noexpand\db@col@elt@end@
  \noexpand\db@col@id@w \number\dtlcolumnnum
  \noexpand\db@col@id@end@
}%
```

Print information to terminal and log file if in verbose mode.

```
\dtl@message{Appended #1\space -> #2\space to database
  '\@dtl@thisdb'}%
\else
```

There is already an entry in this row for the given key

```
\PackageError{datatool}{Can't append entry to row:
  there is already an entry for key '#1' in this row}{}%
\fi
}%
\fi
}
```

moveentryfromrow

```
\DTLremoveentryfromrow{<key>}
```

Removes entry given by *<key>* from current row. (The current row is given by \@dtl@cur<n> where <n> is roman numeral value of \dtlforeachlevel.

```
\newcommand*{\DTLremoveentryfromrow}[1]{%
  \ifnum\dtlforeachlevel=0\relax
  \PackageError{datatool}{\string\DTLremoveentryfromrow\space
    can only be used inside \string\DTLforeach}{}%
  \else
```

Set \@dtl@thisdb to the current database name:

```
\expandafter\let\expandafter\@dtl@thisdb
  \csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
```

Check this isn't in \DTLforeach\*

```
\@dtlifreadonly
{%
  \PackageError{datatool}{\string\DTLremoveentryfromrow\space
    can't be used inside \string\DTLforeach*}{The starred
    version of \string\DTLforeach\space is read only}%
}%
{%
```



Store current row number in \dtlrownum

```
\dtlrownum=  
  \csname dtl@row\romannumeral\dtlforeachlevel\endcsname\relax
```

Is there a column corresponding to this key?

```
\@DTLifhaskey{\@dtl@thisdb}{#1}%  
{%
```

There exists a column for this key, so get the index:

```
\@dtl@getcolumnindex{\thiscol}{\@dtl@thisdb}{#1}\relax  
\dtlcolumnnum=\thiscol\relax
```

Set \dtlcurrentrow to the current row

```
\dtlcurrentrow =  
  \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
```

Does this row have an entry with this key?

```
\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow  
  {\noexpand\dtl@entry}{\number\dtlcolumnnum}%  
}%  
\dtl@dogetentry  
\ifx\dtl@entry\dtlnovalue
```

This row doesn't contain an entry with this key

```
\PackageError{datatool}{Can't remove entry given by '#1'  
  from current row in database '\@dtl@thisdb': no such  
  entry}{The current row doesn't contain an entry for  
  key '#1'}%  
\else
```

Split the current row around the unwanted entry

```
\edef\@dtl@dosplitrow{%  
  \noexpand\dtlsplitrow{\the\dtlcurrentrow}%  
  {\number\dtlcolumnnum}{\noexpand\dtl@pre}%  
  {\noexpand\dtl@post}%  
}%  
\@dtl@dosplitrow
```

Reconstruct row without unwanted entry

```
\expandafter\@dtl@toks\expandafter{\dtl@pre}%  
\expandafter\toks@\expandafter{\dtl@post}%  
\edef\@dtl@tmp{\the\@dtl@toks \the\toks@}%  
\dtlcurrentrow=\expandafter{\@dtl@tmp}%  
\expandafter\global  
  \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname  
  = \dtlcurrentrow  
\dtl@message{Removed entry given by #1\space from current  
  row of database '\@dtl@thisdb'}%  
\fi  
}%  
{%  
\PackageError{datatool}{Can't remove entry given by
```

```

        '#1' - no such key exists}{}%
    }%
  }%
\fi
}

```

placeentryforrow `\DTLreplaceentryforrow{<key>}{<value>}`

Replaces entry given by *<key>* in current row with *<value>*. (The current row is given by the token register `\@dtl@cur<n>` where *<n>* is roman numeral value of `\dtlforeachlevel`).

```

\newcommand*\DTLreplaceentryforrow[2]{%
  \ifnum\dtlforeachlevel=0\relax
    \PackageError{datatool}{\string\DTLreplaceentryforrow\space
      can only be used inside \string\DTLforeach}{}%
  \else

```

Set `\@dtl@thisdb` to the current database name:

```

  \expandafter\let\expandafter\@dtl@thisdb
  \csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname

```

Check this isn't in `\DTLforeach*`

```

\@dtlifreadonly
{%
  \PackageError{datatool}{\string\DTLreplaceentryforrow\space
    can't be used inside \string\DTLforeach*}{The starred version
    of \string\DTLforeach\space is read only}%
}%
{%

```

Store current row number in `\dtlrownum`

```

  \dtlrownum=
  \csname dtl@row\romannumeral\dtlforeachlevel\endcsname\relax

```

Is there a column corresponding to this key?

```

  \@DTLifhaskey{\@dtl@thisdb}{#1}%
  {%

```

There exists a column for this key, so get the index:

```

  \@dtl@getcolumnindex{\thiscol}{\@dtl@thisdb}{#1}\relax
  \dtlcolumnnum=\thiscol\relax

```

Set `\dtlcurrentrow` to the current row

```

  \dtlcurrentrow =
  \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname

```

Does this row have an entry with this key?

```

  \edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
    {\noexpand\dtl@entry}{\number\dtlcolumnnum}%
  }%

```

```

\dtl@dogetentry
\ifx\dtl@entry\dtlnovalue

```

This row doesn't contain an entry with this key

```

\PackageError{datatool}{Can't replace entry given by '#1'
from current row in database '@dtl@thisdb': no such
entry}{The current row doesn't contain an entry for
key '#1'}%
\else

```

Split the current row around the requested entry

```

\edef\dtl@dosplitrow{%
\noexpand\dtlsplitrow{\the\dtlcurrentrow}%
{\number\dtlcolumnnum}{\noexpand\dtl@pre}%
{\noexpand\dtl@post}%
}%
\dtl@dosplitrow

```

Reconstruct row with new value (given by #2).

```

\protected@edef\dtl@tmp{#2}%
\expandafter\dtl@toks\expandafter{\dtl@tmp}% new value
\expandafter\dtl@before\expandafter{\dtl@pre}%
\expandafter\dtl@after\expandafter{\dtl@post}%
\dtl@toks@gconcat@middle@cx
{\dtl@cur\romannumeral\dtlforeachlevel}%
{\dtl@before}%
{%
\noexpand\db@col@id@w \number\dtlcolumnnum
\noexpand\db@col@id@end@%
\noexpand\db@col@elt@w \the\dtl@toks
\noexpand\db@col@elt@end@%
\noexpand\db@col@id@w \number\dtlcolumnnum
\noexpand\db@col@id@end@%
}%
{\dtl@after}%

```

Print information to terminal and log file if in verbose mode.

```

\dtl@message{Updated #1\space -> #2\space in database
 '@dtl@thisdb'}%
\fi
}%
{%

```

There doesn't exist a column for this key.

```

\PackageError{datatool}{Can't replace key '#1' - no such
key in database '@dtl@thisdb'}{}%
}%
}%
\fi
}

```

removecurrentrow

`\DTLremovecurrentrow`

Removes current row. This just sets the current row to empty

```

\newcommand*\DTLremovecurrentrow{%
  \ifnum\dtlforeachlevel=0\relax
    \PackageError{datatool}{\string\DTLremovecurrentrow\space can
      only be used inside \string\DTLforeach}{}%
  \else

```

Set \@dtl@thisdb to the current database name:

```

\expandafter\let\expandafter\@dtl@thisdb
  \csname @dtl@dbname@romannumeral\dtlforeachlevel\endcsname

```

Check this isn't in \DTLforeach\*

```

\@dtlifreadonly
{%
  \PackageError{datatool}{\string\DTLreplaceentryforrow\space
    can't be used inside \string\DTLforeach*}{The starred version
    of \string\DTLforeach\space is read only}%
}%
{%

```

Set the current row to \@nil (\DTLforeach needs to check for this)

```

\expandafter\global
  \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
    ={\@nil}%
}%
\fi
}

```

TLaddentryforrow

`\DTLaddentryforrow{<db name>}{<assign list>}{<condition>}{<key>}{<value>}`

Adds the entry with key given by *<key>* and value given by *<value>* to the first row in the database *<db name>* which satisfies the condition given by *<condition>*. The *<assign list>* is the same as for \DTLforeach and may be used to set the values which are to be tested in *<condition>*.

```

\newcommand{\DTLaddentryforrow}[5]{%

```

Iterate through the data base until condition is met

```

\DTLifdbexists{#1}%
{%
  \def\@dtl@notdone{\PackageError{datatool}{Unable to add entry
    given by key '#4': condition not met for any row in database
    '#1'}{}}%

```

Iterate through each row

```
\DTLforeach[#3]{#1}{#2}%  
{%
```

add entry to this row

```
\DTLappendtorow{#4}{#5}%
```

disable error message

```
\let\@dtl@notdone\relax
```

break out of loop

```
\dtlbreak  
}%  
\@dtl@notdone  
}%  
{%  
\PackageError{datatool}{Unable to add entry given by key ‘#4’:  
database ‘#1’ doesn’t exist}{}%  
}%  
}
```

`\DTLforeachkeyinrow` `\DTLforeachkeyinrow{<cmd>}{<text>}`

Iterates through each key in the current row of `\DTLforeach`, and does `<text>`.

```
\newcommand*{\DTLforeachkeyinrow}[2]{%  
\ifnum\dtlforeachlevel=0\relax  
\PackageError{datatool}{\string\DTLforeachkeyinrow\space can only  
be used inside \string\DTLforeach}{}%  
\else
```

Set `\@dtl@thisdb` to the current database name:

```
\expandafter\let\expandafter\@dtl@thisdb  
\csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
```

Iterate through key list

```
\dtlforeachkey(\dtlkey,\dtlcol,\dtltype,\dtlheader)\in  
\@dtl@thisdb\do{%
```

store row in `\dtlcurrentrow` (This may get nested so need to do it here instead of outside this loop in case `<text>` changes it.)

```
\dtlcurrentrow =  
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
```

Get the value for this key and store in #1

```
\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow  
{\noexpand#1}{\dtlcol}}%  
\dtl@dogetentry
```

Check if null

```
\ifx#1\dtlnovalue  
  \ifnum0\dtltype=0\relax
```

Data type is *empty* or 0, so set to string null.

```
\let#1=\@dtlstringnull  
\else
```

Data type is numerical, so set to number null.

```
\let#1=\@dtlnumbernull  
\fi  
\fi
```

Make #1 global in case this is in a tabular environment (or something similar)

```
\global\let#1#1%
```

Store loop body so that any scoping commands (such as &) don't cause a problem for \ifx

```
\def\@dtl@loop@body{#2}%  
\@dtl@loop@body  
}%  
\fi  
}
```

## 4.6 DTLforeach Conditionals

The following conditionals are only meant to be used within \DTLforeach as they depend on the counter DTLrow $\langle n \rangle$ .

```
\DTLiffirstrow \DTLiffirstrow{\true part}{\false part}
```

Test if the current row is the first row. (This takes *condition*, the optional argument of \DTLforeach, into account, so it may not correspond to row 1 of the database.) Can only be used in \DTLforeachrow.

```
\newcommand{\DTLiffirstrow}[2]{%  
  \PackageError{datatool}{\string\DTLiffirstrow\space can only  
  be used inside \string\DTLforeach}{}%  
}
```

```
\DTLiflastrow \DTLiflastrow{\true part}{\false part}
```

Checks if the current row is the last row of the database. It doesn't take the condition (the optional argument of \DTLforeach) into account, so its possible it may never do *true part*, as the last row of the database may not meet the condition. It is therefore not very useful and is confusing since it behaves differently to \DTLiffirstrow which does take the condition

into account, so I have removed its description from the main part of the manual. If you need to use the optional argument of `\DTLforeach`, you will first have to iterate through the database to count up the number of rows which meet the condition, and then do another pass, checking if the current row has reached that number.

```
\newcommand{\DTLiflastrow}[2]{%
  \PackageError{datatool}{\string\DTLiflastrow\space can only
  be used inside \string\DTLforeach}{}%
}
```

`\DTLifodddrow` `\DTLifodddrow{<true part>}{<>false part>}`

Determines whether the current row is odd (takes the optional argument of `\DTLforeach` into account.)

```
\newcommand{\DTLifodddrow}[2]{%
  \PackageError{datatool}{\string\DTLifodddrow\space can only
  be used inside \string\DTLforeach}{}%
}
```

## 4.7 Displaying Database

This section defines commands to display the entire database in a tabular or longtable environment.

`\dtlbetweencols` This specifies what to put between the column alignment specifiers.

```
\newcommand*{\dtlbetweencols}{}
```

`\dtlbeforecols` This specifies what to put before the first column alignment specifier.

```
\newcommand*{\dtlbeforecols}{}
```

`\dtlaftercols` This specifies what to put after the last column alignment specifier.

```
\newcommand*{\dtlaftercols}{}
```

`\dtlstringalign` Alignment character for columns containing strings

```
\newcommand*{\dtlstringalign}{l}
```

`\dtlintalign` Alignment character for columns containing integers

```
\newcommand*{\dtlintalign}{r}
```

`\dtlrealalign` Alignment character for columns containing real numbers

```
\newcommand*{\dtlrealalign}{r}
```

`\dtlcurrencyalign` Alignment character for columns containing currency numbers

```
\newcommand*{\dtlcurrencyalign}{r}
```

`\dtladdalign` `\dtladdalign{<cs>}{<type>}{<col num>}{<max cols>}`

Adds tabular column alignment character to `<cs>` for column `<col num>` which contains data type `<type>`.

```
\newcommand*{\dtladdalign}[4]{%
  \ifnum#3=1\relax
    \protected@edef#1{\dtlbeforecols}%
  \else
    \protected@edef#1{#1\dtlbetweencols}%
  \fi
  \ifstrempy{#2}%
  {%
    \protected@edef#1{#1c}%
  }%
  {%
    \ifcase#2\relax
      string
        \protected@edef#1{#1\dtlstringalign}%
      \or
      integer
        \protected@edef#1{#1\dtlintalign}%
      \or
      real number
        \protected@edef#1{#1\dtlrealalign}%
      \or
      currency
        \protected@edef#1{#1\dtlcurrencyalign}%
      \else
      Unknown type
        \protected@edef#1{#1c}%
        \PackageError{datatool}{Unknown data type '#2'}{ }%
      \fi
    }%
  \ifnum#3=#4\relax
    \protected@edef#1{#1\dtlaftercols}%
  \fi
}
```

`\dtlheaderformat` `\dtlheaderformat{<text>}`

Specifies how to format the column title.

```
\newcommand*{\dtlheaderformat}[1]{\null\hfil\textbf{#1}\hfil\null}
```



<code>\dtlstringformat</code>	<code>\dtlstringformat{&lt;text&gt;}</code>
	Specifies how to format entries in columns with string data type. <code>\newcommand*{\dtlstringformat}[1]{#1}</code>
<code>\dtlintformat</code>	<code>\dtlintformat{&lt;text&gt;}</code>
	Specifies how to format entries in columns with integer data type. <code>\newcommand*{\dtlintformat}[1]{#1}</code>
<code>\dtlrealformat</code>	<code>\dtlrealformat{&lt;text&gt;}</code>
	Specifies how to format entries in columns with real data type. <code>\newcommand*{\dtlrealformat}[1]{#1}</code>
<code>\dtlcurrencyformat</code>	<code>\dtlcurrencyformat{&lt;text&gt;}</code>
	Specifies how to format entries in columns with currency data type. <code>\newcommand*{\dtlcurrencyformat}[1]{#1}</code>
<code>\dtldisplaystarttab</code>	Indicates what to do just after <code>\begin{tabular}{&lt;column specs&gt;}</code> (e.g. <code>\hline</code> ). <code>\newcommand*{\dtldisplaystarttab}{}</code>
<code>\dtldisplayendtab</code>	Indicates what to do just before <code>\end{tabular}</code> . <code>\newcommand*{\dtldisplayendtab}{}</code>
<code>\dtldisplayafterhead</code>	Indicates what to do after the header row, before the first row of data. <code>\newcommand*{\dtldisplayafterhead}{}</code>
<code>\dtldisplayvalign</code>	Stores the vertical alignment specifier for the tabular environment used in <code>\DTLdisplaydb</code> . <code>\newcommand*{\dtldisplayvalign}{c}</code>
<code>\dtldisplaystartrow</code>	Indicates what to do at the start of each row (not including the header row or the first row of data). <code>\newcommand*{\dtldisplaystartrow}{}</code>
<code>\dtldisplaycr</code>	<code>\newcommand{\dtldisplaycr}{\tabularnewline}</code>

`\DTLdisplaydb`

```
\DTLdisplaydb[<omit list>]{<db>}
```

Displays the database *<db>* in a tabular environment.

```
\newcommand*{\DTLdisplaydb}[2][{}]{%
```

Initialise: only want & between columns

```
\def\@dtl@doamp{\gdef\@dtl@doamp{&}}%
```

```
\def\@dtl@resetdoamp{\gdef\@dtl@doamp{\gdef\@dtl@doamp{&}}}%
```

Store maximum number of columns

```
\edef\@dtl@maxcols{\expandafter\number
```

```
\csname dtlcols@#2\endcsname}%
```

Subtract number of omitted columns

```
\DTLnumitemsinlist{#1}{\@dtl@tmp}%
```

```
\dtlsub{\@dtl@maxcols}{\@dtl@maxcols}{\@dtl@tmp}%
```

```
\dtlclip{\@dtl@maxcols}{\@dtl@maxcols}%
```

Argument for tabular environment

```
\def\@dtl@tabargs{}
```

```
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
```

```
\in{#2}\do
```

```
{%
```

```
\expandafter\DTLifinlist\expandafter{\@dtl@key}{#1}%
```

```
{}%
```

```
{%
```

```
\dtladdalign\@dtl@tabargs\@dtl@type\@dtl@idx\@dtl@maxcols
```

```
}%
```

```
}%
```

Begin tabular environment

```
\edef\@dtl@dobegintab{\noexpand\begin{tabular}[\dtl@displayvalign]{\@dtl@tabargs}}%
```

```
\@dtl@dobegintab
```

Do start hook

```
\dtl@displaystarttab
```

Reset `\@dtl@doamp` so it doesn't do an ampersand at the start of the first column.

```
\@dtl@resetdoamp
```

Do the header row.

```
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
```

```
\in{#2}\do
```

```
{%
```

```
\expandafter\DTLifinlist\expandafter{\@dtl@key}{#1}%
```

```
{}%
```

```
{%
```

```
\@dtl@doamp
```

```
\dtlheaderformat{\@dtl@head}%
```

```

    }%
  }%
  \\%

```

Do the after header hook

```
\dtldisplayafterhead
```

Reset `\@dtl@doamp` so it doesn't do an ampersand at the start of the first column.

```
\@dtl@resetdoamp
```

Iterate through each row of the database

```
\@sDTLforeach{#2}{}{%
```

Do the start row hook if not the first row

```
\DTLiffirstrow{ }\dtldisplaycr\dtldisplaystartrow}%
```

Reset `\@dtl@doamp` so it doesn't do an ampersand at the start of the first column.

```
\@dtl@resetdoamp
```

Iterate through each column.

```
\DTLforeachkeyinrow{\@dtl@val}%
  {%
    \expandafter\DTLifinlist\expandafter{\dtlkey}{#1}%
  }%
  {%

```

Need to make value global as it needs to be used after the ampersand.

```
\global\let\@dtl@val\@dtl@val
\@dtl@doamp
```

`\DTLforeachkeyinrow` sets `\dtltype` to the data type for the current key. This can be used to determine which format to use for this entry.

```

    \@dtl@datatype=0\dtltype\relax
    \ifcase\@dtl@datatype
      \dtlstringformat\@dtl@val
    \or
      \dtlintformat\@dtl@val
    \or
      \dtlrealformat\@dtl@val
    \or
      \dtlcurrencyformat\@dtl@val
    \else
      \@dtl@val
    \fi
  }%
}
\dtldisplayendtab
\end{tabular}%
}

```

Define keys to use in the optional argument of `\DTLdisplaylongdb`.

The caption key sets the caption for the longtable.

```
\define@key{displaylong}{caption}{\def\@dtl@cap{#1}}
```

The contcaption key sets the continuation caption for the longtable.

```
\define@key{displaylong}{contcaption}{\def\@dtl@contcap{#1}}
```

The shortcaption key sets the lof caption for the longtable.

```
\define@key{displaylong}{shortcaption}{\def\@dtl@shortcap{#1}}
```

The label key sets the label for the longtable.

```
\define@key{displaylong}{label}{\def\@dtl@label{#1}}
```

The foot key sets the longtable foot

```
\define@key{displaylong}{foot}{\def\@dtl@foot{#1}}
```

The lastfoot key sets the longtable last foot

```
\define@key{displaylong}{lastfoot}{\def\@dtl@lastfoot{#1}}
```

List of omitted columns

```
\define@key{displaylong}{omit}{\def\@dtl@omitlist{#1}}
```

resetdostartrow Resets start row hook so that it skips the first row.

```
\newcommand*\@dtl@resetdostartrow{%  
  \gdef\@dtl@dostartrow{%  
    \gdef\@dtl@dostartrow{\dtl@displaycr\dtl@displaystartrow}}%  
}
```

DTLdisplaylongdb

```
\DTLdisplaylongdb[options]{db}
```

Displays the database *db* in a longtable environment. (User needs to load longtable).

```
\newcommand*\DTLdisplaylongdb[2] []{%
```

Initialise.

```
  \def\@dtl@cap{\@nil}%  
  \def\@dtl@contcap{\@nil}%  
  \def\@dtl@label{\@nil}%  
  \def\@dtl@shortcap{\@dtl@cap}%  
  \def\@dtl@foot{\@nil}%  
  \def\@dtl@lastfoot{\@nil}%  
  \def\@dtl@omitlist{}
```

Set the options

```
  \setkeys{displaylong}{#1}%
```

Only want & between columns

```
  \def\@dtl@doamp{\gdef\@dtl@doamp{&}}%  
  \def\@dtl@resetdoamp{\gdef\@dtl@doamp{\gdef\@dtl@doamp{&}}}%  
  \@dtl@resetdostartrow
```

Store maximum number of columns

```
\edef\@dtl@maxcols{\expandafter\number  
\csname dtlcols@#2\endcsname}%
```

Subtract number of omitted columns

```
\DTLnumitemsinlist{\@dtl@omitlist}{\@dtl@tmp}%  
\dtlsub{\@dtl@maxcols}{\@dtl@maxcols}{\@dtl@tmp}%  
\dtlclip{\@dtl@maxcols}{\@dtl@maxcols}%
```

Argument for longtable environment

```
\def\@dtl@tabargs{}%  
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%  
\in{#2}\do  
{%  
\expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%  
}%  
{%  
\dtladdalign\@dtl@tabargs\@dtl@type\@dtl@idx\@dtl@maxcols  
}%  
}%
```

Start the longtable environment.

```
\edef\@dtl@dobegintab{\noexpand\begin{longtable}{\@dtl@tabargs}}%  
\@dtl@dobegintab
```

Is a foot required?

```
\ifx\@dtl@foot\@nnil  
\else  
\@dtl@foot\endfoot  
\fi
```

Is a last foot required?

```
\ifx\@dtl@lastfoot\@nnil  
\else  
\@dtl@lastfoot\endlastfoot  
\fi
```

Is a caption required?

```
\ifx\@dtl@cap\@nnil
```

No caption required, just do header row.

```
\@dtl@resetdoamp  
\dtldisplaystarttab  
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%  
\in{#2}\do  
{%  
\expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%  
}%  
{%  
\@dtl@doamp{\dtlheaderformat{\@dtl@head}}%  
}%  
}%
```

```

\@dtl@resetdoamp
\@dtl@resetdostartrow
\endhead\dtldisplayafterhead
\else
Caption is required
\caption[\@dtl@shortcap]{\@dtl@cap}%
Is a label required?
\ifx\@dtl@label\@nnil
\else
\label{\@dtl@label}%
\fi
\dtldisplaycr
Do start hook.
\dtldisplaystarttab
Do header row.
\@dtl@resetdoamp
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
\in{#2}\do
{%
\expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%
}%
\@dtl@doamp{\dtlheaderformat{\@dtl@head}}%
}%
\@dtl@resetdoamp
\dtldisplaycr\dtldisplayafterhead
\endfirsthead
Is a continuation caption required?
\ifx\@dtl@contcap\@nnil
\caption{\@dtl@cap}%
\else
\caption{\@dtl@contcap}%
\fi
Do start hook.
\dtldisplaycr\dtldisplaystarttab
Do header row.
\@dtl@resetdoamp
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
\in{#2}\do
{%
\expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%
}%

```

```

        \@dtl@doamp{\dtlheaderformat{\@dtl@head}}%
    }%
}%
\@dtl@resetdoamp
\@dtl@resetdostartrow

\dtldisplaycr\dtldisplayafterhead
\endhead
\fi

```

Iterate through each row of the database

```

\@sDTLforeach{#2}{-}{%
    \@dtl@dostartrow
    \@dtl@resetdoamp

```

Iterate through each column

```

\DTLforeachkeyinrow{\@dtl@val}%
{%
    \global\let\@dtl@val\@dtl@val
    \expandafter\DTLifinlist\expandafter{\dtlkey}{\@dtl@omitlist}%
}%
{%
    \@dtl@doamp

```

\DTLforeachkeyinrow sets \dtltype to the data type for the current key. This can be used to determine which format to use for this entry.

```

        \@dtl@datatype=0\dtltype\relax
        \ifcase\@dtl@datatype
            \dtlstringformat\@dtl@val
        \or
            \dtlintformat\@dtl@val
        \or
            \dtlrealformat\@dtl@val
        \or
            \dtlcurrencyformat\@dtl@val
        \fi
    }%
}%
}%
\dtldisplayendtab
\end{longtable}%
}

```

## 4.8 Editing Databases

```

\dtlswaprows \dtlswaprows{<db>}{<row1 idx>}{<row2 idx>}

```

Swaps the rows with indices  $\langle row1\ idx\rangle$  and  $\langle row2\ idx\rangle$  in the database  $\langle db\rangle$ . (Doesn't check if data base exists or if indices are out of bounds.)

```
\newcommand*{\dtlswaprows}[3]{%
  \ifnum#2=#3\relax
```

Attempt to swap row with itself: do nothing.

```
\else
```

Let row A be the row with the lower index and row B be the row with ther higher index.

```
\ifnum#2<#3\relax
  \edef\@dtl@rowAidx{\number#2}%
  \edef\@dtl@rowBidx{\number#3}%
\else
  \edef\@dtl@rowAidx{\number#3}%
  \edef\@dtl@rowBidx{\number#2}%
\fi
```

Split the database around row A.

```
\edef\@dtl@dospplit{\noexpand\dtlgetrow{#1}{\@dtl@rowAidx}}%
\@dtl@dospplit
```

Store first part of database in  $\@dtl@firstpart$ .

```
\expandafter\def\expandafter\@dtl@firstpart\expandafter
{\the\dtlbeforerow}%
```

Store row A in  $\@dtl@toksA$ .

```
\@dtl@toksA=\dtlcurrentrow
```

Split the second part (everything after row A).

```
\edef\@dtl@dospplit{\noexpand\@dtlgetrow
{\the\dtlafterrow}{\@dtl@rowBidx}}%
\@dtl@dospplit
```

Store the mid part (everything between row A and row B)

```
\expandafter\def\expandafter\@dtl@secondpart\expandafter
{\the\dtlbeforerow}%
```

Store row B in  $\@dtl@toksB$ .

```
\@dtl@toksB=\dtlcurrentrow
```

Store the last part (everything after row B).

```
\expandafter\def\expandafter\@dtl@thirdpart\expandafter
{\the\dtlafterrow}%
```

Reconstruct database: store first part in  $\toks@$

```
\toks@=\expandafter{\@dtl@firstpart}%
```

Store mid part in  $\dtl@toks$

```
\@dtl@toks=\expandafter{\@dtl@secondpart}%
```

Format data for first part, row B and mid part.

```
\edef\@dtl@tmp{\the\toks@
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \@dtl@rowAidx\noexpand\db@row@id@end@%
```



```

\the\@dtl@toksB
\noexpand\db@row@id@w \@dtl@rowAidx\noexpand\db@row@id@end@%
\noexpand\db@row@elt@end@%
\the\@dtl@toks}%

```

Store data so far in \toks@.

```
\toks@=\expandafter{\@dtl@tmp}%
```

Store last part in \dtl@toks.

```
\@dtl@toks=\expandafter{\@dtl@thirdpart}%
```

Format row A and end part.

```

\edef\@dtl@tmp{\the\toks@
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \@dtl@rowBidx\noexpand\db@row@id@end@%
\the\@dtl@toksA
\noexpand\db@row@id@w \@dtl@rowBidx\noexpand\db@row@id@end@%
\noexpand\db@row@elt@end@%
\the\@dtl@toks}%

```

Update the database

```

\expandafter\global\csname dtldb@#1\endcsname=\expandafter
{\@dtl@tmp}%
\fi
}

```

l@decrementrows

```
\dtl@decrementrows{<toks>}{<n>}
```

decrement by 1 all rows in <toks> with row index above <n>

```

\newcommand*{\dtl@decrementrows}[2]{%
\def\@dtl@newlist{}%
\edef\@dtl@min{\number#2}%
\expandafter\@dtl@decrementrows\the#1%
\db@row@elt@w%
\db@row@id@w \@nil\db@row@id@end@%
\db@row@id@w \@nil\db@row@id@end@%
\db@row@elt@end@%
\@nil
#1=\expandafter{\@dtl@newlist}%
}

```

l@decrementrows

```

\def\@dtl@decrementrows\db@row@elt@w\db@row@id@w #1\db@row@id@end@%
#2\db@row@id@w #3\db@row@id@end@\db@row@elt@end@#4\@nil{%
\def\@dtl@thisrow{#1}%
\ifx\@dtl@thisrow\@nnil
\let\@dtl@donextdec=\@dtl@gobbletonil
\else

```

```

\ifnum\@dtl@thisrow>\@dtl@min
  \@dtl@tmpcount=\@dtl@thisrow\relax
  \advance\@dtl@tmpcount by -1\relax
  \toks@{#2}%
  \@dtl@toks=\expandafter{\@dtl@newlist}%
  \edef\@dtl@newlist{\the\@dtl@toks
    \noexpand\db@row@elt@w% row header
    \noexpand\db@row@id@w \number\@dtl@tmpcount
    \noexpand\db@row@id@end@% row id
    \the\toks@ % row contents
    \noexpand\db@row@id@w \number\@dtl@tmpcount
    \noexpand\db@row@id@end@% row id
    \noexpand\db@row@elt@end@% row end
  }%
\else
  \toks@{#2}%
  \@dtl@toks=\expandafter{\@dtl@newlist}%
  \edef\@dtl@newlist{\the\@dtl@toks
    \noexpand\db@row@elt@w% row header
    \noexpand\db@row@id@w #1%
    \noexpand\db@row@id@end@% row id
    \the\toks@ % row contents
    \noexpand\db@row@id@w #3%
    \noexpand\db@row@id@end@% row id
    \noexpand\db@row@elt@end@% row end
  }%
\fi
\let\@dtl@donextdec=\@dtl@decrementrows
\fi
\@dtl@donextdec#4\@nil
}

```

`\DTLremove`row `\DTLremove`row{<db>}{<row index>}

Remove row with given index from database named <db>.

```
\newcommand*\DTLremove
```

Check database exists

```
\DTLifdbexists{#1}%
{%
```

Check index if index is out of bounds

```
\ifnum#2>0\relax
```

Check if data base has at least <row index> rows

```
\expandafter\ifnum\csname dtlrows@#1\endcsname<#2\relax
\expandafter\ifnum\csname dtlrows@#1\endcsname=1\relax
\PackageError{datatool}{Can't remove row '\number#2' from
```

```

        database '#1': no such row}{Database '#1' only has
        1 row}%
    \else
        \PackageError{datatool}{Can't remove row '\number#2' from
        database '#1': no such row}{Database '#1' only has
        \expandafter\number\csname dtlrows@#1\endcsname\space
        rows}%
    \fi
\else
    \@DTLremoveoverrow{#1}{#2}%
\fi
\else
    \PackageError{datatool}{Can't remove row \number#2: index
    out of bounds}{Row indices start at 1}%
\fi
}%
{%
    \PackageError{datatool}{Can't remove row: database '#1' doesn't
    exist}{}%
}%
}

```

`\@DTLremoveoverrow` `\@DTLremoveoverrow{<db>}{<row index>}`

Doesn't perform any checks for the existence of the database or if the index is in range.

```
\newcommand*{\@DTLremoveoverrow}[2]{%
```

Get row from data base

```

    \edef\dtl@dogetrow{\noexpand\dtlgetrow{#1}{\number#2}}%
    \dtl@dogetrow

```

Update the row indices

```

    \expandafter\dtl@decrementrows\expandafter
    {\dtlbeforeoverrow}{#2}%
    \expandafter\dtl@decrementrows\expandafter
    {\dtlafteroverrow}{#2}%

```

Reconstruct database

```

    \edef\dtl@tmp{\the\dtlbeforeoverrow \the\dtlafteroverrow}%
    \expandafter\global\csname dtldb@#1\endcsname
    =\expandafter{\dtl@tmp}%

```

decrement row counter

```

    \expandafter\global\expandafter\advance
    \csname dtlrows@#1\endcsname by -1\relax
}

```

## 4.9 Database Functions

`\DTLsumforkeys` `\DTLsumforkeys[<condition>][<assign list>]{<db list>}{<key list>}{<cmd>}`

Sums all entries for key *<key>* over all databases listed in *<db list>*, and stores in *<cmd>*, which must be a control sequence. The first argument *<condition>* is the same as that for `\DTLforeach`. The second optional argument provides an assignment list to pass to `\DTLforeach` in case extra information is needed by *<condition>*.

```
\newcommand*\DTLsumforkeys[1][\boolean{true}\and
\DTLisnumerical{\DTLthisval}] {%
\def\@dtl@cond{#1}%
\@dtlsumforkeys
}
```

`\@dtlsumforkeys`

```
\newcommand*\@dtlsumforkeys[4][ ] {%
\def#4{0}%
```

Iterate over all the listed data bases

```
\@for\@dtl@db@name:=#2\do{%
```

Iterate through this database (using read only version)

```
\@sDTLforeach{\@dtl@db@name}%
{#1}% assignment list
{%
```

Iterate through key list.

```
\@for\@dtl@key:=#3\do{%
\@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
\dtlcurrentrow=\expandafter{\dtl@thisrow}%
\dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
\expandafter\ifthenelse\expandafter{\@dtl@cond}%
{\DTLadd{#4}{#4}{\DTLthisval}}{ }%
}%
}%
}%
}
```

`\DTLsumcolumn` `\DTLsumcolumn{<db>}{<key>}{<cmd>}`

Quicker version of `\DTLsumforkeys` that just sums over one column (specified by *<key>*) for a single database (specified by *<db>*) and stores the result in *<cmd>*.

```
\newcommand*\DTLsumcolumn[3]{%
\def#3{0}%
```

Check data base exists

```
\DTLifdbexists{#1}%  
{%
```

Check column exists

```
\@sDTLifhaskey{#1}{#2}%  
{%  
  \@sdtlforcolumn{\DTLthisval}{#1}{#2}%  
  {%  
    \DTLadd{#3}{#3}{\DTLthisval}%  
  }%  
}%
```

key not defined for this data base

```
{%  
  \PackageError{datatool}{Key ‘#2’ doesn’t  
    exist in database ‘#1’}{}%  
}%  
}%
```

data base doesn't exist

```
{%  
  \PackageError{datatool}{Data base ‘#1’ doesn’t  
    exist}{}%  
}%  
}
```

```
\DTLmeanforkeys \DTLmeanforkeys[<condition>][<assign list>]{<db list>}{<key list>}{<cmd>}
```

Computes the arithmetic mean of all entries for each key in *<key list>* over all databases in *<db list>*, and stores in *<cmd>*, which must be a control sequence. The first argument *<condition>* is the same as that for `\DTLforeach`. The second optional argument allows an assignment list to be passed to `\DTLforeach`.

```
\newcommand*{\DTLmeanforkeys}[1][\boolean{true}]\and  
\DTLisnumerical{\DTLthisval}{%  
  \def\@dtl@cond{#1}%  
  \@dtlmeanforkeys  
}
```

```
\@dtl@elements Count register to keep track of number of elements
```

```
\newcount\@dtl@elements
```

```
@dtlmeanforkeys
```

```
\newcommand*{\@dtlmeanforkeys}[4][[]]{%  
  \def#4{0}%  
  \@dtl@elements=0\relax
```

Iterate over all the listed data bases

```
\@for\@dtl@db@name:=#2\do{%
```

Iterate through this database (using read only version)

```
\@sDTLforeach{\@dtl@db@name}%  
{#1}% assignment list  
{%
```

Iterate through key list.

```
\@for\@dtl@key:=#3\do{%  
  \@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%  
  \dtlcurrentrow=\expandafter{\dtl@thisrow}%  
  \dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%  
  \expandafter\ifthenelse\expandafter{\@dtl@cond}%  
  {%  
    \DTLadd{#4}{#4}{\DTLthisval}%  
    \advance\@dtl@elements by 1\relax  
  }{ }%  
}%  
}%  
}%
```

Divide total by number of elements summed.

```
\ifnum\@dtl@elements=0\relax  
  \PackageError{datatool}{Unable to evaluate mean: no data}{ }%  
\else  
  \edef\@dtl@n{\number\@dtl@elements}%  
  \DTLdiv{#4}{#4}{\@dtl@n}%  
\fi  
}
```

DTLmeanforcolumn `\DTLmeanforcolumn{<db>}{<key>}{<cmd>}`

Quicker version of `\DTLmeanforkeys` that just computes the mean over one column (specified by `<key>`) for a single database (specified by `<db>`) and stores the result in `<cmd>`.

```
\newcommand*{\DTLmeanforcolumn}[3]{%  
  \def#3{0}%  
  \@dtl@elements=0\relax
```

Check data base exists

```
\DTLifdbexists{#1}%  
{%
```

Check column exists

```
\@sDTLifhaskey{#1}{#2}%  
{%  
  \@sdtlforcolumn{\DTLthisval}{#1}{#2}%  
  {%
```

```

        \DTLadd{#3}{#3}{\DTLthisval}%
        \advance\@dtl@elements by 1\relax
    }%
    \ifnum\@dtl@elements=0\relax
        \PackageError{datatool}{Can't compute mean for
            column '#2' in database '#1': no data}{}%
    \else
        \edef\@dtl@n{\number\@dtl@elements}%
        \DTLdiv{#3}{#3}{\@dtl@n}%
    \fi
}

```

key not defined for this data base

```

    {%
        \PackageError{datatool}{Key '#2' doesn't
            exist in database '#1'}{}%
    }%
}

```

data base doesn't exist

```

    {%
        \PackageError{datatool}{Data base '#1' doesn't
            exist}{}%
    }%
}

```

\DTLvarianceforkeys

```

\DTLvarianceforkeys[<condition>][<assign list>]{<db list>}{<key list>}
{<cmd>}

```

Computes the variance of all entries for each key in *<key list>* over all databases in *<db list>*, and stores in *<cmd>*, which must be a control sequence. The first optional argument *<condition>* is the same as that for `\DTLforeach`. The second optional argument is an assignment list to pass to `\DTLforeach` in case it is required for the condition.

```

\newcommand*\DTLvarianceforkeys[1][\boolean{true}\and
\DTLisnumerical{\DTLthisval}]{%
\def\@dtl@cond{#1}%
\@dtlvarianceforkeys
}

```

@dtlmeanforkeys

```

\newcommand*\@dtlvarianceforkeys[4][[]]{%
\@dtlmeanforkeys[#1]{#2}{#3}{\dtl@mean}%
\def#4{0}%
\@dtl@elements=0\relax

```

Iterate over all the listed data bases

```

\@for\@dtl@db@name:=#2\do{%

```

Iterate through this database (using read only version)

```
\@sDTLforeach{\@dtl@db@name}%
{#1}% assignment list
{%
```

Iterate through key list.

```
\@for\@dtl@key:=#3\do{%
  \@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
  \dtlcurrentrow=\expandafter{\dtl@thisrow}%
  \dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
  \expandafter\ifthenelse\expandafter{\@dtl@cond}%
  {%
```

compute  $(x_i - \mu)^2$

```
  \DTLsub{\dtl@diff}{\DTLthisval}{\dtl@mean}%
  \DTLmul{\dtl@diff}{\dtl@diff}{\dtl@diff}%
  \DTLadd{#4}{#4}{\dtl@diff}%
  \advance\@dtl@elements by 1\relax
}%
}%
}%
}%
```

Divide by number of elements.

```
\ifnum\@dtl@elements=0\relax
  \PackageError{datatool}{Unable to evaluate variance: no data}{}%
\else
  \edef\@dtl@n{\number\@dtl@elements}%
  \DTLdiv{#4}{#4}{\@dtl@n}%
\fi
}
```

varianceforcolumn

```
\DTLvarianceforcolumn{<db>}{<key>}{<cmd>}
```

Quicker version of `\DTLvarianceforkeys` that just computes the variance over one column (specified by `<key>`) for a single database (specified by `<db>`) and stores the result in `<cmd>`.

```
\newcommand*\DTLvarianceforcolumn}[3]{%
  \DTLmeanforcolumn{#1}{#2}{\dtl@mean}%
  \def#3{0}%
  \@dtl@elements=0\relax
```

Check data base exists

```
\DTLifdbexists{#1}%
{%
```

Check column exists

```
\@sDTLifhaskey{#1}{#2}%
{%
```



```

\@sdtlforcolumn{\DTLthisval}{#1}{#2}%
{%
compute (xi - μ)2
\DTLsub{\dtl@diff}{\DTLthisval}{\dtl@mean}%
\DTLmul{\dtl@diff}{\dtl@diff}{\dtl@diff}%
\DTLadd{#3}{#3}{\dtl@diff}%
\advance\@dtl@elements by 1\relax
}%
\ifnum\@dtl@elements=0\relax
\PackageError{datatool}{Can't compute variance for
column '#2' in database '#1': no data}{}%
\else
\edef\@dtl@n{\number\@dtl@elements}%
\DTLdiv{#3}{#3}{\@dtl@n}%
\fi
}%
key not defined for this data base
{%
\PackageError{datatool}{Key '#2' doesn't
exist in database '#1'}{}%
}%
}%
data base doesn't exist
{%
\PackageError{datatool}{Data base '#1' doesn't
exist}{}%
}%
}

```

```

\DTLsdforkeys \DTLsdforkeys [<condition>] [<assign list>] {<db list>} {<key list>} {<cmd>}

```

Computes the standard deviation of all entries for each key in *<key list>* over all databases in *<db list>*, and stores in *<cmd>*, which must be a control sequence. The first optional argument *<condition>* is the same as that for `\DTLforeach`. The second optional argument is an assignment list for `\DTLforeach` in case it is needed for the condition.

```

\newcommand*{\DTLsdforkeys}[1][\boolean{true}]\and
\DTLisnumerical{\DTLthisval}{}%
\def\@dtl@cond{#1}%
\@dtl@sdforkeys
}

```

```

\@dtl@sdforkeys

```

```

\newcommand*{\@dtl@sdforkeys}[4][[]]{%
\@dtl@varianceforkeys[#1]{#2}{#3}{#4}%

```

```

\DTLsqrt{#4}{#4}%
}

```

```

\DTLsdforcolumn \DTLsdforcolumn{<db>}{<key>}{<cmd>}

```

Quicker version of `\DTLsdforkeys` that just computes the standard deviation over one column (specified by `<key>`) for a single database (specified by `<db>`) and stores the result in `<cmd>`.

```

\newcommand*\DTLsdforcolumn}[3]{%
\DTLvarianceforcolumn{#1}{#2}{#3}%
\DTLsqrt{#3}{#3}%
}

```

```

\DTLminforkeys \DTLminforkeys [<condition>] [<assign list>]{<db list>}{<key list>}{<cmd>}

```

Determines the minimum over all entries for each key in `<key list>` over all databases in `<db list>`, and stores in `<cmd>`, which must be a control sequence. The first optional argument `<condition>` is the same as that for `\DTLforeach`. The second optional argument is an assignment list for `\DTLforeach` in the event that extra information is need for the condition.

```

\newcommand*\DTLminforkeys}[1] [\boolean{true}]\and
\DTLisnumerical{\DTLthisval}] {%
\def\@dtl@cond{#1}%
\@dtlminforkeys
}

```

```

\@dtlminforkeys

```

```

\newcommand*\@dtlminforkeys}[4] [] {%
\def#4{%

```

Iterate over all the listed data bases

```

\@for\@dtl@db@name:=#2\do{%

```

Iterate through this database (using read only version)

```

\@sDTLforeach{\@dtl@db@name}%
{#1}% assignment list
{%

```

Iterate through key list.

```

\@for\@dtl@key:=#3\do{%
\@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
\dtlcurrentrow=\expandafter{\dtl@thisrow}%
\dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
\expandafter\ifthenelse\expandafter{\@dtl@cond}%
{%

```





```
}%
}
```

\DTLmaxforcolumn

```
\DTLmaxforcolumn{<db>}{<key>}{<cmd>}
```

Quicker version of \DTLmaxforkeys that just finds the maximum value in one column (specified by <key>) for a single database (specified by <db>) and stores the result in <cmd>.

```
\newcommand*{\DTLmaxforcolumn}[3]{%
  \def#3{}
```

Check data base exists

```
\DTLifdbexists{#1}%
{%
```

Check column exists

```
\@sDTLifhaskey{#1}{#2}%
{%
  \@sdtlforcolumn{\DTLthisval}{#1}{#2}%
  {%
    \ifdefempty{#3}%
    {%
      \let#3\DTLthisval
    }%
    {%
      \DTLmax{#3}{#3}{\DTLthisval}%
    }%
  }%
}%
```

key not defined for this data base

```
{%
  \PackageError{datatool}{Key ‘#2’ doesn’t
    exist in database ‘#1’}{}%
}%
}
```

data base doesn't exist

```
{%
  \PackageError{datatool}{Data base ‘#1’ doesn’t
    exist}{}%
}%
}
```

\DTLcomputebounds

```
\DTLcomputebounds[<condition>]{<db list>}{<x key>}{<y key>}{<minX cmd>}
{<minY cmd>}{<maxX cmd>}{<maxY cmd>}
```

Computes the maximum and minimum  $x$  and  $y$  values over all the databases listed in  $\langle db\ list \rangle$  where the  $x$  value is given by  $\langle x\ key \rangle$  and the  $y$  value is given by  $\langle y\ key \rangle$ . The results are stored in  $\langle minX\ cmd \rangle$ ,  $\langle minY\ cmd \rangle$ ,  $\langle maxX\ cmd \rangle$  and  $\langle maxY\ cmd \rangle$  in standard decimal format.

```

\newcommand*{\DTLcomputebounds}[8][\boolean{true}] {%
\let#5=\relax
\let#6=\relax
\let#7=\relax
\let#8=\relax
\@for\dtl@thisdb:=#2\do{%
\@sDTLforeach[#1]{\dtl@thisdb}{\DTLthisX=#3,\DTLthisY=#4}{%
\expandafter\DTLconverttodecimal\expandafter{\DTLthisX}{\dtl@decx}%
\expandafter\DTLconverttodecimal\expandafter{\DTLthisY}{\dtl@decy}%
\ifx#5\relax
\let#5=\dtl@decx
\let#6=\dtl@decy
\let#7=\dtl@decx
\let#8=\dtl@decy
\else
\dtlmin{#5}{#5}{\dtl@decx}%
\dtlmin{#6}{#6}{\dtl@decy}%
\dtlmax{#7}{#7}{\dtl@decx}%
\dtlmax{#8}{#8}{\dtl@decy}%
\fi
}%
}%
}

```

TLgetvalueforkey

```
\DTLgetvalueforkey{\langle cmd \rangle}{\langle key \rangle}{\langle db name \rangle}{\langle ref key \rangle}{\langle ref value \rangle}
```

This (globally) sets  $\langle cmd \rangle$  (a control sequence) to the value of the key specified by  $\langle key \rangle$  in the first row of the database called  $\langle db\ name \rangle$  which contains the key  $\langle ref\ key \rangle$  which has the value  $\langle value \rangle$ .

```
\newcommand*{\DTLgetvalueforkey}[5] {%
```

Get row containing referenced (key,value) pair

```
\DTLgetrowforkey{\@dtl@row}{#3}{#4}{#5}%
```

Get column number for  $\langle key \rangle$

```
\@sdtl@getcolumnindex{\@dtl@col}{#3}{#2}%
```

Get value for given column

```

{%
\dtlcurrentrow=\expandafter{\@dtl@row}%
\edef\@dtl@dogetval{\noexpand\dtlgetentryfromcurrentrow
{\noexpand\@dtl@val}{\@dtl@col}}%
\@dtl@dogetval
\global\let#1=\@dtl@val
}

```

```

    }%
}

```

```

\DTLgetrowforkey \DTLgetrowforkey{<cmd>}{<db name>}{<ref key>}{<ref value>}

```

This (globally) sets *<cmd>* (a control sequence) to the first row of the database called *<db name>* which contains the key *<ref key>* that has the value *<value>*.

```

\newcommand*{\DTLgetrowforkey}[4]{%
  \global\let#1=\@empty
  \@sDTLforeach{#2}{\dtl@refvalue=#3}{%
    \DTLifnull{\dtl@refvalue}%
    {}%
    {%
      \ifthenelse{\equal{\dtl@refvalue}{#4}}{%
        {%
          \xdef#1{\the\dtlcurrentrow}%
          \dtlbreak
        }%
      }%
    }%
  }%
}

```

## 4.10 Sorting Databases

```

\@dtl@list Token register to store data when sorting.
  \newtoks\@dtl@list

```

```

\DTLsort \DTLsort[<replacement keys>]{<sort criteria>}{<db name>}

```

Sorts database *<db name>* according to *{<sort criteria>}*, which must be a comma separated list of keys, and optionally *=<order>*, where *<order>* is either ascending or descending. The optional argument is a list of keys to uses if the given key has a null value. The starred version uses a case insensitive string comparison.

```

\newcommand*{\DTLsort}{\@ifstar\@sDTLsort\@DTLsort}

```

```

\@DTLsort Unstarred (case sensitive) version.
  \newcommand{\@DTLsort}[3][ ]{%
    \dtlsort[#1]{#2}{#3}{\dtlcompare}%
  }

```

```

\@sDTLsort Starred (case insensitive) version.
  \newcommand*{\@sDTLsort}[3] [] {%
    \dtlsort[#1]{#2}{#3}{\dtlicompare}%
  }

```

```

\dtlsort \dtlsort[<replacement keys>]{<sort criteria>}{<db name>}{<handler>}

```

More general version where user supplies a handler for the comparison.

```

\newcommand{\dtlsort}[4] [] {%

```

Check the database exists

```

  \DTLifdbexists{#3}%
  {%
    \ifnum\DTLrowcount{#3}>100\relax
      \typeout{Sorting ‘#3’ - this may take a while.}%
    \fi

```

Store replacement keys in \@dtl@replacementkeys.

```

  \edef\@dtl@replacementkeys{#1}%

```

Store sort order in \@dtl@sortorder, but check specified keys exist.

```

  \def\@dtl@sortorder{}%
  \@for\@dtl@level:=#2\do
  {%

```

Get key (stored in \@dtl@key).

```

    \expandafter\@dtl@getsortdirection\@dtl@level=\relax

```

Check key exists.

```

    \DTLifhaskey{#3}{\@dtl@key}%
    {%

```

Key exists, so add to \@dtl@sortorder.

```

      \ifdefempty\@dtl@sortorder
        {\let\@dtl@sortorder=\@dtl@level}%
        {\eappto\@dtl@sortorder{,\@dtl@level}}%
      }%
    {%

```

Key doesn't exist.

```

      \PackageError{datatool}%
      {%
        Can't sort on ‘\@dtl@level’.
        No such key ‘\@dtl@key’ in database ‘#3’%
      }{}%
    }%
  }%

```



Now check if we have any keys left to sort on.

```
\ifdefempty\@dtl@sortorder
{%
  \PackageWarning{datatool}{No keys provided to sort database ‘#3’}%
}%
{%
```

Set `\@dtl@comparecs` to the required string comparison function. (Using case insensitive comparison macro `\dtlicompare`.)

```
\let\@dtl@comparecs=#4%
```

Sort the database.

```
\dtl@sortdata{#3}%
}%
}%
{%
  \PackageError{datatool}{Database ‘#3’ doesn’t exist}{}%
}%
}
```

`\@dtl@rowa` Token register to store first row when sorting.

```
\newtoks\@dtl@rowa
```

`\@dtl@rowb` Token register to store comparison row when sorting.

```
\newtoks\@dtl@rowb
```

```
\dtl@sortdata \dtl@sortdata{<db>}
```

Sorts the data in named database using an insertion sort algorithm. `\@dtl@replacementkeys`, `\@dtl@sortorder` and `\@dtl@comparecs` must be set prior to use.

```
\newcommand*{\dtl@sortdata}[1]{%
```

Initialise macro containing sorted data.

```
\def\@dtl@sortedlist{}%
```

Store database name.

```
\edef\@dtl@dbname{#1}%
```

Iterate through each row and insert into sorted list.

```
\@dtlforeachrow(\@dtl@rowAnum,\@dtl@rowAcontents)\in\@dtl@dbname\do{%
  \@dtl@rowa=\expandafter{\@dtl@rowAcontents}%
```

Create a temporary list

```
\def\@dtl@newlist{}%
```

Initialise the insertion for this iteration. Insertion hasn't been done yet.

```
\@dtl@insertdonefalse
```

Initialise row index to 0

```
\dtlrownum=0\relax
```

Iterate through sorted list.

```
\expandafter\@dtl@foreachrow\@dtl@sortedlist
\db@row@elt@w%
\db@row@id@w \@nil\db@row@id@end@%
\db@row@id@w \@nil\db@row@id@end@%
\db@row@elt@end@%
\@@{\@dtl@rowBnum}{\@dtl@rowBcontents}%
{%
```

Store row B in a token register

```
\@dtl@rowb=\expandafter{\@dtl@rowBcontents}%
```

Get current row number of sorted list

```
\dtlrownum=\@dtl@rowBnum
```

Has the insertion been done?

```
\if@dtl@insertdone
```

New element has already been inserted, so just increment the row number to compensate for the inserted row.

```
\advance\dtlrownum by 1\relax
\else
```

Insertion hasn't been done yet. Compare row A and row B.

```
\@dtl@sortcriteria{\@dtl@rowa}{\@dtl@rowb}%
```

If \dtl@sortresult is negative insert A before B.

```
\ifnum\dtl@sortresult<0\relax
```

Insert row A into new list. First store \@dtl@newlist in \toks@.

```
\toks@=\expandafter{\@dtl@newlist}%
```

Update \@dtl@newlist to be the old value followed by row A.

```
\edef\@dtl@newlist{%
```

Old value:

```
\the\toks@
```

Format row A

```
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end@%
\the\@dtl@rowa
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end@%
\noexpand\db@row@elt@end@%
}%
```

Increment row number to compensate for inserted row.

```
\advance\dtlrownum by 1\relax
```

Mark insertion done.

```
\@dtl@insertdonetrue
\fi
\fi
```

Insert row B

```
\toks@=\expandafter{\@dtl@newlist}%
\edef\@dtl@newlist{\the\toks@
```

row B

```
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end%
\the\@dtl@rowb
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end%
\noexpand\db@row@elt@end%
}%
```

Repeat loop.

```
}\q@nil
```

If row A hasn't been inserted, do so now.

```
\if@dtl@insertdone
\else
```

\dtlrownum contains the index of the last row in new list, So increment it to get the new index for row A.

```
\advance\dtlrownum by 1\relax
```

Insert row A.

```
\toks@=\expandafter{\@dtl@newlist}%
\edef\@dtl@newlist{\the\toks@
```

row A

```
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end%
\the\@dtl@rowa
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end%
\noexpand\db@row@elt@end%
}%
\fi
```

Set sorted list to new list.

```
\let\@dtl@sortedlist=\@dtl@newlist
}%
```

Update database.

```
\expandafter\global\csname dtldb@#1\endcsname=\expandafter
{\@dtl@sortedlist}%
}
```

dtl@sortcriteria

```
\@dtl@sortcriteria{<row a toks>}{<row b toks>}
```

\@dtl@dbname and \@dtl@sortorder must be set before use \@dtl@sortorder is a comma separated list of either just keys or <key>=<direction>. (Check keys are valid before use.)

```
\newcommand{\@dtl@sortcriteria}[2]{%
```

Iterate through the sort order.

```
\@for\@dtl@level:=\@dtl@sortorder\do  
{%
```

Set \@dtl@sortdirection to -1 (ascending) or +1 (descending). Key is stored in \@dtl@key.

```
\expandafter\@dtl@getsortdirection\@dtl@level=\relax
```

Initially comparing on the same key

```
\let\@dtl@keya=\@dtl@key  
\let\@dtl@keyb=\@dtl@key
```

Get values corresponding to key from both rows. First get column index corresponding to key.

```
\@sdtl@getcolumnindex{\@dtl@col}{\@dtl@dbname}{\@dtl@key}%
```

Get entry for this column from row A and store in \@dtl@a.

```
\dtlgetentryfromrow{\@dtl@a}{\@dtl@col}{#1}%
```

Get entry for this column from row B and store in \@dtl@b.

```
\dtlgetentryfromrow{\@dtl@b}{\@dtl@col}{#2}%
```

Has value from row A been defined?

```
\ifx\@dtl@a\dtlnovalue
```

Value hasn't been defined so set to null

```
\@dtl@setnull{\@dtl@a}{\@dtl@key}%  
\fi
```

Has value from row B been defined?

```
\ifx\@dtl@b\dtlnovalue
```

Value hasn't been defined so set to null

```
\@dtl@setnull{\@dtl@b}{\@dtl@key}%  
\fi
```

Check if value for row A is null.

```
\DTLifnull{\@dtl@a}%  
{%
```

Value for row A is null, so find the first non null key in list of replacement keys.

```
\@for\@dtl@keya:=\@dtl@replacementkeys\do{%
```

Get column corresponding to this key.

```
\@sdtl@getcolumnindex{\@dtl@col}{\@dtl@dbname}{\@dtl@keya}%  
\dtlgetentryfromrow{\@dtl@a}{\@dtl@col}{#1}%
```

Has value for row A been defined?

```
\ifx\@dtl@a\dtlnovalue
```

Value for row A hasn't been defined so set to null

```
\@dtl@setnull{\@dtl@a}{\@dtl@key}%  
\fi
```

Is value for row A null? If not null end the loop.

```
\DTLifnull{\@dtl@a}{}\@endfortrue}%  
}%
```

No non-null value found.

```
\ifx\@dtl@keya\@nnil  
\let\@dtl@keya\@dtl@key  
\@dtl@setnull{\@dtl@a}{\@dtl@key}%  
\fi  
}%  
{}%
```

Check if value for row B is null.

```
\DTLifnull{\@dtl@b}%  
{%
```

Value for row B is null, so find the first non null key in list of replacement keys.

```
\@for\@dtl@keyb:=\@dtl@replacementkeys\do{%
```

Get column corresponding to this key.

```
\@sdtl@getcolumnindex{\@dtl@col}{\@dtl@dbname}{\@dtl@keyb}%  
\dtl@getentryfromrow{\@dtl@b}{\@dtl@col}{#2}%
```

Has value for row B been defined?

```
\ifx\@dtl@b\dtlnovalue
```

Value for row B hasn't been defined so set to null.

```
\@dtl@setnull{\@dtl@b}{\@dtl@key}%  
\fi
```

Is value for row B null? If not null end the loop.

```
\DTLifnull{\@dtl@b}{}\@endfortrue}%  
}%
```

No non-null value found.

```
\ifx\@dtl@keyb\@nnil  
\let\@dtl@keyb\@dtl@key  
\@dtl@setnull{\@dtl@b}{\@dtl@key}%  
\fi  
}%  
{}%
```

Compare rows A and B. First store the values for row A and B in token registers so that they can be passed to \dtl@compare@.

```
\@dtl@toksA=\expandafter{\@dtl@a}%  
\@dtl@toksB=\expandafter{\@dtl@b}%
```

Do comparison.

```
\edef\@dtl@docompare{\noexpand\dtl@compare@
{\@dtl@keya}{\@dtl@keyb}%
{\noexpand\@dtl@toksA}{\noexpand\@dtl@toksB}}%
\@dtl@docompare
```

Repeat if the two values are considered identical and there are further sorting options.

```
\ifnum\dtl@sortresult=0\relax
```

Reset switch to prevent breaking out of outer loop.

```
\@endforfalse
\else
```

Break out of loop.

```
\@endfortrue
\fi
}%
```

Apply sort direction

```
\multiply\dtl@sortresult by -\@dtl@sortdirection\relax
}
```

`\@dtl@sortdirection` Get the direction from either *<key>* or *<key>=<direction>*. Sets `\@dtl@sortdirection` to either -1 (ascending) or 1 (descending).

```
\def\@dtl@getsortdirection#1=#2\relax{%
```

Store key in `\@dtl@key`.

```
\def\@dtl@key{#1}%
```

Store sort direction. This will be empty if no direction was specified.

```
\def\@dtl@sortdirection{#2}%
```

Check if a direction was specified.

```
\ifdefempty{\@dtl@sortdirection}%
{%
```

No direction specified so assume ascending.

```
\def\@dtl@sortdirection{-1}%
}%
{%
```

Get the sort direction from the second argument (needs terminating equal sign removed) and store in `\@dtl@sortdirection`.

```
\@dtl@get@sortdirection#2%
```

Determine the direction.

```
\def\@dtl@dir{ascending}%
\ifx\@dtl@sortdirection\@dtl@dir
```

Ascending

```
\def\@dtl@sortdirection{-1}%
\else
```

Check if descending.

```
\def\@dtl@dir{descending}%  
\ifx\@dtl@sortdirection\@dtl@dir
```

Descending

```
\def\@dtl@sortdirection{1}%  
\else
```

Direction not valid. Generate error message.

```
\PackageError{datatool}{Invalid sort direction  
'\@dtl@sortdirection'}{The sort direction can only be  
one of 'ascending' or 'descending'}%
```

Assume ascending.

```
\def\@dtl@sortdirection{-1}%  
\fi  
\fi  
}%  
}
```

`\@dtl@sortdirection` Get direction (trims trailing = sign)

```
\def\@dtl@get@sortdirection#1={\def\@dtl@sortdirection{#1}}
```

`\@dtl@toksA`

```
\newtoks\@dtl@toksA
```

`\@dtl@toksB`

```
\newtoks\@dtl@toksB
```

```
\dtl@compare \dtl@compare{<key>}{<a toks>}{<b toks>}
```

Compares two values according to `<key>` of database given by `\@dtl@dbname`. Sets `\dtl@sortresult`.

`\@dtl@comparecs` must be set to the required comparison macro.

```
\newcommand{\dtl@compare}[3]{%  
\dtl@compare@{#1}{#1}{#2}{#3}%  
}
```

```
\dtl@compare@ \dtl@compare@{<keyA>}{<keyB>}{<A toks>}{<B toks>}
```

Compare `<A>` and `<B>` according `<keyA>` and `<keyB>` for database given by `\@dtl@dbname`. Sets

`\dtl@sortresult`. `\@dtl@comparecs` must be set before use.

```
\newcommand{\dtl@compare@}[4]{%
```

Get the data type for first key and store in `\@dtl@typeA`.

```
\DTLgetdatatype{\@dtl@typeA}{\@dtl@dbname}{#1}%
```

Is it unset? If so, assume string

```
\ifx\@dtl@typeA\DTLunsettype
\let\@dtl@typeA\DTLstringtype
\fi
```

Get the data type for the second key and store in \@dtl@typeB

```
\DTLgetdatatype{\@dtl@typeB}{\@dtl@dbname}{#2}%
```

Is it unset? If so, assume string

```
\ifx\@dtl@typeB\DTLunsettype
\let\@dtl@typeB\DTLstringtype
\fi
```

Multiply the two values together

```
\@dtl@tmpcount=\@dtl@typeA\relax
\multiply\@dtl@tmpcount by \@dtl@typeB\relax
```

If either type is 0 (a string) then the product will also be 0 (string) otherwise it will be one of the numerical types.

```
\ifnum\@dtl@tmpcount=0\relax
```

A string, so use comparison function

```
\edef\@dtl@tmpcmp{%
\noexpand\@dtl@comparecs{\noexpand\dtl@sortresult}%
{\the#3}{\the#4}%
}%
\@dtl@tmpcmp
\ifdtlverbose
\edef\@dtl@a{\the#3}%
\edef\@dtl@b{\the#4}%
\fi
\else
```

Store the first value

```
\edef\@dtl@a{\the#3}%
```

Store the second value

```
\edef\@dtl@b{\the#4}%
```

Compare

```
\DTLifnumlt{\@dtl@a}{\@dtl@b}%
{%
```

$A < B$

```
\dtl@sortresult=-1\relax
}%
{%
\DTLifnumgt{\@dtl@a}{\@dtl@b}%
{%
```

$A > B$

```
\dtl@sortresult=1\relax
}%
{%
```



$A = B$

```
\dtl@sortresult=0\relax
}%
}%
\fi
```

Write comparison result to terminal/log if verbose mode.

```
\ifdtlverbose
\@onelevel@sanitize\@dtl@a
\@onelevel@sanitize\@dtl@b
\dtl@message{'\@dtl@a' <=> '\@dtl@b' = \number\dtl@sortresult}%
\fi
}
```

## 4.11 Saving a database to an external file

\@dtl@write

```
\newwrite\@dtl@write
```

```
\DTLsavedb \DTLsavedb{<db name>}{<filename>}
```

Save a database as an ASCII data file using the separator and delimiter given by \@dtl@separator and \@dtl@delimiter.

```
\newcommand*{\DTLsavedb}[2]{%
\DTLifdbexists{#1}%
{%
```

Open output file

```
\openout\@dtl@write=#2\relax
```

Initialise header row

```
\def\@dtl@header{}}%
```

Construct the header row

```
\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)%
\in{#1}\do
{%
\IfSubStringInString{\@dtl@separator}{\@dtl@key}%
{%
\ifdefempty{\@dtl@header}%
{%
\protected@edef\@dtl@header{%
\@dtl@delimiter\@dtl@key\@dtl@delimiter}%
}%
{%
\toks@=\expandafter{\@dtl@header}%
\protected@edef\@dtl@header{%
```

```

        \the\toks@\@dtl@separator
        \@dtl@delimiter\@dtl@key\@dtl@delimiter}%
    }%
}%
{%
    \ifdefempty{\@dtl@header}%
    {%
        \protected@edef\@dtl@header{\@dtl@key}%
    }%
    {%
        \toks@=\expandafter{\@dtl@header}%
        \protected@edef\@dtl@header{\the\toks@
            \@dtl@separator\@dtl@key}%
    }%
}%
}%
}%

```

Print header

```

\protected@write\@dtl@write{}{\@dtl@header}%

```

Iterate through each row

```

\@sDTLforeach{#1}{}%
{%

```

Initialise row

```

\def\@dtl@row{}%

```

Iterate through each key

```

\DTLforeachkeyinrow{\@dtl@val}%
{%
    \IfSubStringInString{\@dtl@separator}{\@dtl@val}%
    {%
        \ifdefempty{\@dtl@row}%
        {%
            \protected@edef\@dtl@row{%
                \@dtl@delimiter\@dtl@val\@dtl@delimiter}%
        }%
        {%
            \toks@=\expandafter{\@dtl@row}%
            \protected@edef\@dtl@row{\the\toks@\@dtl@separator
                \@dtl@delimiter\@dtl@val\@dtl@delimiter}%
        }%
    }%
    {%
        \ifdefempty{\@dtl@row}%
        {%
            \protected@edef\@dtl@row{\@dtl@val}%
        }%
        {%
            \toks@=\expandafter{\@dtl@row}%
            \protected@edef\@dtl@row{\the\toks@\@dtl@separator

```

```

        \@dtl@val}%
    }%
} %
} %

```

Print row

```

    \protected@write\@dtl@write{}{\@dtl@row}%
} %

```

Close output file

```

    \closeout\@dtl@write
} %
{ %
    \PackageError{datatool}{Can't save database '#1': no such
    database}{}%
} %
}

```

```

\DTLsavetexdb \DTLsavetexdb{<db name>}{<filename>}

```

Save a database as a  $\LaTeX$  file.

```

\newcommand*\DTLsavetexdb [2] { %
    \DTLifdbexists{#1}%
} %

```

Open output file

```

    \openout\@dtl@write=#2\relax

```

Write new data base definition

```

    \protected@write\@dtl@write{}{\string\DTLnewdb{#1}}%

```

Iterate through each row

```

    \@sDTLforeach{#1}{}%
    { %

```

Start new row

```

        \protected@write\@dtl@write{}{\string\DTLnewrow*{#1}}%

```

Iterate through each column

```

        \DTLforeachkeyinrow{\@dtl@val}%
        { %

```

Is this entry null?

```

            \DTLifnull{\@dtl@val}%
            {\def\@dtl@val{}}%
            {}%

```

Add entry

```

            \protected@write\@dtl@write{}{ %
                \string\DTLnewbentry*{#1}{\dtlkey}{\@dtl@val}}%

```

```
}%
}%
```

Save the column headers.

```
\dtlforeachkey(\@dtl@k,\@dtl@c,\@dtl@t,\@dtl@h)\in{#1}\do
{%
  \@onelevel@sanitize\@dtl@h
  \protected@write\@dtl@write}{%
    \string\DTLsetheader*{#1}{\@dtl@k}{\@dtl@h}}%
}%
```

Store name of database in case required after database loaded:

```
\protected@write{\@dtl@write}{\string\def\string\dtllastloadeddb{#1}}%
```

Close output file

```
\closeout\@dtl@write
}%
{%
  \PackageError{datatool}{Can't save database '#1': no such
    database}{}%
}%
}
```

`\@saverawdbhook` Hook used by `\DTLsaverawdb`.

```
\newcommand*\@dtl@saverawdbhook{}
```

`\DTLsaverawdb` Saves given database in its internal form. Not easy for a human to read, but much faster to load.

```
\newcommand*\DTLsaverawdb}[2]{%
  \DTLifdbexists{#1}%
  {%
```

Open output file

```
\openout\@dtl@write=#2\relax
```

Add code at the start of the output file to check for the existence of the database:

```
\protected@write{\@dtl@write}{%
  \string\DTLifdbexists{#1}\expandafter\@gobble\string\%^^J%
  {%
    \string\PackageError{datatool}{Database '#1' ^^Jalready exists}{}%
    \expandafter\@gobble\string\%^^J%
    \string\aftergroup\string\endinput
  }%
  {%
  }\expandafter\@gobble\string\%
}%
```

Scope need to localise definitions:

```
{%
```

```

\def\db@row@elt@w{\expandafter\@gobble\string\%^~J\string\db@row@elt@w\space}%
\def\db@row@elt@end@{\expandafter\@gobble\string\%^~J\string\db@row@elt@end@\space}%
\def\db@row@id@w{\expandafter\@gobble\string\%^~J\string\db@row@id@w\space}%
\def\db@row@id@end@{\expandafter\@gobble\string\%^~J\string\db@row@id@end@\space}%
\def\db@col@elt@w{\expandafter\@gobble\string\%^~J\string\db@col@elt@w\space}%
\def\db@col@elt@end@{\expandafter\@gobble\string\%^~J\string\db@col@elt@end@\space}%
\def\db@col@id@w{\expandafter\@gobble\string\%^~J\string\db@col@id@w\space}%
\def\db@col@id@end@{\expandafter\@gobble\string\%^~J\string\db@col@id@end@\space}%

%
\def\db@plist@elt@w{\expandafter\@gobble\string\%^~J\string\db@plist@elt@w\space}%
\def\db@plist@elt@end@{\expandafter\@gobble\string\%^~J\string\db@plist@elt@end@\space}%
\def\db@key@id@w{\expandafter\@gobble\string\%^~J\string\db@key@id@w\space}%
\def\db@key@id@end@{\expandafter\@gobble\string\%^~J\string\db@key@id@end@\space}%
\def\db@type@id@w{\expandafter\@gobble\string\%^~J\string\db@type@id@w\space}%
\def\db@type@id@end@{\expandafter\@gobble\string\%^~J\string\db@type@id@end@\space}%
\def\db@header@id@w{\expandafter\@gobble\string\%^~J\string\db@header@id@w\space}%
\def\db@header@id@end@{\expandafter\@gobble\string\%^~J\string\db@header@id@end@\space}%

```

Need to ensure the @ character can be used so \makeatletter is required, but localise the effect.

```
\protected@write{\@dtl@write}{\string\bgroup\string\makeatletter}%
```

If in verbose mode, add a message to let the user know what's happening when the file is later loaded.

```

\protected@write{\@dtl@write}{\string\
\string\dtl@message{Reconstructing database^^J'#1'}%
\expandafter\@gobble\string\}%

```

Save the contents of the token register that holds the column information (column id, header, type). (The write is delayed, so the contents are first expanded and stored in a temporary (global) macro to ensure its in the correct format when the write happens.)

```

\protected@write{\@dtl@write}{\string\
\string\expandafter
\string\global\string\expandafter^^J\string\newtoks
\string\csname\space dtlkeys@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\
\string\expandafter
\string\global^^J
\string\csname\space dtlkeys@#1\string\endcsname
=\expandafter\@gobble\string\{\expandafter\@gobble\string\}%
\expandafter\protected@xdef\csname dtl@rawwritedbkeys@#1\endcsname{\
\the\csname dtlkeys@#1\endcsname}%
\protected@write{\@dtl@write}{\csname dtl@rawwritedbkeys@#1\endcsname}%
\protected@write{\@dtl@write}{\string\
\expandafter\@gobble\string\}\expandafter\@gobble\string\}%

```

Hook used by datagidx:

```
\dtl@saverawdbhook
```

Save the contents of the token register that holds the database body.

```
\protected@write{\@dtl@write}{\string\
```

```

\string\expandafter\string\global
\string\expandafter^^J\string\newtoks
  \string\csname\space dtldb@#1\string\endcsname}%
\protected@write{\@dtl@write}{-}{%
  \string\expandafter
  \string\global^^J\string\csname\space dtldb@#1\string\endcsname
  =\expandafter\@gobble\string\{\expandafter\@gobble\string\}%
\expandafter\protected@xdef\csname dtl@rawwritedb@#1\endcsname{\the\csname dtldb@#1\endcs
\protected@write{\@dtl@write}{-}{\csname dtl@rawwritedb@#1\endcsname}%
\protected@write{\@dtl@write}{-}{\expandafter\@gobble\string\}\expandafter\@gobble\string\

```

Now for the count register that keeps track of the row count.

```

\protected@write{\@dtl@write}{-}{\string\expandafter\string\global^^J
\string\expandafter\string\newcount
\string\csname\space dtlrows@#1\string\endcsname}%
\protected@write{\@dtl@write}{-}{\string\expandafter\string\global^^J
\string\csname\space dtlrows@#1\string\endcsname
  =\expandafter\number\csname dtlrows@#1\endcsname\string\relax}%

```

Similarly for the column count.

```

\protected@write{\@dtl@write}{-}{\string\expandafter\string\global^^J
\string\expandafter\string\newcount
\string\csname\space dtlcols@#1\string\endcsname}%
\protected@write{\@dtl@write}{-}{\string\expandafter\string\global^^J
\string\csname\space dtlcols@#1\string\endcsname
  =\expandafter\number\csname dtlcols@#1\endcsname\string\relax}%

```

Add key mappings

```

\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
{%
  \edef\dtl@tmp{%
    \string\expandafter^^J
    \string\gdef
    \string\csname\space dtl@ci@#1\@dtl@key\string\endcsname
    {\csname dtl@ci@#1\@dtl@key\endcsname}\expandafter\@gobble\string\%
  }%
  \expandafter\write\expandafter\@dtl@write\expandafter{\dtl@tmp}%
}%

```

End the scope for \makeatletter:

```

\protected@write{\@dtl@write}{-}{\string\egroup}%

```

End current scope:

```

}%

```

Store name of database in case required after database loaded:

```

\protected@write{\@dtl@write}{-}{\string\def\string\dtllastloadeddb{#1}}%

```

Close output file

```

\closeout\@dtl@write
}%
{%

```

```

        \PackageError{datatool}{Can't save database '#1': no such
        database}{}%
    }%
}

```

protectedsaverawdb Like \DTLsaverawdb but works with fragile contents. If there's a problem with unwanted line breaks every 80 characters, try loading morewrites before datatool.

```

\newcommand*{\DTLprotectedsaverawdb}[2]{%
  \DTLifdbexists{#1}%
  {%

```

Open output file

```

\openout\@dtl@write=#2\relax

```

Add code at the start of the output file to check for the existence of the database:

```

\protected@write{\@dtl@write}{}{%
  \string\DTLifdbexists{#1}\expandafter\@gobble\string\%^~J%
  {%
    \string\PackageError{datatool}{Database '#1' ^~Jalready exists}{}%
    \expandafter\@gobble\string\%^~J%
    \string\aftergroup\string\endinput
  }%
  {%
  }\expandafter\@gobble\string\%
}%

```

Scope needed to localise definitions:

```

{%

```

Need to ensure the @ character can be used so \makeatletter is required, but localise the effect.

```

\protected@write{\@dtl@write}{}{\string\bgroup\string\makeatletter}%

```

If in verbose mode, add a message to let the user know what's happening when the file is later loaded.

```

\protected@write{\@dtl@write}{}{\string\dtl@message{Reconstructing database
  ^~J'#1'}\expandafter\@gobble\string\%^~J%
}

```

Start writing the header token definition.

```

\protected@write{\@dtl@write}{}{%
  \string\expandafter
  \string\global\string\expandafter^~J\string\newtoks
  \string\csname\space dtlkeys@#1\string\endcsname}%
\protected@write{\@dtl@write}{}{%
  \string\expandafter
  \string\global^~J
  \string\csname\space dtlkeys@#1\string\endcsname
  =\expandafter\@gobble\string\{\expandafter\@gobble\string\%^~J%
% Store the contents of the token register that holds the column
% information (column id, header, type) and sanitize.
% \begin{macrocode}

```

```

\edef\dtl@rawwrite@keys{\the\csname dtlkeys@#1\endcsname}%
\@onelevel@sanitize\dtl@rawwrite@keys

```

The write can get delayed, so expand after to ensure it has the actual contents of the database rather than `\dtl@rawwrite@keys`, which may have changed by the time the write occurs. Include the closing brace of the token contents.

```

\expandafter\write\expandafter\@dtl@write\expandafter
  {\dtl@rawwrite@keys\expandafter\@gobble\string\}}%

```

Similarly for the token register that holds the database body.

```

\protected@write{\@dtl@write}{\string\global
\string\expandafter\string\global
\string\expandafter^^J\string\newtoks
\string\csname\space dtldb@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\global
\string\expandafter
\string\global^^J\string\csname\space dtldb@#1\string\endcsname
=\expandafter\@gobble\string\{\expandafter\@gobble\string\}%}
\edef\dtl@rawwrite@db{\the\csname dtldb@#1\endcsname}%
\@onelevel@sanitize\dtl@rawwrite@db

```

Now write the sanitize contents.

```

\expandafter\write\expandafter\@dtl@write\expandafter
  {\dtl@rawwrite@db\expandafter\@gobble\string\}}%

```

Now for the count register that keeps track of the row count.

```

\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\expandafter\string\newcount
\string\csname\space dtlrows@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\csname\space dtlrows@#1\string\endcsname
=\expandafter\number\csname dtlrows@#1\endcsname\string\relax}%

```

Similarly for the column count.

```

\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\expandafter\string\newcount
\string\csname\space dtlcols@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\csname\space dtlcols@#1\string\endcsname
=\expandafter\number\csname dtlcols@#1\endcsname\string\relax}%

```

Add key mappings

```

\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
{%
\edef\dtl@tmp{%
\string\expandafter^^J
\string\gdef
\string\csname\space dtl@ci@#1@\@dtl@key\string\endcsname
{\csname dtl@ci@#1@\@dtl@key\endcsname}\expandafter\@gobble\string\}%
\expandafter\write\expandafter\@dtl@write\expandafter{\dtl@tmp}%

```



```

    }%
End the scope for \makeatletter:
    \protected@write{\@dtl@write}{}{\string\egroup}%
End current scope:
    }%
Provide a means to keep track of the last loaded file:
    \protected@write{\@dtl@write}{}{\string\def\string\dtllastloadeddb{#1}}%
Close output file
    \closeout\@dtl@write
  }%
  {%
    \PackageError{datatool}{Can't save database '#1': no such
      database}{}%
  }%
}

```

## 4.12 Loading a database from an external file

```
\DTLloaddbtex \DTLloaddbtex{<cs>}{<file>}
```

Load a .dbtex file and assign the database name to the control sequence <cs>. Checks the file name exists and the control sequence doesn't exist.

```

\newcommand*{\DTLloaddbtex}[2]{%
  \IfFileExists{#2}%
  {%
    \input{#2}%
    \ifdef#1%
    {%
      \PackageError{datatool}{Command \string#1\space is already defined}%
    }%
  }%
  {%
    \let#1\dtllastloadeddb
  }%
}
{%
  \PackageError{datatool}{File '#2' doesn't exist.}%
}
}

```

```
\@dtl@read
```

```
\newread\@dtl@read
```

`\dtl@entrycr` Keep track of current column in data file  
`\newcount\dtl@entrycr`

`\ifdtlnoheader` The noheader option indicates that the file doesn't have a header row.  
`\define@boolkey{loaddb}{dtl}{noheader}[true]{}`

`\ifdtlautokeys` Assign the default keys even if a header row is supplied.  
`\define@boolkey{loaddb}{dtl}{autokeys}[true]{}`  
`\dtlautokeysfalse`

The keys option specifies the list of keys in the same order as the columns in the data file. Each key is stored in `\@dtl@inky@<n>` where `<n>` is the roman numeral representation of the current column.

```
\define@key{loaddb}{keys}{%
  \dtl@entrycr=0\relax
  \@for\@dtl@key:=#1\do
  {%
    \advance\dtl@entrycr by 1\relax
    \expandafter
    \edef\csname \@dtl@inky@\romannumeral\dtl@entrycr\endcsname{%
      \@dtl@key}%
  }%
}
```

The headers option specifies the list of headers in the same order as the columns in the data file.

```
\define@key{loaddb}{headers}{%
  \dtl@entrycr=0\relax
  \@for\@dtl@head:=#1\do
  {%
    \advance\dtl@entrycr by 1\relax
    \toks@=\expandafter{\@dtl@head}%
    \expandafter
    \edef\csname \@dtl@inhd@\romannumeral\dtl@entrycr\endcsname{%
      \the\toks@}%
  }%
}
```

The following is supplied in a patch by Bruno Le Floch:

```
\newcount{\dtl@omitlines}
\define@key{loaddb}{omitlines}{\dtl@omitlines=#1\relax}
```

`\dtldefaultkey` Default key to use if none specified (column index will be appended).  
`\newcommand*{\dtldefaultkey}{Column}`

`\@dtl@readline` `\@dtl@readline{<file reg>}{<cs>}`

Reads line from  $\langle file\ reg\rangle$ , trims end of line character and stores in  $\langle cs\rangle$ .

```
\newcommand*\@dtl@readline}[2]{%
```

Read a line from #1 and store in #2 but make sure end of line character is removed.

```
\begingroup  
\catcode\endlinechar=\active%  
\global\read#1 to #2%  
\endgroup%
```

If empty the row starts with a comment

```
\ifx#2\empty%  
\else%  
\expandafter\@dtl@stripeol#2%  
\let#2\@dtl@strippedline%  
\fi%  
}
```

$\@dtl@stripeol$

```
\begingroup  
\catcode\endlinechar=\active%  
\gdef\@dtl@stripeol#1  
{\gdef\@dtl@strippedline{#1}}  
\endgroup
```

$\@dtl@readdrawline$   $\@dtl@readdrawline\{\langle file\ register\rangle\}\{\langle cs\rangle\}$

Reads line from  $\langle file\ register\rangle$ , trims end of line character, applies mappings and stores in  $\langle cs\rangle$ .

```
\newcommand*\@dtl@readdrawline}[2]{%
```

Read a line from #1 and store in #2

```
\@dtl@rawread#1 to #2%
```

Apply mappings

```
\dtl@domappings\@dtl@line  
}
```

$\DTLnewdbonload$  Governs whether or not the database should be defined by  $\DTLloaddb$  and  $\DTLloaddrawdb$ .

```
\newif\ifDTLnewdbonload
```

Ensure compatibility with previous versions:

```
\DTLnewdbonloadtrue
```

$\DTLloaddb$   $\DTLloaddb[\langle options\rangle]\{\langle db\ name\rangle\}\{\langle filename\rangle\}$

Creates a new database called *<db name>*, and loads the data in *<filename>* into it. The separator and delimiter used in the file must match `\@dtl@separator` and `\@dtl@delimiter`. The optional argument is a comma-separated list.

```
\newcommand*\DTLloaddb}{%
  \let\@dtl@doreadline\@dtl@readline
  \@dtlloaddb
}
```

`\@dtlloaddb` Loads database using `\@dtl@doreadline` to read and trim line from file. (`\@dtl@doreadline` must be set before use.)

```
\newcommand*\@dtlloaddb}[3][\@dtl@readline]{%
```

Check if file exists

```
\IfFileExists{#3}{%
```

File exists. Locally change catcode of double quote character in case it has been made active.

```
\begingroup
\catcode'\@dtl@readline\relax
```

Initialise default options

```
\dtlnoheaderfalse
```

Get the options

```
\setkeys{loaddb}{#1}%
```

Open the file for reading.

```
\openin\@dtl@read=#3%
\dtl@message{Reading '#3'}%
```

The following supplied in patch by Bruno Le Floch:

```
\loop
\ifnum \dtl@omitlines > \z@
  \advance\dtl@omitlines by \m@ne
  \read\@dtl@read to \@dtl@line
\repeat
```

Create the database if required.

```
\ifDTLnewdbonload
\DTLnewdb{#2}%
\fi
```

Check if the file is empty.

```
\ifeof\@dtl@read
```

File is empty, so just issue a warning.

```
\PackageWarning{datatool}{File '#3' has no data}%
\else
```

Does the file have a header row?

```
\ifdtlnoheader
\else
```

Remove initial blank rows

```

\loop

```

Set repeat condition to false

```

\@dtl@conditionfalse

```

Do nothing if reached the end of file

```

\ifeof\@dtl@read
\else

```

Read a line from the file and store in \@dtl@line

```

\@dtl@doreadline\@dtl@read\@dtl@line

```

If this is a blank row, set repeat condition to true

```

\ifdefempty{\@dtl@line}%
{%
\@dtl@conditiontrue
}%
}%
\fi

```

Repeat loop if necessary

```

\if@dtl@condition
\repeat

```

Parse the header row. Store the row as *<sep><row><sep>* in \@dtl@lin@.

```

\protected@edef\@dtl@lin@{%
\@dtl@separator\@dtl@line\@dtl@separator}%

```

Keep track of columns:

```

\dtl@entrycr=0\relax

```

Keep lopping off elements until the end of the row is reached. (That is, until \@dtl@lin@ is \@dtl@separator.)

```

\loop

```

Lopoff the first element and store in \@dtl@key

```

\expandafter\@dtl@lopoff\@dtl@lin@\to\@dtl@lin@\@dtl@key

```

Increment column count.

```

\advance\dtl@entrycr by 1\relax

```

If autokeys option is on, add generic key

```

\ifdtlautokeys
\csedef{\@dtl@inky@\romannumeral\dtl@entrycr}%
{\dtldefaultkey\number\dtl@entrycr}%
\else

```

If missing a key, add generic one:

```

\ifdefempty{\@dtl@key}%
{%
\edef\@dtl@key{\dtldefaultkey\number\dtl@entrycr}%
}%

```

```
{}%
\fi
```

Store key in \@dtl@toks

```
\expandafter\@dtl@toks\expandafter{\@dtl@key}%
```

Store the key in \@dtl@inky@<n> where <n> is the roman numeral representation of the current column, unless already defined.

```
\@ifundefined{@dtl@inky@\romannumeral\dtl@entrycr}%
{%
\expandafter
\edef\csname @dtl@inky@\romannumeral
\dtl@entrycr\endcsname{\the\@dtl@toks}%
}%
{%
```

If key has been specified in #1, then use the header found in the file, unless a header has also been specified in #1

```
\@ifundefined{@dtl@inhd@\romannumeral\dtl@entrycr}%
{%
\expandafter
\edef\csname @dtl@inhd@\romannumeral
\dtl@entrycr\endcsname{\the\@dtl@toks}%
}%
{}%
}%
```

Check if the loop should be repeated

```
\ifx\@dtl@lin@\@dtl@separator
\@dtl@conditionfalse
\else
\@dtl@conditiontrue
\fi
```

Repeat loop if necessary.

```
\if@dtl@condition
\repeat
```

End if no header

```
\fi
```

Now for the rest of the data. If the end of file has been reached, then only the header row is available or file is empty.

```
\ifeof\@dtl@read
\ifdtlnoheader
\PackageWarning{datatool}{No data in '#3'}%
\else
\PackageWarning{datatool}{Only header row found in '#3'}%
\fi
\else
```

Iterate through the rest of the file. First set the repeat condition to true:

```
\@dtl@conditiontrue
\loop
```

Read in a line

```
\@dtl@doreadline\@dtl@read\@dtl@line
```

Check if the line is empty.

```
\ifdefempty{\@dtl@line}%
{%
```

Do nothing if the row is empty.

```
}%
{%
```

Add a new row to the database. (Don't need to check if the database exists, since it's just been created.)

```
\@sDTLnewrow{#2}%
```

Store the row as  $\langle sep \rangle \langle row \rangle \langle sep \rangle$  to make the lopping off easier

```
\expandafter\@dtl@toks\expandafter{\@dtl@line}%
\edef\@dtl@lin@{\@dtl@separator\the\@dtl@toks
\@dtl@separator}%
```

Reset the column counter.

```
\dtl@entrycr=0\relax
```

Iterate through each element in the row. Needs to be grouped since we're already inside a loop.

```
{%
```

Initialise repeat condition

```
\@dtl@conditiontrue
```

Iterate through the list

```
\loop
```

lop off first element and store in \@dtl@thisentry

```
\expandafter\@dtl@lopoff\@dtl@lin@\to
\@dtl@lin@\@dtl@thisentry
```

Increment the column count.

```
\advance\dtl@entrycr by 1\relax
```

Get the key for this column and store in \@dtl@thiskey. Use default value if not defined.

```
\@ifundefined{\@dtl@inky@\romannumeral\dtl@entrycr}%
{%
\edef\@dtl@thiskey{\dtldefaultkey
\number\dtl@entrycr}%
\expandafter\let
\csname \@dtl@inky@\romannumeral
\dtl@entrycr\endcsname\@dtl@thiskey
}%
```

```

        {%
        \edef\@dtl@thiskey{%
        \csname @dtl@inky@\romannumeral
        \dtl@entrycr\endcsname}%
        }%
Store this entry in \@dtl@toks
        \expandafter\@dtl@toks\expandafter{\@dtl@thisentry}%
Add this entry to the database
        \edef\@do@dtlnewentry{\noexpand\@sDTLnewdentry
        {#2}{\@dtl@thiskey}{\the\@dtl@toks}}%
        \@do@dtlnewentry
Check if loop should be terminated
        \ifx\@dtl@lin@\@dtl@separator
        \@dtl@conditionfalse
        \fi
Repeat loop if necessary
        \if@dtl@condition
        \repeat
        }%
End of parsing this row
        }%
If the end of file has been reached, set the repeat condition to false.
        \ifeof\@dtl@read \@dtl@conditionfalse\fi
Repeat if necessary
        \if@dtl@condition
        \repeat
        \fi
End of first \ifeof
        \fi
Close the input file
        \closein\@dtl@read
Set the headers if required
        \edef\@dtl@maxcols{\expandafter
        \number\csname dtlcols@#2\endcsname}%
        \dtl@forint\dtl@entrycr=1\to\@dtl@maxcols\step1\do
        {%
        \@ifundefined{\@dtl@inhd@\romannumeral\dtl@entrycr}%
        {}%
        {%
        \expandafter\let\expandafter\@dtl@head
        \csname @dtl@inhd@\romannumeral\dtl@entrycr\endcsname
        \@dtl@toks=\expandafter{\@dtl@head}%
        \edef\@dtl@dosetheader{\noexpand\@dtl@setheaderforindex

```



```

        {#2}{\number\dtl@entrycr}{\the\@dtl@toks}}%
    \@dtl@dosetheader
  }%
}%
End current scope
\endgroup
End true part of if file exists
}{%
Requested file not found on TeX's path
  \PackageError{datatool}{Can't load database '#2' (file '#3'
  doesn't exist)}{}%
}%
}

```

`\DTLloadrawdb` `\DTLloadrawdb{<db name>}{<filename>}`

Loads a raw database (substitutes % → \%, \$ → \\$, & → \&, # → \#, ~ → \textasciitilde, \_ → \\_ and ^ → \textasciicircum.) The user can add additional mappings.

```

\newcommand*\DTLloadrawdb{%
  \let\@dtl@doreadline\@dtl@readrawline
  \@dtlloaddb
}

```

`\@dtl@rawread` `\@dtl@rawread<number>to<cmd>`

Reads in a raw line from file given by <number> converts special characters and stores in <cmd>

```

\begingroup
\catcode'\%=\active
\catcode'\$=\active
\catcode'\&=\active
\catcode'\~=\active
\catcode'\_=\active
\catcode'\^=\active
\catcode'\#=\active
\catcode'?=6\relax
\catcode'<=1\relax
\catcode'>=2\relax
\catcode'\{=\active
\catcode'\}=\active
\gdef\@dtl@rawread?1to?2<\relax
<<\catcode'\%=\active

```

```

\catcode'\$=\active
\catcode'\&=\active
\catcode'\~=\active
\catcode'\_=\active
\catcode'\^=\active
\catcode'\#=\active
\catcode'\{=\active
\catcode'\}=\active
\def%<\noexpand\%>\relax
\def$<\noexpand\$>\relax
\def&<\&>\relax
\def#<\#>\relax
\def~<\noexpand\textasciitilde>\relax
\def_<\noexpand\_>\relax
\def^<\noexpand\textasciicircum>\relax
\@dtl@activatebraces
\@dtl@doreadraw?1?2>>>
\gdef\@dtl@doreadraw?1?2<\relax
\begingroup\catcode\endlinechar=\active\global\read?1 to \dtl@tmp\endgroup
\expandafter\@dtl@stripeol\dtl@tmp
\let\dtl@tmp\@dtl@strippedline
\protected@xdef?2<\dtl@tmp>\relax
>
\endgroup

```

`\@activatebraces`    `\@dtl@activatebraces` resets braces for `\@dtl@rawread`

```

\begingroup
\catcode'\{=\active
\catcode'\}=\active
\catcode'\<=1\relax
\catcode'\>=2\relax
\gdef\@dtl@activatebraces<%
\catcode'\{=\active
\catcode'\}=\active
\def{<\noexpand\{>%
\def}<\noexpand\}>%
>%
\endgroup

```

`\DTLrawmap`

<code>\DTLrawmap{&lt;string&gt;}{&lt;replacement&gt;}</code>
--

Additional mappings to perform when reading a raw data file

```

\newcommand*{\DTLrawmap}[2]{%
\expandafter\@dtl@toks\expandafter{\@dtl@rawmappings}%
\ifdefempty{\@dtl@rawmappings}%

```

```

{%
  \def\@dtl@rawmappings{#{#1}{#2}}%
}%
{%
  \def\@dtl@tmp{#{#1}{#2}}%
  \protected@edef\@dtl@rawmappings{\the\@dtl@toks,\@dtl@tmp}%
}%
}

```

`\dtl@rawmappings` List of mappings.

```
\newcommand*\@dtl@rawmappings{}
```

`\dtl@domappings` `\dtl@domappings{<cmd>}`

Do all mappings in string given by `<cmd>`.

```

\newcommand*\dtl@domappings[1]{%
  \@for\@dtl@map:=\@dtl@rawmappings\do{%
    \expandafter\DTLsubstituteall\expandafter#1\@dtl@map
  }%
}

```

## 4.13 Debugging commands

These commands are provided to assist debugging

`\dtlshowdb` `\dtlshowdb{<db name>}`

Shows the database.

```

\newcommand*\dtlshowdb[1]{%
  \expandafter\showthe\csname dtldb@#1\endcsname
}

```

`\dtlshowdbkeys` `\dtlshowdbkeys{<db name>}`

Shows the key list for the named database.

```

\newcommand*\dtlshowdbkeys[1]{%
  \expandafter\showthe\csname dtlkeys@#1\endcsname
}

```

`\dtlshowtype`

```
\dtlshowtype{<db name>}{<key>}
```

Show the data type for given key in the named database. This should be an integer from 0 to 3.

```
\newcommand*{\dtlshowtype}[2]{%  
  \DTLgetdatatype{\@dtl@type}{#1}{#2}\show\@dtl@type  
}
```

## 5 datagidx.sty

This package provides a means to produce indices and glossaries without the need for an external indexing application, such as `makeindex` or `xindy`. However, the code here has been developed to implement the word order style described by the Oxford Style Manual. If you are not writing in English, this may not be applicable to your needs. You may be able to define your own comparison handler to use with `\dtl-sort`. If not, you'll need to use `xindy` with a package such as `glossaries`.

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datagidx}[2018/12/07 v2.31 (NLCT)]
```

Required packages:

```
\RequirePackage{datatool}
\RequirePackage{etoolbox}
\RequirePackage{xkeyval}
\RequirePackage{mfirstuc}
\RequirePackage{xfor}
\RequirePackage{multicol}
\RequirePackage{textcase}

\RequirePackage{afterpage}
```

### 5.1 Default Settings

These commands need to be defined before the package options are used.

`\datagidx@columns` The number of columns to use for the index/glossary.

```
\newcommand*\datagidx@columns{2}
```

`\DTLgidxSetColumns`

```
\newcommand*\DTLgidxSetColumns[1]{%
  \DTLifint{#1}%
  {%
    \def\datagidx@columns{#1}%
  }%
  {%
    \PackageError{datagidx}%
    {Number of columns must be an integer}%
    {%
      You have requested ‘#1’ columns, which can’t be parsed as a
      number%
    }
  }
}
```

```

    }%
  }%
}

LgidxChildCount Child counter.
  \newcounter{DTLgidxChildCount}

LgidxChildCount Reduce duplicate identifier warnings if hyperref in use.
  \def\theHDTLgidxChildCount{\Label.\arabic{DTLgidxChildCount}}

ChildCountLabel Label for child counter.
  \newcommand*{\DTLgidxChildCountLabel}{\theDTLgidxChildCount}

LgidxChildStyle Should the child name be displayed? (Default: show name.) If the name shouldn't be displayed, replace with a number.
  \newcommand*{\DTLgidxChildStyle}[1]{#1}

dx@setchildstyle
  \newcommand*{\datagidx@setchildstyle}[1]{%
    \ifcase#1\relax
      \renewcommand*{\DTLgidxChildStyle}[1]{##1}%
    \or
      \renewcommand*{\DTLgidxChildStyle}[1]{%
        \DTLgidxChildCountLabel
      }%
    \fi
  }

dx@foreachchild Iterate through each child label
  \newcommand{\datagidx@foreachchild}{%
    \datagidx@sort@foreachchild
  }

dx@setchildsort
  \newcommand*{\datagidx@setchildsort}[1]{%
    \ifcase#1\relax
      \renewcommand*{\datagidx@foreachchild}{%
        \datagidx@sort@foreachchild
      }%
    \or
      \renewcommand*{\datagidx@foreachchild}{%
        \datagidx@unsort@foreachchild
      }%
    \fi
  }

DTLgidxPostName What to put after the name. (Defaults to space.)
  \newcommand*{\DTLgidxPostName}{ }

```

`idxPostChildName` What to put after the child name.  
`\newcommand*{\DTLgidxPostChildName}{\DTLgidxPostName}`

`DTLgidxNameCase` Should the name have a case change in the index/glossary? (Default: no change.)  
`\newcommand*{\DTLgidxNameCase}[1]{#1}`

`idx@setnamecase`  
`\newcommand*{\datagidx@setnamecase}[1]{%`  
`\ifcase#1\relax`  
`\renewcommand*{\DTLgidxNameCase}[1]{##1}%`  
`\or`  
`\let\DTLgidxNameCase\MakeTextUppercase`  
`\or`  
`\let\DTLgidxNameCase\MakeTextLowercase`  
`\or`  
`\let\DTLgidxNameCase\xmakefirstuc`  
`\or`  
`\let\DTLgidxNameCase\xcapitalisewords`  
`\fi`  
`}`

`DTLgidxNameFont` The font to use for the name in the index/glossary. (Default: normal font.)  
`\newcommand*{\DTLgidxNameFont}[1]{\textnormal{#1}}`

`PostDescription` What to put after the description. (Defaults to nothing.)  
`\newcommand*{\DTLgidxPostDescription}{}`

`idx@setpostdesc`  
`\newcommand*{\datagidx@setpostdesc}[1]{%`  
`\ifcase#1\relax`  
`\renewcommand*{\DTLgidxPostDescription}{}%`  
`\or`  
`\renewcommand*{\DTLgidxPostDescription}{.}%`  
`\fi`  
`}`

`gidxPreLocation` What to put before the location list. (Defaults to en-space.)  
`\newcommand*{\DTLgidxPreLocation}{\enspace}`

`@setprelocation`  
`\newcommand*{\datagidx@setprelocation}[1]{%`  
`\ifcase#1\relax`  
`\renewcommand*{\DTLgidxPreLocation}{}%`  
`\or`  
`\renewcommand*{\DTLgidxPreLocation}{\enspace}%`  
`\or`  
`\renewcommand*{\DTLgidxPreLocation}{ }%`  
`\or`

```

        \renewcommand*{\DTLgidxPreLocation}{\dotfill}%
    \or
        \renewcommand*{\DTLgidxPreLocation}{\hfill}%
    \fi
}

DTLgidxLocation How to display the location. (Defaults to show the location list.)
    \newcommand*{\DTLgidxLocation}{\dtldolocationlist}

idx@setlocation Should the location list be displayed?
    \newcommand*{\datagidx@setlocation}[1]{%
        \ifcase#1\relax
            \renewcommand*{\DTLgidxLocation}{}%
        \or
            \renewcommand*{\DTLgidxLocation}{\dtldolocationlist}%
        \or
            \renewcommand*{\DTLgidxLocation}{\dtldofirstlocation}%
        \fi
    }

\DTLgidxSee How to display the cross-reference list.
    \newcommand*{\DTLgidxSee}{%
        \DTLifnull{\See}%
        {}%
        {%
            \DTLgidxPreLocation
            \DTLgidxFormatSee{\seename}{\See}%
        }%
    }

\DTLgidxSeeAlso How to display the “see also” list.
    \newcommand*{\DTLgidxSeeAlso}{%
        \DTLifnull{\SeeAlso}%
        {}%
        {%
            \DTLgidxFormatSeeAlso{\seealsoname}{\SeeAlso}%
        }%
    }

ChildrenSeeAlso Display the children and the see also attributes.
    \newcommand*{\DTLgidxChildrenSeeAlso}{%
        \DTLgidxChildren
        \DTLgidxSeeAlso
    }

datagidx@setsee How should cross-references appear?
    \newcommand*{\datagidx@setsee}[1]{%
        \ifcase#1\relax

```



```

\renewcommand*{\DTLgidxSee}{%
  \DTLifnull{\See}{}%
  {%
    , \DTLgidxFormatSee{\seename}{\See}%
  }%
}%
\or
\renewcommand*{\DTLgidxSee}{%
  \DTLifnull{\See}{%
    {%
      \space(\DTLgidxFormatSee{\seename}{\See})%
    }%
  }%
}%
\or
\renewcommand*{\DTLgidxSee}{%
  \DTLifnull{\See}{%
    {%
      . \DTLgidxFormatSee{\xmakefirstuc{\seename}}{\See}%
    }%
  }%
}%
\or
\renewcommand*{\DTLgidxSee}{%
  \DTLifnull{\See}{%
    {%
      \space\DTLgidxFormatSee{\seename}{\See}%
    }%
  }%
}%
\or
\renewcommand*{\DTLgidxSee}{%
  \DTLifnull{\See}{%
    {%
      \DTLgidxFormatSee{\seename}{\See}%
    }%
  }%
}%
\or
\renewcommand*{\DTLgidxSee}{%
  \DTLifnull{\See}{%
    {%
      ; \DTLgidxFormatSee{\seename}{\See}%
    }%
  }%
}%
\or
\renewcommand*{\DTLgidxSee}{%
  \DTLifnull{\See}{%
    {%
      \DTLgidxPreLocation\DTLgidxFormatSee{\seename}{\See}%
    }%
  }%
}%
\fi

```

```

    }
LgidxSymDescSep Separator character between symbol and description if both are present.
    \newcommand*{\DTLgidxSymDescSep}{\space}
gidxsymbolwidth Space to allocate for the symbol. If zero or negative, symbol just occupies its natural space.
    \newlength\datagidxsymbolwidth
dxlocationwidth Space to allocate for the location list. If zero or negative, the list just occupies its natural
space.
    \newlength\datagidxlocationwidth
LgidxFormatDesc How to format the description.
    \newcommand{\DTLgidxFormatDesc}[1]{#1}
ymbolDescription How to format the symbol and description fields.
    \newcommand*{\DTLgidxSymbolDescription}{%
        \DTLgidxSymbolDescLeft
        \DTLgidxSymbolDescRight
    }
    \newcommand*{\DTLgidxSymbolDescLeft}{%
        \ifdefempty{\Symbol}{}{(\Symbol)\DTLgidxSymDescSep}%
    }
    \newcommand*{\DTLgidxSymbolDescRight}{%
        \ifdefempty{\Description}{}%
        {%
            \DTLgidxFormatDesc{\Description}\DTLgidxPostDescription
        }%
    }
}
agidxsymbolleft Identifies whether the symbol has been set to left or right.
    \newif\if@datagidxsymbolleft
    \@datagidxsymbollefttrue
x@formatsymdesc
    \newcommand*{\datagidx@formatsymdesc}[1]{%
        \ifcase#1\relax
Only symbol
        \renewcommand*{\DTLgidxSymbolDescLeft}{%
            \ifdefempty{\Symbol}{}{\Symbol}%
        }%
        \renewcommand*{\DTLgidxSymbolDescRight}{}%
        \@datagidxsymbollefttrue
    \or
Only description
        \renewcommand*{\DTLgidxSymbolDescLeft}{%
            \ifdefempty{\Description}{}%

```

```

    {%
      \DTLgidxFormatDesc{\Description}\DTLgidxPostDescription
    }%
  }%
\renewcommand*{\DTLgidxSymbolDescRight}{}%
\@datagidxsymbolleftfalse
\or
(symbol) description
\renewcommand*{\DTLgidxSymbolDescLeft}{%
  \ifdefempty{\Symbol}{}{(\Symbol)\DTLgidxSymDescSep}%
}%
\renewcommand*{\DTLgidxSymbolDescRight}{%
  \ifdefempty{\Description}{}%
  {%
    \DTLgidxFormatDesc{\Description}\DTLgidxPostDescription
  }%
}%
\@datagidxsymbollefttrue
\or
description (symbol)
\renewcommand*{\DTLgidxSymbolDescLeft}{%
  \ifdefempty{\Description}{}%
  {%
    \DTLgidxFormatDesc{\Description}%
    \DTLgidxPostDescription\DTLgidxSymDescSep
  }%
}%
\renewcommand*{\DTLgidxSymbolDescRight}{%
  \ifdefempty{\Symbol}{}{(\Symbol)}%
}%
\@datagidxsymbolleftfalse
\or
symbol description
\renewcommand*{\DTLgidxSymbolDescLeft}{%
  \ifdefempty{\Symbol}{}{\Symbol\DTLgidxSymDescSep}%
}%
\renewcommand*{\DTLgidxSymbolDescRight}{%
  \ifdefempty{\Description}{}%
  {%
    \DTLgidxFormatDesc{\Description}%
    \DTLgidxPostDescription
  }%
}%
\@datagidxsymbollefttrue
\or
description symbol
\renewcommand*{\DTLgidxSymbolDescLeft}{%

```

```

\ifdefempty{\Description}{}%
{%
  \DTLgidxFormatDesc{\Description}%
  \DTLgidxPostDescription\DTLgidxSymDescSep
}%
}%
\renewcommand*{\DTLgidxSymbolDescRight}{%
  \ifdefempty{\Symbol}{}\{\Symbol}%
}%
\@datagidxsymbolleftfalse
\fi
}

```

idxSetCompositor

```
\DTLgidxSetCompositor{<symbol>}
```

Set the location compositor.

```

\newcommand*{\DTLgidxSetCompositor}[1]{%
  \undef\datagidx@docompllist
  \DeclareListParser{\datagidx@docompllist}{#1}%
  \def\datagidx@compositor{#1}%
}

```

Set the default compositor to . (full stop).

```
\DTLgidxSetCompositor{.}
```

Sorting can take a long time (especially with large databases) but two  $\LaTeX$  runs are usually required to get the index or glossary up-to-date, so we usually don't need to worry about sorting on the first run (unless the order in some way affects the document, e.g. the group headings are to appear in the table of contents). It may also be that some modifications are done to the document that don't require a re-sort. The optimize setting tries to minimize the amount of sorting done to help speed up document compilation.

There are two optimization levels: low and high. The low level optimization just sorts every other  $\LaTeX$  run. This is done by writing to the aux file to determine whether or not the sort should be done next run. This is a cheap and easy hack that won't work if sorting makes the document out-of-date (for example, if the sorted index or glossary affects the table of contents by, say, making the group headings a sectional unit).

The high level optimization is more complicated and involves writing the sorted database to an external file and reading it in on the next run. This requires checks to see if the location lists have changed, in which case a new sort may be required.

The optimization function is only implemented when the sorting is specified via the sort key. Any explicit sorting done by the user via commands such as `\dltsort` are not effected by the optimization setting.

`datagidx@do@sort` Indicate what to do when it's time to sort the index/glossary. This defaults to un-optimised setting to avoid confusing users who don't like to read the manual.

```
\newcommand*{\datagidx@do@sort}{\datagidx@sort}
```

First deal with the low-level optimization as it's easier to implement.

`optimize@sort` The code to perform when the low optimize setting is on. If the command `\datagidx@do@optimize@sort` has been defined, do the sort. If it hasn't been defined, don't sort. If a sort isn't performed, the command definition is written to the aux file. If a sort is performed, the command definition isn't written to the aux file. This will do the sort every other run.

```
\newcommand*{\datagidx@optimize@sort}{%
```

First, has `\datagidx@do@optimize@sort` been defined?

```
\ifdef\datagidx@do@optimize@sort  
{%
```

It has been defined so go ahead and do the sort.

```
\datagidx@sort  
}%  
{%
```

It hasn't been defined so don't sort. Write the command definition into the aux file for the next run.

```
\protected@write\@auxout{}{%%  
\string\gdef\string\datagidx@do@optimize@sort{}%  
}%
```

Let the user know they need to recompile the document.

```
\global\let\@datagidx@dorerun@warn@sort\@data@rerun@warn@sort  
}%  
}
```

`datagidx@warn` Provide a switch to allow warnings to be suppressed.

```
\newif\if@datagidx@warn  
\@datagidx@warntrue
```

`dx@dorerun@warn`

```
\newcommand*\@datagidx@dorerun@warn{}  
\AtEndDocument{\if@datagidx@warn\@datagidx@dorerun@warn\fi}
```

`rerun@warn@sort`

```
\newcommand*\@datagidx@dorerun@warn@sort{}  
\AtEndDocument{\if@datagidx@warn\@datagidx@dorerun@warn@sort\fi}
```

`rerun@warn@sort` Warning issued when a rerun is required to sort the index or glossary.

```
\newcommand*\@data@rerun@warn@sort{%%  
\PackageWarningNoLine{datagidx}{Rerun required to sort the  
index/glossary databases}%  
}
```

gidx@rerun@warn Warning issued when a rerun is required to update the location lists.

```
\newcommand*{\@data@rerun@warn}{%
  \PackageWarningNoLine{datagidx}{Rerun required to ensure the
    index/glossary location lists are up-to-date}%
}
```

The high optimize setting is more complicated. This involves writing each database to an external file (named `\jobname-<db label>.gidx`). The sort is only performed if new terms are added or used.

ighopt@optimize

```
\newcommand*{\@datagidx@do@highopt@optimize}{%
  \renewcommand*{\@datagidx@do@sort}{%
```

Only sort if database has changed.

```
  \ifcsdef{datagidx@do@highopt@sort@\DTLgidxCurrentdb}%
  {%
    \csuse{datagidx@do@highopt@sort@\DTLgidxCurrentdb}%
  }%
  {%
```

Do nothing

```
}%
```

Save the database to file.

```
\bgroup
```

Hook into write macro to clear certain fields and protect commands like `\DTLgidxName`.

```
\def\dtl@saverawdbhook{%
  \let\db@col@id@w\@datagidx@db@col@id@w
  \def\DTLgidxName{\string\DTLgidxName\space}%
  \def\DTLgidxMac{\string\DTLgidxMac\space}%
  \def\DTLgidxRank{\string\DTLgidxRank\space}%
  \def\DTLgidxParen{\string\DTLgidxParen\space}%
  \def\DTLgidxParticle{\string\DTLgidxParticle\space}%
  \def\DTLgidxOffice{\string\DTLgidxOffice\space}%
  \def\DTLgidxSaint{\string\DTLgidxSaint\space}%
  \def\DTLgidxPlace{\string\DTLgidxPlace\space}%
  \def\DTLgidxIgnore{\string\DTLgidxIgnore\space}%
  \def\DTLgidxNameNum{\string\DTLgidxNameNum\space}%
  \def\DTLgidxSubject{\string\DTLgidxSubject\space}%
}%
\DTLsaverawdb{\DTLgidxCurrentdb}{\@datagidxhighoptfilename\DTLgidxCurrentdb}%
\egroup
}%
```

Change the behaviour of `\newgidx`

```
\def\newgidx{\@datagidx@highopt@newgidx}%
```

Change the behaviour of `\newterm`

```
\def\newterm{\@datagidx@highopt@newterm}%
}
```

`idx@db@col@id@w` A bit of trickery is need to clear the Used and Location fields when writing the raw database to file.

```

\def\@datagidx@db@col@id@w#1\db@col@id@end@\db@col@elt@w#2\db@col@elt@end@\db@col@id@w#3\db@col
\expandafter\@gobble\string\%^^J
\string\db@col@id@w\space #1%
\expandafter\@gobble\string\%^^J
\string\db@col@id@end\space
\expandafter\@gobble\string\%^^J
\string\db@col@elt@w\space
\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrentdb @Used\endcsname=#1\space
0%
\else
\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrentdb @Location\endcsname=#1\space
\else
\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrentdb @CurrentLocation\endcsname=#1\space
\else

```

We also want to prevent the first character of the sort field from being expanded to help get the group correct (in case the user wants to sort on, say, the tilde character).

```

\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrentdb @Sort\endcsname=#1\space
\protect#2%
\else
#2%
\fi
\fi
\fi
\fi
\expandafter\@gobble\string\%^^J
\string\db@col@elt@end\space
\expandafter\@gobble\string\%^^J
\string\db@col@id@w\space #3%
\expandafter\@gobble\string\%^^J
\string\db@col@id@end\space
}

```

With the ‘highopt optimize’ setting, whenever a location is written to the aux file, if no location has been defined the database needs sorting.

`highopt@update` Default does nothing. (Argument is the entry’s label.)

```

\newcommand*\@datagidx@do@highopt@update}[1]{}

```

`highoptfilename` Expands to the name of the filename associated with the database identified by the argument for the ‘highopt’ setting.

```

\newcommand*\@datagidxhighoptfilename}[1]{\jobname-#1.gidx}

```

## 5.2 Package Options

`optimize` A boolean option indicating whether or not to optimize the sort. This is only available as a global option. If you want to optimize some glossaries but not others, switch on the `optimize`

function and clear the sort key for the relevant glossaries and manually sort using `\dtlsort` before the glossary is displayed.

```
\define@choicekey{datagidx.sty}{optimize}[\val\nr]%
{off,low,high}[high]%
{%
  \ifcase\nr\relax
  \renewcommand*{\datagidx@do@sort}{\datagidx@sort}
  \or
  \renewcommand*{\datagidx@do@sort}{\datagidx@optimize@sort}
  \or
  \datagidx@do@highopt@optimize
  \fi
}
```

`nowarn` A boolean option to suppress warnings.

```
\define@choicekey{datagidx.sty}{nowarn}[\val\nr]{true,false}[true]%
{%
  \ifcase\nr\relax
  \@datagidx@warnfalse
  \or
  \@datagidx@warntrue
  \fi
}
```

`utf8`

```
\define@choicekey{datatool.sty}{utf8}{true,false}[true]{%
  \setbool{@dtl@utf8}{#1}%
}
```

These options govern the general layout of the glossary/index.

`columns` The number of columns used by `multicols` (or `multicols*`). If only one column is specified, `multicols` (or `multicols*`) isn't used.

```
\define@key{datagidx.sty}{columns}%
{%
  \DTLgidxSetColumns{#1}%
}
```

`child` Indicates whether or not to show the name in child entries.

```
\define@choicekey{datagidx.sty}{child}[\val\nr]%
{named,noname}%
{%
  \datagidx@setchildstyle\nr
}
```

`namecase` Options for name case.

```
\define@choicekey{datagidx.sty}{namecase}[\val\nr]%
{nochange,uc,lc,firstuc,capitalise}%
```



```

    {%
      \datagidx@setnamecase\nr
    }

namefont Option to set the name font.
    \define@key{datagidx.sty}{namefont}%
    {%
      \renewcommand*{\DTLgidxNameFont}[1]{\#1{\#1}}%
    }

postname What to put after the name.
    \define@key{datagidx.sty}{postname}
    {%
      \renewcommand*{\DTLgidxPostName}{\#1}%
    }

postdesc what to put after the description.
    \define@choicekey{datagidx.sty}{postdesc}[\val\nr]%
    {none,dot}%
    {%
      \datagidx@setpostdesc\nr
    }

prelocation What to put before the location list.
    \define@choicekey{datagidx.sty}{prelocation}[\val\nr]%
    {none,enspace,space,dotfill,hfill}%
    {%
      \datagidx@setprelocation\nr
    }

location How to display the location list.
    \define@choicekey{datagidx.sty}{location}[\val\nr]%
    {hide,list,first}%
    {\datagidx@setlocation\nr}

see How to display the cross-reference list.
    \define@choicekey{datagidx.sty}{see}[\val\nr]%
    {comma,brackets,dot,space,nosep,semicolon,location}%
    {\datagidx@setsee\nr}

symbol How to format the symbol in relation to the description.
    \define@choicekey{datagidx.sty}{symboldesc}[\val\nr]%
    {symbol,desc,(symbol) desc,desc (symbol),symbol desc,desc symbol}%
    {\datagidx@formatsymdesc\nr}

compositor Location compositor.
    \define@key{datagidx.sty}{compositor}%
    {%
      \DTLgidxSetCompositor{\#1}%
    }%

```

```

final
  \DeclareOptionX{final}{%
    \let\datagidxshowifdraft\@gobble
  }

```

Set as default:

```
\let\datagidxshowifdraft\@gobble
```

```

draft
  \DeclareOptionX{draft}{%
    \let\datagidxshowifdraft\@firstofone
  }

```

```

verbose
  \define@choicekey{datagidx.sty}{verbose}[\val\nr]%
    {true,false}[true]%
    {%
      \csuse{dtlverbose\val}%
    }

```

Process package options:

```
\ProcessOptionsX
```

Database to keep track of all the defined terms.

```
\DTLnewdb{datagidx}
```

## 5.3 Glossary/Index Formatting

```

\seename
  \providecommand*\seename}{see}

```

```

\seealso
  \providecommand*\seealso}{see also}

```

```

LgidxSeeTagFont
  \newcommand*\DTLgidxSeeTagFont}[1]{\emph{#1}}

```

```

DTLgidxFormatSee \DTLgidxFormatSee{<tag>}{<label list>}

```

```

\newcommand*\DTLgidxFormatSee}[2]{%
  \DTLgidxSeeTagFont{#1} \DTLgidxSeeList{#2}%
}

```

`\idxFormatSeeAlso`

```
\DTLgidxFormatSeeAlso{<tag>}{<label list>}
```

```
\newcommand*{\DTLgidxFormatSeeAlso}[2]{%  
  \datagidxdoseealso  
  {%  
    \DTLgidxSeeTagFont{#1} \DTLgidxSeeList{#2}%  
  }%  
}
```

`\tagidxdoseealso`

```
\newcommand*{\datagidxdoseealso}[1]{%  
  \datagidxseealsostart  
  #1%  
  \datagidxseealsoend  
}
```

`\DTLgidxSeeList`

```
\DTLgidxSeeList{<label list>}
```

```
\newcommand*{\DTLgidxSeeList}[1]{%  
  \def\datagidx@sep{}%  
  \@for\dtl@thislabel:=#1\do  
  {%  
    \ifx\@xfor@nextelement\@nnil
```

Last iteration.

```
    \ifdefempty{\datagidx@sep}%  
    {%
```

Only one element in the list.

```
    }%  
    {%
```

Not the only element in the list.

```
    \DTLidxSeeLastSep  
    }%  
  \else
```

Not last iteration

```
    \datagidx@sep  
    \let\datagidx@sep\DTLidxSeeSep  
  \fi  
  \DTLidxFormatSeeItem{\dtl@thislabel}%  
}%  
}
```

idxFormatSeeItem	<pre>\DTLidxFormatSeeItem{&lt;label&gt;}</pre>
	<pre>\newcommand*{\DTLidxFormatSeeItem}[1]{%   \DTLgidxFetchEntry{\datagidx@value}{#1}{Name}%   \datagidxlink{#1}%   {%     \datagidx@value   }% }</pre>
\DTLidxSeeSep	<p>Separator in cross-reference list.</p> <pre>\newcommand*{\DTLidxSeeSep}{, }</pre>
\DTLidxSeeLastSep	<p>Final separator in cross-reference list.</p> <pre>\newcommand*{\DTLidxSeeLastSep}{ \&amp; }</pre>
DoSeeOrLocation	<p>You should have both a “see” list and a location list. This checks if \See is null. If it isn’t null, it does the “see” part, otherwise it deals with the location list.</p> <pre>\newcommand*{\DTLgidxDoSeeOrLocation}{%   \DTLifnull\See   {%     \See is null. Do we have a location?     \ifdefempty\Location     {%     }%     {%       \DTLgidxPreLocation       \DTLgidxLocation     }%   }%   {%   }% }</pre> <p>\See is not null, so do the cross-reference.</p> <pre>\DTLgidxSee }% }</pre>
idx@sortchildren	<p>The list of child labels needs to be sorted so that the child list follows the same ordering as the database.</p> <pre>\newcommand*{\datagidx@sortchildren}{%   \def\datagidx@sortedlist{%   \@for\Label:=\Children\do   {%     \edef\do@getrow{%       \noexpand\dtlgetrowforvalue       {\DTLgidxCurrentdb}%     }%   }% }</pre>

```

        {\dtlcolumnindex{\DTLgidxCurrenldb}{\Label}}%
        {\Label}%
    }%
    \do@getrow
Row index is stored in \dtlrownum. Is the sorted list empty?
    \ifdefempty\datagidx@sortedlist
    {%
Yes, it's empty.
        \edef\datagidx@newsortedlist{{\number\dtlrownum}{\Label}}%
    }%
    {%
No, it's not empty. Need to insert into list.
        \def\datagidx@newsortedlist{%
        \@for\@datagidx@thisval:=\datagidx@sortedlist\do
        {%
Get the index:
            \edef\datagidx@thisidx{\expandafter\@firstoftwo\@datagidx@thisval}%
Is index greater than \dtlrownum?
            \ifnum\datagidx@thisidx>\dtlrownum\relax
Yes, it is. So insert here.
                \ifdefempty\datagidx@newsortedlist
                {%
                \eappto\datagidx@newsortedlist
                {%
                {\number\dtlrownum}{\Label},\@datagidx@thisval
                }%
                }%
                {%
                \eappto\datagidx@newsortedlist
                {%
                ,{\number\dtlrownum}{\Label},\@datagidx@thisval
                }%
                }%
                }%
Break out of inner loop.
                \@endfortrue
            \else
            \ifdefempty\datagidx@newsortedlist
            {%
            \edef\datagidx@newsortedlist{%
            \@datagidx@thisval
            }%
            }%
            {%
            \eappto\datagidx@newsortedlist
            {%

```

```

        ,\@datagidx@thisval
      }%
    }%
  \fi
}%

```

Was the loop ended prematurely?

```
\if@endfor
```

If loop was ended on the last iteration, \@forremainder will be empty and there's nothing left to do.

```

\ifdefempty\@forremainder
{
}
{

```

Loop prematurely ended, so append remainder to list. newsortedlist,forremainder

```

}
\else

```

Loop wasn't prematurely terminated, so new value hasn't been added. Add now.

```

\ifdefempty\datagidx@newsortedlist
{
\edef\datagidx@newsortedlist{\number\dtlrownum}{\Label}}%
}
{
\eappto\datagidx@newsortedlist{,\number\dtlrownum}{\Label}}%
}
\fi
}%

```

Update.

```
\let\datagidx@sortedlist\datagidx@newsortedlist
```

Don't break out of outer loop.

```

\@endforfalse
}%
}

```

rt@foreachchild Sorted iteration through all the child labels.

```

\newcommand{\datagidx@sort@foreachchild}[1]{%
\datagidx@sortchildren

```

Sorted list stored in \datagidx@sortedlist

```

\@for\@datagidx@thisval:=\datagidx@sortedlist\do
{
\edef\Label{\expandafter\@secondoftwo\@datagidx@thisval}%
#1%
}%
}

```

rt@foreachchild Unsorted iteration through all the child labels.

```
\newcommand{\datagidx@unsort@foreachchild}[1]{%
  \@for\Label:=\Children\do
  {%
    #1%
  }%
}
```

DTLgidxChildren How to display the children

```
\newcommand*{\DTLgidxChildren}{%
  \bgroup
  \DTLifnull\Children
  {}%
  {%
    \advance\datagidx@level by 1\relax
    \datagidxchildstart
    \let\Parent\Label
    \datagidx@foreachchild
    {%
      \edef\do@getrow{%
        \noexpand\dtlgetrowforvalue
        {\DTLgidxCurrentdb}%
        {\dtlcolumnindex{\DTLgidxCurrentdb}{Label}}%
        {\Label}%
      }%
      \do@getrow
      \dtlgetentryfromcurrentrow
      {\Location}%
      {\dtlcolumnindex{\DTLgidxCurrentdb}{Location}}%
      \dtlgetentryfromcurrentrow
      {\See}%
      {\dtlcolumnindex{\DTLgidxCurrentdb}{See}}%
      \dtlgetentryfromcurrentrow
      {\SeeAlso}%
      {\dtlcolumnindex{\DTLgidxCurrentdb}{SeeAlso}}%
      \DTLifnull\Location
      {%
        \DTLifnull\See
        {%
          \DTLifnull\SeeAlso
          {}%
          {%
            \datagidx@displaychild
          }%
        }%
      }%
      {%
        \datagidx@displaychild
      }%
    }%
  }%
}
```

```

        {%
            \datagidx@displaychild
        }%
    }%
    \datagidxchildend
}%
\egroup
}

```

`xgetchildfields` Get the child fields from the current row.

```

\newcommand*{\datagidxgetchildfields}{%
    \dtlgetentryfromcurrentrow
    {\Name}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Name}}%
    \dtlgetentryfromcurrentrow
    {\Description}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Description}}%
    \dtlgetentryfromcurrentrow
    {\Symbol}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Symbol}}%
    \dtlgetentryfromcurrentrow
    {\Long}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Long}}%
    \dtlgetentryfromcurrentrow
    {\Short}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Short}}%
    \dtlgetentryfromcurrentrow
    {\Text}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Text}}%
    \dtlgetentryfromcurrentrow
    {\Plural}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Plural}}%
    \dtlgetentryfromcurrentrow
    {\Short}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Used}}%
    \dtlgetentryfromcurrentrow
    {\Children}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Child}}%
}

```

`dx@displaychild`

```

\newcommand*{\datagidx@displaychild}{%
    \datagidxgetchildfields
    \datagidxchilditem
}

```

Define some keys for `\newgloss`:

`atagidx@heading` Indicates how to format the heading in the glossary/index.



```

\ifdef{\chapter}
{
  \newcommand*\datagidx@heading{\chapter*}
}
\ifdef{\section}
{
  \newcommand*\datagidx@heading{\section*}
}
DTLgidxNoHeading Allow user to suppress the heading. (So to suppress the heading do heading=\DTLgidxNoHeading).
\let\DTLgidxNoHeading@gobble

idx@postheading Indicates what to do immediately after the heading.
\newcommand*\datagidx@postheading{}

agidx@multicols Should we use multicols or multicols*?
\newcommand*\datagidx@multicols{multicols}

\datagidx@sort Indicates how to sort the glossary/index. Defaults to word order.
\newcommand*\datagidx@sort{%
  \dtlwordindexcompare%
}

\@idxitem Some classes, such as beamer, don't define \@idxitem so if it's not already defined, define it
here.
\providecommand{\@idxitem}{\par\hangindent 40\p@}

\datagidxstart Indicates what to do at the start of the glossary/index.
\newcommand*\datagidxstart{%
  \bgroup
  \setlength{\parindent}{0pt}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \let\item\@idxitem
}

\datagidxend Indicates what to do at the end of the glossary/index.
\newcommand*\datagidxend{\egroup}

\datagidxtarget Provide a means to add a hypertarget if \hypertarget has been defined.
\newcommand*\@datagidxtarget}[2]{%
  \ifdef\hypertarget
  {%
    \bgroup
    \let\glsadd@gobble
    \settoheight\dimen@{#2}%
    \raisebox{\dimen@}{\hypertarget{#1}{}}%
    \egroup
  }%
}

```

```

    {%
    }%
    #2%
}
\newcommand*\datagidxtarget{\@datagidxtarget}

\datagidxlink Provide a means to add a link if \hyperlink has been defined.
\newcommand*\@datagidxlink[2]{%
  \ifdef\hyperlink
  {%
    \hyperlink{#1}{#2}%
  }%
  {%
    #2%
  }%
}
\newcommand*\datagidxlink{\@datagidxlink}

gidxEnableHyper Enable hyperlinks (if they are defined).
\newcommand*\DTLgidxEnableHyper{%
  \let\datagidxtarget\@datagidxtarget
  \let\datagidxlink\@datagidxlink
}

gidxDisableHyper Disable hyperlinks (if they are defined).
\newcommand*\DTLgidxDisableHyper{%
  \let\datagidxtarget\@secondoftwo
  \let\datagidxlink\@secondoftwo
}

datagidxgroupsep Indicates what to do between groups (after the previous group and before the header of the
next group).
\newcommand*\datagidxgroupsep{}

gidxgroupheader Indicates what to do at the start of a group. (The current group label can be accessed via
\datagidxcurrentgroup and the previous group label can be accessed via \datagidxprevgroup.)
\newcommand*\datagidxgroupheader{}

\datagidxitem Indicates what to do at the start of each item of the glossary/index.
\newcommand*\datagidxitem{}%

gidxchildstart Indicates what to do at the start of the child glossary/index.
\newcommand*\datagidxchildstart{}

datagidxchildend Indicates what to do at the end of the child glossary/index.
\newcommand*\datagidxchildend{}

```

datagidxchilditem Indicates what to do at the start of each item of the child glossary/index.  
`\newcommand*{\datagidxchilditem}{}`

datagidxseealsostart Indicates what to do at the start of the “see also” list.  
`\newcommand*{\datagidxseealsostart}{}`

datagidxseealsoend Indicates what to do at the end of the “see also” list.  
`\newcommand*{\datagidxseealsoend}{}`

doifsymlocwidth `\datagidx@doifsymlocwidth{<indent>}{<Name code>}{<Location code>}`

What to do if both the symbol width and the location width have been set.

```
\newcommand*{\datagidx@doifsymlocwidth}[3]{%
```

Calculate remaining space left for the description.

```
\setlength{\dtl@tmplength}{\linewidth}%  
\addtolength{\dtl@tmplength}{-#1}%  
\settowidth{\dimen@}{#2}%  
\addtolength{\dtl@tmplength}{-\dimen@}%  
\addtolength{\dtl@tmplength}{-\datagidxsymbolwidth}%  
\addtolength{\dtl@tmplength}{-\datagidxlocationwidth}%  
\settowidth{\dimen@}{\DTLgidxPreLocation}%  
\addtolength{\dtl@tmplength}{-\dimen@}%  
\settowidth{\dimen@}{\DTLgidxSymDescSep}%  
\addtolength{\dtl@tmplength}{-\dimen@}%  
\if@datagidxsymbolleft  
  \begin{minipage}[t]{\datagidxsymbolwidth}%  
    \datagidxsymalign  
    \let\DTLgidxSymDescSep\@empty  
    \DTLgidxSymbolDescLeft  
  \end{minipage}%  
  \DTLgidxSymDescSep  
  \begin{minipage}[t]{\dtl@tmplength}%  
    \let\DTLgidxSymDescSep\@empty  
    \DTLgidxSymbolDescRight  
  \end{minipage}%  
\else  
  \begin{minipage}[t]{\dtl@tmplength}%  
    \let\DTLgidxSymDescSep\@empty  
    \DTLgidxSymbolDescRight  
  \end{minipage}%  
  \DTLgidxSymDescSep  
  \begin{minipage}[t]{\datagidxsymbolwidth}%  
    \datagidxsymalign  
    \let\DTLgidxSymDescSep\@empty  
    \DTLgidxSymbolDescLeft
```

```

        \end{minipage}%
    \fi
    \DTLgidxPreLocation
    \begin{minipage}[t]{\datagidxlocationwidth}%
        \datagidxlocalign
        \let\DTLgidxPreLocation\@empty
        #3%
    \end{minipage}%
}

```

idx@doiflocwidth

```
\datagidx@doiflocwidth{<indent>}{<Name code>}{<Location code>}
```

What to do if only the location width has been set.

```
\newcommand*{\datagidx@doiflocwidth}[3]{%
```

Calculate remaining space left for the symbol and description.

```

    \setlength{\dtl@tmplength}{\linewidth}%
    \addtolength{\dtl@tmplength}{-#1}%
    \settowidth{\dimen@}{#2}%
    \addtolength{\dtl@tmplength}{-\dimen@}%
    \addtolength{\dtl@tmplength}{-\datagidxlocationwidth}%
    \settowidth{\dimen@}{\DTLgidxPreLocation}%
    \addtolength{\dtl@tmplength}{-\dimen@}%
    \begin{minipage}[t]{\dtl@tmplength}%
        \DTLgidxSymbolDescription
    \end{minipage}%
    \DTLgidxPreLocation
    \begin{minipage}[t]{\datagidxlocationwidth}%
        \datagidxlocalign
        \let\DTLgidxPreLocation\@empty
        #3%
    \end{minipage}%
}

```

idx@doifsymwidth

```
\datagidx@doifsymwidth{<indent>}{<Name code>}{<Location code>}
```

What to do if only the location width has been set.

```
\newcommand*{\datagidx@doifsymwidth}[3]{%
```

Calculate remaining space left for the description and location.

```

    \setlength{\dtl@tmplength}{\linewidth}%
    \addtolength{\dtl@tmplength}{-#1}%
    \settowidth{\dimen@}{#2}%
    \addtolength{\dtl@tmplength}{-\dimen@}%
    \addtolength{\dtl@tmplength}{-\datagidxsymbolwidth}%

```

```

\settowidth{\dimen@}{\DTLgidxSymDescSep}%
\addtolength{\dtl@tmplength}{-\dimen@}%
\if@datagidxsymbolleft
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
  \end{minipage}%
  \DTLgidxSymDescSep
  \begin{minipage}[t]{\dtl@tmplength}%
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescRight
    #3%
  \end{minipage}%
\else
  \begin{minipage}[t]{\dtl@tmplength}%
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescRight
  \end{minipage}%
  \DTLgidxSymDescSep
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft

```

This arrangement may look a bit weird.

```

  #3%
  \end{minipage}%
\fi
}

```

`\datagidxlocalign` Alignment of the location when the location width has been set.

```
\newcommand*{\datagidxlocalign}{\raggedleft}
```

`\datagidxsymalign` Alignment of the symbol when the symbol width has been set.

```
\newcommand*{\datagidxsymalign}{\centering}
```

### 5.3.1 Predefined styles

`\datagidxsetstyle` Sets the current index/glossary style

```

\newcommand*{\datagidxsetstyle}[1]{%
  \ifcsdef{datagidx@style@#1}%
  {%
    \csuse{datagidx@style@#1}%
  }%
  {%
    \PackageError{datagidx}{Unknown style ‘#1’}{}%
  }%
}

```

## index

idx@style@index Basic index style.

```
\newcommand*{\datagidx@style@index}{%
\renewcommand*{\datagidxstart}%
{%
\bgroup
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
```

Index columns are usually too narrow for fully justified text.

```
\raggedright
\let\item\@idxitem
```

Have the symbol or location widths been set?

```
\ifdim\datagidxsymbolwidth>0pt\relax
```

Symbol width has been set Has the location width been set?

```
\ifdim\datagidxlocationwidth>0pt\relax
```

Both have been set.

```
\def\datagidx@item@body{%
\datagidx@doifsymlocwidth{0pt}%
{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
{%
\DTLgidxDoSeeOrLocation
}%
}%
\else
```

Location width hasn't been set.

```
\def\datagidx@item@body{%
\datagidx@doiflocwidth{0pt}%
{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
{%
\DTLgidxDoSeeOrLocation
}%
}%
\fi
\else
```

Symbol width hasn't been set Has the location width been set?

```
\ifdim\datagidxlocationwidth>0pt\relax
```

Location width has been set.

```
\def\datagidx@item@body{%
\datagidx@doiflocwidth{0pt}%
{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
{%
\DTLgidxDoSeeOrLocation
}%
}%
\else
```

Neither have been set.

```
\def\datagidx@item@body{%
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
}%
\fi
\fi
}%
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{\ifdatagidxshowgroups\indexspace\fi}%
\renewcommand{\datagidxgroupheader}{%
  \ifdatagidxshowgroups
  \item
  \makebox[\linewidth]%
  {%
    \textbf{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}}%
  }%
  \DTLpar\nobreak\@afterheading
\fi
}%
\renewcommand*{\datagidxitem}{%
```

Is this the start of a new group?

```
\ifdefempty\datagidxprevgroup
{%
```

First item of the list.

```
\datagidxgroupheader
}%
{%
```

Not the first item of the list. Is this item's group the same as the last item's group?

```
\ifdequal\datagidxcurrentgroup\datagidxprevgroup
{%
```

Same, so do nothing.

```
}%
{%
```

Different, so do the separator and the header.

```
\datagidxgroupsep
\datagidxgroupheader
}%
}%
```

Now get on with this item.

```
\item
\datagidxtarget{\Label}%
{%
  \DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
}%
\DTLgidxPostName
```

```

\datagidx@item@body
\DTLgidxChildrenSeeAlso
}%
\renewcommand*{\datagidxchildstart}%
{%
  \bgroup
  \setlength{\parindent}{0pt}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \let\item\@idxitem
}%
\renewcommand*{\datagidxchildend}{\egroup}%
\renewcommand*{\datagidxchilditem}{%
  \setlength{\dimen@}{\datagidxindent}%
  \multiply\dimen@ by \datagidx@level\relax
  \@idxitem\hspace*{\dimen@}%
  \refstepcounter{DTLgidxChildCount}%
  \datagidxtarget{\Label}%
  {%
    \DTLgidxChildStyle
    {%
      \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
      \DTLgidxPostChildName
    }%
  }%
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
  \DTLgidxChildrenSeeAlso
}%
\renewcommand*{\datagidxseealsoend}{\egroup}%
\renewcommand*{\datagidxseealsoend}{\egroup}%
}

```

Make this the default style:

```
\datagidx@style@index
```

## indexalign

Similar to index style but aligns the descriptions.

```
style@indexalign
```



```

\newcommand*{\datagidx@style@indexalign}{%
  \renewcommand*{\datagidxstart}%
  {%
    \bgroup
    \setlength{\parindent}{0pt}%
    \setlength{\parskip}{0pt plus 0.3pt}%
    \setlength{\datagidxnamewidth}{0pt}%
    \DTLforeach*{\DTLgidxCurrentdb}%
      {\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
       \Parent=Parent}%
    {%
      \DTLifnull{\Parent}%
      {%
        \datagidx@doifdisplayed
        {%
          \settowidth{\dimen@}{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
          \ifdim\dimen@>\datagidxnamewidth\relax
            \datagidxnamewidth=\dimen@\relax
          \fi
        }%
      }%
    }%
  }%
  \settowidth{\dimen@}{\DTLgidxPostName}%
  \addtolength{\datagidxnamewidth}{\dimen@}%
  \setlength{\datagidxdescwidth}{\linewidth}%
  \addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
  \ifdim\datagidxsymbolwidth>0pt\relax
    \addtolength{\datagidxdescwidth}{-\datagidxsymbolwidth}%
    \settowidth{\dimen@}{\DTLgidxSymDescSep}%
    \addtolength{\datagidxdescwidth}{-\dimen@}%
  \fi
  \ifdim\datagidxlocationwidth>0pt\relax
    \addtolength{\datagidxdescwidth}{-\datagidxlocationwidth}%
    \settowidth{\dimen@}{\DTLgidxPreLocation}%
    \addtolength{\datagidxdescwidth}{-\dimen@}%
  \fi
}

Has the symbol width been set?
\ifdim\datagidxsymbolwidth>0pt\relax
Yes, symbol width has been set. Has the location width been set?
\ifdim\datagidxlocationwidth>0pt\relax
Both symbol and location widths have been set.
\if@datagidxsymbolleft
Symbol is on the left.
\def\datagidx@item@body{%
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign

```

```

        \let\DTLgidxSymDescSep\@empty
        \DTLgidxSymbolDescLeft
    \end{minipage}%
    \DTLgidxSymDescSep
    \begin{minipage}[t]{\datagidxdescwidth}%
        \let\DTLgidxSymDescSep\@empty
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescRight
    \end{minipage}%
    \DTLgidxPreLocation
    \begin{minipage}[t]{\datagidxlocationwidth}%
        \datagidxlocalign
        \let\DTLgidxPreLocation\@empty
        \DTLgidxDoSeeOrLocation
    \end{minipage}%
    }%
\else

```

Symbol is on the right.

```

    \def\datagidx@item@body{%
        \begin{minipage}[t]{\datagidxdescwidth}%
            \let\DTLgidxSymDescSep\@empty
            \DTLgidxSymbolDescLeft
        \end{minipage}%
        \DTLgidxSymDescSep
        \begin{minipage}[t]{\datagidxsymbolwidth}%
            \datagidxsymalign
            \let\DTLgidxSymDescSep\@empty
            \setlength{\parskip}{0pt plus 0.3pt}%
            \DTLgidxSymbolDescRight
        \end{minipage}%
        \DTLgidxPreLocation
        \begin{minipage}[t]{\datagidxlocationwidth}%
            \datagidxlocalign
            \let\DTLgidxPreLocation\@empty
            \DTLgidxDoSeeOrLocation
        \end{minipage}%
    }%
\fi
\else

```

Location width hasn't been set. (Only symbol width has been set.)

```

\if@datagidxsymbolleft
    \def\datagidx@item@body{%
        \begin{minipage}[t]{\datagidxsymbolwidth}%
            \datagidxsymalign
            \let\DTLgidxSymDescSep\@empty
            \DTLgidxSymbolDescLeft
        \end{minipage}%
        \DTLgidxSymDescSep
    }%
\fi

```

```

        \begin{minipage}[t]{\datagidxdescwidth}%
        \let\DTLgidxSymDescSep\@empty
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescRight
        \DTLgidxDoSeeOrLocation
    \end{minipage}%
}%
\else

```

Symbol is on the right. This combination may look weird.

```

    \def\datagidx@item@body{%
    \begin{minipage}[t]{\datagidxdescwidth}%
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
    \end{minipage}%
    \DTLgidxSymDescSep
    \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \setlength{\parskip}{0pt plus 0.3pt}%
    \DTLgidxSymbolDescRight
    \DTLgidxDoSeeOrLocation
    \end{minipage}%
}%
\fi
\fi
\else

```

Symbol width hasn't been set. Has the location width been set?

```
\ifdim\datagidxlocationwidth>0pt\relax
```

Only location width has been set.

```

    \def\datagidx@item@body{%
    \begin{minipage}[t]{\datagidxdescwidth}%
    \setlength{\parskip}{0pt plus 0.3pt}%
    \DTLgidxSymbolDescription
    \end{minipage}%
    \DTLgidxPreLocation
    \begin{minipage}[t]{\datagidxlocationwidth}%
    \datagidxlocalign
    \let\DTLgidxPreLocation\@empty
    \DTLgidxDoSeeOrLocation
    }%
\else

```

Neither location nor symbol widths have been set.

```

\def\datagidx@item@body{%
\begin{minipage}[t]{\datagidxdescwidth}%
\setlength{\parskip}{0pt plus 0.3pt}%
\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation

```

```

        \end{minipage}%
    }%
    \fi
\fi
}%
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{}%
\renewcommand*{\datagidxgroupheader}{}%
\renewcommand*{\datagidxitem}{%

```

Is this the start of a new group?

```

    \ifdefempty\datagidxprevgroup
    {%

```

First item of the list.

```

        \datagidxgroupheader
    }%
    {%

```

Not the first item of the list. Is this item's group the same as the last item's group?

```

    \ifdequal\datagidxcurrentgroup\datagidxprevgroup
    {%

```

Same, so do nothing.

```

    }%
    {%

```

Different, so do the separator and the header.

```

        \datagidxgroupsep
        \datagidxgroupheader
    }%
}%

```

Get on with this item

```

    \hangindent0pt\relax
    \parindent0pt\relax
    \makebox[\datagidxnamewidth] [l]%
    {%
        \datagidxtarget{\Label}%
        {%
            \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
            \DTLgidxPostName
        }%
    }%
    \datagidx@item@body
    \par
    \DTLgidxChildrenSeeAlso
    \par
}%
\renewcommand*{\datagidxchildstart}%
{%
    \bgroup

```

```

\setlength{\dimen@}{\datagidxindent}%
\multiply\dimen@ by \datagidx@level\relax
\setlength{\dtl@tmplength}{\linewidth}%
\addtolength{\dtl@tmplength}{-\dimen@}%
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
\edef\item{\noexpand\parshape=1 \the\dimen@ \the\dtl@tmplength}%
\setlength{\datagidxnamewidth}{0pt}%
\DTLforeach*{\DTLgidxCurrentdb}%
  {\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
  \Parent=Parent}%
{%
  \DTLifnull{\Parent}%
  {%
    \datagidx@doifdisplayed
    {%
      \settowidth{\dimen@}%
      {%
        \DTLgidxChildStyle
        {%
          \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
        }%
      }%
      \ifdim\dimen@>\datagidxnamewidth\relax
        \datagidxnamewidth=\dimen@\relax
      \fi
    }%
  }%
  {%
    \settowidth{\dimen@}{\DTLgidxChildStyle\DTLgidxPostChildName}%
    \addtolength{\datagidxnamewidth}{\dimen@}%
    \setlength{\datagidxdescwidth}{\dtl@tmplength}%
    \addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
  }%
}
\renewcommand{\datagidxchildend}{\egroup}%
\renewcommand*{\datagidxchilditem}{%
  \item
  \refstepcounter{DTLgidxChildCount}%
  \makebox[\datagidxnamewidth][l]%
  {%
    \datagidxtarget{\Label}%
    {%
      \DTLgidxChildStyle
      {%
        \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
        \DTLgidxPostChildName
      }%
    }%
  }%
}

```

```

    }%
    \begin{minipage}[t]{\datagidxdescwidth}%
      \setlength{\parskip}{0pt plus 0.3pt}%
      \DTLgidxSymbolDescription
      \DTLgidxDoSeeOrLocation
      \DTLgidxChildrenSeeAlso
    \end{minipage}%
  \par
}
}
}

```

`\datagidxindent` Indent used by index and indexalign styles.

```

\newlength\datagidxindent
\setlength\datagidxindent{10\p@}

```

### align

`\datagidxnamewidth` Length used by align and indexalign style name.

```

\newlength\datagidxnamewidth

```

`\datagidxdescwidth` Length used by align and indexalign style description.

```

\newlength\datagidxdescwidth

```

`\datagidx@style@align`

```

\newcommand*\datagidx@style@align{%
  \renewcommand*\datagidxstart{%
    {%
      \bgroup
      \setlength{\parindent}{0pt}%
      \setlength{\parskip}{0pt plus 0.3pt}%
      \setlength{\datagidxnamewidth}{0pt}%
      \DTLforeach*\DTLgidxCurrentdb{%
        {\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
          \Parent=Parent}%
      {%
        \DTLifnull{\Parent}%
        {%
          \datagidx@doifdisplayed
          {%
            \settowidth{\dimen@}{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
            \ifdim\dimen@>\datagidxnamewidth\relax
              \datagidxnamewidth=\dimen@\relax
            \fi
          }%
        }%
      }%
    }%
  \settowidth{\dimen@}{\DTLgidxPostName}%
  \addtolength{\datagidxnamewidth}{\dimen@}%
}

```

```

\setlength{\datagidxdescwidth}{\linewidth}%
\addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
\ifdim\datagidxsymbolwidth>0pt\relax
  \addtolength{\datagidxdescwidth}{-\datagidxsymbolwidth}%
  \settowidth{\dimen@}{\DTLgidxSymDescSep}%
  \addtolength{\datagidxdescwidth}{-\dimen@}%
\fi
\ifdim\datagidxlocationwidth>0pt\relax
  \addtolength{\datagidxdescwidth}{-\datagidxlocationwidth}%
  \settowidth{\dimen@}{\DTLgidxPreLocation}%
  \addtolength{\datagidxdescwidth}{-\dimen@}%
\fi

```

Has the symbol width been set?

```
\ifdim\datagidxsymbolwidth>0pt\relax
```

Yes, symbol width has been set. Has the location width been set?

```
\ifdim\datagidxlocationwidth>0pt\relax
```

Both symbol and location widths have been set.

```
\if@datagidxsymbolleft
```

Symbol is on the left.

```

\def\datagidx@item@body{%
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
  \end{minipage}%
  \DTLgidxSymDescSep
  \begin{minipage}[t]{\datagidxdescwidth}%
    \let\DTLgidxSymDescSep\@empty
    \setlength{\parskip}{0pt plus 0.3pt}%
    \DTLgidxSymbolDescRight
  \end{minipage}%
  \DTLgidxPreLocation
  \begin{minipage}[t]{\datagidxlocationwidth}%
    \datagidxlocalign
    \let\DTLgidxPreLocation\@empty
    \DTLgidxDoSeeOrLocation
    \DTLgidxChildrenSeeAlso
  \end{minipage}%
}%
\else

```

Symbol is on the right.

```

\def\datagidx@item@body{%
  \begin{minipage}[t]{\datagidxdescwidth}%
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
  \end{minipage}%

```

```

\DTLgidxSymDescSep
\begin{minipage}[t]{\datagidxsymbolwidth}%
  \datagidxsymalign
  \let\DTLgidxSymDescSep\@empty
  \setlength{\parskip}{0pt plus 0.3pt}%
  \DTLgidxSymbolDescRight
\end{minipage}%
\DTLgidxPreLocation
\begin{minipage}[t]{\datagidxlocationwidth}%
  \datagidxlocalign
  \let\DTLgidxPreLocation\@empty
  \DTLgidxDoSeeOrLocation
  \DTLgidxChildrenSeeAlso
\end{minipage}%
}%
\fi
\else

```

Location width hasn't been set. (Only symbol width has been set.)

```

\if@datagidxsymbolleft
\def\datagidx@item@body{%
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
  \end{minipage}%
  \DTLgidxSymDescSep
  \begin{minipage}[t]{\datagidxdescwidth}%
    \let\DTLgidxSymDescSep\@empty
    \setlength{\parskip}{0pt plus 0.3pt}%
    \DTLgidxSymbolDescRight
    \DTLgidxDoSeeOrLocation
    \DTLgidxChildrenSeeAlso
  \end{minipage}%
}%
\else

```

Symbol is on the right. This combination may look weird.

```

\def\datagidx@item@body{%
  \begin{minipage}[t]{\datagidxdescwidth}%
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
  \end{minipage}%
  \DTLgidxSymDescSep
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \setlength{\parskip}{0pt plus 0.3pt}%
    \DTLgidxSymbolDescRight
    \DTLgidxDoSeeOrLocation

```



```

        \DTLgidxChildrenSeeAlso
    \end{minipage}%
    }%
\fi
\fi
\else

```

Symbol width hasn't been set. Has the location width been set?

```

\ifdim\datagidxlocationwidth>0pt\relax

```

Only location width has been set.

```

\def\datagidx@item@body{%
    \begin{minipage}[t]{\datagidxdescwidth}%
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescription
    \end{minipage}%
    \DTLgidxPreLocation
    \begin{minipage}[t]{\datagidxlocationwidth}%
        \datagidxlocalign
        \let\DTLgidxPreLocation\@empty
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
    \end{minipage}%
    }%
\else

```

Neither location nor symbol widths have been set.

```

\def\datagidx@item@body{%
    \begin{minipage}[t]{\datagidxdescwidth}%
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescription
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
    \end{minipage}%
    }%
\fi
\fi
}%
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{\ifdatagidxshowgroups\indexspace\fi}%
\renewcommand{\datagidxgroupheader}{%
    \ifdatagidxshowgroups
        \item
        \makebox[\linewidth]{%
            {%
                \textbf{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
            }%
        }%
        \DTLpar\nobreak\@afterheading
    \fi
}%
\renewcommand*{\datagidxitem}{%

```

Is this the start of a new group?

```
\ifdefempty\datagidxprevgroup  
{%
```

First item of the list.

```
\datagidxgroupheader  
}%  
{%
```

Not the first item of the list. Is this item's group the same as the last item's group?

```
\ifdefequal\datagidxcurrentgroup\datagidxprevgroup  
{%
```

Same, so do nothing.

```
}%  
{%
```

Different, so do the separator and the header.

```
\datagidxgroupsep  
\datagidxgroupheader  
}%  
}%  
\hangindent0pt\relax  
\parindent0pt\relax  
\makebox[\datagidxnamewidth][l]%  
{%  
\datagidxtarget{\Label}%  
{%  
\DTLgidxNameFont{\DTLgidxNameCase{\Name}}%  
\DTLgidxPostName  
}%  
}%  
\datagidx@item@body  
\par  
}%  
\renewcommand*{\datagidxchildstart}%  
{%  
\bgroup  
\setlength{\parindent}{0pt}%  
\setlength{\parskip}{0pt plus 0.3pt}%  
\setlength{\datagidxnamewidth}{0pt}%  
\DTLforeach*{\DTLgidxCurrentdb}%  
{\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%  
\Parent=Parent}%  
{%  
\DTLifnull{\Parent}%  
{%  
\datagidx@doifdisplayed  
{%  
\settowidth{\dimen@}%  
{%
```



```

\bgroup
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
\setlength{\datagidxnamewidth}{0pt}%
\DTLforeach*{\DTLgidxCurrentdb}%
  {\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
  \Parent=Parent}%
{%
  \DTLifnull{\Parent}%
  {%
    \datagidx@doifdisplayed
    {%
      \settowidth{\dimen@}{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
      \ifdim\dimen@>\datagidxnamewidth\relax
        \datagidxnamewidth=\dimen@\relax
      \fi
    }%
  }%
  {%
    \settowidth{\dimen@}{\DTLgidxPostName}%
    \addtolength{\datagidxnamewidth}{\dimen@}%
    \setlength{\datagidxdescwidth}{\linewidth}%
    \addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
  }%
  \renewcommand*{\datagidxend}{\egroup}%
  \renewcommand*{\datagidxgroupsep}{\ifdatagidxshowgroups\indexspace\fi}%
  \renewcommand{\datagidxgroupheader}{%
    \ifdatagidxshowgroups
      \item
      \makebox[\linewidth]%
      {%
        \textbf{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
      }%
      \DTLpar\nobreak\@afterheading
    \fi
  }%
  \renewcommand*{\datagidxitem}{%
Is this the start of a new group?
    \ifdefempty\datagidxprevgroup
    {%
First item of the list.
      \datagidxgroupheader
    }%
    {%
Not the first item of the list. Is this item's group the same as the last item's group?
      \ifdefequal\datagidxcurrentgroup\datagidxprevgroup
      {%

```

Same, so do nothing.

```
}%  
{%
```

Different, so do the separator and the header.

```
    \datagidxgroupsep  
    \datagidxgroupheader  
  }%  
}%  
\hangindent0pt\relax  
\parindent0pt\relax  
\makebox[\datagidxnamewidth][l]%  
{%  
  \datagidxtarget{\Label}%  
  {%  
    \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%  
    \DTLgidxPostName  
  }%  
}%  
\begin{minipage}[t]{\datagidxdescwidth}%  
  \setlength{\parskip}{0pt plus 0.3pt}%  
  \@tempswatru  
  \ifdefempty{\Description}%  
  {%  
    \ifdefempty{\Symbol}%  
    {%  
      \ifdefempty{\Location}{\@tempswafalse}{}%  
    }%  
  }%  
  }%  
  \if@tempswa  
    \DTLgidxSymbolDescription  
    \DTLgidxDoSeeOrLocation  
  
  \else  
    \mbox{}%  
  \fi  
  \DTLgidxChildrenSeeAlso  
\end{minipage}%  
\par  
}%  
\renewcommand*{\datagidxchildstart}%  
{%  
  \bgroup  
  \def\datagidx@childsep{}%  
  \setcounter{DTLgidxChildCount}{0}%  
}%  
\renewcommand{\datagidxchildend}{\DTLgidxPostChild\egroup}%  
\renewcommand*{\datagidxchilditem}{%
```

```

\datagidx@childsep
\refstepcounter{DTLgidxChildCount}%
\datagidxtarget{\Label}%
{%
  \DTLgidxChildStyle
  {%
    \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
    \DTLgidxPostChildName
  }%
}%
\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation
\DTLgidxChildrenSeeAlso
\let\datagidx@childsep\DTLgidxChildSep
}%
}

```

`DTLgidxChildSep` Separator between child entries for gloss style.

```
\newcommand*{\DTLgidxChildSep}{ }
```

`DTLgidxPostChild` What to put at the end of child entries for gloss style.

```
\newcommand*{\DTLgidxPostChild}{}
```

`DTLgidxDictHead` Group header for dict style.

```

\ifdef\chapter
{%
  \newcommand\DTLgidxDictHead{%
    \chapter{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
  }%
}%
{%
  \newcommand\DTLgidxDictHead{%
    \section{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
  }%
}%
}

```

`DTLgidxCategoryNameFont` Font used for ‘category’ entries with ‘dict’ style.

```
\newcommand*{\DTLgidxCategoryNameFont}[1]{#1}
```

`DTLgidxCategorySep` Separator used with ‘dict’ style.

```
\newcommand*{\DTLgidxCategorySep}{\space}
```

`DTLgidxSubCategorySep` Separator used with ‘dict’ style.

```
\newcommand*{\DTLgidxSubCategorySep}{\space}
```

`DTLgidxdictindent` Indent used by ‘dict’ style.

```
\newcommand*{\datagidxdictindent}{1em}
```

idxDictPostItem What to do at the end of each item in the ‘dict’ style.

```
\newcommand{\DTLgidxDictPostItem}{\par}
```

gidx@style@dict Dictionary style. This assumes a hierarchical structure where the top level entries have a name. The next level is used to indicate a category, such as “adjective” or “noun”. If there is only one meaning this level also has a description. If there is more than one meaning, each meaning should be a child of the category entry. Only third level entries are numbered. The child key is ignored in this style. The symbol is ignored. The location and symbols widths are also ignored.

```
\newcommand*{\datagidx@style@dict}{%
  \renewcommand*{\datagidxstart}{%
    {%
      \bgroup
      \setlength{\parindent}{0pt}%
      \setlength{\parskip}{0pt plus 0.3pt}%
      \dimen@=\linewidth
      \advance\dimen@ by -\datagidxdictindent\relax
      \dtl@tmplength=\datagidxdictindent\relax
      \xdef\datagidxdictparshape{%
        \noexpand\parshape=2 0pt \the\linewidth\space
        \the\dtl@tmplength\space \the\dimen@\relax
      }%
      \datagidx@level=1\relax
```

Index columns are usually too narrow for fully justified text.

```
\raggedright
}%
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{}%
\renewcommand{\datagidxgroupheader}{%
  \ifdatagidxshowgroups
    \datagidxend
    \datagidx@postend
    \DTLgidxDictHead
    \datagidx@prestart
    \datagidxstart
  \fi
}%
\renewcommand*{\datagidxitem}{%
```

Is this the start of a new group?

```
\ifdefempty\datagidxprevgroup
{%
```

First item of the list.

```
\datagidxgroupheader
}%
{%
```

Not the first item of the list. Is this item’s group the same as the last item’s group?

```

\ifdefequal\datagidxcurrentgroup\datagidxprevgroup
{%

```

Same, so do nothing.

```

}%
{%

```

Different, so do the separator and the header.

```

\datagidxgroupsep
\datagidxgroupheader
}%
}%

```

Now get on with this item.

```

\datagidxdictparshape
\datagidxtarget{\Label}%
{%
\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
}%
\DTLgidxPostName

```

Initialise category separator to do nothing.

```

\let\datagidx@catsep\@empty
\let\datagidx@subcatsep\@empty
\DTLgidxSymbolDescription

```

No location list.

```

\DTLgidxChildrenSeeAlso
\DTLgidxDictPostItem
}%
\renewcommand*{\datagidxchildstart}%
{%
\bgroup
}%
\renewcommand*{\datagidxchildend}{\egroup}%
\renewcommand*{\datagidxchilditem}{%

```

Which level are we on?

```

\ifnum\datagidx@level=2\relax

```

Category entry

```

\datagidx@catsep
\let\datagidx@catsep\DTLgidxCategorySep
\let\datagidx@subcapsep\@empty
\datagidxtarget{\Label}%
{%
\DTLgidxChildStyle
{%
\DTLgidxCategoryNameFont{\DTLgidxNameCase{\Name}}}%
\DTLgidxPostChildName
}%
}%

```



```

        \setcounter{DTLgidxChildCount}{0}%
    \else
Sub Category entry
        \datagidx@subcatsep
        \let\datagidx@subcatsep\DTLgidxSubCategorySep
        \refstepcounter{DTLgidxChildCount}%
        \DTLgidxChildCountLabel
        \DTLgidxPostChildName
    \fi
    \DTLgidxSymbolDescription
    \DTLgidxDoSeeOrLocation
    \DTLgidxChildrenSeeAlso
}%
\renewcommand*{\datagidxseealsostart}%
{%
    \bgroup
        \setlength{\parindent}{0pt}%
        \setlength{\parskip}{0pt plus 0.3pt}%
        \setlength{\dimen@}{\datagidxindent}%
        \advance\datagidx@level by 1\relax
        \multiply\dimen@ by \datagidx@level\relax
        \idxitem\hspace*{\dimen@}%
    }%
\renewcommand{\datagidxseealsoend}{\egroup}%
}

```

### 5.3.2 Location Lists

`dofirstlocation` Only display the first location in the list.

```

\newcommand*{\dtldofirstlocation}{%
    \@for\dtl@thisloc:=\Location\do{%
        \ifdefempty\dtl@thisloc
        }{%
        }%
        \expandafter\datagidx@getlocation\dtl@thisloc
        \datagidxlink{\datagidx@current@target}%
        {%
            \datagidx@formatlocation
            \datagidx@current@format\datagidx@current@locationstring
        }%
    }%
}

```

Only interested in the first item, so break out of loop.

```

        \@endfortrue
    }%
}%
}

```

`@formatlocation`

```

\newcommand*{\datagidx@formatlocation}[2]{%
  \ifdefempty{#1}%
  {#2}%
  {%
    \ifcsdef{#1}%
    {%
      \csuse{#1}{#2}%
    }%
    {%
      \PackageWarning{datagidx}{Unknown format ‘#1’}%
      #2%
    }%
  }%
}

```

`\dtldolocationlist` Display the location list.

```

\newcommand*{\dtldolocationlist}{%
  \DTLifnull{\Location}%
  {}%
  {%
    \def\datagidx@prev@location{-1}%
    \def\datagidx@prev@locationstring{}%
    \def\datagidx@prev@format{}%
    \def\datagidx@prev@locationformat{}%
    \def\datagidx@prev@prefix{}%
    \def\datagidx@prev@target{}%
    \def\datagidx@location@sep{}%
    \def\datagidx@location@start{-1}%
    \expandafter\forcsvlist\expandafter\datagidx@parse@location
    \expandafter{\Location}%
    \do@prevlocation % tidy up loose ends
  }%
}

```

`@dtl@sequential` Conditional to keep track of sequences.

```

\newif\if@dtl@sequential

```

`datagidx@getlocdo` Handler for `\datagidx@docomplis`

```

\newcommand*\datagidx@getlocdo[1]{%
  \ifdefempty\datagidx@current@location
  {}%
  {%
    \eappto\datagidx@current@prefix{%
      \datagidx@current@location\datagidx@compositor
    }%
  }%
  \def\datagidx@current@location{#1}%
}

```

`idx@getlocation` Get the location and store in `\current@location`:

```
\def\datagidx@getlocation[#1]#2#3{%
```

Store the original value.

```
\def\datagidx@current@locationstring{#2}%
```

```
\bgroup
```

```
\datagidx@escapelocationformat
```

```
\xdef\datagidx@current@locationformat{#2}%
```

```
\datagidx@clearlocationformat
```

```
\xdef\datagidx@current@location{#2}%
```

```
\egroup
```

If the location contains a compositor, we need to get the final element and store the rest as a prefix:

```
\let\datagidx@list\datagidx@current@location
```

```
\def\datagidx@current@prefix{}%
```

```
\def\datagidx@current@location{}%
```

```
\let\do\datagidx@getlocdo
```

```
\expandafter\datagidx@docomplis
```

```
\expandafter{\datagidx@list}%
```

Store the format:

```
\def\datagidx@current@format{#1}%
```

Store the target:

```
\def\datagidx@current@target{#3}%
```

```
}
```

`@parse@location` Parses the location list (given in the argument).

```
\newcommand*{\datagidx@parse@location}[1]{%
```

Parse location format.

```
\datagidx@getlocation#1\relax
```

If this is the same as the previous location, do nothing.

```
\ifdefequal{\datagidx@prev@locationstring}{\datagidx@current@locationstring}%  
{%
```

If the format is different, let the non-empty format over-ride the empty format.

```
\ifdefequal{\datagidx@prev@format}{\datagidx@current@format}%
```

```
{%
```

```
}%
```

```
{%
```

```
\ifdefempty{\datagidx@current@format}%
```

```
{%
```

Current format is empty, so keep previous unchanged.

```
}%
```

```
{%
```

```
\ifdefempty{\datagidx@prev@format}%
```

```
{%
```

Previous format is empty, so update.

```
        \let\datagidx@prev@format\datagidx@current@format
    }%
    {%
        \PackageWarning{datagidx}%
        {%
            Conflicting location formats ‘\datagidx@prev@format’ and
            ‘\datagidx@current@format’ for location ‘\datagidx@current@location’%
        }%
    }%
}%
}%
}%
    \@datagidx@parse@location
}%
}
```

@parse@location

```
\newcommand*{\@datagidx@parse@location}{%
```

Check if we have a sequence.

```
\@dtl@sequentialtrue
```

A change in font format breaks the sequence.

```
\ifdefequal{\datagidx@prev@format}{\datagidx@current@format}%
{%
```

A change in location format breaks the sequence.

```
\ifdefequal{\datagidx@prev@locationformat}{\datagidx@current@locationformat}%
{%
```

A change in prefix breaks the sequence.

```
\ifdefequal{\datagidx@prev@prefix}{\datagidx@current@prefix}%
{%
}%
{%
```

Prefixes are different, so not a sequence.

```
\@dtl@sequentialfalse
}%
}%
{%
```

Formats are different, so not a sequence.

```
\@dtl@sequentialfalse
}%
}%
{%
```

Formats are different, so not a sequence.

```
\@dtl@sequentialfalse
```

```
}%
\if@dtl@sequential
```

Is this location one more than the previous location?

```
\ifnumequal{\datagidx@prev@location+1}{\datagidx@current@location}%
{%
```

It is one more than previous value. Is this location the same type as the previous location?

```
\ifdefequal
\datagidx@current@locationformat
\datagidx@prev@locationformat
{%
```

They are the same, so we have a sequence.

```
\@dtl@sequentialtrue
}%
{%
```

They aren't the same, so we don't have a sequence.

```
\@dtl@sequentialfalse
}%
}%
{%
\@dtl@sequentialfalse
}%
\fi
```

Has the sequence flag been set?

```
\if@dtl@sequential
```

Yes, we have a sequence. Has the start of the sequence been set?

```
\ifnumequal{\datagidx@location@start}{-1}%
{%
```

No it hasn't, so set it

```
\let\datagidx@location@start\datagidx@prev@location
\let\datagidx@location@startval\datagidx@prev@locationstring
\let\datagidx@location@format\datagidx@prev@format
\let\datagidx@location@target\datagidx@prev@target
}%
{%
}%
\else
```

We don't have a sequence, so do the previous location.

```
\do@prevlocation
\fi
```

Update previous location macros to this location.

```
\let\datagidx@prev@location\datagidx@current@location
\let\datagidx@prev@format\datagidx@current@format
\let\datagidx@prev@prefix\datagidx@current@prefix
\let\datagidx@prev@locationformat\datagidx@current@locationformat
```

```

\let\datagidx@prev@locationstring\datagidx@current@locationstring
\let\datagidx@prev@target\datagidx@current@target
}

```

`gidxLocationSep` Separator between locations.

```
\newcommand*\DTLgidxLocationSep}{, }
```

`TLgidxLocationF` How to format a location list consisting of only two locations.

```
\newcommand*\DTLgidxLocationF}[2]{%
#1\DTLgidxLocationSep#2%
}
```

`LgidxLocationFF` How to format a location list consisting of three or more locations.

```
\newcommand*\DTLgidxLocationFF}[2]{%
#1--#2%
}
```

`do@prevlocation` Do the previous location in the current list.

```
\newcommand*\do@prevlocation}{%
```

Have we come to the end of a sequence?

```
\ifnumequal{\datagidx@location@start}{-1}%
{%
```

Not the end of a sequence.

```

\ifdefempty{\datagidx@prev@locationstring}%
}{%
{%
\datagidx@location@sep
\datagidxlink{\datagidx@prev@target}%
{%
\datagidx@formatlocation
\datagidx@prev@format\datagidx@prev@locationstring
}%
\def\datagidx@location@sep{\DTLgidxLocationSep}%
}%
}%
{%

```

At the end of a sequence.

```

\datagidx@location@sep
\do@locrange
\def\datagidx@location@sep{\DTLgidxLocationSep}%
\def\datagidx@location@start{-1}%
}%
}

```

`\do@locrange` Format the location range.

```
\newcommand*\do@locrange}{%
```

Are the start and end locations 2 or more apart?

```
\ifnumgreater{\datagidx@prev@location}{\datagidx@location@start+1}%  
{%
```

Yes, they are, so form a range:

```
\DTLgidxLocationFF  
{%  
  \datagidxlink{\datagidx@location@target}%  
  {%  
    \datagidx@formatlocation  
    \datagidx@location@format\datagidx@location@startval  
  }%  
}%  
{%  
  \datagidxlink{\datagidx@prev@target}%  
  {%  
    \datagidx@formatlocation  
    \datagidx@prev@format\datagidx@prev@locationstring  
  }%  
}%  
}%  
{%
```

No, they aren't so don't form a range:

```
\DTLgidxLocationF  
{%  
  \datagidxlink{\datagidx@location@target}%  
  {%  
    \datagidx@formatlocation  
    \datagidx@location@format\datagidx@location@startval  
  }%  
}%  
{%  
  \datagidxlink{\datagidx@prev@target}%  
  {%  
    \datagidx@formatlocation  
    \datagidx@prev@format\datagidx@prev@locationstring  
  }%  
}%  
}%  
}
```

## 5.4 Defining New Glossary/Index Databases

`defaultdatabase` The default database to which terms should be added.

```
\newcommand*{\datagidx@defaultdatabase}{}
```

`idxSetDefaultDB` Allow user to set the default database

```
\newcommand*{\DTLgidxSetDefaultDB}[1]{%
```

```

\renewcommand*\datagidx@defaultdatabase}{#1}%
}

```

Define keys for \newgidx:

```

\define@key{newgloss}{heading}{\renewcommand*\datagidx@heading}{#1}}
\define@key{newgloss}{postheading}{%
\renewcommand*\datagidx@postheading}{#1}%
}

```

datagidxbalance

```

\newif\ifdatagidxbalance
\datagidxbalancetrue

\define@choicekey{newgloss}{balance}[\val\nr]{true,false}[true]{%
\ifcase\nr\relax
\renewcommand*\datagidx@multicols}{multicols}%
\datagidxbalancetrue
\or
\renewcommand*\datagidx@multicols}{multicols*}%
\datagidxbalancefalse
\fi
}
\define@key{newgloss}{sort}{\renewcommand*\datagidx@sort}{#1}}

```

Default style is 'index':

```

\newcommand*\datagidx@style}{index}
\define@key{newgloss}{style}{\renewcommand*\datagidx@style}{#1}}

```

Define conditional to determine whether or not to show group headers and do sep. (Default is false.)

agidxshowgroups

```

\newif\ifdatagidxshowgroups
\newcommand*\datagidx@showgroups}{false}

\define@choicekey{newgloss}{showgroups}{true,false}[true]%
{%
\renewcommand{\datagidx@showgroups}{#1}%
}%

```

\newgidx `\newgloss[options]{database name}{title}`

Define \newgidx if it hasn't already been defined by the 'highopt' optimize setting.

```

\ifundef\newgidx
{%
\newcommand*\newgidx}{\datagidx@newgidx}
}%
{}

```



May only be used in the preamble (otherwise the entries will be undefined when their locations are read from the aux file).

```
\@onlypreamble\newgidx
```

highopt@newgidx The behaviour of \newgidx when the 'highopt' optimize option has been set.

```
\newcommand*{\datagidx@highopt@newgidx}[3] [] {%
```

Get the file name:

```
\edef\datagidx@indexfilename{\datagidxhighoptfilename{#2}}%
```

Has the file been created?

```
\IfFileExists{\datagidx@indexfilename}%  
{%
```

File does exist. Load it.

```
\input{\datagidx@indexfilename}%
```

Update the 'datagidx' database.

```
\bgroup  
  \setkeys{newgloss}{#1}%  
  \datagidx@newgidx@update{#2}{#3}%  
\egroup  
}%  
{%
```

File doesn't exist. Behave as normal.

```
\datagidx@newgidx[#1]{#2}{#3}%  
}%  
}
```

```
\loadgidx \loadgidx[options]{filename}{title}
```

Loads a datagidx database.

```
\newcommand*{\loadgidx}[3] [] {%
```

Load database:

```
\input{#2}%
```

Update the 'datagidx' database. (Assume database is already sorted.)

```
\bgroup  
  \setkeys{newgloss}{sort={},#1}%  
  \expandafter\datagidx@newgidx@update\expandafter  
  {\dtllastloadeddb}{#3}%  
\egroup
```

Set this as the default database:

```
\edef\datagidx@defaultdatabase{\dtllastloadeddb}%
```

Assign labels to this database.

```
\dtlforcolumn{\Label}{\dtllastloadeddb}{\Label}%  
{%  
  \csxdef{datagidxentry@\Label}{\dtllastloadeddb}%  
}%  
}
```

May only be used in the preamble (otherwise the entries will be undefined when their locations are read from the aux file).

```
\@onlypreamble\loadgidx
```

`\datagidx@newgidx` The normal behaviour of `\newgidx`

```
\newcommand*{\datagidx@newgidx}[3] [] {%  
  \bgroup  
  \setkeys{newgloss}{#1}%  
}
```

If no default database has been identified, set the default to this database.

```
\ifdefempty{\datagidx@defaultdatabase}%  
{\xdef\datagidx@defaultdatabase{#2}}%  
{}%  
\DTLgnewdb{#2}%  
\DTLaddcolumn{#2}{\Label}%  
\DTLaddcolumn{#2}{\Location}%  
\DTLaddcolumn{#2}{\CurrentLocation}%  
\DTLaddcolumn{#2}{\FirstId}%  
\DTLaddcolumn{#2}{\Name}%  
\DTLaddcolumn{#2}{\Text}%  
\DTLaddcolumn{#2}{\Parent}%  
\DTLaddcolumn{#2}{\Child}%  
\DTLaddcolumn{#2}{\Description}%  
\DTLaddcolumn{#2}{\Used}%  
\DTLaddcolumn{#2}{\Symbol}%  
\DTLaddcolumn{#2}{\Long}%  
\DTLaddcolumn{#2}{\Short}%  
\DTLaddcolumn{#2}{\See}%  
\DTLaddcolumn{#2}{\SeeAlso}%  
\datagidx@newgidx@update{#2}{#3}%  
\egroup  
}
```

`\@newgidx@update` Update the 'datagidx' database.

```
\newcommand*{\datagidx@newgidx@update}[2] {%  
  \DTLnewrow{datagidx}%  
  \DTLnewbentry{datagidx}{\Glossary}{#1}%  
  \DTLnewbentry{datagidx}{\Title}{#2}%  
  {%  
    \dtlexpandnewvalue  
    \DTLnewbentry{datagidx}{\Heading}{\expandonce\datagidx@heading}%  
    \DTLnewbentry{datagidx}{\PostHeading}{\expandonce\datagidx@postheading}%  
    \DTLnewbentry{datagidx}{\MultiCols}{\expandonce\datagidx@multicols}%  
  }  
}
```

```

\DTLnewbentry{datagidx}{Sort}{\expandonce\datagidx@sort}%
\DTLnewbentry{datagidx}{Style}{\expandonce\datagidx@style}%
\DTLnewbentry{datagidx}{ShowGroups}{\expandonce\datagidx@showgroups}%
}%
}

```

## 5.5 Defining New Terms

### 5.5.1 Options

Define some keys for `\newterm`:

```

\newterm@label
\newcommand*{\newterm@label}{}
\define@key{newterm}{label}{\renewcommand*{\newterm@label}{#1}}

\newterm@parent
\newcommand*{\newterm@parent}{}
\define@key{newterm}{parent}{\renewcommand*{\newterm@parent}{#1}}

\newterm@text
\newcommand*{\newterm@text}{}
\define@key{newterm}{text}{\renewcommand*{\newterm@text}{#1}}

\newterm@description
\newcommand*{\newterm@description}{}
\define@key{newterm}{description}{%
  \renewcommand*{\newterm@description}{#1}%
}

\newterm@plural
\define@key{newterm}{plural}{\def\newterm@plural{#1}}

\newterm@sort
\newcommand*{\newterm@sort}{}
\define@key{newterm}{sort}{\renewcommand*{\newterm@sort}{#1}}

\newterm@symbol
\newcommand*{\newterm@symbol}{}
\define@key{newterm}{symbol}{\renewcommand*{\newterm@symbol}{#1}}

\newterm@database
\newcommand*{\newterm@database}{}
\define@key{newterm}{database}{\renewcommand*{\newterm@database}{#1}}

```

```

\newterm@long
\newcommand*\newterm@long{}
\define@key{newterm}{long}{%
  \renewcommand*\newterm@long{#1}%
  \def\newterm@longplural{#1s}%
}

```

```

\newterm@short
\newcommand*\newterm@short{}
\define@key{newterm}{short}{%
  \renewcommand*\newterm@short{#1}%
  \def\newterm@shortplural{#1s}%
}

```

```

term@longplural
\define@key{newterm}{longplural}{%
  \def\newterm@longplural{#1}%
}

```

```

erm@shortplural
\define@key{newterm}{shortplural}{%
  \def\newterm@shortplural{#1}%
}

```

```

\newterm@see “see” should not be used with a location list. If you have a location list and want a cross-
reference use “see also” instead.
\newcommand*\newterm@see{}
\define@key{newterm}{see}{%
  \renewcommand*\newterm@see{#1}%
}

```

```

newterm@seealso “see also” should be used with a location list (or with child entries with location lists). If an
entry has no location list and not child entries use “see” instead.
\newcommand*\newterm@seealso{}
\define@key{newterm}{seealso}{%
  \renewcommand*\newterm@seealso{#1}%
}

```

## 5.5.2 New Terms

```

rm@defaultshook
\newcommand*\newterm@defaultshook{}

```

```

erm@extrafields
\newcommand*\newterm@extrafields{}

```

LgidxAssignList Assignment list used by \printterms

```

\newcommand*{\DTLgidxAssignList}{%
  \Name=Name,\Description=Description,\Used=Used,\Symbol=Symbol,%
  \Long=Long,\Short=Short,\LongPlural=LongPlural,\ShortPlural=ShortPlural,%
  \Location=Location,\See=See,\SeeAlso=SeeAlso,%
  \Text=Text,\Plural=Plural,\CurrentLocation=CurrentLocation,%
  \Label=Label,\Parent=Parent,\Children=Child,\FirstId=FirstId,\Sort=Sort%
}

```

datagidxtermkeys Keys defined for \newterm corresponding to fields (“name” is added for convenience).

```

\newcommand*{\datagidxtermkeys}{%
  name,description,symbol,long,short,see,seealso,text,plural,%
  label,parent,sort%
}

```

Access keys corresponding to given fields

```

\newcommand*\@datagidx@fieldkey@Name{name}%
\newcommand*\@datagidx@fieldkey@Description{description}%
\newcommand*\@datagidx@fieldkey@Symbol{symbol}%
\newcommand*\@datagidx@fieldkey@Long{long}%
\newcommand*\@datagidx@fieldkey@Short{short}%
\newcommand*\@datagidx@fieldkey@See{see}%
\newcommand*\@datagidx@fieldkey@SeeAlso{seealso}%
\newcommand*\@datagidx@fieldkey@Text{text}%
\newcommand*\@datagidx@fieldkey@Plural{plural}%
\newcommand*\@datagidx@fieldkey@Label{label}%
\newcommand*\@datagidx@fieldkey@Parent{parent}%
\newcommand*\@datagidx@fieldkey@Sort{sort}%

```

\newtermaddfield `\newtermaddfield[<db list>]{<column key>}{<new term key>}{<default value>}`

The default value may contain \field{<key>} to get the value of another field.

```

\newcommand*{\newtermaddfield}[4] [] {%

```

If optional argument not specified, iterate over all defined glossaries/indices

```

  \ifstrempy{#1}%
  {%
    \dtlforcolumn{\datagidx@thisidx}{datagidx}{Glossary}%
    {%
      \DTLaddcolumn{\datagidx@thisidx}{#2}%
    }%
  }%
  {%
    \@for\datagidx@thisidx:=#1\do
    {%

```

```

        \DTLaddcolumn{\datagidx@thisidx}{#2}%
    }%
}%
\expandafter\gdef\csname newterm@#3\endcsname{}%
\define@key{newterm}{#3}%
{%
    \expandafter\def\csname newterm@#3\endcsname{##1}%
}%
\gappto\newterm@defaultshook
{%
    \expandafter\protected@edef\csname newterm@#3\endcsname{#4}%
}%
\gappto\newterm@extrafields
{%
    \protected@edef\datagidx@value{\csname newterm@#3\endcsname}%
    \DTLnewbentry{\newterm@database}{#2}{\expandonce\datagidx@value}%
}%
\xappto\DTLgidxAssignList
{%
    ,\expandafter\noexpand\csname#2\endcsname=#2%
}%
\xappto\datagidxtermkeys{,#3}%
\expandafter\xdef\csname @datagidx@fieldkey@#2\endcsname{#3}%
\xappto\datagidxgetchildfields
{%
    \noexpand\dtlgetentryfromcurrentrow
    {\expandafter\noexpand\csname#2\endcsname}%
    {\noexpand\dtlcolumnindex{\noexpand\DTLgidxCurrentdb}{#2}}%
}%
}
}

```

newtermlabelhook

```
\newcommand*{\newtermlabelhook}{}
```

DTLgidxNoFormat

```
\newcommand*{\DTLgidxNoFormat}[1]{#1}
```

\DTLgidxGobble

```
\newcommand*{\DTLgidxGobble}[1]{}
```

xStripBackslash

Argument must be a control sequence. This is stringified and the first character (The backslash) is removed).

```

\newcommand*{\DTLgidxStripBackslash}[1]{%
    \expandafter@gobble\string#1%
}

```

\DTLgidxName

```
\DTLgidxName{<forenames>}{<surname>}
```

How to format a person's name in the text.

```
\newcommand*{\DTLgidxName}[2]{%  
  #1\space #2%  
}
```

\DTLgidxNameNum

```
\DTLgidxNameNum{<n>}
```

The argument *<n>* should be a number applied to a name (e.g. James<sub>□</sub>\DTLgidxNameNum1). This is converted to a two-digit number for sorting but a Roman numeral for the label and in the text.

```
\newcommand*{\DTLgidxNameNum}[1]{\@Roman{#1}}
```

\DTLgidx@namenum

Conversion for sort key.

```
\newcommand*{\datagidx@namenum}[1]{\two@digits{#1}}
```

\DTLgidxPlace

```
\DTLgidxPlace{<country>}{<town/city>}
```

How to format a place in the text.

```
\newcommand*{\DTLgidxPlace}[2]{%  
  #2%  
}
```

\DTLgidxSubject

```
\DTLgidxSubject{<main>}{<category>}
```

How to format a subject in the text. Ignore the main part in the text.

```
\newcommand*{\DTLgidxSubject}[2]{%  
  #2%  
}
```

\DTLgidxOffice

```
\DTLgidxOffice{<office>}{<name>}
```

Put the office in parentheses in the document text.

```
\newcommand*{\DTLgidxOffice}[2]{%  
  #2 (#1)%  
}
```

\DTLgidxIgnore

Show argument in document text, but disregard in the sort and label.

```
\newcommand*{\DTLgidxIgnore}[1]{#1}
```

`\DTLgidxMac` `\DTLgidxMac{<text>}`

In the document, just does *<text>*, but gets converted to “Mac” in the sort key. (Unless overridden by the user.)

```
\newcommand*\DTLgidxMac}[1]{#1}
```

`\datagidx@mac` `\DTLgidxMac` gets temporarily redefined to `\datagidx@mac` when construction the sort key.  
`\newcommand*\datagidx@mac}[1]{Mac}`

`\DTLgidxSaint` `\DTLgidxSaint{<text>}`

In the document, just does *<text>*, but gets converted to “Saint” in the sort key. (Unless overridden by the user.)

```
\newcommand*\DTLgidxSaint}[1]{#1}
```

`\datagidx@saint` `\DTLgidxMac` gets temporarily redefined to `\datagidx@saint` when construction the sort key.  
`\newcommand*\datagidx@saint}[1]{Saint}`

`\DTLgidxRank` `\DTLgidxRank{<rank>}{<forenames>}`

A person’s title, rank or sanctity should be ignored when sorting.

```
\newcommand*\DTLgidxRank}[2]{#1~#2}
```

`\datagidx@rank` `\DTLidxRank` gets temporarily redefined to `\datagidx@rank` when constructing the sort key. An extra dot is added to the end to ensure names without a rank are sorted before identical names with a rank.  
`\newcommand*\datagidx@rank}[2]{#2.}`

`\DTLgidxParticle` `\DTLgidxParticle{<particle>}{<surname>}`

A particle such as “of”, “de” or “von” should be ignored when sorting.

```
\newcommand*\DTLgidxParticle}[2]{#1~#2}
```

`\datagidx@particle` `\DTLidxParticle` gets temporarily redefined to `\datagidx@particle` when constructing the sort key. An extra dot is added to the end to ensure names without a particle are sorted before identical names with a particle.  
`\newcommand*\datagidx@particle}[2]{#2.}`



`\datagidx@bothoftwo` `\newcommand*{\datagidx@bothoftwo}[2]{#1#2}`

`\datagidx@person` Used when constructing the sort key for a name.  
`\newcommand*{\datagidx@person}[2]{#2\noexpand\datatoolpersoncomma #1}`

`\datagidx@place` Used when constructing the sort key for a place.  
`\newcommand*{\datagidx@place}[2]{#2\noexpand\datatoolplacecomma #1}`

`\datagidx@subject` Used when constructing the sort key for a place.  
`\newcommand*{\datagidx@subject}[2]{#2\noexpand\datatoolsubjectcomma #1}`

`\datagidx@paren` Used when constructing the sort key for a parenthesis.  
`\newcommand*{\datagidx@paren}[1]{\noexpand\datatoolparenstart #1}`

`\datagidx@invert`  
`\newcommand*{\datagidx@invert}[2]{#2, #1}`

`\DTLgidxParen` Parenthetical material.  
`\newcommand*{\DTLgidxParen}[1]{\space(#1)}`

`\idxwordifygreek` Convert commands like `\alpha` into words for indexing and labelling purposes.  
`\newcommand*{\datagidxwordifygreek}{%`  
`\def\alpha{alpha}%`  
`\def\beta{beta}%`  
`\def\gamma{gamma}%`  
`\def\delta{delta}%`  
`\def\epsilon{epsilon}%`  
`\def\varepsilon{epsilon}%`  
`\def\zeta{zeta}%`  
`\def\eta{eta}%`  
`\def\theta{theta}%`  
`\def\vartheta{theta}%`  
`\def\iota{iota}%`  
`\def\kappa{kappa}%`  
`\def\lambda{lambda}%`  
`\def\mu{mu}%`  
`\def\nu{nu}%`  
`\def\xi{xi}%`  
`\def\pi{pi}%`  
`\def\varpi{pi}%`  
`\def\rho{rho}%`  
`\def\varrho{rho}%`  
`\def\sigma{sigma}%`  
`\def\varsigma{sigma}%`  
`\def\tau{tau}%`  
`\def\upsilon{upsilon}%`  
`\def\phi{phi}%`

```

\def\varphi{phi}%
\def\chi{chi}%
\def\psi{psi}%
\def\omega{omega}%
\def\Gamma{Gamma}%
\def\Delta{Delta}%
\def\Theta{Theta}%
\def\Lambda{Lambda}%
\def\Xi{Xi}%
\def\Pi{Pi}%
\def\Sigma{Sigma}%
\def\Upsilon{Upsilon}%
\def\Phi{Phi}%
\def\Psi{Psi}%
\def\Omega{Omega}%
}

```

extendedtoascii Convert commands like \aa into the closest ASCII equivalent.

```

\newcommand{\datagidxextendedtoascii}{%
\def\AE{AE}%
\def\ae{ae}%
\def\OE{OE}%
\def\oe{oe}%
\def\AA{AA}%
\def\aa{aa}%
\def\L{L}%
\def\l{l}%
\def\O{O}%
\def\o{o}%
\def\SS{SS}%
\def\ss{ss}%
\def\th{th}%
\def\TH{TH}%
\def\dh{dh}%
\def\DH{DH}%
}

```

idxconvertchars Convert commands like \&.

```

\newcommand*{\datagidxconvertchars}{%
\let~\space
\ifdef\andname
{%
\let\&\andname
}%
{%
\def\&\expandafter\@gobble\string\&}%
}%
\def\_{\string_}%
\def\${\string$}%

```

```

\def\#{\expandafter\@gobble\string\#}%
\def\%{\expandafter\@gobble\string\}%
\def\{\{\expandafter\@gobble\string\{\}%
\def\}\{\expandafter\@gobble\string\}\}%
}

```

`idxstripaccents` Strip accents so they don't interfere with the label and sort. If you want to write your own comparison handler macro, you'll need to redefine this if you want accented letters to be sorted differently from the unaccented version. This command should only be used within a scope.

```
\newcommand*\datagidxstripaccents}{%
```

These redefinitions will only work with `\edef` or `\xdef`:

```

\let\add@accent@\@secondoftwo
\let\@text@composite@x\@secondoftwo
\let\@tabacckludge\@secondoftwo

```

The following are need with `\protected@edef` or `\protected@xdef`:

```

\expandafter\def\csname \encodingdefault-cmd\endcsname##1##2##3{##3}%
\expandafter\def\csname OT1-cmd\endcsname##1##2##3{##3}%
\expandafter\def\csname T1-cmd\endcsname##1##2##3{##3}%
\expandafter\def\csname PD1-cmd\endcsname##1##2##3{##3}%
\def\IeC##1{\@gobbletwo##1}%
}

```

`\newterm` `\newterm[options] name`

Defaults to normal behaviour.

```
\providecommand{\newterm}{\datagidx@newterm}
```

May only be used in the preamble. (Terms must be defined before the aux file is read.)

```
\@onlypreamble\newterm
```

`@setfieldvalues` Sets the values for all the field.

```
\newcommand*\datagidx@setfieldvalues}[2]{%
```

Set defaults.

```

\def\newterm@name{#2}%
\renewcommand*\newterm@label{#2}%
\renewcommand*\newterm@text{#2}%
\undef\newterm@plural
\renewcommand*{\newterm@description}{}%
\renewcommand*{\newterm@sort}{#2}%
\renewcommand*{\newterm@symbol}{}%
\let\newterm@database\datagidx@defaultdatabase
\renewcommand*{\newterm@short}{#2}%
\undef\newterm@shortplural

```

```

\renewcommand*{\newterm@long}{#2}%
\undef\newterm@longplural
\renewcommand*{\newterm@see}{}%
\renewcommand*{\newterm@seealso}{}%
\renewcommand*{\newterm@parent}{}%

```

Allow hook to access other fields.

```

\let\datagidx@orgfield\field
\def\field##1{\expandafter\noexpand\csname newterm@##1\endcsname}%

```

Hook to make it easier to add extra fields.

```

\newterm@defaultshook
\let\field\datagidx@orgfield

```

Assign values given in optional argument.

```

\setkeys{newterm}{#1}%

```

Temporary redefine commands likely to be contained in the name that may interfere with the label and sort.

```

\bgroup

```

Allow users to, say, specify the name as  $\langle name \rangle \text{\glsadd}\langle other label \rangle$  without having to specify a separate label.

```

\let\glsadd@gobble

```

Strip common formatting commands.

```

\let\MakeUppercase\DTLgidxNoFormat
\let\MakeTextUppercase\DTLgidxNoFormat
\let\MakeLowercase\DTLgidxNoFormat
\let\MakeTextLowercase\DTLgidxNoFormat
\let\acronymfont\DTLgidxNoFormat
\let\textrm\DTLgidxNoFormat
\let\texttt\DTLgidxNoFormat
\let\textsf\DTLgidxNoFormat
\let\textsc\DTLgidxNoFormat
\let\textbf\DTLgidxNoFormat
\let\textmd\DTLgidxNoFormat
\let\textit\DTLgidxNoFormat
\let\textsl\DTLgidxNoFormat
\let\emph\DTLgidxNoFormat
\let\textsuperscript\DTLgidxNoFormat

```

Convert character commands like  $\&$ .

```

\datagidxconvertchars

```

Strip  $\ensuremath$ .

```

\let\ensuremath\DTLgidxNoFormat

```

Ensure that inversions are dealt with for the label.

```

\let\DTLgidxParen@gobble
\let\DTLgidxName@secondoftwo
\let\DTLgidxPlace\datagidx@invert
\let\DTLgidxSubject\datagidx@invert

```

```

\let\DTLgidxOffice\@secondoftwo
\let\DTLgidxParticle\datagidx@bothoftwo

```

Convert Greek maths (such as `\alpha`) to text.

```
\datagidxwordifygreek
```

Strip accent commands so they don't interfere with the label.

```

\datagidxstripaccents
\datagidxextendedtoascii

```

Allow user to hook into this.

```
\newtermlabelhook
```

There shouldn't really be any fragile commands in #2 but using `\protected@xdef` to be on the safe side.

```
\protected@xdef\newterm@label{\newterm@label}%
```

These commands behave differently for the sort key:

```

\let\DTLgidxName\datagidx@person
\let\DTLgidxPlace\datagidx@place
\let\DTLgidxSubject\datagidx@subject
\let\DTLgidxOffice\datagidx@person
\let\DTLgidxParen\datagidx@paren
\let\DTLgidxMac\datagidx@mac
\let\DTLgidxSaint\datagidx@saint
\let\DTLgidxIgnore\@gobble
\let\DTLgidxRank\datagidx@rank
\let\DTLgidxParticle\datagidx@particle
\let\DTLgidxNameNum\datagidx@namenum

```

Need to use `\protected@xdef` here, which means limited support for stripping accents.

```

\protected@xdef\newterm@sort{\newterm@sort}%
\egroup
}

```

`tagidx@add@term` Add term (once all fields have been set. Argument is the name field.

```

\newcommand*{\datagidx@add@term}[1]{%
\global\cslet{datagidxentry@\newterm@label}{\newterm@database}%
\DTLnewrow{\newterm@database}%
\DTLnewdbentry{\newterm@database}{Name}{#1}%
\DTLnewdbentry{\newterm@database}{Used}{0}%
{%
\dtlexpandnewvalue
\DTLnewdbentry{\newterm@database}{Text}{\expandonce\newterm@text}%
\DTLnewdbentry{\newterm@database}{Description}{\expandonce\newterm@description}%
\DTLnewdbentry{\newterm@database}{Label}{\expandonce\newterm@label}%
\DTLnewdbentry{\newterm@database}{Sort}{\expandonce\newterm@sort}%
\DTLnewdbentry{\newterm@database}{Symbol}{\expandonce\newterm@symbol}%
\DTLnewdbentry{\newterm@database}{Short}{\expandonce\newterm@short}%
\DTLnewdbentry{\newterm@database}{Long}{\expandonce\newterm@long}%
\ifundef\newterm@plural

```

```

{%
  \DTLnewbentry{\newterm@database}{Plural}{\expandonce\newterm@text s}%
}%
{%
  \DTLnewbentry{\newterm@database}{Plural}{\expandonce\newterm@plural}%
}%
\ifundef\newterm@shortplural
{%
  \DTLnewbentry{\newterm@database}{ShortPlural}{\expandonce\newterm@short s}%
}%
{%
  \DTLnewbentry{\newterm@database}{ShortPlural}{\expandonce\newterm@shortplural}%
}%
\ifundef\newterm@longplural
{%
  \DTLnewbentry{\newterm@database}{LongPlural}{\expandonce\newterm@long s}%
}%
{%
  \DTLnewbentry{\newterm@database}{LongPlural}{\expandonce\newterm@longplural}%
}%
\ifdefempty{\newterm@see}%
  {}%
  {\DTLnewbentry{\newterm@database}{See}{\newterm@see}}%
\ifdefempty{\newterm@seealso}%
  {}%
  {\DTLnewbentry{\newterm@database}{SeeAlso}{\newterm@seealso}}%

```

Hook to make it easier to add extra fields.

```
\newterm@extrafields
```

Add parent, if supplied.

```

\ifdefempty{\newterm@parent}%
  {}%
  {%
    \iftermexists{\newterm@parent}%
      {%
        \edef\newterm@parentdatabase{\csuse{datagidxentry@\newterm@parent}}%

```

Parent entry must belong to same database as child entry.

```

\ifthenelse{\equal{\newterm@parentdatabase}{\newterm@database}}
  {%
    \DTLnewbentry{\newterm@database}{Parent}{\newterm@parent}%
    \datagidx@addchild{\newterm@database}{\newterm@parent}{\newterm@label}%
  }%
  {%
    \PackageError{datagidx}%
      {%
        Parent entry ‘\newterm@parent’ must belong to the
        same database as child entry ‘\newterm@label’%
      }%
  }%

```



Assign values to all the fields.

```
\datagidx@setfieldvalues{#1}{#2}%
```

Check if database exists.

```
\DTLifdbexists{\newterm@database}%  
{%
```

Database exists. Check if term already exists.

```
\iftermexists{\newterm@label}%  
{%  
  \PackageError{datagidx}{Term ‘\newterm@label’ already  
    exists in database ‘\newterm@database’}{}%  
}%  
{%
```

Add this entry to the database.

```
\datagidx@add@term{#2}%  
}%  
}%  
{%
```

Database doesn't exist.

```
\PackageError{datagidx}%  
{Glossary/index data base ‘\newterm@database’ doesn't exist}%  
{%  
  You must define the glossary/index data base before you can  
  add any terms to it.%  
}%  
}%  
}
```

`highopt@newterm` Used when high optimized setting enabled. This setting must be switched off if the user wants to modify the database.

```
\newcommand{\datagidx@highopt@newterm}[2] [] {%
```

Assign values to all the fields.

```
\datagidx@setfieldvalues{#1}{#2}%
```

Check if database exists.

```
\DTLifdbexists{\newterm@database}%  
{%
```

Database exists. If this is the first run, we need to add the term as usual, otherwise we just need to define `\datagidxentry@⟨label⟩`

```
\edef\dtl@dogetrow{%  
  \noexpand\dtlgetrowindex  
  {\noexpand\dtl@rowidx}%  
  {\newterm@database}%  
  {%  
    \dtlcolumnindex{\newterm@database}{Label}%  
  }%  
}%
```



```

    {\newterm@label}}%
    \dtl@dogetrow
    \ifx\dtl@rowidx\dtlnovalue

```

Hasn't been defined so add.

```

    \datagidx@add@term{#2}%

```

Database will need to be sorted.

```

    \csdef{datagidx@do@highopt@sort@\newterm@database}{\datagidx@sort}%
    \else

```

Has been defined, so just define `\datagidxentry@<label>` and `\datagidxlastlabel`

```

    \global\cslet{datagidxentry@\newterm@label}{\newterm@database}%
    \global\let\datagidxlastlabel\newterm@label
    \fi
}%
{%

```

Database doesn't exist.

```

    \PackageError{datagidx}%
    {Glossary/index data base '\newterm@database' doesn't exist}%
    {%
        You must define the glossary/index data base before you can
        add any terms to it.%
    }%
}%
}

```

tagidx@addchild

```

\newcommand*{\datagidx@addchild}[3]{%
    \edef\dtl@dogetrow{%
        \noexpand\dtlgetrowforvalue
        {#1}%
        {%
            \dtlcolumnindex{\newterm@database}{Label}%
        }%
        {#2}}%
    \dtl@dogetrow
    \dtlgetentryfromcurrentrow
    {\datagidx@child}%
    {\dtlcolumnindex{#1}{Child}}%
    \ifx\datagidx@child\dtlnovalue
        \edef\datagidx@child{#3}%
    \else
        \edef\datagidx@child{\datagidx@child,#3}%
    \fi
    \edef\do@update{\noexpand\dtlupdateentryincurrentrow
        {Child}{\datagidx@child}}%
    \do@update
    \dtlrecombine
}

```

### 5.5.3 Defining Acronyms

`\newacro` `\newacro[options]{short}{long}`

Shortcut command for acronyms.

```
\newcommand{\newacro}[3] [] {%
  \newterm
  [%
    description={\capitalisewords{#3}},%
    short={\acronymfont{#2}},%
    long={#3},%
    text={\DTLgidxAcrStyle{#3}{\acronymfont{#2}}},%
    plural={\DTLgidxAcrStyle{#3s}{\acronymfont{#2s}}},%
    sort={#2},%
    #1%
  ]%
  {\MakeTextUppercase{#2}}%
}
```

`\acronymfont` The font to use for the acronym.

```
\newcommand*{\acronymfont}[1]{#1}
```

`\DTLgidxAcrStyle` `\DTLgidxAcrStyle{long}{short}`

```
\newcommand*{\DTLgidxAcrStyle}[2]{#1 (#2)}
```

## 5.6 Conditionals

`\iftermexists` `\iftermexists{label}{true part}{false part}`

Check if term with given label exists.

```
\newcommand{\iftermexists}[3] {%
  \ifcsdef{datagidxentry@#1}{#2}{#3}%
}
```

`\datagidxdb` Gets the label of database containing the given entry. No check is made for the existence of the entry. Expands to empty if label is undefined.

```
\newcommand*{\datagidxdb}[1] {%
  \csuse{datagidxentry@#1}%
}
```

```
\ifentryused \ifentryused{<label>}{<true part>}{<>false part>}
```

Check if entry with given label has been used.

```
\newcommand*{\ifentryused}[3]{%  
  \letcs{\newterm@database}{datagidxentry@#1}%
```

`\dtlgetrowforvalue` doesn't expand the value when it checks for a match, so make sure label is fully expanded.

```
\edef\dtl@dogetrow{%  
  \noexpand\dtlgetrowforvalue  
  {\newterm@database}%  
  {%  
    \dtlcolumnindex{\newterm@database}{Label}%  
  }%  
  {#1}}%  
\dtl@dogetrow  
\dtlgetentryfromcurrentrow  
  {\datagidx@value}%  
  {\dtlcolumnindex{\newterm@database}{Used}}%  
\ifnum\datagidx@value=1\relax  
  #2%  
\else  
  #3%  
\fi  
}
```

## 5.7 Unsetting and Resetting

```
\glsreset \glsunset{<label>}
```

Mark as un-used.

```
\newcommand*{\glsreset}[1]{%
```

Fetch the name of the database with which this entry is associated.

```
\letcs{\newterm@database}{datagidxentry@#1}%
```

Get the row associated with this label and make it the current row.

```
\edef\do@getrow{%  
  \noexpand\dtlgetrowforvalue  
  {\newterm@database}%  
  {\dtlcolumnindex{\newterm@database}{Label}}%  
  {#1}%  
}%  
\do@getrow
```

Update the Used field.

```
\dtlreplaceentryincurrentrow
  {0}{\dtlcolumnindex{\newterm@database}{Used}}%
```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
}
```

```
\glsunset \glsunset{<label>}
```

Mark as used without affecting location.

```
\newcommand*{\glsunset}[1]{%
```

Fetch the name of the database with which this entry is associated.

```
\letcs{\newterm@database}{datagidxentry@#1}%
```

Get the row associated with this label and make it the current row.

```
\edef\do@getrow{%
  \noexpand\dtlgetrowforvalue
  {\newterm@database}%
  {\dtlcolumnindex{\newterm@database}{Label}}%
  {#1}%
}%
\do@getrow
```

Update the Used field.

```
\dtlreplaceentryincurrentrow
  {1}{\dtlcolumnindex{\newterm@database}{Used}}%
```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
}
```

```
\glsresetall \glsresetall{<db>}
```

Resets all entries in the given database.

```
\newcommand*{\glsresetall}[1]{%
  \def\datagidx@list{}%
  \dtlforcolumn{\datagidx@label}{#1}{Label}%
  {%
    \ifdefempty\datagidx@list
    {%
      \let\datagidx@list\datagidx@label
    }%
  }%
}
```

```

        \eappto\datagidx@list{,\datagidx@label}%
    }%
}%
\@for\datagidx@thislabel:=\datagidx@list\do
{%
    \glsreset{\datagidx@thislabel}%
}%
}

```

`\glsunsetall` `\glsunsetall{<db>}`

Resets all entries in the given database.

```

\newcommand*\glsunsetall}[1]{%
    \def\datagidx@list{}%
    \dtlforcolumn{\datagidx@label}{#1}{Label}%
    {%
        \ifdefempty\datagidx@list
        {%
            \let\datagidx@list\datagidx@label
        }%
        {%
            \eappto\datagidx@list{,\datagidx@label}%
        }%
    }%
    \@for\datagidx@thislabel:=\datagidx@list\do
    {%
        \glsunset{\datagidx@thislabel}%
    }%
}

```

## 5.8 Accessing Entry Information

`idx@anchorcount` Register to make unique anchors.

```
\newcount\datagidx@anchorcount
```

`idx@formatanchor` Format number using six digits.

```

\newcommand*\datagidx@formatanchor}[1]{%
    \ifnum#1<10000
    0%
    \ifnum#1<1000
    0%
    \ifnum#1<100
    0%
    \ifnum#1<10
    0%
}

```

```

        \fi
    \fi
    \fi
    \fi
    \number#1%
}

```

datagidx@escloc

```

\newcommand*{\@datagidx@escloc}[2]{%
    \expandafter\string\csname#1\endcsname{\noexpand\number#2}%
}

```

@escapelocation

```

\newcommand*{\@datagidx@escapelocation}{%
    \def\@arabic{\@datagidx@escloc{\@arabic}}%
    \def\@roman{\@datagidx@escloc{\@roman}}%
    \def\@Roman{\@datagidx@escloc{\@Roman}}%
    \def\@alph{\@datagidx@escloc{\@alph}}%
    \def\@Alph{\@datagidx@escloc{\@Alph}}%
}

```

elocationformat

```

\newcommand*{\@datagidx@escapelocationformat}{%
    \def\@arabic##1{arabic}%
    \def\@roman##1{roman}%
    \def\@Roman##1{Roman}%
    \def\@alph##1{alph}%
    \def\@Alph##1{Alph}%
}

```

rlocationformat

```

\newcommand*{\@datagidx@clearlocationformat}{%
    \let\@arabic\@firstofone
    \let\@roman\@firstofone
    \let\@Roman\@firstofone
    \let\@alph\@firstofone
    \let\@Alph\@firstofone
}

```

AddLocationType Allow user to add their own location type. Argument must be control sequence name without initial backslash.

```

\newcommand*{\DTLgidxAddLocationType}[1]{%
    \gappto\datagidx@escapelocation{%
        \expandafter\def\csname#1\endcsname{\@datagidx@escloc{#1}}%
    }%
    \gappto\datagidx@escapelocationformat{%
        \expandafter\def\csname#1\endcsname##1{#1}%
    }%
}

```

```

\gappto\datagidx@clearlocationformat{%
  \expandafter\let\csname#1\endcsname\@firstofone
}%
}

```

May only be used in the preamble. (Needs to be set before the aux file is read.)

```
\@onlypreamble\DTLgidxAddLocationType
```

```
\datagidx@target \datagidx@target{<label>}{<format>}{<location>}{<text>}
```

Make a target if \hypertarget has been defined.

```

\newcommand*{\datagidx@target}[4]{%
  \global\advance\datagidx@anchorcount by 1\relax
  \edef\@datagidx@target{datagidx.\datagidx@formatanchor\datagidx@anchorcount}%
  \ifstrempy{#3}
  {%
    \datagidx@write@usedentry{#1}{}%
  }%
  {%
    \bgroup
    \datagidx@escapelocation

```

Need to prevent \@arabic etc from being expanded just yet (or it will throw the page numbering out of sync for entries that occur by a page break).

```

  \def\@arabic{\noexpand\@arabic}%
  \def\@roman{\noexpand\@roman}%
  \def\@Roman{\noexpand\@Roman}%
  \def\@alph{\noexpand\@alph}%
  \def\@Alph{\noexpand\@Alph}%
  \protected@edef\@datagidx@dowriteaux{%
    \noexpand\datagidx@write@usedentry{#1}%
    {[#2]{#3}{\@datagidx@target}}%
  }%
  \@datagidx@dowriteaux
\egroup
}%
\ifdef\hypertarget
{%

```

Make sure the current line doesn't scroll off the top of the screen.

```

\datagidxshowifdraft
{%
  [\@datagidx@target]%
  \discretionary{}{}{}%
}%
\bgroup
\let\glsadd@gobble
\settoheight\dimen@{#4}%

```

```

\raisebox{\dimen@}%
{%
\datagidxtarget{\@datagidx@target}{}%
}%
\egroup
}%
{%
}%
\datagidxshowifdraft{[#1]\discretionary-{}{}{}%
#4%
}

```

`\glsdispenentry` `\glsdispenentry{<label>}{<field>}`

Short cut that fetches and displays a value.

```

\DeclareRobustCommand*\glsdispenentry[2]{%
\DTLgidxFetchEntry{\datagidx@dispenentryval}{#1}{#2}%
\datagidx@dispenentryval
}

```

`\Glsdispenentry` `\Glsdispenentry{<label>}{<field>}`

As previous but makes the first letter upper case.

```

\DeclareRobustCommand*\Glsdispenentry[2]{%
\DTLgidxFetchEntry{\datagidx@dispenentryval}{#1}{#2}%
\xmakefirstuc\datagidx@dispenentryval
}

```

`\DTLgidxFetchEntry` Fetch value for the given field for the term identified by *<label>* and store the value in *<cs>* (a control sequence).

```

\newcommand*\DTLgidxFetchEntry[3]{%

```

Does this entry exist?

```

\ifcsdef{datagidxentry@#2}%
{%

```

Fetch the name of the database with which this entry is associated.

```

\letcs{\newterm@database}{datagidxentry@#2}%

```

Get the row associated with this label and make it the current row.

```

\edef\do@getrow{%
\noexpand\dtlgetrowforvalue
{\newterm@database}%
{\dtlcolumnindex{\newterm@database}{Label}}%
{#2}%

```



```
}%
\do@getrow
```

Get the entry for the given field in the current row and store in  $\langle cs \rangle$ .

```
\dtlgetentryfromcurrentrow
  {#1}%
  {\dtlcolumnindex{\newterm@database}{#3}}%
}%
{%
```

Entry hasn't been defined.

```
\PackageError{datagidx}{No term '#2' defined}{}%
}%
}
```

parse@formatlabel

```
\parse@formatlabel{\langle format \rangle label}
```

Separate format and label from argument.

```
\newcommand*\datagidx@parse@formatlabel[1]{%
  \datagidx@parse@format@label@#1\endparse@formatlabel@
}
\newcommand*\datagidx@parse@format@label@{%
  \ifnextchar[{\datagidx@parse@formatlabel@}{\datagidx@parse@formatlabel@[]}%
}
\def\datagidx@parse@formatlabel@[#1]#2\endparse@formatlabel@{%
  \def\datagidx@format{#1}%
  \def\datagidx@label{#2}%
}
```

tagidx@use@entry

```
\@datagidx@use@entry{\link text}
```

The label and format should have been stored in  $\backslash\text{datagidx@label}$  and  $\backslash\text{datagidx@format}$  before calling this macro.

```
\newcommand*\@datagidx@use@entry[1]{%
```

Does this term exist?

```
\ifcsundef{datagidxentry@\datagidx@label}
  {%
  \PackageError{datagidx}{Entry '\datagidx@label' doesn't exist}{}%
  }%
  {%
```

Fetch the name of the database with which this entry is associated.

```
\letcs{\newterm@database}{datagidxentry@\datagidx@label}%
```

Get the row associated with this label and make it the current row.

```
\edef\do@getrow{%
  \noexpand\dtlgetrowforvalue
  {\newterm@database}%
  {\dtlcolumnindex{\newterm@database}{Label}}%
  {\datagidx@label}%
}%
\do@getrow
```

Get the entry for the FirstId field and store in \datagidx@id

```
\dtlgetentryfromcurrentrow
  {\datagidx@id}%
  {\dtlcolumnindex{\newterm@database}{FirstId}}%
```

If it hasn't been defined set it.

```
\DTLifnull\datagidx@id
  {%
```

Count register hasn't been updated yet.

```
  \count@=\datagidx@anchorcount\relax
  \advance\count@ by 1\relax
  \dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\count@}%
}%
  {}%
```

Update the Used field.

```
\dtlreplaceentryincurrentrow
  {1}{\dtlcolumnindex{\newterm@database}{Used}}%
```

Get the parent entry label (if one exists).

```
\dtlgetentryfromcurrentrow
  {\datagidx@parent}%
  {\dtlcolumnindex{\newterm@database}{Parent}}%
```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
```

If parent hasn't be used, give it an empty location.

```
\datagidx@markparent{\newterm@database}{\datagidx@parent}%
```

Write the location to the auxiliary file and display value of field.

```
\datagidx@target{\datagidx@label}{\datagidx@format}%
  {\csuse{the\DTLgidxCounter}}{#1}%
}%
}
```

\DTLgidxCounter The counter used for the location lists.

```
\newcommand*{\DTLgidxCounter}{page}
```

gidx@markparent Assign empty location to parent, if location of that parent is null. (Recursive).

```
\newcommand*{\datagidx@markparent}[2]{%
  \ifx#2\dtlnovalue
```

Null parent, so break out of recursion.

```
\else
```

Write empty location to the auxiliary file.

```
\datagidx@target{#2}{-}{-}{-}%
```

Fetch this parent's parent entry. Get the row associated with this and make it the current row.

```
\edef\do@getrow{%  
  \noexpand\dtlgetrowforvalue  
  {#1}%  
  {\dtlcolumnindex{#1}{Label}}%  
  {#2}}%  
\do@getrow
```

Get the entry for the FirstId field and store in \datagidx@id

```
\dtlgetentryfromcurrentrow  
{\datagidx@id}%  
{\dtlcolumnindex{\newterm@database}{FirstId}}%
```

If it hasn't been defined set it.

```
\DTLifnull\datagidx@id  
{%  
  \dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\datagidx@anchorcount}%  
}%  
{}
```

Get the parent

```
\dtlgetentryfromcurrentrow  
{\datagidx@parent}%  
{\dtlcolumnindex{#1}{Parent}}%
```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
```

Recurse

```
\datagidx@markparent{#1}{\datagidx@parent}%  
\fi  
}
```

write@usedentry Write out location to aux file and add location to the location list for the current run.

```
\newcommand*{\datagidx@write@usedentry}[2]{%
```

Do update if 'highopt optimize' setting is on.

```
\datagidx@do@highopt@update{#1}%
```

Write out location to aux file.

```
\protected@write{\@auxout}{-}{%  
  {%  
    \string\datagidx@usedentry{#1}{#2}%  
  }}%
```

Add to this run's location field.

```
\protected@edef\datagidx@do@usedentry{%
  \noexpand\datagidx@xusedentry{CurrentLocation}{#1}{#2}%
}%
```

If the location counter is the page counter, defer until after the page break.

```
\expandafter\ifstrequal\expandafter{\DTLgidxCOUNTER}{page}%
{%
  \expandafter\afterpage\expandafter{\datagidx@do@usedentry}%
}%
{
  \datagidx@do@usedentry
}%
}
```

agidx@xusedentry

```
\datagidx@usedentry{<location tag>}{<label>}{<location>}
```

Like `\datagidx@usedentry` but expands the location. Unlike `\datagidx@usedentry` the first argument isn't optional.

```
\newcommand*\datagidx@xusedentry}[3]{%
  \protected@edef\@datagidx@do@xusedentry{%
    \noexpand\datagidx@usedentry[#1]{#2}{#3}%
  }%
  \@datagidx@do@xusedentry
}
```

agidx@usedentry

```
\datagidx@usedentry[<location tag>]{<label>}{<location>}
```

Add to the location list for the given entry.

```
\newcommand*\datagidx@usedentry}[3][Location]{%
```

Check if label exists. (It may have been deleted or had a label change.)

```
\ifcsundef{datagidxentry@#2}%
{%
  \PackageWarning{datagidx}{No term ‘#2’ defined. Ignoring}%
}%
{%
% Fetch the name of the database with which this entry is
% associated.
%   \begin{macrocode}
  \letcs{\newterm@database}{datagidxentry@#2}%
```

Get the row associated with this label and make it the current row.

```
\edef\do@getrow{%
  \noexpand\dtlgetrowforvalue
```

```

    {\newterm@database}%
    {\dtlcolumnindex{\newterm@database}{Label}}}%
    {#2}%
  }%
  \do@getrow

```

```

% Get the entry for the \meta{location tag} field in the current row and store in
% \cs{datagidx@loc}.
% \begin{macrocode}
\dtlgetentryfromcurrentrow
  {\datagidx@loc}%
  {\dtlcolumnindex{\newterm@database}{#1}}%

```

Check the success of the previous command.

```
\ifx\datagidx@loc\dtlnovalue
```

There's no *location tag* field in the current row, so add one with the given location.

```

  \def\datagidx@loc{#3}%
  \dtlappendentrytocurrentrow{#1}{\expandonce\datagidx@loc}%
\else

```

There is a *location tag* field in the current row, so append the given location to the list, unless one or the other is empty.

```

  \ifdefempty{\datagidx@loc}%
  {%
    \def\datagidx@loc{#3}%
  }%
  {%
    \ifstrempy{#3}%
    {}%
    {%
      \appto\datagidx@loc{,#3}%
    }%
  }%

```

and update the entry in the current row.

```

\expandafter\dtlreplaceentryincurrentrow\expandafter
  {\datagidx@loc}%
  {\dtlcolumnindex{\newterm@database}{#1}}%
\fi

```

Current row has been edited, so we need to merge the current row back into the database.

```

  \dtlrecombine
  }%
}

```

tagidx@save@loc Store the current location from the previous run.

```

\newcommand*{\datagidx@save@loc}[2]{%
  \bgroup
  \datagidx@escapelocation
  \xdef\datagidx@tmp{#2}%

```

```

\egroup
\expandafter\xdef\csname datagidx@prev@loc@#1\endcsname{\datagidx@tmp}%
}

```

`\glsadd` `\glsadd{<[<format>]label}`

```

\newcommand*\glsadd}[1]{%
  \NoCaseChange{\@glsadd{#1}}%
}
\DeclareRobustCommand*\@glsadd}[1]{%

```

Check term has been defined.

```

\ifcsundef{datagidxentry@\datagidx@label}%
{%
  \PackageError{datagidx}{Term ‘\datagidx@label’ doesn’t exist}{}%
}%
{%
  \datagidx@parse@formatlabel{#1}%

```

Write the location to the auxiliary file.

```

\datagidx@target{\datagidx@label}{\datagidx@format}%
  {\csuse{the\DTLgidxCounter}}{ }%

```

Fetch the name of the database with which this entry is associated.

```

\letcs{\newterm@database}{datagidxentry@\datagidx@label}%

```

Get the row associated with this label and make it the current row.

```

\edef\do@getrow{%
  \noexpand\dtlgetrowforvalue
  {\newterm@database}%
  {\dtlcolumnindex{\newterm@database}{Label}}%
  {\datagidx@label}%
}%
\do@getrow

```

Update the Used field.

```

\dtlreplaceentryincurrentrow
  {1}{\dtlcolumnindex{\newterm@database}{Used}}%

```

Get the entry for the FirstId field and store in `\datagidx@id`

```

\dtlgetentryfromcurrentrow
  {\datagidx@id}%
  {\dtlcolumnindex{\newterm@database}{FirstId}}%

```

If it hasn't been defined set it.

```

\DTLifnull\datagidx@id
{%
  \dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\datagidx@anchorcount}%
}%
{}%

```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
}%
}
```

```
\datagidx@count Loop counter used by \glsaddall
\newcount\datagidx@count
```

```
\glsaddall \glsaddall{<db>}
```

Adds all entries in the given database.

```
\newcommand*\glsaddall}[1]{%
\DTLifdbexists{#1}%
{%
\edef\datagidx@rowcount{\number\DTLrowcount{#1}}%
\datagidx@count=0\relax
\loop
\advance\datagidx@count by 1\relax
\dtlgetrow{#1}{\datagidx@count}%
```

Get the label for this row.

```
\dtlgetentryfromcurrentrow
{\datagidx@label}%
{\dtlcolumnindex{#1}{Label}}%
```

Write blank location to the auxiliary file but temporarily undefine \hypertarget as it doesn't make sense to have a target here.

```
\bgroup
\undef\hypertarget
\datagidx@target{\datagidx@label}{\}{\}%
\egroup
```

Update the Used field.

```
\dtlreplaceentryincurrentrow
{1}{\dtlcolumnindex{#1}{Used}}%
```

Get the entry for the FirstId field and store in \datagidx@id

```
\dtlgetentryfromcurrentrow
{\datagidx@id}%
{\dtlcolumnindex{#1}{FirstId}}%
```

If it hasn't been defined set it.

```
\DTLifnull\datagidx@id
{%
\dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\datagidx@anchorcount}%
}%
{}}%
```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
```

Repeat loop if not finished.

```
\ifnum\datagidx@count<\datagidx@rowcount
\repeat
}%
{%
\PackageError{datagidx}{Database '#1' doesn't exist}{}%
}%
}
```

```
\glslink \glslink{<label>}{<text>}
```

Use given entry but user supplies text.

```
\DeclareRobustCommand*\glslink[2]{%
\datagidx@parse@formatlabel{#1}%
\datagidxlink{\datagidx@label}%
{%
\@datagidx@use@entry{#2}%
}%
}
```

```
\useentry \useentry{<label>}{<field>}
```

Fetch and use the given field for the given entry.

```
\DeclareRobustCommand*\useentry[2]{%
\datagidx@parse@formatlabel{#1}%
\DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
\datagidxlink{\datagidx@label}%
{%
\@datagidx@use@entry{\datagidx@value}%
}%
}
```

```
\Useentry \Useentry{<label>}{<field>}
```

As `\useentry`, but capitalise the first word.

```
\DeclareRobustCommand*\Useentry[2]{%
\datagidx@parse@formatlabel{#1}%
\DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
}
```



```

\datagidxlink{\datagidx@label}%
{%
  \@datagidx@use@entry{\xmakefirstuc{\datagidx@value}}%
}%
}

```

`\USEentry` `\USEentry{<label>}{<field>}`

As `\useentry`, but make the whole term upper case.

```

\DeclareRobustCommand*\USEentry}[2]{%
  \datagidx@parse@formatlabel{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \datagidxlink{\datagidx@label}%
  {%
    \@datagidx@use@entry{\MakeTextUppercase{\datagidx@value}}%
  }%
}

```

`\useentrynl` `\useentrynl{<label>}{<field>}`

Fetch and use the given field for the given entry without creating a hyperlink.

```

\DeclareRobustCommand*\useentrynl}[2]{%
  \datagidx@parse@formatlabel{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \@datagidx@use@entry{\datagidx@value}%
}

```

`\Useentrynl` `\Useentrynl{<label>}{<field>}`

As `\useentry`, but capitalise the first word.

```

\DeclareRobustCommand*\Useentrynl}[2]{%
  \datagidx@parse@formatlabel{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \@datagidx@use@entry{\xmakefirstuc{\datagidx@value}}%
}

```

`\USEentrynl` `\USEentrynl{<label>}{<field>}`

As `\useentry`, but make the whole term upper case.

```
\DeclareRobustCommand*\USEentryn1}[2]{%
  \datagidx@parse@formatlabel{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \@datagidx@use@entry{\MakeTextUppercase{\datagidx@value}}%
}
```

Short cuts to common fields.

```
\gls
\DeclareRobustCommand*\gls}[1]{\useentry{#1}{Text}}
```

```
\glspl
\DeclareRobustCommand*\glspl}[1]{\useentry{#1}{Plural}}
```

```
\Gls
\DeclareRobustCommand*\Gls}[1]{\Useentry{#1}{Text}}
```

```
\Glspl
\DeclareRobustCommand*\Glspl}[1]{\Useentry{#1}{Plural}}
```

```
\glsnl
\DeclareRobustCommand*\glsnl}[1]{\useentryn1{#1}{Text}}
```

```
\glsplnl
\DeclareRobustCommand*\glsplnl}[1]{\useentryn1{#1}{Plural}}
```

```
\Glsnl
\DeclareRobustCommand*\Glsnl}[1]{\Useentryn1{#1}{Text}}
```

```
\Glsplnl
\DeclareRobustCommand*\Glsplnl}[1]{\Useentryn1{#1}{Plural}}
```

```
\glssym
\DeclareRobustCommand*\glssym}[1]{\useentry{#1}{Symbol}}
```

```
\Glssym
\DeclareRobustCommand*\Glssym}[1]{\Useentry{#1}{Symbol}}
```

### 5.8.1 Using Acronyms

```
DTLgidxFormatAcr \DTLgidxFormatAcr{<label>}{<long field>}{<short field>}
```

```
\newcommand*\DTLgidxFormatAcr}[3]{%
  \DTLgidxAcrStyle{\glsdispentry{#1}{#2}}{\useentry{#1}{#3}}%
}
```

LgidxFormatAcrUC

```
\DTLgidxFormatAcr{<label>}{<long field>}{<short field>}
```

As previous but capitalise first word.

```
\newcommand*\DTLgidxFormatAcrUC[3]{%  
  \DTLgidxAcrStyle{\Glsdispenry{#1}{#2}}{\useentry{#1}{#3}}%  
}
```

\acr

```
\DeclareRobustCommand*\acr[1]{%  
  \ifentryused{#1}%  
  {\useentry{#1}{Short}}%  
  {\DTLgidxFormatAcr{#1}{Long}{Short}}%  
}
```

\acrpl

```
\DeclareRobustCommand*\acrpl[1]{%  
  \ifentryused{#1}%  
  {\useentry{#1}{ShortPlural}}%  
  {\DTLgidxFormatAcr{#1}{LongPlural}{ShortPlural}}%  
}
```

\Acr

```
\DeclareRobustCommand*\Acr[1]{%  
  \ifentryused{#1}%  
  {\Useentry{#1}{Short}}%  
  {\DTLgidxFormatAcrUC{#1}{Long}{Short}}%  
}
```

\Acrpl

```
\DeclareRobustCommand*\Acrpl[1]{%  
  \ifentryused{#1}%  
  {\Useentry{#1}{ShortPlural}}%  
  {\DTLgidxFormatAcrUC{#1}{LongPlural}{ShortPlural}}%  
}
```

## 5.9 Displaying Glossaries, Lists of Acronyms, Indices

Define keys for \printterms:

```
\define@key{printterms}{database}{\renewcommand*\newterm@database{#1}}
```

Options for post description.

```
\define@choicekey{printterms}{postdesc}[\val\nr]%  
{none,dot}%  
{%  
  \datagidx@setpostdesc\nr  
}
```

Options for pre-location.

```
\define@choicekey{printterms}{prelocation}[\val\nr]%  
{none,enspace,space,dotfill,hfill}%  
{%  
  \datagidx@setprelocation\nr  
}
```

How to display the location list.

```
\define@choicekey{printterms}{location}[\val\nr]%  
{hide,list,first}%  
{\datagidx@setlocation\nr}
```

How to format the symbol in relation to the description.

```
\define@choicekey{printterms}{symboldesc}[\val\nr]%  
{symbol,desc,(symbol) desc,desc (symbol),symbol desc,desc symbol}%  
{\datagidx@formatsymdesc\nr}
```

How many columns to have.

```
\define@key{printterms}{columns}%  
{%  
  \DTLgidxSetColumns{#1}%  
}
```

How to format the name.

```
\define@choicekey{printterms}{namecase}[\val\nr]%  
{nochange,uc,lc,firstuc,capitalise}%  
{%  
  \datagidx@setnamecase\nr  
}  
  
\define@key{printterms}{namefont}%  
{%  
  \renewcommand*{\DTLgidxNameFont}[1]{\font{#1{##1}}}%  
}  
  
\define@key{printterms}{postname}  
{%  
  \renewcommand*{\DTLgidxPostName}{#1}%  
}  
  
\define@choicekey{printterms}{see}[\val\nr]%  
{comma,brackets,dot,space,nosep,semicolon,location}%  
{\datagidx@setsee\nr}  
  
\define@choicekey{printterms}{child}[\val\nr]%  
{named,noname}%  
{%  
  \datagidx@setchildstyle\nr  
}
```

Symbol width

```
\define@key{printterms}{symbolwidth}%  
{%
```

```

\setlength{\datagidxsymbolwidth}{#1}%
}

```

#### Location width

```

\define@key{printterms}{locationwidth}{%
{%
\setlength{\datagidxlocationwidth}{#1}%
}
}

```

#### Child sort:

```

\define@choickey{printterms}{childsort}[\val\nr]{%
{true,false}[true]{%
{%
\datagidx@setchildsort\nr
}
}
}

```

#### Change style:

```

\define@choickey{printterms}{showgroups}{true,false}[true]{%
\appto\newterm@styles{showgroups={#1},}%
}

\define@key{printterms}{style}{\appto\newterm@styles{style={#1},}}
\define@key{printterms}{heading}{\appto\newterm@styles{heading={#1},}}
\define@key{printterms}{postheading}{%
\appto\newterm@styles{postheading={#1},}%
}

\define@key{printterms}{sort}{\appto\newterm@styles{sort={#1},}}
\define@choickey{printterms}{balance}[\val\nr]{true,false}[true]{%
\ifcase\nr\relax
\appto\newterm@styles{balance=true,}%
\or
\appto\newterm@styles{balance=false,}%
\fi
}

```

terms@condition

```

\newcommand*{\printterms@condition}{\boolean{true}}
\define@key{printterms}{condition}{\renewcommand*{\printterms@condition}{#1}}

```

nttermsstartpar

```

\newcommand{\printtermsstartpar}{\par}

```

s@setupmulticol

```

\newcommand*{\printterms@setupmulticol}{%
\ifdefempty\datagidx@postheading
{%
\edef\datagidx@prestart{%
\noexpand\datagidx@heading{\noexpand\datagidx@title}%
\noexpand\begin{\datagidx@multicols}{\datagidx@columns}%
}
}
}

```

```

    }%
  }%
  {%
    \edef\datagidx@prestart{%
      \noexpand\datagidx@heading{\noexpand\datagidx@title}%
      \noexpand\begin{\datagidx@multicols}{\datagidx@columns}%
      [\noexpand\datagidx@postheading]%
    }%
  }%
  \edef\datagidx@postend{%
    \noexpand\end{\datagidx@multicols}%
  }%
}

```

ms@setuptwocol

```

\newcommand*\printterms@setuptwocol{%
  \def\datagidx@prestart{%
    \twocolumn[\datagidx@heading{\datagidx@title}%
    \datagidx@postheading]}%
  \if@twocolumn
    \def\datagidx@postend{}%
  \else
    \def\datagidx@postend{\printtermsrestoreonecolumn}%
  \fi
}

```

restoreonecolumn

```

\newcommand{\printtermsrestoreonecolumn}{\onecolumn}

```

\printterms

```

\printterms [options]

```

Print the list of terms

```

\newcommand{\printterms}[1] [] {%
  \bgroup

```

Set default database.

```

  \let\newterm@database\datagidx@defaultdatabase

```

Initialise key list for style:

```

  \let\newterm@styles\@empty

```

Set options:

```

  \setkeys{printterms}{#1}%

```

Check if database exists.

```

  \DTLifdbexists{\newterm@database}%
  {%

```

Provide user the means to access the current database name.

```
\edef\DTLgidxCurrendb{\newterm@database}%
```

Get the fields from datagidx:

```
\edef\do@getrow{\noexpand\dtlgetrowforvalue
  {datagidx}%
  {\dtlcolumnindex{datagidx}{Glossary}}%
  {\newterm@database}%
}%
\do@getrow
\dtlgetentryfromcurrentrow
  {\datagidx@title}%
  {\dtlcolumnindex{datagidx}{Title}}%
\dtlgetentryfromcurrentrow
  {\datagidx@heading}%
  {\dtlcolumnindex{datagidx}{Heading}}%
\dtlgetentryfromcurrentrow
  {\datagidx@postheading}%
  {\dtlcolumnindex{datagidx}{PostHeading}}%
\dtlgetentryfromcurrentrow
  {\datagidx@multicols}%
  {\dtlcolumnindex{datagidx}{MultiCols}}%
\dtlgetentryfromcurrentrow
  {\datagidx@sort}%
  {\dtlcolumnindex{datagidx}{Sort}}%
\dtlgetentryfromcurrentrow
  {\datagidx@style}%
  {\dtlcolumnindex{datagidx}{Style}}%
\dtlgetentryfromcurrentrow
  {\datagidx@showgroups}%
  {\dtlcolumnindex{datagidx}{ShowGroups}}%
```

Allow user to override style here.

```
\edef\dtl@do@setkeys{\noexpand\setkeys{newgloss}{\expandonce\newterm@styles}}%
\dtl@do@setkeys
```

Do we need to use multicols?

```
\ifnum\datagidx@columns>1\relax
  \ifnum\datagidx@columns=2\relax
    \ifdatagidxbalance
      \printterms@setupmulticol
    \else
      \printterms@setuptwocol
    \fi
  \else
    \printterms@setupmulticol
  \fi
\else
  \def\datagidx@prestart{}%
  \def\datagidx@postend{}%
```

```

\fi
\let\@dtl@dbname\DTLgidxCurrentdb
Set the style
\csuse{datagidxshowgroups\datagidx@showgroups}%
\datagidxsetstyle{\datagidx@style}%
Now display the glossary/index:
\def\datagidx@labellist{%
\ifnum\datagidx@columns=1\relax
\datagidx@heading{\datagidx@title}%
\datagidx@postheading
\fi
\datagidx@do@sort
\datagidx@prestart
:
\printtermsstartpar
\datagidxstart
\let\DTLgidxName\datagidx@invert
\let\DTLgidxPlace\datagidx@invert
\let\DTLgidxSubject\datagidx@invert
\let\DTLgidxOffice\datagidx@invert
\DTLgidxForeachEntry
{%
\datagidxitem
}%
\datagidxend
\datagidx@end
}%
{%
Database doesn't exist.
\PackageError{datagidx}%
{Glossary/index data base '\newterm@database' doesn't exist}%
{%
You must define the glossary/index data base before you can
use it.%
}%
}%
\egroup
}

```

```

tagidx@getgroup Get the current group.
\def\datagidx@getgroup#1#2\datagidx@endgetgroup{%
\dtl@setcharcode{#1}{\count@}%
\dtlifintclosedbetween{\count@}{48}{57}%
{%
\gdef\datagidxcurrentgroup{Numbers}%
}%
{%

```



```

\dtlifintclosedbetween{\count@}{97}{122}%
{%
  \advance\count@ by -96\relax
  \xdef\datagidxcurrentgroup{\@Alph\count@}%
}%
{%
  \dtlifintclosedbetween{\count@}{65}{90}%
  {%
    \gdef\datagidxcurrentgroup{#1}%
  }%
  {%
    \gdef\datagidxcurrentgroup{Symbols}%
  }%
}%
}%
}

```

groupHeaderTitle Produce the group title from the group label.

```

\newcommand*\DTLgidXGroupHeaderTitle[1]{%
  \ifcsdef{datagidx#1name}
  {%
    \csuse{datagidx#1name}%
  }%
  {%
    #1%
  }%
}

```

gidXForeachEntry `\DTLgidXForeachEntry{<body>}`

Iterate through the current database, but only do *<body>* if there is a location or cross-reference.

```

\newcommand{\DTLgidXForeachEntry}[1]{%
  \def\datagidxprevgroup{}%
  \edef\datagidx@doforeachentry{%
    \noexpand\DTLforeach*[\expandonce\printterms@condition]{\DTLgidXCurrentdb}%
    {\expandonce\DTLgidXAssignList}
  }%
  \datagidx@doforeachentry
  {%

```

Iterate through top-level entries.

```

\DTLifnull{\Parent}%
{%

```

If there's no location, but there is a current location, then document needs updating.

```

\DTLifnull\Location

```

```
{%
  \DTLifnull\CurrentLocation
  {%
  }%
  {%
```

We have a location but not a location.

```
    \global\let\@datagidx@dorerun@warn\@data@rerun@warn
  }%
}%
{%
```

We have a location. Is it up-to-date?

```
\ifcsdef{datagidx@prev@loc@\Label}%
{%
```

Current location was saved in the previous run. Has it changed?

```
  \protected@edef\@prev@location{%
    \csname datagidx@prev@loc@\Label\endcsname}%
  \@onelevel@sanitize\@prev@location
  \protected@edef\@cur@location{\CurrentLocation}%
  \@onelevel@sanitize\@cur@location
  \ifdequal{\@prev@location}{\@cur@location}%
  {}%
  {%
    \global\let\@datagidx@dorerun@warn\@data@rerun@warn
  }%
}%
{%
```

Current location wasn't saved last run, so rerun required.

```
    \global\let\@datagidx@dorerun@warn\@data@rerun@warn
  }%
}%
\datagidx@doifdisplayed
{%
```

Write current location to file to compare current and previous lists. (Can't compare \Location with \CurrentLocation as there may be locations occurring across a page boundary.)

```
\edef\datagidx@dowrite{%
  \noexpand\protected@write\noexpand\@auxout{%}%
  {%
    \string\datagidx@save@loc{\Label}{\CurrentLocation}%
  }%
}%
\datagidx@dowrite
```

Initialise level.

```
\datagidx@level=1\relax
\expandafter\datagidx@getgroup\Sort{}\datagidx@endgetgroup
#1%
\global\let\datagidxprevgroup\datagidxcurrentgroup
```

```

    }%
  }%
  {}%
  }%
}

```

```
\datagidx@doifdisplayed{<body>}
```

Do <body> if entry should appear in the glossary/index. \Location, \See and \SeeAlso must be set before use.

```

\newcommand{\datagidx@doifdisplayed}[1]{%
  \DTLifnull{\Location}%
  {%
    \DTLifnull{\See}
    {%
      \DTLifnull{\SeeAlso}{}%
      {%
        #1%
      }%
    }%
  }%
}

```

See is not null, but have any of the cross-referenced items been used?

```

\@for\dtl@thislabel:=\See\do
{%

```

Does the cross-referenced term exist?

```

  \iftermexists{\dtl@thislabel}%
  {%

```

Has it been used?

```

    \ifentryused{\dtl@thislabel}%
    {%
      #1%
    }

```

Break out of loop.

```

        \@endfortrue
      }%
    {}%
  }%
  {}%
  }%
}

}
{%
  #1%
}
}%
}

```

\datagidx@level Keep track of current level  
    \newcount\datagidx@level

## 6 databib.sty

### 6.1 Package Declaration

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{databib}[2018/12/07 v2.31 (NLCT)]
```

Load required packages:

```
\RequirePackage{datatool}
```

### 6.2 Package Options

`\dtlbib@style` The default bib style is stored in `\dtlbib@style`.

```
\newcommand*{\dtlbib@style}{plain}
```

The `style=databib` package option sets `\dtlbib@style`.

```
\define@choicekey{databib.sty}{style}{plain,abbrv,alpha}{%
\def\dtlbib@style{#1}}
```

Process package options:

```
\ProcessOptionsX
```

### 6.3 Loading BBL file

```
\DTLloadbbl \DTLloadbib[{bbl file}]{{db name}}{{bib list}}
```

```
\newcommand*{\DTLloadbbl}[3][\jobname.bbl]{%
\bibliographystyle{databib}%
\if@filesw
\immediate\write\@auxout{\string\bibdata{#3}}%
\fi
\DTLnewdb{#2}%
\edef\DTLBIBdbname{#2}%
\@input@{#1}}
```

`\DTLnewbibrow` `\DTLnewbibrow` adds a new row to the bibliography database. (`\DTLBIBdbname` must be set prior to use to the name of the datatool database which must exist. Any check to determine its existence should be performed when `\DTLBIBdbname` is set.)

```
\newcommand*{\DTLnewbibrow}{\@DTLnewrow{\DTLBIBdbname}}
```

`\DTLnewbibitem` `\DTLnewbibitem{<key>}{<value>}`

Adds a new database entry with the given key and value.

```
\newcommand*{\DTLnewbibitem}[2]{%
  \@DTLnewdbentry{\DTLBIBdbname}{#1}{#2}}
```

## 6.4 Predefined text

`\andname`  
`\providecommand*{\andname}{and}`

`\ofname`  
`\providecommand*{\ofname}{of}`

`\inname`  
`\providecommand*{\inname}{in}`

`\etalname`  
`\providecommand*{\etalname}{et al.}`

`\editorname`  
`\providecommand*{\editorname}{editor}`

`\editorsname`  
`\providecommand*{\editorsname}{editors}`

`\volumename`  
`\providecommand*{\volumename}{volume}`

`\numbername`  
`\providecommand*{\numbername}{number}`

`\pagesname`  
`\providecommand*{\pagesname}{pages}`

`\pagename`  
`\providecommand*{\pagename}{page}`

`\editionname`  
`\providecommand*{\editionname}{edition}`

`\techreportname`  
`\providecommand*{\techreportname}{Technical report}`

```

\mscthesistitle
\providecommand*\mscthesistitle{Master's thesis}

\phdthesistitle
\providecommand*\phdthesistitle{PhD thesis}

```

## 6.5 Displaying the bibliography

```
\DTLbibliography{<bib dbname>}
```

Displays the bibliography for the database *<bib dbname>* which must have previously been loaded using `\DTLloadbbl`.

DTLbibliography

```

\newcommand*\DTLbibliography}[2] [\boolean{true}] {%
  \begin{DTLthebibliography}[#1][#2]%
  \DTLforeachbibentry[#1][#2]{%
    \DTLbibitem \DTLformatbibentry \DTLendbibitem
  }%
  \end{DTLthebibliography}%
}

```

DTLformatbibentry

```
\DTLformatbibentry
```

Formats the current bib entry.

```
\newcommand*\DTLformatbibentry}{%
```

Check format for this type is defined.

```

\@ifundefined{DTLformat\DBIBentrytype}{%
  {%
    \PackageError{datbib}{Don't know how to format bibliography
      entries of type '\DBIBentrytype'}{}}%
  }%
  {%

```

Print information to terminal and log file if in verbose mode.

```
\dtl@message{[\DBIBcitekey]}%
```

Initialise

```
\DTLstartsentencefalse\DTLmidsentencefalse\DTLperiodfalse
```

Format this entry

```

\csname DTLformat\DBIBentrytype\endcsname
  }%
}

```

DTLformatbibentry

```
\gDTLformatbibentry
```

Global version.

```
\newcommand*{\gDTLformatbibentry}{%
```

Check format for this type is defined.

```
\@ifundefined{DTLformat\DBIBentrytype}{%
```

```
{%
```

```
\PackageError{datbib}{Don't know how to format bibliography  
entries of type '\DBIBentrytype'}{}
```

```
}%
```

```
{%
```

Print information to terminal and log file if in verbose mode.

```
\dtl@message{[\DBIBcitekey]}%
```

Initialise

```
\global\DTLstartsentencefalse
```

```
\global\DTLmidsentencefalse
```

```
\global\DTLperiodfalse
```

Format this entry

```
\csname DTLformat\DBIBentrytype\endcsname
```

```
}%
```

```
}
```

DTLformatthisbibentry

```
\DTLformatthisbibentry{<db>}{<cite key>}
```

Just does \DTLformatbibentry for a given entry.

```
\newcommand*{\DTLformatthisbibentry}[2]{%
```

```
\edef\DBIBname{#1}%
```

```
\edef\DBIBcitekey{#2}%
```

```
\edtlgetrowforvalue{#1}{\dtlcolumnindex{#1}{CiteKey}}{\DBIBcitekey}%
```

```
\dtl@gathervalues{#1}{\dtlcurrentrow}%
```

```
\letcs{\DBIBentrytype}{\dtl@key@EntryType}%
```

```
\DTLformatbibentry
```

```
}
```

\DTLendbibitem Hook to add extra information at the end of a bibliography item. This does nothing by default.

```
\newcommand*{\DTLendbibitem}{}%
```

\DTLwidest Define a length to store the widest bib entry label

```
\newlength\dtl@widest
```



tewidestbibentry

```
\DTLcomputewidestbibentry{<conditions>}{<db name>}{<bib label>}{<cmd>}
```

Computes the widest bibliography entry over all entries satisfying *<condition>* for the database called *<db name>*, where the bibliography label is formatted according to *<bib label>* and stores the result in *<cmd>* which must be a command name.

```
\newcommand*{\DTLcomputewidestbibentry}[4]{%
\dtl@widest=0pt\relax
\let#4=\@empty
\DTLforeachbibentry[#1]{#2}{%
\settowidth{\dtl@tmplength}{#3}%
\ifdim\dtl@tmplength>\dtl@widest\relax
\dtl@widest=\dtl@tmplength
\protected@edef#4{#3}%
\fi
}%
}
```

fforeachbibentry

```
\DTLforeachbibentry[<condition>]{<db name>}{<text>}
```

```
\DTLforeachbibentry* [<condition>]{<db name>}{<text>}
```

Iterates through the database called *<db name>* and does *<text>* if *<condition>* is met. As with `\DTLforeach`, the starred version is read only.

```
\newcommand*{\DTLforeachbibentry}{%
\@ifstar\@sDTLforeachbibentry\@DTLforeachbibentry}
```

fforeachbibentry

Unstarred version

```
\newcommand*{\@DTLforeachbibentry}[3][\boolean{true}]{%
```

Store database name.

```
\edef\DBIBname{#2}%
```

Reset row counter.

```
\setcounter{DTLbibrow}{0}%
```

Iterate through the database.

```
\@DTLforeach{#2}{\DBIBCitekey=CiteKey,\DBIBentrytype=EntryType}%
{%
\dtl@gathervalues{#2}{\dtlcurrentrow}%
\ifthenelse{#1}{\refstepcounter{DTLbibrow}#3}{}%
}%
}
```

foreachbibentry Starred version

```

\newcommand*{\@sDTLforeachbibentry}[3][\boolean{true}]{%
Store database name.
\edef\DBIBname{#2}%
Reset row counter.
\setcounter{DTLbibrow}{0}%
Iterate through the database (read only).
\@sDTLforeach{#2}{\DBIBcitekey=CiteKey,\DBIBentrytype=EntryType}%
{%
\dtl@gathervalues{#2}{\dtlcurrentrow}%
\ifthenelse{#1}{\refstepcounter{DTLbibrow}#3}{}%
}%
}

```

Lforeachbibentry `\gDTLforeachbibentry[<condition>]{<db name>}{<text>}`

`\gDTLforeachbibentry*[<condition>]{<db name>}{<text>}`

Global version.

```

\newcommand{\gDTLforeachbibentry}{%
\@ifstar\@sgDTLforeachbibentry\@gDTLforeachbibentry}

```

foreachbibentry Unstarred version

```

\newcommand*{\@gDTLforeachbibentry}[3][\boolean{true}]{%
Store database name.
\xdef\DBIBname{#2}%
Reset row counter.
\global\c@DTLbibrow = 0\relax
Iterate through the database.
\@DTLforeach{#2}{\DBIBcitekey=CiteKey,\DBIBentrytype=EntryType}%
{%
\dtl@g@gathervalues{#2}{\dtlcurrentrow}%
\ifthenelse{#1}%
{%
\refstepcounter{DTLbibrow}%
\global\c@DTLbibrow=\c@DTLbibrow
#3%
}%
{}}%
}%
}

```

`foreachbibentry` Starred version

```
\newcommand*{\sgDTLforeachbibentry}[3][\boolean{true}]{%
Store database name.
  \xdef\DBIBname{#2}%
Reset row counter.
  \global\c@DTLbibrow = 0\relax
Iterate through the database (read only).
  \@sDTLforeach{#2}{\DBIBCitekey=CiteKey,\DBIBentrytype=EntryType}%
  {%
    \dtl@g@gathervalues{#2}{\dtlcurrentrow}%
    \ifthenelse{#1}%
    {%
      \refstepcounter{DTLbibrow}%
      \global\c@DTLbibrow=\c@DTLbibrow
      #3%
    }%
  }%
}
```

`DTLbibrow` The counter `DTLbibrow` keeps track of the current row in the body of `\DTLforeachbibentry`. (You can't rely on `DTLrowi`, `DTLrowii` and `DTLrowiii`, as `\DTLforeachbibentry` pass the conditions to the optional argument of `\DTLforeach`, but instead uses `\ifthenelse`, which means that `DTLrowi` etc will be incremented, even when the given condition is not met.)

```
\newcounter{DTLbibrow}
```

`\theHDTLbibrow` Keep hyperref happy:

```
\def\theHDTLbibrow{\theHDTLrow.bib.\arabic{DTLbibrow}}%
```

`\DTLbibfield` `\DTLbibfield{<field name>}`

Gets the value assigned to the field `<field name>` for the current row of `\DTLforeachbibentry`. (Doesn't check if the field exists, or if it is being used within `\DTLforeachbibentry`.)

```
\newcommand*{\DTLbibfield}[1]{\csname @dtl@key@#1\endcsname}
```

`\DTLbibfieldlet` `\DTLbibfield{<cs>}{<field name>}`

Gets the value assigned to the field `<field name>` for the current row of `\DTLforeachbibentry` and assigns it to the control sequence `<cs>`. (Doesn't check if the field exists, or if it is being used within `\DTLforeachbibentry`.)

```
\newcommand*\DTLbibfieldlet}[2]{%
  \letcs{#1}{@dtl@key@#2}%
}
```

`\ifbibfieldexists` `\DTLifbibfieldexists{<field name>}{<true part>}{<false part>}`

Determines whether the given field name exists for the current row of `\DTLforeachbibentry`.

```
\newcommand*\DTLifbibfieldexists}[3]{%
  \ifundefined{@dtl@key@#1}{#3}{%
  \expandafter\DTLifnull\csname @dtl@key@#1\endcsname
  #3}{#2}}
```

`\nybibfieldexists` `\DTLifanybibfieldexists{<list of field name>}{<true part>}{<false part>}`

Determines whether any of the listed fields exist for the current row of `\DTLforeachbibentry`.

```
\newcommand*\DTLifanybibfieldexists}[3]{%
  \for@dtl@thisfield:=#1\do{%
  \ifundefined{@dtl@key@dtl@thisfield}{-%
  \expandafter\DTLifnull\csname @dtl@key@dtl@thisfield\endcsname
  }{-%
  \@endfortrue}}}%
  \if@endfor
  #2%
  \else
  #3%
  \fi
  \@endforfalse
}
```

`\ifDTLperiod` The conditional `\ifDTLperiod` is used to keep track of any abbreviations ending with a period, this is to ensure that abbreviations aren't followed by a full stop if they already have a full stop terminating the abbreviation.

```
\newif\ifDTLperiod
```

`\Lcheckendsperiod` `\DTLcheckendperiod{<string>}`

Checks if `<string>` ends with a full stop. This sets `\ifDTLperiod`.

```
\newcommand*\DTLcheckendsperiod}[1]{%
  \dtl@checkendsperiod#1\@nil\relax}
```

```

\def\dtl@checkendsperiod#1#2{%
\def\@dtl@argi{#1}\def\@dtl@argii{#2}%
\def\@dtl@period{.}%
\ifx\@dtl@argi\@nnil
\global\DTLperiodfalse
\let\@dtl@donext=\relax
\else
\ifx\@dtl@argii\@nnil
\ifx\@dtl@argi\@dtl@period
\global\DTLperiodtrue
\else
\global\DTLperiodfalse
\fi
\let\@dtl@donext=\@gobble
\else
\let\@dtl@donext=\dtl@checkendsperiod
\fi
\fi
\@dtl@donext{#2}%
}

```

bfieldendsperiod `\DTLcheckbibfieldendsperiod{<label>}`

Checks if the bib field *<label>* ends with a full stop. This sets `\ifDTLperiod`.

```

\newcommand*{\DTLcheckbibfieldendsperiod}[1]{%
\protected@edef\@dtl@tmp{\DTLbibfield{#1}}%
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}}

```

ifDTLmidsentence `\ifDTLmidsentence`

Determine whether we are in the middle of a sentence.

```
\newif\ifDTLmidsentence
```

DTLstartsentence `\ifDTLstartsentence`

Determine whether we are at the start of a sentence.

```
\newif\ifDTLstartsentence
```

\DTLaddperiod `\DTLaddperiod`

Adds a full stop and sets `\DTLmidsentencefalse`, `\DTLstartsentencetrue` and `\DTLperiodfalse`.

```
\newcommand*{\DTLaddperiod}{\DTLmidsentencefalse\DTLperiodfalse
\DTLstartsentencetrue
\ifDTLperiod\else.\fi}
```

`\DTLaddcomma` `\DTLaddcomma`

Adds a comma and sets `\DTLmidsentencetrue`, `\DTLperiodfalse` and `\DTLstartsentencefalse`

```
\newcommand*{\DTLaddcomma}{, \DTLmidsentencetrue
\DTLperiodfalse\DTLstartsentencefalse}
```

`\DTLstartsentencespace` Adds a space if at the start of the sentence, otherwise does nothing. (The space between sentences is added this way, rather than in `\DTLaddperiod` otherwise spurious extra space can occur at the end of the bib item. The `spacefactor` needs to be set manually, because there's stuff in the way of the previous sentence's full stop and this space which confuses the inter sentence spacing (and, of course, the previous sentence could have ended with a capital letter.)

```
\newcommand*{\DTLstartsentencespace}{%
\ifDTLstartsentence\spacefactor=\sfcode'\.\relax\space
\fi\DTLstartsentencefalse}
```

`\DTLtwoand` In a list of only two author (or editor) names, the text between the two names is given by `\DTLtwoand`:

```
\newcommand*{\DTLtwoand}{\ andname\ }
```

`\DTLlandlast` In a list of author (or editor) names, the text between the penultimate and last name is given by `\DTLlandlast`:

```
\newcommand*{\DTLlandlast}{, \andname\ }
```

`\DTLlandnotlast` In a list of author (or editor) names, the text between the names (except the penultimate and last name) is given by `\DTLlandnotlast`:

```
\newcommand*{\DTLlandnotlast}{, }
```

`\dtl@authorcount` Define a count register to keep track of the number of authors:

```
\newcount\@dtl@authorcount
```

`\DTLmaxauthors` The counter `\DTLmaxauthors` indicates the maximum number of author names to display, if there are more than that number, `\etalname` is used.

```
\newcounter{DTLmaxauthors}
\setcounter{DTLmaxauthors}{10}
```

`\formatauthorlist` Format a list of author names (the list is stored in `\@dtl@key@Author`):

```
\newcommand*{\DTLformatauthorlist}{%
\DTLifbibfieldexists{Author}{%
```

```

\DTLstartsentencespace
\@dtl@authorcount=0\relax
\@for\@dtl@author:=\@dtl@key@Author\do{%
\advance\@dtl@authorcount by 1\relax}%
\@dtl@tmpcount=0\relax
\ifnum\@dtl@authorcount>\c@DTLmaxauthors
{
  \@for\@dtl@author:=\@dtl@key@Author\do{%
  \advance\@dtl@tmpcount by 1\relax
  \ifnum\@dtl@tmpcount=1\relax
  \expandafter\DTLformatauthor\@dtl@author
  \else
  \ifnum\@dtl@tmpcount>\c@DTLmaxauthors
  \DTLlandnotlast \etalname
  \expandafter\DTLcheckendsperiod\expandafter{\etalname}%
  \@endfortrue
  \else
  \DTLlandnotlast \expandafter\DTLformatauthor\@dtl@author
  \fi
  \fi
  }%
}
\else
\@for\@dtl@author:=\@dtl@key@Author\do{%
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
\expandafter\DTLformatauthor\@dtl@author
\else
\ifnum\@dtl@tmpcount=\@dtl@authorcount
\ifnum\@dtl@authorcount=2\relax
\DTLtwoand
\else
\DTLlandlast
\fi
\expandafter\DTLformatauthor\@dtl@author
\else
\DTLlandnotlast \expandafter\DTLformatauthor\@dtl@author
\fi
\fi
}
}
\fi
}{}%
}

```

**DTLmaxeditors** The counter `DTLmaxeditors` indicates the maximum number of editor names to display, if there are more than that number, `\etalname` is used.

```

\newcounter{DTLmaxeditors}
\setcounter{DTLmaxeditors}{10}

```

ormateditorlist   Format a list of editor names (the list is stored in \@dtl@key@Editor):

```
\newcommand*{\DTLformatteditorlist}{%
\DTLifbibfieldexists{Editor}{%
\DTLstartsentencepace
\@dtl@authorcount=0\relax
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\advance\@dtl@authorcount by 1\relax}%
\@dtl@tmpcount=0\relax
\ifnum\@dtl@authorcount>\c@DTLmaxeditors
{
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
\expandafter\DTLformatteditor\@dtl@author
\else
\ifnum\@dtl@tmpcount>\c@DTLmaxeditors
\DTLlandnotlast \etalname
\expandafter\DTLcheckendsperiod\expandafter{\etalname}%
\endfortrue
\else
\DTLlandnotlast \expandafter\DTLformatteditor\@dtl@author
\fi
\fi
}%
\else
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
\expandafter\DTLformatteditor\@dtl@author
\else
\ifnum\@dtl@tmpcount=\@dtl@authorcount
\ifnum\@dtl@authorcount=2\relax
\DTLtwoand
\else
\DTLlandlast
\fi
\expandafter\DTLformatteditor\@dtl@author
\else
\DTLlandnotlast \expandafter\DTLformatteditor\@dtl@author
\fi
\fi
}%
\fi
,
\ifnum\@dtl@authorcount=1\relax
\editorname
\expandafter\DTLcheckendsperiod\expandafter{\editorname}%
\else
```



```

\editorsname
\expandafter\DTLcheckendsperiod\expandafter{\editorsname}%
\fi
}{}%
}

```

formatsurnameonly

```
\DTLformatsurnameonly{<von part>}{<surname>}{<jr part>}{<forenames>}
```

This is used when only the surname should be displayed. (The final argument, *<forenames>*, is ignored.)

```

\newcommand*\DTLformatsurnameonly[4]{%
\DTLstartsentencespace
\def\@dtl@tmp{#1}%
\ifx\@dtl@tmp\@empty\else#1~\fi
#2%
\def\@dtl@tmp{#3}%
\ifx\@dtl@tmp\@empty
\DTLcheckendsperiod{#2}%
\else
, #3%
\DTLcheckendsperiod{#3}%
\fi
}

```

formatforenames

```
\DTLformatforenames{<forenames>}
```

The format of an author/editor's forenames. If the forenames occur at the start of sentence, a new sentence space is added. The argument is checked to determine whether it ends with a full stop (sometimes the forenames may include initials.)

```

\newcommand*\DTLformatforenames[1]{%
\DTLstartsentencespace
#1%
\DTLcheckendsperiod{#1}}

```

formatabbrvforenames

```
\DTLformatabbrvforenames{<forenames>}
```

The format of an author/editor's abbreviated forenames. The initials may or may not end in a full stop depending on the commands governing the format of `\DTLstoreinitials`, so the initials need to be checked using `\DTLcheckendsperiod`.

```
\newcommand*\DTLformatabbrvforenames[1]{%
```

```

\DTLstartsentencespace
\DTLstoreinitials{#1}{\@dtl@tmp}\@dtl@tmp
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}}

```

\DTLformatvon \DTLformatvon{<von part>}

The format of the “von” part. This does nothing if the argument is empty, otherwise it does the argument followed by a non-breakable space.

```

\newcommand*\DTLformatvon[1]{%
\DTLstartsentencespace
\def\@dtl@tmp{#1}%
\ifx\@dtl@tmp\@empty
\else
#1~%
\fi
}

```

DTLformatsurname \DTLformatsurname{<surname>}

The format of an author/editor’s surname.

```

\newcommand*\DTLformatsurname[1]{%
\DTLstartsentencespace
#1\DTLcheckendsperiod{#1}}

```

\DTLformatjr \DTLformatjr{<jr part>}

The format of the “jr” part. This does nothing if the argument is empty.

```

\newcommand*\DTLformatjr[1]{%
\DTLstartsentencespace
\def\@dtl@tmp{#1}%
\ifx\@dtl@tmp\@empty
\else
, #1\DTLcheckendsperiod{#1}%
\fi
}

```

tcrossrefeditor Format cross reference editors:

```

\newcommand*\DTLformatcrossrefeditor{%
\DTLifbibfieldexists{Editor}{%
\DTLstartsentencespace
\@dtl@authorcount=0\relax

```

```

\@for\@dtl@author:=\@dtl@key@Editor\do{%
\advance\@dtl@authorcount by 1\relax}%
{\@dtl@tmpcount=0\relax
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\ifnum\@dtl@authorcount=1\relax
\expandafter\DTLformatsurnameonly\@dtl@author
\else
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
\expandafter\DTLformatsurnameonly\@dtl@author
\else
\ifnum\@dtl@authorcount=2\relax
\ \andname\ \expandafter\DTLformatsurnameonly\@dtl@author
\else
\ \etalname
\expandafter\DTLcheckendsperiod\expandafter{\etalname}
\fi
\@endfortrue
\fi
\fi
}}%
}{}%
}

```

formatvolnumpages Format volume, number and pages (of an article).

```

\newcommand*\DTLformatvolnumpages}{%
\DTLifbibfieldexists{Volume}{%
\DTLstartsentencespace
\DTLbibfield{Volume}\DTLperiodfalse}{}%
\DTLifbibfieldexists{Number}{%
\DTLstartsentencespace
(\DTLbibfield{Number})\DTLperiodfalse}{}%
\DTLifbibfieldexists{Pages}{%
\DTLifanybibfieldexists{Volume,Number}{:}{}%
\DTLstartsentencespace
\protected@edef\@dtl@pages{0\DTLbibfield{Pages}}%
\DTLifnumerical{\@dtl@pages}{\pagename}{\pagesname}~}%
\DTLbibfield{Pages}\DTLperiodfalse}{}%
}

```

TLformatbvolume Format book volume.

```

\newcommand*\DTLformatbvolume}{%
\DTLifbibfieldexists{Volume}{%
\ifDTLmidsentence
\ volumename
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\volumename
\fi
}

```

```

~\DTLbibfield{Volume}%
\DTLifbibfieldexists{Series}{\ \ofname\
{\em\DTLbibfield{Series}}\DTLcheckbibfieldendsperiod{Series}}{%
\DTLcheckbibfieldendsperiod{Volume}}%
}{}

```

matchapterpages Format chapter and pages:

```

\newcommand*\DTLformatchapterpages{%
\DTLifbibfieldexists{Chapter}{%
\DTLifbibfieldexists{Type}{%
\DTLstartsencespace
\DTLbibfield{Type}}{%
\DTLstartsencespace
\chaptername}\DTLbibfield{Chapter}%
\DTLifbibfieldexists{Pages}{\DTLaddcomma}{%
\DTLcheckbibfieldendsperiod{Chapter}}}{%
\DTLstartsencespace
\DTLformatpages}

```

\DTLformatpages Format pages:

```

\newcommand*\DTLformatpages{%
\DTLifbibfieldexists{Pages}{%
\DTLstartsencespace
\protected@edef\@dtl@pages{0\DTLbibfield{Pages}}%
\DTLifnumerical{\@dtl@pages}{\pagename}{\pagesname}~%
\DTLbibfield{Pages}\DTLcheckbibfieldendsperiod{Pages}}{%
}

```

matnumberseries Format number and series (of book)

```

\newcommand*\DTLformatnumberseries{%
\DTLifbibfieldexists{Volume}}{%
\DTLifbibfieldexists{Number}{%
\ifDTLmidsentence
\numbername
\else
\DTLstartsencespace
\expandafter\MakeUppercase\numbername
\fi}\DTLbibfield{Number}%
\DTLifbibfieldexists{Series}{\ \iname\ \DTLbibfield{Series}%
\DTLcheckbibfieldendsperiod{Series}}{%
\DTLcheckbibfieldendsperiod{Number}}%
}{%
\DTLifbibfieldexists{Series}{%
\DTLstartsencespace
\DTLbibfield{Series}%
\DTLcheckbibfieldendsperiod{Series}}}{%
}%
}

```

matbookcrossref Format a book cross reference.

```
\newcommand*{\DTLformatbookcrossref}{%
\DTLifbibfieldexists{Volume}{%
\ifDTLmidsentence
\ volumename
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\volumename
\fi
~\DTLbibfield{Volume}\ \ofname\
}{%
\ifDTLmidsentence
\ inname
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\inname
\fi\ }%
\DTLifbibfieldexists{Editor}{\DTLformatcrossrefeditor}{%
\DTLifbibfieldexists{Key}{%
\DTLbibfield{Key}}{%
\DTLifbibfieldexists{Series}{%
{\em\DTLbibfield{Series}}}{%
}%
}%
~\DTLpcite{\DTLbibfield{CrossRef}}}%
}
```

ollproccrossref Format 'incollections' cross reference.

```
\newcommand*{\DTLformatincollproccrossref}{%
\DTLifbibfieldexists{Editor}{%
\ifDTLmidsentence
\ inname
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\inname
\fi\
\DTLformatcrossrefeditor
}{%
\DTLifbibfieldexists{Key}{%
\ifDTLmidsentence
\ inname
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\inname
\fi\ \DTLbibfield{Key}%
}{%
\DTLifbibfieldexists{BookTitle}{%
\ifDTLmidsentence
\ inname
```

```

\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\iname
\fi\ \DTLformatbooktitle{\DTLbibfield{BookTitle}}}{}%
}}%
~\DTLpcite{\DTLbibfield{CrossRef}}}%
}

```

atinedbooktitle Format editor and booktitle:

```

\newcommand*\DTLformatinedbooktitle}{%
\DTLifbibfieldexists{BookTitle}{%
\ifDTLmidsentence
  \iname
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\iname
\fi\
\DTLifbibfieldexists{Editor}{%
\DTLformatteditorlist\DTLaddcomma \DTLformatbooktitle{\DTLbibfield{BookTitle}}%
\DTLcheckbibfieldendsperiod{BookTitle}%
}{\DTLformatbooktitle{\DTLbibfield{BookTitle}}%
\DTLcheckbibfieldendsperiod{BookTitle}%
}}{}}

```

\DTLformatdate Format date.

```

\newcommand*\DTLformatdate}{%
\DTLifbibfieldexists{Year}{%
\DTLifbibfieldexists{Month}{%
\protected@edef\@dtl@tmp{\DTLbibfield{Month}}%
\ifDTLmidsentence
  \@dtl@tmp
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\@dtl@tmp
\fi\
\DTLmidsentencefalse}{}%
\DTLstartsentencespace
\DTLbibfield{Year}}{%
\DTLifbibfieldexists{Month}{%
\protected@edef\@dtl@tmp{\DTLbibfield{Month}}%
\ifDTLmidsentence
  \@dtl@tmp
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\@dtl@tmp
\fi
\DTLcheckbibfieldendsperiod{Month}%
}}{}}

```

articleglossref Format article cross reference.

```

\newcommand*{\DTLformatarticleglossref}{%
\DTLifbibfieldexists{Key}{%
\ifDTLmidsentence
\inname
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\inname
\fi
\ {\em\DTLbibfield{Key}}}{%
\DTLifbibfieldexists{Journal}{%
\ifDTLmidsentence
\inname
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\inname
\fi
\ {\em\DTLbibfield{Journal}}}{}}%
~\DTLpcite{\DTLbibfield{CrossRef}}%
}

```

\DTLpcite

```

\newrobustcmd*{\DTLpcite}[1]{%
\protected@edef\@dtl@tmp{#1}%
\cite{\@dtl@tmp}%
}

```

### 6.5.1 ifthen conditionals

The conditionals defined in this section may be used in the optional argument of \DTLforeachbibentry. They may also be used in the first argument of \ifthenelse, but only if the command occurs within the body of \DTLforeachbibentry.

TLbibfieldexists

```

\DTLbibfieldexists{<field label>}

```

Checks if named bib field exists for current entry

```

\newcommand*{\DTLbibfieldexists}[1]{%
\TE@throw\noexpand\dtl@testbibfieldexists{#1}%
\noexpand\if@dtl@condition}

```

tbibfieldexists

```

\newcommand*{\dtl@testbibfieldexists}[1]{%
\DTLifbibfieldexists{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}

```

`\DTLbibfieldiseq` `\DTLbibfieldiseq{<field label>}{<value>}`

Checks if the value of the bib field given by *<field label>* is equal to *<value>*. (Uses `\dtlcompare` to determine if the values are equal. If the bib field doesn't exist, the condition is false.)

```
\newcommand*{\DTLbibfieldiseq}[2]{%
\TE@throw\noexpand\dtl@testbibfieldiseq{#1}{#2}%
\noexpand@if@dtl@condition}
```

`estbibfieldiseq`

```
\newcommand*{\dtl@testbibfieldiseq}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount=0\relax
\@dtl@conditiontrue
\else
\@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
```

`\DTLbibfieldislt` `\DTLbibfieldislt{<field label>}{<value>}`

Checks if the value of the bib field given by *<field label>* is less than *<value>*. (If the bib field doesn't exist, the condition is false.)

```
\newcommand*{\DTLbibfieldislt}[2]{%
\TE@throw\noexpand\dtl@testbibfieldislt{#1}{#2}%
\noexpand@if@dtl@condition}
```

`estbibfieldislt`

```
\newcommand*{\dtl@testbibfieldislt}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount=0\relax
\@dtl@conditiontrue
\else
\@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
```



```

\@dtl@docompare
\ifnum\@dtl@tmpcount=-1\relax
  \@dtl@conditiontrue
\else
  \@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}

```

`\DTLbibfieldisle` `\DTLbibfieldisle{<field label>}{<value>}`

Checks if the value of the bib field given by *<field label>* is less than or equal to *<value>*. (If the bib field doesn't exist, the condition is false.)

```

\newcommand*{\DTLbibfieldisle}[2]{%
\TE@throw\noexpand\dtl@testbibfieldisle{#1}{#2}%
\noexpand\if@dtl@condition}

```

`estbibfieldisle`

```

\newcommand*{\dtl@testbibfieldisle}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount<1\relax
  \@dtl@conditiontrue
\else
  \@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}

```

`\DTLbibfieldisgt` `\DTLbibfieldisgt{<field label>}{<value>}`

Checks if the value of the bib field given by *<field label>* is greater than *<value>*. (If the bib field doesn't exist, the condition is false.)

```

\newcommand*{\DTLbibfieldisgt}[2]{%
\TE@throw\noexpand\dtl@testbibfieldisgt{#1}{#2}%
\noexpand\if@dtl@condition}

```

estbibfieldisgt

```
\newcommand*\dtl@testbibfieldisgt}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount=1\relax
\@dtl@conditiontrue
\else
\@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
```

\DTLbibfieldisge

```
\DTLbibfieldisge{<field label>}{<value>}
```

Checks if the value of the bib field given by *field label* is less than or equal to *value*. (If the bib field doesn't exist, the condition is false.)

```
\newcommand*\DTLbibfieldisge}[2]{%
\TE@throw\noexpand\dtl@testbibfieldisge{#1}{#2}%
\noexpand\if@dtl@condition}
```

estbibfieldisge

```
\newcommand*\dtl@testbibfieldisge}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount>-1\relax
\@dtl@conditiontrue
\else
\@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
```

bibfieldcontains

```
\DTLbibfieldcontains{<field label>}{<sub string>}
```

Checks if the value of the bib field given by *<field label>* contains *<sub string>*. (If the bib field doesn't exist, the condition is false.)

```
\newcommand*{\DTLbibfieldcontains}[2]{%
\TE@throw\noexpand\dtl@testbibfieldcontains{#1}{#2}%
\noexpand\if@dtl@condition}
```

ibfieldcontains

```
\newcommand*{\dtl@testbibfieldcontains}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\dtl@testifsubstring\expandafter{\@dtl@tmp}{#2}%
}{\@dtl@conditionfalse}}
```

## 6.6 Bibliography Style Macros

The macros defined in this section should be redefined by bibliography styles.

thebibliography

How to format the entire bibliography:

```
\newenvironment{DTLthebibliography}[2][\boolean{true}]{%
\@dtl@tmpcount=0\relax
\@sDTLforeach{#1}{#2}{-}{\advance\@dtl@tmpcount by 1\relax}%
\begin{thebibliography}{\number\@dtl@tmpcount}
}{\end{thebibliography}}
```

\DTLmonthname

The monthname style. The argument must be a number from 1 to 12. By default, uses \dtl@monthname.

```
\newcommand*{\DTLmonthname}[1]{%
\dtl@monthname{#1}}
```

\dtl@monthname

Full month names:

```
\newcommand*{\dtl@monthname}[1]{%
\ifcase#1%
\or January%
\or February%
\or March%
\or April%
\or May%
\or June%
\or July%
\or August%
\or September%
\or October%
```

```

\or November%
\or December%
\fi}

```

@abbrvmonthname Abbreviated months:

```

\newcommand*{\dtl@abbrvmonthname}[1]{%
\ifcase#1%
\or Jan.%
\or Feb.%
\or Mar.%
\or Apr.%
\or May%
\or June%
\or July%
\or Aug.%
\or Sept.%
\or Oct.%
\or Nov.%
\or Dec.%
\fi}

```

\DTLbibitem Define how to start a new bibitem:

```

\newcommand*{\DTLbibitem}{\bibitem{\DBIBCitekey}}

```

\DTLmbibitem As \DTLbibitem but for \DTLmbibliography

```

\newcommand*{\DTLmbibitem}[1]{\bibitem{#1@\DBIBCitekey}}

```

DTLcustombibitem

```

\DTLcustombibitem{<item code>}{<ref text>}{<cite key>}

```

As \DTLbibitem but user provides <item code> to use in place of \item. This code can access the cite key using \DBIBCitekey. The <ref text> is the text associated with this bib item. (For example, if used in an enumerate environment, <ref text> might be \theenumi.)

```

\newcommand*{\DTLcustombibitem}[3]{%
#1%
\if@filesw
\immediate\write\@auxout{\string\bibcite{#3}{#2}}%
\fi
\ignorespaces
}

```

\DTLformatauthor

```

\DTLformatauthor{<von part>}{<surname>}{<junior part>}{<forenames>}

```

The format of an author's name.

	<pre> \newcommand*{\DTLformatauthor}[4]{% \DTLformatforenames{#4} \DTLformatvon{#1}% \DTLformatsurname{#2}% \DTLformatjr{#3}} </pre>
DTLformatteditor	<p>The format of an editor's name.</p> <pre> \newcommand*{\DTLformatteditor}[4]{% \DTLformatforenames{#4} \DTLformatvon{#1}% \DTLformatsurname{#2}% \DTLformatjr{#3}} </pre>
TLformattedition	<p>The format of an edition:</p> <pre> \newcommand*{\DTLformattedition}[1]{#1 \editionname} </pre>
TLformatarticle	<p>The format of an article:</p> <pre> \newcommand{\DTLformatarticle}{} </pre>
\DTLformatbook	<p>The format of a book:</p> <pre> \newcommand{\DTLformatbook}{} </pre>
TLformatbooklet	<p>The format of a booklet:</p> <pre> \newcommand{\DTLformatbooklet}{} </pre>
DTLformatinbook	<p>The format of an “inbook” type:</p> <pre> \newcommand{\DTLformatinbook}{} </pre>
matincollection	<p>The format of an “incollection” type:</p> <pre> \newcommand{\DTLformatincollection}{} </pre>
matinproceedings	<p>The format of an “inproceedings” type:</p> <pre> \newcommand{\DTLformatinproceedings}{} </pre>
DTLformatmanual	<p>The format of a manual:</p> <pre> \newcommand{\DTLformatmanual}{} </pre>
matmastersthesis	<p>The format of a master's thesis:</p> <pre> \newcommand{\DTLformatmastersthesis}{} </pre>
\DTLformatmisc	<p>The format of a miscellaneous entry:</p> <pre> \newcommand{\DTLformatmisc}{} </pre>
formatphdthesis	<p>The format of a Ph.D. thesis:</p> <pre> \newcommand{\DTLformatphdthesis}{} </pre>
formatproceedings	<p>The format of a proceedings:</p> <pre> \newcommand{\DTLformatproceedings}{} </pre>

`\formattechreport` The format of a technical report:  
`\newcommand{\DTLformattechreport}{}`

`\formatunpublished` The format of an unpublished work:  
`\newcommand{\DTLformatunpublished}{}`

Predefined names (these correspond to the standard  $\text{\LaTeX}$  predefined strings of the same name without the leading `\DTL`):

`\DTLacmcs`  
`\newcommand*{\DTLacmcs}{ACM Computing Surveys}`

`\DTLacta`  
`\newcommand*{\DTLacta}{Acta Informatica}`

`\DTLcacm`  
`\newcommand*{\DTLcacm}{Communications of the ACM}`

`\DTLibmjrd`  
`\newcommand*{\DTLibmjrd}{IBM Journal of Research and Development}`

`\DTLibmsj`  
`\newcommand*{\DTLibmsj}{IBM Systems Journal}`

`\DTLIEEESE`  
`\newcommand*{\DTLIEEESE}{IEEE Transactions on Software Engineering}`

`\DTLIEEEETC`  
`\newcommand*{\DTLIEEEETC}{IEEE Transactions on Computers}`

`\DTLIEEEETCAD`  
`\newcommand*{\DTLIEEEETCAD}{IEEE Transactions on Computer-Aided Design of Integrated Circuits}`

`\DTLipl`  
`\newcommand*{\DTLipl}{Information Processing Letters}`

`\DTLjacm`  
`\newcommand*{\DTLjacm}{Journal of the ACM}`

`\DTLjcsc`  
`\newcommand*{\DTLjcsc}{Journal of Computer and System Sciences}`

`\DTLscp`  
`\newcommand*{\DTLscp}{Science of Computer Programming}`

```

\DTLsicomp
\newcommand*\DTLsicomp}{SIAM Journal on Computing}

\DTLtocs
\newcommand*\DTLtocs}{ACM Transactions on Computer Systems}

\DTLtods
\newcommand*\DTLtods}{ACM Transactions on Database Systems}

\DTLtog
\newcommand*\DTLtog}{ACM Transactions on Graphics}

\DTLtoms
\newcommand*\DTLtoms}{ACM Transactions on Mathematical Software}

\DTLtoois
\newcommand*\DTLtoois}{ACM Transactions on Office Information
Systems}

\DTLtoplas
\newcommand*\DTLtoplas}{ACM Transactions on Programming Languages
and Systems}

\DTLtcs
\newcommand*\DTLtcs}{Theoretical Computer Science}

```

## 6.7 Bibliography Styles

Each bibliography style is set by the command `\dtlbst@<style>`, where *<style>* is the name of the bibliography style.

`\dtlbst@plain` The ‘plain’ style:

```
\newcommand{\dtlbst@plain}{%
```

Set how to format the entire bibliography:

```

\renewenvironment{DTLthebibliography}[2][\boolean{true}]{%
\@dtl@tmpcount=0\relax
\@sDTLforeach[##1][##2]{-}{\advance\@dtl@tmpcount by 1\relax}%
\begin{thebibliography}{\number\@dtl@tmpcount}%
}{\end{thebibliography}}%

```

Set how to start the bibliography entry:

```

\renewcommand*\DTLbibitem}{\bibitem{\DBIBcitekey}}%
\renewcommand*\DTLmbibitem}[1]{\bibitem{##1@DBIBcitekey}}%

```

Sets the author name format.

```
\renewcommand*{\DTLformatauthor}[4]{%
\DTLformatforenames{##4}
\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}}
```

Sets the editor name format.

```
\renewcommand*{\DTLformateditor}[4]{%
\DTLformatforenames{##4}
\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}}
```

Sets the edition format.

```
\renewcommand*{\DTLformatedition}[1]{##1 \editionname}%
```

Sets the monthname format.

```
\let\DTLmonthname\dtl@monthname
```

Sets other predefined names:

```
\renewcommand*{\DTLacmcs}{ACM Computing Surveys}
\renewcommand*{\DTLacta}{Acta Informatica}
\renewcommand*{\DTLcacm}{Communications of the ACM}
\renewcommand*{\DTLibmjrd}{IBM Journal of Research and Development}
\renewcommand*{\DTLibmsj}{IBM Systems Journal}
\renewcommand*{\DTLIEEE}{IEEE Transactions on Software Engineering}
\renewcommand*{\DTLIEEEtc}{IEEE Transactions on Computers}
\renewcommand*{\DTLIEEEtcad}{IEEE Transactions on Computer-Aided Design
of Integrated Circuits}
\renewcommand*{\DTLipl}{Information Processing Letters}
\renewcommand*{\DTLjacm}{Journal of the ACM}
\renewcommand*{\DTLjcss}{Journal of Computer and System Sciences}
\renewcommand*{\DTLscpp}{Science of Computer Programming}
\renewcommand*{\DTLsicomp}{SIAM Journal on Computing}
\renewcommand*{\DTLtocs}{ACM Transactions on Computer Systems}
\renewcommand*{\DTLtods}{ACM Transactions on Database Systems}
\renewcommand*{\DTLtog}{ACM Transactions on Graphics}
\renewcommand*{\DTLtoms}{ACM Transactions on Mathematical Software}
\renewcommand*{\DTLtoois}{ACM Transactions on Office Information
Systems}
\renewcommand*{\DTLtoplas}{ACM Transactions on Programming Languages
and Systems}
\renewcommand*{\DTLtcs}{Theoretical Computer Science}
```

The format of an article.

```
\renewcommand*{\DTLformatarticle}{%
\DTLformatauthorlist
\DTLifbibfieldexists{Author}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace\DTLbibfield{Title}%
```



```

\DTLcheckbibfielddendsperiod{Title}%
\DTLaddperiod}{}%
\DTLifbibfielddexists{CrossRef}{%
% cross ref field
\DTLformatarticlecrossref
\DTLifbibfielddexists{Pages}{\DTLaddcomma}{}%
\DTLformatpages
\DTLaddperiod
}{% no cross ref field
\DTLifbibfielddexists{Journal}{\DTLstartsentencespace
{\em\DTLbibfield{Journal}}}%
\DTLcheckbibfielddendsperiod{Journal}%
\DTLifanybibfielddexists{Number,Volume,Pages,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{%
\DTLformatvolnumpages
\DTLifanybibfielddexists{Volume,Number,Pages}{%
\DTLifanybibfielddexists{Year,Month}{\DTLaddcomma}{%
\DTLaddperiod}%
\DTLmidsentencefalse}{}%
\DTLformatdate
\DTLifanybibfielddexists{Year,Month}{\DTLaddperiod}}}{%
}%
\DTLifbibfielddexists{Note}{\DTLstartsentencespace\DTLbibfield{Note}}%
\DTLcheckbibfielddendsperiod{Note}%
\DTLaddperiod}{}%
}

```

The format of a book.

```

\renewcommand*{\DTLformatbook}{%
\DTLifbibfielddexists{Author}%
{%
\DTLformatauthorlist\DTLaddperiod
}%
{%
\DTLformateditorlist
\DTLifbibfielddexists{Editor}%
{%
\DTLaddperiod
}%
}%
}%
\DTLifbibfielddexists{Title}%
{%
\DTLstartsentencespace
\DTLformatbooktitle{\DTLbibfield{Title}}%
\DTLcheckbibfielddendsperiod{Title}%
}%
}%
\DTLifbibfielddexists{CrossRef}%
{%

```

## Cross ref field

```
\DTLifbibfieldexists{Title}{\DTLaddperiod}{}%  
\DTLformatbookcrossref  
\DTLifanybibfieldexists{Edition,Month,Year}%  
{\DTLaddcomma}%  
{\DTLaddperiod}%  
}%  
{%
```

## no cross ref field

```
\DTLifbibfieldexists{Title}%  
{%  
  \DTLifbibfieldexists{Volume}{\DTLaddcomma}{\DTLaddperiod}%  
}%  
{}%  
\DTLformatbvvolume  
\DTLformatnumberseries  
\DTLifanybibfieldexists{Number,Series,Volume}{\DTLaddperiod}{}%  
\DTLifbibfieldexists{Publisher}%  
{%  
  \DTLstartsentencespace  
  \DTLbibfield{Publisher}%  
  \DTLcheckbibfieldendsperiod{Publisher}%  
  \DTLifbibfieldexists{Address}%  
  {\DTLaddcomma}%  
  {%  
    \DTLifanybibfieldexists{Month,Year}%  
    {\DTLaddcomma}%  
    {\DTLaddperiod}%  
  }%  
}%  
{%  
  \DTLifbibfieldexists{Address}%  
  {%  
    \DTLstartsentencespace  
    \DTLbibfield{Address}%  
    \DTLcheckbibfieldendsperiod{Address}%  
    \DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{\DTLaddperiod}%  
  }%  
  }%  
}%  
\DTLifbibfieldexists{Edition}%  
{%  
  \protected@edef\@dtl@tmp{\DTLformattedition{\DTLbibfield{Edition}}}%  
  \ifDTLmidsentence  
    \@dtl@tmp  
  \else  
    \DTLstartsentencespace\expandafter\MakeUppercase\@dtl@tmp  
  \fi  
  \expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%  
}
```

```

    \DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{\DTLaddperiod}%
  }%
  {}%
  \DTLformatdate
  \DTLifanybibfieldexists{Year,Month}{\DTLaddperiod}{}%
  \DTLifbibfieldexists{Note}%
  {%
    \DTLstartsencespace
    \DTLbibfield{Note}%
    \DTLcheckbibfieldendsperiod{Note}%
    \DTLaddperiod
  }%
  {}%
}%

```

The format of a booklet.

```

\renewcommand*{\DTLformatbooklet}{%
\DTLifbibfieldexists{Author}{%
\DTLformatauthorlist\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{\DTLstartsencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}{}%
\DTLifbibfieldexists{HowPublished}{%
\DTLstartsencespace\DTLbibfield{HowPublished}%
\DTLcheckbibfieldendsperiod{HowPublished}%
\DTLifanybibfieldexists{Address,Month,Year}{\DTLaddcomma
}{\DTLaddperiod}}{%
\DTLifbibfieldexists{Address}{\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{\DTLaddperiod}}{%
\DTLformatdate
\DTLifanybibfieldexists{Year,Month}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Note}{\DTLstartsencespace\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{%
}%

```

The format of an 'inbook' entry.

```

\renewcommand*{\DTLformatinbook}{%
\DTLifbibfieldexists{Author}{%
\DTLformatauthorlist\DTLaddperiod}{%
\DTLifbibfieldexists{Editor}{\DTLformateditorlist\DTLaddperiod}}{%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
{\em\DTLbibfield{Title}}%
\DTLcheckbibfieldendsperiod{Title}%
}{}%
\DTLifbibfieldexists{CrossRef}{%

```

```

% Cross ref entry
\DTLifbibfieldexists{Title}{%
\DTLifbibfieldexists{Chapter}{\DTLaddcomma}{\DTLaddperiod}}{}%
\DTLformatchapterpages
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddperiod}}{}%
\DTLformatbookcrossref
}{% no cross ref
\DTLifbibfieldexists{Title}{%
\DTLifanybibfieldexists{Chapter,Volume}{\DTLaddcomma
}{\DTLaddperiod}}{}%
\DTLformatbvvolume
\DTLifanybibfieldexists{Volume,Series}{%
\DTLifanybibfieldexists{Chapter,Pages}{%
\DTLaddcomma}{\DTLaddperiod}}{}%
\DTLformatchapterpages
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddperiod}}{}%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsentencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifbibfieldexists{Address}{\DTLaddcomma}}{}%
\DTLifbibfieldexists{Address}{%
\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}}{}%
}%
\DTLifanybibfieldexists{Edition,Month,Year}{\DTLaddcomma
}{\DTLaddperiod}%
\DTLifbibfieldexists{Edition}{%
\protected@edef\@dtl@tmp{\DTLformattedition{\DTLbibfield{Edition}}}%
\ifDTLmidsentence
\@dtl@tmp
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\@dtl@tmp
\fi
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma
}{\DTLaddperiod}%
}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{}%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{}%
}%

```

The format of an ‘incollection’ entry.

```

\renewcommand*{\DTLformatincollection}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}{}%
\DTLifbibfieldexists{CrossRef}{%
% cross ref entry
\DTLformatincolprocrossref
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddcomma}{}%
\DTLformatchapterpages\DTLaddperiod
}{% no cross ref entry
\DTLformatinedbooktitle
\DTLifbibfieldexists{BookTitle}{%
\DTLifanybibfieldexists{Volume,Series,Chapter,Pages,Number}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatbvvolume
\DTLifbibfieldexists{Volume}{%
\DTLifanybibfieldexists{Number,Series,Chapter,Pages}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatnumberseries
\DTLifanybibfieldexists{Number,Series}{%
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddcomma
}{\DTLaddperiod}}}%
\DTLformatchapterpages
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsentencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifanybibfieldexists{Address,Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Address}{%
\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Edition}{%
\protected@edef\@dtl@tmp{\DTLformatedition{\DTLbibfield{Edition}}}%
\ifDTLmidsentence
\@dtl@tmp
\else
\DTLstartsentencespace
\expandafter\MakeUppercase\@dtl@tmp
\fi
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma

```

```

} {\DTLaddperiod}%
} {}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year} {\DTLaddperiod} {}%
}%
\DTLifbibfieldexists{Note} {}%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod} {}%
}%

```

The format of an 'inproceedings' entry.

```

\renewcommand*{\DTLformatinproceedings} {}%
\DTLifbibfieldexists{Author} {\DTLformatauthorlist
\DTLaddperiod} {}%
\DTLifbibfieldexists{Title} {}%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod} {}%
\DTLifbibfieldexists{CrossRef} {}%
% cross ref entry
\DTLformatincollproccrossref
\DTLifbibfieldexists{Pages} {\DTLaddcomma} {}%
\DTLaddperiod}%
\DTLformatpages
\DTLifbibfieldexists{Pages} {\DTLaddperiod} {}%
} {}% no cross ref
\DTLformatinedbooktitle
\DTLifbibfieldexists{BookTitle} {}%
\DTLifanybibfieldexists{Volume, Series, Pages, Number, Address, %
Month, Year} {}%
\DTLaddcomma} {\DTLaddperiod} {} {}%
\DTLformatbvvolume
\DTLifbibfieldexists{Volume} {}%
\DTLifanybibfieldexists{Number, Series, Pages, Address, Month, Year} {}%
\DTLaddcomma} {\DTLaddperiod} {} {}%
\DTLformatnumberseries
\DTLifanybibfieldexists{Number, Series} {}%
\DTLifanybibfieldexists{Pages, Address, Month, Year} {}%
\DTLaddcomma} {\DTLaddperiod} {} {}%
\DTLformatpages
\DTLifbibfieldexists{Pages} {}%
\DTLifanybibfieldexists{Address, Month, Year} {}%
\DTLaddcomma} {\DTLaddperiod} {} {}%
\DTLifbibfieldexists{Address} {}%
\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%

```

```

\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Organization}{%
\DTLstartsentencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifbibfieldexists{Publisher}{\DTLaddcomma}{%
\DTLaddperiod}}{}%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsentencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLaddperiod}{}%
}%
\DTLifanybibfieldexists{Publisher,Organization}{%
\DTLaddperiod}{}%
\DTLifbibfieldexists{Organization}{%
\DTLstartsentencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifanybibfieldexists{Publisher,Month,Year}{%
\DTLaddcomma}}{}}{}%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsentencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}}{}}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}{}%
}%
}%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}{}%
}%

```

The format of a manual.

```

\renewcommand*{\DTLformatmanual}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist
\DTLaddperiod}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsentencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifbibfieldexists{Address}{\DTLaddcomma \DTLbibfield{Address}%

```

```

\DTLcheckbibfielddendsperiod{Address}%
}{}%
\DTLaddperiod}{}%
}%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
{\em\DTLbibfield{Title}}%
\DTLcheckbibfielddendsperiod{Title}%
\DTLifbibfieldexists{Author}{%
\DTLifanybibfieldexists{Organization,Address}{%
\DTLaddperiod}{\DTLaddcomma}}{%
\DTLifanybibfieldexists{Organization,Address,Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{}%
\DTLifbibfieldexists{Author}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfielddendsperiod{Organization}%
\DTLifanybibfieldexists{Address,Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{}%
\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfielddendsperiod{Address}%
\DTLifanybibfieldexists{Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{%
}{%
\DTLifbibfieldexists{Organization}{}{%
\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfielddendsperiod{Address}%
\DTLifanybibfieldexists{Edition,Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}}}{%
}%
\DTLifbibfieldexists{Edition}{%
\protected@edef\@dtl@tmp{\DTLformattedition{\DTLbibfield{Edition}}}%
\ifDTLmidsentence
\@dtl@tmp
\else
\DTLstartsencespace
\expandafter\MakeUppercase\@dtl@tmp
\fi
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}}}{%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}{%
\DTLifbibfieldexists{Note}{%

```



```

\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}{}%
}%

```

The format of a master's thesis.

```

\renewcommand*{\DTLformatmastersthesis}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}{}%
\DTLifbibfieldexists{Type}{%
\DTLstartsentencespace
\DTLbibfield{Type}%
\DTLcheckbibfieldendsperiod{Type}%
\DTLifanybibfieldexists{School,Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLifbibfieldexists{School}{%
\DTLstartsentencespace
\DTLbibfield{School}%
\DTLcheckbibfieldendsperiod{School}%
\DTLifanybibfieldexists{Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Address}{%
\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}{}%
}%

```

The format of a miscellaneous entry.

```

\renewcommand*{\DTLformatmisc}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLifbibfieldexists{HowPublished}{\DTLaddperiod}{%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%

```

```

\DTLaddperiod}%
}%
\DTLmidsentencefalse}{}%
\DTLifbibfieldexists{HowPublished}{%
\DTLstartsentencespace
\DTLbibfield{HowPublished}%
\DTLcheckbibfieldendsperiod{HowPublished}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}}}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}{}%
}%

```

The format of a PhD thesis.

```

\renewcommand*{\DTLformatphdthesis}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}}}{%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace
{\em\DTLbibfield{Title}}}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}}{%
\DTLifbibfieldexists{Type}{%
\DTLstartsentencespace
\DTLbibfield{Type}%
\DTLcheckbibfieldendsperiod{Type}%
\DTLifanybibfieldexists{School,Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{}%
\DTLifbibfieldexists{School}{%
\DTLstartsentencespace
\DTLbibfield{School}%
\DTLcheckbibfieldendsperiod{School}%
\DTLifanybibfieldexists{Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{}%
\DTLifbibfieldexists{Address}{%
\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%

```

```
\DTLaddperiod}{}%  
}%
```

The format of a proceedings.

```
\renewcommand*{\DTLformatproceedings}{%  
\DTLifbibfieldexists{Editor}{%  
\DTLformatteditorlist\DTLaddperiod}{%  
\DTLifbibfieldexists{Organization}{%  
\DTLstartsencespace  
\DTLbibfield{Organization}%  
\DTLcheckbibfieldendsperiod{Organization}%  
\DTLaddperiod}{}}%  
\DTLifbibfieldexists{Title}{%  
\DTLstartsencespace  
{\em\DTLbibfield{Title}}%  
\DTLcheckbibfieldendsperiod{Title}%  
\DTLifanybibfieldexists{Volume,Number,Address,Editor,Publisher,%  
Month,Year}{\DTLaddcomma}{\DTLaddperiod}}%  
}%}%  
\DTLformatbvvolume  
\DTLifbibfieldexists{Volume}{%  
\DTLifanybibfieldexists{Number,Address,Editor,Publisher,%  
Month,Year}{\DTLaddcomma}{\DTLaddperiod}}}%  
\DTLformatnumberseries  
\DTLifbibfieldexists{Number}{%  
\DTLifanybibfieldexists{Address,Editor,Publisher,%  
Month,Year}{\DTLaddcomma}{\DTLaddperiod}}}%  
\DTLifbibfieldexists{Address}{%  
\DTLstartsencespace  
\DTLbibfield{Address}%  
\DTLcheckbibfieldendsperiod{Address}%  
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{\DTLaddperiod}}%  
\DTLformatdate  
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}}%  
\DTLifbibfieldexists{Editor}{\DTLifbibfieldexists{Organization}{%  
\DTLstartsencespace  
\DTLbibfield{Organization}%  
\DTLcheckbibfieldendsperiod{Organization}%  
\DTLifbibfieldexists{Publisher}{%  
\DTLaddcomma}{\DTLaddperiod}}}}}%  
\DTLifbibfieldexists{Publisher}{%  
\DTLstartsencespace  
\DTLbibfield{Publisher}%  
\DTLcheckbibfieldendsperiod{Publisher}%  
\DTLaddperiod  
}%}%  
}{% no address  
\DTLifbibfieldexists{Editor}{%  
\DTLifbibfieldexists{Organization}{%  
\DTLstartsencespace
```

```

\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifanybibfieldexists{Publisher,Month,Year}{%
\DTLaddcomma}\DTLaddperiod}}{%
}%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsentencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}\DTLaddperiod}}{%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{%
}%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{%
}%

```

The format of a technical report.

```

\renewcommand*{\DTLformattechreport}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}}{%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}{%
\DTLifbibfieldexists{Type}{%
\DTLstartsentencespace
\DTLbibfield{Type}%
\DTLcheckbibfieldendsperiod{Type}%
\DTLifbibfieldexists{Number}{~}}}{%
\DTLifbibfieldexists{Number}{%
\DTLstartsentencespace
\DTLbibfield{Number}%
\DTLcheckbibfieldendsperiod{Number}%
}}{%
\DTLifanybibfieldexists{Type,Number}{%
\DTLifanybibfieldexists{Institution,Address,Month,Year}{\DTLaddcomma
}\DTLaddperiod}}{%
\DTLifbibfieldexists{Institution}{%
\DTLstartsentencespace
\DTLbibfield{Institution}%
\DTLcheckbibfieldendsperiod{Institution}%
\DTLifanybibfieldexists{Address,Month,Year}{\DTLaddcomma
}\DTLaddperiod}}{%
\DTLifbibfieldexists{Address}{%
\DTLstartsentencespace
\DTLbibfield{Address}%

```

```

\DTLcheckbibfielddendsperiod{Address}%
\DTLifanybibfielddexists{Month,Year}{\DTLaddcomma
}\DTLaddperiod}}{}%
\DTLformatdate
\DTLifanybibfielddexists{Month,Year}{\DTLaddperiod}}{}%
\DTLifbibfielddexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfielddendsperiod{Note}%
\DTLaddperiod}}{}%
}%

```

The format of an unpublished work.

```

\renewcommand*{\DTLformatunpublished}{%
\DTLifbibfielddexists{Author}{\DTLformatauthorlist\DTLaddperiod}}{}%
\DTLifbibfielddexists{Title}{%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfielddendsperiod{Title}%
\DTLaddperiod}}{}%
\DTLifbibfielddexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfielddendsperiod{Note}%
\DTLifanybibfielddexists{Month,Year}{\DTLaddcomma}\DTLaddperiod}}{}%
\DTLformatdate
\DTLifanybibfielddexists{Month,Year}{\DTLaddperiod}}{}%
}%

```

End of 'plain' style.

```
}

```

formatbooktitle

```
\newcommand*{\DTLformatbooktitle}[1]{\emph{#1}}
```

\dtlbst@abbrv Define 'abbrv' style. This is similar to 'plain' except that some of the values are abbreviated

```
\newcommand{\dtlbst@abbrv}{%

```

Base this style on 'plain':

```
\dtlbst@plain

```

Sets the author name format.

```

\renewcommand*{\DTLformatauthor}[4]{%
\DTLformatabbrvforenames{##4}
\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}}

```

Sets the editor name format.

```

\renewcommand*{\DTLformateditor}[4]{%
\DTLformatabbrvforenames{##4}

```

```

\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}

```

Sets the monthname format.

```
\let\DTLmonthname\dtl@abbrvmonthname
```

Sets other predefined names:

```

\renewcommand*\DTLacmcs}{ACM Comput.\ Surv.}
\renewcommand*\DTLacta}{Acta Inf.}
\renewcommand*\DTLcacm}{Commun.\ ACM}
\renewcommand*\DTLibmjrd}{IBM J.\ Res.\ Dev.}
\renewcommand*\DTLibmsj}{IBM Syst.~J.}
\renewcommand*\DTLieceese}{IEEE Trans. Softw.\ Eng.}
\renewcommand*\DTLieceetc}{IEEE Trans.\ Comput.}
\renewcommand*\DTLieceetcad}{IEEE Trans.\ Comput.-Aided Design
Integrated Circuits}
\renewcommand*\DTLipl}{Inf.\ Process.\ Lett.}
\renewcommand*\DTLjacm}{J.~ACM}
\renewcommand*\DTLjcscs}{J.~Comput.\ Syst.\ Sci.}
\renewcommand*\DTLscps}{Sci.\ Comput.\ Programming}
\renewcommand*\DTLsicomp}{SIAM J.~Comput.}
\renewcommand*\DTLtocs}{ACM Trans.\ Comput.\ Syst.}
\renewcommand*\DTLtods}{ACM Trans.\ Database Syst.}
\renewcommand*\DTLtog}{ACM Trans.\ Gr.}
\renewcommand*\DTLtoms}{ACM Trans.\ Math. Softw.}
\renewcommand*\DTLtoois}{ACM Trans. Office Inf.\ Syst.}
\renewcommand*\DTLtoplas}{ACM Trans.\ Prog. Lang.\ Syst.}
\renewcommand*\DTLtcs}{Theoretical Comput.\ Sci.}

```

End of ‘abbrv’ style.

```
}
```

`\dtlbst@alpha` Define ‘alpha’ style. This is similar to ‘plain’ except that the labels are strings rather than numerical.

```
\newcommand{\dtlbst@alpha}{%
```

Base this style on ‘plain’:

```
\dtlbst@plain
```

Set how to format the entire bibliography:

```

\renewenvironment{DTLthebibliography}[2][\boolean{true}]{%
\dtl@createalphabiblabeles{##1}{##2}%
\begin{thebibliography}{\@dtl@widestlabel}%
}{\end{thebibliography}}%

```

Set how to start the bibliography entry:

```

\renewcommand*\DTLbibitem}{%
\expandafter\bibitem\expandafter
[\csname dtl@biblabel@DBIBCitekey\endcsname]{\DBIBCitekey}}%
\renewcommand*\DTLmbibitem}[1]{%

```

```

\expandafter\bibitem\expandafter
[\csname dtl@biblabel@<DBIBcitekey>\endcsname]{##1@<DBIBcitekey>}}%

```

End of 'alpha' style.

```

}

```

tealphabiblabels

```

\dtl@createalphabiblabels{<condition>}{<db name>}

```

Constructs the alpha style bib labels for the given database. (Labels are stored in the control sequence \dtl@biblabel@<citekey>.) This also sets \dtl@widestlabel to the widest label.

```

\newcommand*{\dtl@createalphabiblabels}[2]{%
\dtl@message{Creating bib labels}%
\begingroup
\gdef\@dtl@widestlabel{}%
\dtl@widest=0pt\relax
\DTLforeachbibentry[#1]{#2}{%
\dtl@message{\DBIBcitekey}%
\DTLifbibfieldexists{Author}{%
\dtl@listgetalphalabel{\@dtl@thislabel}{\@dtl@key@Author}%
}%
\DTLifbibfieldexists{Editor}{%
\dtl@listgetalphalabel{\@dtl@thislabel}{\@dtl@key@Editor}%
}%
\DTLifbibfieldexists{Key}{%
\expandafter\dtl@get@firstthree\expandafter
{\@dtl@key@Key}{\@dtl@thislabel}%
}%
\DTLifbibfieldexists{Organization}{%
\expandafter\dtl@get@firstthree\expandafter
{\@dtl@key@Organization}{\@dtl@thislabel}%
}%
\expandafter\dtl@get@firstthree\expandafter
{\DBIBentrytype}{\@dtl@thislabel}%
}%
}}%
\DTLifbibfieldexists{Year}{}{\DTLifbibfieldexists{CrossRef}{%
\DTLgetvalueforkey{\@dtl@key@Year}{Year}{#2}{CiteKey}{%
\@dtl@key@CrossRef}}{}}%
\DTLifbibfieldexists{Year}{%
\expandafter\dtl@get@yearsuffix\expandafter{\@dtl@key@Year}%
\expandafter\toks@\expandafter{\@dtl@thislabel}%
\expandafter\@dtl@toks\expandafter{\@dtl@year}%
\edef\@dtl@thislabel{\the\toks@\the\@dtl@toks}%
}%
\let\@dtl@s@thislabel=\@dtl@thislabel
\@onelevel@sanitize\@dtl@s@thislabel
\@ifundefined{c@biblabel@\@dtl@s@thislabel}{%

```

```

\newcounter{biblabel@\@dtl@s@thislabel}%
\setcounter{biblabel@\@dtl@s@thislabel}{1}%
\expandafter\edef\csname @dtl@bibfirst@\@dtl@s@thislabel\endcsname{%
\DBIBCitekey}%
\expandafter\global
\expandafter\let\csname dtl@biblabel@\DBIBCitekey\endcsname=
\@dtl@thislabel
}%
\expandafter\ifnum\csname c@biblabel@\@dtl@s@thislabel\endcsname=1\relax
\expandafter\let\expandafter\@dtl@tmp
\csname @dtl@bibfirst@\@dtl@s@thislabel\endcsname
\expandafter\protected@xdef\csname dtl@biblabel@\@dtl@tmp\endcsname{%
\@dtl@thislabel a}%
\fi
\stepcounter{biblabel@\@dtl@s@thislabel}%
\expandafter\protected@xdef\csname dtl@biblabel@\DBIBCitekey\endcsname{%
\@dtl@thislabel\alph{biblabel@\@dtl@s@thislabel}}%
}%
\settowidth{\@dtl@tmplength}{%
\csname dtl@biblabel@\DBIBCitekey\endcsname}%
\ifdim\@dtl@tmplength>\@dtl@widest
\@dtl@widest=\@dtl@tmplength
\expandafter\global\expandafter\let\expandafter\@dtl@widestlabel
\expandafter=\csname dtl@biblabel@\DBIBCitekey\endcsname
\fi
}%
\endgroup
}

```

stgetalphalabel Determine the alpha style label from a list of authors/editors (the first argument must be a control sequence (in which the label is stored), the second argument must be the list of names.)

```

\newcommand*{\@dtl@listgetalphalabel}[2]{%
\@dtl@authorcount=0\relax
\@for\@dtl@author:=#2\do{%
\advance\@dtl@authorcount by 1\relax}%
\ifnum\@dtl@authorcount=1\relax
\expandafter\@dtl@getsinglealphalabel#2{#1}\relax
\else
{%
\edef#1{%
\@dtl@tmpcount=0\relax
\def\DTLafterinitials{ }\def\DTLbetweeninitials{ }%
\def\DTLafterinitialbeforehyphen{ }\def\DTLinitialhyphen{ }%
\@for\@dtl@author:=#2\do{%
\expandafter\@dtl@getauthorinitial\@dtl@author
\expandafter\toks@\expandafter{\@dtl@tmp}%
\expandafter\@dtl@toks\expandafter{#1}%
\edef#1{\the\@dtl@toks\the\toks@}%

```





```

\def\@dtl@year{}%
\let\@dtl@donext=\relax
\else
\ifx\@dtl@argii\@nnil
\dtl@ifsingle{#1}{%
\def\@dtl@year{#1}%
\let\@dtl@donext=\relax
}%
\def\@dtl@donext{\dtl@getyearsuffix#1#2#3}%
}%
\else
\ifx\@dtl@argiii\@nnil
\dtl@ifsingle{#1}{%
\dtl@ifsingle{#2}{%
\def\@dtl@year{#1#2}%
\let\@dtl@donext=\relax
}%
\def\@dtl@donext{\dtl@getyearsuffix#2#3}%
}%
}%
\def\@dtl@donext{\dtl@getyearsuffix#2#3}%
}%
\else
\def\@dtl@donext{\dtl@getyearsuffix{#2}{#3}}%
\fi
\fi
\fi
\@dtl@donext
}

```

bibliographystyle `\DTLbibliographystyle{<style>}`

Sets the bibliography style.

```

\newcommand*\DTLbibliographystyle}[1]{%
\@ifundefined{dtlbst@#1}{\PackageError{datbib}{Unknown
bibliography style ‘#1’}{}}{\csname dtlbst@#1\endcsname}}

```

Set the default bibliography style:

```

\DTLbibliographystyle{\dtlbib@style}

```

## 6.8 Multiple Bibliographies

In order to have multiple bibliographies, there needs to be an aux file for each bibliography. The main bibliography is in `\jobname.aux`, but need to provide a means of creating additional aux files.

\DTLmultibibs

```
\DTLmultibibs{<list>}
```

This creates an auxiliary file for each name in *<list>*. For example, `\DTLmultibibs{foo,bar}` will create the files `foo.aux` and `bar.aux`.

```
\newcommand*{\DTLmultibibs}[1]{%
\@for\@dtl@af:=#1\do{%
\@ifundefined{dtl@aux@\@dtl@af}{%
\expandafter\newwrite\csname dtl@aux@\@dtl@af\endcsname
\expandafter\immediate
\expandafter\openout\csname dtl@aux@\@dtl@af\endcsname=\@dtl@af.aux
\expandafter\def\csname b@\@dtl@af @*\endcsname{}}%
}{%
\PackageError{datbib}{Can't create auxiliary file '@@dtl@af.aux',
\expandafter\string\csname dtl@aux@\@dtl@af\endcsname\space
already exists}{}}}
```

Can only be used in the preamble:

```
\@onlypreamble{\DTLmultibibs}
```

\DTLcite

```
\DTLcite[<text>]{<mbib>}{<labels>}
```

This is similar to `\cite[<text>]{<labels>}`, except 1) the cite information is written to the auxiliary file associated with the multi-bib *<mbib>* (which must be named in `\DTLmultibibs`) and 2) the cross referencing label is constructed from *<mbib>* and *<label>* to allow for the same citation to appear in multiple bibliographies.

```
\newcommand*{\DTLcite}{\@ifnextchar[{\@tempwatrue \dtl@citex
}{\@tempwafalse \dtl@citex []}}
```

\dtl@citex

```
\def\dtl@citex[#1]#2#3{%
\leavevmode\let\@citea\@empty
\@cite{\@for\@citeb:=#3\do{\@citea
\def\@citea{\penalty \@m \ }}%
\edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
\if@filesw
\@ifundefined{dtl@aux@#2}{%
\PackageError{datbib}{multibib '#2' not defined}{%
You need to define '#2' in \string\DTLmultibibs}%
}{%
\expandafter\immediate
\expandafter\write\csname dtl@aux@#2\endcsname{%
\string\citation{\@citeb}}%
}%
\fi
```

```

\@ifundefined{b@#2@\@citeb}{%
  \hbox{\reset@font\bfseries ?}%
  \@refundefinedtrue
  \@latex@warning{Citation ‘\@citeb ’ on page \thepage \space
    undefined}%
}%
\@cite@ofmt{\csname b@#2@\@citeb \endcsname }%
}%
}}{#1}%
}

```

`\DTLnocite` `\DTLnocite{<mbib>}{<key list>}`

As `\nocite` but uses the aux file associated with `<mbib>` which must have been defined using `\DTLmultibibs`.

```

\newcommand*\DTLnocite}[2]{%
\@ifundefined{dtl@aux@#1}{%
  \PackageError{datbib}{multibib ‘#1’ not defined}{%
    You need to define ‘#1’ in \string\DTLmutlibibs}%
}%
\@bsphack
\ifx\@onlypreamble\document
  \@for\@citeb:=#2\do{%
    \edef\@citeb{\expandafter\@firstofone\@citeb}%
    \if@filesw
      \expandafter\immediate
      \expandafter\write\csname dtl@aux@#1\endcsname{%
        \string\citation{\@citeb}}%
    \fi
    \@ifundefined{b@#1@\@citeb}{%
      \@refundefinedtrue
      \@latex@warning{Citation ‘\@citeb ’ undefined}}{}%
  }%
\else
  \@latex@error{Cannot be used in preamble}\@eha
\fi
\@esphack
}%
}

```

`\DTLloadmbbl` `\DTLloadmbib{<mbib>}{<db name>}{<bib list>}`

```

\newcommand*\DTLloadmbbl}[3]{%
\@ifundefined{dtl@aux@#1}{%

```

```

\PackageError{datbib}{multibib ‘#1’ not defined}{%
You need to define ‘#1’ in \string\DTLmutlibibs}%
}{%
\if@filesw
\expandafter\immediate\expandafter
\write\csname dtl@aux@#1\endcsname{\string\bibstyle{datbib}}%
\expandafter\immediate\expandafter
\write\csname dtl@aux@#1\endcsname{\string\bibdata{#3}}%
\fi
\DTLnewdb{#2}%
\edef\DTLBIBdbname{#2}%
\@input@{#1.bbl}%
}%
}

```

`\DTLmbibliography[condition]{mbib name}{bib dbname}`

Displays the bibliography for the database *bib dbname* which must have previously been loaded using `\DTLloadmdbl`, where *mbib name* must be listed in `\DTLmultibibs`.

`\DTLmbibliography`

```

\newcommand*{\DTLmbibliography}[3][\boolean{true}]{%
\begin{DTLthebibliography}[#1]{#3}%
\DTLforeachbibentry[#1]{#3}{%
\DTLmbibitem{#2} \DTLformatbibentry \DTLendbibitem
}%
\end{DTLthebibliography}%
}

```

## 7 databar.sty

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{databar}[2018/12/07 v2.31 (NLCT)]
```

Require xkeyval package

```
\RequirePackage{xkeyval}
```

Require dataplot package

```
\RequirePackage{dataplot}
```

`\DTLcolorbarchart` The conditional `\ifDTLcolorbarchart` is used to determine whether to use colour or grey scale.

```
\newif\ifDTLcolorbarchart
\DTLcolorbarcharttrue
```

Package options to change the conditional:

```
\DeclareOption{color}{\DTLcolorbarcharttrue}
\DeclareOption{gray}{\DTLcolorbarchartfalse}
```

`\DTLbarXlabelalign` specifies the alignment for the  $x$  axis labels.

```
\newcommand*\DTLbarXlabelalign{left,rotate=-90}
```

`\DTLbarYticklabelalign` specifies the alignment for the  $y$  axis labels.

```
\newcommand*\DTLbarYticklabelalign{right}
```

`\DTLverticalbars` Define boolean keys to govern bar chart orientation.

```
\define@boolkey{databar}[DTL]{verticalbars}[true]{%
\ifDTLverticalbars
\def\DTLbarXlabelalign{left,rotate=-90}%
\def\DTLbarYticklabelalign{right}
\else
\def\DTLbarXlabelalign{right}%
\def\DTLbarYticklabelalign{center}
\fi}
```

Set defaults:

```
\DTLverticalbarstrue
```

Package options to change `\ifDTLverticalbars`

```
\DeclareOption{vertical}{\DTLverticalbarstrue}
\def\DTLbarXlabelalign{left,rotate=-90}%
\def\DTLbarYticklabelalign{right}
```

```

}
\DeclareOption{horizontal}{\DTLverticalbarsfalse
\def\DTLbarXlabelalign{right}%
\def\DTLbarYticklabelalign{center}
}

```

Process options:

```
\ProcessOptions
```

Required packages:

```
\RequirePackage{datatool}
\RequirePackage{tikz}

```

Define some variables that govern the appearance of the bar chart.

<code>\DTLbarchartlength</code>	The total height of the bar chart is given by <code>\DTLbarchartheight</code> <pre>\newlength\DTLbarchartlength \DTLbarchartlength=3in</pre>
<code>\DTLbarwidth</code>	The width of each bar is given by <code>\DTLbarwidth</code> . <pre>\newlength\DTLbarwidth \DTLbarwidth=1cm</pre>
<code>\DTLbarlabeloffset</code>	The offset from the $x$ axis to the bar label if given by <code>\DTLbarlabeloffset</code> . <pre>\newlength\DTLbarlabeloffset \setlength\DTLbarlabeloffset{10pt}</pre>
<code>\DTLBarXAxisStyle</code>	The style of the $x$ axis is given by <code>\DTLBarXAxisStyle</code> <pre>\newcommand*\DTLBarXAxisStyle{-}</pre>
<code>\DTLBarYAxisStyle</code>	The style of the $y$ axis is given by <code>\DTLBarYAxisStyle</code> . <pre>\newcommand*\DTLBarYAxisStyle{-}</pre>
<code>\DTLbarroundvar</code>	<code>\DTLbarroundvar</code> is a counter governing the number of digits to round to when using <code>\FPround</code> . <pre>\newcounter{DTLbarroundvar} \setcounter{DTLbarroundvar}{1}</pre>
<code>\DTLdisplayYticklabel</code>	<code>\DTLdisplayYticklabel</code> governs how the $y$ tick labels appear. <pre>\newcommand*\DTLdisplayYticklabel}[1]{#1}</pre>
<code>\DTLdisplaylowerbarlabel</code>	<code>\DTLdisplaylowerbarlabel</code> governs how the lower bar labels appear. <pre>\newcommand*\DTLdisplaylowerbarlabel}[1]{#1}</pre>
<code>\DTLdisplaylowermultibarlabel</code>	<code>\DTLdisplaylowermultibarlabel</code> governs how the lower multi bar labels appear. <pre>\newcommand*\DTLdisplaylowermultibarlabel}[1]{#1}</pre>
<code>\DTLdisplayupperbarlabel</code>	<code>\DTLdisplayupperbarlabel</code> governs how the upper bar labels appear. <pre>\newcommand*\DTLdisplayupperbarlabel}[1]{#1}</pre>

`\DTLdisplayuppermultibarlabel` governs how the upper multi bar labels appear.  
`\newcommand*\DTLdisplayuppermultibarlabel}[1]{#1}`

`\DTLbaratbegintikz` specifies any commands to apply at the start of the `tikzpicture` environment. By default it does nothing.  
`\newcommand*\DTLbaratbegintikz}{}`

`\DTLbaratendtikz` specifies any commands to apply at the end of the `tikzpicture` environment. By default it does nothing.  
`\newcommand*\DTLbaratendtikz}{}`

The conditional `\ifDTLbarxaxis` is used to determine whether or not to display the  $x$  axis  
`\newif\ifDTLbarxaxis`

The conditional `\ifDTLbaryaxis` is used to determine whether or not to display the  $y$  axis.  
`\newif\ifDTLbaryaxis`

The conditional `\ifDTLbarytics` to determine whether or not to display the  $y$  tick marks.  
`\newif\ifDTLbarytics`

The count register `\@dtl@barcount` is used to store the current bar index.  
`\newcount\@dtl@barcount`

`\DTLsetbarcolor` `\DTLsetbarcolor{<n>}{<color>}`

Assigns colour name `<color>` to the `<n>`th bar.

```
\newcommand*\DTLsetbarcolor}[2]{%
\expandafter\def\csname dtlbar@segcol\romannumeral#1\endcsname{#2}%
}
```

`\DTLgetbarcolor` `\DTLgetbarcolor{<n>}`

Gets the colour specification for the `<n>`th bar.

```
\newcommand*\DTLgetbarcolor}[1]{%
\csname dtlbar@segcol\romannumeral#1\endcsname}
```

`\DTLdobarcolor` `\DTLdobarcolor{<n>}`

Sets the colour to that for the `<n>`th bar.



```

\newcommand*{\DTLdobarcolor}[1]{%
\expandafter\color\expandafter
{\csname dtlbar@segcol\romannumeral#1\endcsname}}

```

currentbarcolor \DTLdocurrentbarcolor sets the colour to that of the current bar.

```

\newcommand*{\DTLdocurrentbarcolor}{%
\ifnum\dtlforeachlevel=0\relax
\PackageError{databar}{Can't use
\string\DTLdocurrentbarcolor\space outside
\string\DTLbarchart}{}%
\else
\expandafter\DTLdobarcolor\expandafter{%
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname}%
\fi}

```

baroutlinecolor \DTLbaroutlinecolor specifies what colour to draw the outline.

```

\newcommand*{\DTLbaroutlinecolor}{black}

```

baroutlinewidth \DTLbaroutlinewidth specifies the line width of the outline: Outline is only drawn if the linewidth is greater than 0pt.

```

\newlength\DTLbaroutlinewidth
\DTLbaroutlinewidth=0pt

```

Set the default colours. If there are more than eight bars, more colours will need to be defined.

```

\ifDTLcolorbarchart
\DTLsetbarcolor{1}{red}
\DTLsetbarcolor{2}{green}
\DTLsetbarcolor{3}{blue}
\DTLsetbarcolor{4}{yellow}
\DTLsetbarcolor{5}{magenta}
\DTLsetbarcolor{6}{cyan}
\DTLsetbarcolor{7}{orange}
\DTLsetbarcolor{8}{white}
\else
\DTLsetbarcolor{1}{black!15}
\DTLsetbarcolor{2}{black!25}
\DTLsetbarcolor{3}{black!35}
\DTLsetbarcolor{4}{black!45}
\DTLsetbarcolor{5}{black!55}
\DTLsetbarcolor{6}{black!65}
\DTLsetbarcolor{7}{black!75}
\DTLsetbarcolor{8}{black!85}
\fi

```

DTLeverybarhook Code to apply at every bar. The start point of the bar can be accessed via \DTLstartpt, the mid point of the bar can be accessed via \DTLmidpt and the end point of the bar can be accessed via \DTLendpt

```

\newcommand*{\DTLeverybarhook}{}

```

Define keys for `\DTLbarchart` optional argument. Set the maximum value of the  $y$  axis.

```
\define@key{databar}{max}{\def\DTLbarmax{#1}}
```

Set the total length of the bar chart

```
\define@key{databar}{length}{\DTLbarchartlength=#1\relax  
}
```

Set the maximum depth (negative extent)

```
\define@key{databar}{maxdepth}{%  
\ifnum#1>0\relax  
\PackageError{databar}{depth must be zero or negative}{}%  
\else  
\def\DTLnegextent{#1}%  
\fi}
```

Determine which axes should be shown

```
\define@choicekey{databar}{axes}[\var\nr]{both,x,y,none}{%  
\ifcase\nr\relax  
% both  
\DTLbarxaxistrue  
\DTLbaryaxistrue  
\DTLbaryticstrue  
\or  
% x only  
\DTLbarxaxistrue  
\DTLbaryaxisfalse  
\DTLbaryticsfalse  
\or  
% y only  
\DTLbarxaxisfalse  
\DTLbaryaxistrue  
\DTLbaryticstrue  
\or  
% neither  
\DTLbarxaxisfalse  
\DTLbaryaxisfalse  
\DTLbaryticsfalse  
\fi  
}
```

Variable used to create the bar chart. (Must be a control sequence.)

```
\define@key{databar}{variable}{%  
\def\DTLbarvariable{#1}%  
}
```

Variables used to create the multi bar chart. (Must be a comma separated list of control sequences.)

```
\define@key{databar}{variables}{%  
\def\dtlbar@variables{#1}%  
}
```

Bar width

```
\define@key{databar}{barwidth}{\setlength{\DTLbarwidth}{#1}}
```

Lower bar labels

```
\define@key{databar}{barlabel}{%
```

```
\def\dtl@barlabel{#1}}
```

```
\def\dtl@barlabel{}}
```

Lower bar labels for multi-bar charts

```
\define@key{databar}{multibarlabels}{%
```

```
\def\dtl@multibarlabels{#1}}
```

```
\def\dtl@multibarlabels{}}
```

Gap between groups in multi-bar charts (This should be in  $x$  units where 1  $x$  unit is the width of a bar.)

```
\define@key{databar}{groupgap}{\def\dtlbar@groupgap{#1}}
```

```
\def\dtlbar@groupgap{1}}
```

Upper bar labels

```
\define@key{databar}{upperbarlabel}{%
```

```
\def\dtl@upperbarlabel{#1}}
```

```
\def\dtl@upperbarlabel{}}
```

Upper bar labels for multi-bar charts

```
\define@key{databar}{uppermultibarlabels}{%
```

```
\def\dtl@uppermultibarlabels{#1}}
```

```
\def\dtl@uppermultibarlabels{}}
```

Define list of points for  $y$  tics. (Must be a comma separated list of decimal numbers.)

```
\define@key{databar}{yticpoints}{%
```

```
\def\dtlbar@yticlist{#1}\DTLbaryticstrue\DTLbaryaxistrue}
```

```
\let\dtlbar@yticlist=\relax
```

Set the  $y$  tick gap:

```
\define@key{databar}{yticgap}{%
```

```
\def\dtlbar@yticgap{#1}\DTLbaryticstrue\DTLbaryaxistrue}
```

```
\let\dtlbar@yticgap=\relax
```

Define list of labels for  $y$  tics.

```
\define@key{databar}{yticlabels}{%
```

```
\def\dtlbar@yticlabels{#1}\DTLbaryticstrue\DTLbaryaxistrue}
```

```
\let\dtlbar@yticlabels=\relax
```

Define  $y$  axis label.

```
\define@key{databar}{ylabel}{%
```

```
\def\dtlbar@ylabel{#1}}
```

```
\let\dtlbar@ylabel=\relax
```

```
\DTLbarchart \DTLbarchart [<conditions>]{<option list>}{<db name>}{<assign list>}
```

Make a bar chart from data given in data base  $\langle db\ name\rangle$ , where  $\langle assign\ list\rangle$  is a comma-separated list of  $\langle cmd\rangle=\langle key\rangle$  pairs.  $\langle option\ list\rangle$  must include  $variable=\langle cmd\rangle$ , where  $\langle cmd\rangle$  is included in  $\langle assign\ list\rangle$ . The optional argument  $\langle conditions\rangle$  is the same as that for `\DTLforeach`.

```
\newcommand*{\DTLbarchart}[4][\boolean{true}]%
{%
  \undef\DTLbarvariable
  \undef\DTLbarmax
  \undef\DTLnegextent
  \disable@keys{databar}{variables,multibarlabels,%
    uppermultibarlabels,groupgap}%
  \setkeys{databar}{#2}%
  \ifundef{\DTLbarvariable}%
  {%
    \PackageError{databar}%
    {\string\DTLbarchart\space missing variable}%
    {You haven't use the "variable" key}%
  }%
  {%
```

Compute the maximum bar height, unless `\DTLbarmax` has been set.

```
\ifundef{\DTLbarmax}%
{%
  \@sDTLforeach[#1]{#3}{#4}{%
    \expandafter\DTLconverttodecimal\expandafter
    {\DTLbarvariable}{\dtl@barvar}%
    \ifundef{\DTLbarmax}%
    {%
      \let\DTLbarmax=\dtl@barvar
    }%
    {%
      \let\dtl@old=\DTLbarmax
      \dtlmax{\DTLbarmax}{\dtl@old}{\dtl@barvar}%
    }%
  }%
  \ifx\dtlbar@yticgap\relax
  \else
    \let\dtl@thistick=\dtlbar@yticgap
    \whiledo{\DTLisFPopenbetween{\dtl@thistick}{0}{\DTLbarmax}}%
    {%
      \dtladd{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
    }%
    \let\DTLbarmax=\dtl@thistick
  \fi
}%
{}
```

Compute the bar depth, unless `\DTLnegextent` has been set.

```
\ifundef{\DTLnegextent}%
{%
```

```

\def\DTLnegextent{0}%
\@sDTLforeach[#1]{#3}{#4}{%
  \expandafter\DTLconverttodecimal\expandafter
    {\DTLbarvariable}{\dtl@barvar}%
  \let\dtl@old=\DTLnegextent
  \DTLmin{\DTLnegextent}{\dtl@old}{\dtl@barvar}%
}%
\ifx\dtlbar@yticgap\relax
\else
  \ifthenelse{\DTLisFPgt{\DTLnegextent}{0}}{%
    {%
      \edef\dtl@thistick{0}%
      \whiledo{\DTLisFPclosedbetween{\dtl@thistick}{\DTLnegextent}{0}}{%
        \dtlsub{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
      }%
      \let\DTLnegextent=\dtl@thistick
    }{%
  \fi
}%
{}%

```

Determine scaling factor

```

\@dtl@tmpcount=\DTLbarchartlength
\dtlsub{\dtl@extent}{\DTLbarmax}{\DTLnegextent}%
\dtldiv{\dtl@unit}{\number\@dtl@tmpcount}{\dtl@extent}%

```

Construct y tick list if required

```

\setlength{\dtl@yticlabelwidth}{0pt}%
\ifDTLbarytics
  \ifx\dtlbar@yticlist\relax
    \ifx\dtlbar@yticgap\relax
      \@dtl@tmpcount=\DTLmintickgap
      \divide\@dtl@tmpcount by 65536\relax
      \dtldiv{\dtl@mingap}{\number\@dtl@tmpcount}{\dtl@unit}%
      \dtl@constructticklist\DTLnegextent\DTLbarmax
        \dtl@mingap\dtlbar@yticlist
    \else
      \dtl@constructticklistwithgapz
        \DTLnegextent\DTLbarmax\dtlbar@yticlist\dtlbar@yticgap
    \fi
  \fi
\ifx\dtlbar@ylabel\relax
\else
  \ifx\dtlbar@yticlabels\relax
    \@for\dtl@thislabel:=\dtlbar@yticlist\do{%
      \dtlround{\dtl@thislabel}{\dtl@thislabel}
        {\c@DTLbarroundvar}%
    \ifDTLverticalbars
      \settowidth{\dtl@tmplength}{%
        \DTLbardisplayYticklabel{\dtl@thislabel}}%
    \fi
  \fi
\fi

```

```

\else
  \settoheight{\dtl@tmplength}{%
    \DTLbardisplayYticklabel{\dtl@thislabel}}%
  \edef\@dtl@h{\the\dtl@tmplength}%
  \settodepth{\dtl@tmplength}{%
    \DTLbardisplayYticklabel{\dtl@thislabel}}%
  \addtolength{\dtl@tmplength}{\@dtl@h}%
  \addtolength{\dtl@tmplength}{\baselineskip}%
\fi
\ifdim\dtl@tmplength>\dtl@yticlabelwidth
  \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
\fi
}%
\else
\@for\dtl@thislabel:=\dtlbar@yticlabels\do{%
  \ifDTLverticalbars
    \settowidth{\dtl@tmplength}{%
      \DTLbardisplayYticklabel{\dtl@thislabel}}%
  \else
    \settoheight{\dtl@tmplength}{%
      \DTLbardisplayYticklabel{\dtl@thislabel}}%
    \edef\@dtl@h{\the\dtl@tmplength}%
    \settodepth{\dtl@tmplength}{%
      \DTLbardisplayYticklabel{\dtl@thislabel}}%
    \addtolength{\dtl@tmplength}{\@dtl@h}%
    \addtolength{\dtl@tmplength}{\baselineskip}%
  \fi
  \ifdim\dtl@tmplength>\dtl@yticlabelwidth
    \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
  \fi
}%
\fi
\fi
\fi

```

Store the width of the bar chart in `\DTLbarchartwidth`

```
\edef\DTLbarchartwidth{\expandafter\number\csname dtlrows@#3\endcsname}
```

Do the bar chart

```
\begin{tikzpicture}
```

Set unit vectors

```

\ifDTLverticalbars
  \pgfsetyvec{\pgfpoint{0pt}{\dtl@unit sp}}%
  \pgfsetxvec{\pgfpoint{\DTLbarwidth}{0pt}}%
\else
  \pgfsetxvec{\pgfpoint{\dtl@unit sp}{0pt}}%
  \pgfsetyvec{\pgfpoint{0pt}{\DTLbarwidth}}%
\fi

```

Begin hook

```

\DTLbaratbegintikz
Initialise
\def\@dtl@start{0}%
Iterate through data
\@sDTLforeach[#1]{#3}{#4}{%
Store the bar number in \@dtl@bar
\expandafter\let\expandafter\@dtl@bar
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname%
Convert variable to decimal
\expandafter\DTLconverttodecimal\expandafter
{\DTLbarvariable}{\dtl@variable}%
Draw bars
\begin{scope}
\DTLdocurrentbarcolor
\ifDTLverticalbars
\fill (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
-- (\@dtl@bar,\dtl@variable) -- (\@dtl@bar,0) -- cycle;
\else
\fill (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
-- (\dtl@variable,\@dtl@bar) -- (0,\@dtl@bar) -- cycle;
\fi
\end{scope}
Draw outline
\begin{scope}
\ifdim\DTLbaroutlinewidth>0pt
\expandafter\color\expandafter{\DTLbaroutlinecolor}
\ifDTLverticalbars
\draw (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
-- (\@dtl@bar,\dtl@variable) -- (\@dtl@bar,0) -- cycle;
\else
\draw (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
-- (\dtl@variable,\@dtl@bar) -- (0,\@dtl@bar) -- cycle;
\fi
\fi
\end{scope}
Draw lower  $x$  labels
\ifDTLverticalbars
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\@dtl@start.5}{0}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLbarlabeloffset}}},
\DTLbarXlabelalign
}%
Set \DTLstartpt to the starting point.

```

```

\edef\DTLstartpt{\noexpand\pgfpointxy{\@dtl@start.5}{0}}%
\else
\edef\dtl@textopt{%
  at={\noexpand\pgfpointadd
    {\noexpand\pgfpointxy{0}{\@dtl@start.5}}
    {\noexpand\pgfpoint{-\noexpand\DTLbarlabeloffset}{0pt}}},
  \DTLbarXlabelalign
}%
Set \DTLstartpt to the starting point.
\edef\DTLstartpt{\noexpand\pgfpointxy{0}{\@dtl@start.5}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
  \DTLdisplaylowerbarlabel{\dtl@barlabel}}
Draw upper x labels
\ifDTLverticalbars
Vertical bars
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}%
{
\edef\dtl@textopt{%
  at={\noexpand\pgfpointadd
    {\noexpand\pgfpointxy{\@dtl@start.5}{\dtl@variable}}
    {\noexpand\pgfpoint{0pt}{-\noexpand\DTLbarlabeloffset}}}
}%
}{%
\edef\dtl@textopt{%
  at={\noexpand\pgfpointadd
    {\noexpand\pgfpointxy{\@dtl@start.5}{\dtl@variable}}
    {\noexpand\pgfpoint{0pt}{\noexpand\DTLbarlabeloffset}}}
}%
}
Set \DTLendpt to the end point.
\edef\DTLendpt{\noexpand\pgfpointxy{\@dtl@start.5}{\dtl@variable}}%
\else
Horizontal bars
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}%
{
\edef\dtl@textopt{right,
  at={\noexpand\pgfpointadd
    {\noexpand\pgfpointxy{\dtl@variable}{\@dtl@start.5}}
    {\noexpand\pgfpoint{-\noexpand\DTLbarlabeloffset}{0pt}}}
}%
}{%
\edef\dtl@textopt{left,
  at={\noexpand\pgfpointadd
    {\noexpand\pgfpointxy{\dtl@variable}{\@dtl@start.5}}
    {\noexpand\pgfpoint{\noexpand\DTLbarlabeloffset}{0pt}}}
}%
}

```



```

    }%
  }
Set \DTLendpt to the end point.
  \edef\DTLendpt{\noexpand\pgfpointxy{\dtl@variable}{\@dtl@start.5}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
  \DTLdisplayupperbarlabel{\dtl@upperbarlabel}}
Set the mid point
  \def\DTLmidpt{\pgfpointlineattime{0.5}{\DTLstartpt}{\DTLendpt}}%
Do every bar hook
  \DTLeverybarhook
End of loop
  \edef\@dtl@start{\number\@dtl@bar}%
}%
Draw x axis
  \ifDTLbarxaxis
  \ifDTLverticalbars
    \expandafter\draw\expandafter[\DTLBarXAxisStyle]
      (0,0) -- (\DTLbarchartwidth,0);
  \else
    \expandafter\draw\expandafter[\DTLBarXAxisStyle]
      (0,0) -- (0,\DTLbarchartwidth);
  \fi
\fi
Draw y axis
  \ifDTLbaryaxis
  \ifDTLverticalbars
    \expandafter\draw\expandafter[\DTLBarYAxisStyle]
      (0,\DTLnegextent) -- (0,\DTLbarmax);
  \else
    \expandafter\draw\expandafter[\DTLBarYAxisStyle]
      (\DTLnegextent,0) -- (\DTLbarmax,0);
  \fi
\fi
Plot y tick marks if required
\ifx\dtlbar@yticlist\relax
\else
  \@for\dtl@thistick:=\dtlbar@yticlist\do{%
    \ifDTLverticalbars
      \pgfpathmoveto{\pgfpointxy{0}{\dtl@thistick}}
      \pgfpathlineto{
        \pgfpointadd{\pgfpointxy{0}{\dtl@thistick}}
          {\pgfpoint{-\DTLticklength}{0pt}}}
    \else
      \pgfpathmoveto{\pgfpointxy{\dtl@thistick}{0}}

```

```

\pgfpathlineto{
  \pgfpointadd{\pgfpointxy{\dtl@thistick}{0}}
    {\pgfpoint{0pt}{-\DTLticklength}}}
\fi
\pgfusepath{stroke}
\ifx\dtlbar@yticlabels\relax
  \dtlround{\dtl@thislabel}{\dtl@thistick}
    {\c@DTLbarroundvar}%
\else
  \dtl@chopfirst\dtlbar@yticlabels\dtl@thislabel\dtl@rest
  \let\dtlbar@yticlabels=\dtl@rest
\fi
\ifDTLverticalbars
  \edef\dtl@textopt{\DTLbarYticklabelalign,%
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{0}{\dtl@thistick}}
      {\noexpand\pgfpoint{-\noexpand\DTLticklabeloffset}{0pt}},
    }}%
\else
  \edef\dtl@textopt{\DTLbarYticklabelalign,
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{\dtl@thistick}{0}}
      {\noexpand\pgfpoint{0pt}{-\noexpand\DTLticklabeloffset}}}
    }}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
  \DTLbardisplayYticklabel{\dtl@thislabel}}
}%
\fi
Plot the y label if required
\ifx\dtlbar@ylabel\relax
\else
\addtolength{\dtl@yticlabelwidth}{\baselineskip}%
\setlength{\dtl@tmplength}{0.5\DTLbarchartlength}
\ifDTLverticalbars
  \pgftext[bottom,center,at={\pgfpointadd
    {\pgfpointxy{0}{\DTLnegextent}}%
    {\pgfpoint{-\dtl@yticlabelwidth}{\dtl@tmplength}}},
    rotate=90]{%
    \dtlbar@ylabel}
\else
  \pgftext[bottom,center,at={\pgfpointadd
    {\pgfpointxy{\DTLnegextent}{0}}%
    {\pgfpoint{\dtl@tmplength}{-\dtl@yticlabelwidth}}}] {%
    \dtlbar@ylabel}
\fi
\fi
Finish bar chart

```

```

\DTLbaratendtikz
\end{tikzpicture}
}%
}%
}

```

DTLmultibarchart

```
\DTLmultibarchart[<conditions>]{<option list>}{<db name>}{<assign list>}
```

Make a multi-bar chart from data given in data base *<db name>*, where *<assign list>* is a comma-separated list of *<cmd>=<key>* pairs. *<option list>* must include the variables key which must be a comma separated list of commands, where each command is included in *<assign list>*. The optional argument *<conditions>* is the same as that for `\DTLforeach`.

```

\newcommand*{\DTLmultibarchart}[4][\boolean{true}]{%
{\let\dtlbar@variables=\relax
\let\DTLbarmax=\relax
\let\DTLnegextent=\relax
\disable@keys{databar}{variable,upperbarlabel}%
\setkeys{databar}{#2}%
\ifx\dtlbar@variables\relax
\PackageError{databar}{\string\DTLmultibarchart\space missing variables setting}{}%
\else

```

Compute the maximum bar height, unless `\DTLbarmax` has been set.

```

\ifx\DTLbarmax\relax
\@sDTLforeach[#1]{#3}{#4}{%
\@for\DTLbarvariable:=\dtlbar@variables\do{%
\expandafter\DTLconverttodecimal\expandafter
{\DTLbarvariable}{\dtl@barvar}%
\ifx\DTLbarmax\relax
\let\DTLbarmax=\dtl@barvar
\else
\let\dtl@old=\DTLbarmax
\dtlmax{\DTLbarmax}{\dtl@old}{\dtl@barvar}%
\fi
}%
}%
\ifx\dtlbar@yticgap\relax
\else
\let\dtl@thistick=\dtlbar@yticgap%
\whiledo{\DTLisFPopenbetween{\dtl@thistick}{0}{\DTLbarmax}}{%
\dtladd{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
}%
\let\DTLbarmax=\dtl@thistick
\fi
\fi

```

Compute the bar depth, unless `\DTLnegextent` has been set.

```

\ifx\DTLnegextent\relax
  \def\DTLnegextent{0}%
  \@sDTLforeach[#1]{#3}{#4}{%
    \@for\DTLbarvariable:=\dtlbar@variables\do{%
      \expandafter\DTLconverttodecimal\expandafter
        {\DTLbarvariable}{\dtl@barvar}%
      \let\dtl@old=\DTLnegextent
      \DTLmin{\DTLnegextent}{\dtl@old}{\dtl@barvar}%
    }%
  }%
\ifx\dtlbar@yticgap\relax
\else
  \ifthenelse{\DTLisFP1t{\DTLnegextent}{0}}{%
    \edef\dtl@thistick{0}%
    \whiledo{\DTLisFPclosedbetween{\dtl@thistick}{\DTLnegextent}{0}}{%
      \dtlsub{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
    }%
    \let\DTLnegextent=\dtl@thistick
  }{%
  }%
\fi
\fi

```

Determine scaling factor

```

\@dtl@tmpcount=\DTLbarchartlength
\dtlsub{\dtl@extent}{\DTLbarmax}{\DTLnegextent}%
\dtldiv{\dtl@unit}{\number\@dtl@tmpcount}{\dtl@extent}%

```

Construct y tick list if required

```

\setlength{\dtl@yticlabelwidth}{0pt}%
\ifDTLbarytics
  \ifx\dtlbar@yticlist\relax
    \ifx\dtlbar@yticgap\relax
      \@dtl@tmpcount=\DTLmintickgap
      \divide\@dtl@tmpcount by 65536\relax
      \dtldiv{\dtl@mingap}{\number\@dtl@tmpcount}{\dtl@unit}%
      \dtl@constructticklist\DTLnegextent\DTLbarmax
        \dtl@mingap\dtlbar@yticlist
    \else
      \dtl@constructticklistwithgapz
        \DTLnegextent\DTLbarmax\dtlbar@yticlist\dtlbar@yticgap
    \fi
  \fi
\ifx\dtlbar@ylabel\relax
\else
  \ifx\dtlbar@yticlabels\relax
    \@for\dtl@thislabel:=\dtlbar@yticlist\do{%
      \dtlround{\dtl@thislabel}{\dtl@thislabel}
        {\c@DTLbarroundvar}%
    }
    \ifDTLverticalbars
      \settowidth{\dtl@tmplength}{%

```

```

        \DTLbardisplayYticklabel{\dtl@thislabel}}%
\else
  \settoheight{\dtl@tmplength}{%
    \DTLbardisplayYticklabel{\dtl@thislabel}}%
  \edef\@dtl@h{\the\dtl@tmplength}%
  \settodepth{\dtl@tmplength}{%
    \DTLbardisplayYticklabel{\dtl@thislabel}}%
  \addtolength{\dtl@tmplength}{\@dtl@h}%
  \addtolength{\dtl@tmplength}{\baselineskip}%
\fi
\ifdim\dtl@tmplength>\dtl@yticlabelwidth
  \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
\fi
}%
\else
  \@for\dtl@thislabel:=\dtlbar@yticlabels\do{%
    \ifDTLverticalbars
      \settowidth{\dtl@tmplength}{%
        \DTLbardisplayYticklabel{\dtl@thislabel}}%
    \else
      \settoheight{\dtl@tmplength}{%
        \DTLbardisplayYticklabel{\dtl@thislabel}}%
      \edef\@dtl@h{\the\dtl@tmplength}%
      \settodepth{\dtl@tmplength}{%
        \DTLbardisplayYticklabel{\dtl@thislabel}}%
      \addtolength{\dtl@tmplength}{\@dtl@h}%
      \addtolength{\dtl@tmplength}{\baselineskip}%
    \fi
    \ifdim\dtl@tmplength>\dtl@yticlabelwidth
      \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
    \fi
  }%
\fi
\fi
\fi

```

Calculate the offset for the lower label and number of labels

```

\dtl@xticlabelheight=0pt\relax
\@dtl@tmpcount=0\relax
\@for\dtl@thislabel:=\dtl@multibarlabels\do{%
  \advance\@dtl@tmpcount by 1\relax
  \settoheight{\dtl@tmplength}{\tikz\expandafter\pgftext\expandafter
    [\DTLbarXlabelalign]{\DTLdisplaylowerbarlabel{\dtl@thislabel}};}%
  \edef\@dtl@h{\the\dtl@tmplength}%
  \settodepth{\dtl@tmplength}{\tikz\expandafter\pgftext\expandafter
    [\DTLbarXlabelalign]{\DTLdisplaylowerbarlabel{\dtl@thislabel}};}%
  \addtolength{\dtl@tmplength}{\@dtl@h}%
  \addtolength{\dtl@tmplength}{\baselineskip}%
  \ifdim\dtl@tmplength>\dtl@xticlabelheight
    \setlength{\dtl@xticlabelheight}{\dtl@tmplength}%
  \fi
}

```

```

    \fi
  }
Calculate number of bars per group
  \@dtl@tmpcount=0\relax
  \@for\dtl@this:=\dtlbar@variables\do{%
    \advance\@dtl@tmpcount by 1\relax
  }%
  \edef\DTLbargroupwidth{\number\@dtl@tmpcount}%
Compute the total width of the bar chart (in terms of the  $x$  unit vector.)
  \edef\dtl@n{\expandafter\number\csname dtlrows@#3\endcsname}
  \dtl@mul{\dtl@tmpi}{\dtl@n}{\DTLbargroupwidth}
  \dtl@sub{\dtl@tmpii}{\dtl@n}{1}%
  \dtl@mul{\dtl@tmpii}{\dtl@tmpii}{\dtlbar@groupgap}%
  \dtl@add{\DTLbarchartwidth}{\dtl@tmpi}{\dtl@tmpii}
Do the bar chart
  \begin{tikzpicture}
Set unit vectors
  \ifDTLverticalbars
    \pgfsetyvec{\pgfpoint{0pt}{\dtl@unit sp}}%
    \pgfsetxvec{\pgfpoint{\DTLbarwidth}{0pt}}%
  \else
    \pgfsetxvec{\pgfpoint{\dtl@unit sp}{0pt}}%
    \pgfsetyvec{\pgfpoint{0pt}{\DTLbarwidth}}%
  \fi
Begin hook
  \DTLbaratbegintikz
Initialise
  \def\@dtl@start{0}%
Iterate through data
  \@sDTLforeach[#1]{#3}{#4}{%
Store the bar number in \@dtl@bar
  \@dtl@barcount = 1\relax
Set the multibar label lists
  \let\dtl@multibar@labels=\dtl@multibarlabels
  \let\dtl@uppermultibar@labels=\dtl@uppermultibarlabels
Compute mid point over group
  \dtl@mul{\dtl@multimidpt}{\DTLbargroupwidth}{0.5}%
  \dtl@add{\dtl@multimidpt}{\dtl@multimidpt}{\@dtl@start}%
Iterate through each variable
  \@for\DTLbarvariable:=\dtlbar@variables\do{%
Set end point
  \dtl@add{\@dtl@endpt}{\@dtl@start}{1}%

```

Convert variable to decimal

```
\expandafter\DTLconverttodecimal\expandafter
{\DTLbarvariable}{\dtl@variable}%
```

Get the current lower label:

```
\dtl@chopfirst\dtl@multibar@labels\dtl@thisbarlabel\dtl@rest
\let\dtl@multibar@labels=\dtl@rest
```

Get the current upper label:

```
\dtl@chopfirst\dtl@uppermultibar@labels\dtl@thisupperbarlabel\dtl@rest
\let\dtl@uppermultibar@labels=\dtl@rest
```

Draw bars

```
\begin{scope}
\expandafter\color\expandafter{\DTLgetbarcolor{\@dtl@barcount}}%
\ifDTLverticalbars
\fill (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
-- (\@dtl@endpt,\dtl@variable) -- (\@dtl@endpt,0) -- cycle;
\else
\fill (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
-- (\dtl@variable,\@dtl@endpt) -- (0,\@dtl@endpt) -- cycle;
\fi
\end{scope}
```

Draw outline

```
\begin{scope}
\ifdim\DTLbaroutlinewidth>0pt
\expandafter\color\expandafter{\DTLbaroutlinecolor}
\ifDTLverticalbars
\draw (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
-- (\@dtl@endpt,\dtl@variable) -- (\@dtl@endpt,0) -- cycle;
\else
\draw (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
-- (\dtl@variable,\@dtl@endpt) -- (0,\@dtl@endpt) -- cycle;
\fi
\fi
\end{scope}
```

Calculate mid point

```
\dtl@ladd{\@dtl@midpt}{\@dtl@start}{0.5}%
```

Draw lower  $x$  labels

```
\ifDTLverticalbars
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\@dtl@midpt}{0}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLbarlabeloffset}}},
\DTLbarXlabelalign
}%
\edef\DTLstartpt{\noexpand\pgfpointxy{\@dtl@midpt}{0}}%
\else
\edef\dtl@textopt{%
```

```

        at={\noexpand\pgfpointadd
            {\noexpand\pgfpointxy{0}{\@dtl@midpt}}
            {\noexpand\pgfpoint{-\noexpand\DTLbarlabeloffset}{0pt}}},
        \DTLbarXlabelalign
    }%
\edef\DTLstartpt{\noexpand\pgfpointxy{0}{\@dtl@midpt}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
    \DTLdisplaylowermultibarlabel{\dtl@thisbarlabel}}
Draw upper x labels
\ifDTLverticalbars
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}
{
    \edef\dtl@textopt{%
        at={\noexpand\pgfpointadd
            {\noexpand\pgfpointxy{\@dtl@midpt}{\dtl@variable}}
            {\noexpand\pgfpoint{0pt}{-\noexpand\DTLbarlabeloffset}}}
    }%
}%
\edef\dtl@textopt{%
    at={\noexpand\pgfpointadd
        {\noexpand\pgfpointxy{\@dtl@midpt}{\dtl@variable}}
        {\noexpand\pgfpoint{0pt}{\noexpand\DTLbarlabeloffset}}}
    }%
}
\edef\DTLendpt{\noexpand\pgfpointxy{\@dtl@midpt}{\dtl@variable}}%
\else
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}
{
    \edef\dtl@textopt{right,
        at={\noexpand\pgfpointadd
            {\noexpand\pgfpointxy{\dtl@variable}{\@dtl@midpt}}
            {\noexpand\pgfpoint{-\noexpand\DTLbarlabeloffset}{0pt}}}
    }%
}%
\edef\dtl@textopt{left,
    at={\noexpand\pgfpointadd
        {\noexpand\pgfpointxy{\dtl@variable}{\@dtl@midpt}}
        {\noexpand\pgfpoint{\noexpand\DTLbarlabeloffset}{0pt}}}
    }%
}
\edef\DTLendpt{\noexpand\pgfpointxy{\dtl@variable}{\@dtl@midpt}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
    \DTLdisplayuppermultibarlabel{\dtl@thisupperbarlabel}}
Set the mid point
\def\DTLmidpt{\pgfpointlineattime{0.5}{\DTLstartpt}{\DTLendpt}}%
Do every bar hook

```



```

\DTLeverybarhook
End of loop increment loop variables
  \dtladd{\@dtl@start}{\@dtl@start}{1}%
  \advance\@dtl@barcount by 1\relax
}%
% Draw lower group $$ labels
% \begin{macrocode}
\setlength{\dtl@tmplength}{\DTLbarlabeloffset}%
\addtolength{\dtl@tmplength}{\dtl@xticlabelheight}%
\ifDTLverticalbars
  \edef\dtl@textopt{%
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{\dtl@multimidpt}{0}}
      {\noexpand\pgfpoint{0pt}{-\noexpand\dtl@tmplength}}},
    \DTLbarXlabelalign
  }%
\else
  \edef\dtl@textopt{%
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{0}{\dtl@multimidpt}}
      {\noexpand\pgfpoint{-\noexpand\dtl@tmplength}{0pt}}},
    \DTLbarXlabelalign
  }%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
  \DTLdisplaylowerbarlabel{\dtl@barlabel}}
Increment starting position by \dtlbar@groupgap
  \dtladd{\@dtl@start}{\@dtl@start}{\dtlbar@groupgap}%
}
Draw x axis
\ifDTLbarxaxis
  \ifDTLverticalbars
    \expandafter\draw\expandafter[\DTLBarXAxisStyle]
      (0,0) -- (\DTLbarchartwidth,0);
  \else
    \expandafter\draw\expandafter[\DTLBarXAxisStyle]
      (0,0) -- (0,\DTLbarchartwidth);
  \fi
\fi
Draw y axis
\ifDTLbaryaxis
  \ifDTLverticalbars
    \expandafter\draw\expandafter[\DTLBarYAxisStyle]
      (0,\DTLnegextent) -- (0,\DTLbarmax);
  \else
    \expandafter\draw\expandafter[\DTLBarYAxisStyle]
      (\DTLnegextent,0) -- (\DTLbarmax,0);
  \fi
\fi

```

```

\fi
\fi
Plot y tick marks if required
\ifx\dtlbar@yticlist\relax
\else
\@for\dtl@thistick:=\dtlbar@yticlist\do{%
\ifDTLverticalbars
\pgfpathmoveto{\pgfpointxy{0}{\dtl@thistick}}
\pgfpathlineto{
\pgfpointadd{\pgfpointxy{0}{\dtl@thistick}}
{\pgfpoint{-\DTLticklength}{0pt}}}
\else
\pgfpathmoveto{\pgfpointxy{\dtl@thistick}{0}}
\pgfpathlineto{
\pgfpointadd{\pgfpointxy{\dtl@thistick}{0}}
{\pgfpoint{0pt}{-\DTLticklength}}}
\fi
\pgfusepath{stroke}
\ifx\dtlbar@yticlabels\relax
\dtlround{\dtl@thislabel}{\dtl@thistick}
{\c@DTLbarroundvar}%
\else
\dtl@chopfirst\dtlbar@yticlabels\dtl@thislabel\dtl@rest
\let\dtlbar@yticlabels=\dtl@rest
\fi
\ifDTLverticalbars
\edef\dtl@textopt{\DTLbarYticklabelalign,%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{0}{\dtl@thistick}}
{\noexpand\pgfpoint{-\noexpand\DTLticklabeloffset}{0pt}},
}}%
\else
\edef\dtl@textopt{\DTLbarYticklabelalign,
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\dtl@thistick}{0}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLticklabeloffset}}}
}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
\DTLbardisplayYticklabel{\dtl@thislabel}}
}%
\fi
Plot the y label if required
\ifx\dtlbar@ylabel\relax
\else
\addtolength{\dtl@yticlabelwidth}{\baselineskip}%
\setlength{\dtl@tmplength}{0.5\DTLbarchartlength}
\ifDTLverticalbars

```

```

\pgftext [bottom,center,at={\pgfpointadd
  {\pgfpointxy{0}{\DTLnegextent}}%
  {\pgfpoint{-\dtl@yticlabelwidth}{\dtl@tmplength}}},
  rotate=90]{%
  \dtlbar@ylabel}
\else
\pgftext [bottom,center,at={\pgfpointadd
  {\pgfpointxy{\DTLnegextent}{0}}%
  {\pgfpoint{\dtl@tmplength}{-\dtl@yticlabelwidth}}]{%
  \dtlbar@ylabel}
\fi
\fi

```

Finish bar chart

```

\DTLbaratendtikz
\end{tikzpicture}
\fi
}}
```

## 8 datapie.sty

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datapie}[2018/12/07 v2.31 (NLCT)]
```

Require xkeyval package

```
\RequirePackage{xkeyval}
```

`\DTLcolorpiechart` The conditional `\ifDTLcolorpiechart` is to determine whether to use colour or grey scale.

```
\newif\ifDTLcolorpiechart
\DTLcolorpiecharttrue
```

Package options to change the conditional:

```
\DeclareOption{color}{\DTLcolorpiecharttrue}
\DeclareOption{gray}{\DTLcolorpiechartfalse}
```

`\DTLrotateinner` Define boolean keys to govern label rotations.

```
\define@boolkey{datapie}[DTL]{rotateinner}[true]{}
```

`\DTLrotateouter`

```
\define@boolkey{datapie}[DTL]{rotateouter}[true]{}
```

Set defaults:

```
\DTLrotateinnerfalse
\DTLrotateouterfalse
```

Package options to change `\DTLrotateinner`

```
\DeclareOption{rotateinner}{\DTLrotateinnertrue}
\DeclareOption{norotateinner}{\DTLrotateinnerfalse}
```

Package options to change `\DTLrotateouter`

```
\DeclareOption{rotateouter}{\DTLrotateoutertrue}
\DeclareOption{norotateouter}{\DTLrotateouterfalse}
```

Process options:

```
\ProcessOptions
```

Required packages:

```
\RequirePackage{datatool}
\RequirePackage{tikz}
```

Define some variables that govern the appearance of the pie chart.

<code>\DTLradius</code>	The radius of the pie chart is given by <code>\DTLradius</code> . <code>\newlength\DTLradius</code> <code>\DTLradius=2cm</code>
<code>\DTLinnerratio</code>	The inner label offset ratio is given by <code>\DTLinnerratio</code> <code>\newcommand*\DTLinnerratio{0.5}</code>
<code>\DTLouterratio</code>	The outer label offset ratio is given by <code>\DTLouterratio</code> . <code>\newcommand*\DTLouterratio{1.25}</code>
<code>DTLcutawayratio</code>	The cutaway offset ratio is given by <code>\DTLcutawayratio</code> . <code>\newcommand*\DTLcutawayratio{0.2}</code>
<code>\DTLstartangle</code>	The angle of the first segment is given by <code>\DTLstartangle</code> . <code>\newcommand*\DTLstartangle{0}</code>
<code>dtl@inneroffset</code>	<code>\newlength\dtl@inneroffset</code> <code>\dtl@inneroffset=\DTLinnerratio\DTLradius</code>
<code>dtl@outeroffset</code>	<code>\newlength\dtl@outeroffset</code> <code>\dtl@outeroffset=\DTLouterratio\DTLradius</code>
<code>l@cutawayoffset</code>	<code>\newlength\dtl@cutawayoffset</code> <code>\dtl@cutawayoffset=\DTLcutawayratio\DTLradius</code>
<code>dtl@piecutaways</code>	<code>\dtl@piecutaways</code> is a comma separated list of segments that need to be cut away from the pie chart. <code>\newcommand*\dtl@piecutaways{}</code>
<code>\dtl@innerlabel</code>	<code>\dtl@innerlabel</code> specifies the label to appear inside the segment. By default this is the variable used to create the pie chart. <code>\def\dtl@innerlabel{\DTLpievariable}%</code>
<code>\dtl@outerlabel</code>	<code>\def\dtl@outerlabel{}</code>
<code>DTLpieroundvar</code>	<code>DTLpieroundvar</code> is a counter governing the number of digits to round to when using <code>\FPround</code> . <code>\newcounter{DTLpieroundvar}</code> <code>\setcounter{DTLpieroundvar}{1}</code>

`isplayinnerlabel` `\DTLdisplayinnerlabel{<label>}`

This is used to format the inner label. This just does the label by default.

`\newcommand*\DTLdisplayinnerlabel}[1]{#1}`

`displayouterlabel` `\DTLdisplayouterlabel{<label>}`

This is used to format the outer label. This just does the label by default.

```
\newcommand*{\DTLdisplayouterlabel}[1]{#1}
```

`\DTLpiepercent` `\DTLpiepercent` returns the percentage value of the current segment.

```
\newcommand*{\DTLpiepercent}{%
\ifnum\dtlforeachlevel=0\relax
\PackageError{datapie}{Can't use
\string\DTLpiepercent\space outside
\string\DTLpiechart}{}%
\else
\csname dtl@piepercent@romannumeral\@dtl@seg\endcsname
\fi}
```

`\DTLpieatbegintikz` `\DTLpieatbegintikz` specifies any commands to apply at the start of the tikzpicture environment. By default it does nothing.

```
\newcommand*{\DTLpieatbegintikz}{}
```

`\DTLpieatendtikz` `\DTLpieatendtikz` specifies any commands to apply at the end of the tikzpicture environment. By default it does nothing.

```
\newcommand*{\DTLpieatendtikz}{}
```

`tpiesegmentcolor` `\DTLsetpiesegmentcolor{<n>}{<color>}`

Assign colour name `<color>` to the `<n>`th segment.

```
\newcommand*{\DTLsetpiesegmentcolor}[2]{%
\expandafter\def\csname dtl@pie@segcol\romannumeral#1\endcsname{#2}%
}
```

`tpiesegmentcolor` `\DTLgetpiesegmentcolor{<n>}`

Get the colour specification for segment `<n>`

```
\newcommand*{\DTLgetpiesegmentcolor}[1]{%
\csname dtl@pie@segcol\romannumeral#1\endcsname}
```

`opiesegmentcolor` `\DTLdopiesegmentcolor{<n>}`

Set the colour to that for segment  $\langle n \rangle$

```
\newcommand*{\DTLdopiecolor}[1]{%
\expandafter\color\expandafter
{\csname dtlpie@segcol\romannumeral#1\endcsname}}
```

piecolor  $\backslash$ DTLdopiecolor sets the colour to that of the current segment.

```
\newcommand*{\DTLdopiecolor}{%
\ifnum\dtlforeachlevel=0\relax
\PackageError{datapie}{Can't use
\string\DTLdopiecolor\space outside
\string\DTLpiechart}{}%
\else
\expandafter\DTLdopiecolor\expandafter{%
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname}%
\fi}
```

pieoutlinecolor  $\backslash$ DTLpieoutlinecolor specifies what colour to draw the outline.

```
\newcommand*{\DTLpieoutlinecolor}{black}
```

pieoutlinewidth  $\backslash$ DTLpieoutlinewidth specifies the line width of the outline: Outline is only drawn if the linewidth is greater than 0pt.

```
\newlength\DTLpieoutlinewidth
\DTLpieoutlinewidth=0pt
```

Set the default colours. If there are more than eight segments, more colours will need to be defined.

```
\ifDTLcolorpiechart
\DTLsetpiecolor{1}{red}
\DTLsetpiecolor{2}{green}
\DTLsetpiecolor{3}{blue}
\DTLsetpiecolor{4}{yellow}
\DTLsetpiecolor{5}{magenta}
\DTLsetpiecolor{6}{cyan}
\DTLsetpiecolor{7}{orange}
\DTLsetpiecolor{8}{white}
\else
\DTLsetpiecolor{1}{black!15}
\DTLsetpiecolor{2}{black!25}
\DTLsetpiecolor{3}{black!35}
\DTLsetpiecolor{4}{black!45}
\DTLsetpiecolor{5}{black!55}
\DTLsetpiecolor{6}{black!65}
\DTLsetpiecolor{7}{black!75}
\DTLsetpiecolor{8}{black!85}
\fi
```

Define keys for  $\backslash$ DTLpiechart optional argument. Set the starting angle of the first segment.

```
\define@key{datapie}{start}{\def\DTLstartangle{#1}}
```

Set the radius of the pie chart (must be set prior to inneroffset and outeroffset keys.)

```
\define@key{datapie}{radius}{\DTLradius=#1\relax
\dtl@inneroffset=\DTLinnerratio\DTLradius
\dtl@outeroffset=\DTLouterratio\DTLradius
\dtl@cutawayoffset=\DTLcutawayratio\DTLradius}
```

Set the inner ratio.

```
\define@key{datapie}{innerratio}{%
\def\DTLinnerratio{#1}%
\dtl@inneroffset=\DTLinnerratio\DTLradius}
```

Set the outer ratio

```
\define@key{datapie}{outerratio}{%
\def\DTLouterratio{#1}%
\dtl@outeroffset=\DTLouterratio\DTLradius}
```

The cutaway offset ratio

```
\define@key{datapie}{cutawayratio}{%
\def\DTLcutawayratio{#1}%
\dtl@cutawayoffset=\DTLcutawayratio\DTLradius}
```

Set the inner offset as an absolute value (not dependent on the radius.)

```
\define@key{datapie}{inneroffset}{%
\dtl@inneroffset=#1}
```

Set the outer offset as an absolute value (not dependent on the radius.)

```
\define@key{datapie}{outeroffset}{%
\dtl@outeroffset=#1}
```

Set the cutaway offset as an absolute value (not dependent on the radius.)

```
\define@key{datapie}{cutawayoffset}{%
\dtl@cutawayoffset=#1}
```

List of cut away segments.

```
\define@key{datapie}{cutaway}{%
\renewcommand*{\dtl@piecutaways}{#1}}
```

Variable used to create the pie chart. (Must be a control sequence.)

```
\define@key{datapie}{variable}{%
\def\DTLpievariable{#1}}
```

Inner label

```
\define@key{datapie}{innerlabel}{%
\def\dtl@innerlabel{#1}}
```

Outer label

```
\define@key{datapie}{outerlabel}{%
\def\dtl@outerlabel{#1}}
```

```
\DTLpiechart \DTLpiechart [<conditions>] {<option list>} {<db name>} {<assign list>}
```



Make a pie chart from data given in data base  $\langle db\ name\rangle$ , where  $\langle assign\ list\rangle$  is a comma-separated list of  $\langle cmd\rangle=\langle key\rangle$  pairs.  $\langle option\ list\rangle$  must include  $variable=\langle cmd\rangle$ , where  $\langle cmd\rangle$  is included in  $\langle assign\ list\rangle$ . The optional argument  $\langle conditions\rangle$  is the same as that for `\DTLforeach`.

```
\newcommand*\DTLpiechart}[4][\boolean{true}]{%
\bgroup
\let\DTLpievariable=\relax
\setkeys{datapie}{#2}%
\ifx\DTLpievariable\relax
\PackageError{datapie}%
{\string\DTLpiechart\space missing variable}{}%
\else
```

Compute the total.

```
\def\dtl@total{0}%
\@sDTLforeach[#1]{#3}{#4}{%
\let\dtl@oldtotal=\dtl@total
\expandafter\DTLconverttodecimal\expandafter
{\DTLpievariable}{\dtl@variable}%
\dtladd{\dtl@total}{\dtl@variable}{\dtl@total}%
}%
```

Compute the angles

```
\expandafter\DTLconverttodecimal\expandafter
{\DTLstartangle}{\@dtl@start}%
\@sDTLforeach[#1]{#3}{#4}{%
\expandafter\DTLconverttodecimal\expandafter
{\DTLpievariable}{\dtl@variable}%
\dtl@computeangles
{\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname}%
{\dtl@variable}%
\expandafter\@dtl@seg\expandafter=
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname%
\dtlmul{\dtl@tmp}{\dtl@variable}{100}%
\let\dtl@old=\dtl@tmp
\dtldiv{\dtl@tmp}{\dtl@old}{\dtl@total}%
\expandafter\dtlround
\csname dtl@piepercent@\romannumeral\@dtl@seg\endcsname\dtl@tmp
\c@DTLpieroundvar
}%
```

Compute the offsets for each cut away segment

```
\@for\dtl@row:=\dtl@piecutaways\do{%
\expandafter\@dtl@set@off\dtl@row-\relax
}%
```

Set the starting angle

```
\let\dtl@start=\DTLstartangle
```

Do the pie chart

```
\begin{tikzpicture}
```

```

\DTLpieatbegintikz
\@sDTLforeach[#1]{#3}{#4}%
{%

```

Store the segment number in \@dtl@seg

```

\expandafter\@dtl@seg\expandafter=
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname%

```

Set the start angle.

```

\edef\dtl@start{%
\csname dtl@sang@\romannumeral\@dtl@seg\endcsname}%

```

Set the extent

```

\edef\dtl@extent{%
\csname dtl@angle@\romannumeral\@dtl@seg\endcsname}%

```

Compute the end angle

```

\dtladd{\dtl@endangle}{\dtl@start}{\dtl@extent}%

```

Compute the shift.

```

\edef\dtl@angle{%
\csname dtl@cut@angle@\romannumeral\@dtl@seg\endcsname}%
\let\dtl@old=\dtl@angle
\dtl@truncatedecimal\dtl@angle
\ifnum\dtl@angle>180\relax
\dtlsub{\dtl@angle}{\dtl@old}{360}%
\dtl@truncatedecimal\dtl@angle
\fi
\edef\dtl@cutlen{%
\csname dtl@cut@len@\romannumeral\@dtl@seg\endcsname
}%
\edef\@dtl@shift{(\dtl@angle:\dtl@cutlen)}%

```

Compute the mid way angle.

```

\dtlmul{\dtl@angle}{\dtl@extent}{0.5}%
\dtladd{\dtl@midangle}{\dtl@angle}{\dtl@start}%

```

Draw the segment.

```

\begin{scope}[shift={\@dtl@shift}]%

\fill[color=\DTLgetpiesegmentcolor\@dtl@seg] (0,0) --
(\dtl@start:\DTLradius)
arc (\dtl@start:\dtl@endangle:\DTLradius) -- cycle;

```

Draw the outline if required:

```

\ifdim\DTLpieoutlinewidth>0pt\relax
\draw[color=\DTLpieoutlinecolor,%
line width=\DTLpieoutlinewidth]
(0,0) -- (\dtl@start:\DTLradius)
arc (\dtl@start:\dtl@endangle:\DTLradius) -- cycle;
\fi

```

Convert decimal to an integer

```
\dtl@truncatedecimal\dtl@midangle
```

Determine whether to rotate inner labels

```
\ifDTLrotateinner
```

If the mid way angle is between 90 and 270, the text will look upside-down, so adjust accordingly.

```
\dtlifnumopenbetween{\dtl@midangle}{90}{270}%  
{%  
  \let\@dtl@next\@firstoftwo  
}%  
{%  
  \dtlifnumlt{\dtl@midangle}{-90}%  
  {\let\@dtl@next\@firstoftwo}%  
  {\let\@dtl@next\@secondoftwo}%  
}%  
\@dtl@next  
{%  
  \dtlsub{\dtl@labelangle}{\dtl@midangle}{180}%  
  \dtl@truncatedecimal\dtl@labelangle  
  \edef\dtl@innernodeopt{anchor=east,rotate=\dtl@labelangle}%  
}%  
{%  
  \edef\dtl@innernodeopt{anchor=west,rotate=\dtl@midangle}%  
}%
```

Don't rotate inner labels

```
\else  
  \edef\dtl@innernodeopt{anchor=center}%  
\fi
```

Determine whether to rotate outer labels

```
\ifDTLrotateouter
```

If the mid way angle is between 90 and 270, the text will look upside-down, so adjust accordingly.

```
\dtlifnumopenbetween{\dtl@midangle}{90}{270}%  
{%  
  \let\@dtl@next\@firstoftwo  
}%  
{%  
  \dtlifnumlt{\dtl@midangle}{-90}%  
  {\let\@dtl@next\@firstoftwo}%  
  {\let\@dtl@next\@secondoftwo}%  
}%  
\@dtl@next  
{%  
  \dtlsub{\dtl@labelangle}{\dtl@midangle}{180}%  
  \dtl@truncatedecimal\dtl@labelangle  
  \edef\dtl@outernodeopt{anchor=east,rotate=\dtl@labelangle}%
```

```

}%
{%
\edef\dtl@outernodeopt{anchor=west,rotate=\dtl@midangle}%
}%

```

Don't rotate outer labels

```

\else
If  $(\theta > -45$  and  $\theta < 45)$  or  $\theta = 45$  or  $\theta > 315$ 
\dtlifnumeq{\dtl@midangle}{45}
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumgt{\dtl@midangle}{315}
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumopenbetween{\dtl@midangle}{-45}{45}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\let\@dtl@next\@secondoftwo
}%
}%
}%
\@dtl@next
{%

```

East quadrant

```

\edef\dtl@outernodeopt{anchor=west}%
}%
{%
\dtlifnumopenbetween{\dtl@midangle}{45}{135}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumeq{\dtl@midangle}{135}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\let\@dtl@next\@secondoftwo
}%
}%
\@dtl@next
{%

```

North quadrant

```
\edef\dtl@outernodeopt{anchor=south}%
}%
{%
If  $(\theta > 135$  and  $\theta < 225)$  or  $\theta = 225$  or  $\theta = -135$  or  $\theta < -135$ 
\dtlifnumopenbetween{\dtl@midangle}{135}{225}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumeq{\dtl@midangle}{225}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumeq{\dtl@midangle}{-135}%
{%
\let\@dtl@next\@firstoftwo
}%
}%
\dtlifnumlt{\dtl@midangle}{-135}%
{%
\let\@dtl@next\@firstoftwo
}%
}%
\let\@dtl@next\@secondoftwo
}%
}%
\@dtl@next
{%
```

West quadrant

```
\edef\dtl@outernodeopt{anchor=east}%
}%
{%
\edef\dtl@outernodeopt{anchor=north}%
}%
}%
}%
\fi
```

Draw inner and outer labels

```
\edef\@dtl@dolabel{%
\noexpand\draw (\dtl@midangle:\the\dtl@inneroffset)
node[\dtl@innernodeopt]{%
\noexpand\DTLdisplayinnerlabel{\noexpand\dtl@innerlabel}};
}%
```

```

\@dtl@dolabel
\edef\@dtl@dolabel{%
  \noexpand\draw (\dtl@midangle:\the\dtl@outeroffset)
    node[\dtl@outernodeopt]{%
      \noexpand\DTLdisplayouterlabel{\noexpand\dtl@outerlabel}};
}%
\@dtl@dolabel
\end{scope}%
}%
\DTLpieatendtikz
\end{tikzpicture}%
\fi
\egroup
}

```

\dtl@computeangles

```
\dtl@computeangles{<n>}{<variable>}
```

Compute the angles for segment  $\langle n \rangle$ . This sets  $\dtl@sang@{\langle n \rangle}$  (start angle),  $\dtl@angle@{\langle n \rangle}$  (extent angle),  $\dtl@cut@angle@{\langle n \rangle}$  (cut away angle) and  $\dtl@cut@len@{\langle n \rangle}$  (cut away length).

```

\newcommand*{\dtl@computeangles}[2]{%
  \dtlifnumgt{\@dtl@start}{180}%
  {%
if startangle > 180
  \let\dtl@old=\@dtl@start
startangle := startangle - 360
  \dtlsub{\@dtl@start}{\dtl@old}{360}%
}%
  {}%
  \dtlifnumlt{\@dtl@start}{-180}%
  {%
if startangle < -180
  \let\dtl@old=\@dtl@start
startangle = startangle + 360
  \dtladd{\@dtl@start}{\dtl@old}{360}%
}%
  {}%
  \expandafter\edef\csname dtl@sang@\romannumeral#1\endcsname{%
    \@dtl@start}%
  \dtlmul{\dtl@angle}{360}{#2}%
  \let\dtl@old=\dtl@angle
  \dtldiv{\dtl@angle}{\dtl@old}{\dtl@total}%
  \expandafter\let\csname dtl@angle@\romannumeral#1\endcsname=\dtl@angle
  \let\dtl@old=\@dtl@start

```

```

\dtladd{\@dtl@start}{\dtl@old}{\dtl@angle}%
\expandafter\def\csname dtl@cut@angle@\romannumeral#1\endcsname{0}%
\expandafter\def\csname dtl@cut@len@\romannumeral#1\endcsname{0cm}%
}

```

Set the offset angles.

`\@dtl@set@off`

```

\def\@dtl@set@off#1-#2\relax{%
  \ifstrempy{#2}%
  {%
    \@dtl@set@off{#1}%
  }%
  {%
    \@dtl@set@offr#1-#2\relax
  }%
}

```

Set offset for individual segment:

`\@@dtl@set@off`

```

\newcommand*\@@dtl@set@off}[1]{%
  \edef\dtl@old{\csname dtl@angle@\romannumeral#1\endcsname}%
  \dtlmul{\dtl@angle}{\dtl@old}{0.5}%
  \let\dtl@old=\dtl@angle
  \edef\dtl@sang{\csname dtl@sang@\romannumeral#1\endcsname}%
  \dtladd{\dtl@angle}{\dtl@old}{\dtl@sang}%
  \expandafter\edef\csname dtl@cut@angle@\romannumeral#1\endcsname{%
  \dtl@angle}%
  \expandafter\edef\csname dtl@cut@len@\romannumeral#1\endcsname{%
  \the\dtl@cutawayoffset}%
}

```

Define count register to keep track of segments

`\@dtl@seg`

```
\newcount\@dtl@seg
```

`\@@dtl@set@offr` Set offset for a range of segments

```

\def\@@dtl@set@offr#1-#2-\relax{%
  \ifnum#1>#2\relax
    \PackageError{datapie}{Segment ranges must go in ascending order}{%
      Try #2-#1 instead of #1-#2}%
  \else
    \def\dtl@angle{0}%
    \@dtl@seg=#1\relax
    \whiledo{\not\(\@dtl@seg > #2\)}{%
      \let\dtl@old=\dtl@angle
      \edef\dtl@segang{\csname dtl@angle@\romannumeral\@dtl@seg\endcsname}%
      \dtladd{\dtl@angle}{\dtl@old}{\dtl@segang}%
    }
  \end{code}

```

```

    \advance\@dtl@seg by 1\relax
  }%
  \let\dtl@old=\dtl@angle
  \dtlmul{\dtl@angle}{\dtl@old}{0.5}%
  \edef\dtl@sang{\csname dtl@sang@\romannumeral#1\endcsname}%
  \let\dtl@old=\dtl@angle
  \dtladd{\dtl@angle}{\dtl@old}{\dtl@sang}%
  \@dtl@seg=#1\relax
  \whiledo{\not\(\@dtl@seg > #2\)}{%
  \expandafter
  \let\csname dtl@cut@angle@\romannumeral\@dtl@seg\endcsname
  =\dtl@angle
  \expandafter
  \edef\csname dtl@cut@len@\romannumeral\@dtl@seg\endcsname{%
  \the\dtl@cutawayoffset}
  \advance\@dtl@seg by 1\relax
  }%
\fi
}

```



## 9 dataplot.sty

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{dataplot}[2018/12/07 v2.31 (NLCT)]
```

Required packages

```
\RequirePackage{xkeyval}
\RequirePackage{tikz}
\RequirePackage{datatool}
```

Load TikZ plot libraries

```
\usetikzlibrary{plotmarks}
\usetikzlibrary{plohandlers}
```

Load calc library

```
\usetikzlibrary{calc}
```

```
\DTLplotstream \DTLplotstream[<condition>]{<db name>}{<x key>}{<y key>}
```

Add points to a stream from the database called *<db name>* where the *x* co-ordinates are given by the key *<x key>* and the *y* co-ordinates are given by the key *<y key>*. The optional argument *<condition>* is the same as that for `\DTLforeach`

```
\newcommand*{\DTLplotstream}[4][\boolean{true}]{%
  \@sDTLforeach[#1]{#2}{\dtl@x=#3,\dtl@y=#4}{%
    \DTLconverttodecimal{\dtl@x}{\dtl@decx}%
    \DTLconverttodecimal{\dtl@y}{\dtl@decy}%
    \pgfplotstreampoint{\pgfpointxy{\dtl@decx}{\dtl@decy}}%
  }%
}
```

```
\DTLplotmarks \DTLplotmarks contains a list of plot marks used by \DTLplot.
```

```
\newcommand*{\DTLplotmarks}{%
  \pgfuseplotmark{o},%
  \pgfuseplotmark{x},%
  \pgfuseplotmark{+},%
  \pgfuseplotmark{square},%
  \pgfuseplotmark{triangle},%
  \pgfuseplotmark{diamond},%
  \pgfuseplotmark{pentagon},%
  \pgfuseplotmark{asterisk},%
```

```

        \pgfuseplotmark{star}%
    }

Lplotmarkcolors \DTLplotmarkcolors contains a list of the plot mark colours.
    \newcommand*\DTLplotmarkcolors{%
        red,%
        green,%
        blue,%
        yellow,%
        magenta,%
        cyan,%
        orange,%
        black,%
        gray}

\DTLplotlines \DTLplotlines contains a list of dash patterns used by \DTLplot.
    \newcommand*\DTLplotlines{%
        \pgfsetdash{}{0pt},% solid line
        \pgfsetdash{{10pt}{5pt}}{0pt},%
        \pgfsetdash{{5pt}{5pt}}{0pt},%
        \pgfsetdash{{1pt}{5pt}}{0pt},%
        \pgfsetdash{{5pt}{5pt}{1pt}{5pt}}{0pt},%
        \pgfsetdash{{1pt}{3pt}}{0pt},%
    }

Lplotlinecolors \DTLplotlinecolors contains a list of the plot line colours.
    \newcommand*\DTLplotlinecolors{%
        red,%
        green,%
        blue,%
        yellow,%
        magenta,%
        cyan,%
        orange,%
        black,%
        gray}

\DTLplotwidth The default total plot width is stored in the length \dtlplotwidth
    \newlength\DTLplotwidth
    \setlength\DTLplotwidth{4in}

\DTLplotheight The default total plot height is stored in the length \dtlplotheight
    \newlength\DTLplotheight
    \setlength\DTLplotheight{4in}

\DTLticklength The length of the tick marks is given by \DTLticklength
    \newlength\DTLticklength
    \setlength\DTLticklength{5pt}

```

<code>minorticklength</code>	The length of the minor tick marks is given by <code>\DTLminorticklength</code> . <code>\newlength\DTLminorticklength</code> <code>\setlength\DTLminorticklength{2pt}</code>
<code>ticklabeloffset</code>	The offset from the axis to the tick label is given by <code>\DTLticklabeloffset</code> . <code>\newlength\DTLticklabeloffset</code> <code>\setlength\DTLticklabeloffset{8pt}</code>
<code>xticlabelheight</code>	<code>\dtl@xticlabelheight</code> is used to store the height of the $x$ tick labels. <code>\newlength\dtl@xticlabelheight</code>
<code>yticlabelwidth</code>	<code>\dtl@yticlabelwidth</code> is used to store the width of the $y$ tick labels. <code>\newlength\dtl@yticlabelwidth</code>
<code>\DTLmintickgap</code>	<code>\DTLmintickgap</code> stores the suggested minimum distance between tick marks where the gap is not specified. <code>\newlength\DTLmintickgap</code> <code>\setlength\DTLmintickgap{20pt}</code>
<code>minminortickgap</code>	The suggested minimum distance between minor tick marks where the gap is not specified is given by <code>\DTLminminortickgap</code> . <code>\newlength\DTLminminortickgap</code> <code>\setlength\DTLminminortickgap{5pt}</code>
<code>DTLplotroundvar</code>	Round $x$ tick labels to the number of digits given by the counter <code>DTLplotroundXvar</code> . <code>\newcounter{DTLplotroundXvar}</code> <code>\setcounter{DTLplotroundXvar}{2}</code>
<code>DTLplotroundYvar</code>	Round $y$ tick labels to the number of digits given by the counter <code>DTLplotroundYvar</code> . <code>\newcounter{DTLplotroundYvar}</code> <code>\setcounter{DTLplotroundYvar}{2}</code>
<code>\ifDTLxaxis</code>	The conditional <code>\ifDTLxaxis</code> is used to determine whether or not to display the $x$ axis. <code>\newif\ifDTLxaxis</code> <code>\DTLxaxistrue</code>
<code>\DTLXAxisStyle</code>	The style of the $x$ axis is given by <code>\DTLXAxisStyle</code> . This is just a solid line by default. <code>\newcommand*\DTLXAxisStyle{-}</code>
<code>\ifDTLyaxis</code>	The conditional <code>\ifDTLyaxis</code> is used to determine whether or not to display the $y$ axis <code>\newif\ifDTLyaxis</code> <code>\DTLyaxistrue</code>
<code>\DTLYAxisStyle</code>	The style of the $y$ axis is given by <code>\DTLYAxisStyle</code> . This is just a solid line by default. <code>\newcommand*\DTLYAxisStyle{-}</code>

<code>\DTLmajorgridstyle</code>	The style of the major grid lines is given by <code>\DTLmajorgridstyle</code> . <code>\newcommand*{\DTLmajorgridstyle}{color=gray,-}</code>
<code>\DTLminorgridstyle</code>	The style of the minor grid lines is given by <code>\DTLminorgridstyle</code> . <code>\newcommand*{\DTLminorgridstyle}{color=gray,loosely dotted}</code>
<code>\ifDTLxticsin</code>	The conditional <code>\ifDTLxticsin</code> is used to determine whether the $x$ tics should point in or out. <code>\newif\ifDTLxticsin</code> <code>\DTLxticsintrue</code>
<code>\ifDTLyticsin</code>	The conditional <code>\ifDTLyticsin</code> is used to determine whether the $y$ tics should point in or out. <code>\newif\ifDTLyticsin</code> <code>\DTLyticsintrue</code>
<code>\dtl@legendsetting</code>	The legend setting is stored in the count register <code>\dtl@legendsetting</code> . <code>\newcount\dtl@legendsetting</code>
<code>\DTLlegendxoffset</code>	The gap between the border of plot and legend is given by the lengths <code>\DTLlegendxoffset</code> and <code>\DTLlegendyoffset</code> <code>\newlength\DTLlegendxoffset</code> <code>\setlength\DTLlegendxoffset{10pt}</code>
<code>\DTLlegendyoffset</code>	<code>\newlength\DTLlegendyoffset</code> <code>\setlength\DTLlegendyoffset{10pt}</code>
<code>\DTLformatlegend</code>	<code>\DTLformatlegend{\langle legend \rangle}</code>
	This formats the legend. <code>\newcommand*{\DTLformatlegend}[1]{%</code> <code>\setlength{\fboxrule}{1.1pt}%</code> <code>\fcolorbox{black}{white}{#1}}</code>
<code>\ifDTLshowmarkers</code>	The conditional <code>\ifDTLshowmarkers</code> is used to specify whether or not to use markers. <code>\newif\ifDTLshowmarkers</code> <code>\DTLshowmarkerstrue</code>
<code>\ifDTLshowlines</code>	The conditional <code>\ifDTLshowlines</code> is used to specify whether or not to use lines. <code>\newif\ifDTLshowlines</code> <code>\DTLshowlinesfalse</code>

plotatbegintikz `\DTLplotatbegintikz` is a hook to insert stuff at the start of the tikzpicture environment (after the unit vectors have been set).

```
\newcommand*\DTLplotatbegintikz{}
```

plothandlermark Provide a convenient access to `\pgfplothandlermark` that reverses the effect of the plot scaling.

```
\newcommand*\@dtlplothandlermark[1]{%
  \pgfplothandlermark
  {%
    \pgfmathparse{1/\dtl@scale@x}%
    \pgftransformxscale{\pgfmathresult}%
    \pgfmathparse{1/\dtl@scale@y}%
    \pgftransformyscale{\pgfmathresult}%
    #1%
  }%
}
```

Just in case a user attempts to use `\dtlplothandermark` outside `\DTLplot`:

```
\newcommand*\dtlplothandlermark[1]{%
  \PackageWarning{dataplot}{\string\dtlplothandlermark\space
    found outside \string\DTLplot}%
  \pgfplothandlermark{#1}%
}
```

TLplotatendtikz `\DTLplotatendtikz` is a hook to insert stuff at the end of the tikzpicture environment.

```
\newcommand*\DTLplotatendtikz{}
```

Plot settings. The database key for the  $x$  value is given by the `x` setting:

```
\define@key{dataplot}{x}{%
  \def\dtl@xkey{#1}}
```

The database key for the  $y$  value is given by the `y` setting:

```
\define@key{dataplot}{y}{%
  \def\dtl@ykey{#1}}
```

The list of plot mark colours is given by the `markcolors` setting. (This should be a comma separated list of colour names.)

```
\define@key{dataplot}{markcolors}{%
  \def\DTLplotmarkcolors{#1}}
```

The list of plot line colours is given by the `linecolors` setting. (This should be a comma separated list of colour names.)

```
\define@key{dataplot}{linecolors}{%
  \def\DTLplotlinecolors{#1}}
```

The list of plot mark and line colours is given by the `colors` setting. (This should be a comma separated list of colour names.)

```
\define@key{dataplot}{colors}{%
  \def\DTLplotmarkcolors{#1}%
  \def\DTLplotlinecolors{#1}}
```

The list of plot marks is given by the marks setting. (This should be a comma separated list of code that generates pgf plot marks.)

```
\define@key{dataplot}{marks}{%
\def\DTLplotmarks{#1}}
```

The list of plot line styles is given by the lines setting. (This should be a comma separated list of code that sets the line style.) An empty set will create solid lines.

```
\define@key{dataplot}{lines}{%
\def\DTLplotlines{#1}}
```

The total width of the plot is given by the width setting.

```
\define@key{dataplot}{width}{%
\setlength\DTLplotwidth{#1}}
```

The total height of the plot is given by the height setting.

```
\define@key{dataplot}{height}{%
\setlength\DTLplotheight{#1}}
```

Determine whether to show lines, markers or both

```
\define@choicekey{dataplot}{style}[\val\nr]{both,lines,markers}{%
\ifcase\nr\relax
\DTLshowlinestrue
\DTLshowmarkerstrue
\or
\DTLshowlinestrue
\DTLshowmarkersfalse
\or
\DTLshowmarkerstrue
\DTLshowlinesfalse
\fi}
```

Determine whether or not to display the axes

```
\define@choicekey{dataplot}{axes}[\val\nr]{both,x,y,none}[both]{%
\ifcase\nr\relax
% both
\DTLxaxistrue
\DTLxticstrue
\DTLyaxistrue
\DTLyticstrue
\or % x
\DTLxaxistrue
\DTLxticstrue
\DTLyaxisfalse
\DTLyticfalse
\or % y
\DTLxaxisfalse
\DTLxticfalse
\DTLyaxistrue
\DTLyticstrue
\or % none
\DTLxaxisfalse
```

```

        \DTLxticsfalse
        \DTLyaxisfalse
        \DTLyticsfalse
    \fi
}

\ifDTLbox Enclose plot in a box
    \define@boolkey{dataplot}[DTL]{box}[true]{}
    \DTLboxfalse

\ifDTLxticstrue Condition to determine whether to show the  $x$  tick marks
    \define@boolkey{dataplot}[DTL]{xtics}[true]{}
    \DTLxticstrue

\ifDTLyticstrue Condition to determine whether to show the  $y$  tick marks
    \define@boolkey{dataplot}[DTL]{ytics}[true]{}
    \DTLyticstrue

\ifDTLxminortics Condition to determine whether to show the  $x$  minor tick marks
    \define@boolkey{dataplot}[DTL]{xminortics}[true]{}
    \ifDTLxminortics \DTLxticstrue\fi
    \DTLxminorticsfalse

\ifDTLyminortics Condition to determine whether to show the  $y$  minor tick marks
    \define@boolkey{dataplot}[DTL]{yminortics}[true]{}
    \ifDTLyminortics \DTLyticstrue\fi
    \DTLyminorticsfalse

\ifDTLgrid Determine whether to draw the grid
    \define@boolkey{dataplot}[DTL]{grid}[true]{}

Determine whether the  $x$  tick marks should point in or out:
    \define@choicekey{dataplot}{xticdir}[\val\nr]{in,out}{}
    \ifcase\nr\relax
        \DTLxticsintrue
    \or
        \DTLxticsinfalse
    \fi
}

Determine whether the  $y$  tick marks should point in or out:
    \define@choicekey{dataplot}{yticdir}[\val\nr]{in,out}{}
    \ifcase\nr\relax
        \DTLyticsintrue
    \or
        \DTLyticsinfalse
    \fi
}

```

Determine whether the  $x$  and  $y$  tick marks should point in or out;

```
\define@choicekey{dataplot}{ticdir}[\val\nr]{in,out}{%
\ifcase\nr\relax
\DTLxticsintrue
\DTLyticsintrue
\or
\DTLxticsinfalse
\DTLyticsinfalse
\fi
}
```

Set the bounds of the graph (value must be in the form  $\langle \min x \rangle, \langle \min y \rangle, \langle \max x \rangle, \langle \max y \rangle$  (bounds overrides minx, miny, maxx and maxy settings.)

```
\define@key{dataplot}{bounds}{%
\def\dtl@bounds{#1}}
\let\dtl@bounds=\relax
```

Set only the lower  $x$  bound

```
\define@key{dataplot}{minx}{%
\def\dtl@minx{#1}}
\let\dtl@minx=\relax
```

Set only the upper  $x$  bound:

```
\define@key{dataplot}{maxx}{%
\def\dtl@maxx{#1}}
\let\dtl@maxx=\relax
```

Set only the lower  $y$  bound:

```
\define@key{dataplot}{miny}{%
\def\dtl@miny{#1}}
\let\dtl@miny=\relax
```

Set only the upper  $y$  bound:

```
\define@key{dataplot}{maxy}{%
\def\dtl@maxy{#1}}
\let\dtl@maxy=\relax
```

Define list of points for  $x$  ticks. (Must be a comma separated list of decimal numbers.)

```
\define@key{dataplot}{xticpoints}{%
\def\dtl@xticlist{#1}\DTLxticstrue\DTLxaxistrue}
\let\dtl@xticlist=\relax
```

Define list of points for  $y$  ticks. (Must be a comma separated list of decimal numbers.)

```
\define@key{dataplot}{yticpoints}{%
\def\dtl@yticlist{#1}\DTLyticstrue\DTLyaxistrue}
\let\dtl@yticlist=\relax
```

Define a the gap between  $x$  tick marks (xticpoints overrides xticgap)

```
\define@key{dataplot}{xticgap}{\def\dtl@xticgap{#1}%
\DTLxticstrue\DTLxaxistrue}
\let\dtl@xticgap=\relax
```



Define a the gap between  $y$  tick marks (yticpoints overrides yticgap)

```
\define@key{dataplot}{yticgap}{\def\dtl@yticgap{#1}%
\DTLyticstrue\DTLyaxistrue}
\let\dtl@yticgap=\relax
```

Define comma separated list of labels for  $x$  ticks.

```
\define@key{dataplot}{xticlabels}{%
\def\dtl@xticlabels{#1}\DTLxticstrue\DTLxaxistrue}
\let\dtl@xticlabels=\relax
```

Define comma separated list of labels for  $y$  ticks.

```
\define@key{dataplot}{yticlabels}{%
\def\dtl@yticlabels{#1}\DTLyticstrue\DTLyaxistrue}
\let\dtl@yticlabels=\relax
```

Define  $x$  axis label

```
\define@key{dataplot}{xlabel}{%
\def\dtl@xlabel{#1}}
\let\dtl@xlabel=\relax
```

Define  $y$  axis label

```
\define@key{dataplot}{ylabel}{%
\def\dtl@ylabel{#1}}
\let\dtl@ylabel=\relax
```

The legend setting may be one of: none (don't show it), north, northeast, east, southeast, south, southwest, west, or northwest. These set the count register `\dtl@legendsetting`.

```
\define@choicekey{dataplot}{legend}[\val\nr]{none,north,northeast,%
east,southeast,south,southwest,west,northwest}[northeast]{%
\dtl@legendsetting=\nr\relax
}
```

Legend labels (comma separated list). If omitted, the database name is used.

```
\define@key{dataplot}{legendlabels}{\def\dtl@legendlabels{#1}}
```

`\DTLplot` `\DTLplot[<condition>]{<db list>}{<settings>}`

Creates a plot (inside a `tikzpicture` environment) of all the data given in the databases listed in *<db list>*.

```
\newcommand*{\DTLplot}[3][\boolean{true}]{%
\bgroup
\let\dtl@xkey=\relax
\let\dtl@ykey=\relax
\let\dtl@legendlabels=\relax
\setkeys{dataplot}{#3}%
\let\dtl@plotmarklist=\DTLplotmarks
\let\dtl@plotlinelist=\DTLplotlines
\let\dtl@plotmarkcolorlist=\DTLplotmarkcolors
```

```

\let\dtl@plotlinecolorlist=\DTLplotlinecolors
\def\dtl@legend{}%
\ifx\dtl@legendlabels\relax
\edef\dtl@legendlabels{#2}%
\fi
\ifx\dtl@xkey\relax
\PackageError{dataplot}{Missing x setting for
\string\DTLplot}{}%
\else
\ifx\dtl@ykey\relax
\PackageError{dataplot}{Missing y setting for
\string\DTLplot}{}%
\else

```

If user didn't specified bounds, compute the maximum and minimum  $x$  and  $y$  values over all the databases listed.

```

\ifx\dtl@bounds\relax
\DTLcomputebounds[#1]{#2}{\dtl@xkey}{\dtl@ykey}
{\DTLminX}{\DTLminY}{\DTLmaxX}{\DTLmaxY}%
\ifx\dtl@minx\relax
\else
\let\DTLminX=\dtl@minx
\fi
\ifx\dtl@maxx\relax
\else
\let\DTLmaxX=\dtl@maxx
\fi
\ifx\dtl@miny\relax
\else
\let\DTLminY=\dtl@miny
\fi
\ifx\dtl@maxy\relax
\else
\let\DTLmaxY=\dtl@maxy
\fi

```

Otherwise extract information from `\dtl@bounds`

```

\else
\expandafter\dtl@getbounds\dtl@bounds\@nil
\fi

```

Determine scaling factors and offsets. The  $x$ -scale factor is given by:

$$s_x = \frac{W}{x_{\max} - x_{\min}}$$

where  $W$  is the plot width. The  $x$  offset is  $-s_x x_{\min}$ . Similarly for  $y$ .

```

\@dtl@tmpcount=\DTLplotwidth
\divide\@dtl@tmpcount by 65536\relax
\dtlsub{\dtl@dx}{\DTLmaxX}{\DTLminX}%
\dtldiv{\dtl@scale@x}{\number\@dtl@tmpcount}{\dtl@dx}%

```

```

\dtl@mul{\dtl@offset@x}{-\dtl@scale@x}{\DTLminX}%
\@dtl@tmpcount=\DTLplotheight
\divide\@dtl@tmpcount by 65536\relax
\dtl@sub{\dtl@dy}{\DTLmaxY}{\DTLminY}%
\dtl@div{\dtl@scale@y}{\number\@dtl@tmpcount}{\dtl@dy}%
\dtl@mul{\dtl@offset@y}{-\dtl@scale@y}{\DTLminY}%

```

If x tics specified, construct a list of x tic points if not already specified.

```

\ifDTLxtics
\ifx\dtl@xticlist\relax
\ifx\dtl@xticgap\relax

```

Get the min tick gap in data co-ordinates

```

\dtl@sub{\dtl@mingap}{\number\DTLmintickgap}{\dtl@offset@x}%
\dtl@div{\dtl@mingap}{\dtl@mingap}{\dtl@scale@x}%
\dtl@div{\dtl@mingap}{\dtl@mingap}{65536}%

```

construct tick list

```

\dtl@constructticklist\DTLminX\DTLmaxX
\dtl@mingap\dtl@xticlist
\else
\DTLifFPopenbetween{0}{\DTLminX}{\DTLmaxX}{%
\dtl@constructticklistwithgapz
\DTLminX\DTLmaxX\dtl@xticlist\dtl@xticgap}{%
\dtl@constructticklistwithgap
\DTLminX\DTLmaxX\dtl@xticlist\dtl@xticgap}%
\fi
\fi

```

Construct a list of x minor tick points if required

```

\let\dtl@xminorticlist\@empty
\ifDTLxminortics
\let\dtl@prevtick=\relax
\@for\dtl@nexttick:=\dtl@xticlist\do{%
\ifx\dtl@prevtick\relax
\else
\dtl@constructminorticklist
\dtl@prevtick\dtl@nexttick\dtl@scale@x\dtl@xminorticlist
\fi
\let\dtl@prevtick=\dtl@nexttick
}%
\fi

```

Determine the height of the x tick labels.

```

\ifx\dtl@xticlabels\relax
\settoheight{\dtl@xticlabelheight}{\dtl@xticlist}%
\else
\settoheight{\dtl@xticlabelheight}{\dtl@xticlabels}%
\fi
\else
\setlength{\dtl@xticlabelheight}{0pt}%
\fi

```

If y tics specified, construct a list of y tic points if not already specified.

```
\setlength{dtl@yticlabelwidth}{0pt}%
\ifDTLytics
  \ifx\dtl@yticlist\relax
    \ifx\dtl@yticgap\relax
```

Get the min tick gap in data co-ordinates

```
\dtlsub{dtl@mingap}{\number\DTLmintickgap}{\dtl@offset@y}%
\dtldiv{dtl@mingap}{\dtl@mingap}{\dtl@scale@y}%
\dtldiv{dtl@mingap}{\dtl@mingap}{65536}%
```

construct tick list

```
\dtl@constructticklist\DTLminY\DTLmaxY
  \dtl@mingap\dtl@yticlist
\else
  \DTLifFPopenbetween{0}{\DTLminY}{\DTLmaxY}{%
    \dtl@constructticklistwithgapz
    \DTLminY\DTLmaxY\dtl@yticlist\dtl@yticgap}{%
    \dtl@constructticklistwithgap
    \DTLminY\DTLmaxY\dtl@yticlist\dtl@yticgap}%
  \fi
\fi
```

Construct a list of y minor tick points if required

```
\let\dtl@yminorticlist\@empty
\ifDTLyminortics
  \let\dtl@prevtick=\relax
  \@for\dtl@nexttick:=\dtl@yticlist\do{%
    \ifx\dtl@prevtick\relax
      \else
        \dtl@constructminorticklist
          \dtl@prevtick\dtl@nexttick\dtl@scale@y\dtl@yminorticlist
        \fi
      \let\dtl@prevtick=\dtl@nexttick
    }%
  \fi
```

Determine the width of the y tick labels.

```
\ifx\dtl@ylabel\relax
\else
  \ifx\dtl@yticlabels\relax
    \@for\dtl@thislabel:=\dtl@yticlist\do{%
      \dtlround{\dtl@thislabel}{\dtl@thislabel}
        {\c@DTLplotroundYvar}%
      \settowidth{\dtl@tmplength}{\dtl@thislabel}%
      \ifdim\dtl@tmplength>\dtl@yticlabelwidth
        \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
      \fi
    }%
  \else
    \@for\dtl@thislabel:=\dtl@yticlabels\do{%
```

```

        \settoheight{\dtl@tmplength}{\dtl@thislabel}%
        \ifdim\dtl@tmplength>\dtl@yticlabelwidth
            \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
        \fi
    }%
\fi
\fi
\fi

```

Start the picture.

```
\begin{tikzpicture}
```

Set the  $x$  and  $y$  unit vectors.

```

\pgfsetxvec{\pgfpoint{1pt}{0pt}}%
\pgfsetyvec{\pgfpoint{0pt}{1pt}}%

```

Set the transformation matrix, so user can plot things using the data co-ordinate space, but scope it, so it doesn't affect any plot marks later

```

\begin{scope}
\pgftransformcm{\dtl@scale@x}{0}{0}{\dtl@scale@y}%
{\pgfpoint{\dtl@offset@x pt}{\dtl@offset@y pt}}%

```

Add any extra information the user requires

```

\let\dtlplotatbegin\dtlplotatbegin
\DTLplotatbegin

```

Determine whether to put a box around the plot

```

\ifDTLbox
\draw (\DTLminX,\DTLminY) -- (\DTLmaxX,\DTLminY) --
(\DTLmaxX,\DTLmaxY) -- (\DTLminX,\DTLmaxY) --
cycle;
\else

```

Plot  $x$  axis if required.

```

\ifDTLxaxis
\expandafter\draw\expandafter[\DTLXAxisStyle]
(\DTLminX,\DTLminY) -- (\DTLmaxX,\DTLminY);
\fi

```

Plot  $y$  axis if required.

```

\ifDTLyaxis
\expandafter\draw\expandafter[\DTLYAxisStyle]
(\DTLminX,\DTLminY) -- (\DTLminX,\DTLmaxY);
\fi
\fi

```

Plot grid if required

```

\ifDTLgrid
\ifDTLxminor
\@for\dtl@thistick:=\dtl@xminorlist\do{%
\expandafter\draw\expandafter[\DTLminorgridstyle]
(\dtl@thistick,\DTLminY) -- (\dtl@thistick,\DTLmaxY);
}

```

```

    }%
\fi
\ifDTLyminortics
  \@for\dtl@thistick:=\dtl@yminorticlist\do{%
    \expandafter\draw\expandafter[\DTLminorgridstyle]
      (\DTLminX,\dtl@thistick) -- (\DTLmaxX,\dtl@thistick);
  }%
\fi
\@for\dtl@thistick:=\dtl@xticlist\do{%
  \expandafter\draw\expandafter[\DTLmajorgridstyle]
    (\dtl@thistick,\DTLminY) -- (\dtl@thistick,\DTLmaxY);
}%
\@for\dtl@thistick:=\dtl@yticlist\do{%
  \expandafter\draw\expandafter[\DTLmajorgridstyle]
    (\DTLminX,\dtl@thistick) -- (\DTLmaxX,\dtl@thistick);
}%
\fi

```

Plot x tics if required.

```
\ifDTLxtics
```

Get tick length in terms of canvas co-ordinates

```

\dtlsub{\dtl@ticklength}{\number\DTLticklength}{-\dtl@offset@y}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@y}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%

```

Get tick label offset in terms of canvas co-ordinates

```

\addtolength\dtl@xticlabelheight{\DTLticklabeloffset}%
\dtlsub{\dtl@ticlabeloffset}{\number\dtl@xticlabelheight}{-\dtl@offset@y}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@scale@y}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{65536}%

```

Iterate through tick list.

```
\@for\dtl@thistick:=\dtl@xticlist\do{%
```

Store tick label in \dtl@thislabel

```

\let\dtl@thisticklabel\dtl@thistick
\ifx\dtl@xticlabels\relax
  \dtlround{\dtl@thislabel}{\dtl@thistick}
  {\c@DTLplotroundXvar}%
\else
  \dtl@chopfirst\dtl@xticlabels\dtl@thislabel\dtl@rest
  \let\dtl@xticlabels=\dtl@rest
\fi

```

Draw tick.

```

\ifDTLxticsin
  \draw (\dtl@thistick,\DTLminY) -- ++(0,\dtl@ticklength);
  \draw (\dtl@thistick,\DTLminY)
    ++ (0,-\dtl@ticlabeloffset) node {\dtl@thislabel};
\else
  \draw (\dtl@thistick,\DTLminY) -- ++(0,-\dtl@ticklength)

```

```

        ++ (0,-\dtl@ticlabeloffset) node {\dtl@thislabel};
    \fi

```

Draw opposite tick, if box setting is on.

```

    \ifDTLbox
    \ifDTLxticsin
        \draw (\dtl@thistick,\DTLmaxY) -- ++(0,-\dtl@ticklength);
    \else
        \draw (\dtl@thistick,\DTLmaxY) -- ++(0,\dtl@ticklength);
    \fi
    \fi
} %
\fi

```

Plot  $x$  label if required.

```

\ifx\dtl@xlabel\relax
\else

```

Get baseline in terms of canvas co-ordinates

```

\dtladd{\dtl@x}{\number\baselineskip}{\dtl@offset@y}%
\dtldiv{\dtl@x}{\dtl@x}{\dtl@scale@y}%
\dtldiv{\dtl@x}{\dtl@x}{65536}%
\dtladd{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@x}%

```

Get halfway position

```

\dtlmul{\dtl@x}{\dtl@dx}{0.5}%
\draw (\DTLminX,\DTLminY) ++(\dtl@x,-\dtl@ticlabeloffset)
node[anchor=north] {\dtl@xlabel};
\fi

```

Plot the  $x$  minor ticks if required

```

\ifDTLxminortics

```

Get tick length in terms of canvas co-ordinates

```

\dtlsub{\dtl@ticklength}{\number\DTLminorticticklength}{-\dtl@offset@y}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@y}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%

```

Iterate through minor ticks.

```

\@for\dtl@thistick:=\dtl@xminorticlist\do{%
    \ifDTLxticsin
        \draw (\dtl@thistick,\DTLminY) -- ++(0,\dtl@ticklength);
        \draw (\dtl@thistick,\DTLminY)
            ++ (0,-\dtl@ticlabeloffset) node[anchor=north] {\dtl@thislabel};
    \else
        \draw (\dtl@thistick,\DTLminY) -- ++(0,-\dtl@ticklength)
            ++ (0,-\dtl@ticlabeloffset) node[anchor=north] {\dtl@thislabel};
    \fi
}
\fi

```

Draw opposite tick, if box setting is on.

```

\ifDTLbox
\ifDTLxticsin

```

```

        \draw (\dtl@thistick,\DTLmaxY) -- ++(0,-\dtl@ticklength);
    \else
        \draw (\dtl@thistick,\DTLmaxY) -- ++(0,\dtl@ticklength);
    \fi
\fi
}%
\fi

```

Plot y tics if required.

```
\ifDTLytics
```

Get tick length in terms of canvas co-ordinates

```

\dtlsub{\dtl@ticklength}{\number\DTLticklength}{-\dtl@offset@x}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@x}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%

```

Get tick label offset in terms of canvas co-ordinates

```

\dtladd{\dtl@ticlabeloffset}{\number\DTLticlabeloffset}{0}%
\dtlsub{\dtl@ticlabeloffset}{\number\DTLticlabeloffset}{-\dtl@offset@x}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@scale@x}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{65536}%

```

Iterate through tick list.

```
\@for\dtl@thistick:=\dtl@yticlist\do{%
```

Store tick label in \dtl@thislabel

```

\let\dtl@thisticklabel\dtl@thistick
\ifx\dtl@yticlabels\relax
    \dtlround{\dtl@thislabel}{\dtl@thistick}
        {\c@DTLplotroundXvar}%
\else
    \dtl@chopfirst\dtl@yticlabels\dtl@thislabel\dtl@rest
    \let\dtl@yticlabels=\dtl@rest
\fi

```

Draw tick.

```

\ifDTLyticsin
    \draw (\DTLminX,\dtl@thistick) -- ++(\dtl@ticklength,0);
    \draw (\DTLminX,\dtl@thistick)
        ++ (-\dtl@ticlabeloffset,0) node[anchor=east] {\dtl@thislabel};
\else
    \draw (\DTLminX,\dtl@thistick) -- ++(-\dtl@ticklength,0)
        ++ (-\dtl@ticlabeloffset,0) node[anchor=east] {\dtl@thislabel};
\fi

```

Draw opposite tick, if box setting is on.

```

\ifDTLbox
    \ifDTLyticsin
        \draw (\DTLmaxX,\dtl@thistick) -- ++(-\dtl@ticklength,0);
    \else
        \draw (\DTLmaxX,\dtl@thistick) -- ++(\dtl@ticklength,0);
    \fi

```



```

    \fi
  }%
\fi

```

Plot  $y$  label if required.

```

\ifx\dtl@ylabel\relax
\else
  \setlength{\dtl@tmplength}{\baselineskip}%
  \addtolength{\dtl@tmplength}{\dtl@yticlabelwidth}%
  \addtolength{\dtl@tmplength}{\DTLticklabeloffset}%
  \dtlsub{\dtl@ticlabeloffset}{\number\dtl@tmplength}{-\dtl@offset@x}%
  \dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@scale@x}%
  \dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{65536}%

```

Get halfway position

```

\dtlmul{\dtl@y}{\dtl@dy}{0.5}%
\draw (\DTLminX,\DTLminY) ++(-\dtl@ticlabeloffset,\dtl@y)
  node[rotate=90,anchor=south] {\dtl@ylabel};
\fi

```

Plot the  $y$  minor ticks if required

```

\ifDTLyminortics

```

Get tick length in terms of canvas co-ordinates

```

\dtlsub{\dtl@ticklength}{\number\DTLminorticklength}{-\dtl@offset@x}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@x}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%

```

Iterate through minor ticks.

```

\@for\dtl@thistick:=\dtl@yminorticlist\do{%
  \ifDTLyticsin
    \draw (\DTLminX,\dtl@thistick) -- ++(\dtl@ticklength,0);
  \else
    \draw (\DTLminX,\dtl@thistick) -- ++(-\dtl@ticklength,0);
  \fi
}

```

Draw opposite tick, if box setting is on.

```

\ifDTLbox
  \ifDTLyticsin
    \draw (\DTLmaxX,\dtl@thistick) -- ++(-\dtl@ticklength,0);
  \else
    \draw (\DTLmaxX,\dtl@thistick) -- ++(\dtl@ticklength,0);
  \fi
\fi
}
\fi

```

End the transformation scope. (Don't want marker shapes to be scaled or skewed.)

```

\end{scope}

```

Iterate through each database

```

\@for\dtl@thisdb:=#2\do{%

```

Get the current plot mark colour.

```
\ifx\dtl@plotmarkcolorlist\@empty
  \let\dtl@plotmarkcolorlist=\DTLplotmarkcolors
\fi
\dtl@chopfirst\dtl@plotmarkcolorlist\dtl@thisplotmarkcolor
  \dtl@remainder
\let\dtl@plotmarkcolorlist=\dtl@remainder
```

Get the current plot mark, and store in \dtl@mark

```
\ifDTLshowmarkers
  \ifx\dtl@plotmarklist\@empty
    \let\dtl@plotmarklist=\DTLplotmarks
  \fi
  \dtl@chopfirst\dtl@plotmarklist\dtl@thisplotmark
    \dtl@remainder
  \let\dtl@plotmarklist=\dtl@remainder
  \ifx\dtl@thisplotmark\relax
    \let\dtl@mark=\relax
  \else
    \expandafter\toks@\expandafter{\dtl@thisplotmark}%
    \ifx\dtl@thisplotmarkcolor\@empty
      \edef\dtl@mark{\the\toks@}%
    \else
      \edef\dtl@mark{%
        \noexpand\color{\dtl@thisplotmarkcolor}%
        \the\toks@}%
    \fi
  \fi
\else
  \let\dtl@mark=\relax
\fi
```

Get the current plot line colour.

```
\ifx\dtl@plotlinecolorlist\@empty
  \let\dtl@plotlinecolorlist=\DTLplotlinecolors
\fi
\dtl@chopfirst\dtl@plotlinecolorlist\dtl@thisplotlinecolor
  \dtl@remainder
\let\dtl@plotlinecolorlist=\dtl@remainder
```

Get the current line style, and store in \dtl@linestyle

```
\ifDTLshowlines
  \ifx\dtl@plotlinelist\@empty
    \let\dtl@plotlinelist=\DTLplotlines
  \fi
  \dtl@chopfirst\dtl@plotlinelist\dtl@thisplotline
    \dtl@remainder
  \let\dtl@plotlinelist=\dtl@remainder
  \expandafter\ifx\dtl@thisplotline\relax
  \let\dtl@linestyle=\relax
```

```

\else
  \expandafter\toks@\expandafter{\dtl@thisplotline}%
  \ifx\dtl@thisplotlinecolor\@empty
    \edef\dtl@linestyle{\the\toks@}%
  \else
    \edef\dtl@linestyle{%
      \noexpand\color{\dtl@thisplotlinecolor}%
      \the\toks@}%
  \fi
\fi
\let\dtl@linestyle=\relax
\fi

```

Append this plot setting to the legend.

```

\ifnum\dtl@legendsetting>0\relax
  \dtl@chopfirst\dtl@legendlabels\dtl@thislabel\dtl@rest
  \let\dtl@legendlabels=\dtl@rest
  \expandafter\toks@\expandafter{\dtl@mark}%
  \expandafter\@dtl@toks\expandafter{\dtl@linestyle}%
  \edef\dtl@addtolegend{\noexpand\DTLaddtoplotlegend
    {\the\toks@}{\the\@dtl@toks}{\dtl@thislabel}}%
  \dtl@addtolegend
\fi

```

Store stream in \dtl@stream

```

\def\dtl@stream{\pgfplotstreamstart}%

```

Only plot points that lie inside bounds.

```

\@sDTLforeach[#1]{\dtl@thisdb}{\dtl@x=\dtl@xkey,%
  \dtl@y=\dtl@ykey}{%
  \DTLconverttodecimal{\dtl@x}{\dtl@decx}%
  \DTLconverttodecimal{\dtl@y}{\dtl@decy}%
  \ifthenelse{%
    \DTLisclosedbetween{\dtl@x}{\DTLminX}{\DTLmaxX}%
    \and
    \DTLisclosedbetween{\dtl@y}{\DTLminY}{\DTLmaxY}%
  }%
  {%
    \expandafter\toks@\expandafter{\dtl@stream}%
  }%
}

```

Apply transformation to co-ordinates

```

\dtl@mul{\dtl@decx}{\dtl@decx}{\dtl@scale@x}%
\dtl@add{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtl@round{\dtl@decx}{\dtl@decx}{1}%
\dtl@mul{\dtl@decy}{\dtl@decy}{\dtl@scale@y}%
\dtl@add{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\dtl@round{\dtl@decy}{\dtl@decy}{1}%
\edef\dtl@stream{\the\toks@
  \noexpand\pgfplotstreampoint
  {\noexpand\pgfpointxy{\dtl@decx}{\dtl@decy}}}%

```

```

    }{}%
}%
\expandafter\toks@\expandafter{\dtl@stream}%
\edef\dtl@stream{\the\toks@\noexpand\pgfplotstreamend}%

```

End plot stream and draw path.

```

\ifx\dtl@linestyle\relax
\else
  \begin{scope}
    \dtl@linestyle
    \pgfplotshandlerlineto
    \dtl@stream
    \pgfusepath{stroke}
  \end{scope}
\fi
\ifx\dtl@mark\relax
\else
  \begin{scope}
    \pgfplotshandlermark{\dtl@mark}%
    \dtl@stream
    \pgfusepath{stroke}
  \end{scope}
\fi
}%

```

Plot legend if required.

```

\ifcase\dtl@legendsetting
% none
\or % north
  \dtlmlul{\dtl@decx}{\dtl@dx}{0.5}%
  \dtladd{\dtl@decx}{\DTLminX}{\dtl@decx}%
  \dtlmlul{\dtl@decx}{\dtl@decx}{\dtl@scale@x}%
  \dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
  \dtlmlul{\dtl@decy}{\DTLmaxY}{\dtl@scale@y}%
  \dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
  \draw (\dtl@decx,\dtl@decy) ++(0,-\DTLlegendyoffset)
    node[anchor=north]
    {\DTLformatlegend
     {\begin{tabular}{c1}\dtl@legend\end{tabular}}}%
  };
\or % north east
  \dtlmlul{\dtl@decx}{\DTLmaxX}{\dtl@scale@x}%
  \dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
  \dtlmlul{\dtl@decy}{\DTLmaxY}{\dtl@scale@y}%
  \dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
  \draw (\dtl@decx,\dtl@decy) ++(-\DTLlegendxoffset,-\DTLlegendyoffset)
    node[anchor=north east]
    {\DTLformatlegend
     {\begin{tabular}{c1}\dtl@legend\end{tabular}}}%
  };

```

```

\or % east
\dtlmlul{\dtl@decy}{\dtl@dy}{0.5}%
\dtladd{\dtl@decy}{\DTLminY}{\dtl@decy}%
\dtlmlul{\dtl@decy}{\dtl@decy}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\dtlmlul{\dtl@decx}{\DTLmaxX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\draw (\dtl@decx,\dtl@decy) ++(-\DTLlegendxoffset,0)
node[anchor=east]
{\DTLformatlegend
{\begin{tabular}{c1}\dtl@legend\end{tabular}}%
};
\or % south east
\dtlmlul{\dtl@decx}{\DTLmaxX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtlmlul{\dtl@decy}{\DTLminY}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(-\DTLlegendxoffset,\DTLlegendyoffset)
node[anchor=south east]
{\DTLformatlegend
{\begin{tabular}{c1}\dtl@legend\end{tabular}}%
};
\or % south
\dtlmlul{\dtl@decx}{\dtl@dx}{0.5}%
\dtladd{\dtl@decx}{\DTLminX}{\dtl@decx}%
\dtlmlul{\dtl@decx}{\dtl@decx}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtlmlul{\dtl@decy}{\DTLminY}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(0,\DTLlegendyoffset)
node[anchor=south]
{\DTLformatlegend
{\begin{tabular}{c1}\dtl@legend\end{tabular}}%
};
\or % south west
\dtlmlul{\dtl@decx}{\DTLminX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtlmlul{\dtl@decy}{\DTLminY}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(\DTLlegendxoffset,\DTLlegendyoffset)
node[anchor=south west]
{\DTLformatlegend
{\begin{tabular}{c1}\dtl@legend\end{tabular}}%
};
\or % west
\dtlmlul{\dtl@decy}{\dtl@dy}{0.5}%
\dtladd{\dtl@decy}{\DTLminY}{\dtl@decy}%
\dtlmlul{\dtl@decy}{\dtl@decy}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%

```

```

\dtlmlul{\dtl@decx}{\DTLminX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\draw (\dtl@decx,\dtl@decy) ++(\DTLlegendxoffset,0)
  node[anchor=west]
  {\DTLformatlegend
  {\begin{tabular}{c1}\dtl@legend\end{tabular}}}%
  };
\or % north west
\dtlmlul{\dtl@decx}{\DTLminX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtlmlul{\dtl@decy}{\DTLmaxY}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(\DTLlegendxoffset,-\DTLlegendyoffset)
  node[anchor=north west]
  {\DTLformatlegend
  {\begin{tabular}{c1}\dtl@legend\end{tabular}}}%
  };
\fi

```

Set the transformation matrix, so user can plot things using the data co-ordinate space

```

\pgftransformcm{\dtl@scale@x}{0}{0}{\dtl@scale@y}%
{\pgfpoint{\dtl@offset@x pt}{\dtl@offset@y pt}}%

```

End hook

```

\let\dtlpllothandlermark\@dtlpllothandlermark
\DTLplotatendtikz
\end{tikzpicture}
\fi
\fi
\egroup
}

```

`\dtl@getbounds` Extract bounds:

```

\def\dtl@getbounds#1,#2,#3,#4\@nil{%
\def\DTLminX{#1}%
\def\DTLminY{#2}%
\def\DTLmaxX{#3}%
\def\DTLmaxY{#4}%
\dtlifnumgt{\DTLminX}{\DTLmaxX}
{%
\PackageError{dataplot}{Min X > Max X in bounds #1,#2,#3,#4}{%
The bounds must be specified as minX,minY,maxX,maxY}%
}%
\dtlifnumgt{\DTLminY}{\DTLmaxY}
{%
\PackageError{dataplot}{Min Y > Max Y in bounds #1,#2,#3,#4}{%
The bounds must be specified as minX,minY,maxX,maxY}%
}%
}

```

constructticklist

```
\dtl@constructticklist{<min>}{<max>}{<min gap>}{<list>}
```

Constructs a list of tick points between  $\langle min \rangle$  and  $\langle max \rangle$  and store in  $\langle list \rangle$  (a control sequence.)

```
\newcommand*\dtl@constructticklist[4]{%
  \DTLifFPopenbetween{0}{#1}{#2}%
  {%
```

Tick list straddles the origin.

```
  \dtlsub{\@dtl@width}{0}{#1}%
  \dtldiv{\@dtl@neggap}{\@dtl@width}{10}%
  \dtlifnumlt{\@dtl@neggap}{#3}%
  {%
    \edef\@dtl@neggap{#3}%
  }%
  {}%
  \dtldiv{\@dtl@posgap}{#2}{10}%
  \dtlifnumlt{\@dtl@posgap}{#3}%
  {%
    \edef\@dtl@posgap{#3}%
  }%
  {}%
  \dtlmax{\@dtl@gap}{\@dtl@neggap}{\@dtl@posgap}%
```

Don't construct a list if minimum gap is greater than plot width

```
  \dtlifnumgt{\@dtl@gap}{\@dtl@width}%
  {}%
  {%
    \dtl@constructticklistwithgapz{#1}{#2}{#4}{\@dtl@gap}%
  }%
  }%
  {%
```

Tick list doesn't straddle the origin.

```
  \dtlsub{\@dtl@width}{#2}{#1}%
  \dtldiv{\@dtl@gap}{\@dtl@width}{10}%
  \dtlifnumlt{\@dtl@gap}{#3}%
  {%
```

Don't construct a list if minimum gap is greater than plot width

```
  \dtlifnumgt{#3}{\@dtl@width}%
  {%
    \def#4{#1,#2}%
  }%
  {}%
  {%
    \dtl@constructticklistwithgap{#1}{#2}{#4}{#3}%
  }
  }%
  {%
```

```

        \dtl@constructticklistwithgap{#1}{#2}{#4}{\@dtl@gap}%
    }%
}
}

```

tticklistwithgap

```
\dtl@constructticklistwithgap{<min>}{<max>}{<list>}{<gap>}
```

Constructs a list of tick points between  $\langle min \rangle$  and  $\langle max \rangle$  and store in  $\langle list \rangle$  (a control sequence) using the gap given by  $\langle gap \rangle$  where the gap is given in user co-ordinates.

```

\newcommand*\dtl@constructticklistwithgap}[4]{%
\edef\@dtl@thistick{#1}%
\edef#3{#1}%
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\@dtl@thistick}{#1}{#2}}{%
\expandafter\toks@\expandafter{\@dtl@thistick}%
\edef#3{#3,\the\toks@}%
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
}%
\expandafter\toks@\expandafter{#2}%
\edef#3{#3,\the\toks@}%
}

```

tticklistwithgapz

```
\dtl@constructticklistwithgapz{<min>}{<max>}{<list>}{<gap>}
```

Constructs a list of tick points between  $\langle min \rangle$  and  $\langle max \rangle$  and store in  $\langle list \rangle$  (a control sequence) using the gap given by  $\langle gap \rangle$  where the tick list straddles zero.

```

\newcommand*\dtl@constructticklistwithgapz}[4]{%
\edef\@dtl@thistick{0}%
\edef#3{0}%
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\@dtl@thistick}{0}{#2}}{%
{%
\expandafter\toks@\expandafter{\@dtl@thistick}%
\edef#3{#3,\the\toks@}%
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
}%
\expandafter\toks@\expandafter{#2}%
\edef#3{#3,\the\toks@}%
\dtlifnumeq{#1}{0}%
}%
{%
\edef\@dtl@thistick{0}%
\dtlsub{\@dtl@thistick}{\@dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\@dtl@thistick}{#1}{0}}%
}
}

```



```

    {%
      \expandafter\toks@\expandafter{\@dtl@thistick}%
      \edef#3{\the\toks@,#3}%
      \dtlsub{\@dtl@thistick}{\@dtl@thistick}{#4}%
    }%
    \expandafter\toks@\expandafter{#1}%
    \edef#3{\the\toks@,#3}%
  }%
}

```

uctminorticklist

```
\dtl@constructminorticklist{<min>}{<max>}{<scale factor>}{<list>}
```

Constructs a list of minor tick points between  $\langle min \rangle$  and  $\langle max \rangle$  and append to  $\langle list \rangle$  (a control sequence.)

```

\newcommand*{\dtl@constructminorticklist}[4]{%
  \dtlsub{\@dtl@width}{#2}{#1}%
  \dtlmlf{\@dtl@width}{\@dtl@width}{#3}%
  \dtldiv{\@dtl@gap}{\@dtl@width}{10}%
  \setlength\dtl@tmplength{\@dtl@gap sp}%
  \ifdim\dtl@tmplength<\DTLminminortickgap
    \dtldiv{\@dtl@gap}{\@dtl@width}{4}%
    \setlength\dtl@tmplength{\@dtl@gap sp}%
  \ifdim\dtl@tmplength<\DTLminminortickgap
    \dtldiv{\@dtl@gap}{\@dtl@width}{2}%
    \setlength\dtl@tmplength{\@dtl@gap sp}%
  \ifdim\dtl@tmplength<\DTLminminortickgap
    \let\@dtl@gap=\@dtl@width
  \fi
  \fi
  \fi
  \dtldiv{\@dtl@gap}{\@dtl@gap}{#3}%
  \dtl@constructticklistwithgapex{#1}{#2}{\dtl@tmp}{\@dtl@gap}%
  \ifx#4@empty
    \let#4=\dtl@tmp
  \else
    \expandafter\toks@\expandafter{#4}%
    \edef#4{#4,\dtl@tmp}%
  \fi
}

```

icklistwithgapex

```
\dtl@constructticklistwithgapex{<min>}{<max>}{<list>}{<gap>}
```

Constructs a list of tick points between  $\langle min \rangle$  and  $\langle max \rangle$  and store in  $\langle list \rangle$  (a control sequence) using the gap given by  $\langle gap \rangle$  where the gap is given in user co-ordinates. The end

points are excluded from the list.

```

\newcommand*{\dtl@constructticklistwithgapex}[4]{%
\edef\dtl@thistick{#1}%
\let#3=\@empty
\dtladd{\dtl@thistick}{\dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\dtl@thistick}{#1}{#2}}{%
\expandafter\toks@\expandafter{\dtl@thistick}%
\ifx#3\@empty
\edef#3{\the\toks@}%
\else
\edef#3{#3,\the\toks@}%
\fi
\dtladd{\dtl@thistick}{\dtl@thistick}{#4}%
}%
}

```

Laddtopplotlegend

```
\DTLaddtopplotlegend{<marker>}{<line style>}{<label>}
```

Adds entry to legend.

```

\newcommand*{\DTLaddtopplotlegend}[3]{%
\def\dtl@legendline{}%
\ifx\relax#2\relax
\else
\toks@{#2%
\pgfpathmoveto{\pgfpoint{-10pt}{0pt}}%
\pgfpathlineto{\pgfpoint{10pt}{0pt}}%
\pgfusepath{stroke}}%
\edef\dtl@legendline{\the\toks@}%
\fi
\ifx\relax#1\relax
\else
\toks@{#1}%
\expandafter\dtl@toks\expandafter{\dtl@legendline}%
\edef\dtl@legendline{\the\dtl@toks\the\toks@}%
\fi
\expandafter\toks@\expandafter{\dtl@legendline}%
\ifx\dtl@legend\@empty
\xdef\dtl@legend{\noexpand\tikz\the\toks@; \noexpand & #3}%
\else
\expandafter\dtl@toks\expandafter{\dtl@legend}%
\xdef\dtl@legend{\the\dtl@toks\noexpand\\%
\noexpand\tikz\the\toks@; \noexpand & #3}%
\fi
}

```

# 10 person.sty

## 10.1 Package Declaration

Package identification:

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{person}[2018/12/07 v2.31 (NLCT)]
```

Requires the ifthen package.

```
\RequirePackage{ifthen}
\RequirePackage{datatool}
```

## 10.2 Defining People

`people` Keep count of the number of people who have been defined:

```
\newcounter{people}
```

`person` Temporary counter

```
\newcounter{person}
```

`\@people@list` Keep a list of labels for each person who has been defined:

```
\newcommand*{\@people@list}{,}
```

`get@firstperson` Get the first person's name in `\@people@list`, and store in the argument (which must be a control sequence.)

```
\newcommand*{\@get@firstperson}[1]{%
\expandafter\@get@firstperson\@people@list,\@nil{#1}}
\def\@get@firstperson,#1,#2\@nil#3{%
\def#3{#1}%
}
```

`\malelabels` List of labels that can be used to indicate that a person is male (when defining a person using `\newperson`).

```
\newcommand*{\malelabels}{male, Male, MALE, M, m}
```

`\addmalelabel` Adds a label to the list of male labels.

```
\newcommand*{\addmalelabel}[1]{%
\expandafter\@dtl@toksA\expandafter{\malelabels}%
\expandafter\@dtl@toksB\expandafter{#1}%
\edef\malelabels{\the\@dtl@toksA,\the\@dtl@toksB}%
}
```

`\addfemalelabel` Adds a label to the list of female labels.

```

\newcommand*\addfemalelabel}[1]{%
  \expandafter\@dtl@toksA\expandafter{\femalelabels}%
  \expandafter\@dtl@toksB\expandafter{#1}%
  \edef\femalelabels{\the\@dtl@toksA,\the\@dtl@toksB}%
}

```

`\femalelabels` List of labels that can be used to indicate that a person is female (when defining a person using `\newperson`).

```

\newcommand*\femalelabels{female,Female,FEMALE,F,f}

```

`\ifmalelabel` Determines if first argument is contained in the list of male labels. (One level expansion is performed on the first object in first argument.) If true does second argument, otherwise does third argument.

```

\newcommand*\ifmalelabel}[3]{%
  \expandafter\DTLifinlist\expandafter{#1}{\malelabels}{#2}{#3}%
}

```

`\iffemalelabel` Determines if first argument is contained in the list of female labels. (One level expansion is performed on the first object in first argument.) If true does second argument, otherwise does third argument.

```

\newcommand*\iffemalelabel}[3]{%
  \expandafter\DTLifinlist\expandafter{#1}{\femalelabels}{#2}{#3}%
}

```

`\newperson` Define a new person. The optional argument specifies a label with which to refer to that person. If omitted, `anon` is used. If more than one person is defined, the optional argument will be required to specify a unique label. The compulsory arguments are the person's full name, their familiar name and their gender.

```

\newcommand*\newperson}[4][anon]{%
  \ifundefined{person@#1@name}%
  {%
    \ifmalelabel{#4}%
    {%
      \expandafter\gdef\csname person@#1@gender\endcsname{male}%
    }%
    {%
      \iffemalelabel{#4}%
      {%
        \expandafter\gdef\csname person@#1@gender\endcsname{female}%
      }%
      {%
        \PackageError{person}{Unknown gender ‘#4’ for person
          ‘#1’}{Allowed gender labels are: \malelabels\space or
          \femalelabels}%
        \namedef{person@#1@gender}{other}%
      }%
    }%
  }%
}

```

```

}%
\expandafter
  \protected@xdef\csname person@#1@fullname\endcsname{#2}%
\expandafter
  \protected@xdef\csname person@#1@name\endcsname{#3}%
\protected@xdef\@people@list{\@people@list#1,}%
\stepcounter{people}%
}%
{%
  \PackageError{person}{Person ‘#1’ has already been defined}{-}%
}%
}

```

### 10.3 Remove People

`\removeperson` Removes person identified by their label from the list.

```

\newcommand*{\removeperson}[1][anon]{%
  \edef\@person@label{#1}%
  \expandafter\@removeperson\expandafter{\@person@label}%
}

```

The label has to be full expanded for the internal command.

```

\newcommand*{\@removeperson}[1]{%
  \ifpersonexists{#1}%
  {%

```

Remove label from list of people.

```

  \def\@remove@person##1,##2\@nil{%
    \def\@prsn@pre{##1}\def\@prsn@post{##2}}%
  \expandafter\@remove@person\@people@list\@nil
  \xdef\@people@list{\@prsn@pre,\@prsn@post}%

```

Decrement number of people:

```

  \addtocounter{people}{-1}%

```

Undefine associated control sequences:

```

  \expandafter\global\expandafter
    \let\csname person@#1@name\endcsname\undefined
  \expandafter\global\expandafter
    \let\csname person@#1@fullname\endcsname\undefined
  \expandafter\global\expandafter
    \let\csname person@#1@gender\endcsname\undefined
}%
{%
  \PackageError{person}{Can't remove person ‘#1’: no such
  person}{-}%
}%
}

```

`\removepeople` Removes the people listed.

```

\newcommand*{\removepeople}[1]{%
  \@for\@thisperson:=#1\do{%
    \ifx\@thisperson\@empty
    \else
      \expandafter\removeperson\expandafter[\@thisperson]%
    \fi
  }%
}

```

`\removeallpeople` Removes everyone.

```

\newcommand*{\removeallpeople}{%
  \@for\@thisperson:=\@people@list\do{%
    \expandafter\global\expandafter
      \let\csname person@\@thisperson @name\endcsname\undefined
    \expandafter\global\expandafter
      \let\csname person@\@thisperson @fullname\endcsname\undefined
    \expandafter\global\expandafter
      \let\csname person@\@thisperson @gender\endcsname\undefined
  }%
  \setcounter{people}{0}%
  \gdef\@people@list{,}%
}

```

## 10.4 Conditionals and Loops

`\ifpersonexists` If person whose label is given by the first argument exists, then do the second argument otherwise do third argument.

```

\newcommand{\ifpersonexists}[3]{%
  \@ifundefined{person@#1@name}{#3}{#2}%
}

```

`\ifmale` If the person given by the label in the first argument is male, do the second argument, otherwise do the third argument.

```

\newcommand{\ifmale}[3]{%
  \ifpersonexists{#1}%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \ifx\@gender\@male@label
      #2%
    \else
      #3%
    \fi
  }%
  {%
    \PackageError{person}{Person ‘#1’ doesn’t exist.}{}%
  }%
}
\def\@male@label{male}

```

`\ifallmale` If all people listed in first argument are male, do the second argument otherwise do the third argument. If the first argument is omitted, all defined people are checked.

```

\newcommand{\ifallmale}[3][\@people@list]{%
  \@for\@thisperson:=#1\do{%
    \ifpersonexists{\@thisperson}%
    {%
      \edef\@gender{\csname person@\@thisperson @gender\endcsname}%
      \ifx\@gender\@male@label
      \else
        \@endfortrue
      \fi
    }%
    {%
      \PackageError{person}{Person ‘#1’ doesn’t exist.}{}%
    }%
  }%
\if@endfor
#3%
\else
#2%
\fi
}

```

`\iffemale` If the person given by the label in the first argument is female, do the second argument, otherwise do the third argument.

```

\newcommand{\iffemale}[3]{%
  \ifpersonexists{#1}%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \ifx\@gender\@female@label
      #2%
    \else
      #3%
    \fi
  }%
  {%
    \PackageError{person}{Person ‘#1’ doesn’t exist.}{}%
  }%
}
\def\@female@label{female}

```

`\ifallfemale` If all people listed in first argument are female, do the second argument otherwise do the third argument.

```

\newcommand{\ifallfemale}[3][\@people@list]{%
  \@for\@thisperson:=#1\do{%
    \edef\@gender{\csname person@\@thisperson @gender\endcsname}%
    \ifx\@gender\@female@label
    \else
      \@endfortrue
    \fi
  }%
}

```

```

    \fi
  }%
  \if@endfor
  #3%
  \else
  #2%
  \fi
}

```

```

\foreachperson \foreachperson(<name cs>,<full name cs>,<gender cs>,<label cs>)\in
{<list>}\do{<body>}

```

Iterates through list of people the `\in{<list>}` is optional. If omitted, the list of all defined people is used.

```

\def\foreachperson(#1,#2,#3,#4)#5{%
  \ifx#5\in
    \def\@do@foreachperson{\@foreachperson(#1,#2,#3,#4)#5}%
  \else
    \def\@do@foreachperson{%
      \@foreachperson(#1,#2,#3,#4)\in\@people@list#5}%
  \fi
  \@do@foreachperson
}
\long\def\@foreachperson(#1,#2,#3,#4)\in#5\do#6{%
  \@for#4:=#5\do{%
    \ifx#4\@empty
    \else
      \ifpersonexists{#4}%
      {%
        \expandafter
        \let\expandafter#1\csname person@#4@name\endcsname
        \expandafter
        \let\expandafter#2\csname person@#4@fullname\endcsname
        \expandafter
        \let\expandafter#3\csname person@#4@gender\endcsname
        \ifx#3\@male@label
        \let#3\malename
        \else
        \ifx#3\@female@label
        \let#3\femalename
        \fi
        \fi
        #6%
      }%
      {%
        \PackageError{person}{Person ‘#4’ doesn’t exist}{-}%
      }%
    }%
  }%
}

```



```

    \fi
  }%
}

```

## 10.5 Predefined Words

These commands should be redefined if you are writing in another language, but note that these are structured according to English grammar.

```

\malepronoun
\newcommand*\malepronoun}{he}

\femalepronoun
\newcommand*\femalepronoun}{she}

\pluralpronoun
\newcommand*\pluralpronoun}{they}

\maleobjpronoun
\newcommand*\maleobjpronoun}{him}

\femaleobjpronoun
\newcommand*\femaleobjpronoun}{her}

\pluralobjpronoun
\newcommand*\pluralobjpronoun}{them}

\malepossadj
\newcommand*\malepossadj}{his}

\femalepossadj
\newcommand*\femalepossadj}{her}

\pluralpossadj
\newcommand*\pluralpossadj}{their}

\maleposspronoun
\newcommand*\maleposspronoun}{his}

\femaleposspronoun
\newcommand*\femaleposspronoun}{hers}

\pluralposspronoun
\newcommand*\pluralposspronoun}{theirs}

\malechild
\newcommand*\malechild}{son}

```

```

\femalechild
\newcommand*\femalechild{daughter}

\pluralchild
\newcommand*\pluralchild{children}

\malechildren
\newcommand*\malechildren{sons}

\femalechildren
\newcommand*\femalechildren{daughters}

\maleparent
\newcommand*\maleparent{father}

\femaleparent
\newcommand*\femaleparent{mother}

\pluralparent
\newcommand*\pluralparent{parents}

\malesibling
\newcommand*\malesibling{brother}

\femalesibling
\newcommand*\femalesibling{sister}

\pluralsibling
\newcommand*\pluralsibling{siblings}

\malesiblings
\newcommand*\malesiblings{brothers}

\femalesiblings
\newcommand*\femalesiblings{sisters}

\andname Define \andname if it hasn't already been defined:
\providecommand*\andname{and}

\malename
\newcommand*\malename{male}

\femalename
\newcommand*\femalename{female}

\personsep Separator to use between people (but not the between the last two).
\newcommand*\personsep{, }

```

`\personlastsep` Separator to use between last two people.  
`\newcommand*{\personlastsep}{\space\andname\space}`

`\twopeoplesep` Separator to use when list only contains two people.  
`\newcommand*{\twopeoplesep}{\space\andname\space}`

## 10.6 Displaying Information

`\personfullname` The person's full name can be displayed using `\personfullname [⟨label⟩]`, where `⟨label⟩` is the unique label used when defining that person. If `⟨label⟩` is omitted, `anon` is used.

```
\newcommand*{\personfullname}[1][anon]{%
  \ifundefined{person@#1@fullname}%
  {%
    \PackageError{person}{Person ‘#1’ has not been defined}{}%
  }%
  {%
    \csname person@#1@fullname\endcsname
  }%
}
```

`\peoplefullname` List all defined people's full names. This iterates through all labels in `\@people@list`.

```
\newcommand*{\peoplefullname}{%
  \setcounter{person}{1}%
  \@for\@thisperson:=\@people@list\do{%
    \ifthenelse{\equal{\@thisperson}{}}{%
    }{%
      \personfullname[\@thisperson]%
      \stepcounter{person}%
      \ifnum\c@people=1\relax
      \else
        \ifnum\c@person=\c@people
          \ifnum\c@people=2\relax
            \twopeoplesep
          \else
            \personlastsep
          \fi
        \else
          \ifnum\c@person<\c@people
            \personsep
          \fi
        \fi
      \fi
    }%
  }%
}
```

`\personname` As `\personfullname`, but for the person's familiar name.

```
\newcommand*{\personname}[1][anon]{%
  \@ifundefined{person@#1@name}%
  {%
    \PackageError{person}{Person '#1' has not been defined}{}%
  }%
  {%
    \csname person@#1@name\endcsname
  }%
}
```

`\peoplename` List all defined people's familiar names. This iterates through all labels in `\@people@list`.

```
\newcommand*{\peoplename}{%
  \setcounter{person}{1}%
  \@for\@thisperson:=\@people@list\do{%
    \ifthenelse{\equal{\@thisperson}{}}%
    {}%
    {%
      \personname[\@thisperson]%
      \stepcounter{person}%
      \ifnum\c@people=1\relax
      \else
        \ifnum\c@person=\c@people
          \ifnum\c@people=2\relax
            \twopeoplesep
          \else
            \personlastsep
          \fi
        \else
          \ifnum\c@person<\c@people
            \personsep
          \fi
        \fi
      \fi
    }%
  }%
}
```

`\personpronoun` Display the pronoun (he/she) according to the person's gender.

```
\newcommand*{\personpronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person '#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender pronoun\endcsname
  }%
}
```

`\Personpronoun` As above, but make the first letter uppercase.

```

\newcommand*{\Personpronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person ‘#1’ has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \expandafter\expandafter\expandafter
    \MakeUppercase\csname\@gender pronoun\endcsname
  }%
}

```

`\peoplepronoun` If there is more than one person, `\peoplepronoun` will use `\pluralpronoun`, otherwise it will use `\personpronoun`.

```

\newcommand*{\peoplepronoun}{%
  \ifnum\c@people>1\relax
    \pluralpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \personpronoun[\@thisperson]%
  \fi
}

```

`\Peoplepronoun` As above, but first letter in upper case

```

\newcommand*{\Peoplepronoun}{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \Personpronoun[\@thisperson]%
  \fi
}

```

`ersonobjpronoun` Display the objective pronoun (him/her) according to the person's gender.

```

\newcommand*{\personobjpronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person ‘#1’ has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender objpronoun\endcsname
  }%
}

```

`ersonobjpronoun` As above, but make the first letter uppercase.

```

\newcommand*{\Personobjpronoun}[1][anon]{%

```

```

\@ifundefined{person@#1@gender}%
{%
  \PackageError{person}{Person ‘#1’ has not been defined}{}%
}%
{%
  \edef\@gender{\csname person@#1@gender\endcsname}%
  \expandafter\expandafter\expandafter
  \MakeUppercase\csname\@gender objpronoun\endcsname
}%
}

```

`\peopleobjpronoun` If there is more than one person, `\peopleobjpronoun` will use `\pluralobjpronoun`, otherwise it will use `\personobjpronoun`.

```

\newcommand*\peopleobjpronoun{%
  \ifnum\c@people>1\relax
    \pluralobjpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \personobjpronoun[\@thisperson]%
  \fi
}

```

`\Peopleobjpronoun` As above, but first letter in upper case

```

\newcommand*\Peopleobjpronoun{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralobjpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \Personobjpronoun[\@thisperson]%
  \fi
}

```

`\personpssadj` Display the possessive adjective (his/her) according to the person's gender.

```

\newcommand*\personpossadj}[1] [anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person ‘#1’ has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender possadj\endcsname
  }%
}

```

`\Personpossadj` As above, but make the first letter uppercase.

```

\newcommand*\Personpossadj}[1] [anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person ‘#1’ has not been defined}{}%
  }%
}

```

```

}%
{%
  \edef\@gender{\csname person@#1@gender\endcsname}%
  \expandafter\expandafter\expandafter
  \MakeUppercase\csname\@gender possadj\endcsname
}%
}
}

```

`\peoplepossadj` If there is more than one person, `\peoplepossadj` will use `\pluralpossadj`, otherwise it will use `\personpossadj`.

```

\newcommand*\peoplepossadj{%
  \ifnum\c@people>1\relax
    \pluralpossadj
  \else
    \@get@firstperson{\@thisperson}%
    \personpossadj[\@thisperson]%
  \fi
}

```

`\Peoplepossadj` As above, but first letter in upper case

```

\newcommand*\Peoplepossadj{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralpossadj
  \else
    \@get@firstperson{\@thisperson}%
    \Personpossadj[\@thisperson]%
  \fi
}

```

`\personposspronoun` Display possessive pronoun (his/hers) according to the person's gender.

```

\newcommand*\personposspronoun[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person ‘#1’ has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender posspronoun\endcsname
  }%
}

```

`\Personposspronoun` As above, but make the first letter uppercase.

```

\newcommand*\Personposspronoun[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person ‘#1’ has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%

```

```

\expandafter\expandafter\expandafter
\MakeUppercase\csname\@gender posspronoun\endcsname
}%
}

```

`\peopleposspronoun` If there is more than one person, `\peopleposspronoun` will use `\pluralposspronoun`, otherwise it will use `\personposspronoun`.

```

\newcommand*\peopleposspronoun}{%
\ifnum\c@people>1\relax
\pluralposspronoun
\else
\@get@firstperson{\@thisperson}%
\personposspronoun[\@thisperson]%
\fi
}

```

`\opleposspronoun` As above, but first letter in upper case

```

\newcommand*\Peopleposspronoun}{%
\ifnum\c@people>1\relax
\expandafter\MakeUppercase\pluralposspronoun
\else
\@get@firstperson{\@thisperson}%
\Personposspronoun[\@thisperson]%
\fi
}

```

`\personchild` Display this person's relationship to their parent (i.e. son or daughter).

```

\newcommand*\personchild}[1][anon]{%
\@ifundefined{person@#1@gender}{%
{%
\PackageError{person}{Person '#1' has not been defined}{}%
}%
{%
\edef\@gender{\csname person@#1@gender\endcsname}%
\csname\@gender child\endcsname
}%
}
}

```

`\Personchild` As above, but make first letter uppercase.

```

\newcommand*\Personchild}[1][anon]{%
\@ifundefined{person@#1@gender}{%
{%
\PackageError{person}{Person '#1' has not been defined}{}%
}%
{%
\edef\@gender{\csname person@#1@gender\endcsname}%
\expandafter\expandafter\expandafter\MakeUppercase
\csname\@gender child\endcsname
}%
}
}

```



```
}
```

`\peoplechild` If there is more than one person, `\peoplechild` will use `\malechildren` (if all male), `\femalechildren` (if all female) or `\pluralchild` (if mixed), otherwise it will use `\personchild`.

```
\newcommand*{\peoplechild}{%
  \ifnum\c@people>1\relax
    \ifallmale
      {\malechildren}%
    {\ifallfemale{\femalechildren}{\pluralchild}}%
  \else
    \@get@firstperson{\@thisperson}%
    \personchild[\@thisperson]%
  \fi
}
```

`\Peoplechild` As above but first letter is made uppercase.

```
\newcommand*{\Peoplechild}{%
  \ifnum\c@people>1\relax
    \ifallmale
      {\expandafter\MakeUppercase\malechildren}%
    {\ifallfemale
      {\expandafter\MakeUppercase\femalechildren}
      {\expandafter\MakeUppercase\pluralchild}}%
  \else
    \@get@firstperson{\@thisperson}%
    \Personchild[\@thisperson]%
  \fi
}
```

`\personparent` Display this person's relationship to their child (i.e. father or mother).

```
\newcommand*{\personparent}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person '#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender parent\endcsname
  }%
}
```

`\Personparent` As above, but make the first letter uppercase.

```
\newcommand*{\Personparent}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person '#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
  }%
}
```

```

        \expandafter\expandafter\expandafter\MakeUppercase
        \csname\@gender parent\endcsname
    }%
}

```

`\peopleparent` If there is more than one person, `\peopleparent` will use `\pluralparent`, otherwise it will use `\personparent`.

```

\newcommand*\peopleparent{%
  \ifnum\c@people>1\relax
    \pluralparent
  \else
    \@get@firstperson{\@thisperson}%
    \personparent[\@thisperson]%
  \fi
}

```

`\Peopleparent` As above, but make first letter uppercase.

```

\newcommand*\Peopleparent{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralparent
  \else
    \@get@firstperson{\@thisperson}%
    \Personparent[\@thisperson]%
  \fi
}

```

`\personsibling` Display this person's relationship to their siblings (i.e. brother or sister).

```

\newcommand*\personsibling[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person '#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender sibling\endcsname
  }%
}

```

`\Personsisibling` Display this person's relationship to their siblings (i.e. brother or sister).

```

\newcommand*\Personsisibling[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person '#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \expandafter\expandafter\expandafter\MakeUppercase
    \csname\@gender sibling\endcsname
  }%
}

```

```
}
```

`\peoplesibling` If there is more than one person, `\peoplesibling` will use `\malesiblings` (if all male), `\femalesiblings` (if all female) or `\pluralsibling` (if mixed), otherwise it will use `\personsibling`.

```
\newcommand*{\peoplesibling}{%
  \ifnum\c@people>1\relax
    \ifallmale
      {\malesiblings}%
    {\ifallfemale{\femalesiblings}{\pluralsibling}}%
  \else
    \@get@firstperson{\@thisperson}%
    \personsibling[\@thisperson]%
  \fi
}
```

`\persongender` Displays the given person's gender (`\malename` or `\femalename`).

```
\newcommand*{\persongender}[1]{%
  \ifmale{#1}{\malename}{\femalename}%
}
```

## 10.7 Extracting Information

`getpersongender` Gets person's gender and stores in first argument which must be a control sequence.

```
\newcommand*{\getpersongender}[2]{%
  \ifmale{#2}{\let#1\malename}{\let#1\femalename}%
}
```

`\getpersonname` Gets person's name and stores in first argument which must be a control sequence.

```
\newcommand*{\getpersonname}[2]{%
  \ifpersonexists{#2}%
  {%
    \expandafter\let\expandafter#1\csname person@#2@name\endcsname
  }%
  {%
    \PackageError{person}{Person '#2' doesn't exist}{}%
  }%
}
```

`tpersonfullname` Gets person's full name and stores in first argument which must be a control sequence.

```
\newcommand*{\getpersonfullname}[2]{%
  \ifpersonexists{#2}%
  {%
    \expandafter
      \let\expandafter#1\csname person@#2@fullname\endcsname
  }%
  {%
    \PackageError{person}{Person '#2' doesn't exist}{}%
  }%
}
```

} }%

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

<b>Symbols</b>	
\"	111, 217
\#	223, 288
\\$	18, 23, 24, 46, 223, 287
\%	209–213, 222, 223, 236, 288
\&	14, 223, 241, 287
\(	97, 98, 404, 405
\)	97, 98, 404, 405
\.	331
\@@	133, 134, 149–151, 199
\@dtl@set@off	404
\@dtl@set@offr	404
\@dtl@setnull	134, 135
\@dtl@strip@numgrpchar	19, 20
\@get@firstperson	432
\@Alph	299, 300, 318
\@DTLaddcolumn	125
\@DTLforeach	155, 156, 326, 327
\@DTLforeachbibentry	326
\@DTLifclosedbetween	86
\@DTLifdbempty	118, 156, 161
\@DTLifeq	81
\@DTLifgt	79
\@DTLifhaskey	119, 152, 166, 167
\@DTLiflt	77
\@DTLifopenbetween	89
\@DTLifstringclosedbetween	85, 87
\@DTLifstringeq	80, 81
\@DTLifstringgt	78, 79
\@DTLifstringlt	77, 78
\@DTLifstringopenbetween	87–89
\@DTLnewdbentry	130, 323
\@DTLnewrow	118, 322
\@DTLremoveover	184
\@DTLsetheader	128
\@DTLsort	196
\@Roman	284, 299, 300
\@after	6
\@afterheading	252, 262, 265
\@alph	299, 300
\@arabic	299, 300
\@auxout	234, 304, 319, 322, 345
\@before	6
\@bsphack	369
\@checkend	6
\@cite	368
\@cite@ofmt	369
\@citea	368
\@citeb	368, 369
\@cur@location	319
\@currenvir	5
\@data@rerun@warn	235, 319
\@data@rerun@warn@sort	234
\@datagidx@db@col@id@w	235
\@datagidx@do@xusedentry	305
\@datagidx@dorerun@warn	319
\@datagidx@dorerun@warn@sort	234
\@datagidx@dowriteaux	300
\@datagidx@escloc	299
\@datagidx@fieldkey@Description	282
\@datagidx@fieldkey@Label	282
\@datagidx@fieldkey@Long	282
\@datagidx@fieldkey@Name	282
\@datagidx@fieldkey@Parent	282
\@datagidx@fieldkey@Plural	282
\@datagidx@fieldkey@See	282
\@datagidx@fieldkey@SeeAlso	282
\@datagidx@fieldkey@Short	282
\@datagidx@fieldkey@Sort	282
\@datagidx@fieldkey@Symbol	282
\@datagidx@fieldkey@Text	282
\@datagidx@parse@location	273
\@datagidx@target	300, 301
\@datagidx@thisval	242, 243

<code>\@datagidx@use@entry</code>	309–311	<code>\@dtl@checknumerical</code>	49–51, 86, 87, 89, 126, 128
<code>\@datagidx@warnfalse</code>	237	<code>\@dtl@checknumericalloop</code>	47
<code>\@datagidx@warntrue</code>	234, 237	<code>\@dtl@checknumericalnoop</code>	48
<code>\@datagidxlink</code>	247	<code>\@dtl@checknumericalstart</code>	45
<code>\@datagidxsymbolleftfalse</code>	232, 233	<code>\@dtl@chop@trailingzeroes</code>	18
<code>\@datagidxsymbollefttrue</code>	231, 232	<code>\@dtl@chopexcessfrac</code>	22
<code>\@datagidxtarget</code>	246, 247	<code>\@dtl@choptrailingzeroes</code>	17
<code>\@do@dtl@env@foreach</code>	155	<code>\@dtl@chopzeroesnext</code>	19
<code>\@do@dtl@env@forint</code>	99	<code>\@dtl@col</code>	115–117, 137, 138, 185, 187, 189, 191, 193, 195, 201, 202, 206, 211, 213
<code>\@do@dtl@newentry</code>	221	<code>\@dtl@colhead</code>	126, 127, 129, 137
<code>\@do@dtl@foreach@person</code>	437	<code>\@dtl@colnum</code>	129
<code>\@do@dtl@sdtl@env@foreach</code>	156	<code>\@dtl@comparecs</code>	198, 205
<code>\@dtl@A@after</code>	68, 69, 71	<code>\@dtl@cond</code>	185–191, 193
<code>\@dtl@A@before</code>	68–71	<code>\@dtl@conditionfalse</code>	41, 42, 51, 82–84, 90–96, 218, 219, 221, 340–344
<code>\@dtl@A@chargroup</code>	70	<code>\@dtl@conditiontrue</code>	40–42, 51, 82, 83, 90–96, 218–220, 340–343
<code>\@dtl@A@comma</code>	68, 71	<code>\@dtl@construct@getintfrac</code>	17
<code>\@dtl@B@after</code>	69, 71	<code>\@dtl@construct@getnums</code>	16, 23
<code>\@dtl@B@before</code>	69–71	<code>\@dtl@construct@lop@off</code>	113
<code>\@dtl@B@chargroup</code>	70	<code>\@dtl@construct@lop@off</code>	112
<code>\@dtl@B@comma</code>	69, 71	<code>\@dtl@construct@lop@offs</code>	110, 111, 113
<code>\@dtl@a</code>	201, 202, 205, 206	<code>\@dtl@construct@qlop@off</code>	113
<code>\@dtl@activatebraces</code>	223	<code>\@dtl@construct@stripnumgrpchar</code>	16, 23
<code>\@dtl@af</code>	368	<code>\@dtl@contcap</code>	177, 179
<code>\@dtl@after</code>	126, 127, 129, 137, 159, 160, 168	<code>\@dtl@countdigits</code>	21, 108, 109
<code>\@dtl@after@cs</code>	141, 142	<code>\@dtl@countnext</code>	21
<code>\@dtl@afterpart</code>	43, 44, 68, 69	<code>\@dtl@curi</code>	155
<code>\@dtl@arg</code>	3, 4	<code>\@dtl@curii</code>	155
<code>\@dtl@argA</code>	53, 64, 65, 67, 68, 81–83	<code>\@dtl@curiii</code>	155
<code>\@dtl@argB</code>	53, 64, 65, 67, 69, 81–83	<code>\@dtl@currencies</code>	24
<code>\@dtl@argi</code>	18, 330, 366	<code>\@dtl@currency</code>	17, 22, 25, 45
<code>\@dtl@argii</code>	18, 330, 366, 367	<code>\@dtl@currentrow</code>	10, 11
<code>\@dtl@argiii</code>	366, 367	<code>\@dtl@datatype</code>	45–51, 87, 89, 126, 128, 176, 180
<code>\@dtl@asg@value</code>	133	<code>\@dtl@db@name</code>	185, 187–189, 191, 193
<code>\@dtl@assign</code>	132, 133, 158, 162	<code>\@dtl@dbname</code>	134, 135, 156, 158, 161, 198, 201, 202, 204, 205, 317
<code>\@dtl@assigncmd</code>	133	<code>\@dtl@decimal</code>	16, 17, 20, 23, 47, 48
<code>\@dtl@assigncmdnoop</code>	134	<code>\@dtl@decimal@to@localeint</code>	21
<code>\@dtl@author</code>	332, 333, 336, 365	<code>\@dtl@decimal@to@locale</code>	20, 22
<code>\@dtl@authorcount</code>	331–333, 335, 336, 365	<code>\@dtl@decimal@to@localefrac</code>	21
<code>\@dtl@b</code>	201, 202, 205, 206	<code>\@dtl@decimal@to@localeint</code>	20
<code>\@dtl@bar</code>	380, 382	<code>\@dtl@decrementrows</code>	182
<code>\@dtl@barcount</code>	387, 388, 390	<code>\@dtl@decvals</code>	33, 34
<code>\@dtl@before</code>	126, 127, 129, 137, 159, 168	<code>\@dtl@delimiter</code>	111, 112, 206, 207
<code>\@dtl@before@cs</code>	141, 142		
<code>\@dtl@beforepart</code>	43, 44, 68, 69		
<code>\@dtl@c</code>	209		
<code>\@dtl@cap</code>	177–179		
<code>\@dtl@chars</code>	112, 113		
<code>\@dtl@chcknumnext</code>	48		

<code>\@dtl@dict@compare</code>	72	<code>\@dtl@firsttype</code>	51
<code>\@dtl@diff</code>	33, 34	<code>\@dtl@foot</code>	177, 178
<code>\@dtl@digitcount</code>	22	<code>\@dtl@forcolnext</code>	154
<code>\@dtl@digitcountnext</code>	22	<code>\@dtl@forcolnoop</code>	154
<code>\@dtl@dir</code>	203, 204	<code>\@dtl@forcolumn</code>	154
<code>\@dtl@do@compare</code>	72, 73	<code>\@dtl@foreach@level</code>	98, 99, 149–151
<code>\@dtl@do@getentry</code>	143	<code>\@dtl@foreachkey</code>	150
<code>\@dtl@do@splitrow</code>	141, 142	<code>\@dtl@foreachnext</code>	150, 151
<code>\@dtl@do@stripnumgrpchar</code>	19	<code>\@dtl@foreachnoop</code>	149, 151
<code>\@dtl@doamp</code>	175–180	<code>\@dtl@foreachrow</code>	149, 199
<code>\@dtl@dobegintab</code>	175, 178	<code>\@dtl@formatlist@handler</code>	15
<code>\@dtl@docompare</code>	203, 341–343	<code>\@dtl@formatlist@item</code>	15
<code>\@dtl@doforcol</code>	152, 153	<code>\@dtl@formatlist@itemsep</code>	14
<code>\@dtl@dogetdata</code>	124	<code>\@dtl@formatlist@lastitem</code>	14, 15
<code>\@dtl@dogetentry</code>	134	<code>\@dtl@formatlist@prelastitem</code>	14, 15
<code>\@dtl@dogetkeydata</code>	137	<code>\@dtl@formatlist@prelastitemsep</code>	14
<code>\@dtl@dogetkeyforcolumn</code>	122	<code>\@dtl@fracpart</code>	16, 17, 20, 22, 23, 108, 109
<code>\@dtl@dogetprops</code>	126, 129	<code>\@dtl@gap</code>	428–430
<code>\@dtl@dogetrow</code>	138, 139	<code>\@dtl@gatherintfrac</code>	108, 109
<code>\@dtl@dogetrowforvalue</code>	139	<code>\@dtl@get@int@part</code>	17
<code>\@dtl@dogetval</code>	195	<code>\@dtl@get@intpart</code>	16
<code>\@dtl@doifinlist</code>	6	<code>\@dtl@get@keydata</code>	124, 125
<code>\@dtl@dolabel</code>	402, 403	<code>\@dtl@get@keyforcolumn</code>	122
<code>\@dtl@dollar</code>	47	<code>\@dtl@get@next@intpart</code>	18
<code>\@dtl@donext</code>	82, 330, 367	<code>\@dtl@get@nextintpart</code>	18
<code>\@dtl@donextdec</code>	182, 183	<code>\@dtl@get@sortdirection</code>	203
<code>\@dtl@donextinitials</code>	38	<code>\@dtl@get@columnindex</code>	120, 166, 167
<code>\@dtl@doreadline</code>	217, 218, 220, 222	<code>\@dtl@get@datatype</code>	124
<code>\@dtl@doreadraw</code>	223	<code>\@dtl@get@fracpart</code>	17
<code>\@dtl@dosetheader</code>	221, 222	<code>\@dtl@get@intfrac</code>	16, 17
<code>\@dtl@dosplit</code>	181	<code>\@dtl@get@keyforcolumn</code>	122
<code>\@dtl@dosplitrow</code>	166, 168	<code>\@dtl@get@location</code>	147
<code>\@dtl@dostartrow</code>	177, 180	<code>\@dtl@get@props</code>	126, 129, 137
<code>\@dtl@dosubs</code>	24, 112	<code>\@dtl@getrow</code>	140
<code>\@dtl@dosubstitute</code>	44	<code>\@dtl@getrowindex</code>	148
<code>\@dtl@dosubstitutenoop</code>	44	<code>\@dtl@get@sortdirection</code>	197, 201
<code>\@dtl@dosubstnext</code>	44	<code>\@dtl@get@value</code>	146
<code>\@dtl@dotestifsubstring</code>	81	<code>\@dtl@gobbletonil</code>	19, 22, 40–42, 182
<code>\@dtl@dovalue</code>	85, 86, 88, 101, 102	<code>\@dtl@h</code>	209, 379, 386
<code>\@dtl@element</code>	7–9	<code>\@dtl@head</code>	115–117, 137, 138, 175, 178–180, 206, 211, 213, 215, 221
<code>\@dtl@elements</code>	186–190	<code>\@dtl@header</code>	206, 207
<code>\@dtl@endgrabword</code>	73	<code>\@dtl@idx</code>	175, 178, 179
<code>\@dtl@endloophook</code>	97	<code>\@dtl@ifDigitOrDecimalSep</code>	48
<code>\@dtl@endpt</code>	387, 388	<code>\@dtl@ifsingle</code>	3, 4
<code>\@dtl@entryI</code>	143	<code>\@dtl@initials</code>	38
<code>\@dtl@entryII</code>	143	<code>\@dtl@insertdonefalse</code>	10, 12, 198
<code>\@dtl@falsepart</code>	105–107	<code>\@dtl@insertdonetrue</code>	10, 12, 200
<code>\@dtl@firstpart</code>	181	<code>\@dtl@intpart</code>	17, 18, 20, 21, 23, 108, 109
<code>\@dtl@firsttonil</code>	55		

<code>\@dtl@k</code> .....	209	<code>\@dtl@numii</code> 25-27, 30, 31, 51, 78, 80, 85, 87
<code>\@dtl@key</code> .....	115-117, 126,	<code>\@dtl@numiii</code> .....
	129, 137, 138, 142, 175, 178, 179,	<code>\@dtl@oldbreak</code> .....
	185, 187, 189, 191, 193, 197, 201-	<code>\@dtl@oldtype</code> .....
	203, 206, 207, 211, 213, 215, 218, 219	<code>\@dtl@omitlist</code> .....
<code>\@dtl@key@Author</code> .....	332, 364	<code>\@dtl@org@currency</code> .....
<code>\@dtl@key@CrossRef</code> .....	364	<code>\@dtl@orgbreak</code> .....
<code>\@dtl@key@Editor</code> .....	333, 336, 364	<code>\@dtl@pages</code> .....
<code>\@dtl@key@Key</code> .....	364	<code>\@dtl@parse@words</code> .....
<code>\@dtl@key@Organization</code> .....	364	<code>\@dtl@period</code> .....
<code>\@dtl@key@Year</code> .....	364	<code>\@dtl@plus</code> .....
<code>\@dtl@keya</code> .....	201-203	<code>\@dtl@posgap</code> .....
<code>\@dtl@keyb</code> .....	201-203	<code>\@dtl@previ</code> .....
<code>\@dtl@keys</code> .....	150	<code>\@dtl@previi</code> .....
<code>\@dtl@label</code> .....	177, 179	<code>\@dtl@previii</code> .....
<code>\@dtl@lastfoot</code> .....	177, 178	<code>\@dtl@protect</code> .....
<code>\@dtl@level</code> .....	197, 201	<code>\@dtl@qlopoff</code> .....
<code>\@dtl@lin@</code> .....	218-221	<code>\@dtl@rawmappings</code> .....
<code>\@dtl@line</code> .....	216-218, 220	<code>\@dtl@rawread</code> .....
<code>\@dtl@listelement@outofrange</code> .....	7, 8	<code>\@dtl@read</code> .....
<code>\@dtl@localeintnext</code> .....	21, 22	<code>\@dtl@readline</code> .....
<code>\@dtl@loop@body</code> .....	171	<code>\@dtl@readrawline</code> .....
<code>\@dtl@loopbody</code> .....	149-151	<code>\@dtl@replaced</code> .....
<code>\@dtl@lopoff</code> .....	111, 112	... 24-30, 32, 33, 35, 36, 43, 44, 68, 69
<code>\@dtl@lopoff</code> .....	111, 218, 220	<code>\@dtl@replacementkeys</code> .....
<code>\@dtl@map</code> .....	224	<code>\@dtl@resetdoamp</code> .....
<code>\@dtl@mathprocessor</code> ...	2, 3, 100, 105, 113	<code>\@dtl@resetdostartrow</code> .....
<code>\@dtl@max</code> .....	31, 32	<code>\@dtl@row</code> .....
<code>\@dtl@maxcols</code> .....	175, 178, 221	<code>\@dtl@rowAcontents</code> .....
<code>\@dtl@mean</code> .....	32-34	<code>\@dtl@rowAidx</code> .....
<code>\@dtl@midpt</code> .....	388, 389	<code>\@dtl@rowAnum</code> .....
<code>\@dtl@min</code> .....	30, 182, 183	<code>\@dtl@rowBcontents</code> .....
<code>\@dtl@minus</code> .....	46	<code>\@dtl@rowBidx</code> .....
<code>\@dtl@n</code> .....	32-34, 187-190	<code>\@dtl@rowBnum</code> .....
<code>\@dtl@neggap</code> .....	428	<code>\@dtl@rowa</code> .....
<code>\@dtl@newlist</code> .....	182, 183, 198-200	<code>\@dtl@rowb</code> .....
<code>\@dtl@newsortedlist</code> .....	10-13	<code>\@dtl@s@thislabel</code> .....
<code>\@dtl@newstuff</code> .....	10-12	<code>\@dtl@sd</code> .....
<code>\@dtl@next</code> .....	20, 134, 400-402	<code>\@dtl@secondpart</code> .....
<code>\@dtl@nexti</code> .....	155	<code>\@dtl@seg</code> .....
<code>\@dtl@nextii</code> .....	155	<code>\@dtl@separator</code> .....
<code>\@dtl@nextiii</code> .....	155	... 110, 112, 113, 206, 207, 218-221
<code>\@dtl@notdone</code> .....	169, 170	<code>\@dtl@sequentialfalse</code> .....
<code>\@dtl@num</code> .....	25, 30, 32-34	<code>\@dtl@sequentialtrue</code> .....
<code>\@dtl@numbergroupchar</code> 16, 19, 21, 23, 48		<code>\@dtl@set@off</code> .....
<code>\@dtl@numgrpsepcount</code> .....	21, 45, 48	<code>\@dtl@set@options</code> .....
<code>\@dtl@numgrpsepfalse</code> .....	45	<code>\@dtl@setheaderforindex</code> .....
<code>\@dtl@numgrpseptrue</code> .....	48	<code>\@dtl@setnewvalue</code> .....
<code>\@dtl@numi</code> 25-31, 35, 36, 51, 78, 80, 85, 87		<code>\@dtl@setnull</code> .....
		138, 201, 202



<code>\@dtl@setwordbreaks</code>	74, 75	<code>\@dtl@tmpi</code>	26, 29, 31–35
<code>\@dtl@setwordbreaks@next</code>	74	<code>\@dtl@tmpii</code>	25–31, 35, 36
<code>\@dtl@shift</code>	399	<code>\@dtl@toks</code>	9–13, 22–24, 37, 38, 40, 42–44, 130, 131, 137, 144–146, 164–166, 168, 181–183, 219–224, 341–343, 364, 365, 424, 431
<code>\@dtl@shortcap</code>	177, 179	<code>\@dtl@toks@gconcat@middle@cx</code>	127, 129, 131, 140, 159, 168
<code>\@dtl@sortcriteria</code>	199	<code>\@dtl@toks@gput@right@cx</code>	119, 128, 141, 144, 145, 165
<code>\@dtl@sortdirection</code>	203, 204	<code>\@dtl@toks@name</code>	15
<code>\@dtl@sortedlist</code>	10, 11, 198–200	<code>\@dtl@toksA</code>	181, 182, 202, 203, 432, 433
<code>\@dtl@sortorder</code>	197, 198, 201	<code>\@dtl@toksB</code>	181, 182, 202, 203, 432, 433
<code>\@dtl@splitsubstr</code>	44	<code>\@dtl@truepart</code>	105–107
<code>\@dtl@standardize@currency</code>	17, 45	<code>\@dtl@truncatedecimal</code>	19
<code>\@dtl@start</code>	380–382, 387, 388, 390, 398, 403, 404	<code>\@dtl@type</code>	115–117, 126–129, 135, 137, 138, 175, 178, 179, 206, 211, 213, 225
<code>\@dtl@string</code>	37	<code>\@dtl@typeA</code>	204, 205
<code>\@dtl@strip@numgrpchar</code>	17	<code>\@dtl@typeB</code>	205
<code>\@dtl@stripeol</code>	216, 223	<code>\@dtl@updatefkcs</code>	150
<code>\@dtl@stripped</code>	19, 20	<code>\@dtl@updatekeys</code>	125, 130, 142, 144, 145, 164
<code>\@dtl@strippedline</code>	216, 223	<code>\@dtl@val</code>	176, 180, 195, 207, 208
<code>\@dtl@stuff</code>	15, 142, 143	<code>\@dtl@var</code>	33, 34
<code>\@dtl@subnobrsp</code>	37	<code>\@dtl@vonpart</code>	366
<code>\@dtl@subnobrspnext</code>	37	<code>\@dtl@widestlabel</code>	363–365
<code>\@dtl@subs@argA</code>	82	<code>\@dtl@width</code>	428, 430
<code>\@dtl@subs@argB</code>	82	<code>\@dtl@wordbreak</code>	56, 63, 65, 67, 73, 81, 83
<code>\@dtl@sum</code>	25, 26	<code>\@dtl@write</code>	206–214
<code>\@dtl@t</code>	209	<code>\@dtl@year</code>	364, 367
<code>\@dtl@tabargs</code>	175, 178	<code>\@dtldictcompare</code>	67
<code>\@dtl@testifsubstring</code>	82	<code>\@dtl@envforeach@args</code>	155
<code>\@dtl@teststartswith</code>	82–85	<code>\@dtl@envgforint@arg</code>	99
<code>\@dtl@thirdpart</code>	181, 182	<code>\@dtl@forcolumn</code>	152
<code>\@dtl@thiscurrency</code>	24	<code>\@dtl@forcolumnidx</code>	153
<code>\@dtl@thisdb</code>	164–170	<code>\@dtl@foreachrow</code>	162, 198
<code>\@dtl@thisentry</code>	220, 221	<code>\@dtl@formatlist</code>	14
<code>\@dtl@thiskey</code>	220, 221	<code>\@dtl@getdatatype</code>	123
<code>\@dtl@thislabel</code>	364, 365	<code>\@dtl@getkeydata</code>	136
<code>\@dtl@thisreplaced</code>	27, 28	<code>\@dtl@getkeyforcolumn</code>	121
<code>\@dtl@thisrow</code>	182, 183	<code>\@dtl@getrow</code>	138, 139, 181
<code>\@dtl@thistick</code>	429–431	<code>\@dtl@getrowindex</code>	147, 148
<code>\@dtl@tmp</code>	5, 17, 20, 25–29, 31, 35–37, 45–48, 51, 82, 86, 87, 89, 122, 130, 138, 144, 145, 159, 164, 166, 168, 175, 178, 181, 182, 224, 330, 334, 335, 339–344, 351, 353, 354, 357, 365, 366	<code>\@dtl@lifereadonly</code>	164, 165, 167, 169
<code>\@dtl@tmpcmp</code>	77–80, 85, 86, 88, 205	<code>\@dtl@loadb</code>	217, 222
<code>\@dtl@tmpcount</code>	7, 8, 17, 18, 21–23, 45, 48, 77–80, 85, 86, 88, 108, 109, 155, 158, 183, 205, 332, 333, 336, 341–344, 348, 365, 366, 378, 385–387, 415, 416	<code>\@dtl@maxforkeys</code>	193
<code>\@dtl@tmpcpz</code>	18, 19	<code>\@dtl@meanforkeys</code>	186
<code>\@dtl@tmpdtl</code>	20, 22	<code>\@dtl@minforkeys</code>	191
		<code>\@dtl@novalue</code>	136, 144, 147, 148
		<code>\@dtl@numbernull</code>	135, 171
		<code>\@dtl@plotheadlermark</code>	410, 418, 427

<code>\@dtlsdforkeys</code>	190	<code>\@male@label</code>	435–437
<code>\@dtlsplitrow</code>	141	<code>\@namedef</code>	433
<code>\@dtlstringnull</code>	135, 171	<code>\@one</code>	22
<code>\@dtlsumforkeys</code>	185	<code>\@onil</code>	3, 4, 6, 18, 19, 22, 37–39, 41, 43–49, 55, 56, 74–76, 122, 133, 149, 154, 169, 177, 182, 183, 199, 329, 366, 415, 427, 432, 434
<code>\@dtlvarianceforkeys</code>	188, 190	<code>\@onnil</code>	6, 37–42, 48, 74, 76, 134, 149, 154, 159, 178, 179, 182, 202, 240, 330, 366, 367
<code>\@dtlwordindexcompare</code>	70, 71	<code>\@onx</code>	5
<code>\@eha</code>	369	<code>\@onelevel@sanitize</code>	206, 209, 213, 319, 364
<code>\@empty</code>	6, 8, 9, 17, 20, 27, 30, 31, 33, 34, 43, 196, 248–250, 255, 256, 260–262, 269, 315, 326, 334, 335, 366, 368, 416, 417, 423, 424, 430, 431, 435, 437	<code>\@onlypreamble</code>	278, 279, 288, 300, 368, 369
<code>\@emptytoks</code>	5	<code>\@org@dtl@paren@start</code>	70, 71
<code>\@endforfalse</code>	9–12, 24, 203, 243, 329	<code>\@org@dtl@person@comma</code>	70, 71
<code>\@endfortrue</code>	7, 9, 24, 202, 203, 242, 270, 320, 329, 332, 333, 336, 366, 436	<code>\@org@dtl@place@comma</code>	70, 71
<code>\@endparse@formatlabel@</code>	302	<code>\@org@dtl@subject@comma</code>	70, 71
<code>\@envbody</code>	5	<code>\@people@list</code>	432, 434–437, 440, 441
<code>\@esphack</code>	369	<code>\@person@label</code>	434
<code>\@female@label</code>	436, 437	<code>\@prev@location</code>	319
<code>\@firstofone</code>	239, 299, 300, 368, 369	<code>\@prsn@post</code>	434
<code>\@firstoftwo</code>	242, 400–402	<code>\@prsn@pre</code>	434
<code>\@for</code>	7–12, 15, 24, 25, 30–34, 185, 187–189, 191, 193, 195, 197, 201, 202, 215, 224, 240–244, 270, 282, 298, 320, 329, 332, 333, 336, 365, 368, 369, 378, 379, 382, 384–387, 391, 398, 416–422, 435–437, 440, 441	<code>\@remove@person</code>	434
<code>\@foreachperson</code>	437	<code>\@removeperson</code>	434
<code>\@forremainder</code>	9, 243	<code>\@roman</code>	299, 300
<code>\@gDTLforeachbibentry</code>	327	<code>\@sDTLaddcolumn</code>	125
<code>\@gender</code>	435, 436, 441–447	<code>\@sDTLforeach</code>	156, 176, 180, 185, 187, 189, 191, 193, 195, 196, 207, 208, 327, 328, 344, 348, 377, 378, 380, 384, 385, 387, 398, 399, 406, 424
<code>\@get@firstperson</code>	442–448	<code>\@sDTLforeachbibentry</code>	326
<code>\@glsadd</code>	307	<code>\@sDTLifclosedbetween</code>	86, 87, 92
<code>\@gobble</code>	6, 18, 21, 38, 76, 209–213, 236, 239, 246, 283, 287–290, 300, 330	<code>\@sDTLlifeq</code>	81, 91
<code>\@gobbletwo</code>	74, 288	<code>\@sDTLifgt</code>	79, 90
<code>\@idxitem</code>	246, 251, 253, 270	<code>\@sDTLifhaskey</code>	119, 120, 123, 126, 128, 134, 135, 137, 186, 187, 189, 192, 194
<code>\@ifnextchar</code>	302, 368	<code>\@sDTLiflt</code>	77, 78, 90
<code>\@ifstar</code>	14, 77–81, 85–87, 89, 118–121, 123, 125, 128, 130, 136, 152, 153, 156, 196, 326, 327	<code>\@sDTLifopenbetween</code>	89, 93
<code>\@ifundefined</code>	24, 120, 132, 219–221, 324, 325, 329, 364, 367–369, 433, 435, 440–447	<code>\@sDTLifstringclosedbetween</code>	85–87
<code>\@input@</code>	322, 370	<code>\@sDTLifstringeq</code>	80, 81
<code>\@latex@error</code>	369	<code>\@sDTLifstringgt</code>	78, 79
<code>\@latex@warning</code>	369	<code>\@sDTLifstringlt</code>	77, 78
<code>\@m</code>	368	<code>\@sDTLifstringopenbetween</code>	87–89
		<code>\@sDTLnewdbentry</code>	130, 221
		<code>\@sDTLnewrow</code>	118, 119, 220
		<code>\@sDTLsetheader</code>	128
		<code>\@sDTLsort</code>	196

<code>\@sdtl@getcolumnindex</code>	120, 121, 137, 185, 187, 189, 191, 193, 195, 201, 202	<code>amsmath package</code>	5, 6
<code>\@sdtlforcolumn</code>	152, 186, 187, 190, 192, 194	<code>\and</code>	185, 186, 188, 190, 191, 193, 424
<code>\@sdtlforcolumnidx</code>	153	<code>\andname</code>	14, 287, 331, 336, 440
<code>\@sdtlgetdatatype</code>	123, 135	<code>\appto</code>	74, 306, 314
<code>\@sdtlgetkeydata</code>	136, 137	<code>\arabic</code>	155, 158, 163, 227, 328
<code>\@sdtlgetkeyforcolumn</code>	121, 122, 142	<code>\AtBeginDocument</code>	24
<code>\@secondoftwo</code>	243, 247, 288–290, 400–402	<code>\AtEndDocument</code>	234
<code>\@sgDTLforeachbibentry</code>	327	<b>B</b>	
<code>\@tabacckludge</code>	288	<code>\baselineskip</code>	379, 383, 386, 391, 420, 422
<code>\@tempswafalse</code>	266, 368	<code>beamer class</code>	246
<code>\@tempswatru</code>	266, 368	<code>\begin</code>	6, 133, 152, 153, 175, 178, 212, 248–250, 254–256, 259–262, 264, 266, 292, 305, 306, 314, 315, 324, 344, 348, 363, 370, 379, 380, 387, 388, 390, 398, 399, 418, 425–427
<code>\@text@composite@x</code>	288	<code>\begin@stack</code>	5, 6
<code>\@thisperson</code>	435, 436, 440–448	<code>\begingroup</code>	5, 7, 111, 216, 217, 222, 223, 364
<code>\@xfor@nextelement</code>	240	<code>\beta</code>	286
<code>\@xp</code>	5, 6	<code>\bfseries</code>	369
<code>\\</code>	176, 431	<code>\bgroup</code>	210, 212, 235, 244, 246, 251, 253, 254, 257, 259, 263, 265, 266, 268–270, 272, 278, 279, 289, 300, 306, 308, 315, 398, 414
<code>\{</code>	210–213, 222, 223, 288	<code>\bibtex</code>	345
<code>\}</code>	210, 211, 213, 222, 223, 288	<code>\bibdata</code>	322, 370
<code>\^</code>	110	<code>\bibitem</code>	345, 348, 363, 364
<code>\_</code>	223, 287	<code>\bibliographystyle</code>	322
<code>\_</code>	37, 38, 57, 63, 74, 76, 331, 336–340, 363, 368	<code>\bibstyle</code>	370
<b>A</b>		<code>\boolean</code>	155, 156, 160, 185, 186, 188, 190, 191, 193, 195, 314, 324, 326–328, 344, 348, 363, 370, 377, 384, 398, 406, 414
<code>\AA</code>	287	<code>\boolfalse</code>	2, 3
<code>\aa</code>	287	<code>\booltrue</code>	2
<code>\acronymfont</code>	289, 295	<b>C</b>	
<code>\active</code>	216, 222, 223	<code>\c@DTLbarroundvar</code>	378, 383, 385, 391
<code>\add@accent@</code>	288	<code>\c@DTLbibrow</code>	327, 328
<code>\addtocounter</code>	434	<code>\c@DTLmaxauthors</code>	332
<code>\addtolength</code>	248–250, 254, 258–260, 264, 265, 379, 383, 386, 390, 391, 419, 422	<code>\c@DTLmaxeditors</code>	333
<code>\advance</code>	7, 8, 21, 22, 48, 97–99, 108, 109, 119, 127, 149–151, 155, 156, 159–161, 163, 183, 184, 187–190, 199, 200, 215, 217, 218, 220, 244, 253, 268, 270, 300, 303, 308, 318, 332, 333, 336, 344, 348, 365, 366, 386, 387, 390, 405	<code>\c@DTLpieroundvar</code>	398
<code>\AE</code>	287	<code>\c@DTLplotroundXvar</code>	419, 421
<code>\ae</code>	287	<code>\c@DTLplotroundYvar</code>	417
<code>\aftergroup</code>	209, 212	<code>\c@DTLrow</code>	156, 161
<code>\afterpage</code>	305	<code>\c@people</code>	440–448
<code>\alph</code>	365	<code>\c@person</code>	440, 441
<code>\alpha</code>	286	<code>\capitalisewords</code>	295
		<code>\caption</code>	179
		<code>\catcode</code>	110, 111, 216, 217, 222, 223

<code>\centering</code> .....	250	<code>\datagidx@current@locationstring</code> ..	
<code>\changes</code> .....	152, 292	.....	270, --272, 275
<code>\chapter</code> .....	246, 267	<code>\datagidx@current@prefix</code> .....	271–274
<code>\chaptername</code> .....	337	<code>\datagidx@current@target</code> .	270, --272, 275
<code>\chi</code> .....	287	<code>\datagidx@defaultdatabase</code> .....	
<code>\Children</code> .....	241, 244, 245, --282	.....	277–279, --288, 315
<code>\citation</code> .....	368, 369	<code>\datagidx@dispenryval</code> .....	301
<code>\cite</code> .....	340	<code>\datagidx@displaychild</code> .....	244, 245
<code>\closein</code> .....	221	<code>\datagidx@do@highopt@optimize</code> .....	237
<code>\closeout</code> .....	208, 209, 211, --214	<code>\datagidx@do@highopt@update</code> .....	304
<code>\color</code> .....	374, 380, --388, 396, 423, 424	<code>\datagidx@do@optimize@sort</code> .....	234
<code>\count@</code> .....	22, 75, 76, --303, 317, 318	<code>\datagidx@do@sort</code> .....	235, --237, 317
<code>\cs</code> .....	133, 152, --306	<code>\datagidx@do@usedentry</code> .....	305
<code>\csdef</code> .....	294	<code>\datagidx@docomplst</code> .....	233, --272
<code>\csedef</code> .....	218	<code>\datagidx@doforeachentry</code> .....	318
<code>\cslet</code> .....	290, 294	<code>\datagidx@doifdisplayed</code> .....	
<code>\csname</code> .....	5, 15, --37, 98,	.....	254, --258, 259, 263, 265, --319
99, 112, --114–119, 121, 122, --124, 126,		<code>\datagidx@doiflocwidth</code> .....	251
127, --129–131, 137–139, --141, 146–		<code>\datagidx@doifsymlocwidth</code> .....	251
153, 155, --157–167, 169, 170, --175,		<code>\datagidx@dowrite</code> .....	319
178, 182–184, --200, 210–213, 215,		<code>\datagidx@endgetgroup</code> .....	317, --319
--219–221, 224, 236, --283, 288, 289,		<code>\datagidx@escapelocation</code> .	299, 300, --306
--299, 300, 307, 319, --324, 325, 328,		<code>\datagidx@escapelocationformat</code>	272, --299
329, --341–344, 363–365, --367–370,		<code>\datagidx@foreachchild</code> .....	227, --244
373, 374, --379, 380, 387, --395, 396,		<code>\datagidx@format</code> .....	302, 303, --307
398, 399, --403–405, 433–437, --440–448		<code>\datagidx@formatanchor</code> .....	
<code>\csuse</code> .....	235, 239, --250,	.....	300, --303, 304, 307, 308
271, 291, 292, --295, 303, 307, --317, 318		<code>\datagidx@formatlocation</code> .	270, --275, 276
<code>\csxdef</code> .....	279	<code>\datagidx@formatsymdesc</code> .....	238, --313
<code>\CurrentLocation</code> .....	282, 319	<code>\datagidx@getgroup</code> .....	319
<b>D</b>			
<code>datagidx</code> package .....	210	<code>\datagidx@getlocation</code> .....	270, --272
<code>\datagidx@add@term</code> .....	293, 294	<code>\datagidx@getlocdo</code> .....	272
<code>\datagidx@addchild</code> .....	291	<code>\datagidx@heading</code> .....	277, --279, 314–317
<code>\datagidx@anchorcount</code> .....		<code>\datagidx@highopt@newgidx</code> .....	235
.....	300, --303, 304, 307, 308	<code>\datagidx@highopt@newterm</code> .....	235
<code>\datagidx@bothoftwo</code> .....	290	<code>\datagidx@id</code> .....	303, 304, --307, 308
<code>\datagidx@catsep</code> .....	269	<code>\datagidx@indexfilename</code> .....	278
<code>\datagidx@child</code> .....	294	<code>\datagidx@invert</code> .....	289, 317
<code>\datagidx@childsep</code> .....	266, 267	<code>\datagidx@item@body</code> ...	251–257, --260–263
<code>\datagidx@clearlocationformat</code>	272, --300	<code>\datagidx@label</code> 297, 298, --302, 303, 307–311	
<code>\datagidx@columns</code> .....	226, --314–317	<code>\datagidx@labellist</code> .....	317
<code>\datagidx@compositor</code> .....	233, --271	<code>\datagidx@level</code> 244, 253, --258, 268–270, 319	
<code>\datagidx@count</code> .....	308, 309	<code>\datagidx@list</code> .....	272, --297, 298
<code>\datagidx@current@format</code> .	270, --272–274	<code>\datagidx@loc</code> .....	306
<code>\datagidx@current@location</code> ....	271–274	<code>\datagidx@location@format</code> ....	274, --276
<code>\datagidx@current@locationformat</code> ..		<code>\datagidx@location@sep</code> .....	271, --275
.....	--272–274	<code>\datagidx@location@start</code> .	271, --274–276
		<code>\datagidx@location@startval</code> ..	274, --276
		<code>\datagidx@location@target</code> ....	274, --276

<code>\datagidx@mac</code>	290	<code>\datagidx@style</code>	277, 280, --316, 317
<code>\datagidx@markparent</code>	303	<code>\datagidx@style@index</code>	253
<code>\datagidx@multicols</code>	277, --279, 314–316	<code>\datagidx@subcapsep</code>	269
<code>\datagidx@namenum</code>	290	<code>\datagidx@subcatsep</code>	269, 270
<code>\datagidx@newgidx</code>	277, 278	<code>\datagidx@subject</code>	290
<code>\datagidx@newgidx@update</code>	278, 279	<code>\datagidx@target</code>	303, 304, --307, 308
<code>\datagidx@newsortedlist</code>	242, 243	<code>\datagidx@thisidx</code>	242, --282, 283
<code>\datagidx@newterm</code>	288	<code>\datagidx@thislabel</code>	298
<code>\datagidx@optimize@sort</code>	237	<code>\datagidx@title</code>	314–317
<code>\datagidx@orgfield</code>	289	<code>\datagidx@tmp</code>	306, 307
<code>\datagidx@paren</code>	290	<code>\datagidx@unsort@foreachchild</code>	227
<code>\datagidx@parent</code>	303, 304	<code>\datagidx@usedentry</code>	304, 305
<code>\datagidx@parse@format@label@</code>	302	<code>\datagidx@value</code>	241, 283, --296, 309–311
<code>\datagidx@parse@formatlabel</code>	307, --309–311	<code>\datagidx@write@usedentry</code>	300
<code>\datagidx@parse@formatlabel@</code>	302	<code>\datagidx@xusedentry</code>	305
<code>\datagidx@parse@location</code>	271	<code>\datagidxbalancefalse</code>	277
<code>\datagidx@particle</code>	290	<code>\datagidxbalancetrue</code>	277
<code>\datagidx@person</code>	290	<code>\datagidxchildend</code>	245, --253, 258, 264, --266, 269
<code>\datagidx@place</code>	290	<code>\datagidxchilditem</code>	245, --253, 258, 264, --266, 269
<code>\datagidx@postend</code>	268, --315–317	<code>\datagidxchildstart</code>	244, --253, 257, 263, --266, 269
<code>\datagidx@postheading</code>	277, --279, 314–317	<code>\datagidxconvertchars</code>	289
<code>\datagidx@prestart</code>	268, --314–317	<code>\datagidxcurrentgroup</code>	252, --257, 262, 263, 265, --267, 269, 317–319
<code>\datagidx@prev@format</code>	271–276	<code>\datagidxdescwidth</code>	254–256, --258–262, 264–266
<code>\datagidx@prev@location</code>	271, --274, 276	<code>\datagidxdictindent</code>	268
<code>\datagidx@prev@locationformat</code>	271, --273, 274	<code>\datagidxdictparshape</code>	268, 269
<code>\datagidx@prev@locationstring</code>	--271, 272, 274–276	<code>\datagidxdoseealso</code>	240
<code>\datagidx@prev@prefix</code>	271, --273, 274	<code>\datagidxend</code>	252, 257, --262, 265, 268, --317
<code>\datagidx@prev@target</code>	271, --274–276	<code>\datagidxextendedtoascii</code>	290
<code>\datagidx@rank</code>	290	<code>\datagidxgetchildfields</code>	245, --283
<code>\datagidx@rowcount</code>	308, 309	<code>\datagidxgroupheader</code>	252, --257, 262, 263, --265, 266, 268, 269
<code>\datagidx@saint</code>	290	<code>\datagidxgroupsep</code>	252, --257, 262, 263, --265, 266, 268, 269
<code>\datagidx@save@loc</code>	319	<code>\datagidxhighoptfilename</code>	235, --278
<code>\datagidx@sep</code>	240	<code>\datagidxindent</code>	253, 258, --270
<code>\datagidx@setchildsort</code>	314	<code>\datagidxitem</code>	252, 257, --262, 265, 268, --317
<code>\datagidx@setchildstyle</code>	237, --313	<code>\datagidxlastlabel</code>	292, --294
<code>\datagidx@setfieldvalues</code>	293	<code>\datagidxlink</code>	241, 247, --270, 275, 276, --309, 310
<code>\datagidx@setlocation</code>	238, --313	<code>\datagidxlocalign</code>	249, --255, 256, 260–262
<code>\datagidx@setnamecase</code>	238, --313	<code>\datagidxlocationwidth</code>	248, 249, --251, 254–256, --260–262, 314
<code>\datagidx@setpostdesc</code>	238, --312	<code>\datagidxnamewidth</code>	254, --257–260, 263–266
<code>\datagidx@setprelocation</code>	238, --313		
<code>\datagidx@setsee</code>	238, 313		
<code>\datagidx@showgroups</code>	277, --280, 316, 317		
<code>\datagidx@sort</code>	234, 237, --277, 280, 294, --316		
<code>\datagidx@sort@foreachchild</code>	227		
<code>\datagidx@sortchildren</code>	243		
<code>\datagidx@sortedlist</code>	241–243		

<code>\datagidxprevgroup</code> .....	<code>\db@row@elt@w</code> .....
. 252, --257, 263, 265, --268, 269, 318, 319	119, 131, --140, 149, 159, --181-183, 199, 200, --210
<code>\datagidxseealsoend</code> .....	<code>\db@row@id@end@</code> .....
240, --253, 270	119, 131, --140, 146-149, 160, --181-183, 199, 200, --210
<code>\datagidxseealsoend</code> .....	<code>\db@row@id@w</code> .....
240, --253, 270	119, 131, --140, 146-149, --159, 160, 181-183, --199, 200, 210
<code>\datagidxsetstyle</code> .....	<code>\db@type@id@end@</code> .....
317	. 122, --124, 125, 127-129, --150, 151, 210
<code>\datagidxshowifdraft</code> .....	<code>\db@type@id@w</code> .....
239, --300, 301	. 122, --124, 125, 127-129, --150, 151, 210
<code>\datagidxstart</code> 251, 254, --259, 264, 268, --317	<code>\DBIBCitekey</code> ..
<code>\datagidxstripaccents</code> .....	324-328, --345, 348, 363-365
290	<code>\DBIBentrytype</code> .....
<code>\datagidxsymalign</code> .....	324-328, --364
. 248, --250, 254-256, --260, 261	<code>\DBIBname</code> .....
<code>\datagidxsymbolwidth</code> .....	325-328
. 248-251, --254-256, 260, 261, --314	<code>\DeclareListParser</code> .....
<code>\datagidxtarget</code> .....	233
247, --252, 253, 257, 258, --263, 264, 266, 267, --269, 301	<code>\DeclareOption</code> .....
<code>\datagidxtermkeys</code> .....	371, 372, --393
283	<code>\DeclareOptionX</code> .....
<code>\datagidxwordifygreek</code> .....	239
290	<code>\DeclareRobustCommand</code> .....
<code>dataplot</code> package .....	. 113, --301, 307, 309-312
371	<code>\def</code> .....
<code>datatool</code> package .....	3-6, 8, --10-12, 14-22, --24, 25, 30-34, --37-47, 49, 51, --55, 56, 68-71, --73-76, 82, 83, --85-89, 97-99, --101, 102, 105-109, --111, 112, 122-127, --130, 134, 136, --140, 141, 143, 144, --146-151, 154-156, --169, 171, 175, --177, 178, 181, 182, --185-194, 197, 198, --203, 204, 206-211, --214, 223, 224, --226, 227, 233, --235, 236, 240-242, --251, 252, 254-256, --260-262, 266, --271, 272, 275, --280, 281, 283, --286-289, 297-300, --302, 306, 315-318, --322, 328, 330, --334, 335, 365-368, --371-373, 375, 376, --378, 380, 382, --385, 387, 389, --394-398, 404, --410, 411, 413-415, --424, 427, 428, --431, 432, 434-437
2, --212, 322	<code>\define@boolkey</code> 2, 113, --215, 371, 393, --412
<code>datatool-base</code> package .....	<code>\define@choicekey</code> ... 2, 100, --113, 237-239, 277, --312-314, 322, 375, --411-414
100, --105, 113	<code>\define@key</code> .....
<code>datatool-fp</code> package .....	113, 177, --215, 237, 238, 277, --280, 281, 283, --312-314, 375, 376, --396, 397, 410, 411, --413, 414
2	<code>\Delta</code> .....
<code>\datatoolparenstart</code> .....	287
68-71, --286	<code>\delta</code> .....
<code>\datatoolpersoncomma</code> .....	286
68-71, --286	<code>\Description</code> .....
<code>\datatoolplacecomma</code> .....	231-233, --245, 266, 282
68-71, --286	<code>\DH</code> .....
<code>\datatoolsubjectcomma</code> .....	287
68-71, --286	<code>\dh</code> .....
<code>\db@col@elt@end@</code> .....	287
131, 142, --144, 146-148, 154, --165, 168, 210, --236	<code>\dimen@</code> .....
<code>\db@col@elt@w</code> .....	246, 248-250, --253, 254, 258-260, --263-265, 268, 270, --300, 301
131, 142, --144, 146-148, 154, --165, 168, 210, --236	<code>\disable@keys</code> .....
<code>\db@col@id@end@</code> .....	377, 384
122-125, --127-129, 131, --141, 142, 144-148, --150, 151, 154, 165, --168, 210, 236	
<code>\db@col@id@w</code> .....	
122-125, --127-129, 131, --141, 142, 144-148, --150, 151, 154, 165, --168, 210, 235, 236	
<code>\db@header@id@end@</code> .....	
. 122-125, --127-129, 150, 151, --210	
<code>\db@header@id@w</code> .....	
. 122-125, --127-129, 150, 151, --210	
<code>\db@key@id@end@</code> .....	
. 122, --124, 125, 127-129, --150, 151, 210	
<code>\db@key@id@w</code> .....	
. 122, --124, 125, 127-129, --150, 151, 210	
<code>\db@plist@elt@end@</code> .....	
. 122-125, --127-129, 150, 151, --210	
<code>\db@plist@elt@w</code> .....	
. 122, 124, --127-129, 150, 151, --210	
<code>\db@row@elt@end@</code> .....	
119, 131, --140, 149, 160, --182, 183, 199, 200, --210	



<code>\discretionary</code> .....	300, 301	<code>\dtl@constructticklistwithgap</code> .....	.....
<code>\divide</code> .....	21, 378, 385, 415, 416	<code>\dtl@constructticklistwithgapex</code> ...	430
<code>\dlt@parsewordshandler</code> .....	77	<code>\dtl@constructticklistwithgapz</code> ....	.....
<code>\do</code> .....	7-12, 15, 24, 25, 30-34, 97-99, 115-117, 137, 138, 149, 150, 158, 162, 170, 175, 178, 179, 185, 187-189, 191, 193, 195, 197, 198, 201, 202, 206, 209, 211, 213, 215, 221, 224, 240-244, 270, 272, 282, 298, 320, 329, 332, 333, 336, 365, 368, 369, 378, 379, 382, 384-387, 391, 398, 416-422, 435-437, 440, 441	<code>\dtl@createalphabiblabels</code> .....	363, 364
<code>\do@dtlreplaceincurrentrow</code> .....	146	<code>\dtl@cutawayoffset</code> .....	397, 404, 405
<code>\do@getrow</code> .....	.....	<code>\dtl@cutlen</code> .....	399
. 241, 242, 244, 296, 297, 301-307, 316		<code>\dtl@decrementrows</code> .....	141, 159, 184
<code>\do@locrange</code> .....	275	<code>\dtl@decx</code> .....	195, 406, 424-427
<code>\do@prevlocation</code> .....	271, 274	<code>\dtl@decy</code> .....	195, 406, 424-427
<code>\do@update</code> .....	294	<code>\dtl@diff</code> .....	189, 190
<code>\document</code> .....	369	<code>\dtl@do@setkeys</code> .....	316
<code>\dotfill</code> .....	229	<code>\dtl@do@setwordbreaks</code> .....	74, 75
<code>\draw</code> .....	380, 382, 388, 390, 399, 402, 403, 418-422, 425-427	<code>\dtl@dogetentry</code> .....	.....
<code>\dtl@A@first</code> .....	73	. 130, 131, 143-145, 164, 166-168, 170	
<code>\dtl@A@remain</code> .....	73	<code>\dtl@dogetrow</code> .	130, 158, 184, 293, 294, 296
<code>\dtl@abbrvmonthname</code> .....	363	<code>\dtl@dogetrowindex</code> .....	147, 148
<code>\dtl@addtolegend</code> .....	424	<code>\dtl@dogetvalue</code> .....	146
<code>\dtl@angle</code> .....	399, 403-405	<code>\dtl@domappings</code> .....	216
<code>\dtl@argi</code> .....	39, 41	<code>\dtl@donext</code> ..	54, 55, 65-67, 70, 76, 82-85
<code>\dtl@argii</code> .....	39-41	<code>\dtl@dotestiflowernext</code> .....	42
<code>\dtl@asg@rowidx</code> .....	133	<code>\dtl@dotestifuppernext</code> .....	40
<code>\dtl@assignfirstmatch</code> .....	132, 133	<code>\dtl@dx</code> .....	415, 420, 425, 426
<code>\dtl@B@first</code> .....	73	<code>\dtl@dy</code> .....	416, 422, 426
<code>\dtl@B@remain</code> .....	73	<code>\dtl@end@if@two@octets</code> ..	4, 55-57, 64, 75
<code>\dtl@barlabel</code> .....	376, 381, 390	<code>\dtl@end@if@case@chargroup</code> ....	69, 70, 75
<code>\dtl@barvar</code> .....	377, 378, 384, 385	<code>\dtl@endangle</code> .....	399
<code>\dtl@bounds</code> .....	413, 415	<code>\dtl@endhyp</code> .....	38, 39
<code>\dtl@checkendsperiod</code> .....	329, 330	<code>\dtl@entry</code> 130, 131, 144, 145, 164, 166-168	
<code>\dtl@chopfirst</code> .....	.....	<code>\dtl@entrycr</code> .....	215, 218-222
..... 383, 388, 391, 419, 421, 423, 424		<code>\dtl@extent</code> .....	378, 385, 399
<code>\dtl@citex</code> .....	368	<code>\dtl@first</code> .....	53, 55, 56, 65, 75, 82-84
<code>\dtl@code</code> .....	41, 42	<code>\dtl@firstA</code> .....	53-55, 65-67, 83-85
<code>\dtl@codeA</code> .....	53, 54, 56, 65, 66, 84	<code>\dtl@firstB</code> .....	53-55, 65, 67, 84, 85
<code>\dtl@codeB</code> .....	53, 54, 56, 65, 66, 84	<code>\dtl@forcolum</code> .....	152, 153
<code>\dtl@compare@</code> .....	203, 204	<code>\dtl@g@gathervalues</code> .....	327, 328
<code>\dtl@computeangles</code> .....	398	<code>\dtl@gathervalues</code> .....	325-327
<code>\dtl@construct@subnobrsp</code> .....	37	<code>\dtl@get@firstthree</code> .....	364, 366
<code>\dtl@constructminorticklist</code> ...	416, 417	<code>\dtl@get@yearsuffix</code> .....	364, 366
<code>\dtl@constructticklist</code> 378, 385, 416, 417		<code>\dtl@getauthorinitial</code> .....	365, 366
		<code>\dtl@getbounds</code> .....	415
		<code>\dtl@getentryfromrow</code> .....	143
		<code>\dtl@getfirst</code> .....	53, 65, 82, 83
		<code>\dtl@getfirst@UTFviii</code> .....	4, 56, 75
		<code>\dtl@getfirstthree</code> .....	366
		<code>\dtl@getsinglalphalabel</code> .....	365, 366
		<code>\dtl@getvalue</code> .....	146
		<code>\dtl@getyearsuffix</code> .....	366, 367

<code>\dtl@grabword</code>	73	<code>\dtl@outhernodeopt</code>	400–403
<code>\dtl@if@two@octets</code>	4, 56, 57, 64, 75	<code>\dtl@outeroffset</code>	397, 403
<code>\dtl@ifcasechargroup</code>	69, 70	<code>\dtl@parsewordshandler</code>	76
<code>\dtl@ifsingle</code>	4, 17, 30, 31, 38, 45, 51, 56, 82, 84, 86, 87, 89, 111, 367	<code>\dtl@piecutaways</code>	397, 398
<code>\dtl@ifsingleorUTFviii</code>	53, 65	<code>\dtl@plotlinecolorlist</code>	415, 423
<code>\dtl@inithyphen</code>	38, 39	<code>\dtl@plotlinelist</code>	414, 423
<code>\dtl@initials</code>	37, 38	<code>\dtl@plotmarkcolorlist</code>	414, 423
<code>\dtl@initialscmd</code>	37, 38	<code>\dtl@plotmarklist</code>	414, 423
<code>\dtl@initialshyphen</code>	38	<code>\dtl@post</code>	166, 168
<code>\dtl@initialsnext</code>	38, 39	<code>\dtl@pre</code>	166, 168
<code>\dtl@innerlabel</code>	397, 402	<code>\dtl@prevtick</code>	416, 417
<code>\dtl@innernodeopt</code>	400, 402	<code>\dtl@rawwrite@db</code>	213
<code>\dtl@inneroffset</code>	397, 402	<code>\dtl@rawwrite@keys</code>	213
<code>\dtl@insertinto</code>	10	<code>\dtl@refvalue</code>	196
<code>\dtl@int@round</code>	108	<code>\dtl@remainder</code>	423
<code>\dtl@int@trunc</code>	108, 109	<code>\dtl@rest</code>	4, 53, 55, 56, 65, 82–84, 383, 388, 391, 419, 421, 424
<code>\dtl@labelangle</code>	400	<code>\dtl@restA</code>	53–55, 65–67, 83–85
<code>\dtl@lccode</code>	42	<code>\dtl@restB</code>	53–55, 65–67, 84, 85
<code>\dtl@legend</code>	415, 425–427, 431	<code>\dtl@row</code>	398
<code>\dtl@legendlabels</code>	414, 415, 424	<code>\dtl@rowi</code>	155
<code>\dtl@legendline</code>	431	<code>\dtl@rowidx</code>	139, 293, 294
<code>\dtl@legendsetting</code>	414, 424, 425	<code>\dtl@rowii</code>	155
<code>\dtl@linestyle</code>	423–425	<code>\dtl@rowiii</code>	155
<code>\dtl@listgetalphalabel</code>	364	<code>\dtl@sang</code>	404, 405
<code>\dtl@mark</code>	423–425	<code>\dtl@saverawdbhook</code>	210, 235
<code>\dtl@maxx</code>	413, 415	<code>\dtl@scale@x</code>	410, 415, 416, 418, 421, 422, 424–427
<code>\dtl@maxy</code>	413, 415	<code>\dtl@scale@y</code>	410, 416–420, 424–427
<code>\dtl@mean</code>	188–190	<code>\dtl@segang</code>	404
<code>\dtl@message</code>	114, 116, 119, 131, 141–143, 145, 146, 165, 166, 168, 206, 210, 212, 217, 324, 325, 364	<code>\dtl@setcharcode</code>	53, 84, 317
<code>\dtl@midangle</code>	399–403	<code>\dtl@setlccharcode</code>	65
<code>\dtl@mingap</code>	378, 385, 416, 417	<code>\dtl@setwordbreaks</code>	72
<code>\dtl@minx</code>	413, 415	<code>\dtl@setwordbreaksnohyphens</code>	65, 74, 81, 83
<code>\dtl@miny</code>	413, 415	<code>\dtl@sg@arg</code>	4
<code>\dtl@monthname</code>	344, 349	<code>\dtl@sortdata</code>	198
<code>\dtl@multibar@labels</code>	387, 388	<code>\dtl@sortresult</code>	10, 12, 199, 203, 205, 206
<code>\dtl@multibarlabels</code>	376, 386, 387	<code>\dtl@split@str</code>	43
<code>\dtl@multimidpt</code>	387, 390	<code>\dtl@splitstr</code>	43, 44
<code>\dtl@n</code>	387	<code>\dtl@srtelement</code>	10, 12, 13
<code>\dtl@nexttick</code>	416, 417	<code>\dtl@start</code>	398, 399
<code>\dtl@offset@x</code>	416, 418, 421, 422, 424–427	<code>\dtl@stream</code>	424, 425
<code>\dtl@offset@y</code>	416–420, 424–427	<code>\dtl@string</code>	37, 38, 65, 72, 74–76, 81–83
<code>\dtl@old</code>	377, 378, 384, 385, 398, 399, 403–405	<code>\dtl@subnohrsp</code>	37, 38, 53, 64, 67, 74, 76, 81, 83
<code>\dtl@oldtotal</code>	398	<code>\dtl@tc@arg</code>	40, 41
<code>\dtl@omitlines</code>	215, 217	<code>\dtl@tc@rest</code>	39–42
<code>\dtl@outerlabel</code>	397, 403	<code>\dtl@test@iflowercase</code>	41, 42



<code>\dtl@test@ifuppercase</code>	40	<code>\dtl@thisloc</code>	270
<code>\dtl@testbibfieldcontains</code>	344	<code>\dtl@thisplotline</code>	423, 424
<code>\dtl@testbibfieldexists</code>	340	<code>\dtl@thisplotlinecolor</code>	423, 424
<code>\dtl@testbibfieldiseq</code>	341	<code>\dtl@thisplotmark</code>	423
<code>\dtl@testbibfieldisge</code>	343	<code>\dtl@thisplotmarkcolor</code>	423
<code>\dtl@testbibfieldisgt</code>	342	<code>\dtl@thisrow</code>	162, 185, 187, 189, 191, 193
<code>\dtl@testbibfieldisle</code>	342	<code>\dtl@thistick</code>	..... 377, 378, 382-385, 391, 418-422
<code>\dtl@testbibfieldislt</code>	341	<code>\dtl@thisticklabel</code>	419, 421
<code>\dtl@testbothnumerical</code>	..... 77-79, 81, 86, 87, 89	<code>\dtl@thisupperbarlabel</code>	388, 389
<code>\dtl@testclosedbetween</code>	92	<code>\dtl@thisval</code>	25, 30-34
<code>\dtl@testcurrency</code>	96	<code>\dtl@ticklength</code>	419-422
<code>\dtl@testcurrencyunit</code>	96	<code>\dtl@ticlabeloffset</code>	419-422
<code>\dtl@tetesteq</code>	91	<code>\dtl@tlc</code>	41
<code>\dtl@testFPiseq</code>	95	<code>\dtl@tmp</code>	38, 74, 76, 134, 149, 184, 211, 213, 223, 398, 430
<code>\dtl@testFPisgt</code>	94	<code>\dtl@tmpi</code>	387
<code>\dtl@testFPisgteq</code>	95	<code>\dtl@tmpii</code>	387
<code>\dtl@testFPislt</code>	94	<code>\dtl@tmplength</code>	248-250, 258, 268, 326, 365, 378, 379, 383, 385, 386, 390-392, 417, 418, 422, 430
<code>\dtl@testFPislteq</code>	95	<code>\dtl@tmpshift</code>	107, 108
<code>\dtl@testFPopenbetween</code>	93	<code>\dtl@total</code>	398, 403
<code>\dtl@testgt</code>	90	<code>\dtl@truncatedecimal</code>	22, 399, 400
<code>\dtl@testiceq</code>	91	<code>\dtl@tuc</code>	39
<code>\dtl@testicgt</code>	91	<code>\dtl@uccode</code>	40, 41
<code>\dtl@testiclosedbetween</code>	93	<code>\dtl@unit</code>	378, 379, 385, 387
<code>\dtl@testiclt</code>	90	<code>\dtl@upperbarlabel</code>	376, 382
<code>\dtl@testiflowercase</code>	41, 42	<code>\dtl@uppermultibar@labels</code>	387, 388
<code>\dtl@testiflowernext</code>	41, 42	<code>\dtl@uppermultibarlabels</code>	376, 387
<code>\dtl@testifsubstring</code>	81, 91, 344	<code>\dtl@variable</code>	380-382, 388, 389, 398
<code>\dtl@testifuppercase</code>	39-41	<code>\dtl@widest</code>	325, 326, 364, 365
<code>\dtl@testifuppernext</code>	39-41	<code>\dtl@x</code>	406, 420, 424
<code>\dtl@testinlist</code>	91	<code>\dtl@xkey</code>	410, 414, 415, 424
<code>\dtl@testint</code>	96	<code>\dtl@xlabel</code>	414, 420
<code>\dtl@testiopenbetween</code>	93	<code>\dtl@xminorticlist</code>	416, 418, 420
<code>\dtl@testlt</code>	90	<code>\dtl@xticgap</code>	413, 416
<code>\dtl@testnumclosedbetween</code>	92	<code>\dtl@xticlabelheight</code>	386, 390, 416, 419
<code>\dtl@testnumerical</code>	96	<code>\dtl@xticlabels</code>	414, 416, 419
<code>\dtl@testnumopenbetween</code>	92	<code>\dtl@xticlist</code>	413, 416, 419
<code>\dtl@testopenbetween</code>	93	<code>\dtl@y</code>	406, 422, 424
<code>\dtl@testreal</code>	96	<code>\dtl@ykey</code>	410, 414, 415, 424
<code>\dtl@teststartswith</code>	82, 91	<code>\dtl@ylabel</code>	414, 417, 422
<code>\dtl@teststring</code>	96	<code>\dtl@yminorticlist</code>	417, 419, 422
<code>\dtl@textopt</code>	380-383, 388-391	<code>\dtl@yticgap</code>	414, 417
<code>\dtl@this</code>	387	<code>\dtl@yticlabels</code>	414, 417, 421
<code>\dtl@thisbarlabel</code>	388, 389	<code>\dtl@yticlabelwidth</code>	378, 379, 383, 385, 386, 391, 392, 417, 418, 422
<code>\dtl@thisdb</code>	195, 422, 424	<code>\dtl@yticlist</code>	413, 417, 419, 421
<code>\dtl@thisfield</code>	329		
<code>\dtl@thisidx</code>	162		
<code>\dtl@thislabel</code>	240, 320, 378, 379, 383, 385, 386, 391, 417-421, 424		

<code>\DTLabs</code> .....	28	<code>\DTLbarwidth</code> .....	376, 379, --387
<code>\dtlabs</code> .....	28	<code>\DTLbarxaxisfalse</code> .....	375
<code>\DTLacmcs</code> .....	349, 363	<code>\DTLBarXAxisStyle</code> .....	382, --390
<code>\DTLacta</code> .....	349, 363	<code>\DTLbarxaxistrue</code> .....	375
<code>\DTLadd</code> .....	25, 185–190	<code>\DTLbarXlabelalign</code> .....	
<code>\dtladd</code> .....	25, 32–	.....	371, 372, --380, 381, 386, --388–390
34, --377, 384, 387, 388, --390, 398, 399,		<code>\DTLbaryaxisfalse</code> .....	375
--403–405, 420, 421, --424–427, 429, 431		<code>\DTLBarYAxisStyle</code> .....	382, --390
<code>\dtladdalign</code> .....	175, 178	<code>\DTLbaryaxistrue</code> .....	375, 376
<code>\DTLaddall</code> .....	26	<code>\DTLbarYticklabelalign</code>	371, 372, --383, 391
<code>\DTLaddcolumn</code> .....	279, --282, 283	<code>\DTLbaryticsfalse</code> .....	375
<code>\DTLaddcomma</code> .....	337, 339, --350–362	<code>\DTLbaryticstrue</code> .....	375, 376
<code>\DTLaddperiod</code> .....	349–362	<code>\dtlbeforecols</code> .....	173
<code>\DTLaddtopplotlegend</code> .....	424	<code>\dtlbeforerow</code>	131, --140, 141, 158, 181, --184
<code>\dtlaftercols</code> .....	173	<code>\dtlbetweencols</code> .....	173
<code>\DTLafterinitialbeforehyphen</code> .....		<code>\DTLbetweeninitials</code> .....	38, --365, 366
.....	39, --365, 366	<code>\dtlbib@style</code> .....	322, 367
<code>\DTLafterinitials</code> .....	38, --365, 366	<code>\DTLBIBdbname</code> .....	322, 323, --370
<code>\dtlafterrow</code> .	131, --140, 141, 158, 181, --184	<code>\DTLbibfield</code> .....	330, --336–340, 349–362
<code>\DTLandlast</code> .....	332, 333	<code>\DTLbibitem</code> .....	324, 348, --363
<code>\DTLandname</code> .....	14	<code>\DTLbibliographystyle</code> .....	367
<code>\DTLandnotlast</code> .....	332, 333	<code>\DTLboxfalse</code> .....	412
<code>\dtlappendtrytocurrentrow</code> .....		<code>\dtlbreak</code>	97–99, --149–151, 153, 154, --170, 196
.....	303, 304, --306–308	<code>\dtlbst@plain</code> .....	362, 363
<code>\DTLappendrow</code> .....	164	<code>\DTLcacm</code> .....	349, 363
<code>\DTLappendtorow</code> .....	170	<code>\DTLcheckbibfieldendsperiod</code> .....	
<code>\DTLassignfirstmatch</code> .....	133	.....	337, --339, 350–362
<code>\dtlautokeysfalse</code> .....	215	<code>\DTLcheckendsperiod</code> .....	
<code>\dtlbar@groupgap</code> .....	376, 387, --390	.....	330, --332–336, 351, --353, 354, 357
<code>\dtlbar@variables</code> .....	375, --384, 385, 387	<code>\DTLclip</code> .....	36
<code>\dtlbar@ylabel</code>	376, 378, --383, 385, 391, 392	<code>\dtlclip</code> .....	36, 175, --178
<code>\dtlbar@yticgap</code> .....	376–378, --384, 385	<code>\dtlcol</code> .....	170
<code>\dtlbar@yticlabels</code> .....		<code>\DTLcolorbarchartfalse</code> .....	371
.....	376, --378, 379, 383, --385, 386, 391	<code>\DTLcolorbarcharttrue</code> .....	371
<code>\dtlbar@yticlist</code> .	376, 378, --382, 385, 391	<code>\DTLcolorpiechartfalse</code> .....	393
<code>\DTLbaratbegintikz</code> .....	380, --387	<code>\DTLcolorpiecharttrue</code> .....	393
<code>\DTLbaratendtikz</code> .....	384, 392	<code>\dtlcolumnindex</code> .....	124, 126, --129,
<code>\DTLbarchart</code> .....	374	130, 133, 134, --139, 144, 145, 152,	
<code>\DTLbarchartlength</code>	375, --378, 383, 385, --391	--164, 242, 244, 245, --283, 293, 294,	
<code>\DTLbarchartwidth</code> .....	379, --382, 387, 390	--296, 297, 301–304, --306–308, 316, 325	
<code>\DTLbardisplayYticklabel</code> .....		<code>\dtlcolumnnum</code> .	126–131, --144–146, 164–168
.....	378, 379, --383, 386, 391	<code>\dtlcompare</code> .....	
<code>\DTLbargroupwidth</code> .....	387	70, 74, --77, 78, 80, 85, --88, 196, 341–343	
<code>\DTLbarlabeloffset</code> ....	380, 381, --388–390	<code>\dtlcomparewords</code> .....	71
<code>\DTLbarmax</code> .	375, 377, 378, --382, 384, 385, 390	<code>\DTLcomputebounds</code> .....	415
<code>\DTLbaroutlinecolor</code> .....	380, --388	<code>\DTLconverttodecimal</code> .....	16, 17,
<code>\DTLbaroutlinewidth</code> .....	380, --388	--25–36, 51, 78, --80, 85, 87, --195, 377,	
<code>\DTLbarvariable</code> .....	375,	378, 380, --384, 385, 388, 398, --406, 424	
--377, 378, 380, 381, --384, 385, 387–389		<code>\dtlcurrencyalign</code> .....	173

`\dtlcurrencyformat` ..... 176, 180  
`\DTLcurrentindex` ..... 158, 162  
`\dtlcurrentrow` .... 131, 140–143, 158,  
162, 164, 166–168, 170, 181, 185,  
187, 189, 191, 193, 195, 196, 325–328  
`\dtlcurrentvalue` ..... 139  
`\DTLcutawayratio` ..... 394, 397  
`\dtldbname` ..... 138–146  
`\DTLdecimaltocurrency` .... 25–30, 32–36  
`\DTLdecimaltolocale` . 25–30, 32, 33, 35, 36  
`\dtldefaultkey` ..... 218, 220  
`\dtldisplayafterhead` .... 176, 179, 180  
`\dtldisplayacr` ..... 176, 177, 179, 180  
`\dtldisplayendtab` ..... 176, 180  
`\DTLdisplayinnerlabel` ..... 402  
`\DTLdisplaylowerbarlabel` . 381, 386, 390  
`\DTLdisplaylowermultibarlabel` .... 389  
`\DTLdisplayouterlabel` ..... 403  
`\dtldisplaystartrow` ..... 176, 177  
`\dtldisplaystarttab` ..... 175, 178, 179  
`\DTLdisplayupperbarlabel` ..... 382  
`\DTLdisplayuppermultibarlabel` .... 389  
`\dtldisplayvalign` ..... 175  
`\DTLdiv` ..... 28, 187–190  
`\dtldiv` ..... 27, 32–34, 378, 385,  
398, 403, 415–417, 419–422, 428, 430  
`\DTLdobarcolor` ..... 374  
`\DTLdocurrentbarcolor` ..... 380  
`\dtldofirstlocation` ..... 229  
`\dtldolocationlist` ..... 229  
`\DTLdopiesegmentcolor` ..... 396  
`\DTLendbibitem` ..... 324, 370  
`\DTLendpt` ..... 381, 382, 389  
`\DTLeverybarhook` ..... 382, 390  
`\dtlexpandnewvalue` ..... 279, 290  
`\dtlforcolumm` ..... 279, 282, 297, 298  
`\dtlforcolumnid` ..... 152, 153  
`\DTLforeach` .... 156, 161, 164, 165, 167,  
169–172, 254, 258, 259, 263, 265, 318  
`\DTLforeachbibentry` ... 324, 326, 364, 370  
`\dtlforeachkey` .... 115–117, 137, 138,  
170, 175, 178, 179, 206, 209, 211, 213  
`\DTLforeachkeyinrow` ... 176, 180, 207, 208  
`\dtlforeachlevel` .....  
. 155–170, 374, 380, 395, 396, 398, 399  
`\DTLformatabbrvforenames` ..... 362  
`\DTLformatarticle` ..... 349  
`\DTLformatarticlecrossref` ..... 350  
`\DTLformatauthor` ..... 332, 349, 362  
`\DTLformatauthorlist` ..... 349,  
350, 352, 354–356, 358, 359, 361, 362  
`\DTLformatbibentry` ..... 324, 325, 370  
`\DTLformatbook` ..... 350  
`\DTLformatbookcrossref` ..... 351, 353  
`\DTLformatbooklet` ..... 352  
`\DTLformatbooktitle` ..... 339, 350  
`\DTLformatbvolume` .... 351, 353–355, 360  
`\DTLformatchapterpages` ..... 353, 354  
`\DTLformatcrossrefeditor` ..... 338  
`\DTLformatdate` .... 350, 352, 353, 355–362  
`\DTLformatedition` . 349, 351, 353, 354, 357  
`\DTLformateditor` ..... 333, 349, 362  
`\DTLformateditorlist` .. 339, 350, 352, 360  
`\DTLformatforenames` ..... 346, 349  
`\DTLformatinbook` ..... 352  
`\DTLformatincollection` ..... 354  
`\DTLformatincolprocrossref` .. 354, 355  
`\DTLformatinedbooktitle` ..... 354, 355  
`\DTLformatinproceedings` ..... 355  
`\DTLformatjr` ..... 346, 349, 362, 363  
`\DTLformatlegend` ..... 425–427  
`\DTLformatmanual` ..... 356  
`\DTLformatmastersthesis` ..... 358  
`\DTLformatmisc` ..... 358  
`\DTLformatnumberseries` 351, 354, 355, 360  
`\DTLformatpages` ..... 337, 350, 355  
`\DTLformatphdthesis` ..... 359  
`\DTLformatproceedings` ..... 360  
`\DTLformatsurname` .... 346, 349, 362, 363  
`\DTLformatsurnameonly` ..... 336  
`\DTLformattechreport` ..... 361  
`\DTLformatunpublished` ..... 362  
`\DTLformatvolnumpages` ..... 350  
`\DTLformatvon` ..... 346, 349, 362, 363  
`\DTLgetbarcolor` ..... 388  
`\DTLgetdatatype` ..... 204, 205, 225  
`\dtlgetentryfromcurrentrow` .....  
..... 130, 134, 139, 143–145,  
164, 166, 167, 170, 195, 244, 245,  
283, 294, 296, 302–304, 306–308, 316  
`\dtlgetentryfromrow` ..... 138,  
143, 185, 187, 189, 191, 193, 201, 202  
`\DTLgetpiesegmentcolor` ..... 399  
`\dtlgetrow` 130, 132, 133, 158, 181, 184, 308  
`\DTLgetrowforkey` ..... 195  
`\dtlgetrowforvalue` .... 139, 241, 244,  
294, 296, 297, 301, 303–305, 307, 316  
`\dtlgetrowindex` ..... 133, 139, 293

\DTLgetvalueforkey ..... 364  
\dTLgforint ..... 99, 158, --221  
\DTLgidxAcrStyle ..... 295, --311, 312  
\DTLgidxAssignList ..... 283, --318  
\DTLgidxCategoryNameFont ..... 269  
\DTLgidxCategorySep ..... 269  
\DTLgidxChildCountLabel ..... 227, --270  
\DTLgidxChildren ..... 229  
\DTLgidxChildrenSeeAlso ..... 253,  
--257, 259-262, 264, --266, 267, 269, 270  
\DTLgidxChildSep ..... 267  
\DTLgidxChildStyle .....  
..... 227, --253, 258, 264, --267, 269  
\DTLgidxCounter ..... 303, 305, --307  
\DTLgidxCurrentdb .....  
..... 235, 236, --241, 242, 244-246,  
--254, 258, 259, 263, --265, 283, 316-318  
\DTLgidxDictHead ..... 268  
\DTLgidxDictPostItem ..... 269  
\DTLgidxDoSeeOrLocation .... 251-253,  
--255, 256, 259-262, --264, 266, 267, 270  
\DTLgidxFetchEntry .... 241, --301, 309-311  
\DTLgidxForeachEntry ..... 317  
\DTLgidxFormatAcr ..... 312  
\DTLgidxFormatAcrUC ..... 312  
\DTLgidxFormatDesc ..... 231-233  
\DTLgidxFormatSee ..... 229, 230  
\DTLgidxFormatSeeAlso ..... 229  
\DTLgidxGroupHeaderTitle .....  
..... 252, --262, 265, 267  
\DTLgidxIgnore ..... 235, 290  
\DTLgidxLocation ..... 229, 241  
\DTLgidxLocationF ..... 276  
\DTLgidxLocationFF ..... 276  
\DTLgidxLocationSep ..... 275  
\DTLgidxMac ..... 235, 290  
\DTLgidxName ..... 235, --289, 290, 317  
\DTLgidxNameCase .....  
. 228, --251-254, 257-259, --263-267, 269  
\DTLgidxNameFont ..... 238,  
--251-254, 257-259, --263-267, 269, 313  
\DTLgidxNameNum ..... 235, 290  
\DTLgidxNoFormat ..... 289  
\DTLgidxOffice ..... 235, 290, --317  
\DTLgidxParen ..... 235, --289, 290  
\DTLgidxParticle ..... 235, 290  
\DTLgidxPlace ..... 235, --289, 290, 317  
\DTLgidxPostChild ..... 266  
\DTLgidxPostChildName .....  
..... 253, --258, 264, 267, --269, 270  
\DTLgidxPostDescription .. 228, --231-233  
\DTLgidxPostName ..... 228, 238, --252,  
254, 257, --259, 263, 265, 266, --269, 313  
\DTLgidxPreLocation ..... 228-  
230, --241, 248, 249, --254-256, 260-262  
\DTLgidxRank ..... 235, 290  
\DTLgidxSaint ..... 235, 290  
\DTLgidxSee ..... 230, 241  
\DTLgidxSeeAlso ..... 229  
\DTLgidxSeeList ..... 239, 240  
\DTLgidxSeeTagFont ..... 239, 240  
\DTLgidxSetColumns ..... 237, --313  
\DTLgidxSetCompositor ..... 233, --238  
\DTLgidxSubCategorySep ..... 270  
\DTLgidxSubject ..... 235, --289, 290, 317  
\DTLgidxSymbolDescLeft .....  
. 231, 232, --248, 250, 255, 256, --260, 261  
\DTLgidxSymbolDescRight .....  
. 231-233, --248, 250, 255, 256, --260, 261  
\DTLgidxSymbolDescription .....  
..... 249, --252, 253,  
256, 259, --262, 264, 266, 267, --269, 270  
\DTLgidxSymDescSep .....  
. 231-233, --248, 250, 254-256, --260, 261  
\DTLgnewdb ..... 279  
\dTLheader ..... 170  
\dTLheaderformat ..... 175, --178-180  
\DTLibmjrd ..... 349, 363  
\DTLibmsj ..... 349, 363  
\dTLicompare ... 73, 77, --79, 80, 86, 88, --197  
\dTLicomparewords ..... 70, 71  
\DTLidxFormatSeeItem ..... 240  
\DTLidxSeeLastSep ..... 240  
\DTLidxSeeSep ..... 240  
\DTLIEEE ..... 349, 363  
\DTLIEEEetc ..... 349, 363  
\DTLIEEEetcad ..... 349, 363  
\DTLifanybibfieldexists .. 336, --350-362  
\DTLifbibfieldexists .....  
..... 331, --333, 335-344, --349-362, 364  
\dTLifcasechargroup ..... 75  
\DTLifclosedbetween ..... 92  
\DTLifcurrency ..... 96  
\DTLifcurrencyunit ..... 96  
\DTLifdbexists .....  
..... 114-121, --123, 125, 128, --130,  
132, 133, 137, --152, 153, 156, 160,

--169, 183, 186, 187, --189, 192, 194,  
 --197, 206, 208, 209, --212, 293, 308, --315  
 \DTLlifeq ..... 91  
 \DTLliffirstrow .... 157, --160, 161, 163, 176  
 \DTLlifFPclosedbetween ..... 85  
 \DTLlifFPopenbetween . 87, --93, 416, 417, 428  
 \DTLlifgt ..... 90  
 \DTLlifhaskey ..... 197  
 \DTLlifinlist ... 91, 175, 176, --178–180, 433  
 \DTLlifint ..... 75, 96, --226  
 \dtlifintclosedbetween .. 75, 76, --317, 318  
 \dtlifintopenbetween ..... 5  
 \DTLliflastrow ..... 157, --160, 161, 163  
 \DTLliflt ..... 90  
 \DTLlifnull .....  
 . 136, 196, --201, 202, 208, --229, 230,  
 241, 244, --254, 258, 259, 263, --265,  
 271, 303, 304, --307, 308, 318–320, --329  
 \DTLlifnumclosedbetween ..... 87, --92  
 \dtlifnumclosedbetween ..... 90  
 \DTLlifnumeq ..... 81  
 \dtlifnumeq .....  
 .. 19, 20, 23, --80, 94, 102, --401, 402, 429  
 \DTLlifnumerical ..... 96, --336, 337  
 \DTLlifnumgt ..... 79, 205  
 \dtlifnumgt ..... 31,  
 78, --94, 95, 101, 102, --401, 403, 427, 428  
 \DTLlifnumlt ..... 78, 205, --381, 389  
 \dtlifnumlt ..... 30,  
 51, --94, 95, 101, 102, --400, 402, 403, 428  
 \DTLlifnumopenbetween ..... 89, --92  
 \dtlifnumopenbetween ..... 89, --400–402  
 \DTLlifoddrow ..... 157, 160, --162, 163  
 \DTLlifopenbetween ..... 93  
 \DTLlifreal ..... 96  
 \DTLlifstring ..... 96  
 \DTLlifSubString ..... 12, 13, --366  
 \DTLlinitialhyphen ..... 39, --365, 366  
 \DTLlinnerratio ..... 394, 397  
 \dtlinsertinto ..... 11, 13  
 \dtlintalign ..... 173  
 \dtlintformat ..... 176, 180  
 \DTLipl ..... 349, 363  
 \DTLisclosedbetween ..... 424  
 \DTLisFPclosedbetween ..... 378, --385  
 \DTLisFPplt ..... 378, 385  
 \DTLisFPopenbetween ... 377, --384, 429, 431  
 \DTLisnumclosedbetween ..... 93  
 \DTLisnumerical 185, 186, --188, 190, 191, 193  
 \DTLjacm ..... 349, 363  
 \DTLjcss ..... 349, 363  
 \dtlkey ..... 170, 176, --180, 208  
 \dtllastloadeddb .. 209, 211, --214, 278, 279  
 \DTLlegendxoffset ..... 425–427  
 \DTLlegendyoffset ..... 425–427  
 \DTLlistformatitem ..... 14  
 \DTLlistformatlastsep ..... 14  
 \DTLlistformatoxford ..... 14  
 \DTLlistformatsep ..... 14  
 \DTLlistskipemptytrue ..... 6  
 \DTLmajorgridstyle ..... 419  
 \DTLmax ..... 31, 193, 194  
 \dtlmax ..... 31, 32, 195, --377, 384, 428  
 \DTLmaxall ..... 32  
 \DTLmaxX .....  
 . 415, 416, --418, 419, 421, 422, --424–427  
 \DTLmaxY ..... 415–421, --424, 425, 427  
 \DTLmbibitem ..... 348, 363, --370  
 \DTLmeanforall ..... 33  
 \DTLmeanforcolumn ..... 189  
 \DTLmidpt ..... 382, 389  
 \DTLmidsentencefalse .....  
 ..... 324, 325, --331, 339, 350, --359  
 \DTLmidsentencetrue ..... 331  
 \DTLmin ..... 30, 192, --378, 385  
 \dtlmin ..... 30, 195  
 \DTLminall ..... 31  
 \DTLminminortickgap ..... 430  
 \DTLminorgridstyle ..... 418, 419  
 \DTLminorticklength ..... 420, --422  
 \DTLmintickgap ..... 378, 385, --416, 417  
 \DTLminX ..... 415, 416, --418–422, 424–427  
 \DTLminY ..... 415–420, 422, --424, 426, 427  
 \DTLmonthname ..... 349, 363  
 \DTLmul ..... 27, 189, 190  
 \dtlmul ..... 27, 33, 34, --387, 398, 399,  
 --403–405, 416, 420, --422, 424–427, 430  
 \DTLmutlibibs ..... 368–370  
 \DTLneg ..... 29  
 \dtlneg ..... 29  
 \DTLnegextent .....  
 ..... 375, --377, 378, 382–385, --390, 392  
 \DTLnewcurrencysymbol ..... 24  
 \DTLnewdb ..... 208, 217, --239, 322, 370  
 \DTLnewdbentry 208, --279, 280, 283, --290, 291  
 \DTLnewdbonloadtrue ..... 216  
 \DTLnewrow ..... 208, 279, --290  
 \dtlnoheaderfalse ..... 217

<code>\dtlnovalue</code> .....	131, 133, 134, --136, 138, 139, --144, 145, 147, 164, --166, 168, 171, --201, 202, 294, 303, --306	<code>\DTLsaveastrowcount</code> .....	155
<code>\DTLnumbernull</code> .....	135, 136	<code>\DTLsaverawdb</code> .....	235
<code>\DTLnumitemsinlist</code> .....	175, --178	<code>\DTLscp</code> .....	349, 363
<code>\DTLouterratio</code> .....	394, 397	<code>\DTLsdforall</code> .....	35
<code>\DTLpar</code> .....	252, 262, --265	<code>\DTLsetbarcolor</code> .....	374
<code>\DTLpcite</code> .....	338–340	<code>\dtlsetcharcode</code> .....	57
<code>\DTLperiodfalse</code> ...	324, 325, --330, 331, 336	<code>\dtlsetdefaultUTFviiicharcode</code> .....	57
<code>\DTLperiodtrue</code> .....	330	<code>\dtlsetdefaultUTFviiilccharcode</code> ....	57
<code>\DTLpieatbegin tikz</code> .....	399	<code>\DTLsetdelimiter</code> .....	113
<code>\DTLpieatend tikz</code> .....	403	<code>\DTLsetheader</code> .....	209
<code>\DTLpiechart</code> .....	395, 396	<code>\dtlsetlccharcode</code> .....	64
<code>\DTLpieoutlinecolor</code> .....	399	<code>\DTLsetpiesegmentcolor</code> .....	396
<code>\DTLpieoutlinewidth</code> .....	399	<code>\DTLsetseparator</code> .....	110, 113
<code>\DTLpievariable</code> .....	394, --397, 398	<code>\dtlsetUTFviiicharcode</code> .....	57
<code>\DTLplot</code> .....	410	<code>\dtlsetUTFviiilccharcode</code> .....	64, --75
<code>\DTLplotatbegin tikz</code> .....	418	<code>\DTLshowlinesfalse</code> .....	409, --411
<code>\DTLplotatend tikz</code> .....	427	<code>\DTLshowlinestrue</code> .....	411
<code>\dtlplotohandlermark</code> .....	418, --427	<code>\DTLshowmarkersfalse</code> .....	411
<code>\DTLplotheight</code> .....	411, 416	<code>\DTLshowmarkerstrue</code> .....	409, --411
<code>\DTLplotlinecolors</code> .....	410, --415, 423	<code>\DTLsicomp</code> .....	349, 363
<code>\DTLplotlines</code> .....	411, 414, --423	<code>\dtlsort</code> .....	196, 197, 246
<code>\DTLplotmarkcolors</code> .....	410, --414, 423	<code>\dtlsplitrow</code> .....	141, 142, --166, 168
<code>\DTLplotmarks</code> .....	411, 414, --423	<code>\DTLsplitstring</code> .....	43, 44, --68, 69
<code>\DTLplotwidth</code> .....	411, 415	<code>\DTLsqrt</code> .....	29, 191
<code>\DTLradius</code> .....	394, 397, --399	<code>\DTLstartangle</code> .....	396, 398
<code>\dtlrealalign</code> .....	173	<code>\DTLstartpt</code> .....	381, 382, --388, 389
<code>\dtlrealformat</code> .....	176, 180	<code>\DTLstartsentencefalse</code> ...	324, 325, --331
<code>\dtlrecombine</code> .....		<code>\DTLstartsentencespace</code> 332–340, --349–362	
.....	294, 297, --303, 304, 306, --308, 309	<code>\DTLstartsentencetrue</code> .....	331
<code>\DTLremoveentryfromrow</code> .....	165	<code>\DTLstoreinitials</code> .....	335, --366
<code>\DTLreplaceentryforrow</code> .....	169	<code>\dtlstringalign</code> .....	173
<code>\dtlreplaceentryincurrentrow</code> .....		<code>\dtlstringformat</code> .....	176, 180
.....	143, --146, 297, 303, --306–308	<code>\DTLstringnull</code> .....	134–136
<code>\dtlroot</code> .....	29, 34	<code>\DTLstringtype</code> .....	205
<code>\DTLrotateinnerfalse</code> .....	393	<code>\DTLsub</code> .....	26, 189, 190
<code>\DTLrotateinnertrue</code> .....	393	<code>\dtlsub</code> .....	26, 33, 34, --175, 178, 378, --385, 387, 399, 400, --403, 415–417, --419–422, 428–430
<code>\DTLrotateouterfalse</code> .....	393	<code>\DTLsubstitute</code> .....	24
<code>\DTLrotateoutertrue</code> .....	393	<code>\DTLsubstituteall</code> .....	
<code>\DTLround</code> .....	35	.....	37, 38, --53, 74, 76, --112, 224
<code>\dtlround</code> .....	35, 378, --383, 385, 391, --398, 417, 419, --421, 424	<code>\DTLtcs</code> .....	349, 363
<code>\DTLrowcount</code> .....	197, 308	<code>\DTLthisval</code> .....	185–194
<code>DTLrowi (counter)</code> .....	328	<code>\DTLthisX</code> .....	195
<code>DTLrowii (counter)</code> .....	328	<code>\DTLthisY</code> .....	195
<code>DTLrowiii (counter)</code> .....	328	<code>\DTLticklabeloffset</code> 383, --391, 419, 421, 422	
<code>\dtlrownum</code> .....	138– 141, 164, --166, 167, 199, 200, --242, 243	<code>\DTLticklength</code> ...	382, 383, --391, 419, 421
		<code>\DTLtocs</code> .....	349, 363
		<code>\DTLtods</code> .....	349, 363

<code>\DTLtog</code>	349, 363	<code>\editorname</code>	333
<code>\DTLtoms</code>	349, 363	<code>\editorsname</code>	334
<code>\DTLtoois</code>	349, 363	<code>\edtlgetrowforvalue</code>	139, 325
<code>\DTLtoplas</code>	349, 363	<code>\egroup</code>	211, 214, 235, 245, 246, 252, 253, 257, 258, 262, 264–266, 268–270, 272, 278, 279, 290, 300, 301, 307, 308, 317, 403, 427
<code>\DTLtrunc</code>	36	<code>\else</code>	4–8, 10–13, 15, 17, 18, 20–23, 37–42, 45–51, 54, 55, 57, 63–66, 70, 71, 74–82, 84, 86–89, 95, 97, 98, 100, 101, 107, 108, 111, 118, 122, 127, 131, 133–136, 139, 145, 146, 149, 151, 153–159, 161–171, 173, 176, 178, 179, 181–184, 187–190, 195, 199, 200, 203–205, 216–219, 236, 240, 242, 243, 248, 250, 251, 255, 256, 260–262, 266, 270, 274, 294, 296, 304, 306, 315, 316, 329–343, 351, 353, 354, 357, 365–367, 369, 371, 374, 375, 377–392, 395, 396, 398, 400, 401, 404, 415–425, 430, 431, 435–437, 440–448
<code>\dtltrunc</code>	36	<code>\em</code>	337, 338, 340, 350, 352, 357, 359, 360
<code>\DTLtwoand</code>	332, 333	<code>\emph</code>	239, 289, 362
<code>\dtltype</code>	170, 171, 176, 180	<code>\empty</code>	216
<code>\DTLunsettype</code>	205	<code>\encodingdefault</code>	288
<code>\dtlupdateentryincurrentrow</code>	294	<code>\end</code>	5, 6, 40–42, 152, 176, 180, 248–250, 255–257, 259–262, 264, 266, 292, 315, 324, 344, 348, 363, 370, 380, 384, 388, 392, 403, 422, 425–427
<code>\DTLvarianceforall</code>	34	<code>\end@dtl@doifinlist</code>	6
<code>\DTLvarianceforcolumn</code>	191	<code>\end@dtl@getfirst</code>	53, 56, 65, 82, 83
<code>\DTLverticalbarsfalse</code>	372	<code>\end@dtl@getfirst@UTFviii</code>	4, 55, 56, 75
<code>\DTLverticalbarstrue</code>	371	<code>\endcsname</code>	5, 15, 37, 98, 99, 112, 114–119, 121, 122, 124, 126, 127, 129–131, 137–139, 141, 146–153, 155, 157–167, 169, 170, 175, 178, 182–184, 200, 210–213, 215, 219–221, 224, 236, 283, 288, 289, 299, 300, 307, 319, 324, 325, 328, 329, 341–344, 363–365, 367–370, 373, 374, 379, 380, 387, 395, 396, 398, 399, 403–405, 433–437, 440–448
<code>\dtlwordindexcompare</code>	246	<code>\endfirsthead</code>	179
<code>\DTLxaxisfalse</code>	411	<code>\endfoot</code>	178
<code>\DTLXAxisStyle</code>	418	<code>\endgroup</code>	6–8, 110, 111, 216, 222, 223, 365
<code>\DTLxaxistrue</code>	408, 411, 413, 414	<code>\endhead</code>	179, 180
<code>\DTLxminorticsfalse</code>	412	<code>\endinput</code>	209, 212
<code>\DTLxticsfalse</code>	411, 412	<code>\endlastfoot</code>	178
<code>\DTLxticsinfalse</code>	412, 413		
<code>\DTLxticsintrue</code>	409, 412, 413		
<code>\DTLxticstrue</code>	411–414		
<code>\DTLyaxisfalse</code>	411, 412		
<code>\DTLYAxisStyle</code>	418		
<code>\DTLyaxistrue</code>	408, 411, 413, 414		
<code>\DTLxminorticsfalse</code>	412		
<code>\DTLyticsfalse</code>	411, 412		
<code>\DTLyticsinfalse</code>	412, 413		
<code>\DTLyticsintrue</code>	409, 412, 413		
<code>\DTLyticstrue</code>	411–414		
<b>E</b>			
<code>\eappto</code>	197, 242, 243, 271, 298		
<code>\edef</code>	5, 8–13, 15–24, 33, 34, 37–45, 51, 54, 55, 65–67, 70, 72–76, 82, 83, 86, 87, 89, 108, 109, 111, 112, 122, 124, 126–130, 134, 137–139, 141–150, 152, 153, 155, 158, 159, 162, 164, 166–168, 170, 175, 178, 181–184, 187–190, 195, 197–200, 203, 205, 211, 213, 215, 218–221, 241–244, 258, 278, 291, 293, 294, 296, 297, 300, 301, 303–305, 307, 308, 314–316, 318, 319, 322, 325–327, 341–343, 364, 365, 368–370, 378–383, 385–391, 399–405, 415, 423–425, 428–436, 441–447		
<code>\editionname</code>	346, 349		



<code>\endlinechar</code> .....	216, 223	374, 375, --377-392, 395, 396, --399,
<code>\enspace</code> .....	228	400, 402, 403, --405, 411-413, --415-
<code>\ensuremath</code> .....	289	425, 427, --430, 431, 435-438, --440-448
<code>\epsilon</code> .....	286	<code>\field</code> .....
<code>\equal</code> .....	50, 196, --291, 440, 441	<code>\fill</code> .....
<code>\eta</code> .....	286	380, 388, --399
<code>\etalname</code> .....	332, 333, 336	<code>\FirstId</code> .....
etoolbox's package .....	292	<code>\forcsvlist</code> .....
<code>\euro</code> .....	24	271
<code>\expandafter</code> .....	4, 6, --9-	fp package .....
13, 15, 17-20, --22-25, 30, 32-34, --37-		2, 16, --25, 100, 113
45, 47, 48, 51, --53, 55-57, 64, 65, --68-		<code>\FPabs</code> .....
70, 73-75, --82-84, 86, 87, 89, --98, 99,		104
108, 109, --112-118, 121, 122, --124,		<code>\FPadd</code> .....
126, 127, --129, 130, 133, --137-139,		103
142-153, --155-170, 175, 176, --178-		<code>\FPclip</code> .....
185, 187, 189, --191, 193, 195, --197-		103
202, 206, 207, --209-213, 215, 216,		<code>\FPdiv</code> .....
--218-221, 223, 224, --236, 242, 243,		103
--270-272, 278, 283, --287-289, 299,		<code>\FPifeq</code> .....
300, --305-307, 319, --329, 330, 332-		100
344, --351, 353, 354, 357, --363-365,		<code>\FPifgt</code> .....
368-370, --373, 374, 377-391, --395,		101
396, 398, 399, --403-405, 415, --418,		<code>\FPiflt</code> .....
419, 423-425, --429-435, 437, --442-448		101
<code>\expandonce</code> .....	8, 54, 55,	<code>\FPmax</code> .....
--65-67, 70, 72-76, --82-85, 133, 142,		104
--279, 280, 283, --290, 291, 306, 316, --318		<code>\FPmessagesfalse</code> .....
		100
		<code>\FPmessagestrue</code> .....
		100
		<code>\FPmin</code> .....
		103
		<code>\FPmul</code> .....
		103
		<code>\FPneg</code> .....
		104
		<code>\FProot</code> .....
		103
		<code>\FPround</code> .....
		103
		<code>\FPsub</code> .....
		103
		<code>\FPtrunc</code> .....
		103
		<b>G</b>
		<code>\G@refundefinedtrue</code> .....
		369
		<code>\Gamma</code> .....
		287
		<code>\gamma</code> .....
		286
		<code>\gappto</code> .....
		283, 299, 300
		<code>\gdef</code> .. 98, 110, 111, --149-151, 157, --161,
		162, 175, 177, --211, 213, 216, --222,
		223, 234, 283, --317, 318, 364, 433, --435
		<code>\global</code> .....
		5, 11, --13,
		15, 25-36, --98, 99, 116, 117, --119,
		127, 134, 135, --138, 149-151, --156-
		163, 166, 169, --171, 176, 180, --182,
		184, 195, 196, --200, 210-213, 216,
		--223, 234, 290, --292, 294, 300, --319,
		325, 327, 328, --330, 365, 366, --434, 435
		glossaries package .....
		10, --226
		<code>\glsadd</code> .....
		246, 289, --300
		<code>\Glsdispenry</code> .....
		312
		<code>\glsdispenry</code> .....
		311
		<code>\glsreset</code> .....
		298
		<code>\glsunset</code> .....
		298
		<b>H</b>
		<code>\hangindent</code> .....
		246, 257, --263, 264, 266



<code>\hbox</code> .....	369	<code>\ifdim</code> .....	251, 254, 256,
<code>\hfil</code> .....	173		258–260, 262, 264, 265, 326, 365,
<code>\hfill</code> .....	229		379, 380, 386, 388, 399, 417, 418, 430
<code>\hspace</code> .....	253, 270	<code>\ifdtlautokeys</code> .....	218
<code>\hyperlink</code> .....	247	<code>\ifDTLbarxaxis</code> .....	382, 390
hyperref package .....	155, 156, 160, 227, 328	<code>\ifDTLbaryaxis</code> .....	382, 390
<code>\hypertarget</code> .....	246, 300, 308	<code>\ifDTLbarytics</code> .....	378, 385
<b>I</b>			
<code>\IeC</code> .....	288	<code>\ifDTLbox</code> .....	418, 420–422
<code>\if</code> .....	18	<code>\ifDTLcolorbarchart</code> .....	374
<code>\if@datagidx@warn</code> .....	234	<code>\ifDTLcolorpiechart</code> .....	396
<code>\if@datagidxsymbolleft</code> .....		<code>\ifDTLgrid</code> .....	418
	248, 250, 254, 255, 260, 261	<code>\ifDTLlistskipempty</code> .....	7, 8, 15
<code>\if@dtl@condition</code> 39, 41, 77–79, 81, 82,		<code>\ifDTLmidsentence</code> .....	
86, 87, 89–96, 218, 219, 221, 340–344			336–340, 351, 353, 354, 357
<code>\if@dtl@insertdone</code> .....	10–13, 199, 200	<code>\ifDTLnewdbonload</code> .....	217
<code>\if@dtl@numgrpsep</code> .....	45, 48	<code>\ifdtlnoheader</code> .....	217, 219
<code>\if@dtl@sequential</code> .....	274	<code>\ifDTLperiod</code> .....	331
<code>\if@endfor</code> .....	7–9, 243, 329, 436, 437	<code>\ifDTLrotateinner</code> .....	400
<code>\if@filesw</code> .....	322, 345, 368–370	<code>\ifDTLrotateouter</code> .....	400
<code>\if@tempswa</code> .....	266	<code>\ifDTLshowlines</code> .....	423
<code>\if@twocolumn</code> .....	315	<code>\ifDTLshowmarkers</code> .....	423
<code>\ifallfemale</code> .....	446, 448	<code>\ifDTLstartsentence</code> .....	331
<code>\ifallmale</code> .....	446, 448	<code>\ifdtlverbose</code> .....	2, 3, 100, 205, 206
<code>\ifbool</code> .....	4, 55, 56	<code>\ifDTLverticalbars</code> .....	378–383, 385–391
<code>\ifboolexpr</code> .....	57–63	<code>\ifDTLxaxis</code> .....	418
<code>\ifcase</code> .....	50, 70, 100, 126,	<code>\ifDTLxminortics</code> .....	416, 418, 420
173, 176, 180, 227–229, 231, 237,		<code>\ifDTLxtics</code> .....	416, 419
277, 314, 344, 345, 375, 411–413, 425		<code>\ifDTLxticsin</code> .....	419, 420
<code>\ifcat</code> .....	38, 57, 63	<code>\ifDTLyaxis</code> .....	418
<code>\ifcsdef</code> .....		<code>\ifDTLyminortics</code> .....	417, 419, 422
	235, 250, 271, 292, 295, 301, 318, 319	<code>\ifDTLytics</code> .....	417, 421
<code>\ifcsemtyp</code> .....	292	<code>\ifDTLyticsin</code> .....	421, 422
<code>\ifcsundef</code> .....	302, 305, 307	<code>\ifentryused</code> .....	312, 320
<code>\ifdatagidxbalance</code> .....	316	<code>\ifeof</code> .....	217–219, 221
<code>\ifdatagidxshowgroups</code> .	252, 262, 265, 268	<code>\iffemalelabel</code> .....	433
<code>\ifdef</code> 2, 14, 214, 234, 246, 247, 267, 287, 300		<code>\IfFileExists</code> .....	214, 217, 278
<code>\ifdefempty</code> .....		<code>\ifFPmessages</code> .....	100
... 3, 4, 7–9, 11–13, 15–17, 20, 24–		<code>\ifmale</code> .....	448
30, 32–36, 38, 39, 43–47, 53, 54, 56,		<code>\ifmalelabel</code> .....	433
64, 66–69, 72, 73, 82, 83, 126, 136,		<code>\ifnum</code> .....	4, 5, 7, 10, 12, 17, 21–
192–194, 197, 198, 203, 206, 207,			23, 41, 42, 45–51, 53, 54, 64–66, 70,
218, 220, 223, 231–233, 240–243,			71, 73, 75, 77–80, 84–89, 97, 98, 107,
252, 257, 263, 265, 266, 268, 270–			108, 118, 122, 126, 127, 135, 151,
272, 275, 279, 291, 297, 298, 306, 314			153, 155–157, 161, 164, 165, 167,
<code>\ifdefequal</code> .....	28, 134,		169–171, 173, 181, 183, 187–190,
252, 257, 263, 265, 269, 272–274, 319			197, 199, 203, 205, 217, 236, 242,
			269, 296, 298, 309, 316, 317, 332,
			333, 336, 341–343, 365, 366, 374,
			375, 395, 396, 399, 404, 424, 440–448



<code>\mbox</code>	266	<code>\newterm@plural</code>	288, 290, 291
<code>\meta</code>	306	<code>\newterm@see</code>	289, 291
morewrites package	212	<code>\newterm@seealso</code>	289, 291
<code>\mu</code>	286	<code>\newterm@short</code>	288, 290, 291
<code>\multiply</code>	18, 21, 51, 203, 205, 253, 258, 270	<code>\newterm@shortplural</code>	281, 288, 291
<b>N</b>			
<code>\Name</code>	245, 251–254, 257–259, 263–267, 269, 282	<code>\newterm@sort</code>	288, 290
<code>\NeedsTeXFormat</code>	2, 100, 105, 110, 226, 322, 371, 393, 406, 432	<code>\newterm@styles</code>	314–316
<code>\newcommand</code>	2–6, 8–20, 22–39, 41, 43–47, 49–51, 53, 56, 57, 61, 63, 64, 67, 71–83, 85–97, 99–126, 128–130, 132, 133, 135–148, 150, 152, 153, 155, 156, 160, 163–165, 167, 169–175, 177, 181–198, 201, 204, 206, 208, 209, 212, 214–217, 222–229, 231, 233–236, 239–241, 243–251, 254, 259, 264, 267, 268, 270–273, 275–288, 290, 292–308, 311, 312, 314, 315, 318, 320, 322–331, 333–348, 362–374, 377, 384, 394–396, 398, 403, 404, 406–410, 414, 428–436, 438–448	<code>\newterm@symbol</code>	288, 290
<code>\newcount</code>	3, 13, 16, 45, 56, 98, 115, 116, 119, 154, 155, 186, 211, 213, 215, 298, 308, 321, 331, 373, 404, 409	<code>\newterm@text</code>	288, 290, 291
<code>\newcounter</code>	154, 155, 227, 328, 331, 332, 365, 372, 394, 408, 432	<code>\newterm@labelhook</code>	290
<code>\newenvironment</code>	99, 155, 156, 344	<code>\newtoks</code>	3, 114–116, 125, 138, 155, 196, 198, 204, 210–213
<code>\newgidx</code>	235	<code>\newwrite</code>	206, 368
<code>\newif</code>	6, 13, 44, 47, 216, 231, 234, 271, 277, 329, 330, 371, 373, 393, 408, 409	<code>\nobreak</code>	252, 262, 265
<code>\newlength</code>	3, 231, 259, 325, 372, 374, 394, 396, 407–409	<code>\NoCaseChange</code>	307
<code>\newread</code>	214	<code>\noexpand</code>	8, 16, 17, 19, 20, 24, 37, 38, 40, 42, 47, 54, 55, 57, 63, 65–67, 70, 72–86, 88, 90–96, 105–107, 111, 112, 119, 122, 124, 126–131, 134, 137–148, 152, 153, 158–160, 164–168, 170, 175, 178, 181–184, 195, 199, 200, 203, 205, 221, 223, 241, 244, 258, 268, 283, 286, 289, 293, 294, 296, 297, 299–301, 303–305, 307, 314–316, 318, 319, 340–344, 380–383, 388–391, 402, 403, 423–425, 431
<code>\newrobustcmd</code>	7, 8, 14, 340	<code>\not</code>	404, 405
<code>\newterm</code>	235, 288, 295	<code>\nr</code>	2, 100, 113, 237–239, 277, 312–314, 375, 411–414
<code>\newterm@database</code>	283, 288, 290–294, 296, 297, 301–307, 312, 315–317	<code>\nu</code>	286
<code>\newterm@defaultshook</code>	283, 289	<code>\null</code>	173
<code>\newterm@description</code>	288, 290	<code>\number</code>	8, 23, 41, 42, 51, 75, 76, 105–109, 117–119, 122, 126–131, 138–148, 153, 155, 158–160, 164–168, 175, 178, 181–184, 187–190, 199, 200, 206, 211, 213, 218, 220–222, 242, 243, 299, 308, 344, 348, 378, 379, 382, 385, 387, 415–417, 419–422
<code>\newterm@extrafields</code>	283, 291	<code>\numbername</code>	337
<code>\newterm@label</code>	288, 290–294	<code>\numexpr</code>	108, 109
<code>\newterm@long</code>	289–291	<b>O</b>	
<code>\newterm@longplural</code>	281, 289, 291	<code>\O</code>	287
<code>\newterm@name</code>	288	<code>\o</code>	287
<code>\newterm@parent</code>	289, 291, 292	<code>\OE</code>	287
<code>\newterm@parentdatabase</code>	291, 292	<code>\oe</code>	287
		<code>\ofname</code>	337, 338
		<code>\Omega</code>	287
		<code>\omega</code>	287

<code>\onecolumn</code>	315	<code>\Personpronoun</code>	442
<code>\openin</code>	217	<code>\personpronoun</code>	442
<code>\openout</code>	206, 208, 209, 212, 368	<code>\personsep</code>	440, 441
<code>\or</code>	50, 70, 100, 126, 127, 173, 176, 180, 227–232, 237, 277, 314, 344, 345, 375, 411–413, 425–427	<code>\personsibling</code>	448
<b>P</b>			
<code>\p@</code>	246, 259	<code>pgfmath package</code>	2, 25, 105, 113
package options:		<code>\pgfmathabs</code>	109
style		<code>\pgfmathadd</code>	107
databib	322	<code>\pgfmathdivide</code>	107
verbose	2, 100	<code>\pgfmathifthenelse</code>	105–107
<code>\PackageError</code>	97, 114– 122, 124, 125, 128, 130–134, 137, 139, 145, 147, 152, 153, 156, 160, 161, 163–173, 183, 184, 186–190, 192–194, 197, 198, 204, 208, 209, 212, 214, 222, 226, 250, 291–294, 302, 307, 309, 317, 324, 325, 367– 370, 374, 375, 377, 384, 395, 396, 398, 404, 415, 427, 433–437, 440–448	<code>\pgfmathmax</code>	109
<code>\PackageWarning</code>	8, 198, 217, 219, 271, 273, 305, 410	<code>\pgfmathmin</code>	109
<code>\PackageWarningNoLine</code>	234, 235	<code>\pgfmathmul</code>	109
<code>\pagename</code>	336, 337	<code>\pgfmathmultiply</code>	107
<code>\pagesname</code>	336, 337	<code>\pgfmathparse</code>	107, 108, 410
<code>\par</code>	113, 246, 257, 259, 263, 264, 266, 268, 314	<code>\pgfmathresult</code>	105–109, 410
<code>\Parent</code>	244, 254, 258, 259, 263, 265, 282, 318	<code>\pgfmathsqrt</code>	107
<code>\parindent</code>	246, 251, 253, 254, 257–259, 263–266, 268, 270	<code>\pgfmathsubtract</code>	107
<code>\parse@wordsnext</code>	76, 77	<code>\pgfpathlineto</code>	382, 383, 391, 431
<code>\parshape</code>	258, 268	<code>\pgfpathmoveto</code>	382, 391, 431
<code>\parskip</code>	246, 251, 253–256, 258–266, 268, 270	<code>\pgfplothandlerlineto</code>	425
<code>\penalty</code>	368	<code>\pgfplothandlermark</code>	410, 425
<code>\Personchild</code>	446	<code>\pgfplotstreamend</code>	425
<code>\personchild</code>	446	<code>\pgfplotstreampoint</code>	406, 424
<code>\personfullname</code>	440	<code>\pgfplotstreamstart</code>	424
<code>\personlastsep</code>	440, 441	<code>\pgfpoint</code>	379–383, 387–392, 418, 427, 431
<code>\personname</code>	441	<code>\pgfpointadd</code>	380–383, 388–392
<code>\Personobjpronoun</code>	443	<code>\pgfpointlineattime</code>	382, 389
<code>\personobjpronoun</code>	443	<code>\pgfpointxy</code>	380–383, 388–392, 406, 424
<code>\Personparent</code>	447	<code>\pgfsetdash</code>	407
<code>\personparent</code>	447	<code>\pgfsetxvec</code>	379, 387, 418
<code>\Personpossadj</code>	444	<code>\pgfsetyvec</code>	379, 387, 418
<code>\personpossadj</code>	443, 444	<code>\pgftext</code>	381–383, 386, 389–392
<code>\Personposspronoun</code>	445	<code>\pgftransformcm</code>	418, 427
<code>\personposspronoun</code>	445	<code>\pgftransformxscale</code>	410
		<code>\pgftransformyscale</code>	410
		<code>\pgfusepath</code>	383, 391, 425, 431
		<code>\pgfuseplotmark</code>	406, 407
		<code>\Phi</code>	287
		<code>\phi</code>	286
		<code>\Pi</code>	287
		<code>\pi</code>	286
		<code>\Plural</code>	245, 282
		<code>\pluralchild</code>	446
		<code>\pluralobjpronoun</code>	443
		<code>\pluralparent</code>	447
		<code>\pluralpossadj</code>	444
		<code>\pluralposspronoun</code>	445
		<code>\pluralpronoun</code>	442
		<code>\pluralsibling</code>	448

<code>\postnewtermhook</code> .....	292	253, 254, --256-260, 262-266, --268-
<code>\pounds</code> .....	23	270, 272, 277, --296, 300, 303, --308,
<code>\printterms@condition</code> .....	318	314, 316-319, --326-333, 335, 336,
<code>\printterms@setupmulticol</code> .....	316	--341-344, 348, --364-367, 374-378,
<code>\printterms@setuptwocol</code> .....	316	--382-387, 390, 391, --395-399, 404,
<code>\printtermsrestoreonecolumn</code> .....	315	405, --411-417, 419-425, --431, 440-448
<code>\printtermsstartpar</code> .....	317	<code>\removeperson</code> .....
<code>\process@envbody</code> .....	5, 6	435
<code>\ProcessOptions</code> .....	372, 393	<code>\renewcommand</code> ... 2, 14, --16, 25, 110, 111,
<code>\ProcessOptionsX</code> 3, 100, --105, 113, 239, --322		--113, 227-233, 235, --237, 238, 251-
<code>\protect</code> .....	18, 37, --39, 41, 46, --236	254, --257-259, 262-266, --268-270,
<code>\protected@edef</code> .....		277, --280, 281, 288, 289, --312-314,
..... 6, 13, --39, 41, 43, --54, 77-82,		348-350, --352, 354-356, --358-363, 397
84-86, --88, 130, 133, --139, 144, 145,		<code>\renewenvironment</code> .....
148, --164, 168, 173, --206, 207, 218,		348, --363
224, --283, 300, 305, --319, 326, 330,		<code>\repeat</code> .....
--336, 337, 339, 340, --351, 353, 354, 357		217-219, 221, --309
<code>\protected@write</code> .. 207-214, --234, 304, 319		<code>\RequirePackage</code> ... 2, 3, 100, --105, 110,
<code>\protected@xdef</code> .....		113, --226, 322, 371, 372, --393, 406, 432
..... 210, 211, --223, 290, 365, --434		<code>\reset@font</code> .....
<code>\providecommand</code> .....	3, 100,	369
--105, 113, 239, --246, 288, 323, 324, --439		<code>\restB</code> .....
<code>\ProvidesPackage</code> .....	2, 100,	54, 66
--105, 110, 226, --322, 371, 393, --406, 432		<code>\rho</code> .....
<code>\Psi</code> .....	287	286
<code>\psi</code> .....	287	<code>\romannumeral</code> .....
		. 155, --157-170, 215, --218-221, 373,
		374, --380, 395, 396, --398, 399, 403-405
		<b>S</b>
		<code>\s@DTLaddcolumn</code> .....
		125
		<code>\s@dtlenvforeach@args</code> .....
		156
		<code>\s@dtlformatlist</code> .....
		14, 15
		<code>\section</code> .....
		246, 267
		<code>\See</code> .....
		229, 230, 241,
		--244, 254, 258, 259, --263, 265, 282, --320
		<code>\SeeAlso</code> .....
		229,
		244, --254, 258, 259, 263, --265, 282, 320
		<code>\seealsoname</code> .....
		229
		<code>\seename</code> .....
		229, 230
		<code>\setbool</code> .....
		113, 237
		<code>\setcounter</code> .... 266, 270, --326, 327, 331,
		332, --365, 372, 394, --408, 435, 440, 441
		<code>\setkeys</code> .....
		177, 217, --278,
		279, 289, --315, 316, 377, 384, --398, 414
		<code>\setlength</code> .... 246, 248, 249, --251, 253-
		256, --258-266, 268, 270, --314, 372,
		376, --378, 379, 383, --385, 386, 390,
		391, --407-409, 411, --416-418, 422, 430
		<code>\settodepth</code> .....
		379, 386
		<code>\settoheight</code> .....
		246, 300, --379, 386, 416
		<code>\settowidth</code> .....
		... 248-250, 254, --258-260, 263-265,
		--326, 365, 378, 379, --385, 386, 417, 418
		<code>\sfcode</code> .....
		331
		<code>\Short</code> .....
		245, 282

## Q

<code>\q@nil</code> .....	122-
125, 140, 141, --144, 146-151, 154, --200	

## R

<code>\raggedleft</code> .....	250
<code>\raggedright</code> .....	251, 268
<code>\raisebox</code> .....	246, 301
<code>\read</code> .....	216, 217, 223
<code>\refstepcounter</code> .....	156, 158, --160,
162, 253, --258, 264, 267, --270, 326-328	
<code>\relax</code> .....	4,
5, 7, 8, --10, 12, 16-23, --37-42, 44-51,	
--53-67, 70-73, --75-80, 84-89, --97-	
102, 107-111, --115, 117-119, 122,	
--126, 127, 129, 130, --134, 135, 138,	
139, --144, 145, 149-151, --153, 155-	
167, --169-171, 173, 176, --180, 181,	
183, 184, --186-190, 195, 197, --199-	
201, 203, --205, 206, 208, 209, --211-	
213, 215, --217, 218, 220, --222, 223,	
227-229, --231, 237, 242, --244, 251,	

<code>\ShortPlural</code>	282	<code>\TH</code>	287
<code>\show</code>	225	<code>\th</code>	287
<code>\showthe</code>	224	<code>\the</code>	5, 9–13, 15, 17, 20, 23, 24, 33, 34, 37, 38, 40, 42–45, 74, 75, 98, 99, 122, 124, 126–129, 131, 137–144, 146–153, 157, 159–163, 165, 166, 168, 181–184, 196, 199, 200, 205, 207, 210, 211, 213, 215, 219–222, 224, 258, 268, 341–343, 364, 365, 379, 386, 402–405, 423–425, 429–433
<code>\Sigma</code>	287	<code>\theDTLgidxChildCount</code>	227
<code>\sigma</code>	286	<code>\theHDTLrow</code>	155, 328
<code>\Sort</code>	282, 319	<code>\theHDTLrowi</code>	155
<code>\space</code>	14, 37, 38, 53, 71, 72, 74–76, 122, 131, 134, 141–143, 145–147, 153, 156, 161, 164–172, 184, 210– 214, 230, 231, 235, 236, 267, 268, 284, 286, 287, 331, 368, 369, 374, 377, 384, 395, 396, 398, 410, 433, 440	<code>\theHDTLrowii</code>	155
<code>\spacefactor</code>	331	<code>\theHDTLrowiii</code>	155
<code>\SS</code>	287	<code>\thepage</code>	369
<code>\ss</code>	287	<code>\Theta</code>	287
<code>\step</code>	97, 98, 158, 221	<code>\theta</code>	286
<code>\stepcounter</code>	365, 434, 440, 441	<code>\thiscol</code>	166, 167
<code>\string</code>	40–42, 133, 134, 156, 161, 164, 165, 167, 169–172, 208–214, 234–236, 283, 287, 288, 299, 304, 319, 322, 345, 368–370, 374, 377, 384, 395, 396, 398, 410, 415	<code>\tikz</code>	386, 431
substr package	2	<code>\to</code>	97, 98, 111, 112, 158, 218, 220, 221
<code>\Symbol</code>	231–233, 245, 266, 282	<code>\toks@</code>	5, 9–13, 17, 20, 24, 33, 34, 37, 38, 40, 42–45, 74, 75, 138, 139, 142, 146–148, 152, 153, 166, 181–183, 199, 200, 206, 207, 215, 341–343, 364, 365, 423–425, 429–431
<b>T</b>			
<code>\tabularnewline</code>	174	<code>\two@digits</code>	284
<code>\tau</code>	286	<code>\twocolumn</code>	315
<code>\TE@or</code>	97, 98	<code>\twopeoplesep</code>	440, 441
<code>\TE@throw</code>	90–96, 340–344	<code>\typeout</code>	3, 197
<code>\Text</code>	245, 282	<b>U</b>	
<code>\textasciicircum</code>	223	<code>\uccode</code>	40
<code>\textasciitilde</code>	223	<code>\undef</code>	233, 288, 289, 308, 377
<code>\textbf</code>	173, 252, 262, 265, 289	<code>\undefined</code>	115–117, 434, 435
<code>\textcurrency</code>	24	<code>\uppercase</code>	40
<code>\textdollar</code>	24	<code>\Upsilon</code>	287
<code>\texteuro</code>	24	<code>\upsilon</code>	286
<code>\textit</code>	289	<code>\Used</code>	282
<code>\textmd</code>	289	<code>\Useentry</code>	311, 312
<code>\textnormal</code>	228	<code>\useentry</code>	311, 312
<code>\textrm</code>	289	<code>\Useentrynl</code>	311
<code>\textsc</code>	289	<code>\useentrynl</code>	311
<code>\textsf</code>	289	<code>\usetikzlibrary</code>	406
<code>\textsl</code>	289	<code>\UTFviii@two@octets</code>	2, 55
<code>\textstirling</code>	24	<b>V</b>	
<code>\textsuperscript</code>	289	<code>\val</code>	2, 100, 113, 237–239, 277, 312–314, 411–414
<code>\texttt</code>	289	<code>\var</code>	375
<code>\textwon</code>	24		
<code>\textyen</code>	24		



# Change History

1.01 (2007 Aug 17)	
\@dtl@checknumericalloop: fixed bug caused by commands occurring within text being tested .....	47
\@dtl@ifDigitOrDecimalSep: new ...	47
\DTLaddall: removed extraneous space .	25
\DTLbarchart: uses \@sDTLforeach instead of \DTLforeach .....	377
\dtlcompare: replaces \compare (no longer using compare.tex) .....	53
\DTLforeach: added starred version ..	156
\DTLgetrowforkey: new .....	196
\DTLgetvalueforkey: new .....	195
\dtlicompare: new .....	64
\DTLifclosedbetween: added starred version .....	86
\DTLlifeq: added starred version .....	81
\DTLifgt: added starred version .....	79
\DTLiflastrow: fixed bug .....	172
\DTLiflt: added starred version .....	77
\DTLifopenbetween: added starred version .....	89
\DTLifStartsWith: new .....	82
\DTLifstringclosedbetween: added starred version .....	85
\DTLifstringeq: added starred version	80
\DTLifstringgt: added starred version	78
\DTLifstringlt: added starred version	77
\DTLifstringopenbetween: added starred version .....	87
\DTLifSubString: new .....	81
\DTLinitialhyphen: new .....	39
\DTLinitials: now uses \DTLinitialhyphen .....	37
now works with unbreakable space symbol .....	37
\DTLisiclosedbetween: new .....	93
\DTLisieq: new .....	91
\DTLisigt: new .....	91
\DTLisilt: new .....	90
\DTLisiopenbetween: new .....	93
\DTLisPrefix: new .....	91
\DTLisSubString: new .....	91
\DTLmaxall: removed extraneous space .	31
\DTLmeanforall: removed extraneous space .....	32
\DTLminall: removed extraneous space .	30
\DTLmultibarchart: uses \@sDTLforeach instead of \DTLforeach .....	384
\DTLpiechart: uses \@sDTLforeach instead of \DTLforeach .....	398
\DTLplot: uses \@sDTLforeach instead of \DTLforeach .....	424
\DTLplotstream: uses \@sDTLforeach instead of \DTLforeach .....	406
\DTLremovecurrentrow: fix bug caused by missing \fi and unrequired argument .....	169
\DTLsdforall: fixed bug .....	34
removed extraneous space .....	34
\DTLsort: added optional argument ..	196
added starred version .....	196
\DTLsplitstring: new .....	43
\DTLstoreinitials: now uses \DTLinitialhyphen .....	38
now works with unbreakable space symbol .....	38
\DTLsubstituteall: fixed bug caused when certain commands occur in the string .....	44
\DTLvarianceforall: fixed bug .....	33
removed extraneous space .....	33
1.01 (2007/08/22)	
\DTLmultibibs: new .....	368
1.03 (2009 January 27)	
\DTLnewbibitem: removed check if database exists .....	323
\DTLnewbibrow: removed check if database exists .....	322



\DTLplotlines: fixed error in solid line setting .....	407	\dtladdalign: new .....	173
2.0 (2009 February 27)		\DTLaddentryforrow: updated to use new database structure .....	169
\@DTLforeach: updated to use new database structure .....	156	\dtlaftercols: new .....	172
\@DTLifdbempty: new .....	118	\DTLappendtorow: updated to use new database structure .....	164
\@DTLremoveorow: new .....	184	\DTLbarchart: added \DTLeverybarhook .....	382
\@dtl@after: new .....	125	\dtlbeforecols: new .....	172
\@dtl@assign: updated to use new database structure .....	133	\dtlbetweencols: new .....	172
\@dtl@before: new .....	125	\DTLcolumncount: new .....	118
\@dtl@colhead: new .....	125	\dtlcolumnindex: new .....	121
\@dtl@decrementrows: new .....	182	\dtlcolumnnum: new .....	119
\@dtl@getcolumnindex: new ...	120, 121	\dtlcurrencyformat: new .....	174
\@dtl@getdatatype: new .....	124	\DTLcurrencytype: new .....	123
\@dtl@getprops: new .....	124	\dtldisplayafterhead: new .....	174
\@dtl@getsortdirection: modified to use \ifx instead of \ifthenelse ..	203	\DTLdisplaydb: new .....	175
\@dtl@list: new .....	196	\dtldisplayendtab: new .....	174
\@dtl@setnull: modified to use new database structure .....	135	\DTLdisplaylongdb: new .....	177
\@dtl@sortcriteria: updated to take account of new database structure ..	201	\dtldisplaystartrow: new .....	174
\@dtl@updatekeys: new .....	126	\dtldisplaystarttab: new .....	174
\@dtlgetdatatype: new .....	123	\DTLeverybarhook: new .....	374
\@dtlifreadonly: new .....	163	\DTLforeachkeyinrow: updated to use new database structure .....	170
\@dtlloaddb: changed \ifthenelse to \ifx to improve efficiency .....	~220	\DTLgetcolumnindex: new .....	120
changed \whiledo to \loop to improve efficiency .....	~218, 220	\DTLgetdatatype: new .....	123
\@sDTLforeach: updated to use new database structure .....	160	\dtlgetentryfromcurrentrow: new ..	143
\@sDTLnewrow: new .....	119	\DTLgetrowforkey: update to use new database structure .....	196
\@sdtlgetdatatype: new .....	124	\DTLgetvalueforkey: updated to use new database structure .....	195
General: added etex as a required package .....	110	\dtlheaderformat: new .....	173
removed \@dtl@getidtype .....	132	\DTLiffirstrow: modified to have different definition depending on location .....	171
removed \@dtl@ifrowcontains ...	132	\DTLifhaskey: new .....	119
removed \@dtl@setidtype .....	132	\DTLiflastrow: modified to have different definition depending on location .....	172
removed \@dtl@setkeys .....	132	\DTLifoddrrow: modified to have different definition depending on location .....	172
removed \dtl@getentryid .....	132	\dtlintformat: new .....	174
removed \dtl@getentryvalue ...	132	\DTLinttype: new .....	123
\dtl@compare: no longer used .....	204	\DTLloaddb: added optional argument removed checks to see if the database exists when adding to it .....	217
\dtl@compare@: updated to use new database structure .....	204	\DTLmaxforcolumn: new .....	194
\dtl@decrementrows: new .....	182		
\dtl@gathervalues: updated to use new database structure .....	137		
\dtl@sortdata: new .....	198		

\DTLmaxforkeys: added second optional argument .....	193	2.02 (2009 July 13)	\DTLsavedb: Fixed bug that didn't set the filename .....	206
\DTLmeanforcolumn: new .....	187	2.03 (2009 November 15)	\@dtl@assigncmd: modified to ignore spaces after commas .....	134
\DTLmeanforkeys: added second optional argument .....	186	\@sDTLnewdbentry: value can be expanded before adding to database	131	
\DTLminforcolumn: new .....	192	\DTLappendtorow: value expanded before storing .....	164	
\DTLminforkeys: added second optional argument .....	191	\DTLcleardb: new .....	115	
\DTLmultibarchart: added \DTLeverybarhook .....	389	\dtlcolumnindex: renamed \dtl@columnindex to \dtlcolumnindex .....	121	
\DTLnewdb: Changed way database is stored .....	114	\DTLdeletedb: new .....	115	
\dtlrealformat: new .....	174	\DTLreplaceentryforrow: expand replacement entry .....	168	
\DTLrealtype: new .....	123	\DTLsavedb: Moved outside loop .....	208	
\DTLremovecurrentrow: updated to use new database structure .....	169	2.10 (2012-07-18)	\@dtl@construct@qlopoff: Added code to replace escaped delimiters ..	112
\DTLremoveentryfromrow: updated to use new database structure .....	165	\@dtl@getkeyforcolumn: fixed bug ..	122	
\DTLremoverow: new .....	183	\@dtl@ifDigitOrDecimalSep: Rewritten .....	47	
\DTLreplaceentryforrow: updated to use new database structure .....	167	\@dtlloaddb: add generic header if missing .....	218	
\dtlrownum: new .....	119	added code to skip lines .....	217	
\DTLsavedb: updated to use new database structure .....	206	changed \ifx to \ifdefempty .....	220	
\DTLsavetexdb: updated to use new database structure .....	208	General: added omitlines key .....	215	
\DTLsdforcolumn: new .....	191	\dtl@domappings: replaced \DTLsubstitute with \DTLsubstituteall .....	224	
\DTLsdforkeys: added second optional argument .....	190	\dtlappendentrytocurrentrow: new	144	
\dtlshowdb: updated to use new database structure .....	224	\DTLassign: new .....	132	
\dtlshowdbkeys: updated to use new database structure .....	224	\DTLdisplaydb: added optional arg ...	175	
\dtlshowtype: updated to use new database structure .....	225	\DTLdisplaylongdb: added omit option .....	177	
\DTLsort: updated to use new data structure .....	196	\DTLifnumeq: changed \FPifeq to \dtlifnumeq .....	80	
\dtlstringformat: new .....	174	\DTLifnumgt: changed \FPifgt to \dtlifnumgt .....	78	
\DTLstringtype: new .....	123	\DTLifnumlt: changed \FPiflt to \dtlifnumlt .....	51	
\DTLsumcolumn: new .....	185	\dtlrecombineomitcurrent: new ...	141	
\DTLsumforkeys: added second optional argument .....	185	\dtlremoveentryincurrentrow: new	142	
\DTLunsettype: new .....	123	\dtlreplaceentryincurrentrow: new	141	
\DTLvarianceforcolumn: new .....	189	\DTLsettabseparator: changed tab character to ^^I .....	110	
\DTLvarianceforkeys: added second optional argument .....	188	\DTLsubstituteall: added \long .....	44	
2.01 (2009 March 27)				
\@dtl@sortcriteria: fixed sort direction .....	203			

<code>\dtlswapentriesincurrentrow</code> : new	143	fixed bug where characters without a lower case equivalent were all considered equal	^^64
<code>\long@addto@envbody</code> : new	5		
<code>\long@collect@body</code> : new	6		
<code>\long@push@begins</code> : new	6		
2.11 (2012-09-25)			
<code>\@dtl@updatekeys</code> : remove unwanted space	126	<code>\dtl@testifsubstring</code> : now using <code>\dtl@setwordbreaksnohyphens</code> to deal with spaces	^^81
<code>\@dtl@getrowindex</code> : new	148	<code>\dtl@teststartswith</code> : now using <code>\dtl@setwordbreaksnohyphens</code> to deal with spaces	^^83
<code>\DTLaddcolumn</code> : new	125	<code>\DTLaddentryforrow</code> : removed spurious space	169
<code>\dtldisplayvalign</code> : new	174	<code>\DTLdisplaydb</code> : removed spurious space	175
<code>\dtlgetrowforvalue</code> : new	139	<code>\DTLdisplaylongdb</code> : removed spurious space	177
<code>\DTLgetrowindex</code> : new	147	<code>\DTLforeachkeyinrow</code> : changed to use <code>\@dtlstringnull</code> and <code>\@dtlnumbernull</code>	^^171
<code>\dtlgetrowindex</code> : new	148	<code>\DTLgcleardb</code> : new	117
<code>\dtlupdateentryincurrentrow</code> : new	145	<code>\DTLgdeletedb</code> : new	116
2.12 (2012-11-30)		<code>\DTLgnewdb</code> : new	116
<code>\@DTLforeach</code> : fixed bug in <code>\DTLiflastrow</code>	157	<code>\dtlcompare</code> : now using <code>\dtl@setwordbreaksnohyphens</code> to deal with spaces	^^65
<code>\@dtl@construct@getintfrac</code> : switched to <code>\ifdefempty</code>	16	<code>\dtlparsewords</code> : new	76
<code>\@sDTLforeach</code> : fixed bug in <code>\DTLiflastrow</code>	161	<code>\DTLrawmap</code> : removed spurious space	224
<code>\dtlifnumclosedbetween</code> : fixed bug causing premature expansion	106	<code>\DTLsaverawdb</code> : new	209
<code>\dtlifnumeq</code> : fixed bug causing premature expansion	105	<code>\dtlsort</code> : new	197
<code>\dtlifnumgt</code> : fixed bug causing premature expansion	106	<code>\ifDTLnewdbonload</code> : new	216
<code>\dtlifnumlt</code> : fixed bug causing premature expansion	106	2.14 (2013-06-28)	
<code>\dtlifnumopenbetween</code> : fixed bug causing premature expansion	106	<code>\@dtl@updatekeys</code> : expand value before testing if it's empty	126
2.13 (2013-01-15)		General: added calc library requirement	406
<code>\@DTLnewrow</code> : fixed typo in <code>\PackageError</code>	118	<code>\datagidx@add@term</code> : added <code>\postnewtermhook</code>	292
<code>\@dtl@getsortdirection</code> : removed spurious space	204	<code>\datagidx@style@gloss</code> : removed spurious see also line	266
<code>\@dtl@setheaderforindex</code> : removed spurious space	129	<code>\datagidxdb</code> : new	295
<code>\@dtlnumbernull</code> : new	135	<code>\dtl@constructminorticklist</code> : replaced <code>\FPsub</code> with <code>\dtlsub</code> etc	430
<code>\@dtlstringnull</code> : new	135	<code>\dtl@constructticklist</code> : replaced <code>\FPsub</code> with <code>\dtlsub</code> etc	428
General: added <code>\datagidx</code> package	226	<code>\dtl@constructticklistwithgap</code> : replaced <code>\FPadd</code> with <code>\dtladd</code>	429
math: changed <code>\newcommand</code> to <code>\providecommand</code>	113	<code>\dtl@constructticklistwithgapex</code> : replaced <code>\FPadd</code> with <code>\dtladd</code> and changed third argument to minimum gap width (in data co-ordinates)	^^431
<code>\dtl@setcharcode</code> : change from check for space and tilde to check for <code>\@dtl@wordbreak</code>	^^57		
<code>\dtl@setlccharcode</code> : changed to test for <code>\@dtl@wordbreak</code> instead of space and tilde	^^63		

\dtl@constructticklistwithgapz: replaced \FPadd with \dtladd etc .	429	2.18 (2013-09-06)	\DTLpar: changed back to a robust command .....	113
\dtl@getbounds: changed \FPifgt to \dtlifnumgt .....	427		\dtl@sort: added check for existence of keys listed in sort criteria .....	197
\DTLgidxForeachEntry: Added optional argument when using \DTLforeach	318	2.19 (2014-01-17)	\@datagidx@use@entry: renamed \@datagidx@use@entry to \@datagidx@use@entry and removed redundant field argument	302
\DTLpar: changed to \let .....	113		\@dtl@resetdostartrow: switched to \dtl@displaycr .....	177
\DTLplot: replaced \FPround with \dtlround .....	417		\dtl@displaycr: new .....	174
replaced \FPsub etc with \dtlsub etc .....	415		\DTLdisplaydb: switched to \dtl@displaycr .....	176
\ifnewtermfield: new .....	292		\glsaddall: Fixed bug in database reference .....	308
\newtermfield: new .....	292		2.20 (2014-02-03)	
\printterms@condition: new .....	314		\@DTLforeach: change \gdef to \xdef	156
2.15 (2013-07-10)			\@dtl@assign: Added check for empty argument .....	133
\@dtlminforkeys: Replaced \ifstrempty with \ifdefempty ..	192		\@dtl@assigncmd: Stored db label in \@dtl@dbname .....	134
General: added afterpage as a required package .....	226		\@sDTLforeach: Added missing \@dtl@dbname assignment .....	161
\datagidx@target: fixed page breaking bug .....	300		\DTLassignfirstmatch: new .....	132
\datagidx@write@usedentry: Added check for page counter .....	305		\DTLifnulloreempty: new .....	136
\do@locrange: removed spurious space	276		\DTLloaddbtex: new .....	214
\DTLaddtoplotlegend: Used \xdef instead of \edef as may be scoped.	431		\xDTLassignfirstmatch: new .....	133
\DTLgidxForeachEntry: expanded and sanitize locations before comparing them .....	319	2.21 (2014-03-08)	\@gDTLforeachbibentry: new .....	327
\dtlplothandlermark: new .....	410		\@sgDTLforeachbibentry: new .....	328
\DTLprotectedsaverawdb: new .....	212		\datagidx@parse@location: replaced \ifstrequal with \ifdefequal ..	272
\DTLsaverawdb: added \dtl@lastloadeddb .....	211		\dtl@g@gathervalues: new .....	138
\DTLsavetexdb: added \dtl@lastloadeddb .....	209		\dtl@gathervalues: fixed bug that ignore row tok argument .....	138
\loadgidx: new .....	278		\DTLdisplaylongdb: added missing \dtl@displayafterhead .....	179
nowarn: new .....	237		fixed location of \dtl@displaystarttab .....	179
2.16 (2013-08-16)			moved misplaced \dtl@displayafterhead .....	180
\@dtl@checknumerical: Moved empty check .....	45		\DTLforeachbibentry: fixed bug in starred version .....	326
\@dtl@updatekeys: reverted to not expanding value (2.14 change causes an error with fragile commands). Fix now in \@dtl@checknumerical ..	126		\gDTLforeachbibentry: new .....	327
2.17 (2013-08-29)			\gDTLformatbibentry: new .....	325
\DTLfetch: new .....	139	2.22 (2014-06-10)	\@dtl@chopexcessfrac: new .....	22
\edtlgetrowforvalue: new .....	139			

\@dtl@decimaltolocalefrac: removed	utf8: new .....	2
\@dtl@choptrailingzeroes and	2.25 (2016-01-18)	
added \@dtl@chopexcessfrac ...	\@dtldictcompare: added	
... --22	\expandonce .....	70
\@dtl@digitcount: new .....	\dtlcompare: added \expandonce ...	54
22	\dtlicompare: added \expandonce ...	65
\@dtlloaddb: added check for autokeys	2.26 (2016-07-20)	
218	\@@dtl@set@off: replaced fp	
\DTLcustombibitem: new .....	commands .....	404
345	\@@dtl@setoffr: replaced fp	
\DTLformatbooktitle: new .....	commands .....	404
362	\@dtl@gatherintfrac: new .....	108
\DTLformatthisbibentry: new .....	\dtl@computeangles: replaced fp	
325	commands .....	403
\DTLpcite: new .....	\dtl@insertinto: fixed bug (incorrect	
340	inequality sign) .....	10
\ifdtlautokeys: new .....	fixed bug (missing \@dtl@sortresult)	10
215	\dtlifnumclosedbetween: added	
2.23 (2015-07-11)	\number .....	106
\@DTLsort: bug fix: replaced	\dtlifnumeq: added \number .....	105
\dtlicompare with \dtlcompare .	\dtlifnumgt: added \number .....	106
196	\dtlifnumlt: added \number .....	106
General: removed etex as a required	\dtlifnumopenbetween: added	
package .....	\number .....	106
110	\DTLpiechart: removed truncation	
\dtl@getfirst: changed \end to	(caused minor gap between first and	
\end@dtl@getfirst .....	last segments) .....	--399
56	replaced \ifthen .....	400
\dtl@testifsubstring: bug fix: temp	replaced fp commands .....	398
control sequences clash with	\dtlround: fixed bug cause by rounding	
\@dtl@teststartswith .....	fixed bug caused by rounding errors .	108
--82	\dtltrunc: fixed bug caused by rounding	
\dtl@testinlist: new .....	errors .....	109
91	new .....	108
\DTLisinlist: new .....	2.27 (2016-07-28)	
91	\dtl@insertinto: undone the incorrect	
\DTLmaketabspace: restores tab catcode	change in v2.26 .....	10
to 10 .....	\dtlinsertinto: new .....	11
110	\dtl@sortlist: new .....	11
\getpersongender: bug fix: replaced	\edtlininsertinto: new .....	13
\ifpersonmale with \ifmale ....	2.28 (2017-11-10)	
448	\@dtl@formatlist@handler: new ....	14
\iffemale: bug fix: replaced	\@dtl@rawread: changed \xdef to	
\@thisperson with #1 .....	\protected\xdef .....	223
436	\@dtl@set@options: new .....	113
\ifmale: bug fix: replaced	\@dtl@formatlist: new .....	15
\@thisperson with #1 .....	General: renamed \toks@g... to	
435	\dtl@toks@g... .....	15
\persongender: bug fix: replaced	\datagidxconvertchars: new .....	287
\ifpersonmale with \ifmale ....		
448		
2.24 (2016-01-12)		
\@dtl@firsttonil: new .....		
56		
\dtl@getfirst@UTFviii: new .....		
55		
\dtl@if@two@octets: new .....		
55		
\dtl@ifcasechargroup: added check		
for UTF8 .....		
75		
\dtl@ifsingleorUTFviii: new .....		
4		
\dtldisableUTFviii: new .....		
3		
\dtlenableUTFviii: new .....		
2		
\dtlsetcharcode: new .....		
57		
\dtlsetdefaultUTFviiiicharcode:		
new .....		
57		
\dtlsetdefaultUTFviiiilccharcode:		
new .....		
61		
\dtlsetlccharcode: new .....		
57		
\dtlsetUTFviiiicharcode: new .....		
57		
\dtlsetUTFviiiilccharcode: new ....		
57		

\datagidxextendedtoascii:new ...	287	\xdtlgetrowindex:new .....	148
\DTLlandname:new .....	14	2.29 (2017-11-12)	
\DTLformatlist:new .....	14	\@dtl@readline: changed line read ..	216
\DTLlistformatitem:new .....	14	\@dtl@stripeol:new .....	216
\DTLlistformatlastsep:new .....	14	2.30 (2018-04-16)	
\DTLlistformatoxford:new .....	14	\@dtl@construct@lopoff: removed	
\DTLlistformatsep:new .....	14	spurious spaces .....	111
\ifdatagidxbalance:new .....	277	2.31 (2018-12-07)	
\printterms: added paragraph break at the start .....	317	\@dtl@dollar:new .....	46
\printterms@setupmulticol:new ..	314	\@dtl@listelement@outofrange:new ..	8
\printterms@setuptwocol:new ....	315	\@dtl@minus:new .....	46
\printtermsstartpar:new .....	314	\@dtl@plus:new .....	46
\s@dtlformatlist:new .....	14	\@dtl@protect:new .....	46
utf8:new .....	113,237	\DTLnumitemsinlist: made robust .....	8
		\ifDTLlistskipempty:new .....	6