

MASARYK UNIVERSITY
FACULTY OF EDUCATION
DEPARTMENT OF COMPUTER GRAPHICS AND DESIGN



***A fithesis3* user guide**
for the Faculty of Education

BACHELOR'S THESIS

Vít Novotný

Advisor: Doc. RNDr. Petr Sojka, Ph.D.

Brno, Spring 2018

Bibliographic record

NOVOTNÝ, Vít. *A fithesis3 user guide for the Faculty of Education*. Brno: Masaryk University, Faculty of Education, Department of Computer Graphics and Design, 2018. 17 p. Advisor: Doc. RNDr. Petr Sojka, Ph.D.

Abstract

Fithesis3 is a L^AT_EX document class, which streamlines the typesetting of the mandatory parts of theses, so that the author can focus at content alone. Fithesis3 can be used to write theses in various languages across the faculties of the Masaryk University.

This document describes the installation of the fithesis3 class, its configuration and its use at the Faculty of Education. As a demonstration of its capabilities, this document was typeset using the fithesis3 class.

Keywords

thesis, typesetting, L^AT_EX

Declaration

Hereby I declare that this paper is my original authorial work, which I have worked out on my own. All sources, references, and literature used or excerpted during elaboration of this work are properly cited and listed in complete reference to the due source.

Vít Novotný

Contents

1	Introduction	1
1.1	<i>Installation</i>	1
1.1.1	Installing a T _E X distribution	1
1.1.2	Installing packages	1
1.2	<i>Picking a T_EX engine</i>	3
1.3	<i>Creating and typesetting a fithesis3 document</i>	4
2	Configuration	7
2.1	<i>Setting the class options</i>	7
2.2	<i>Filling out the metadata</i>	10
3	Advanced usage	13
3.1	<i>Throubleshooting option clashes</i>	13
3.2	<i>Overriding changes made by style and locale files</i>	13
3.3	<i>Changing the layout</i>	14
3.4	<i>Replacing the backend</i>	16
	Bibliography	17

List of Figures

3.1 A document with disabled autoLayout 15

1 Introduction

To use the `fithesis3` class, you can use an online \LaTeX editor, such as Overleaf,¹ which allows you to skip the installation described in Section 1.1 completely.

1.1 Installation

1.1.1 Installing a \TeX distribution

If you decided not to use a public \TeX distribution, you will need to install one locally before proceeding further. A \TeX distribution contains tools and packages that are going to help you with preparing and typesetting your \LaTeX documents.

The two major \TeX distributions that you can install are Mik \TeX ,² which can be used with the Microsoft Windows operating system, and \TeX Live,³ which can be installed on both Unix and Windows operating systems. The advantages of Mik \TeX over \TeX Live include refined graphical user interface and the ability to install new packages on the fly.

Along with Mik \TeX , you will also need to install a Perl interpreter, such as Strawberry Perl.⁴ \TeX Live installs a Perl interpreter by default.

1.1.2 Installing packages

In order to function properly, `fithesis3` needs the following packages to be installed in your \TeX distribution: `keyval`, `etoolbox`, `ifxetex`, `ifluatex`, `inputenc`, `xcolor`, `graphix`, `pdfpages`, `hyperref`, `microtype`, `tikz`, `fontspec`, `unicode-math`, `mathpazo`, `tex-gyre-pagella`, `lm`, `cmap`, `fontenc`, `tabularx`, `tabu`, `booktabs`, `csquotes`, `biblatex`, `fithesis`.

If you performed a full installation of \TeX Live, you should already have all the required packages installed. If you are using a partial installation of \TeX Live, you can use the `tlmgr` command-line tool by

-
1. Overleaf `fithesis3` templates are located at <http://www.overleaf.com/gallery/tagged/muni>.
 2. Mik \TeX can be acquired from <http://miktex.org/2.9/setup>.
 3. \TeX Live can be acquired from <http://www.tug.org/texlive>.
 4. Strawberry Perl can be downloaded from <http://strawberryperl.com/>.

1. INTRODUCTION

executing `tlmgr install <pkgname>`, where `<pkgname>` is the name of the package you wish to install. In some cases, T_EX Live may assign a different name to a package. To find out the T_EX Live name of a package, open the <http://www.ctan.org/pkg/<pkgname>> webpage in a web browser. It should contain the following text:

Contained in T_EX Live as `<texlivename>`

where `<texlivename>` corresponds to the T_EX Live name of the package. Use this name instead of `<pkgname>` with `tlmgr`. Alternatively, you can download the packages manually from <http://www.ctan.org/pkg/<pkgname>> and extract them into the `texmf/` directory located in your user home directory. Mind that the packages themselves may depend on other packages; if you are using a partial installation of T_EX Live, you will have to resolve these dependencies manually by inspecting the documentation of each package.

If you use MikT_EX and you enabled the *over the air installation of packages* during the installation, MikT_EX will automatically download all the required packages, when you first typeset a fibeamer document. If you didn't enable this feature, you will need to enter the MikT_EX package manager by running

Start >> MikTeX >> MikTeX Package Manager (Admin)

and download the packages manually through the user interface. In some cases, MikT_EX may assign a different name to a package. To find out the MikT_EX name of a package, open the <http://www.ctan.org/pkg/<pkgname>> webpage in a web browser, where `<pkgname>` is the name of the package you wish to install. It should contain the following text:

Contained in MikT_EX as `<miktexname>`

where `<miktexname>` corresponds to the MikT_EX name of the package. If you still can't find the package, try synchronizing the package database by selecting

Repository >> Synchronize

from the menu bar of the MikT_EX package manager. Mind that the packages themselves may depend on other packages; if you disabled

the over the air installation of packages, you will have to resolve these dependencies manually by inspecting the documentation of each package.

If you wish to use a newer version of `fithesis3` than the one that is available in your $\text{T}_{\text{E}}\text{X}$ distribution, you should download a file named `fithesis.tds.zip` containing the version of the package you wish to use and place it in a root directory that is recognized by your $\text{T}_{\text{E}}\text{X}$ distribution. In $\text{T}_{\text{E}}\text{X}$ Live,⁵ one of such directories is the `texmf/` folder in your user home directory. In Mik $\text{T}_{\text{E}}\text{X}$,⁶ the list of recognized root directories can be gleaned by running

```
Start >> MikTeX >> MikTeX Options (Admin) >> Roots
```

1.2 Picking a $\text{T}_{\text{E}}\text{X}$ engine

There are several programs, called $\text{T}_{\text{E}}\text{X}$ engines, that you can use to typeset `fithesis3` $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ source files into displayable `PDF` documents. The ones we will discuss are `pdf $\text{T}_{\text{E}}\text{X}$` and `Lua $\text{T}_{\text{E}}\text{X}$` .

`pdf $\text{T}_{\text{E}}\text{X}$` is the more conservative choice and most $\text{T}_{\text{E}}\text{X}$ editors use `pdf $\text{T}_{\text{E}}\text{X}$` as the default $\text{T}_{\text{E}}\text{X}$ engine. The main advantage `Lua $\text{T}_{\text{E}}\text{X}$` over `pdf $\text{T}_{\text{E}}\text{X}$` for a `fithesis3` user is the ability to use standard OpenType and TrueType fonts installed on your system, whereas `pdf $\text{T}_{\text{E}}\text{X}$` is confined to the fonts installed in your $\text{T}_{\text{E}}\text{X}$ distribution.

If the ability to use arbitrary fonts within your documents interests you, Chapter 3 of the `fontspec` package manual⁷ should provide you with the relevant information. If you are only going to use the fonts present in the $\text{T}_{\text{E}}\text{X}$ distribution or if you do not intend to change the preset `fithesis3` fonts at all, you can safely use `pdf $\text{T}_{\text{E}}\text{X}$` , which is currently also considerably faster than `Lua $\text{T}_{\text{E}}\text{X}$` .

5. For more information about the $\text{T}_{\text{E}}\text{X}$ Live root directories, see <http://www.tug.org/texlive/doc/texlive-en/texlive-en.html#x1-110002.3>, Chapter 2.3.


6. For more information about the Mik $\text{T}_{\text{E}}\text{X}$ root directories, see <http://docs.miktex.org/manual/localadditions.html>.

7. The `fontspec` package manual is available at <http://mirrors.ctan.org/macros/latex/contrib/fontspec/fontspec.pdf>.

1.3 Creating and typesetting a fithesis3 document

Before using the `fithesis3` class, it is useful to be familiar with the \LaTeX typesetting system. A good way to get started is to read one of the introductory texts in English [7, 2, 4, 1] or in Czech [5, 6]. Taking one of the *FI:PB029*, *PřF:M5751*, or *FF:PLIN028* courses taught at the Masaryk University is also helpful.

To become familiar with `fithesis3`, you are encouraged to inspect the example documents `ped-pdflatex.pdf` and `ped-lualatex.pdf` as well as their \LaTeX source files that are named `ped-pdflatex.tex` and `ped-lualatex.tex`. The example documents are distributed along with the package inside the `example/` directory.⁸ By modifying and by typesetting these \LaTeX source files using either the `pdf \TeX` or the `Lua \TeX` engine, you can quickly gain a working knowledge of \LaTeX and use these source files as the basis for your thesis.

If you are using an online editor, such as Overleaf⁹, \LaTeX source files will be typeset automatically, as you edit them. The \TeX engine can be selected inside the  project settings.

If you are using a graphical \TeX editor, such as \TeX works,¹⁰ you can typeset a \LaTeX source file by opening the source file from within the editor and running either the `pdf \LaTeX` or `Lua \LaTeX` (depending on your choice of \TeX engine) command from the task bar. The command needs to be executed at least twice to produce the table of contents, the list of tables, and the list of figures. Additional commands for the typesetting of the bibliography and the index are described in the example documents.

If you are using the command line, you can typeset \LaTeX source files by running either the `pdf \LaTeX --shell-escape name.tex` command or the `lualatex name.tex` command depending on your chosen \TeX engine, where *name.tex* corresponds to the name of a \LaTeX

8. The example `fithesis3` documents are also available online at <http://mirror.ctan.org/macros/latex/contrib/fithesis/example/mu> To typeset the example documents, you need to download the `example.bib` file as well, as it contains the bibliography database used in the examples.

9. Overleaf `fithesis3` templates are located at <http://www.overleaf.com/gallery/tagged/muni>.

10. \TeX works can be downloaded from <http://www.tug.org/texworks/>.

source file. In the case of the two aforementioned example files, the corresponding commands would be

```
pdflatex --shell-escape ped-pdflatex.tex for pdfLATEX,  
and lualatex ped-lualatex.tex for LuaLATEX.
```

The command needs to be executed from within the directory, where the L^AT_EX source file is located. In Windows, the command line can be opened in a directory by holding down the **Shift** key and by clicking the right mouse button while hovering the cursor over a directory. Select the **Open Command Window Here** option in the context menu that opens shortly afterwards. The command also needs to be executed at least twice.

Beside Overleaf and T_EXworks, any text editor can be used to modify L^AT_EX source files. However, it is important to ensure that the text editor saves the L^AT_EX source files in the UTF-8 text encoding. A L^AT_EX file saved in a different text encoding is likely to be either impossible to typeset or to produce unexpected output.

2 Configuration

This chapter provides a full list of the settings that can be used to set up and customize the fithesis3 class.

2.1 Setting the class options

At the beginning of a fithesis3 L^AT_EX source file, the command

```
\documentclass[option1, option2, ..., optionN]{fithesis3}
```

is used. The following list summarizes the options that are supported by the fithesis3 class and their meaning. Options that are enabled by default are *set in italics*.

digital This option sets the options that are the default for the digital version of a thesis. These options are *set in red*.

printed This option sets the options that are the default for the printed version of a thesis. These options are *set in blue*.

10pt, 11pt, 12pt These options set the font size of the main text to either 10 pt, 11 pt, or 12 pt, respectively. Using the 12 pt font size with the preset fonts should result in the optimal line width of approximately 66 characters in one-column typesetting. With two-column typesetting, the 10 pt font size is a better choice, yielding approximately the optimal 45 characters per line.

oneside This option enables one-sided typesetting. One-sided typesetting and printing is generally discouraged. Use only if you don't have access to a double-sided printer, or if one-sided typesetting is a formal requirement at your faculty.

twoside This option enables double-sided typesetting. Double-sided typesetting is generally regarded as more visually pleasing and double-sided printing consumes less paper. Use at least 120 grams per square meter paper to prevent show-through.

*You may feel compelled to use **twoside** for the printed version of the thesis and **oneside** for the digital version to reduce the number of*

2. CONFIGURATION

blank pages. This will, however, cause the page numbers to differ between the printed and the digital version, which will make it difficult to cite your work. Do not do it.

onecolumn This option causes the main text of the thesis to be set in one column.

twocolumn This option causes the main text of the thesis to be set in two columns. The two-column format is unconventional in theses; you should consult its use with your thesis advisor. If you decide to use the two-column format, remember that you also need to change the font size option (**10pt**, **11pt**, **12pt**).

draft This option replaces any images with blank rectangles and marks all overfull lines with black boxes. Other packages that you use may behave differently¹ with the **draft** option specified. This can be useful, if you are going to print and proofread a draft of your document.

final Unlike the **draft** option, this option typesets the release version of the document.

palatino This option sets the roman text font family and the mathematical font family to Palatino.

nopalatino This option prevents fithesis3 from setting up the fonts. The user must set the fonts manually in the preamble of the document.

color This option enables the use of colors. Note that all color definitions and colored logos are currently in `rgb`, which makes this option generally unsuitable for the printed version of the document. Although most printers will accept `rgb` documents, the resulting colors may not match what you see on screen.

Unless you have a compelling reason not to, you should use this option in the electronic version that you are going to publish online.

1. For more information about the effects of the `draft` option on various packages, see <http://tex.stackexchange.com/a/49369/70941>.

monochrome This option disables colors. Disabling colors is generally discouraged, unless you don't have access to a color printer. However, due to the prevalence of monochrome printing, this option is the default.

microtype This option sets up microtypographic extensions,² which results in visually more pleasing paragraphs of text.

nomicrotype This option prevents fithesis3 from setting up microtypographic extensions.

table This option redefines some of the L^AT_EX table environments (*tabular*, *tabularx*, and *tabu*) to use alternating colors for odd and even rows. This option only works, if the ***color*** option is enabled.

oldtable This option instructs the style not to redefine any table environments.

lot This option causes the list of tables to be included in the front matter of the thesis.

noлот This option removes the list of tables from the front matter of the thesis.

lof This option causes the list of figures to be included in the front matter of the thesis.

noлот This option removes the list of figures from the front matter of the thesis.

cover This option instructs the class to typeset the cover of the thesis on the first pages of the resulting document. A cover should be generally present in the electronic version of the document for completeness. The cover should not appear inside the printed document and should only serve as a template for the text imprinted on the front cover of the thesis cover.

2. For more information about the T_EX engine microtypographic extensions, see <http://mirrors.ctan.org/macros/latex/contrib/microtype/microtype.pdf>.

nocover This option forbids the typesetting of the thesis cover. Use, if you are typesetting the printed version of a thesis and you are not going to have a cover made for your thesis.

2.2 Filling out the metadata

Beside the class options, you can also fill out information about your thesis by inserting the command

```
\thesissetup{
  key1 = {value1},
  key2 = {value2},
  ...
  keyN = {valueN},
}
```

into the preamble of your thesis. The following list summarizes the keys and values that are recognized by the `fithesis3` class and are meaningful for the Faculty of Education.

title This key can be used to specify the title of the thesis. The value will be stored as one of the properties of the output PDF file; do not use any \LaTeX formatting commands within the value.

TeXtitle This key can be used to specify the title of the thesis. The value will be typeset in the resulting PDF document, so you can use \LaTeX formatting commands within the value. If the value of the key is unspecified, the value of the **title** key will be used instead.

author This key can be used to specify the full name of the author.

keywords This key can be used to specify a list of keywords for your thesis. The value will be stored as one of the properties of the output PDF file; do not use any \LaTeX formatting commands within the value.

TeXkeywords This key can be used to specify a list of keywords for your thesis. The value will be typeset in the resulting PDF document, so you can use \LaTeX formatting commands within the

value. If the value of the key is unspecified, the value of the **keywords** key will be used instead.

keywordsEn This key can be used to specify a list of English keywords for your thesis. Do not use any \LaTeX formatting commands within the value. If you are typesetting your thesis in English, this value does not need to be specified.

TeXkeywordsEn This key can be used to specify a list of English keywords for your thesis. The value will be typeset in the resulting PDF document, so you can use \LaTeX formatting commands within the value. If you are typesetting your thesis in English, this value does not need to be specified.

advisor This key can be used to specify the full name of the thesis advisor.

gender This key can be used to specify the gender of the author. It is used to determine the suffixes employed in the Czech and Slovak locales. If you are typesetting your document in English, you don't need to specify this information. The valid values include:

m Male

f Female

type This key can be used to specify the type of the thesis. The recognized types of theses include:

bc Bachelor's thesis

mgr Master's thesis

d Doctoral thesis

r Rigorous thesis

faculty This key can be used to set the faculty at which the thesis is going to be defended. To choose the Faculty of Education, use **ped** as the value.

department This key can be used to specify the name of the department at which the thesis is going to be defended.

2. CONFIGURATION

date This key can be used to specify the date of the thesis submission in the YYYY/MM/DD format, where YYYY stands for the full year, MM stands for the month, and DD stands for the day of month.

bib This key can be used to specify a list of BIB files containing the bibliography databases. The list should be in the following format:

```
path/to/first/file.bib, path/to/second/file.bib, ...
```

When this key is specified, the `fithesis3` class will automatically typeset a bibliography section.³ If you want more control over where and how the bibliography is typeset, use the `\printbibliography[bibintoc]` command.

When this key is not specified, no bibliography will be produced, which provides the opportunity for the advanced user to set up their bibliography management manually.

abstract This key can be used to specify the abstract of the thesis.

abstractEn This key can be used to specify the English abstract of the thesis. If you are typesetting your thesis in English, this value does not need to be specified.

thanks This key can be used to specify the text of the acknowledgements.

declaration This key can be used to specify the text of the declaration. If the value of the key is unspecified, the following text is going to be used instead in the English locale: *“Hereby I declare that this paper is my original authorial work, which I have worked out on my own. All sources, references, and literature used or excerpted during elaboration of this work are properly cited and listed in complete reference to the due source.”*

The complete list of metadata keys can be found in Section 2.2 of the technical documentation of the `fithesis3` class [3].

3. The bibliography will be typeset according to the ISO 690:2010 standard using the `biblatex-iso690` bibliography style. For more information, see <https://www.ctan.org/pkg/biblatex-iso690>.

3 Advanced usage

This chapter contains a couple of tips for the advanced user, who may want to configure the class beyond what the class options and the metadata settings offer. An understanding of how the main routine of `fithesis3` works is beneficial. The main routine is documented in Section 2.4 of the technical documentation of the `fithesis3` class [3].

3.1 Troubleshooting option clashes

If you need to load a package with a specific set of options and the package happens to be required by the `fithesis3` class, as specified in Section 1.1.2, you may experience an option clash error. If this error occurs, prepend `\PassOptionsToPackage{options}{package}` before the `\documentclass[...]{fithesis3}` command. If you need to configure the package, you can do that anywhere after the document preamble. If the package needs to be configured within the preamble, you can load the `fithesis3` style files prematurely using the `\thesisload` command as follows:

```
\documentclass[...]{fithesis3}
%% The preamble
\thesisload
%% Here goes the package configuration.
\begin{document}
  %% The document
\end{document}
```

Note that only a small portion of the packages loaded by `fithesis3` is loaded with a specific set of options. The rest of the packages is *lazy-loaded* (loaded only if the user hasn't already loaded them), in which case no clash is possible.

3.2 Overriding changes made by style and locale files

The `fithesis3` style files are loaded immediately before the beginning of your document and may change values you would like to set by

yourself, such as the L^AT_EX `tocdepth` and `secnumdepth` counters. Locale files are also loaded immediately before your document, which prevents you from modifying locale strings from within the preamble of your document.

To overcome this limitation, you can load the style and locale files prematurely using the `\thesisload` command as follows:

```
\documentclass[...]{fithesis3}
%% The preamble
\thesisload
%% Here go your changes.
\begin{document}
  %% The document
\end{document}
```

Although you may use the `\thesisload` command anywhere in the preamble, using the command before configuring your metadata using the `\thesissetup` command will load all the wrong style and locale files not taking into account your faculty and locale settings.

Another danger is that `\thesisload` command loads the `hyperref` package, which adds hyperlinks and PDF metadata into the resulting PDF document. The `hyperref` package is rather delicate in that it needs to be loaded after most other packages. Loading additional packages after `\thesisload` may therefore cause these packages to work incorrectly.

3.3 Changing the layout

If you are unsatisfied with the automatic arrangement of the mandatory parts of the thesis, you may disable it using the `autoLayout` metadata key:

```
\documentclass[...]{fithesis3}
\thesissetup{
  faculty=ped,
  autoLayout=false}
\begin{document}
  A document which, except for this line,
```

A document which, except for this line, is completely empty.
--

Figure 3.1: A document with disabled autoLayout

is completely empty.

```
\end{document}
```

This results in a document that only consists of the main matter of the thesis (see Figure 3.1). You can now manually insert the preamble and the postamble:

```
\documentclass[...] {fithesis3}
\thesissetup{
  faculty=ped,
  autoLayout=false}
\begin{document}
  \makeatletter\thesis@preamble\makeatother
  A document which once again contains all
  the mandatory parts of a thesis.
  \makeatletter\thesis@postamble\makeatother
\end{document}
```

We are now back to the original document. Instead of inserting the `\thesis@preamble` and `\thesis@postamble` commands into the document, we may however insert only certain sections at the beginning and at the end of the document.

The `\thesis@preamble` and `\thesis@postamble` commands set up the proper environment and execute the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` commands. To change the layout, it is sufficient to redefine the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` commands.

To create a document that only contains the title page at the beginning of the document and the list of tables at the end of the document, we would use the following code:

```
\documentclass[...] {fithesis3}
\thesissetup{
  faculty=ped,
  autoLayout=false}
```

```
\begin{document}
  \makeatletter
  \def\thesis@blocks@preamble{\thesis@blocks@titlePage}
  \thesis@preamble
  \makeatother
  A document that only contains the title page and the
  list of tables.
  \makeatletter
  \def\thesis@blocks@postamble{\thesis@blocks@lot}
  \thesis@postamble
  \makeatother
\end{document}
```

The available blocks are documented in Section 3.5 of the technical documentation of the fithesis3 class [3].

3.4 Replacing the backend

Fithesis3 operates on top of the rapport3 class, which defines much of the document design. To change the backend class, you need to redefine the value of `\thesis@backend` from the default value of

```
[a4paper] {rapport3}
```

to a different value. This assignment needs to be performed prior to the `\documentclass` command. If you wanted to change the backend class of fithesis3 to the KOMA-Script `screprt` with the `a4paper` option, your document would begin as follows:

```
\let\ChapFont\bfseries
\let\PageFont\bfseries
\makeatletter
  \def\thesis@backend{[a4paper]{screprt}}
\makeatother
\documentclass[...]{fithesis3}
%% Here goes the rest of the document.
```

The `\ChapFont` and `\PageFont` commands are provided by the `rapport3` class, but not by the `screprt` class, which is why we needed to define them manually. Inconsistencies between different backend classes need to be resolved on a case-by-case basis.

Bibliography

1. \LaTeX [online]. Wikibooks.org, 2013 [visited on 2015-05-03]. Available from: <http://en.wikibooks.org/wiki/LaTeX>.
2. COTTRELL, Allin. *A short introduction to \LaTeX* [online]. 1995 [visited on 2015-05-03]. Available from: http://ricardo.ecn.wfu.edu/~cottrell/ecn297/latex_tut.pdf.
3. NOVOTNÝ, Vít; MAREK, Daniel; PAVLOVIČ, Jan; SOJKA, Petr. *The fithesis3 class for the typesetting of theses written at the Masaryk University in Brno* [online]. 2015 [visited on 2015-11-11]. Available from: <http://mirrors.ctan.org/macros/latex/contrib/fithesis/fithesis.pdf>.
4. OETIKER, Tobias; PARTL, Hubert; HYNA, Irene; SCHLEGL, Elisabeth. *The Not So Short Introduction to \LaTeX 2 ϵ or \LaTeX 2 ϵ in 157 minutes* [online]. 2014 [visited on 2015-05-03]. Available from: <http://tobi.oetiker.ch/lshort/lshort.pdf>.
5. RYBIČKA, Jiří. *\LaTeX pro začátečníky*. 3rd ed. Konvoj, 2003. ISBN 80-7302-049-1.
6. SATRAPA, Pavel. *\LaTeX pro pragmatiky* [online]. 2011 [visited on 2015-05-03]. Available from: <http://mirror.ctan.org/info/czech/latex-pro-pragmatiky/latex-pro-pragmatiky.pdf>.
7. *The very short guide to typesetting with \LaTeX* [online]. Silmaril Consultants, 2013 [visited on 2015-05-03]. Available from: <http://tug.ctan.org/info/latex-veryshortguide/veryshortguide.pdf>.