

# The soulutf8 package

Heiko Oberdiek\*

<heiko.oberdiek at gmail.com>

2016/05/16 v1.1

## Abstract

This package extends package soul and adds some support for UTF-8. Namely the input encodings utf8.def from package inputenc and package ucs's utf8x.def are supported.

## Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Documentation</b>                    | <b>2</b>  |
| 1.1      | Patch                                   | 2         |
| 1.2      | Future                                  | 2         |
| <b>2</b> | <b>Implementation</b>                   | <b>2</b>  |
| 2.1      | Reload check and package identification | 2         |
| 2.2      | Catcodes                                | 4         |
| 2.3      | Loading packages                        | 5         |
| 2.3.1    | plain T <sub>E</sub> X                  | 5         |
| 2.3.2    | L <sup>A</sup> T <sub>E</sub> X         | 5         |
| 2.3.3    | ε-T <sub>E</sub> X                      | 6         |
| 2.4      | Macro for redefinitions                 | 6         |
| 2.5      | Redefinition of \SOUL@eval              | 6         |
| 2.6      | UTF-8 analysis                          | 9         |
| 2.6.1    | Help strings                            | 9         |
| 2.6.2    | Support for utf8.def                    | 10        |
| 2.6.3    | Support for utf8x.def                   | 10        |
| 2.7      | Actions for UTF-8 sequences             | 11        |
| 2.7.1    | Redefinition of \SOUL@splittoken        | 12        |
| 2.8      | Patches                                 | 12        |
| <b>3</b> | <b>Test</b>                             | <b>15</b> |
| 3.1      | Catcode checks for loading              | 15        |
| 3.2      | L <sup>A</sup> T <sub>E</sub> Xtests    | 16        |
| 3.2.1    | Driver definitions                      | 17        |
| 3.2.2    | Test macros                             | 19        |
| 3.2.3    | Testing                                 | 22        |
| <b>4</b> | <b>Installation</b>                     | <b>22</b> |
| 4.1      | Download                                | 22        |
| 4.2      | Bundle installation                     | 23        |
| 4.3      | Package installation                    | 23        |
| 4.4      | Refresh file name databases             | 23        |
| 4.5      | Some details for the interested         | 24        |
| <b>5</b> | <b>Catalogue</b>                        | <b>24</b> |

---

\*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

|          |                             |           |
|----------|-----------------------------|-----------|
| <b>6</b> | <b>References</b>           | <b>25</b> |
| <b>7</b> | <b>History</b>              | <b>25</b> |
|          | [2007/09/09 v1.0] . . . . . | 25        |
|          | [2016/05/16 v1.1] . . . . . | 25        |
| <b>8</b> | <b>Index</b>                | <b>25</b> |

## 1 Documentation

This package `soulutf8` does not have own options and does not define new user commands. Any option is passed to package `soul` [1] that is loaded first. Then some internal macros of `soul` are redefined to add support for UTF-8. The following input encodings are supported:

```
utf8    LATEX base    TDS:tex/latex/base/utf8.def [3]
utf8x   Package ucs    TDS:tex/latex/ucs/utf8x.def [2]
```

UTF-8 byte sequences are added as token group to a word, even if these UTF-8 characters are some kind of hyphen or space. As exception the following three Unicode characters are handled specially:

| Slot   | Name           | Action |
|--------|----------------|--------|
| U+00A0 | NO-BREAK SPACE | like ~ |
| U+2013 | EN DASH        | --     |
| U+2014 | EM DASH        | ---    |

### 1.1 Patch

Also package `soulutf8` tries to patch package `soul` to improve its behaviour:

- A problem with additional levels of curly braces is fixed. As advantage more implicate kernings are detected. However, the result may be incompatible with the original behaviour of package `soul` because of these respected implicate kernings.
- $\varepsilon$ -T<sub>E</sub>X, especially `\unexpanded` is supported. This allows a better protection of token groups (`\mbox{...}`, `math`, ...).

### 1.2 Future

Currently package `soul` does not seem to be maintained. Nevertheless if there will be a new version that adds support for UTF-8, then this package may become obsolete.

## 2 Implementation

```
1 \langle *package \rangle
```

### 2.1 Reload check and package identification

Reload check, especially if the package is not used with L<sup>A</sup>T<sub>E</sub>X.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
```

```

9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@soulutf8.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{ }%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{soulutf8}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%

```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1{#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[#{#3}]%
58 \ifx#1\@undefined
59 \xdef#1{#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1{#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@soulutf8.sty\endcsname
67 \ProvidesPackage{soulutf8}%
68 [2016/05/16 v1.1 Permit use of UTF-8 characters in soul (HO)]%

```

## 2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76 \expandafter\edef\csname SOuL@AtEnd\endcsname{%
77 \endlinechar=\the\endlinechar\relax
78 \catcode13=\the\catcode13\relax
79 \catcode32=\the\catcode32\relax
80 \catcode35=\the\catcode35\relax
81 \catcode61=\the\catcode61\relax
82 \catcode64=\the\catcode64\relax
83 \catcode123=\the\catcode123\relax
84 \catcode125=\the\catcode125\relax
85 }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95 \edef\SOuL@AtEnd{%
96 \SOuL@AtEnd
97 \catcode#1=\the\catcode#1\relax
98 }%
99 \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{10}{12}% ^^J
102 \TMP@EnsureCode{33}{12}% !
103 \TMP@EnsureCode{34}{12}% "
104 \TMP@EnsureCode{36}{3}% $
105 \TMP@EnsureCode{39}{12}% '
106 \TMP@EnsureCode{40}{12}% (
107 \TMP@EnsureCode{41}{12}% )
108 \TMP@EnsureCode{42}{12}% *
109 \TMP@EnsureCode{43}{12}% +
110 \TMP@EnsureCode{44}{12}% ,
111 \TMP@EnsureCode{45}{12}% -
112 \TMP@EnsureCode{46}{12}% .
113 \TMP@EnsureCode{47}{12}% /
114 \TMP@EnsureCode{58}{12}% :
115 \TMP@EnsureCode{60}{12}% <
116 \TMP@EnsureCode{62}{12}% >
117 \TMP@EnsureCode{91}{12}% [
118 \TMP@EnsureCode{93}{12}% ]
119 \TMP@EnsureCode{94}{7}% ^
120 \TMP@EnsureCode{96}{12}% `
121 \TMP@EnsureCode{126}\active % ~
122 \TMP@EnsureCode{128}{12}% ^^80
123 \TMP@EnsureCode{147}{12}% ^^93
124 \TMP@EnsureCode{148}{12}% ^^94
125 \TMP@EnsureCode{160}{12}% ^^a0
126 \TMP@EnsureCode{194}{12}% ^^c2
127 \TMP@EnsureCode{226}{12}% ^^e2
128 \edef\SOuL@AtEnd{\SOuL@AtEnd\noexpand\endinput}

```

## 2.3 Loading packages

Package `soul` uses `\documentclass` to detect L<sup>A</sup>T<sub>E</sub>X.

```
129 \ifx\documentclass\@undefined
```

### 2.3.1 plain T<sub>E</sub>X

First we check, whether package `soul` is already loaded.

```
130 \expandafter\ifx\csname SOUL@\endcsname\relax
```

In case of plain T<sub>E</sub>X package `soul` defines some macros in a simple manner that will break the definitions of `miniltx.tex`, for example. Therefore these macros are first saved and restored afterwards.

```
131 \let\SOuL@orgDeclareRobustCommand\DeclareRobustCommand
132 \let\SOuL@orgnewcommand \newcommand
133 \let\SOuL@orgDeclareOption \DeclareOption
134 \let\SOuL@orgPackageError \PackageError
135 \def\SOuL@restorelatexcmds{%
136 \let\DeclareRobustCommand\SOuL@orgDeclareRobustCommand
137 \let\newcommand \SOuL@orgnewcommand
138 \let\DeclareOption \SOuL@orgDeclareOption
139 \let\PackageError \SOuL@orgPackageError
140 }%
141 \input soul.sty\relax
142 \SOuL@restorelatexcmds
143 \fi
```

`\SOUL@error` Package `soul`'s use of `\PackageError` is replaced by `\@PackageError` of package `infwarerr`.

```
144 \input infwarerr.sty\relax
145 \let\SOuL@orgSOUL@error\SOUL@error
146 \def\SOUL@error{%
147 \begingroup
148 \let\PackageError\@PackageError
149 \SOuL@orgSOUL@error
150 \endgroup
151 }%
152 \input etexcmds.sty\relax
```

`\@onelevel@sanitize` Define L<sup>A</sup>T<sub>E</sub>X's `\@onelevel@sanitize` if not already available.

```
153 \expandafter\ifx\csname @onelevel@sanitize\endcsname\relax
154 \def\@onelevel@sanitize#1{%
155 \edef#1{%
156 \expandafter\strip@prefix\meaning#1%
157 }%
158 }%
```

`\strip@prefix`

```
159 \def\strip@prefix#1>{}%
160 \fi
161 \else
```

### 2.3.2 L<sup>A</sup>T<sub>E</sub>X

```
162 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{soul}}%
163 \ProcessOptions\relax
164 \RequirePackage{soul}[2003/11/17]%
165 \RequirePackage{infwarerr}[2016/05/16]%
166 \RequirePackage{etexcmds}[2016/05/16]%
167 \fi
```

### 2.3.3 $\epsilon$ -TeX

In plain TeX command `\+` is an *outer* macro. Therefore numbers are used to avoid problems.

```
168 \ifetex@unexpanded
169 \catcode33=14 % '!': comment
170 \catcode43=9 % '+': ignore
171 \else
172 \catcode33=9 % '!': ignore
173 \catcode43=14 % '+': comment
174 \fi
```

## 2.4 Macro for redefinitions

`\SOuL@redefine`

```
175 \def\SOuL@redefine#1{%
176 \begingroup
177 \def\SOuL@cmd{#1}%
178 \afterassignment\SOuL@cmdcheck
179 \def\SOuL@temp
180 }
```

`\SOuL@cmdcheck`

```
181 \def\SOuL@cmdcheck{%
182 \expandafter\ifx\SOuL@cmd\SOuL@temp
183 \else
184 \edef\SOuL@temp*{\expandafter\string\SOuL@cmd}%
185 \@PackageWarningNoLine{soulutf8}{%
186 Command \SOuL@temp* has changed.\MessageBreak
187 Supported versions of package `soul': 2003/11/17.\MessageBreak
188 Depending on the unknown changes the redefinition\MessageBreak
189 of \SOuL@temp* may not behave correctly%
190 }%
191 \fi
192 \expandafter\endgroup
193 \expandafter\def\SOuL@cmd
194 }
```

## 2.5 Redefinition of `\SOUL@eval`

`\SOUL@eval` Macro `\SOUL@eval` is redefined to add detection of the first byte of a UTF-8 sequence. Because `\SOUL@eval` is overwritten, a warning is issued, if the contents of `\SOUL@eval` is not as expected.

```
195 \SOuL@redefine\SOUL@eval{%
```

First the expected definition.

```
196 \def\SOUL@n*##1{\SOUL@scan}%
197 \if\noexpand\SOUL@@\SOUL@spc
198 \else
199 \SOUL@ignorespacesfalse
200 \fi
201 \ifnum\SOUL@minus=\thr@@
202 \SOUL@flushminus
203 \else\ifnum\SOUL@comma=\tw@
204 \SOUL@flushcomma
205 \else\ifnum\SOUL@apo=\tw@
206 \SOUL@flushapo
207 \else\ifnum\SOUL@grave=\tw@
208 \SOUL@flushgrave
209 \fi\fi\fi\fi
210 \ifx\SOUL@@-\else\SOUL@flushminus\fi
211 \ifx\SOUL@@,\else\SOUL@flushcomma\fi
```

```

212 \ifx\SOUL@@'\else\SOUL@flushapo\fi
213 \ifx\SOUL@@`\else\SOUL@flushgrave\fi
214 \ifx\SOUL@@-%
215   \advance\SOUL@minus\@ne
216 \else\ifx\SOUL@@,%
217   \advance\SOUL@comma\@ne
218 \else\ifx\SOUL@@'\%
219   \advance\SOUL@apo\@ne
220 \else\ifx\SOUL@@`%
221   \advance\SOUL@grave\@ne
222 \else
223   \SOUL@flushminus
224   \SOUL@flushcomma
225   \SOUL@flushapo
226   \SOUL@flushgrave
227 \ifx\SOUL@@\SOUL@stop
228   \def\SOUL@n*{%
229     \SOUL@doword
230     \SOUL@eventuallyexhyphen\null
231   }%
232 \else\ifx\SOUL@@\par
233   \def\SOUL@n*\par{\par\leavevmode\SOUL@scan}%
234 \else\if\noexpand\SOUL@@\SOUL@spc
235   \SOUL@doword
236   \SOUL@eventuallyexhyphen\null
237   \ifSOUL@ignorespaces
238   \else
239     \SOUL@everySPACE{}%
240   \fi
241   \def\SOUL@n* {\SOUL@scan}%
242 \else\ifx\SOUL@@\%
243   \SOUL@doword
244   \SOUL@eventuallyexhyphen\null
245   \SOUL@everySPACE{\unskip\nobreak\hfil\break}%
246   \SOUL@ignorespacestrue
247 \else\ifx\SOUL@@-%
248   \SOUL@doword
249   \SOUL@eventuallyexhyphen\null
250   \SOUL@everySPACE{\nobreak}%
251 \else\ifx\SOUL@@\slash
252   \SOUL@doword
253   \SOUL@eventuallyexhyphen{/}%
254   \SOUL@exhyphen{/}%
255 \else\ifx\SOUL@@\mbox
256   \def\SOUL@n*{\SOUL@addprotect}%
257 \else\ifx\SOUL@@\hbox
258   \def\SOUL@n*{\SOUL@addprotect}%
259 \else\ifx\SOUL@@\soulomit
260   \def\SOUL@n*\soulomit##1{%
261     \SOUL@doword
262     {\spaceskip\SOUL@spaceskip##1}%
263   \SOUL@scan
264   }%
265 \else\ifx\SOUL@@\break
266   \SOUL@doword
267   \break
268 \else\ifx\SOUL@@\linebreak
269   \SOUL@doword
270   \SOUL@everySPACE{\linebreak}%
271 \else\ifcat\bgroup\noexpand\SOUL@@
272   \def\SOUL@n*{\SOUL@addgroup{}}%
273 \else\ifcat$\noexpand\SOUL@@

```

```

274 \def\SOUL@n*{\SOUL@addmath}%
275 \else
276 \def\SOUL@n*{\SOUL@dotoken}%
277 \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi
278 \fi\fi\fi\fi
279 \SOUL@n*%
280 }{%

```

Now the redefined version follows.

```

281 \def\SOUL@n*##1{\SOUL@scan}%
282 \if\noexpand\SOUL@@\SOUL@spc
283 \else
284 \SOUL@ignorespacesfalse
285 \fi
286 \ifnum\SOUL@minus=\thr@@
287 \SOUL@flushminus
288 \else\ifnum\SOUL@comma=\tw@
289 \SOUL@flushcomma
290 \else\ifnum\SOUL@apo=\tw@
291 \SOUL@flushapo
292 \else\ifnum\SOUL@grave=\tw@
293 \SOUL@flushgrave
294 \fi\fi\fi\fi
295 \ifx\SOUL@@-\else\SOUL@flushminus\fi
296 \ifx\SOUL@@,\else\SOUL@flushcomma\fi
297 \ifx\SOUL@@'\else\SOUL@flushapo\fi
298 \ifx\SOUL@@`\else\SOUL@flushgrave\fi
299 \ifx\SOUL@@-%
300 \advance\SOUL@minus\@ne
301 \else\ifx\SOUL@@,%
302 \advance\SOUL@comma\@ne
303 \else\ifx\SOUL@@'%
304 \advance\SOUL@apo\@ne
305 \else\ifx\SOUL@@`\
306 \advance\SOUL@grave\@ne
307 \else
308 \SOUL@flushminus
309 \SOUL@flushcomma
310 \SOUL@flushapo
311 \SOUL@flushgrave
312 \ifx\SOUL@@\SOUL@stop
313 \def\SOUL@n*{%
314 \SOUL@doword
315 \SOUL@eventuallyexhyphen\null
316 }%
317 \else\ifx\SOUL@@\par
318 \def\SOUL@n*\par{\par\leavevmode\SOUL@scan}%
319 \else\if\noexpand\SOUL@@\SOUL@spc
320 \SOUL@doword
321 \SOUL@eventuallyexhyphen\null
322 \ifSOUL@ignorespaces
323 \else
324 \SOUL@everyspace{ }%
325 \fi
326 \def\SOUL@n* {\SOUL@scan}%
327 \else\ifx\SOUL@@\%
328 \SOUL@doword
329 \SOUL@eventuallyexhyphen\null
330 \SOUL@everyspace{\unskip\nobreak\hfil\break}%
331 \SOUL@ignorespacestrue
332 \else\ifx\SOUL@@-%
333 \SOUL@doword
334 \SOUL@eventuallyexhyphen\null

```



```

335 \SOUL@everySPACE{\nobreak}%
336 \else\ifx\SOUL@@\slash
337 \SOUL@doword
338 \SOUL@eventuallyexhyphen{/}%
339 \SOUL@exhyphen{/}%
340 \else\ifx\SOUL@@\mbox
341 \def\SOUL@n*{\SOUL@addprotect}%
342 \else\ifx\SOUL@@\hbox
343 \def\SOUL@n*{\SOUL@addprotect}%
344 \else\ifx\SOUL@@\soulomit
345 \def\SOUL@n*\soulomit###1{%
346 \SOUL@doword
347 {\spaceskip\SOUL@spaceskip###1}%
348 \SOUL@scan
349 }%
350 \else\ifx\SOUL@@\break
351 \SOUL@doword
352 \break
353 \else\ifx\SOUL@@\linebreak
354 \SOUL@doword
355 \SOUL@everySPACE{\linebreak}%
356 \else\ifcat\bgroup\noexpand\SOUL@@
357 \def\SOUL@n*{\SOUL@addgroup{}}%
358 \else\ifcat$\noexpand\SOUL@@
359 \def\SOUL@n*{\SOUL@addmath}%
360 \else

```

The current token is examined to detect the start of a UTF-8 sequence.

```

361 \SOuL@analyzeutfviii
362 \ifcase\SOuL@octets
363 \SOuL@analyzeutfviii
364 \fi
365 \ifcase\SOuL@octets
366 \def\SOUL@n*{\SOUL@dotoken}%
367 \or % 1
368 \or % 2
369 \def\SOUL@n*{\SOuL@addtwooctets}%
370 \or % 3
371 \def\SOUL@n*{\SOuL@addthreeoctets}%
372 \or % 4
373 \def\SOUL@n*{\SOuL@addfouroctets}%
374 \fi
375 \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi
376 \fi\fi\fi\fi
377 \SOUL@n*%
378 }

```

## 2.6 UTF-8 analysis

### 2.6.1 Help strings

```

379 \def\SOuL@defsanitizedstring#1#2{%
380 \expandafter\def\csname SOuL@string#1\endcsname{#2}%
381 \expandafter\@onelevel@sanitize\csname SOuL@string#1\endcsname
382 }
383 \SOuL@defsanitizedstring{UTFviii}{UTFviii@}
384 \SOuL@defsanitizedstring{octets}{@octets}
385 \SOuL@defsanitizedstring{two}{two}
386 \SOuL@defsanitizedstring{three}{three}
387 \SOuL@defsanitizedstring{four}{four}
388 \SOuL@defsanitizedstring{macrocolon}{macro:}
389 \SOuL@defsanitizedstring{csnameu}{csname u8-}
390 \SOuL@defsanitizedstring{undeferr}{utf@viii@undeferr}

```

```

391 \def\Soul@stringendash{^^e2^^80^^93}
392 \def\Soul@stringemdash{^^e2^^80^^94}
393 \def\Soul@stringnobreakspace{^^c2^^a0}
394 \edef\Soul@charhash{\string #}
395 \edef\Soul@chartwo{\string 2}
396 \edef\Soul@chartthree{\string 3}
397 \def\Soul@empty{ }

```

## 2.6.2 Support for utf8.def

\Soul@analyzeutfviii

```

398 \begingroup
399 \edef\x{\endgroup
400 \def\noexpand\Soul@analyzeutfviii{%
401 \noexpand\expandafter\noexpand\Soul@checkutfviii
402 \noexpand\meaning\noexpand\Soul@@
403 \Soul@stringUTFviii\Soul@stringoctets
404 \noexpand\@nil
405 }%
406 \def\noexpand\Soul@checkutfviii
407 ##1\Soul@stringUTFviii##2\Soul@stringoctets##3\noexpand\@nil
408 }%
409 \x{%
410 \def\Soul@temp{#2}%
411 \chardef\Soul@octets=%
412 \ifx\Soul@temp\Soul@stringtwo
413 \tw@
414 \else\ifx\Soul@temp\Soul@stringthree
415 \thr@@
416 \else\ifx\Soul@temp\Soul@stringfour
417 4 %
418 \else
419 \z@
420 \fi\fi\fi
421 }

```

## 2.6.3 Support for utf8x.def

\Soul@analyzeutfviiiix

```

422 \begingroup
423 \edef\x{\endgroup
424 \def\noexpand\Soul@analyzeutfviiiix{%
425 \noexpand\expandafter\noexpand\Soul@checkutfviiiix
426 \noexpand\meaning\noexpand\Soul@@
427 \Soul@stringmacrocolon\Soul@charhash1{-}{-}{-}{-}%
428 \Soul@stringcsnameu\Soul@stringundeferr
429 \noexpand\@nil
430 }%

```

\Soul@checkutfviiiix

```

431 \def\noexpand\Soul@checkutfviiiix
432 ##1\Soul@stringmacrocolon\Soul@charhash1##2##3##4##5##6%
433 \Soul@stringcsnameu##7\Soul@stringundeferr##8\noexpand\@nil
434 }%
435 \x{%
436 \def\Soul@temp{#7}%
437 \ifx\Soul@temp\Soul@empty
438 \chardef\Soul@octets=\z@
439 \else
440 \def\Soul@temp{#5}%
441 \ifx\Soul@temp\Soul@chartthree
442 \chardef\Soul@octets=4 %
443 \else

```

```

444 \def\Soul@temp{#3}%
445 \ifx\Soul@temp\Soul@chartwo
446 \chardef\Soul@octets=\thr@@
447 \else
448 \chardef\Soul@octets=\tw@
449 \fi
450 \fi
451 \fi
452 }

```

## 2.7 Actions for UTF-8 sequences

\Soul@addtwooctets

```

453 \def\Soul@addtwooctets#1#2{%
454 \def\Soul@temp{#1#2}%
455 \@onelevel@sanitize\Soul@temp
456 \ifx\Soul@temp\Soul@stringnobreakspace
457 \Soul@doword
458 \Soul@eventuallyexhyphen\null
459 \Soul@everyspace{\nobreak}%
460 \let\Soul@next\Soul@scan
461 \else
462 \def\Soul@next{%
463 ! \Soul@addtoken{\noexpand#1\noexpand#2}}%
464 + \Soul@addtoken{\etex@unexpanded{#1#2}}}%
465 }%
466 \fi
467 \Soul@next
468 }

```

\Soul@addthreeoctets

```

469 \def\Soul@addthreeoctets#1#2#3{%
470 \def\Soul@temp{#1#2#3}%
471 \@onelevel@sanitize\Soul@temp
472 \ifx\Soul@temp\Soul@stringendash
473 \Soul@doword
474 \Soul@eventuallyexhyphen{-}%
475 \Soul@exhyphen{--}%
476 \let\Soul@next\Soul@scan
477 \else
478 \ifx\Soul@temp\Soul@stringemdash
479 \Soul@doword
480 \Soul@eventuallyexhyphen{-}%
481 \Soul@exhyphen{---}%
482 \let\Soul@next\Soul@scan
483 \else
484 \def\Soul@next{%
485 ! \Soul@addtoken{\noexpand#1\noexpand#2\noexpand#3}}%
486 + \Soul@addtoken{\etex@unexpanded{#1#2#3}}}%
487 }%
488 \fi
489 \fi
490 \Soul@next
491 }

```

\Soul@addfouroctets

```

492 \def\Soul@addfouroctets#1#2#3#4{%
493 ! \Soul@addtoken{\noexpand#1\noexpand#2\noexpand#3\noexpand#4}}%
494 + \Soul@addtoken{\etex@unexpanded{#1#2#3#4}}}%
495 }

```

### 2.7.1 Redefinition of \SOUL@splittoken

`\SOUL@splittoken` Macro `\SOUL@splittoken` separates the first token or token group from a word and redefines the word to contain the remaining tokens. However if the remaining tokens are a token group, then the curly braces will be removed and the token group is splitted by the next call of `\SOUL@splittoken`. The redefinition avoids the removal of curly braces around the remaining tokens.

```
496 \SOuL@redefine\SOUL@splittoken#1#2\SOUL@stop{%
497 \global\SOUL@token={#1}%
498 \global\SOUL@word={#2}%
499 }#1{%
500 \global\SOUL@token={#1}%
501 \SOuL@remainingtoken\relax
502 }
```

`\SOuL@remainingtoken`

```
503 \def\SOuL@remainingtoken#1\SOUL@stop{%
504 \global\SOUL@word=\expandafter{\@gobble#1}%
505 }
```

## 2.8 Patches

The fixed `\SOUL@splittoken` allows to remove the double sets of curly braces in other macros of package `soul`. The benefit is that implicate kernings are more often detected and fixes a bug in package `soul`. The disadvantage is incompatibility. The width of the resulting strings may change.

`\SOUL@flushcomma`

```
506 \SOuL@redefine\SOUL@flushcomma{%
507 \ifcase\SOUL@comma
508 \or
509 \edef\x{\SOUL@word={\the\SOUL@word,}}\x
510 \or
511 \edef\x{\SOUL@word={\the\SOUL@word{,,}}}\x
512 \fi
513 \SOUL@comma\z@
514 }{%
515 \ifcase\SOUL@comma
516 \or
517 \edef\x{\SOUL@word={\the\SOUL@word,}}\x
518 \or
519 \edef\x{\SOUL@word={\the\SOUL@word{,,}}}\x
520 \fi
521 \SOUL@comma\z@
522 }
```

`\SOUL@flushapo`

```
523 \SOuL@redefine\SOUL@flushapo{%
524 \ifcase\SOUL@apo
525 \or
526 \edef\x{\SOUL@word={\the\SOUL@word'}}\x
527 \or
528 \edef\x{\SOUL@word={\the\SOUL@word{'}}}\x
529 \fi
530 \SOUL@apo\z@
531 }{%
532 \ifcase\SOUL@apo
533 \or
534 \edef\x{\SOUL@word={\the\SOUL@word'}}\x
535 \or
536 \edef\x{\SOUL@word={\the\SOUL@word{'}}}\x
537 \fi
```

```
538 \SOUL@apo\z@
539 }
```

\SOUL@flushgrave

```
540 \SOuL@redefine\SOUL@flushgrave{%
541 \ifcase\SOUL@grave
542 \or
543 \edef\x{\SOUL@word={\the\SOUL@word`}}\x
544 \or
545 \edef\x{\SOUL@word={\the\SOUL@word{``}}}\x
546 \fi
547 \SOUL@grave\z@
548 }{%
549 \ifcase\SOUL@grave
550 \or
551 \edef\x{\SOUL@word={\the\SOUL@word`}}\x
552 \or
553 \edef\x{\SOUL@word={\the\SOUL@word{``}}}\x
554 \fi
555 \SOUL@grave\z@
556 }
```

\SOUL@addgroup

```
557 \SOuL@redefine\SOUL@addgroup#1#2{%
558 {%
559 \let\protect\noexpand
560 \edef\x{%
561 \global\SOUL@word={%
562 \the\SOUL@word
563 {\noexpand#1#2}}%
564 }%
565 }%
566 \x
567 }%
568 \SOUL@scan
569 }#1#2{%
570 \begingroup
571 \let\protect\noexpand
572 \edef\x{\endgroup
573 \SOUL@word={%
574 \the\SOUL@word
575 ! {\noexpand#1{#2}}%
576 + {\etex@unexpanded{#1{#2}}}%
577 }%
578 }%
579 \x
580 \SOUL@scan
581 }
```

\SOUL@addmath

```
582 \SOuL@redefine\SOUL@addmath$#1${%
583 {%
584 \let\protect\noexpand
585 \edef\x{%
586 \global\SOUL@word={%
587 \the\SOUL@word
588 {\hbox{ $#1$ }}%
589 }%
590 }%
591 \x
592 }%
593 \SOUL@scan
```

```

594 }$#1${%
595 \begingroup
596 \let\protect\noexpand
597 \edef\x{\endgroup
598 \SOUL@word={%
599 \the\SOUL@word
600 ! {\hbox{ $#1$}}%
601 + {\etex@unexpanded{\hbox{ $#1$}}}%
602 }%
603 }%
604 \x
605 \SOUL@scan
606 }

```

\SOUL@addprotect

```

607 \SOuL@redefine\SOUL@addprotect#1#2{%
608 {%
609 \let\protect\noexpand
610 \edef\x{%
611 \global\SOUL@word={%
612 \the\SOUL@word
613 {\hbox{#2}}}%
614 }%
615 }%
616 \x
617 }%
618 \SOUL@scan
619 }#1#2{%
620 \begingroup
621 \let\protect\noexpand
622 \edef\x{\endgroup
623 \SOUL@word={%
624 \the\SOUL@word
625 ! {\hbox{#2}}}%
626 + {\etex@unexpanded{\hbox{#2}}}%
627 }%
628 }%
629 \x
630 \SOUL@scan
631 }

```

\SOUL@addtoken

```

632 + \SOuL@redefine\SOUL@addtoken#1{%
633 + \edef\x{%
634 + \SOUL@word={%
635 + \the\SOUL@word
636 + \noexpand#1%
637 + }%
638 + }%
639 + \x
640 + \SOUL@scan
641 + }#1{%
642 + \edef\x{%
643 + \SOUL@word={%
644 + \the\SOUL@word
645 + \etex@unexpanded{#1}%
646 + }%
647 + }%
648 + \x
649 + \SOUL@scan
650 + }%

651 \SOuL@AtEnd%

```

652  $\langle$ /package $\rangle$

### 3 Test

#### 3.1 Catcode checks for loading

```
653  $\langle$ *test1 $\rangle$ 
654 \catcode`\{=1 %
655 \catcode`\}=2 %
656 \catcode`\#=6 %
657 \catcode`\@=11 %
658 \expandafter\ifx\csname count@\endcsname\relax
659 \countdef\count@=255 %
660 \fi
661 \expandafter\ifx\csname @gobble\endcsname\relax
662 \long\def\@gobble#1{}%
663 \fi
664 \expandafter\ifx\csname @firstofone\endcsname\relax
665 \long\def\@firstofone#1{#1}%
666 \fi
667 \expandafter\ifx\csname loop\endcsname\relax
668 \expandafter\@firstofone
669 \else
670 \expandafter\@gobble
671 \fi
672 {%
673 \def\loop#1\repeat{%
674 \def\body{#1}%
675 \iterate
676 }%
677 \def\iterate{%
678 \body
679 \let\next\iterate
680 \else
681 \let\next\relax
682 \fi
683 \next
684 }%
685 \let\repeat=\fi
686 }%
687 \def\RestoreCatcodes{
688 \count@=0 %
689 \loop
690 \edef\RestoreCatcodes{%
691 \RestoreCatcodes
692 \catcode\the\count@=\the\catcode\count@\relax
693 }%
694 \ifnum\count@<255 %
695 \advance\count@ 1 %
696 \repeat
697
698 \def\RangeCatcodeInvalid#1#2{%
699 \count@=#1\relax
700 \loop
701 \catcode\count@=15 %
702 \ifnum\count@<#2\relax
703 \advance\count@ 1 %
704 \repeat
705 }
706 \def\RangeCatcodeCheck#1#2#3{%
707 \count@=#1\relax
```

```

708 \loop
709   \ifnum#3=\catcode\count@
710   \else
711     \errmessage{%
712       Character \the\count@\space
713       with wrong catcode \the\catcode\count@\space
714       instead of \number#3%
715     }%
716   \fi
717 \ifnum\count@<#2\relax
718   \advance\count@ 1 %
719 \repeat
720 }
721 \def\space{ }
722 \expandafter\ifx\csname LoadCommand\endcsname\relax
723 \def\LoadCommand{\input soulutf8.sty\relax}%
724 \fi
725 \def\Test{%
726   \RangeCatcodeInvalid{0}{47}%
727   \RangeCatcodeInvalid{58}{64}%
728   \RangeCatcodeInvalid{91}{96}%
729   \RangeCatcodeInvalid{123}{255}%
730   \catcode`\@=12 %
731   \catcode`\=0 %
732   \catcode`\%=14 %
733   \LoadCommand
734   \RangeCatcodeCheck{0}{36}{15}%
735   \RangeCatcodeCheck{37}{37}{14}%
736   \RangeCatcodeCheck{38}{47}{15}%
737   \RangeCatcodeCheck{48}{57}{12}%
738   \RangeCatcodeCheck{58}{63}{15}%
739   \RangeCatcodeCheck{64}{64}{12}%
740   \RangeCatcodeCheck{65}{90}{11}%
741   \RangeCatcodeCheck{91}{91}{15}%
742   \RangeCatcodeCheck{92}{92}{0}%
743   \RangeCatcodeCheck{93}{96}{15}%
744   \RangeCatcodeCheck{97}{122}{11}%
745   \RangeCatcodeCheck{123}{255}{15}%
746   \RestoreCatcodes
747 }
748 \Test
749 \csname @@end\endcsname
750 \end
751 </test1>

```

### 3.2 L<sup>A</sup>T<sub>E</sub>X tests

```

752 <*test2 j test3 j test4 j test5>
753 <noetex> \let \SavedUnexpanded\unexpanded
754 <noetex> \let \unexpanded\UNDEFINED
755 \NeedsTeXFormat{LaTeX2e}
756 \documentclass{article}
757 \usepackage[T1]{fontenc}
758 \usepackage{lmodern}
759 \usepackage{textcomp}
760 \usepackage[ngerman]{babel}
761 \expandafter\def\csname ver@hypdestopt.sty\endcsname{}
762 \usepackage[unicode]{hyperref}
763 \usepackage{bookmark}
764 \usepackage{color}
765 \usepackage{soul}[2003/11/17]
766 \makeatletter
767 \newcommand*{\@ifDefined}[1]{%

```



```

768 \@ifundefined{#1}{%
769   \@latex@error{%
770     \expandafter\noexpand\csname#1\endcsname undefined%
771   }\@ehc
772 }%
773 }
774 \newcommand*{\SaveOrg}[1]{%
775   \@ifdefinable{ORG@SOUL@#1}{%
776     \@ifDefined{SOUL@#1}{%
777       \expandafter\let\csname ORG@SOUL@#1\expandafter\endcsname
778         \csname SOUL@#1\endcsname
779     }%
780 }%
781 }
782 \newcommand*{\RestoreOrg}[1]{%
783   \@ifDefined{ORG@SOUL@#1}{%
784     \@ifDefined{SOUL@#1}{%
785       \expandafter\let\csname SOUL@#1\expandafter\endcsname
786         \csname ORG@SOUL@#1\endcsname
787     }%
788 }%
789 }
790 \makeatother
791 \SaveOrg{eval}
792 \SaveOrg{splittoken}
793 \SaveOrg{flushcomma}
794 \SaveOrg{flushapo}
795 \SaveOrg{grave}
796 \SaveOrg{addgroup}
797 \SaveOrg{addmath}
798 \SaveOrg{addprotect}
799 \SaveOrg{addtoken}
800 \usepackage{soulutf8}[2016/05/16]
801 \langle noetex \rangle \let \unexpanded \SavedUnexpanded

```

Input encoding utf8.

```

802 \langle *utf8 \rangle
803 \usepackage[utf8]{inputenc}
804 \DeclareUnicodeCharacter{00A0}{\nobreakspace}
805 \langle /utf8 \rangle

```

Input encoding utf8x. Package ucs has a nasty bug, that it redefines \show.

```

806 \langle *utf8x \rangle
807 \let \origshow \show
808 \usepackage[utf8x]{inputenc}
809 \AtBeginDocument{%
810   \let \show \origshow
811 }
812 \langle /utf8x \rangle

```

### 3.2.1 Driver definitions

```
813 \makeatletter
```

\an The definition for \an is taken from the documentation of package soul.

```

814 \DeclareRobustCommand*{\an}{%
815   \def\SOUL@preamble{${\sim}P}$}%
816   \def\SOUL@everyspace##1{##1\texttt{\char` \ }\linebreak[2]}%
817   \def\SOUL@postamble{${\sim}E}$}%
818   \def\SOUL@everyhyphen${\sim}-}\linebreak[1]}%
819   \def\SOUL@everyexhyphen##1{##1${\sim}=$}$}%
820   \def\SOUL@everysyllable{${\sim}S}$}%
821   \def\SOUL@everytoken{\the\SOUL@token${\sim}T}$}%
822   \def\SOUL@everylowerthan{${\sim}L}$}%
823   \SOUL@

```

824 }

\sy The definition for \sy is taken from the documentation of package soul.

```
825 \DeclareRobustCommand*{\sy}{%
826 \SOUL@setup
827 \def\SOUL@preamble{%
828 \lefthyphenmin=\z@
829 \righthyphenmin=\z@
830 }%
831 \def\SOUL@everyspace##1{##1\space}%
832 \def\SOUL@everysyllable{\the\SOUL@syllable}%
833 \def\SOUL@everyhyphen{%
834 \discretionary{%
835 \SOUL@setkern\SOUL@hyphkern
836 \SOUL@sethyphenchar
837 }{}{%
838 \hbox{\kern1pt$\cdot$}%
839 }%
840 }%
841 \def\SOUL@everyexhyphen##1{%
842 \SOUL@setkern\SOUL@hyphkern
843 \hbox{##1}%
844 \discretionary{}{}{%
845 \SOUL@setkern\SOUL@charkern
846 }%
847 }%
848 \SOUL@
849 }
```

\soulH

```
850 \DeclareRobustCommand*{\soulH}{%
851 \def\SOUL@preamble{%
852 \gdef\SOULH{}%
853 \soulHadd{}}%
854 }%
855 \def\SOUL@everyspace##1{%
856 \soulHadd{Sp}%
857 }%
858 \def\SOUL@postamble{%
859 \soulHadd{}}%
860 }%
861 \def\SOUL@everyhyphen{%
862 \soulHadd{Hy}%
863 }%
864 \def\SOUL@everyexhyphen##1{%
865 \soulHadd{Exhy}%
866 }%
867 \def\SOUL@everysyllable{%
868 \soulHadd{Sy}%
869 }%
870 \def\SOUL@everytoken{%
871 \soulHadd{T}%
872 }%
873 \def\SOUL@everylowerthan{%
874 \soulHadd{<}%
875 }%
876 \SOUL@
877 }
878 \newcommand*{\soulHadd}[1]{%
879 #1%
880 \expandafter\gdef\expandafter\soulHstring\expandafter{%
881 \soulHstring
882 #1%
```

```

883 }%
884 }

```

### 3.2.2 Test macros

```

885 \usepackage{qstest}
886 \IncludeTests{*}
887 \LogTests{log}{*}{*}

888 \newsavebox\boxA
889 \newsavebox\boxB
890 \newsavebox\boxC

\TestDriver

891 \newcommand*\TestDriver[4]{%
892 \subsection{Driver #1}%
893 \@PackageInfo{soulutf8-test}{* Driver #1}%
894 \expandafter\let\expandafter\testdriver\csname #1\endcsname
895 \def\teststringA{#3}%
896 \def\teststringB{#4}%
897 \begin{qstest}{string-#2-driver-#1}{string,#2,driver,#1}%
898 \@PackageInfo{soulutf8-test}{* Version: soulutf8}%
899 \global\let\soulHstring\@empty
900 \setbox0=\hbox{\expandafter\testdriver\expandafter{\teststringA}}%
901 \let\HstringA\soulHstring
902 \SetTestVBox{\boxA}{\teststringA}%
903 %
904 \@PackageInfo{soulutf8-test}{* Version: soul + patch}%
905 \global\let\soulHstring\@empty
906 \RestoreOrg{eval}%
907 \setbox2=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
908 \let\HstringB\soulHstring
909 \SetTestVBox{\boxB}{\teststringB}%
910 %
911 \@PackageInfo{soulutf8-test}{* Version: original soul}%
912 \global\let\soulHstring\@empty
913 \RestoreOrg{splittoken}%
914 \RestoreOrg{flushcomma}%
915 \RestoreOrg{flushapo}%
916 \RestoreOrg{grave}%
917 \RestoreOrg{addgroup}%
918 \RestoreOrg{addmath}%
919 \RestoreOrg{addprotect}%
920 \RestoreOrg{addtoken}%
921 \setbox4=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
922 \let\HstringC\soulHstring
923 \SetTestVBox{\boxC}{\teststringB}%
924 %
925 \TestInfo{0}{soulutf8}%
926 \TestInfo{2}{soul + patch}%
927 \TestInfo{4}{original soul}%
928 \TestInfoVBox
929 \showboxdepth=\maxdimen
930 \showboxbreadth=\maxdimen
931 \tracingonline=\@ne
932 \Expect*{\HstringA}*{\HstringB}%
933 \Expect*{\HstringA}*{\HstringC}%
934 \Expect*{\the\wd0}*{\the\wd2}%
935 \ifdim\wd0=\wd2 %
936 \else
937 \showbox0 %
938 \showbox2 %
939 \fi
940 \Expect*{\the\ht0}*{\the\ht2}%

```

```

941 \Expect*{\the\dp0}*{\the\dp2}%
942 \Expect*{\the\wd\boxB}*{\the\wd\boxA}%
943 \Expect*{\the\wd\boxC}*{\the\wd\boxA}%
944 \Expect*{\the\ht\boxB}*{\the\ht\boxA}%
945 \ifdim\ht\boxB=\ht\boxA
946 \else
947 \showbox\boxA
948 \showbox\boxB
949 \fi
950 \Expect*{\the\ht\boxC}*{\the\ht\boxA}%
951 \Expect*{\the\dp\boxB}*{\the\dp\boxA}%
952 \Expect*{\the\dp\boxC}*{\the\dp\boxA}%
953 \end{qstest}%
954 }

```

#### \SetTestVBox

```

955 \newcommand*{\SetTestVBox}[2]{%
956 \setbox#1=\vbox{%
957 \hsize=0pt\relax
958 \hfuzz=100mm\relax
959 \expandafter\testdriver\expandafter{#2}%
960 }%
961 }

```

#### \TestInfo

```

962 \newcommand*{\TestInfo}[2]{%
963 \par
964 \noindent
965 \copy#1\relax
966 \hfill
967 \begingroup
968 \small
969 \ifdim\wd0=\wd2\relax
970 \ifdim\wd0=\wd4\relax
971 \else
972 \ifnum#1=2 %
973 \raisebox{.5\baselineskip}[0pt][0pt]{%
974 \llap{$\}$}%
975 \rlap{width = \the\wd#1\relax\space$\{ $\}%
976 \phantom{width = 999.99999pt}}%
977 \qqquad
978 }%
979 \else
980 \ifnum#1=4 %
981 \rlap{width = \the\wd#1}%
982 \phantom{width = 999.99999pt}}%
983 \qqquad
984 \fi
985 \fi
986 \fi
987 \else
988 \begingroup
989 \bfseries
990 \rlap{width = \the\wd#1}%
991 \phantom{width = 999.99999pt}}%
992 \endgroup
993 \qqquad
994 \fi
995 \rlap{(#2)}%
996 \phantom{(original soul)}%
997 \endgroup
998 \par
999 }

```

\TestInfoVBox

```
1000 \newcommand*{\TestInfoVBox}{%
1001 \par
1002 \noindent
1003 \mbox{\vrule\relax\space\copy\boxA}%
1004 \ifdim\ht\boxA=\ht\boxB
1005 \else
1006 \hfill
1007 \begingroup
1008 \small
1009 \rlap{(soulutf8)}%
1010 \phantom{(soulutf8)}%
1011 \endgroup
1012 \par
1013 \noindent
1014 \mbox{\vrule\relax\space\copy\boxB}%
1015 \hfill
1016 \begingroup
1017 \small
1018 \rlap{(soul)}%
1019 \phantom{(soulutf8)}%
1020 \endgroup
1021 \fi
1022 \par
1023 }
```

\Test

```
1024 \makeatletter
1025 \newcommand*{\Test}[3]{%
1026 \clearpage
1027 \begingroup
1028 \def\linebreak{\textbackslash linebreak }%
1029 \def\{\textbackslash\textbackslash}%
1030 \def\soulomit###1{%
1031 \textbackslash soulomit\textbraceleft##1\textbraceright
1032 }%
1033 \def\mbox###1{%
1034 \textbackslash mbox\textbraceleft##1\textbraceright
1035 }%
1036 \def\abc{\textbackslash abc }%
1037 \def\texttt###1{%
1038 \textbackslash texttt\textbraceleft##1\textbraceright
1039 }%
1040 \def\c###1{%
1041 \textbackslash c\textbraceleft##1\textbraceright
1042 }%
1043 < *utf8x >
1044 \count@=128 %
1045 \loop
1046 \ifnum\count@<256 %
1047 \lccode`~=\count@
1048 \lowercase{%
1049 \def~{\noexpand~}%
1050 }%
1051 \advance\count@\@ne
1052 \repeat
1053 < /utf8x >
1054 \csname protected@edef@endcsname\x{\endgroup
1055 \noexpand\section{String #1: #2}%
1056 }%
1057 \x
1058 \TestDriver{so}{#1}{#2}{#3}%
```

```

1059 \TestDriver{caps}{#1}{#2}{#3}%
1060 \TestDriver{ul}{#1}{#2}{#3}%
1061 \TestDriver{st}{#1}{#2}{#3}%
1062 \TestDriver{hl}{#1}{#2}{#3}%
1063 \TestDriver{an}{#1}{#2}{#3}%
1064 \TestDriver{sy}{#1}{#2}{#3}%
1065 \TestDriver{soulH}{#1}{#2}{#3}%
1066 }
1067 \makeatother

```

### 3.2.3 Testing

```

1068 \begin{document}
1069 \Test A{}{}%
1070 \Test B{Hello World}{Hello World}%
1071 \Test C{}%
1072 Umlauts: ~c3~84~c3~96~c3~9c~c3~a4~c3~b6~c3~bc~c3~9f%
1073 }{}%
1074 Umlauts: \"A\"O\"U\"a\"o\"u\"ss
1075 }%
1076 \Test D{Euro: ~e2~82~ac}{Euro: \texteuro}%
1077 \Test E{Stra~c3~9fe}{Stra\ss e}%
1078 \Test F{R~c3~b6mer}{R\"omer}%
1079 \Test G{A~e2~80~93B~e2~80~94C}{A--B---C}%
1080 \Test H{X~c2~a0Y}{X~Y}%
1081 \Test I{A~c5~a4}{A\v T}%
1082 \Test J{A,B,,C,,,D,,,,E}{A,B,,C,,,D,,,,E}%
1083 \Test K{A'B''C'''D''''E}{A'B''C'''D''''E}%
1084 \Test L{A`B``C``D````E}{A`B``C``D````E}%
1085 \Test M{A$x$B}{A$x$B}%
1086 \Test N{A\mbox{abc}B}{A\mbox{abc}B}%
1087 \Test O{,,TA''}{,,TA''}%
1088 \Test P{{!`}Hola{?`}}{!`}Hola{?`}}%
1089 \Test Q{re-sent\slash x}{re-sent\slash x}%
1090 \Test R{new\\line}{new\\line}%
1091 \Test S{foo\linebreak bar}{foo\linebreak bar}%
1092 \Test T{Virchow{sche}}{Virchow{sche}}%
1093 \Test U{A\soulomit{foo}B}{A\soulomit{foo}B}%
1094 \Test V{A\texttt{xyz}B}{A\texttt{xyz}B}%
1095 \Test W{\mfm}{\mfm}%
1096 \Test X{f{f}{i}}{f{f}{i}}%
1097 \Test Y{f\mbox{f}\mbox{i}}{f\mbox{f}\mbox{i}}%
1098 \Test Z{\c{a}}{\c{a}}%
1099 <*test2 j test3>
1100 \let\abcx\UNDEFINED
1101 \def\abc{}%
1102 \begingroup
1103 \def\abcx{x}%
1104 \abcx
1105 \endgroup
1106 }%
1107 \Test{AA}{{x\abc x}}{{xxx}}%
1108 </test2 j test3>
1109 \end{document}
1110 </test2 j test3 j test4 j test5>

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

<sup>1</sup><http://ctan.org/pkg/soulutf8>

[CTAN:macros/latex/contrib/oberdiek/soulutf8.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/soulutf8.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

## 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

## 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T<sub>E</sub>X:

```
tex soulutf8.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
soulutf8.sty          → tex/generic/oberdiek/soulutf8.sty
soulutf8.pdf          → doc/latex/oberdiek/soulutf8.pdf
test/soulutf8-test1.tex → doc/latex/oberdiek/test/soulutf8-test1.tex
test/soulutf8-test2.tex → doc/latex/oberdiek/test/soulutf8-test2.tex
test/soulutf8-test3.tex → doc/latex/oberdiek/test/soulutf8-test3.tex
test/soulutf8-test4.tex → doc/latex/oberdiek/test/soulutf8-test4.tex
test/soulutf8-test5.tex → doc/latex/oberdiek/test/soulutf8-test5.tex
soulutf8.dtx          → source/latex/oberdiek/soulutf8.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 4.4 Refresh file name databases

If your T<sub>E</sub>X distribution (teT<sub>E</sub>X, mikT<sub>E</sub>X, ...) relies on file name databases, you must refresh these. For example, teT<sub>E</sub>X users run `texhash` or `mktextlsr`.

## 4.5 Some details for the interested

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The .dtx chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run docstrip and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for docstrip (really, docstrip does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{soulutf8.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
```

## 5 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `soulutf8.xml`.

```
1111 <*catalogue>
1112 <?xml version='1.0' encoding='us-ascii'?>
1113 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
1114 <entry datestamp='$Date$' modifier='$Author$' id='soulutf8'>
1115   <name>soulutf8</name>
1116   <caption>Permit use of UTF-8 characters in soul.</caption>
1117   <authorref id='auth:oberdiek' />
1118   <copyright owner='Heiko Oberdiek' year='2007' />
1119   <license type='lppl1.3' />
1120   <version number='1.1' />
1121   <description>
1122     This package extends package <xref refid='soul'>soul</xref> and adds
1123     some support for UTF-8. Namely the input encodings in
1124     &#x2018;<tt>utf8.def</tt>&#x2019; from package
1125     <xref refid='inputenc'>inputenc</xref> and
1126     &#x2018;<tt>utf8x.def</tt>&#x2019; from package
1127     <xref refid='unicode'>ucs</xref> are supported.
1128   <p />
1129   The package is part of the <xref refid='oberdiek'>oberdiek</xref>
1130   bundle.
1131 </description>
1132 <documentation details='Package documentation'
1133   href='ctan:/macros/latex/contrib/oberdiek/soulutf8.pdf' />
1134 <ctan file='true' path='/macros/latex/contrib/oberdiek/soulutf8.dtx' />
1135 <miktex location='oberdiek' />
1136 <texlive location='oberdiek' />
1137 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
1138 </entry>
1139 </catalogue>
```



## 6 References

- [1] Melchior Franz: *The soul package*; 2003/11/17;  
[CTAN:macros/latex/contrib/soul/](#).
- [2] Dominique P. G. Unruh: *ucs.sty – Unicode Support*; 2004/10/17;  
[CTAN:macros/latex/contrib/unicode/](#).
- [3] Frank Mittelbach, Chris Rowley: *Providing some UTF-8 support via inputenc*;  
2006/03/30;  
[CTAN:macros/latex/base/utf8ienc.dtx](#).

## 7 History

[2007/09/09 v1.0]

- First version.

[2016/05/16 v1.1]

- Documentation updates.

## 8 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols                                   |   |
|---|---|
| <code>\"</code> .....                     | 1074, 1078, 1098  |
| <code>\#</code> .....                     | 656   |
| <code>\%</code> .....                     | 732   |
| <code>\@</code> .....                     | 657, 730  |
| <code>\@PackageError</code> .....         | 148   |
| <code>\@PackageInfo</code> .....          | 893, 898, 904, 911  |
| <code>\@PackageWarningNoLine</code> ..... | 185   |
| <code>\@ehc</code> .....                  | 771   |
| <code>\@empty</code> .....                | 899, 905, 912   |
| <code>\@firstofone</code> .....           | 665, 668  |
| <code>\@gobble</code> .....               | 504, 662, 670   |
| <code>\@ifDefined</code> .....            | 767, 776, 783, 784  |
| <code>\@ifdefinable</code> .....          | 775   |
| <code>\@ifundefined</code> .....          | 768   |
| <code>\@latex@error</code> .....          | 769   |
| <code>\@one</code> .....                  | 215, 217, 219,<br>221, 300, 302, 304, 306, 931, 1051  |
| <code>\@nil</code> .....                  | 404, 407, 429, 433  |
| <code>\@onelevel@sanitize</code> ..       | <u>153</u> , 381, 455, 471  |
| <code>\@undefined</code> .....            | 58, 129   |
| <code>\@</code> .....                     | 242, 327, 731, 1029, 1090   |
| <code>\{</code> .....                     | 654, 975  |
| <code>\}</code> .....                     | 655, 974  |
| <code>\~</code> .....                     | 1047  |
| <code>\_</code> .....                     | 816   |
| A   |   |
| <code>\abc</code> .....                   | 1036, 1101, 1107  |
| <code>\abcx</code> .....                  | 1100, 1103, 1104  |
| <code>\active</code> .....                | 121   |
| <code>\advance</code> ...                 | 215, 217, 219, 221, 300,<br>302, 304, 306, 695, 703, 718, 1051  |
| <code>\afterassignment</code> .....       | 178   |
| <code>\aftergroup</code> .....            | 29  |
| <code>\an</code> .....                    | <u>814</u>  |
| <code>\AtBeginDocument</code> .....       | 809   |
| B   |   |
| <code>\baselineskip</code> .....          | 973   |
| <code>\begin</code> .....                 | 897, 1068   |
| <code>\bfseries</code> .....              | 989   |
| <code>\body</code> .....                  | 674, 678  |
| <code>\boxA</code> .....                  | 888, 902, 942, 943, 944,<br>945, 947, 950, 951, 952, 1003, 1004   |
| <code>\boxB</code> .....                  | 889, 909,<br>942, 944, 945, 948, 951, 1004, 1014  |
| <code>\boxC</code> .....                  | 890, 923, 943, 950, 952   |
| <code>\break</code> .....                 | 245, 265, 267, 330, 350, 352  |
| C   |   |
| <code>\c</code> .....                     | 1040, 1098  |
| <code>\catcode</code> .....               | 2, 3, 5, 6, 7,<br>8, 9, 10, 11, 12, 13, 33, 34, 36,<br>37, 38, 39, 40, 41, 42, 43, 44, 45,<br>46, 47, 48, 49, 69, 70, 72, 73, 74,<br>78, 79, 80, 81, 82, 83, 84, 87, 88,<br>90, 91, 92, 93, 97, 99, 169, 170,<br>172, 173, 654, 655, 656, 657,<br>692, 701, 709, 713, 730, 731, 732 |
| <code>\cdot</code> .....                  | 838   |
| <code>\char</code> .....                  | 816   |

|   |  |   |   |
|---|--|---|---|
| <code>\chardef</code> . . . . .                 | 411, 438, 442, 446, 448  | <code>\ifSOUL@ignorespaces</code> . . . . . | 237, 322  |
| <code>\clearpage</code> . . . . .               | 1026   | <code>\ifx</code> . . . . .                 | 15, 18, 21, 50,<br>58, 61, 129, 130, 153, 182, 210,<br>211, 212, 213, 214, 216, 218,<br>220, 227, 232, 242, 247, 251,<br>255, 257, 259, 265, 268, 295,<br>296, 297, 298, 299, 301, 303,<br>305, 312, 317, 327, 332, 336,<br>340, 342, 344, 350, 353, 412,<br>414, 416, 437, 441, 445, 456,<br>472, 478, 658, 661, 664, 667, 722 |
| <code>\copy</code> . . . . .                    | 965, 1003, 1014  | <code>\immediate</code> . . . . .           | 23, 52  |
| <code>\count@</code> . . . . .                  | 659,<br>688, 692, 694, 695, 699, 701,<br>702, 703, 707, 709, 712, 713,<br>717, 718, 1044, 1046, 1047, 1051             | <code>\IncludeTests</code> . . . . .        | 886   |
| <code>\countdef</code> . . . . .                | 659  | <code>\input</code> . . . . .               | 141, 144, 152, 723  |
| <code>\csname</code> . . . . .                  | 14, 21, 50,<br>66, 76, 130, 153, 380, 381, 658,<br>661, 664, 667, 722, 749, 761,<br>770, 777, 778, 785, 786, 894, 1054 | <code>\iterate</code> . . . . .             | 675, 677, 679   |
| <code>\CurrentOption</code> . . . . .           | 162  |   |   |
| <b>D</b>  |  |   |   |
| <code>\DeclareOption</code> . . . . .           | 133, 138, 162  | <b>K</b>                                    |   |
| <code>\DeclareRobustCommand</code> . . . . .    | 131, 136, 814, 825, 850  | <code>\kern</code> . . . . .                | 838   |
| <code>\DeclareUnicodeCharacter</code> . . . . . | 804  | <b>L</b>                                    |   |
| <code>\discretionary</code> . . . . .           | 834, 844   | <code>\lcode</code> . . . . .               | 1047  |
| <code>\documentclass</code> . . . . .           | 129, 756   | <code>\leavevmode</code> . . . . .          | 233, 318  |
| <code>\dp</code> . . . . .                      | 941, 951, 952  | <code>\lefthyphenmin</code> . . . . .       | 828   |
| <b>E</b>  |  |   |   |
| <code>\empty</code> . . . . .                   | 17, 18   | <code>\linebreak</code> . . . . .           | 268,<br>270, 353, 355, 816, 818, 1028, 1091   |
| <code>\end</code> . . . . .                     | 750, 953, 1109   | <code>\llap</code> . . . . .                | 974   |
| <code>\endcsname</code> . . . . .               | 14, 21, 50,<br>66, 76, 130, 153, 380, 381, 658,<br>661, 664, 667, 722, 749, 761,<br>770, 777, 778, 785, 786, 894, 1054 | <code>\LoadCommand</code> . . . . .         | 723, 733  |
| <code>\endinput</code> . . . . .                | 29, 128  | <code>\LogTests</code> . . . . .            | 887   |
| <code>\endlinechar</code> . . . . .             | 4, 35, 71, 77, 89  | <code>\loop</code> . . . . .                | 673, 689, 700, 708, 1045  |
| <code>\errmessage</code> . . . . .              | 711  | <code>\lowercase</code> . . . . .           | 1048  |
| <code>\etex@unexpanded</code> . . . . .         | 464, 486, 494, 576, 601, 626, 645  | <b>M</b>                                    |   |
| <code>\Expect</code> . . . . .                  | 932, 933, 934, 940,<br>941, 942, 943, 944, 950, 951, 952   | <code>\makeatletter</code> . . . . .        | 766, 813, 1024  |
| <b>G</b>  |  |   |   |
| <code>\gdef</code> . . . . .                    | 852, 880   | <code>\makeatother</code> . . . . .         | 790, 1067   |
| <b>H</b>  |  |   |   |
| <code>\hbox</code> . . . . .                    | 257, 342, 588, 600, 601, 613,<br>625, 626, 838, 843, 900, 907, 921   | <code>\maxdimen</code> . . . . .            | 929, 930  |
| <code>\hfil</code> . . . . .                    | 245, 330   | <code>\mbox</code> . . . . .                | 255,<br>340, 1003, 1014, 1033, 1086, 1097   |
| <code>\hfill</code> . . . . .                   | 966, 1006, 1015  | <code>\meaning</code> . . . . .             | 156, 402, 426   |
| <code>\hfuzz</code> . . . . .                   | 958  | <code>\MessageBreak</code> . . . . .        | 186, 187, 188   |
| <code>\hsize</code> . . . . .                   | 957  | <b>N</b>                                    |   |
| <code>\HstringA</code> . . . . .                | 901, 932, 933  | <code>\NeedsTeXFormat</code> . . . . .      | 755   |
| <code>\HstringB</code> . . . . .                | 908, 932   | <code>\newcommand</code> . . . . .          | 132, 137, 767, 774,<br>782, 878, 891, 955, 962, 1000, 1025  |
| <code>\HstringC</code> . . . . .                | 922, 933   | <code>\newsavebox</code> . . . . .          | 888, 889, 890   |
| <code>\ht</code> . . . . .                      | 940, 944, 945, 950, 1004   | <code>\next</code> . . . . .                | 679, 681, 683   |
| <b>I</b>  |  |   |   |
| <code>\if</code> . . . . .                      | 197, 234, 282, 319   | <code>\nobreak</code> . . . . .             | 245, 250, 330, 335, 459   |
| <code>\ifcase</code> . . . . .                  | 362,<br>365, 507, 515, 524, 532, 541, 549  | <code>\nobreakspace</code> . . . . .        | 804   |
| <code>\ifcat</code> . . . . .                   | 271, 273, 356, 358   | <code>\noindent</code> . . . . .            | 964, 1002, 1013   |
| <code>\ifdim</code> . . . . .                   | 935, 945, 969, 970, 1004   | <code>\null</code> . . . . .                | 230, 236,<br>244, 249, 315, 321, 329, 334, 458  |
| <code>\ifetex@unexpanded</code> . . . . .       | 168  | <code>\number</code> . . . . .              | 714   |
| <code>\ifnum</code> . . . . .                   | 201, 203,<br>205, 207, 286, 288, 290, 292,<br>694, 702, 709, 717, 972, 980, 1046                                       | <b>O</b>                                    |   |
| <b>P</b>  |  |   |   |
| <code>\origshow</code> . . . . .                | 807, 810   | <code>\PackageError</code> . . . . .        | 134, 139, 148   |
| <b>P</b>  |  |   |   |
| <code>\PackageInfo</code> . . . . .             | 26   | <code>\par</code> . . . . .                 | 232, 233,<br>317, 318, 963, 998, 1001, 1012, 1022   |
| <code>\PassOptionsToPackage</code> . . . . .    | 162  | <code>\phantom</code> . . . . .             | 976, 982, 991, 996, 1010, 1019  |

|  |   |   |   |
|--|---|---|---|
| <code>\ProcessOptions</code> .....       | 163   | <code>\SOuL@checkutfviii</code> .....   | 425, <a href="#">431</a>  |
| <code>\protect</code> ...                | 559, 571, 584, 596, 609, 621  | <code>\SOuL@cmd</code> .....  | 177, 182, 184, 193  |
| <code>\ProvidesPackage</code> .....      | 19, 67  | <code>\SOuL@cmdcheck</code> .....   | 178, <a href="#">181</a>  |
| <b>Q</b>                                 |   |   |   |
| <code>\qqquad</code> .....               | 977, 983, 993   | <code>\SOuL@comma</code> .....  | 203,<br>217, 288, 302, 507, 513, 515, 521   |
| <b>R</b>                                 |   |   |   |
| <code>\raisebox</code> .....             | 973   | <code>\SOuL@defsanitizedstring</code>   | 379, 383,<br>384, 385, 386, 387, 388, 389, 390  |
| <code>\RangeCatcodeCheck</code> .....    | 706, 734, 735, 736, 737, 738,<br>739, 740, 741, 742, 743, 744, 745  | <code>\SOuL@dotoken</code> .....  | 276, 366  |
| <code>\RangeCatcodeInvalid</code> .....  | 698, 726, 727, 728, 729   | <code>\SOuL@doword</code> .....   | 229, 235, 243, 248, 252, 261,<br>266, 269, 314, 320, 328, 333,<br>337, 346, 351, 354, 457, 473, 479 |
| <code>\repeat</code> ..                  | 673, 685, 696, 704, 719, 1052   | <code>\SOuL@empty</code> .....  | 397, 437  |
| <code>\RequirePackage</code> .....       | 164, 165, 166   | <code>\SOuL@error</code> .....  | <a href="#">144</a>   |
| <code>\RestoreCatcodes</code> ..         | 687, 690, 691, 746  | <code>\SOuL@eval</code> .....   | <a href="#">195</a>   |
| <code>\RestoreOrg</code> .....           | 782, 906, 913,<br>914, 915, 916, 917, 918, 919, 920   | <code>\SOuL@eventuallyexhyphen</code> .....   | 230, 236, 244, 249, 253, 315,<br>321, 329, 334, 338, 458, 474, 480                                  |
| <code>\righthyphenmin</code> .....       | 829   | <code>\SOuL@everyexhyphen</code> ..   | 819, 841, 864   |
| <code>\rlap</code> ...                   | 975, 981, 990, 995, 1009, 1018  | <code>\SOuL@everyhyphen</code> ....   | 818, 833, 861   |
| <b>S</b>                                 |   |   |   |
| <code>\SavedUnexpanded</code> .....      | 753, 801  | <code>\SOuL@everylowerthan</code> .....   | 822, 873  |
| <code>\SaveOrg</code> .....              | 774, 791, 792,<br>793, 794, 795, 796, 797, 798, 799   | <code>\SOuL@everyspace</code> .....   | 239, 245, 250, 270, 324,<br>330, 335, 355, 459, 816, 831, 855                                       |
| <code>\section</code> .....              | 1055  | <code>\SOuL@everysyllable</code> ....   | 820, 832, 867   |
| <code>\setbox</code> .....               | 900, 907, 921, 956  | <code>\SOuL@everytoken</code> .....   | 821, 870  |
| <code>\SetTestVBox</code> .....          | 902, 909, 923, <a href="#">955</a>  | <code>\SOuL@exhyphen</code> ..  | 254, 339, 475, 481  |
| <code>\show</code> .....                 | 807, 810  | <code>\SOuL@flushapo</code> .....   | 206, 212, 225, 291, 297, 310, <a href="#">523</a>   |
| <code>\showbox</code> .....              | 937, 938, 947, 948  | <code>\SOuL@flushcomma</code> .....   | 204, 211, 224, 289, 296, 309, <a href="#">506</a>   |
| <code>\showboxbreadth</code> .....       | 930   | <code>\SOuL@flushgrave</code> .....   | 208, 213, 226, 293, 298, 311, <a href="#">540</a>   |
| <code>\showboxdepth</code> .....         | 929   | <code>\SOuL@flushminus</code> .....   | 202, 210, 223, 287, 295, 308  |
| <code>\slash</code> .....                | 251, 336, 1089  | <code>\SOuL@grave</code> .....  | 207,<br>221, 292, 306, 541, 547, 549, 555   |
| <code>\small</code> .....                | 968, 1008, 1017   | <code>\SOuL@hyphkern</code> .....   | 835, 842  |
| <code>\SOuL@</code> .....                | 823, 848, 876   | <code>\SOuL@ignorespacesfalse</code> ....   | 199, 284  |
| <code>\SOuL@@</code> .....               | 197, 210, 211,<br>212, 213, 214, 216, 218, 220,<br>227, 232, 234, 242, 247, 251,<br>255, 257, 259, 265, 268, 271,<br>273, 282, 295, 296, 297, 298,<br>299, 301, 303, 305, 312, 317,<br>319, 327, 332, 336, 340, 342,<br>344, 350, 353, 356, 358, 402, 426 | <code>\SOuL@ignorepacestrue</code> .....  | 246, 331  |
| <code>\SOuL@addfouroctets</code> .....   | 373, <a href="#">492</a>  | <code>\SOuL@minus</code> .....  | 201, 215, 286, 300  |
| <code>\SOuL@addgroup</code> .....        | 272, 357, <a href="#">557</a>   | <code>\SOuL@n</code> 196, 228, 233, 241, 256, 258,<br>260, 272, 274, 276, 279, 281,<br>313, 318, 326, 341, 343, 345,<br>357, 359, 366, 369, 371, 373, 377 |   |
| <code>\SOuL@addmath</code> .....         | 274, 359, <a href="#">582</a>   | <code>\SOuL@next</code> .....   | 460, 462, 467, 476, 482, 484, 490   |
| <code>\SOuL@addprotect</code> .....      | 256, 258, 341, 343, <a href="#">607</a>   | <code>\SOuL@octets</code> .....   | 362, 365, 411, 438, 442, 446, 448   |
| <code>\SOuL@addthreeoctets</code> .....  | 371, <a href="#">469</a>  | <code>\SOuL@orgDeclareOption</code> ....  | 133, 138  |
| <code>\SOuL@addtoken</code> .....        | 463, 464, 485, 486, 493, 494, <a href="#">632</a>   | <code>\SOuL@orgDeclareRobustCommand</code>  | 131, 136  |
| <code>\SOuL@addtwooctets</code> .....    | 369, <a href="#">453</a>  | .....   | 132, 137  |
| <code>\SOuL@analyzutfviii</code> .....   | 361, <a href="#">398</a>  | <code>\SOuL@orgPackageError</code> ....   | 134, 139  |
| <code>\SOuL@analyzutfviiiix</code> ..... | 363, <a href="#">422</a>  | <code>\SOuL@orgSOuL@error</code> .....  | 145, 149  |
| <code>\SOuL@apo</code> .....             | 205,<br>219, 290, 304, 524, 530, 532, 538   | <code>\SOuL@postamble</code> .....  | 817, 858  |
| <code>\SOuL@AtEnd</code> .....           | 95, 96, 128, 651  | <code>\SOuL@preamble</code> .....   | 815, 827, 851   |
| <code>\SOuL@charhash</code> .....        | 394, 427, 432   | <code>\SOuL@redefine</code> .....   | <a href="#">175</a> , 195, 496,<br>506, 523, 540, 557, 582, 607, 632                                |
| <code>\SOuL@charkern</code> .....        | 845   | <code>\SOuL@remainingtoken</code> .....   | 501, <a href="#">503</a>  |
| <code>\SOuL@charthree</code> .....       | 396, 441  | <code>\SOuL@restorelatexcmds</code> .....   | 135, <a href="#">142</a>  |
| <code>\SOuL@chartwo</code> .....         | 395, 445  |   |   |
| <code>\SOuL@checkutfviii</code> .....    | 401, 406  |   |   |

