

The packages **svg** and **svg-extract**

Philip Ilten (2012–2016)

Falk Hanisch (2017–)

<https://github.com/mrpiggi/svg>

hanisch.latex@outlook.com

v2.02b (2018/11/12)

The **svg** package is intended for the automated integration of SVG graphics into \LaTeX documents. Therefor the capabilities provided by **Inkscape**—or more precisely its command line tool—are used to export the text within a SVG graphic to a separate file, which is then rendered by \LaTeX . The two commands `\includesvg` and `\includeinkscape` are provided as central user-interface, which are very similar to the `\includegraphics` command of the **graphicx** package.

In addition, the package **svg-extract** allows the extraction of these graphics into independent files in different graphic formats, exactly as it is rendered within the document. For the creation of these graphics in the well-known formats PDF, EPS and PS, \LaTeX and possibly conversion tools shipped with the distribution are used. If the graphics are required in other file formats, either **ImageMagick** or **Ghostscript** can be invoked.

Contents

I.	User documentation	2
1.	Introduction	2
2.	Usage of package <code>svg</code>	3
2.1.	General settings	3
2.2.	Options for the invocation of Inkscape	4
2.3.	Options for the graphic inclusion	5
2.4.	Including SVG files	6
2.5.	Including already exported SVG files	6
3.	Usage of package <code>svg-extract</code>	7
3.1.	General settings	7
3.2.	Extract independent graphic files	8
3.3.	Convert extracted graphic files	10
3.3.1.	Settings for the invocation of ImageMagick	11
3.3.2.	Settings for the invocation of Ghostscript	11
4.	Example	11
5.	Troubleshooting and reporting issues	13
6.	Include SVG files created with <code>ROOT</code>	13
II.	Implementation	16
A.	Initialization	16
A.1.	Packages	16

A.2.	Helper macros	16
B.	Including SVG files with package <code>svg</code>	16
B.1.	Options	16
B.1.1.	The invocation of <i>Inkscape</i>	17
B.1.2.	Setting input folder and file	20
B.1.3.	Setting output folder	21
B.1.4.	Options for the inclusion of graphics	22
B.2.	Handling path information	23
B.3.	Optional Parameters for user commands	30
B.4.	User commands	31
B.5.	Auxiliary macros	34
B.6.	Patches	39
C.	Extracting independent graphic files with <code>svg-extract</code>	40
C.1.	Options	40
C.1.1.	Controlling the extract process	41
C.1.2.	Invoking external application for graphic conversion	45
C.1.3.	Setting output folder	48
C.1.4.	Options for the extraction of graphics	49
C.1.5.	Miscellaneous options	51
C.2.	User commands	52
C.3.	Auxiliary macros	53
C.4.	Commands for the separate auxiliary \LaTeX -file	65
D.	Processing Options	67
E.	Macros for file access	67
	Index	69
	Change History	72

Part I.

User documentation

1. Introduction

The open source program *Inkscape* has provided an excellent resource for the simple and easy creation of images and diagrams using a graphical user interface. The work by Johan B. C. Engelen has further enhanced the ability of *Inkscape* to split a SVG file into a text component that can be compiled with \LaTeX , and an image component that can be imported as a PDF file. For further information see the documentation of [svg-inkscape on CTAN](http://www.ctan.org/pkg/svg-inkscape)¹. The procedure described therein is taken up and consistently expanded. Thus, it is now possible to include a SVG file into a \LaTeX document where the text within the SVG graphic will be rendered natively by \LaTeX .

Both packages `svg` and `svg-extract` rely heavily upon executing commands from the shell using the `\ShellEscape` command—or respectively the old known `\write18`—for executing a variety of commands directly to the system. So it is necessary to include the flag `--shell-escape` when compiling documents using `svg` and/or `svg-extract`. The executed commands and the possibilities to adapt their invocation with the appropriate options are described later on in this documentation. All this is done automatically with the `\includesvg` command. If you don't want to use the `--shell-escape` flag, either for security reasons or because the export of the SVG files is done in another way, there's also the command `\includeinkscape` which includes files already exported by *Inkscape*.

¹<http://www.ctan.org/pkg/svg-inkscape>

An working installation of **Inkscape** is required for the automated integration of SVG graphics, whereby the installation path must be known to the operating system. This can be checked on shell by typing `inkscape -V`. Moreover, there are some required packages which are loaded by packages **svg** and **svg-extract** to provide the functionality. These are:

scrbase for the definition and handling of options in key-value-syntax
ifpdf, ifluatex, ifxetex for flow control depending on the used L^AT_EX engine
pdftexcmds, shellest to allocate the same primitives independent of the used L^AT_EX engine
ifplatform to control the file access depending on the operating system
trimspaces to remove unwanted spaces in file paths
graphicx for including the graphic files after the **Inkscape** export
xcolor,transparent are possibly needed by the separate L^AT_EX files created by **Inkscape**
xr is used by **svg-extract** in order to include labels within the independent graphic files

If you want to pass options to package **graphicx**, you must either load it before package **svg**

```
\usepackage[options]{graphicx}
...
\usepackage[options]{svg}
```

or use `\PassOptionsToPackage`.

```
\PassOptionsToPackage{options}{graphicx}
...
\documentclass[options]{class}
...
\usepackage[options]{svg}
```

The usage of packages **xcolor** and **transparent** can be switched off while loading package **svg**. See the two options `usexcolor` and `usetransparent` below.

2. Usage of package `svg`

The purpose of this package is to include SVG graphics into a L^AT_EX document. The command `\includesvg` is defined which does all necessary steps for this task. It first launches the export of a SVG file to a supported file format with Inkscape, if necessary, and includes the exported graphic file afterwards. The usage and the syntax is quite similar to the command `\includegraphics` from the **graphicx** package. In fact, the inclusion of the exported graphic file is done with `\includegraphics`.

`usexcolor` (opt.) The packages **xcolor** and **transparent** are loaded by default at the end of package **svg**. The listed options are intended to prevent these packages from loading. They are the only options which have to be given while loading the **svg** package. All supported boolean values (`true/on/yes/false/off/no`) can be assigned to `usexcolor` and `usetransparent`, while `noxcolor` and `notransparent` don't accept any value.

`usetransparent` (opt.)

`noxcolor` (opt.)

`notransparent` (opt.)

```
\usepackage[options]{svg}
```

2.1. General settings

`\svgsetup` All other options described in detail below can also be changed after loading the package either in the preamble or within the document. They don't have to be given as optional argument to `\usepackage[options]{svg}` but can be set by using macro `\svgsetup{options}` where `{options}` is a comma separated list of options. Settings with `\svgsetup` are done in the current scope which means globally or within the current group.

```
\svgsetup{options}
```

Further, it's possible to reset any setting locally with the optional argument of the commands `\includesvg[options]{svg filename}` or `\includesvg[options]{graphic filename}`.

`\svgpath` Most likely you want to organize your SVG files in a separate folder either as a subfolder in the working directory or elsewhere in your local folder structure. For this purpose, a list of root paths to SVG files can be specified using the `\svgpath` command in the same way as `\graphicspath` is used. Every path has to be given in a group of braces `{}`—even if there is only one—and terminate with `/` last. For example:

```
\svgpath{{svg/}{/usr/local/svg/}}
```

would cause the system to look first in the subdirectory `svg/` and afterwards in the absolute path `/usr/local/svg/`. Further, if no path was specified with `\svgpath` or the desired file wasn't found, all directories given with `\graphicspath` are searched too. Please keep in mind that the current working directory is browsed first in any case. It's recommended to avoid any spaces and/or quotes respectively `\dq` both in paths and file names, especially when DVI output is active.

2.2. Options for the invocation of *Inkscape*

`inkscape` (opt.) This option controls, when the export with *Inkscape* is invoked and is `true` by default.

`false/off/no`

Inkscape won't be invoked in any case, no export is done.

`true/on/yes/newer/onlynewer`

The export with *Inkscape* will only be done, if the exported graphic file either does not exist or the file modification date of the SVG file is newer than that of the exported graphic file. Thus the compilation time of the \LaTeX document can be reduced to the necessary minimum. Unfortunately a primitive like `\pdffilemoddate` is missing for XeTeX, so with this engine, the behaviour will be the same as `inkscape=forced`.

`forced/force/overwrite`

The *Inkscape* export will definitely be done, any already existing exported file will be overwritten regardlessly.

In addition to controlling the export behavior, the option `inkscape` can also be used to make additional settings, which then acts as a wrapper for the options described below.

`pdf/eps/ps/png`

see `inkscapeformat=pdf/eps/ps/png`

`latex/nolatem`

see `inkscapelatem=true/false`

`drawing/page`

see `inkscapearea=drawing/page`

`<integer>dpi`

see `inkscapedpi=<integer>`

`inkscapepath` (opt.) The option `inkscapepath` specifies, where the resulting files of the *Inkscape* export should be located. The subfolder `./svg-inkscape/` within the current working directory is used by default (`inkscapepath=basesubdir`).

`svgdir/svgpath`

The PDF/EPS/PS/PNG graphic files as well as the \LaTeX files generated by *Inkscape* will be located in the same directory as the corresponding SVG file.

`svgsubdir/svgsubpath`

Within the folder of the encountered SVG file, all exported files will be located in a subfolder named `svg-inkscape/`.

`basedir/basepath/jobdir/jobpath`

All exported files will be located in the current working directory.

`basesubdir/basesubpath/jobsubdir/jobsubpath`

A subfolder named `svg-inkscape/` within the current working directory will be used for files generated by *Inkscape*.

`/path/to/somewhere/`

It is also possible to give a custom path, either relative to the current working directory (`./relative/path/`) or as an absolute path.

- `inkscapefilename` (opt.) The file names of the **Inkscape** export are derived from the name of the base SVG file and can be modified with `inkscapefilename=<filename>`. It's possible to use counters for specifying the name of the exported file. Repeatedly specifying the same file name will overwrite previously created files.
- `inkscapeexe` (opt.) For including a SVG file, **Inkscape** is used to separate the text and image from the SVG file itself. In order to execute the command line tool from shell, the path where the executable is located has to be known to the operating system. You can check this by typing `inkscape -V` into the shell. If this check fails and you don't want to change environment variable `path` on your OS, you can use option `inkscapeexe` to set the absolute path where the executable of **Inkscape** is located. The option is set to `inkscapeexe=inkscape` by default.
- `inkscapeformat` (opt.) With this option, the **Inkscape** export format can be controlled. Valid values are `pdf`, `eps`, `ps` and `png`, where a \LaTeX export is not possible for `png` and option `inkscapelatex` won't have any effect. By default, `inkscapeformat=pdf` is set unless DVI output was detected. In this case `inkscapeformat=eps` is the default setting.
- `inkscapelatex` (opt.) If option `inkscapelatex=true` is set, the output is split into a separate PDF/EPS/PS file (see option `inkscapeformat`) and a corresponding \LaTeX file. This is the default setting. Setting `inkscapelatex=false` will result in a single PDF/EPS/PS file, where any contained text won't be rendered by \LaTeX .
- `inkscapearea` (opt.) This option controls which area of the SVG file should be exported, `drawing` is set by default.
- drawing/crop**
The area exported corresponds to the bounding box of all objects in a drawing, including any that are not on the page.
- page/nocrop**
The area exported will correspond to the defined page area within the SVG file.
- `inkscaledpi` (opt.) The resolution used either for PNG export or for fallback rasterization of filtered objects when exporting to PDF/EPS/PS file. For PNG export it is set to 300 dpi by default, if no value was given. The given value should be a positive integer. The default behaviour can be reversed after a given value with `inkscaledpi=\relax`.
- `inkscapeopt` (opt.) You can use this option to pass additional switches to the **Inkscape** command line tool. For further information see the documentation of **Inkscape**².
- `svgextension` (opt.) The package assumes SVG files with `.svg` extension as source for the **Inkscape** export. This option can be used to change this behaviour. For example, in order to process `.dia` files instead of `.svg` you could use

```
\includesvg[svgextension=dia,<additional options>]{<filename>}
```

2.3. Options for the graphic inclusion

- `width` (opt.) The width of the included graphic file can be specified via the `width` option and the height
- `height` (opt.) by the `height` option. If both the width and height are specified, the figure will be scaled
- `distort` (opt.) such that neither of the specified dimensions is exceeded, unless option `distort=true` is
- `scale` (opt.) given.³ If `width` and/or `height` once have been set, this can be undone by setting them to `Opt` or `\relax`. If neither `width` nor `height` are set, the included graphic file can also be scaled by setting `scale` to a positive real number.
- `pretex` (opt.) Commands prior and post to the inclusion of the graphic file may be desired, such as font or
- `aptex` (opt.) color commands. The options `pretex` and `aptex` are provided where the \LaTeX code given to `pretex` is included before the graphic file and `aptex` right afterwards. For example, to change the size of the included text one could use:

```
\includesvg[pretex=\tiny,<additional options>]{<svg filename>}
```

²<https://inkscape.org/de/doc/inkscape-man.html>

³to provide compatibility for package `graphicx`, it's possible to use `keepaspectratio=true` as alias for `distort=false` and the other way round

- `draft` (opt.) This option can be used with boolean values and is equal to the identically named option of the **graphicx** package. If the `draft` option is given to **graphicx**, it's activated for **svg** as well.
- `lastpage` (opt.) A [bug](#)⁴ concerning the L^AT_EX export has been reported for **Inkscape** 0.91. It may happen that within the exported L^AT_EX file, it's attempted to include more pages of the PDF graphics than actually exist. The **svg** package attempts to bypass the resulting error.

Consequently, the total number of pages is read and only existing PDF pages are included, if both options `inkscapeformat=pdf` and `lastpage=true` are set. This is the default setting and can be switched off with `lastpage=false`. It's also possible to set the number of the last page included of a PDF graphic manually as optional parameter for `\includesvg` or `\includeinkscape`. For details, see the description of the respective commands.

2.4. Including SVG files

- `\includesvg` The command `\includesvg` to include a SVG file is quite similar to the `\includegraphics` command provided by the **graphicx** package.

```
\includesvg[parameters]{svg filename}
```

- `inkscape` (param.) It is used right in the same way but where `{svg filename}` is the file name of the SVG file, where any given file extension will be replaced with `.svg` ruthlessly. In order to change the source file format for the **Inkscape** export, you have to use parameter `svgextension`.
- `inkscapeformat` (param.)
- `inkscapecatex` (param.)
- `inkscapearea` (param.) If the given file is not located in the current working directory but elsewhere on your file system, the command `\svgpath` could be used to specify this path. It is recommended to avoid any spaces and/or quotes respectively `\dq` both in paths and file names. Especially when DVI output is active using quotes will certainly cause an error.
- `inkscapecdpi` (param.)
- `inkscapeopt` (param.)
- `svgextension` (param.)
- `width` (param.)
- `height` (param.)
- `distort` (param.) The command `\includesvg` is intended to do an automated export with **Inkscape** at first, where the given SVG file is exported to a PDF/EPS/PS/PNG file (see `inkscapeformat`) and perhaps a correlating L^AT_EX file (see `inkscapecatex`). The export with **Inkscape** is only invoked, if the SVG file is newer than the exported graphic file or latter doesn't exist at all.⁵ Once the export has been done, the graphic file and maybe the L^AT_EX file are included.
- `scale` (param.)
- `pretex` (param.)
- `apptex` (param.)
- `draft` (param.) All previously described options can also be used as optional parameters to `\includesvg` and do have the same effect as described before. However, the optional parameters specified have an effect only once when `\includesvg` is executed and remain unchanged afterwards.
- `lastpage` (param.) In addition to the use of boolean values, the parameter `lastpage` can also be assigned a specific (integer) page number, which defines the last used page of a PDF graphic. This, just like the identically named option, has an effect only when `inkscapeformat=pdf` is set.
- `angle` (param.) Both parameters correlate to the identically named parameters of the `\includegraphics` command provided by the **graphicx** package. However, unlike to `\includegraphics`, they `angle` and `origin` are *always evaluated after width, height, distort and scale* by `\includesvg`, regardless of the used order of the given parameters. This is mainly due to the inclusion of the L^AT_EX files corresponding to the graphic files generated by **Inkscape**.
- `origin` (param.)

2.5. Including already exported SVG files

- `\includeinkscape` If you don't want to make use of the automated export with **Inkscape** but the user interface provided by the **svg** package, you can use `\includeinkscape` instead of `\includesvg`.

```
\includeinkscape[parameters]{graphic filename}
```

⁴<https://bugs.launchpad.net/ubuntu/+source/inkscape/+bug/1417470>

⁵Due to the lack of XeTeX to compare file modification dates, using this L^AT_EX engine leads to **Inkscape** exports with every run unless `inkscape=false` is used.

<code>inkscapeformat</code> (param.)	You can use it similar to <code>\includesvg</code> but <code>{\langle graphic filename \rangle}</code> has to be the filename
<code>inksapelatex</code> (param.)	of the already exported graphic file. If a valid file extension (<code>.pdf/.eps/.ps/.png</code>) is
<code>width</code> (param.)	given, the current setting for <code>inkscapeformat</code> is overwritten. It's even possible to specify a
<code>height</code> (param.)	file extension like <code>.pdf_tex</code> to activate <code>inksapelatex</code> . Furthermore, all optional parameters
<code>distort</code> (param.)	for <code>\includeinkscape</code> do have the same effect as described before for command <code>\includesvg</code>
<code>scale</code> (param.)	once when <code>\includeinkscape</code> is executed and remain unchanged afterwards.
<code>pretex</code> (param.)	
<code>apptex</code> (param.)	
<code>draft</code> (param.)	
<code>lastpage</code> (param.)	
<code>angle</code> (param.)	
<code>origin</code> (param.)	

3. Usage of package `svg-extract`

This package allows the extraction of independent graphic files out of SVG files which have been included and rendered with L^AT_EX by the `svg` package. This is particularly useful when attempting to provide images to journals or collaborators, and one wishes the image to appear exactly as it does within the original L^AT_EX document.

In order to extract to PDF, EPS, or PS files the programs `pstoeps`, `pstopdf` and `pdftops` are used which are usually provided by most of the L^AT_EX 2_ε distributions. In addition, the command line tools of *ImageMagick* and *Ghostscript* can be invoked for converting images in formats like PNG, JPG, TIF or something else. It's also possible to create PDF, EPS or PS files with one of the two programs. Therefor the desired program—`magick` and/or `gswin32c/gswin64c` on Windows respectively `convert` and/or `gs` on unix-like operating systems—must be installed. By typing `\langle program \rangle --version` on shell, this can be checked.

If you want to extract independent graphic files from included SVG files, you only have to load `svg-extract`. All actions for the extraction process will be done by using `\includesvg` or `\includeinkscape`. Without any additional settings, the extraction will render the SVG file to the specified output formats(s) of choice using the same settings as specified within the two commands. Consequently, the scale between the image and text in the extracted files will remain identical to the scale within the document from which the SVG file was extracted.

In contrast to package `svg`, the console commands for graphic extraction are executed with each LaTeX run by package `svg-extract` when `--shell-escape` mode is activated. This behaviour can be switched of with option `extract=false`.

Important changes

In version v1.0 of package `svg` the extracted files were named like the numbering of the current `subfig` environment by default. As package `subfig` sometime causes problems and because of the large amount of different L^AT_EX packages which all provide the possibility to include subfigures with very different implemetations, this feature can't be provided reliably by `svg-extract`. See option `extractname` for further information.

3.1. General settings

<code>on</code> (opt.)	This options have to be given while loading the <code>svg-extract</code> package and are intended to
<code>off</code> (opt.)	toggle the functionality of this package. As both extracting and converting independent
	graphic files is invoked with every L ^A T _E X run when <code>--shell-escape</code> is activated, the option
	<code>off</code> can be given to save compilation time, once the creation of all desired images has been
	done and they no longer need to be re-generated. The option <code>on</code> can be used to reactivate
	functionality of this package. This can also be done by using <code>extract=true/false</code> .
<code>\svgsetup</code>	With package <code>svg-extract</code> the applicable options for <code>\svgsetup{\langle options \rangle}</code> as well as pa-
<code>\includesvg</code>	rameters for the already described macros <code>\includesvg[\langle parameters \rangle]{\langle filename \rangle}</code> and
<code>\includeinkscape</code>	<code>\includeinkscape[\langle parameters \rangle]{\langle filename \rangle}</code> are extended. They can be used to control
	the process of graphic extraction and converting.
<code>extractangle</code> (param.)	With this parameter the graphic is rotated during the extraction process. The value is not
	inherited from <code>angle</code> if it was given by default. this can be achieved by setting:

```
\includesvg[angle=\langle angle \rangle,extractangle=inherit]{\langle filename \rangle}
```

All option described below can be used together with `\svgsetup` and are then valid in the current scope. There also exist identically named parameters for the optional arguments of

```
\includesvg[parameters]{svg filename}
\includeinkscape[parameters]{graphic filename}
```

These parameters have an effect only once when the specific command is executed and remain unchanged afterwards. These parameters are: `extract`, `extractpreamble`, `extractformat`, `extractruns`, `latexopt`, `extractwidth`, `extractheight`, `extractdistort`, `extractscale`, `extractangle`, `extractpretex`, `extractapptex`, `convert`, `convertformat`, `convertdpi`, `magicksetting`, `magickoperator`, `gsopt`, `gsdevice`, `clean`, `exclude`.

3.2. Extract independent graphic files

- `extract` (opt.) This option can be used with boolean values. Using `extract=true` activates the functionality for both extracting and converting which is the default setting, whereas `extract=false` turns it off completely.
- `extractpath` (opt.) The path where the extracted and converted files are located can be specified with option `extractpath`, whereas `extractpath=basesubdir` is set by default.
- `svgdir/svgpath`
The extracted and converted independent graphic files are located in the same directory as the corresponding SVG file.
- `svgsubdir/svgsubpath`
Within the folder of the encountered SVG file, all extracted and converted files will be located in a subfolder named `svg-extract/`.
- `basedir/basepath/jobdir/jobpath`
All extracted and converted files will be located in the current working directory.
- `basesubdir/basesubpath/jobsubdir/jobsubpath`
A subfolder named `svg-extract/` within the current working directory will be used for all extracted and converted files.
- `/path/to/somewhere/`
It is also possible to give a custom path, either relative to the current working directory (`./relative/path/`) or as an absolute path.
- `extractname` (opt.) It's also possible to change the name for extracted and converted files. The default setting is `extractname=filenamenumbered`.
- `filename/name`
The name of the exported **Inkscape** file is used and the suffix `-extract` is attached.
- `filenamenumbered/namenumbered/numberedfilename/numberedname`
Same as above, but a prefix with the count of extracted files is used instead of the suffix.
- `numbered/section/numberedsection/sectionnumbered`
The file name is composed by the number of extracted files and the current outline numbering.
- `{filename}`
You can use any file name, the file extension is derived from option `extractformat`. It's possible to use counters for specifying the name of the extracted file. Repeatedly specifying the same file name will overwrite previously created files.
- `extractformat` (opt.) The included SVG file can be extracted from the document into a independent graphic file of type PDF, EPS or PS. The option can be used with either a single value (`extractformat=pdf`) or a comma separated list. For example,

```
\includesvg[extractformat={pdf,eps,ps}]{svg filename}
```

will extract the SVG file to both PDF and EPS formats and generates two independent graphic files. By default, `extractformat=pdf` is set unless DVI output was detected. In this case `extractformat=eps` is the default setting.

<code>extractwidth</code> (opt.) <code>extractheight</code> (opt.) <code>extractdistort</code> (opt.) <code>extractscale</code> (opt.) <code>extractpretex</code> (opt.) <code>extractapptex</code> (opt.)	<p>These options can be used to overwrite the settings given for the appearance of a SVG file within the document. For example, a SVG file should cover the entire text width within the document but be extracted to a fixed width, this can be done with:</p> <div style="border: 1px solid black; padding: 5px; background-color: #ffffcc; margin: 10px 0;"> <pre style="margin: 0;">\includesvg[width=\textwidth,extractwidth=500pt]{<svg filename>}</pre> </div> <p>Assigning the value <code>inherit</code> to one of these options—which is set by default—leads to the usage of the corresponding option of package <code>svg</code> (<code>width/height/scale/pretex/apptex</code>), whereas <code>extract...=\relax</code> can be used to ignore a parent option utterly. Only option <code>extractdistort</code> is initialized to <code>false</code> and does not inherit from <code>distort</code> by default.</p>
<code>extractpreamble</code> (opt.) <code>extractpreambleend</code> (opt.)	<p>Within the included and extracted SVG files any L^AT_EX macro can be used either defined by the user—this should be done in the preamble of the L^AT_EX document in which the SVG file is to be included—or provided by a package which is loaded. As the extraction process of the SVG files needs an auxiliary L^AT_EX file all used packages and commands have to be known within this file. Consequently, the preamble of the current L^AT_EX document is used for the extraction of the SVG file by default.</p> <p>However, it is possible to specify a different <i>preamble file</i> with the option <code>extractpreamble</code> where the file to use as the preamble is given as the argument—including maybe path, but file name and file extension in any case. The given preamble file is searched similar to SVG files meaning, every path given with <code>\svgpath</code> or <code>\graphicspath</code> is examined. The default definition of <code>extractpreamble</code> is <code>\jobname.tex</code>—more precisely the file extension given by option <code>latexext</code> is used—and should suffice for most cases. The preamble up to the line defined by the option <code>extractpreambleend</code> will be used, which is set to a default with <code>\begin{document}</code>.</p>
<code>\svghidepreamblestart</code> <code>\svghidepreambleend</code>	<p>In case, the preamble of the current L^AT_EX document is used, there are maybe packages included or some parts within the preamble, which should not be used within the separate auxiliary L^AT_EX file. These parts can be excluded if they are enclosed by <code>\svghidepreamblestart</code> and <code>\svghidepreambleend</code>.</p> <p>For example, your current L^AT_EX document uses package <code>showframe</code> which causes some problems with the extraction of independent graphic files. So you want to get rid of it within the auxiliary L^AT_EX file. This can be done with:</p> <div style="border: 1px solid black; padding: 5px; background-color: #ffffcc; margin: 10px 0;"> <pre style="margin: 0;">\documentclass{<documentclassname>} ... \usepackage{svg-extract} ... \svghidepreamblestart \usepackage{showframe} \svghidepreambleend ...</pre> </div>
<code>extractruns</code> (opt.)	<p>When extracting independent graphic files by compiling the generated auxiliary L^AT_EX file, it's maybe necessary to do multiple L^AT_EX runs on this file. The number of runs can be controlled with option <code>extractruns</code>. It's set to <code>extractruns=2</code> by default.</p>
<code>latexexe</code> (opt.) <code>latexopt</code> (opt.) <code>latexext</code> (opt.)	<p>For the extraction of an independent graphic file, the L^AT_EX program is used which is set by the <code>latexexe</code> option. Depending on the L^AT_EX processor used for the current L^AT_EX document, it is set to either <code>pdflatex</code>, <code>lualatex</code>, <code>xelatex</code> or <code>latex</code> by default. It's also possible to specify additional flags or switches for the L^AT_EX runs, which are performed during the extraction process by the <code>latexopt</code> option. If you are used to utilize a other file extension for L^AT_EX files than <code>.tex</code>, option <code>latexext</code> can be used like <code>latexext=ltx</code>.</p>
<code>dvipsopt</code> (opt.) <code>pstoeps</code> (opt.) <code>pstopdf</code> (opt.) <code>pdftoeps</code> (opt.) <code>pdftops</code> (opt.)	<p>Depending on the used L^AT_EX processor, the file type of the extracted graphic differs. In order to create all formats, requested with option <code>extractformat</code>, several converting tools provided by most of the L^AT_EX 2_ε distributions are maybe invoked. These are <code>dvips</code>, <code>ps2eps</code>, <code>ps2pdf</code> and/or <code>pdftops</code> and can't be changed. It's only possible to specify additional switches for every single tool with <code>dvipsopt</code>, <code>pstoeps</code>, <code>pstopdf</code>, <code>pdftoeps</code> and <code>pdftops</code>.</p>
<code>clean</code> (opt.)	<p>During the extraction process many files are generated for each SVG file extraction. So it's oftentimes desirable to automatically remove these temporary files. Using the option <code>clean=true</code> will remove any generated files created other than the extracted output format(s)</p>

requested. Setting `clean=false` is useful for debugging and set by default. Additionally, it's possible to use option `clean` with a list of file extensions in order to specify auxiliary files generated by package **svg-extract** to be deleted, for example `clean={log,aux}`.

`exclude` (opt.) Sometimes it may be necessary to extract and/or convert a SVG file without including it. If the flag `exclude` is specified, the SVG file will not be rendered in the current L^AT_EX document, but will be extracted and/or converted to the requested output format(s).

3.3. Convert extracted graphic files

Based on the extraction of independent graphic files, the **svg-extract** packages also provides the possibility to convert those extracted graphics in another format than PDF, EPS or PS with either **ImageMagick**—which is set by default—or **Ghostscript**.

`convert` (opt.) This option can be used to control the invocation of the conversion process. By default, `convert=false` is set. For Windows, there exist two different versions of **Ghostscript**, either 64 bit or 32 bit. If it is selected as converting tool the 64 bit executable is set by default.

`false/off/no`

No conversion is done.

`true/on/yes`

The conversion will be done with the current chosen converting tool.

`magick/imagemagick/convert`

The conversion is activated and **ImageMagick** is selected.

`gs/ghostscript`

The conversion is activated and **Ghostscript** is selected.

`gs64/ghostscript64`

This value activates **Ghostscript** as conversion tool and sets `gsex=gswin64c`. On unix-like operating systems, the value for `gsex` remains unchanged.

`gs32/ghostscript32`

The same as for the latter case applies, only option `gsex=gswin32c` is set on Windows.

`convertformat` (opt.) With this option, the desired output format(s) can be given. Multiple graphic formats can be specified in a list, for example something like `convertformat={png,jpg,tif}`. The value specified in `extractformat` is used as the source format for the conversion. If `extractformat` itself contains a file list, the first value within this list is considered. If `extractformat` is defined empty, the file generated anyway during the extraction is used.

Settings for specific converting formats

Maybe it's desired to apply varying settings for different output formats. Therefor some options described below can either be set for all converted files or for a specific output format. In particular, these are the options `convertdpi` as well as `magicksetting`, `magickoperator`, `gsdevice` and `gsopt`. All these mentioned options can be used like either $\langle option \rangle = \langle value \rangle$ or $\langle option \rangle = \{ \langle outputformat \rangle = \langle value \rangle \}$ and even $\langle option \rangle = \{ \langle outputformat \rangle += \langle value \rangle \}$ where the desired output format is trailed with + as inner key.

The first variant is applied to all output formats in general. If one of these mentioned options is evaluated and a output format specific value was given like in the second variant, the general setting is overwritten. If the general setting should be used and extended by an additional output format specific settings, then the third variant is to be used. In this case, no output format specific setting (second variant) must not have been used.

If you want to reverse any setting, you only have to use `\relax` as a value, either for a general option ($\langle option \rangle = \backslash relax$) or a specific one ($\langle option \rangle = \{ \langle outputformat \rangle [+]= \backslash relax \}$).

`convertdpi` (opt.) This option controls the used density for all file formats or a specific one, whether **ImageMagick** or **Ghostscript** is used for the graphic conversion. The desired resolution of the converted file is given in dots per inch (DPI) either as a scalar value (e.g. `convertdpi=600`) or with different resolutions in x- and y-direction (e.g. `convertdpi=600x400`).

As described before, it's also possible to declare a specific resolution for each desired converting format. For example, you want to set different resolution for PNG and JPG formats and something for all other formats:

```
\svgsetup{%
  convertdpi={png=600},%
  convertdpi={jpg=150},%
  convertdpi=300%
}%
```

If a setting for a specific output format is given, any unspecific setting is overwritten, when the conversion to this format is done. With `convertdpi={output format}=relax}` a specific setting can be reversed.

Please note that not every graphic format support different resolutions in x- and y-direction. So using a value like `convertdpi=600x400` may not necessarily lead to the desired result. However, this is then due to the used conversion tool and not to the processing of the option.

3.3.1. Settings for the invocation of *ImageMagick*

`magickexe` (opt.) The conversion with *ImageMagick* via the `magick` or `convert` command-line tool can be controlled with these options. The option `magickexe` determines the used executable and is set to `magick` on Windows and otherwise to `convert` by default. Additionally, there are the two options `magicksetting` and `magickoperator` which can be used to define *settings* and *operators* for the conversion process. As described before, the two options `magicksetting` and `magickoperator` can be set for all output formats or a *specific* one either resetting or extending the general settings. For further information see the documentation of *ImageMagick command-line tool*⁶.

`magicksetting` (opt.)

`magickoperator` (opt.)

3.3.2. Settings for the invocation of *Ghostscript*

`gsexe` (opt.) The conversion with *Ghostscript* is done with command-line tool `gs` on unix-like operating systems and `gswin64c` or `gswin32c` on Windows. The executable can be changed with option `gsexe`. Because *Ghostscript* requires the specification of a device, there are some predefined for the most common output formats. These are:

`gsdevice` (opt.)

`gsopt` (opt.)

```
\svgsetup{%
  gsdevice={png=png16m},gsdevice={jpeg=jpeg},gsdevice={jpg=jpeg},%
  gsdevice={tif=tiff48nc},gsdevice={tiff=tiff48nc},%
  gsdevice={eps=eps2write},gsdevice={ps=ps2write}%
}%
```

Furthermore, with `gsopt` additional switches for *Ghostscript* can be set. As described before, both `gsdevice` and `gsopt` can be defined in general or for specific output formats. For further information see the documentation of *Ghostscript*⁷.

4. Example


As an minimal example⁸ take the following lines of code:

```
\documentclass{article}
\usepackage[T1]{fontenc}
\usepackage{svg}
\usepackage[off]{svg-extract}
\svgsetup{clean=true}
%\pdfsuppresswarningpagegroup=1
\usepackage{relsize}
```

⁶<http://www.imagemagick.org/script/command-line-processing.php>

⁷<https://ghostscript.com/doc/current/Use.htm>

⁸The image used here is a slightly modified version of the image used in the initial documentation on how to include a SVG file in L^AT_EX by Johan B. C. Engelen available as package `svg-inkscape` on CTAN.



(a) This text is too large!

(b) This text fits better.

Figure 1: An example figure with \LaTeX support




Figure 2: The same example figure without \LaTeX support

```

\usepackage{subcaption}
\begin{document}
\begin{figure}
\begin{minipage}{.5\linewidth}
\includesvg[width=\linewidth]{svg-example}%
\subcaption{This text is too large!}
\end{minipage}%
\begin{minipage}{.5\linewidth}
\includesvg[width=\linewidth,pretex=\relscale{0.6}]{svg-example}%
\subcaption{This text fits better.}
\end{minipage}
\caption{An example figure with \LaTeX-support}\label{fig:example}
\end{figure}
\begin{figure}\centering
\includesvg[%
width=.5\linewidth,inkscapelatex=false,extractformat={pdf,eps}%
]{svg-example}%
\caption{The same example figure without \LaTeX-support}
\end{figure}
\end{document}

```

If you are willing to compile the example, there are two aspects to consider. First, the included SVG file `svg-example.svg` has to be located in the current folder and is located in `(texmf)/doc/latex/svg/examples/`. Second, you have to run the desired \LaTeX engine with `--shell-escape` option enabled.

The output is shown in [Figure 1](#) and [Figure 2](#). Within this example the file `svg-example.svg` was included three times using the `\includesvg` command.

As you can see, [Figure 1a](#) is created with default settings, except for the width specification.

So the **Inkscape** export with L^AT_EX support is done as well as the extraction of a independent graphic file in PDF format as the **svg-extract** package was loaded.

However, the text is slightly overrunning the margins of the image, and so [Figure 1b](#)—which again uses the same **Inkscape** export results—decreases the font size of the text within the image relative using the `pretex` option together with the `\relscale` command provided by the **resize** package.

In [Figure 2](#) the same SVG file was used but without the export of a separate L^AT_EX file containing all text elements.

Feel free to use this given example to try out all the options and possibilities described in [section 2](#) for package **svg**. Especially if you want to use package **svg-extract** for the automated extraction of independent graphics ([subsection 3.2](#)) and their conversion to different graphic formats with **ImageMagick** and/or **Ghostscript** ([subsection 3.3](#)), this example can be easily used for the first steps.

5. Troubleshooting and reporting issues

When using the packages **svg** and **svg-extract**, the most likely occurring problems will be caused by calling the external programs. For this reason, a short package information is written into the log file right before each call of an external program via shell. If a file should have been created, both packages check after the external call, whether this file exists or not and raise an error or at least a warning, if this file is missing. If you got such a message, please check the log file for lines like:

```
Package svg Info: or Package svg-extract Info:
```

Right afterwards, there should appear `runsystem(<command>)...executed.` which you should try to execute manually from shell in the right directory. In most cases, the problem will be an invalid command call. If something goes wrong during the extraction/converting process of package **svg-extract**, it would make sense to set option `clean=false` to not delete any auxiliary files that might be needed.

If you are sure that the problem is not caused by the configuration of your operating system, you can send an error report either via email or create a new issue on GitHub. Both addresses can be found on the title.

When using pdfL^AT_EX there are a lot of warnings

It may happen that several warnings like

```
pdfTeX warning: pdflatex.exe(file <filename>.pdf): PDF inclusion:
multiple pdfs with page group included in a single page
```

occur when including the PDF graphics exported with **Inkscape**. This is related to the handling of transparency effects within PDF files. Since pdfL^AT_EX version 1.40.15 or later, you can get rid of these messages by using `\pdfsuppresswarningpagegroup=1`. See also the discussion on [LaTeX Stack Exchange](#)⁹ for more information.

6. Include SVG files created with **ROOT**

This section was originally written by Philip Ilten. In the hope that since then nothing has changed fundamentally in the described procedure, this passage remains in the documentation, even if it will almost certainly be relevant to experimental particle physicists only, who frequently use the analysis package **ROOT**.

ROOT has the ability to export directly to a SVG file, which means that it is possible to completely by-pass all of **ROOT**'s internal text rendering machinery, and let L^AT_EX handle the text natively. This means that all of the ugly fonts that are rendered by **ROOT** can

⁹<http://tex.stackexchange.com/questions/76273/>

now be completely avoided, with the additional bonus of being able to add references within plots. So how does one go about using this package with **ROOT**?

1. Create the plot with **ROOT** as normal, but turn off all \LaTeX interpretation of text strings. This is a bit tricky, but can be accomplished by setting the font in **ROOT** to a precision of zero as described in the documentation for `TAttFill`¹⁰. Remember that the font is set by using the function `(TAttFill*)->SetTextFont(i)` with

$$i = (\text{font type}) \times 10 + (\text{font precision})$$

In the following lines of code, a `TStyle` is defined which sets the font to type “Courier New” with a precision of zero.

```
TStyle *style = new TStyle("style","style"); int FONT = 80;
style->SetTextFont(FONT);
style->SetLabelFont(FONT,"XYZ");
style->SetTitleFont(FONT,"XYZ");
style->SetTitleFont(FONT,"");
gROOT->SetStyle("style");
gROOT->ForceStyle();
```

Now, you can just use the well-known standard \LaTeX syntax for creating labels, etc. Note however, that backslashes have to be escaped due to interpretation of special characters by `C++`.

2. Print the plot as a SVG file.

```
gPad->Print("foo.svg");
```

3. Include the SVG file within the document using this package.

```
\usepackage{svg}
\usepackage{svg-extract}
\svgsetup{clean=true}
...
\includesvg[width=\linewidth]{foo}
```

Consider the following example image produced by **ROOT** in [Figure 3](#). This figure was generated by the **ROOT** macro `root.C`, provided within `<texmf>/doc/latex/svg/examples/`, which produces the file `root.svg` when run. The code used to produce this SVG file from within **ROOT** is

```
void root() {
    // Set the style.
    gStyle->SetTextFont(80);      gStyle->SetLabelFont(80,"XYZ");
    gStyle->SetTitleFont(80,"");  gStyle->SetTitleFont(80,"XYZ");
    gStyle->SetPalette(1);       gStyle->SetOptStat(0);

    // Draw the plot.
    TH2D *h = new TH2D("", "", 25, 0, 3.9, 25, 0, 3.9); TRandom r;
    for (int i = 0; i < 30000; i++) h->Fill(r.Gaus(2.,1), r.Gaus(2.,1));
    h->GetXaxis()->CenterTitle(); h->GetXaxis()->SetTitleOffset(2.5);
    h->GetYaxis()->CenterTitle(); h->GetYaxis()->SetTitleOffset(2.5);
    h->GetXaxis()->SetTitle("\\larger[2]$x$");
    h->GetYaxis()->SetTitle("\\larger[2]$y$");
    h->Draw("LEG02");

    // Draw additional text.
    TText *t = new TText(); t->SetTextAlign(31);
    t->DrawText(0.7, 0.9, "\\larger[2]$z(x,y) = \\frac{1}{\\sqrt{4\\pi^2}}\\exp\\left(- \\left(\\frac{(x-\\mu_x)^2}{2\\sigma_x^2} + \\frac{(y-\\mu_y)^2}{2\\sigma_y^2} \\right)\\right)$");

    // Print the plot.
```

¹⁰<http://root.cern.ch/root/html/TAttText.html>




Figure 3: Rendering of a **ROOT** plot—no more *Comic CERNs*

```
gPad->Print("root.svg");
}
```

where the text produced within the **ROOT** plot is set to a precision of zero.

The plot was then included within this document using the following \LaTeX code

```
\begin{figure}
\centering%
\includesvg[%
inkscapearea=page,height=6cm,pretex=\tiny,convertformat=png%
]{root}%
\caption{Rendering of a \app{ROOT} plot---no more \emph{Comic CERNs}}%
\label{fig:root}%
\end{figure}
```

which includes the graphic as well as the \LaTeX file exported by **Inkscape**, produces the extracted PDF image (`root.pdf`) and converts this to a PNG image (`root.png`) by using **ImageMagick**. Enjoy plots from **ROOT** with natively rendered \LaTeX !

Part II.

Implementation

A. Initialization

A.1. Packages

The package **svg** requires **scrbase** for options processing, the packages **ifluatex**, **ifpdf** and **ifxetex** for detecting the used L^AT_EX engine, **pdftexcmds** for pdfT_EX primitives when using LuaT_EX, **shellesc** and **ifplatform** for engine independent access to systems commands and files as well as **graphicx** for the inclusion of PDF files. The usage of packages **xcolor** and **transparent** can be switched of with the corresponding options. Package **svg-extract** only needs package **svg** itself.

```
1 (*base)
2 \RequirePackage{scrbase}[2016/06/14]
3 \RequirePackage{ifpdf}[2016/05/14]
4 \RequirePackage{ifluatex}[2016/05/16]
5 \RequirePackage{ifxetex}[2010/09/12]
6 \RequirePackage{pdftexcmds}[2016/05/21]
7 \RequirePackage{shellesc}[2016/06/07]
8 \RequirePackage{trimspaces}[2009/09/17]
9 \RequirePackage{graphicx}[1999/02/16]
10 \end{base}
11 (*extract)
12 \RequirePackage{svg}[2017/03/27]
13 \end{extract}
```

A.2. Helper macros

```
\svg@tempa Internal temporary macros. The catcode for double quotes are also temporarily changed.
\svg@tempb
\svg@box
\if@svg@tempswa
14 \newcommand*\svg@tempa{}
15 \newcommand*\svg@tempb{}
16 \newbox\svg@box
17 \newif\if@svg@tempswa
18 \edef\svg@catcodecodes@restore{%
19 \catcode'\noexpand\"the\catcode'\relax%
20 }
21 \@makeother\"%
```

B. Including SVG files with package **svg**

B.1. Options

All options, which can be set either as package options or with `\svgsetup`, as well as the optional parameters for both user commands `\includesvg[parameters]{svg filename}` and `\includeinkscape[parameters]{graphic filename}` are defined with the interface provided by package **scrbase**.

```
22 \DefineFamily{SVG}
23 \DefineFamilyMember{SVG}
```

`\svg@deprecated@key` With version v2.00 the whole user interface was renewed. For reasons of compatibility, outdated options and parameters from version v1.0 are also provided. If an old key was given, a warning is issued and the valid key is used.

```

24 \newcommand*\svg@deprecated@key[3][svg]{%
25   \PackageWarning{#1}{%
26     The option key ‘#2’ is deprecated.\MessageBreak%
27     It’s recommended to use ‘#3’\MessageBreak%
28     instead%
29   }%
30   \FamilyOptions{SVG}{#3}%
31 }

```

Within the exported L^AT_EX files of *Inkscape*, some commands are used out of additional packages. But maybe the user doesn’t want to load this packages anyways.

<code>usexcolor</code> (opt.)	Options for preventing packages xcolor and transparent to be loaded.
<code>noxcolor</code> (opt.)	
<code>\ifsvg@use@xcolor</code>	<code>32 \newif\ifsvg@use@xcolor</code>
<code>usetransparent</code> (opt.)	<code>33 \FamilyBoolKey{SVG}{usexcolor}{@svg@use@xcolor}</code>
<code>nottransparent</code> (opt.)	<code>34 \DeclareOption{noxcolor}{\FamilyOptions{SVG}{usexcolor=false}}</code>
<code>\ifsvg@use@transparent</code>	<code>35 \newif\ifsvg@use@transparent</code>
	<code>36 \FamilyBoolKey{SVG}{usetransparent}{@svg@use@transparent}</code>
	<code>37 \DeclareOption{nottransparent}{\FamilyOptions{SVG}{usetransparent=false}}</code>

They are only available during the loading process of package **svg**.

```

38 \AtEndOfPackage{%
39   \RelaxFamilyKey{SVG}{usexcolor}%
40   \RelaxFamilyKey{SVG}{usetransparent}%
41   \ifsvg@use@xcolor%
42     \RequirePackage{xcolor}[2016/05/11]%
43   \else%
44     \AfterPackage*{xcolor}{%
45       \PackageWarning{svg}{Package ‘xcolor’ was loaded anyway}%
46     }%
47   \fi%
48   \ifsvg@use@transparent%
49     \RequirePackage{transparent}[2016/05/16]%
50   \else%
51     \AfterPackage*{transparent}{%
52       \PackageWarning{svg}{Package ‘transparent’ was loaded anyway}%
53     }%
54   \fi%
55 }

```

B.1.1. The invocation of *Inkscape*

The Application *Inkscape* is used to create includable graphic files in a desired format (PDF/EPS/PS/PNG) out of files in SVG format, whereas the support of L^AT_EX can optionally be used.

<code>inkscape</code> (opt.)	The intension of option <code>inkscape</code> is to control the running behaviour of <i>Inkscape</i> . It can be switched off at all (<code>inkscape=false</code>) or invoked only if necessary (<code>inkscape=true</code>) or the command line call can be forced with every L ^A T _E X run (<code>inkscape=forced</code>). Additionally, option <code>inkscape</code> can be used as wrapper for options <code>inkscapeformat</code> , <code>inkscapecatex</code> , <code>inkscapearea</code> and <code>inkscapecdpi</code> , which are declared later.
<code>\svg@ink@mode</code>	

```

56 \newcommand*\svg@ink@mode{}
57 \DefineFamilyKey{SVG}{inkscape}[true]{%
58   \lowercase{\svg@sanitize@dq\svg@tempb{#1}}%
59   \FamilySetNumerical{SVG}{inkscape}{svg@tempa}{%
60     {false}{0},{off}{0},{no}{0},%

```

```

61 {true}{1},{on}{1},{yes}{1},{onlynewer}{1},{newer}{1},%
62 {force}{2},{forced}{2},{overwrite}{2},%
63 {pdf}{3},{eps}{4},{ps}{5},{png}{6},%
64 {drawing}{7},{crop}{7},%
65 {page}{8},{nocrop}{8},%
66 {tex}{9},{latex}{9},{exportlatex}{9},{latexexport}{9},%
67 {notex}{10},{nolatemx}{10},{noexportlatex}{10},{nolatemxexport}{10},%
68 {latexnoexport}{10},{raw}{10},{plain}{10},{simple}{10}%
69 }\svg@tempb}%
70 \ifx\FamilyKeyState\FamilyKeyStateProcessed%

```

Setting the mode for invoking *Inkscape*...

```

71 \ifnum\svg@tempa<\thr@@\relax%
72 \let\svg@ink@mode\svg@tempa%
73 \else%

```

...and the part as wrapper for different options.

```

74 \ifcase\svg@tempa\relax\or\or\or% pdf
75 \FamilyOptions{SVG}{inkscapeformat=pdf}%
76 \or% eps
77 \FamilyOptions{SVG}{inkscapeformat=eps}%
78 \or% ps
79 \FamilyOptions{SVG}{inkscapeformat=ps}%
80 \or% png
81 \FamilyOptions{SVG}{inkscapeformat=png}%
82 \or% drawing
83 \FamilyOptions{SVG}{inkscapearea=drawing}%
84 \or% page
85 \FamilyOptions{SVG}{inkscapearea=page}%
86 \or% tex
87 \FamilyOptions{SVG}{inkscapelatex=true}%
88 \or% notex
89 \FamilyOptions{SVG}{inkscapelatex=false}%
90 \fi%
91 \fi%

```

It's also possible to set the option `inkscape` by passing a number followed by `dpi` like `inkscape=300dpi`.

```

92 \else% dpi
93 \def\svg@tempa##1dpi##2\@nil{%
94 \ifstr{##2}{dpi}{\FamilyOptions{SVG}{inkscapedpi=##1}}{%
95 }%
96 \lowercase{\expandafter\svg@tempa\svg@tempb dpi \@nil}%

```

In version v1.0 the option `inkscape` was used to set both the executable and options for *Inkscape*. This is taken into account here.

```

97 \ifx\FamilyKeyState\FamilyKeyStateProcessed\else%

```

Splitting executable from options with delimited macros. After calling `\svg@tempa` with the given value, the part for the executable is stored in `\svg@tempa` and the option part—which is recognized by the first `-` character—in `\svg@tempb`.

```

98 \svg@quotes@remove[#{#1}]{\svg@tempb}%
99 \def\svg@tempa##1-##2\@nil{%
100 \IfArgIsEmpty{##2}{\def\svg@tempb{}}%
101 \def\svg@tempa####1-\@nil{\def\svg@tempb{-####1}}%
102 \svg@tempa##2\@nil%
103 }%
104 \edef\svg@tempa{\trim@spaces{##1}}%
105 }%
106 \edef\svg@tempb{%
107 \noexpand\svg@tempa\svg@tempb-\noexpand\@nil%
108 }%

```

```

109 \svg@tempb%
110 \if@svg@quotes@found%
111 \edef\svg@tempa{"\svg@tempa"}%
112 \fi%
113 \PackageWarning{svg}{%
114 Setting the executable%
115 \ifx\svg@tempb\@empty\else%
116 \space and associated options%
117 \fi%
118 \MessageBreak%
119 for Inkscape should be done with options\MessageBreak%
120 'inkscapeexe=\svg@tempa'%
121 \ifx\svg@tempb\@empty\else%
122 \MessageBreak and 'inkscapeopt=\svg@tempb'%
123 \fi.\MessageBreak%
124 Nevertheless, this was done by now anyway%
125 }%
126 \edef\svg@tempa{%
127 \noexpand\FamilyOptions{SVG}{inkscapeexe=\svg@tempa}%
128 \ifx\svg@tempb\@empty\else%
129 \noexpand\FamilyOptions{SVG}{inkscapeopt=\svg@tempb}%
130 \fi%
131 }%
132 \svg@tempa%
133 \fi%
134 \fi%
135 }

```

on (opt.) Package options which can be used to switch functionality on or off during the loading of
off (opt.) package **svg**.

```

136 \DeclareOption{on}{\FamilyOptions{SVG}{inkscape=true}}
137 \DeclareOption{off}{\FamilyOptions{SVG}{inkscape=false}}

```

inkscapeformat (opt.) With option `inkscapeformat` the output format of the **Inkscape** export function, which
\svg@ink@format is called via `\ShellEscape`, can be configured. It is set to pdf or, if dvi output could be
detected, to eps during initialization.

```

138 \newcommand*\svg@ink@format{pdf}
139 \ifxetex\else\ifpdf\else
140 \renewcommand*\svg@ink@format{eps}
141 \fi\fi
142 \DefineFamilyKey{SVG}{inkscapeformat}{%
143 \lowercase{\def\svg@tempa{#1}}%
144 \FamilySetNumerical{SVG}{inkscapeformat}{\svg@tempa}{%
145 {pdf}{0},{eps}{1},{ps}{2},{png}{3}}%
146 }{\svg@tempa}%
147 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
148 \ifcase\svg@tempa\relax% latex
149 \renewcommand*\svg@ink@format{pdf}%
150 \or% eps
151 \renewcommand*\svg@ink@format{eps}%
152 \or% ps
153 \renewcommand*\svg@ink@format{ps}%
154 \or% png
155 \renewcommand*\svg@ink@format{png}%
156 \fi%
157 \fi%
158 }

```

inksapelatex (opt.) This option controls whether the **Inkscape** export will be invoked with or without the
latex (opt.) generation of a separate L^AT_EX file.

```

tex (opt.)
\svg@ink@latex 159 \newif\if@svg@ink@latex
160 \FamilyBoolKey{SVG}{inksapelatex}{@svg@ink@latex}

```

```
161 \FamilyBoolKey{SVG}{\latex}{@svg@ink@latex}
162 \FamilyBoolKey{SVG}{\tex}{@svg@ink@latex}
```

`inkscapearea` (opt.) The exported area for an *Inkscape* graphic can be set with this option.

```
\svg@ink@area
163 \newcommand*\svg@ink@area{}
164 \DefineFamilyKey{SVG}{inkscapearea}{%
165   \FamilySetNumerical{SVG}{inkscapearea}{svg@tempa}{%
166     {drawing}{0},{crop}{0},%
167     {page}{1},{nocrop}{1}%
168   }{#1}%
169   \ifx\FamilyKeyState\FamilyKeyStateProcessed%
170     \ifcase\svg@tempa\relax% drawing
171       \renewcommand*\svg@ink@area{-D}%
172     \else% page
173       \renewcommand*\svg@ink@area{-C}%
174     \fi%
175   \fi%
176 }
```

`inkscapedpi` (opt.) A density can be chosen, which is used during export with *Inkscape* for bitmaps and
`inkscapedensity` (opt.) rasterization of filters.

```
\svg@ink@dpi
177 \newcommand*\svg@ink@dpi{}
178 \let\svg@ink@dpi\relax
179 \DefineFamilyKey{SVG}{inkscapedpi}{%
180   \FamilyKeyStateUnknownValue%
181   \svg@ifvalueisrelax{#1}{%
182     \let\svg@ink@dpi\relax%
183     \FamilyKeyStateProcessed%
184   }{%
185     \def\svg@tempa##1dpi##2\@nil{\def\svg@tempa{##1}}%
186     \lowercase{\svg@tempa#1dpi\@nil}%
187     \ifnumber{\svg@tempa}{%
188       \edef\svg@ink@dpi{\svg@tempa}%
189       \FamilyKeyStateProcessed%
190     }{}}%
191   }%
192 }
193 \DefineFamilyKey{SVG}{inkscapedensity}{\FamilyOptions{SVG}{inkscapedpi=#1}}
```

`inkscapeexe` (opt.) With these options, the terminal command for invoking *Inkscape* as well as additional
`\svg@ink@exe` options can be defined.

```
inkscapeopt (opt.)
\svg@ink@opt
194 \newcommand*\svg@ink@exe{inkscape}
195 \DefineFamilyKey{SVG}{inkscapeexe}{%
196   \renewcommand*\svg@ink@exe{#1}%
197   \FamilyKeyStateProcessed%
198 }
199 \newcommand*\svg@ink@opt{}
200 \DefineFamilyKey{SVG}{inkscapeopt}{%
201   \renewcommand*\svg@ink@opt{#1}%
202   \FamilyKeyStateProcessed%
203 }
```

B.1.2. Setting input folder and file

`svgpath` (opt.) In version v1.0 setting the path to SVG files was done via option. So this method is provided as well.

```
204 \DefineFamilyKey{SVG}{svgpath}{%
205   \PackageWarning{svg}{%
206     The key ‘svgpath’ is deprecated. It’s recommended\MessageBreak%
207     to use ‘\string\svgpath’ instead%
```



```

208 }%
209 \ifx\svgpath\@undefined%
210 \AtEndOfPackage{\svgpath{#{1}}}%
211 \else%
212 \svgpath{#{1}}%
213 \fi%
214 \FamilyKeyStateProcessed%
215 }

```

`svgextension` (opt.) This option modifies the expected extension for the input file which is exported with *Inkscape*. It is set to `svg` by default.

```

extension (opt.)
  ext (opt.)
  \svg@file@ext
216 \newcommand*\svg@file@ext{svg}
217 \DefineFamilyKey{SVG}{svgextension}{%

```

The extension should be in lower case letters.

```

218 \lowercase{\svg@quotes@remove[#{1}]{\svg@file@ext}}%

```

Remove leading dots from the extension.

```

219 \svg@remove@leadingchar.\svg@file@ext%
220 }
221 \DefineFamilyKey{SVG}{extension}{\FamilyOptions{SVG}{svgextension=#1}}
222 \DefineFamilyKey{SVG}{ext}{\FamilyOptions{SVG}{svgextension=#1}}

```

B.1.3. Setting output folder

`inkscapepath` (opt.) The option `inkscapepath` controls, in which folder the results of the *Inkscape* export will be located. With option `inkscapepath` the name of the exported file itself can be changed.

```

inkscapepath (opt.)
inkscapepath (opt.)
  \svg@out@path
  \svg@out@name
  \svg@out@base
223 \newcommand*\svg@out@path{}
224 \newcommand*\svg@out@name{\svg@file@name\svg@file@suffix}
225 \newcommand*\svg@out@base{\svg@out@path\svg@out@name.\svg@ink@format}
226 \DefineFamilyKey{SVG}{inkscapepath}{%
227 \svg@sanitize@dq\svg@tempb{#{1}}%
228 \FamilySetNumerical{SVG}{inkscapepath}{\svg@tempa}{%
229 {svgpath}{0},{svgdir}{0},%
230 {svgsubpath}{1},{svgsubdir}{1},%
231 {basepath}{2},{basedir}{2},{jobpath}{2},{jobdir}{2},%
232 {basesubpath}{3},{basesubdir}{3},{jobsubpath}{3},{jobsubdir}{3}%
233 }{\svg@tempb}%
234 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
235 \ifcase\svg@tempa\relax% svgpath
236 \renewcommand*\svg@out@path{\svg@file@path}%
237 \or% svgsubpath
238 \renewcommand*\svg@out@path{\svg@file@path\svg-inkscape/}%
239 \or% basepath
240 \renewcommand*\svg@out@path{./}%
241 \or% basesubpath
242 \renewcommand*\svg@out@path{./svg-inkscape/}%
243 \fi%
244 \else%
245 \edef\svg@out@path{\svg@tempb}%
246 \svg@normalize@path{\svg@out@path}%
247 \FamilyKeyStateProcessed%
248 \fi%
249 }
250 \DefineFamilyKey{SVG}{inkscapepath}{%
251 \renewcommand*\svg@out@name{#{1}\svg@file@suffix}%
252 \FamilyKeyStateProcessed%
253 }

```

B.1.4. Options for the inclusion of graphics

After the graphic export with *Inkscape*, the inclusion of those graphics can be controlled with the following options.

<pre> width (opt.) \svg@param@width height (opt.) \svg@param@width distort (opt.) keepaspectratio (opt.) \if@svg@param@distort scale (opt.) \svg@param@scale </pre>	<pre> These options determine the size of the included graphics. The usage of \relax as value resets the respective option to the default behavior. 254 \newcommand*\svg@param@width{\z@} 255 \DefineFamilyKey{SVG}{width}{% 256 \FamilyKeyStateUnknownValue% 257 \svg@ifvalueisrelax{#1}{% 258 \renewcommand*\svg@param@width{\z@}% 259 \FamilyKeyStateProcessed% 260 }{% 261 \FamilySetLengthMacro{SVG}{width}{\svg@param@width}{#1}% 262 \ifx\FamilyKeyState\FamilyKeyStateProcessed% 263 \ifdim\svg@param@width<\z@\relax% 264 \FamilyKeyStateUnknownValue% 265 \fi% 266 \fi% 267 }% 268 } 269 \newcommand*\svg@param@height{\z@} 270 \DefineFamilyKey{SVG}{height}{% 271 \FamilyKeyStateUnknownValue% 272 \svg@ifvalueisrelax{#1}{% 273 \renewcommand*\svg@param@height{\z@}% 274 \FamilyKeyStateProcessed% 275 }{% 276 \FamilySetLengthMacro{SVG}{height}{\svg@param@height}{#1}% 277 \ifx\FamilyKeyState\FamilyKeyStateProcessed% 278 \ifdim\svg@param@height<\z@\relax% 279 \FamilyKeyStateUnknownValue% 280 \fi% 281 \fi% 282 }% 283 } 284 \newif\if@svg@param@distort 285 \FamilyBoolKey{SVG}{distort}{@svg@param@distort} 286 \DefineFamilyKey{SVG}{keepaspectratio}[true]{% 287 \FamilySetBool{SVG}{keepaspectratio}{@svg@tempswa}{#1}% 288 \ifx\FamilyKeyState\FamilyKeyStateProcessed% 289 \if@svg@tempswa% 290 \FamilyOptions{SVG}{distort=false}% 291 \else 292 \FamilyOptions{SVG}{distort=true}% 293 \fi% 294 \fi% 295 } 296 \newcommand*\svg@param@scale{1} 297 \DefineFamilyKey{SVG}{scale}{% 298 \FamilyKeyStateUnknownValue% 299 \svg@ifvalueisrelax{#1}{% 300 \renewcommand*\svg@param@scale{1}% 301 \FamilyKeyStateProcessed% 302 }{% 303 \ifisdimension{#1\p@}{% 304 \ifdim\dimexpr#1\p@\relax>\z@\relax% 305 \renewcommand*\svg@param@scale{#1}% 306 \FamilyKeyStateProcessed% 307 \fi% 308 }{}% 309 }% 310 } </pre>
---	--

`pretex` (opt.) For executing code right before or after the graphic inclusion, two hooks are defined.

```

\svg@param@pretex
  aptex (opt.)
\svg@param@aptex
  postex (opt.)
311 \newcommand*\svg@param@pretex{}
312 \let\svg@param@pretex\relax
313 \DefineFamilyKey{SVG}{pretex}{%
314   \svg@ifvalueisrelax{#1}{%
315     \let\svg@param@pretex\relax%
316   }{%
317     \def\svg@param@pretex{#1}%
318   }%
319   \FamilyKeyStateProcessed%
320 }
321 \newcommand*\svg@param@aptex{}
322 \let\svg@param@aptex\relax
323 \DefineFamilyKey{SVG}{aptex}{%
324   \svg@ifvalueisrelax{#1}{%
325     \let\svg@param@aptex\relax%
326   }{%
327     \def\svg@param@aptex{#1}%
328   }%
329   \FamilyKeyStateProcessed%
330 }
331 \DefineFamilyKey{SVG}{postex}{%
332   \svg@deprecated@key{postex=#1}{aptex=#1}%
333 }
```

`lastpage` (opt.) For *Inkscape* 0.91 a bug concerning the L^AT_EX export has been reported (<https://bugs.launchpad.net/ubuntu/+source/inkscape/+bug/1417470>). Sometimes the L^AT_EX file created by *Inkscape* tries to include more pages than actually are present in the PDF file. To work around this problem, a patch is provided. For this purpose, the total page number is read from the PDF file.

```

\svg@param@lastpage (counter)
334 \newcounter{svg@param@lastpage}
335 \DefineFamilyKey{SVG}{lastpage}{%
336   \FamilySetNumerical{SVG}{lastpage}{svg@tempa}{%
337     {false}{0},{off}{0},{no}{0},{ignore}{0},%
338     {true}{1},{on}{1},{yes}{1},{auto}{1}%
339   }{#1}%
340   \ifx\FamilyKeyState\FamilyKeyStateProcessed%
341     \ifcase\svg@tempa\relax% false
342     \FamilySetCounter{SVG}{lastpage}{svg@param@lastpage}{\m@ne}%
343     \or% true
344     \FamilySetCounter{SVG}{lastpage}{svg@param@lastpage}{\z@}%
345     \fi%
346   \fi%
347 }
```

`draft` (opt.) The option `draft` has the same effect as the eponymous option of package **graphicx**.

```

\if@svg@draft
348 \newif\if@svg@draft
349 \FamilyBoolKey{SVG}{draft}{@svg@draft}
350 \AtBeginDocument{\if@svg@draft\else\ifGin@draft\@svg@drafttrue\fi\fi}
```

B.2. Handling path information

Both packages **svg** and **svg-extract** should be able to handle user-defined input and output paths. As there is the possibility for users to provide paths with or without quotes to L^AT_EX, this is taken into account.

`\svg@deactivate@dq` In order to avoid errors concerning file names with package **babel** and its active double quotes, this command is defined.

```

351 \newcommand*\svg@deactivate@dq{}
```

```

352 \AfterPackage+{babel}{%
353   \renewcommand*{svg@deactivate@dq}{\bbl@deactivate{}}%
354   \providecommand*\bbl@deactivate[1]{}%
355 }

```

`\svg@sanitize@dq` Save expansion of the second argument in the macro from the first argument with deactivated double quotes.

```

356 \newcommand*{svg@sanitize@dq}[2]{%
357   \begingroup%
358   \svg@deactivate@dq%
359   \edef\svg@tempa{\endgroup\def\noexpand#1{#2}}%
360   \svg@tempa%
361 }

```

`\svg@quotes@remove` and `\svg@quotes@@remove` These two commands are used to remove all occurring quotes within a string. The only argument passed to `\svg@quotes@remove` is not the string itself but a macro in which a string is stored.

```

362 \newcommand*{svg@quotes@remove}[2][ ]{%
363   \begingroup%
364   \IfArgIsEmpty{#1}{\def\svg@tempb{#2}}{\def\svg@tempb{#1}}%
365   \svg@sanitize@dq\svg@tempa{\svg@tempb}%
366   \expandafter\svg@quotes@check\expandafter{\svg@tempa}%
367   \expandafter\svg@quotes@@remove\svg@tempa""\nil%
368   \edef\svg@tempb{%
369     \endgroup%
370     \def\noexpand#2{\svg@tempa}%
371     \if@svg@quotes@found%
372       \noexpand\@svg@quotes@foundtrue%
373     \else%
374       \noexpand\@svg@quotes@foundfalse%
375     \fi%
376   }%
377   \svg@tempb%
378 }
379 \newcommand*{svg@quotes@@remove}{
380 \def\svg@quotes@@remove#1"#2"#3\nil{%
381   \IfArgIsEmpty{#2}{%
382     \edef\svg@tempa{#1}%
383   }{%
384     \svg@quotes@@remove#1"#2"#3""\nil%
385   }%
386 }

```

`\svg@quotes@check` and `\if@svg@quotes@found` During the treatment of paths, it may be necessary to temporarily remove quotes and, if required, add them again later. For this purpose, the switch `\if@svg@quotes@found` as well as the commands `\svg@quotes@check` and `\svg@quotes@@check`, which controls the switch, are defined. As before, the string is passed in a macro to `\svg@quotes@check`.

```

387 \newif\if@svg@quotes@found
388 \newcommand*{svg@quotes@check}[1]{%
389   \expandafter\svg@quotes@@check#1""\nil%
390 }
391 \newcommand*{svg@quotes@@check}{
392 \def\svg@quotes@@check#1"#2\nil{%
393   \IfArgIsEmpty{#2}{\@svg@quotes@foundfalse}{\@svg@quotes@foundtrue}%
394 }

```

`\svg@remove@leadingchar` This command removes the single character in given with the first argument from the expanded macro in the second argument.

```

395 \newcommand*{svg@remove@leadingchar}[2]{%
396   \begingroup%

```

```

397 \svg@sanitize@dq\svg@tempa{#2}%
398 \def\svg@tempb{%
399 \def\svg@tempa###1\@nil{\def\svg@tempa{###1}}%
400 \kernel@ifnextchar#1%
401 {\expandafter\svg@tempa\@gobble}%
402 {\svg@tempa}%
403 }%
404 \expandafter\svg@tempb\svg@tempa\@nil%
405 \edef\svg@tempb{%
406 \endgroup%
407 \def\noexpand#2{\svg@tempa}%
408 }%
409 \svg@tempb%
410 }

```

`\svg@set@input@path` In order to import SVG files from different folders, `\svg@set@input@path` evaluates several macros, which are supposed to be used for holding different search folders. Any given path will be handled by `\svg@normalize@path`. The optional argument can be used to append an additional search path.

```

411 \newcommand*\svg@set@input@path[1] []{%
412 \begingroup%
413 \svg@deactivate@dq%

```

If a path was already found and stored within `\svg@file@path`, it is searched first and wrapped in curly braces. This is necessary for using commands like `\input{(tex filename)}` within SVG files.

```

414 \ifx\svg@file@path\@empty\else%
415 \svg@normalize@path{\svg@file@path}%
416 \edef\svg@file@path{\{\svg@file@path\}}%
417 \fi%

```

Afterwards, several search paths are appended. If `\svg@path` was used, it is searched next. If nothing was found, `\graphicspath` is considered if defined followed by a path given in the third argument. If nothing was found yet, the standard `\input@path` is searched last.

```

418 \svg@append@input@path{\svg@file@path}\svg@input@path}%
419 \svg@append@input@path{\svg@file@path}\Ginput@path}%
420 \IfArgIsEmpty{#1}\{\svg@append@input@path{\svg@file@path}{#1}}}%
421 \svg@append@input@path{\svg@file@path}\input@path}%

```

Finally, `\input@path` is set.

```

422 \edef\svg@tempa{%
423 \endgroup%
424 \ifx\svg@file@path\@empty\else%
425 \def\noexpand\input@path{\svg@file@path}%
426 \fi%
427 }%
428 \svg@tempa%
429 }

```

Only, if a certain search path is defined, it is added. The paths given in the first argument are compared to each path in the second argument and only new ones are added.

```

430 \newcommand*\svg@append@input@path[2] {%
431 \ifx#2\@undefined\else%
432 \edef\svg@tempb{#2}%
433 \expandafter\@tfor\expandafter\svg@tempa\expandafter:\expandafter=%
434 \svg@tempb\do{%

```

Passing each new path to `\svg@normalize@path`. If a path already exists, switch `\if@svg@tempswa` is set to false.

```

435     \ifx\svg@tempa\@empty\else%
436     \@svg@tempswatrue%
437     \svg@normalize@path{\svg@tempa}%
438     \expandafter\@tfor\expandafter\svg@tempb\expandafter:\expandafter=%
439     #1\do{%
440     \ifx\svg@tempa\svg@tempb%
441     \@svg@tempswafalse%
442     \@break@tfor%
443     \fi%
444     }%
445     \if@svg@tempswa%
446     \edef#1{#1\svg@tempa}%
447     \fi%
448     \fi%
449     }%
450 \fi%
451 }

```

`\svg@normalize@path` If any path is given, a trailing slash is needed. These two macros ensure that this condition is fulfilled in any case, even if this is not considered by the user. As before, a macro containing the path string is passed to `\svg@normalize@path`.

`\svg@normalize@@path`

```

452 \newcommand*\svg@normalize@path[1]{%
453 \begingroup%
454 \svg@quotes@remove[#{1}]{\svg@tempa}%
455 \ifx\svg@tempa\@empty\relax%
456 \def\svg@tempa{./}%
457 \fi%
458 \expandafter\svg@normalize@@path\svg@tempa//\@nil%
459 \edef\svg@tempb{%
460 \endgroup%
461 \if@svg@quotes@found%
462 \def\noexpand#1{"\svg@tempa"%
463 \else%
464 \def\noexpand#1{\svg@tempa}%
465 \fi%
466 }%
467 \svg@tempb%
468 }
469 \newcommand*\svg@normalize@@path{}
470 \def\svg@normalize@@path#1/#2/\@nil{%
471 \IfArgIsEmpty{#2}{%
472 \IfArgIsEmpty{#1}{\def\svg@tempa{}}{\def\svg@tempa{#1/}}%
473 }{%
474 \svg@normalize@@path#2/\@nil%
475 \edef\svg@tempa{#1/\svg@tempa}%
476 }%
477 }

```

`\svg@ifvalueisrelax` For some keys the usage of `\relax` as a value should lead to a special reaction, such as restoring to default behavior or resetting the key. Therefore, `\svg@ifvalueisrelax` checks, whether `\relax` was used as value or not.

```

478 \newcommand*\svg@ifvalueisrelax[1]{%
479 \begingroup%
480 \def\svg@tempa{#1}%
481 \def\svg@tempb{\relax}%
482 \ifx\svg@tempa\svg@tempb\relax%
483 \aftergroup\@firstoftwo%
484 \else%
485 \aftergroup\@secondoftwo%
486 \fi%

```



```
487 \endgroup%
488 }
```

`\svg@get@path` The command `\svg@get@path` tries to find a given SVG file. If the searched file wasn't found in the current path, all paths given with `\svg@path` are evaluated. If there was no appropriate file again, all paths given by `\graphicspath` are examined. In the last step, a given path within the second mandatory argument is browsed. The results for file path and name are stored in `\svg@file@path` and `\svg@file@name` as well as the compound of both is saved in `\svg@file@base`.

```
489 \newif\if@svg@file@found
490 \newcommand*\svg@file@path{}
491 \newcommand*\svg@file@name{}
492 \newcommand*\svg@file@base{}
493 \newcommand*\svg@file@suffix{}
494 \newcommand*\svg@get@path[3][\svg@file@ext]{%
495 \begingroup%
```

A maybe given, unneeded file extension is removed.

```
496 \svg@filename@parse[#{1}]#{2}%
497 \IfArgIsEmpty{#1}{%
498 \edef\svg@tempa{\filename@area\filename@base.\filename@ext}%
499 }{%
500 \edef\svg@tempa{\filename@area\filename@base.#1}%
501 }%
```

After calling `\svg@set@input@path`, all search paths are stored in `\input@path`, a single path given in the third argument will also be considered.

```
502 \svg@set@input@path[#{3}]%
```

The specified file is searched with `\IfFileExists`. If the file search was successful, the macro `\svg@filename@parse` is called with the result.

```
503 \@svg@tempswafalse%
504 \expandafter\IfFileExists\expandafter{\svg@tempa}{%
505 \@svg@tempswatruetrue%
506 \edef\@filef@und{\expandafter\trim@spaces\expandafter{\@filef@und}}%
507 \svg@filename@parse[#{1}]{\@filef@und}%
508 }{}%
509 \edef\svg@tempa{%
510 \endgroup%
511 \if@svg@tempswa%
512 \noexpand\@svg@file@foundtrue%
513 \def\noexpand\svg@file@path{\filename@area}%
514 \def\noexpand\svg@file@name{\filename@base}%
515 \def\noexpand\svg@file@base{\filename@area\filename@base}%
516 \else%
517 \noexpand\@svg@file@foundfalse%
518 \def\noexpand\svg@file@path{}%
519 \def\noexpand\svg@file@name{#2}%
520 \def\noexpand\svg@file@base{#2}%
521 \fi%
522 }%
523 \svg@tempa%
524 }
```

`\svg@filename@parse` As the internal L^AT_EX 2_ε command `\filename@parse` is not able to split a given file name containing quotes, `\svg@filename@parse` is defined to resolve this problem. The optional argument can be used to give a specific file extension, which should be searched within `\filename@ext`. If found at the very end, the previous part is appended to `\filename@base`.

```
525 \newcommand*\svg@filename@parse[2][{}]{%
526 \begingroup%
```

The given path and file is parsed with `\filename@parse`.

```
527 \svg@sanitize@dq\svg@tempa{#2}%
528 \expandafter\filename@parse\expandafter{\svg@tempa}%
529 % If there are quotes in the file path, the closing one will be found as first
530 % character in \cs{filename@base} as \cs{filename@area} is splitted at the last
531 % slash. This leading quote is removed from \cs{filename@base} with
532 % \cs{svg@remove@leadingchar}.
533 % \begin{macrocode}
534 \svg@quotes@remove{\filename@area}%
535 \if@svg@quotes@found%
536 \edef\filename@area{"\filename@area"%
537 \svg@remove@leadingchar"\filename@base%
538 \fi%
```

The found extension is parsed against the optional argument. If a double quote was found within the extension, it actually belongs to `\filename@base`.

```
539 \ifx\filename@ext\relax\else%
540 \svg@quotes@remove{\filename@ext}%
541 \svg@extension@parse{#1}%
542 \if@svg@quotes@found%
543 \edef\filename@base{\filename@base"%
544 \fi%
545 \fi%
```

Quotes within `\filename@base` are normalized.

```
546 \svg@quotes@remove{\filename@base}%
547 \if@svg@quotes@found%
548 \edef\filename@base{"\filename@base"%
549 \fi%
```

With `\svg@tempa` the group is closed and the results are saved in the macros `\filename@...`

```
550 \edef\svg@tempa{%
551 \endgroup%
552 \def\noexpand\filename@area{\filename@area}%
553 \def\noexpand\filename@base{\filename@base}%
554 \ifx\filename@ext\relax%
555 \let\noexpand\filename@ext\noexpand\relax%
556 \else%
557 \def\noexpand\filename@ext{\filename@ext}%
558 \fi%
559 }%
560 \svg@tempa%
561 }
```

`\svg@extension@parse` `\svg@extension@@parse` These macros are used to permit multiple dots in file names. The content of `\filename@ext` is split at each occurrence of `.` and the trailing part is compared against the content of the argument of `\svg@extension@parse`, which is probably `\svg@file@ext`. If they are equal, the previous part is appended to `\filename@base` and `\filename@ext` is set to the content of the first argument.

```
562 \newcommand*\svg@extension@parse[1]{%
563 \IfArgIsEmpty{#1}{}-%
564 \ifstr{#1}{\filename@ext}{}-%
565 \beginingroup%
```

Macro `\svg@tempa` is used to temporarily store anything before the searched extension at the end of `\filename@ext` and `\svg@tempb` is set to the actual searched extension if found.

```
566 \edef\svg@tempa{%
567 \def\noexpand\svg@tempa{}%
568 \let\noexpand\svg@tempb\relax%
569 \noexpand\svg@extension@@parse%
```

```

570         \filename@ext.\noexpand\@nil#1\noexpand\@nil%
571     }%
572     \svg@tempa%
573     \edef\svg@tempa{%
574         \endgroup%

```

If the trailing extension was found, \filename@base and \filename@ext are adopted.

```

575         \def\noexpand\filename@base{\filename@base\svg@tempa}%
576         \ifx\svg@tempb\relax%
577             \let\noexpand\filename@ext\relax%
578         \else%
579             \def\noexpand\filename@ext{\svg@tempb}%
580         \fi%
581     }%
582     \svg@tempa%
583 }%
584 }%
585 }

```

Macro \svg@extension@@parse is recursively called as long as there are any dots or the searched extension is found.

```

586 \newcommand*\svg@extension@@parse{}
587 \def\svg@extension@@parse#1.#2\@nil#3\@nil{%
588     \edef\svg@tempa{\svg@tempa.#1}%
589     \IfArgIsEmpty{#2}{-}{%
590         \ifstr{#2}{#3.}{%

```

If the trailing extension is found, \svg@tempb is defined.

```

591         \edef\svg@tempb{#3}%
592     }{%
593         \svg@extension@@parse#2\@nil#3\@nil%
594     }%
595 }%
596 }

```

`\svg@file@missing` The error message, which is raised, if a file is missing either after the export with *Inkscape* or in general.

```

597 \newcommand*\svg@file@missing[3] []{%
598     \begingroup%
599     \svg@quotes@remove[#{#2}]{\svg@tempa}%
600     \svg@filename@parse[#{#1}]{\svg@tempa}%
601     \IfArgIsEmpty{#1}{-}{%
602         \svg@quotes@remove[#{#3}]{\svg@tempb}%
603         \def\svg@tempa{%
604             Did you run the export with Inkscape? There's no file\MessageBreak%
605             '\filename@area\filename@base.\filename@ext'\MessageBreak%
606             although '\svg@tempb' was found.%
607         }%
608     }%
609     \edef\filename@ext{#1}%
610     \ifstr{\filename@area}{.}{\let\filename@area\@empty}{-}%

```

Collecting all considered path for the error message.

```

611         \edef\svg@tempb{#3}%
612         \ifstr{\svg@tempb}{.}{\let\svg@tempb\@empty}{-}%
613         \ifx\svg@tempb\@empty%
614             \svg@set@input@path%
615         \else%
616             \svg@set@input@path[\svg@tempb]%
617         \fi%
618         \ifx\input@path\@undefined%

```

```

619     \def\svg@tempb{No additional path was given.}%
620     \else%
621     \def\svg@tempb{Following folders have additionally been searched:}%
622     \expandafter\@tfor\expandafter\svg@tempa\expandafter:\expandafter=%
623     \input@path\do{%
624     \edef\svg@tempb{\svg@tempb\noexpand\MessageBreak\svg@tempa}%
625     }%
626     \fi%

```

The error message itself.

```

627     \def\svg@tempa{%
628     There's no file '\filename@base.\filename@ext'\MessageBreak%
629     \ifx\filename@area\@empty%
630     neither in the current directory nor any other searched\MessageBreak%
631     path given by \string\svgpath\space or \string\graphicspath.%
632     \MessageBreak\svg@tempb%
633     \else%
634     in folder '\filename@area'.%
635     \fi%
636     }%
637     }%
638     \PackageError{svg}{%
639     File '\filename@base.\filename@ext' is missing%
640     }{\svg@tempa}%
641     \endgroup%
642 }

```

`\svg@iffilenewer` The macro `\svg@iffilenewer` is used to decide, whether the export with *Inkscape* is necessary due to an updated SVG file. This can only be done, if `\pdf@filemoddate` is defined. Unfortunately this functionality isn't provided by XeTeX.

```

643 \ifx\pdf@filemoddate\@undefined
644 \newcommand*\svg@iffilenewer[2]{\@gobbletwo}
645 \else
646 \newcommand*\svg@iffilenewer[2]{%
647 \begingroup%
648 \edef\svg@tempa{\pdf@filemoddate{#1}}%
649 \edef\svg@tempb{\pdf@filemoddate{#2}}%
650 \ifnum\pdf@strcmp{\svg@tempa}{\svg@tempb}>\z@\relax%
651 \aftergroup\@firstoftwo%
652 \else%
653 \aftergroup\@secondoftwo%
654 \fi%
655 \endgroup%
656 }
657 \fi

```

B.3. Optional Parameters for user commands

`\svg@local@param@set` Most of the package options can also be used as optional parameters for `\includesvg` or `\includeinkscape`. Some of them are overloaded for the usage as optional argument and there are some keys, which *only* can be used as optional parameters. This is realized in such a way that `\svg@local@param@use` is extended with `\svg@local@param@def` by the definition of local keys during the loading of package **svg**.

```

658 \newcommand*\svg@local@param@set[1]{%
659 \svg@local@param@use%
660 \FamilyOptions{SVG}{#1}%

```

As `\svg@local@param@set` is always used in a local group, it is possible to set `inkscapelatex` to `false`, if the output format was set to `png` with option `inkscapeformat`.

```

661 \ifstr{\svg@ink@format}{png}{\FamilyOptions{SVG}{inkscapelatex=false}}{ }%

```

Using `distort=true` is only reasonable, if `height` and `width` are given.

```

662 \svg@tempwafalse%
663 \ifdim\svg@param@width>\z@\relax\ifdim\svg@param@height>\z@\relax%
664 \svg@tempwattrue%
665 \fi\fi%
666 \ifsvg@tempswa\else%
667 \FamilyOptions{SVG}{distort=false}%
668 \fi%
669 }
670 \newcommand*\svg@local@param@use{}
671 \newcommand*\svg@local@param@def[1]{%
672 \edef\svg@local@param@use{%
673 \unexpanded\expandafter{\svg@local@param@use}\unexpanded{#1}%
674 }%
675 }

```

The family member is defined for both `svg` and `svg-extract`.

```

676 (*body)
677 \DefineFamilyMember[.param]{SVG}
678 </body>

```

B.4. User commands

`\svgsetup` The macro `\svgsetup` can be used to change options after loading the package `svg` both in preamble and the document body. For compatibility reasons, `\setsvg` is also defined.

```

679 \newcommand*\svgsetup{\FamilyOptions{SVG}}
680 \newcommand*\setsvg{\FamilyOptions{SVG}}

```

`\svgpath` With `\svgpath` the user can give several root paths to SVG files in the same way as `\graphicspath` is used. The only difference is that a missing slash is added at the end of the path, if needed.

```

681 \newcommand*\svg@input@path{}
682 \let\svg@input@path\input@path
683 \newcommand*\svgpath[1]{%
684 \def\svg@tempa##1\@nil{%
685 \ifx\svg@tempb\bgroup%
686 \def\svg@input@path{#1}%
687 \else%
688 \def\svg@input@path{{#1}}%
689 \fi%
690 }%
691 \futurelet\svg@tempb\svg@tempa#1\@nil%
692 }

```

`\includesvg` For the inclusion of SVG files the command `\includesvg` is defined.

```

693 \newcommand*\includesvg[2] []{%
694 \begingroup%

```

Checking for deprecated commands `\svgwidth` and `\svgscale`.

```

695 \svg@deprecated@param%

```

`inkscape` (param.) Most of the optional parameters have the same effect as the identically named options.
`inkscapeformat` (param.) Only parameter `lastpage` is extended (see below). Moreover, there are some additional
`inkscapelatex` (param.) parameters, which can only be used as optional argument for `\includesvg` (`angle` and
`inkscapearea` (param.) `origin`) but not as an option. Now all parameters are set in local context (within a group).
`inkscapedpi` (param.)
`inkscapeopt` (param.)

```

696 \svg@local@param@set{#1}%

```

`svgextension` (param.)

`width` (param.)

`height` (param.)

`distort` (param.)

`scale` (param.)

`pretex` (param.)

`apptex` (param.)

`draft` (param.)

The file suffix used by both packages **svg** and **svg-extract**.

```
697 \if@svg@ink@latex%
698 \edef\svg@file@suffi{x}_{\svg@file@ext-tex}%
699 \else%
700 \edef\svg@file@suffi{x}_{\svg@file@ext-raw}%
701 \fi%
702 \@onelevel@sanitize\svg@file@suffi{x}%
```

Searching all given paths for the relevant SVG file.

```
703 \svg@get@path{#2}{}%
704 \if@svg@file@found%
```

Running the export with **Inkscape** (if necessary) and checking the required files for graphic inclusion.

```
705 \svg@ink@run%
706 \IfFileExists{\svg@out@base}{}%
707 \@svg@file@foundfalse%
708 \svg@file@missing{\svg@out@base}{\svg@file@base.\svg@file@ext}%
709 }%
710 \if@svg@ink@latex%
711 \IfFileExists{\svg@out@base_tex}{}%
712 \@svg@file@foundfalse%
713 \svg@file@missing{\svg@out@base_tex}{\svg@file@base.\svg@file@ext}%
714 }%
715 \fi%
```

Include the resulting graphic file and maybe extract independent files.

```
716 \if@svg@file@found%
717 \svg@input{\svg@out@base}%
718 \svg@extract{\svg@out@base}%
719 \fi%
720 \else%
```

Raise an error, if the requested SVG file wasn't found.

```
721 \svg@file@missing[\svg@file@ext]{\svg@file@base}{}%
722 \fi%
723 \endgroup%
724 }
```

lastpage (param.) In addition to the automatic finding of the last page, which is included, it can also be given directly as parameter.

```
725 \svg@local@param@def{%
726 \FamilyCounterKey[.param]{SVG}{lastpage}{svg@param@lastpage}%
727 }
```

angle (param.) **origin** (param.) The parameters **angle** and **origin** are defined as pendants to the keys provided by **\includegraphics**.

```
728 \newcommand*\svg@param@angle{0}
729 \svg@local@param@def{%
730 \DefineFamilyKey[.param]{SVG}{angle}{%
731 \ifisdimension{#1\p@}{%
732 \renewcommand*\svg@param@angle{#1}%
733 \FamilyKeyStateProcessed%
734 }%
735 }%
736 }
737 \newcommand*\svg@param@origin{c}
738 \svg@local@param@def{%
739 \DefineFamilyKey[.param]{SVG}{origin}[c]{%
```

```

740 \renewcommand*\svg@param@origin{#1}%
741 \FamilyKeyStateProcessed%
742 }%
743 }

```

`\includeinkscape` The command `\includeinkscape` can be used for including the export results of *Inkscape*, if this part of the job was done in another way.

```

744 \newcommand*\includeinkscape[2] [] {%
745 \beginngroup%

```

Checking for deprecated commands `\svgwidth` and `\svgscale`.

```

746 \svg@deprecated@param%

```

The given file extension is examined, where a known extension overwrites the current setting for `inkscapeformat`. If there's a suffix `_tex`, the option `inkscapecatex` is set to `true` by default.

```

747 \svg@filename@parse{#2}%
748 \ifx\filename@ext\relax\else%
749 \svg@quotes@remove{\filename@ext}%
750 \expandafter\lowercase\expandafter{%
751 \expandafter\def\expandafter\filename@ext\expandafter{\filename@ext}%
752 }%
753 \def\svg@tempb##1_tex##2\@nil{%
754 \IfArgIsEmpty{##1}{\def\filename@ext{##1}}%
755 \ifstr{##2}{_tex}{\@svg@tempswatruetrue}{\@svg@tempswafalse}%
756 }%
757 \@svg@tempswafalse%
758 \@tfor\svg@tempa:={pdf}{eps}{ps}{png}\do{%
759 \beginngroup%
760 \expandafter\svg@tempb\filename@ext_tex\@nil%
761 \svg@extension@parse{\svg@tempa}%
762 \ifx\filename@ext\relax%
763 \def\svg@tempb{\endgroup}%
764 \else%
765 \edef\svg@tempb{%
766 \endgroup%
767 \noexpand\FamilyOptions{SVG}{inkscapeformat=\svg@tempa}%
768 \if@svg@tempswa%
769 \noexpand\FamilyOptions{SVG}{inkscapecatex=true}%
770 \fi%
771 \def\noexpand\filename@base{\filename@base}%
772 \def\noexpand\filename@ext{\filename@ext}%
773 \noexpand\@svg@tempswatruetrue%
774 }%
775 \fi%
776 \svg@tempb%

```

Break for loop, if valid extension was found.

```

777 \if@svg@tempswa%
778 \break@tfor%
779 \fi%
780 }%

```

If no valid extension was found, it is set to the specified format and the actual found one is appended to `cssvg.dtx@base`.

```

781 \if@svg@tempswa\else%
782 \svg@extension@parse{\svg@ink@format}%
783 \fi%
784 \fi%

```

`inkscapeformat` (param.) Parameters, which are supported by `\includesvg`, can also be used with `\includeinkscape`
`inkscapelatex` (param.) even if some of them—more precisely those that control the export with *Inkscape*—don't
`width` (param.) have an effect at all. Nevertheless, they are set right now in local context (within a group).
`height` (param.)
`distort` (param.) 785 `\svg@local@param@set{#1}%`
`scale` (param.)
`pretex` (param.) Searching all given paths for the relevant PDF/EPS file.
`apptex` (param.)
`draft` (param.) 786 `\svg@get@path[\svg@ink@format]{\filename@area\filename@base}{\svg@out@path}%`
`lastpage` (param.) 787 `\if@svg@file@found%`
`angle` (param.)
`origin` (param.) Checking the required files for graphic inclusion.

```
788 \edef\svg@out@name{\svg@file@name}%
789 \edef\svg@out@base{\svg@file@path\svg@file@name.\svg@ink@format}%
790 \if@svg@ink@latex%
791 \IfFileExists{\svg@out@base_tex}{-}{%
792 \@svg@file@foundfalse%
793 \svg@file@missing{\svg@out@base_tex}{\svg@out@base}%
794 }%
795 \fi%
```

Include the resulting graphic file and maybe extract independent files.

```
796 \if@svg@file@found%
797 \svg@input{\svg@out@base}%
798 \svg@extract{\svg@out@base}%
799 \fi%
800 \else%
```

Raise an error, if the requested PDF/EPS file wasn't found.

```
801 \svg@file@missing[\svg@ink@format]{\svg@file@base}{\svg@out@path}%
802 \fi%
803 \endgroup%
804 }
```

B.5. Auxiliary macros

`\svg@deprecated@param` This macro checks, if `\svgwidth` or `\svgscale` are defined. In this case, the given values are passed to the correlating parameters and a warning is raised.

```
805 \newcommand*\svg@deprecated@param{%
806 \@svg@tempswafalse%
807 \ifx\svgwidth\@undefined\else%
808 \edef\svg@tempa{\noexpand\FamilyOptions{SVG}{width=\svgwidth}}%
809 \svg@tempa%
810 \@svg@tempswatrue%
811 \fi%
812 \ifx\svgscale\@undefined\else%
813 \edef\svg@tempa{\noexpand\FamilyOptions{SVG}{scale=\svgscale}}%
814 \svg@tempa%
815 \@svg@tempswatrue%
816 \fi%
817 \if@svg@tempswa%
818 \PackageWarning{svg}{%
819 You should specify the image size with parameters\MessageBreak%
820 'width' and 'height' or 'scale' instead of using\MessageBreak%
821 '\string\svgscale' or '\string\svgwidth'%
822 }%
823 \let\svgwidth\@undefined%
824 \let\svgscale\@undefined%
825 \fi%
826 }
```


`\svg@ink@run` The command, which performs the call of *Inkscape* via `\ShellEscape`.
`\if@svg@ink@run`

```
827 \newif\if@svg@ink@run
828 \newcommand*\svg@ink@run{%
829   \ifnum\svg@ink@mode>\z@\relax%
830     \begingroup%
```

If the mode for *inkscape* was set to *forced*, *Inkscape* will be called in any case. Otherwise, some checks are performed to detect, if a run of *Inkscape* is actually necessary.

```
831   \@svg@ink@runtrue%
832   \ifnum\svg@ink@mode=\tw@\relax\else%
```

This is the case when the SVG file is newer than the corresponding exported file, or if the latter isn't present at all.

```
833     \svg@iffilenewer{\svg@file@base.\svg@file@ext}{\svg@out@base}{-}{%
834       \svg@ink@runfalse%
835     }%
```

The same is true, when the associated L^AT_EX file is missing. But when this file already exists, maybe the user did some changes to this file. In this case, overwriting this file is maybe not intended.

```
836     \if@svg@ink@latex%
837       \IfFileExists{\svg@out@base_tex}{%
838         \ifnum\pdf@shellescape=\@ne\relax\if@svg@ink@run%
839           \svg@iffilenewer{\svg@out@base_tex}{\svg@out@base}{-}{%
840             \@svg@ink@runfalse%
841             \svg@quotes@remove[\svg@out@base]{\svg@tempa}%
842             \PackageWarning{svg}{%
843               Since the encountered filedate of file\MessageBreak%
844               ‘\svg@tempa_tex’ is newer than \MessageBreak%
845               ‘\svg@tempa’ it’s supposed that\MessageBreak%
846               you customized this file. To avoid an accidental\MessageBreak%
847               overwriting of this file, the Inkscape export\MessageBreak%
848               won’t be done. If you want to overwrite the\MessageBreak%
849               existing file please choose the parameter\MessageBreak%
850               ‘inkscape=force’%
851             }%
852           }-}{%
853         \fi\fi%
854       }{\@svg@ink@runtrue}%
855     \fi%
856   \fi%
```

If all checks were positive, the export with *Inkscape* can be done in case `--shell-escape` is enabled.

```
857     \if@svg@ink@run%
858     \ifnum\pdf@shellescape=\@ne\relax%
```

For exporting PNG files, the used density ist set to 300dpi, if no value was given.

```
859     \ifx\svg@ink@dpi\relax%
860       \ifstr{\svg@ink@format}{png}{%
861         \FamilyOptions{SVG}{inkscape=300}%
862       }-}{%
863     \fi%
864     \PackageInfo{svg}{%
865       Calling Inkscape%
866       \ifx\svg@ink@opt\@empty\else%
867         \space with added options ‘\svg@ink@opt’%
868     \fi%
869   }%
```

Executing *Inkscape* on command line. Afterwards, the export results are moved into the given output path.

```

870     \svg@quotes@remove[\svg@file@base]{\svg@tempa}%
871     \svg@quotes@remove[\svg@out@name]{\svg@tempb}%
872     \ShellEscape{\svg@ink@cmd{\svg@tempa}{\svg@tempb}}%
873     \IfFileExists{\svg@out@name.\svg@ink@format}{%
874         \edef\svg@tempb{\svg@tempb.\svg@ink@format}%
875         \svg@quotes@remove{\svg@out@base}%
876         \svg@shell@mkdir{\svg@out@path}%
877         \svg@shell@move{\svg@tempb}{\svg@out@base}%
878         \if@svg@ink@latex%
879             \svg@shell@move{\svg@tempb_tex}{\svg@out@base_tex}%
880         \fi%
881     }{%
882         \PackageWarning{svg}{%
883             The export with Inkscape failed for file\MessageBreak%
884             ‘\svg@tempa.\svg@file@ext’\MessageBreak%
885             Troubleshooting: Please check in the log file how\MessageBreak%
886             the invocation of Inkscape took place and try to\MessageBreak%
887             execute it yourself in the terminal%
888         }%
889     }%

```

If `--shell-escape` wasn't enabled, a warning is issued.

```

890     \else%
891         \svg@quotes@remove[\svg@file@base]{\svg@tempa}%
892         \PackageWarning{svg}{%
893             You didn't enable 'shell escape' (or 'write18')\MessageBreak%
894             so it wasn't possible to launch the Inkscape export\MessageBreak%
895             for ‘\svg@tempa.\svg@file@ext’%
896         }%
897     \fi%
898 \fi%
899 \endgroup%
900 \fi%
901 }

```

`\svg@ink@cmd` The actual call of *Inkscape* at command line.

```

902 \newcommand*\svg@ink@cmd[2]{%
903     \svg@ink@exe\space-z\space\svg@ink@area\space%
904     \ifx\svg@ink@dpi\relax\else--export-dpi=\svg@ink@dpi\space\fi%
905     \if@svg@ink@latex--export-latex\space\fi%
906     \svg@ink@opt\space%
907     --file="#1.\svg@file@ext"\space%
908     --export-\svg@ink@format="#2.\svg@ink@format"\space%
909 }

```

`\svg@get@lastpage` This macro is used to circumvent the multiple pages bug for PDF files of *Inkscape* 0.91, when the the L^AT_EX export was enabled. For this purpose, the total page number is read from the PDF file.

```

910 \newcommand*\svg@get@lastpage[1]{%
911     \ifstr{\svg@ink@format}{pdf}{%
912         \begingroup%
913             \@tempcnta=\m@ne\relax%
914             \ifx\XeTeXpdfpagecount\undefined%
915                 \ifpdf%
916                     \ifx\pdfximage\undefined%
917                         \ifx\saveimageresource\undefined\else%
918                             \saveimageresource{#1}%
919                             \@tempcnta=\lastsavedimageresourcepages\relax%
920                         \fi%

```

```

921         \else%
922         \pdfximage{#1}%
923         \@tempcnta=\pdfastximagepages\relax%
924         \fi%
925     \fi%
926 \else%
927     \@tempcnta=\XeTeXpdfpagecount#1\relax%
928 \fi%
929 \ifnum\@tempcnta=\m@ne\relax%
930     \PackageWarning{svg}{%
931         It wasn't possible to detect the last page\MessageBreak%
932         of '#1'%
933     }%
934 \else%
935     \PackageInfo{svg}{Last page of '#1' is \the\@tempcnta}%
936 \fi%
937 \edef\svg@tempa{%
938     \endgroup%
939     \noexpand\FamilyOptions{SVG}{lastpage=\the\@tempcnta}%
940 }%
941 \svg@tempa%
942 }{}%
943 }

```

`\svg@wrn@scale` The option `scale` respectively the parameter `scale` is only considered if the size was not specified.

```

944 \newcommand*\svg@wrn@scale{%
945     \ifdim\dimexpr\svg@param@scale\p@\relax=\p@\relax\else%
946         \@svg@tempswafalse%
947         \ifdim\svg@param@width>\z@\relax%
948             \@svg@tempswatruetrue%
949         \fi%
950         \ifdim\svg@param@height>\z@\relax%
951             \@svg@tempswatruetrue%
952         \fi%
953     \if@svg@tempswa%
954         \PackageWarning{svg}{%
955             The parameter 'scale' is only considered if neither\MessageBreak%
956             'width' nor 'height' are specified%
957         }%
958     \fi%
959 \fi%
960 }

```

`\svg@input` With `\svg@@input` the export results of **Inkscape** are included. The macro `\svg@input` is defined in order to realize the option `exclude` for package **svg-extract**. The macro `\svg@set@input@path` is called to support commands like `\input{tex filename}` within SVG files.

```

961 \newcommand*\svg@input{\svg@@input}
962 \newcommand*\svg@@input [2] [] {%
963     \IfArgIsEmpty{#1}{\svg@local@param@set{#1}}%
964     \svg@set@input@path%
965     \if@svg@draft%
966         \@svg@ink@latexfalse%
967     \fi%

```

In order to support file names with multiple dots, the second argument is parsed and only the part after the last dot is stored in `\svg@tempb` as extension. Everything before is stored in `\svg@tempa`.

```

968 \def\svg@tempb##1.##2\@nil{%
969     \IfArgIsEmpty{##2}{%
970         \def\svg@tempb{##1}%

```

```

971   }{%
972     \edef\svg@tempa{\svg@tempa.##1}%
973     \svg@tempb##2\nil%
974   }%
975 }%
976 \edef\svg@tempa{%
977   \def\noexpand\svg@tempa{%}
978   \noexpand\svg@tempb#2.\noexpand\nil%
979 }%
980 \svg@tempa%

```

Afterwards `\svg@tempa` is defined with the file name itself within enclosing braces followed by the extension and `\svg@tempb` holds the original file name plus extension without enclosing braces.

```

981 \svg@remove@leadingchar.\svg@tempa%
982 \edef\svg@tempa{\svg@tempa}.\svg@tempb}%
983 \edef\svg@tempb{#2}%

```

If the export with *Inkscape* was done with L^AT_EX support enabled, the corresponding file will be used together with `\input`. The necessary patches to environment `picture` as well as command `\includegraphics` are made beforehand with `\svg@patches`.

```

984 \if@svg@ink@latex%
985   \svg@patches{\svg@tempa}%
986   \ifnum\value{svg@param@lastpage}=\z@\relax%
987     \expandafter\svg@get@lastpage\expandafter{\svg@tempb}%
988   \fi%
989   \edef\svg@tempa{%
990     \ifx\svg@param@pretex\relax\else%
991       \noexpand\svg@param@pretex%
992     \fi%
993     \noexpand\input{\svg@tempb_tex}%
994     \ifx\svg@param@apptex\relax\else%
995       \noexpand\svg@param@apptex%
996     \fi%
997   }%

```

If `distort=true` is desired, the input is resized with `\resizebox*`.

```

998   \if@svg@param@distort%
999     \def\svg@tempb{\resizebox*{\svg@param@width}{\svg@param@height}}%
1000   \else%
1001     \let\svg@tempb\@firstofone%
1002   \fi%
1003   \sbox\svg@box{\svg@tempb{\svg@tempa}}%

```

If a rotation angle was given, the input is done within `\rotatebox`.

```

1004   \ifdim\dimexpr\svg@param@angle\p@\relax=\z@\relax%
1005     \let\svg@tempb\@firstofone%
1006   \else%
1007     \edef\svg@tempb{%
1008       \noexpand\rotatebox[origin=\svg@param@origin]{\svg@param@angle}%
1009     }%
1010   \fi%
1011   \svg@tempb{\usebox\svg@box}%
1012 \else%

```

If the export with *Inkscape* was done without L^AT_EX support, the resulting graphic file will be included with `\includegraphics`.

```

1013 \svg@wrn@scale%
1014 \edef\svg@tempb{%
1015   draft\if@svg@draft\else=false\fi,%
1016   scale=\svg@param@scale,%
1017   keepaspectratio\if@svg@param@distort=false\fi%

```

```

1018 }%
1019 \ifdim\svg@param@height>\z@\relax%
1020   \edef\svg@tempb{\svg@tempb,height=\svg@param@height}%
1021 \fi%
1022 \ifdim\svg@param@width>\z@\relax%
1023   \edef\svg@tempb{\svg@tempb,width=\svg@param@width}%
1024 \fi%
1025 \ifdim\dimexpr\svg@param@angle\p@\relax=\z@\relax\else%
1026   \edef\svg@tempb{%
1027     \svg@tempb,origin=\svg@param@origin,angle=\svg@param@angle%
1028   }%
1029 \fi%
1030 \expandafter\includegraphics\expandafter[\svg@tempb]{\svg@tempa}%
1031 \fi%
1032 }

```

B.6. Patches

`\svg@patches` For including the export results from *Inkscape* with L^AT_EX support enabled, there are some patches necessary for environment `picture` and `\includegraphics`. Those patches are done with `\svg@patches`.

`\svg@picture@saved`

```

1033 \newcommand*\svg@picture@saved{}
1034 \let\svg@picture@saved\picture
1035 \newcommand*\svg@includegraphics@saved{}
1036 \let\svg@includegraphics@saved\includegraphics
1037 \newcommand*\svg@patches[1]{%
1038   \let\picture\svg@picture@patched%
1039   \let\includegraphics\svg@includegraphics@patched%
1040   \edef\svg@includegraphics@file{#1}%
1041 }

```

`\svg@pictur@patched` In order to provide the possibility specify the desired width of a graphic, the appropriate `\unitlength` is calculated at the beginning of the `picture` environment.

```

1042 \newcommand*\svg@picture@patched{}
1043 \newcommand*\svg@pictur@patched{}
1044 \long\def\svg@picture@patched#1{\svg@pictur@patched@#1}
1045 \def\svg@pictur@patched@(#1,#2){%
1046   \svg@wrn@scale%

```

If a desired height is present, the resulting `\unitlength` is calculated with the ratio of the coordinates of the `picture` environment given as arguments for x- and y-direction by using `\Gscale@div`. With this factor, `\unitlength`—which is connected to the x-coordinate—can be scaled in a suitable manner.

```

1047 \ifdim\svg@param@height>\z@\relax%
1048   \Gscale@div\svg@tempa{#1\p@}{#2\p@}%
1049   \setlength\unitlength{\svg@param@height}%
1050   \setlength\unitlength{\svg@tempa\unitlength}%
1051 \ifdim\svg@param@width>\z@\relax%
1052   \ifdim\unitlength>\svg@param@width\relax%
1053     \setlength\unitlength{\svg@param@width}%
1054   \fi%
1055 \fi%
1056 \else%

```

If no height is given, `\unitlength` can be set easily.

```

1057 \ifdim\svg@param@width>\z@\relax%
1058   \setlength\unitlength{\svg@param@width}%
1059 \else%
1060   \setlength\unitlength{\svg@param@scale\unitlength}%
1061 \fi%
1062 \fi%

```

After setting `\unitlength`, the `picture` environment can be called with its original definition.

```
1063 \svg@picture@saved(#1,#2)%
1064 }
```

`\svg@includegraphics@patched` The patch to `\includegraphics` is meant to dissolve the *Inkscape* bug concerning the inclusion of more PDF pages than actually are existing.

`\svg@includegraphics@file`

The given optional parameters to `\includegraphics` are processed and the counter `svg@param@currpage` is set to the value of a given `page`. The value of parameter `width` is ignored.

```
1065 \DefineFamily{SVGpatch}
1066 \DefineFamilyMember{SVGpatch}
1067 \newcounter{svg@param@currpage}
1068 \setcounter{svg@param@currpage}{\m@ne}
1069 \FamilyCounterKey{SVGpatch}{page}{svg@param@currpage}
1070 \DefineFamilyKey{SVGpatch}{width}{\FamilyKeyStateProcessed}
1071 \newcommand*\svg@includegraphics@file{}
1072 \newcommand*\svg@includegraphics@patched[2] []{%
1073 \FamilyOptions{SVGpatch}{#1}%
```

If option `lastpage` was set to `false`, each page is included—even if it doesn’t exist, which may cause errors.

```
1074 \ifnum\value{svg@param@lastpage}<\z@ \relax%
1075 \FamilySetCounter{SVGpatch}{page}{svg@param@currpage}{%
1076 \the\value{svg@param@lastpage}%
1077 }%
1078 \fi%
```

Only if counter `svg@param@lastpage` is smaller than `svg@param@currpage`, pages are included, where `svg@param@lastpage` was either given as a number with parameter `lastpage` or was automatically calculated with `\svg@get@lastpage`.

```
1079 \ifnum\value{svg@param@currpage}>\value{svg@param@lastpage} \relax \else%
```

A page is included with the original definition of `\includegraphics`. All optional parameters are passed.

```
1080 \svg@includegraphics@saved[#{#1}]{\svg@includegraphics@file}%
1081 \fi%
1082 }
```

C. Extracting independent graphic files with `svg-extract`

C.1. Options

For package `svg-extract` the user interface is extended. The following options can either be set with `\svgsetup` or be used as local optional parameters for `\includesvg` and `\includeinkscape`.

`\svg@dummys@key` If package `svg-extract` wasn’t loaded, the following options are defined for package `svg` in order to raise a warning message. Primarily this is done for compatibility reasons.

```
1083 (*base)
1084 \DefineFamilyMember[.dummy]{SVG}
1085 \newcommand*\svg@dummys@key[2] []{%
1086 \@ifpackageloaded{svg-extract}{}{%
1087 \IfArgIsEmpty{#1}{%
1088 \DefineFamilyKey[.dummy]{SVG}{#2}{%
1089 \PackageWarning{svg}{%
1090 The option key ‘#2’ can only\MessageBreak%
```

```

1091         be used with package ‘svg-extract’, but\MessageBreak%
1092         you didn’t load it%
1093     }%
1094     \FamilyKeyStateProcessed%
1095 }%
1096 }{%
1097     \DefineFamilyKey[.dummy]{SVG}{#2}[{#1}] {%
1098     \PackageWarning{svg}{%
1099         The option key ‘#2’ can only\MessageBreak%
1100         be used with package ‘svg-extract’, but\MessageBreak%
1101         you didn’t load it%
1102     }%
1103     \FamilyKeyStateProcessed%
1104 }%
1105 }%

```

Before package **svg-extract** the given key #2 of family member .dummy is relaxed.

```

1106     \AfterPackage{svg-extract}{\RelaxFamilyKey[.dummy]{SVG}{#2}}%
1107 }%
1108 }
1109 </base>

```

C.1.1. Controlling the extract process

extract (opt.) With option **extract** it can be controlled, if the extraction of independent graphic files should be done.

```

1110 <*base>
1111 \svg@dummy@key[true]{extract}
1112 </base>
1113 <*extract>
1114 \newif\if@svgx@run
1115 \DefineFamilyKey{SVG}{extract}[true]{%
1116     \lowercase{\def\svg@tempa{#1}}%
1117     \FamilySetNumerical{SVG}{extract}{svg@tempa}{%
1118         {false}{0},{off}{0},{no}{0},%
1119         {true}{1},{on}{1},{yes}{1},{onlynewer}{1},{newer}{1},%
1120         {overwrite}{1},{force}{1},{forced}{1},%
1121         {pdf}{2},{eps}{3},{ps}{4}}%
1122 }{\svg@tempa}%
1123 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1124     \ifcase\svg@tempa\relax% false
1125         \@svgx@runfalse%
1126     \or% true
1127         \@svgx@runtrue%
1128     \or% pdf
1129         \FamilyOptions{SVG}{extractformat=pdf}%
1130     \or% eps
1131         \FamilyOptions{SVG}{extractformat=eps}%
1132     \or% ps
1133         \FamilyOptions{SVG}{extractformat=ps}%
1134     \fi%
1135 \fi%
1136 }
1137 </extract>

```

on (opt.) Package options which can be used to switch functionality on or off during the loading of package **svg-extract**.

```

1138 <*extract>
1139 \DeclareOption{on}{\FamilyOptions{SVG}{extract=true}}
1140 \DeclareOption{off}{\FamilyOptions{SVG}{extract=false}}
1141 </extract>

```

`extractformat` (opt.) Option `extractformat` controls the output format (pdf/eps/ps). It is set to pdf or, if dvi output could be detected, to eps during initialization.

`\svgx@format`

pdf (opt.)

eps (opt.)

```

1142 < *base>
1143 \svg@dummys@key{extractformat}
1144 \svg@dummys@key[true]{pdf}
1145 \svg@dummys@key[true]{eps}
1146 < /base>
1147 < *extract>
1148 \newcommand*\svgx@format{pdf}
1149 \ifxetex\else\ifpdf\else
1150 \renewcommand*\svgx@format{eps}
1151 \fi\fi
1152 \DefineFamilyKey{SVG}{extractformat}{%
1153 \lowercase{\edef\svgx@format{#1}}%
1154 \FamilyKeyStateProcessed%
1155 }
1156 \DefineFamilyKey{SVG}{pdf}[true]{%
1157 \FamilySetBool{SVG}{pdf}{@svg@tempswa}{#1}%
1158 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1159 \if@svg@tempswa%
1160 \svgx@ifinlist{pdf}{\svgx@format}{}%
1161 \edef\svgx@format{\svgx@format,pdf}%
1162 }%
1163 \svg@deprecated@key{pdf}{extractformat={\svgx@format}}%
1164 \else%
1165 \FamilyKeyStateUnknownValue%
1166 \fi%
1167 \fi%
1168 }
1169 \DefineFamilyKey{SVG}{eps}[true]{%
1170 \FamilySetBool{SVG}{eps}{@svg@tempswa}{#1}%
1171 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1172 \if@svg@tempswa%
1173 \svgx@ifinlist{eps}{\svgx@format}{}%
1174 \edef\svgx@format{\svgx@format,eps}%
1175 }%
1176 \svg@deprecated@key{eps}{extractformat={\svgx@format}}%
1177 \else%
1178 \FamilyKeyStateUnknownValue%
1179 \fi%
1180 \fi%
1181 }
1182 < /extract>

```

`extractpreamble` (opt.) For the extraction process, a preamble is necessary for a separate auxiliary L^AT_EX file.

`preamble` (opt.) By default, the preamble of the main document is used, which end is detected at

`\svgx@preamble` `\begin{document}`.

`extractpreambleend` (opt.)

`end` (opt.)

`\svgx@endpreamble`

```

1183 < *base>
1184 \svg@dummys@key{extractpreamble}
1185 \svg@dummys@key{preamble}
1186 \svg@dummys@key{extractpreambleend}
1187 \svg@dummys@key{end}
1188 < /base>
1189 < *extract>
1190 \newcommand*\svgx@preamble{\jobname.\svgx@latex@ext}%
1191 \DefineFamilyKey{SVG}{extractpreamble}{%
1192 \renewcommand*\svgx@preamble{#1}%
1193 \FamilyKeyStateProcessed%
1194 }
1195 \DefineFamilyKey{SVG}{preamble}{%
1196 \svg@deprecated@key[svg-extract]{preamble=#1}{extractpreamble=#1}%
1197 }
1198 \newcommand*\svgx@endpreamble{}

```



```

1199 \expandafter\def\expandafter\svgx@endpreamble\expandafter{%
1200 \csname begin\endcsname{document}%
1201 }
1202 \DefineFamilyKey{SVG}{extractpreambleend}{%
1203 \renewcommand*\svgx@endpreamble{#1}%
1204 \FamilyKeyStateProcessed%
1205 }
1206 \DefineFamilyKey{SVG}{end}{%
1207 \svg@deprecated@key[svg-extract]{end=#1}{extractpreambleend=#1}%
1208 }
1209 \extract)

```

extractruns (opt.) With this option, the number of L^AT_EX runs for the separate auxiliary file can be set.
svgx@runs (counter)

```

1210 (*base)
1211 \svg@dummy@key{extractruns}
1212 \base)
1213 (*extract)
1214 \newcounter{svgx@runs}
1215 \DefineFamilyKey{SVG}{extractruns}{%
1216 \FamilySetCounter{SVG}{extractruns}{svgx@runs}{#1}%
1217 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1218 \ifnum\value{svgx@runs}<\@ne\relax%
1219 \PackageWarning{svg-extract}{%
1220 The count for runs has to be at least one%
1221 }%
1222 \FamilySetCounter{SVG}{extractruns}{svgx@runs}{\@ne}%
1223 \fi%
1224 \fi%
1225 }
1226 \extract)

```

latexexe (opt.) The command and facultative options for the L^AT_EX call of the separate auxiliary file. The
pdflatex (opt.) default is set according to the currently used compiler.

```

\svgx@latex@exe
1227 (*base)
latexext (opt.) 1228 \svg@dummy@key{latexexe}
\svgx@latex@ext 1229 \svg@dummy@key{pdflatex}
latexopt (opt.) 1230 \svg@dummy@key{latexext}
\svgx@latex@opt 1231 \svg@dummy@key{latexopt}
1232 \base)
1233 (*extract)
1234 \ifxetex
1235 \newcommand*\svgx@latex@exe{xelatex}
1236 \else\ifluatex
1237 \ifpdf
1238 \newcommand*\svgx@latex@exe{lualatex}
1239 \else
1240 \newcommand*\svgx@latex@exe{lualatex --output-format=dvi}
1241 \fi
1242 \else\ifpdf
1243 \newcommand*\svgx@latex@exe{pdflatex}
1244 \else
1245 \newcommand*\svgx@latex@exe{latex}
1246 \fi\fi\fi
1247 \DefineFamilyKey{SVG}{latexexe}{%
1248 \renewcommand*\svgx@latex@exe{#1}%
1249 \FamilyKeyStateProcessed%
1250 }
1251 \DefineFamilyKey{SVG}{pdflatex}{%
1252 \svg@deprecated@key[svg-extract]{pdflatex=#1}{latexexe=#1}%
1253 }
1254 \newcommand*\svgx@latex@ext{tex}
1255 \DefineFamilyKey{SVG}{latexext}{%
1256 \renewcommand*\svgx@latex@ext{#1}%

```

```

1257 \FamilyKeyStateProcessed%
1258 }
1259 \newcommand*{svgx@latex@opt{}}
1260 \DefineFamilyKey{SVG}{latexopt}{%
1261 \renewcommand*{svgx@latex@opt{#1}}%
1262 \FamilyKeyStateProcessed%
1263 }
1264 </extract>

dvipsopt (opt.) Options and macros for calling convert commands, which are supplied by most LATEX 2ε distri-
\svgx@dvips@exe butions. These are used to generate all files, which are supported by option extractformat,
\svgx@dvips@opt as they don't need an additional application.
pstoeps (opt.)
\svgx@pstoeps@exe 1265 (*base)
\svgx@pstoeps@opt 1266 \svg@dummy@key{dvipsopt}
pstopdf (opt.) 1267 \svg@dummy@key{pstoeps}
\svgx@pstopdf@exe 1268 \svg@dummy@key{pstopdf}
\svgx@pstopdf@opt 1269 \svg@dummy@key{pdftoeps}
pdftoeps (opt.) 1270 \svg@dummy@key{pdftops}
\svgx@pdftoeps@exe 1271 \svg@dummy@key{pdftops}
\svgx@pdftoeps@opt 1272 </base>
pdftops (opt.) 1273 (*extract)
\svgx@pdftops@exe 1274 \newcommand*{svgx@dvips@exe{dvips}}
\svgx@pdftops@opt 1275 \newcommand*{svgx@dvips@opt{}}
\svgx@pdftops@opt 1276 \DefineFamilyKey{SVG}{dvipsopt}{%
pdftops (opt.) 1277 \renewcommand*{svgx@dvips@opt{#1}}%
1278 \FamilyKeyStateProcessed%
1279 }
1280 \newcommand*{svgx@pstoeps@exe{ps2eps}}
1281 \newcommand*{svgx@pstoeps@opt{-B -C}}
1282 \DefineFamilyKey{SVG}{pstoeps}{%
1283 \renewcommand*{svgx@pstoeps@opt{#1}}%
1284 \FamilyKeyStateProcessed%
1285 }
1286 \newcommand*{svgx@pstopdf@exe{ps2pdf}}
1287 \newcommand*{svgx@pstopdf@opt{}}
1288 \DefineFamilyKey{SVG}{pstopdf}{%
1289 \renewcommand*{svgx@pstopdf@opt{#1}}%
1290 \FamilyKeyStateProcessed%
1291 }
1292 \newcommand*{svgx@pdftoeps@exe{pdftops -eps}}
1293 \newcommand*{svgx@pdftoeps@opt{}}
1294 \DefineFamilyKey{SVG}{pdftoeps}{%
1295 \renewcommand*{svgx@pdftoeps@opt{#1}}%
1296 \FamilyKeyStateProcessed%
1297 }
1298 \newcommand*{svgx@pdftops@exe{pdftops}}
1299 \newcommand*{svgx@pdftops@opt{}}
1300 \DefineFamilyKey{SVG}{pdftops}{%
1301 \renewcommand*{svgx@pdftops@opt{#1}}%
1302 \FamilyKeyStateProcessed%
1303 }
1304 \DefineFamilyKey{SVG}{pdftops}{%
1305 \PackageWarning{#1}{%
1306 The option key 'pdftops' is deprecated.\MessageBreak%
1307 You should use either 'pdftoeps' or\MessageBreak%
1308 'pdftops' instead. See the manual for\MessageBreak%
1309 more. Nothing was done%
1310 }%
1311 \FamilyKeyStateProcessed%
1312 }
1313 </extract>

```

C.1.2. Invoking external application for graphic conversion

Besides the use of a conversion tool supplied by L^AT_EX 2_ε, the applications *ImageMagick* and *Ghostscript* can be used for converting graphics.

`convert` (opt.) The option `convert` can be used to define, which of both applications should be use.
`\if@svgx@cnv@run` *ImageMagick* is set by default.
`\svgx@cnv@cmd`

```

1314 (*base)
1315 \svg@dumy@key[true]{convert}
1316 </base>
1317 (*extract)
1318 \newif\if@svgx@cnv@run
1319 \newcommand*\svgx@cnv@cmd{}
1320 \DefineFamilyKey{SVG}{convert}[true]{%
1321   \FamilySetNumerical{SVG}{convert}{svg@tempa}{%
1322     {false}{0},{off}{0},{no}{0},%
1323     {true}{1},{on}{1},{yes}{1},{onlynewer}{1},{newer}{1},%
1324     {overwrite}{1},{force}{1},{forced}{1},%
1325     {magick}{2},{imagemagick}{2},{convert}{2},%
1326     {gs}{3},{ghostscript}{3},%
1327     {gs64}{4},{ghostscript64}{4},%
1328     {gs32}{5},{ghostscript32}{5}%
1329   }{#1}%
1330 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1331   \ifcase\svg@tempa\relax% false
1332     \@svgx@cnv@runfalse%
1333   \or% true
1334     \@svgx@cnv@runtrue%
1335   \or% magick
1336     \@svgx@cnv@runtrue%
1337     \renewcommand*\svgx@cnv@cmd{\svgx@magick@cmd}%
1338   \or% gs
1339     \@svgx@cnv@runtrue%
1340     \renewcommand*\svgx@cnv@cmd{\svgx@gs@cmd}%
1341   \or% gs64
1342     \@svgx@cnv@runtrue%
1343     \renewcommand*\svgx@cnv@cmd{\svgx@gs@cmd}%
1344     \svgx@onlywindows{%
1345       \renewcommand*\svgx@gs@exe{gswin64c}%
1346     }%
1347   \or% gs32
1348     \@svgx@cnv@runtrue%
1349     \renewcommand*\svgx@cnv@cmd{\svgx@gs@cmd}%
1350     \svgx@onlywindows{%
1351       \renewcommand*\svgx@gs@exe{gswin32c}%
1352     }%
1353   \fi%
```

In version v1.0 the option `convert` was used to set both the executable and options for the conversion application, meant for the usage of *ImageMagick*. This is taken into account here.

```
1354 \else%
```

Same doing like with option `inkscape`.

```

1355   \def\svg@tempa##1-##2\@nil{%
1356     \IfArgIsEmpty{##2}{\def\svg@tempb{}}{%
1357       \def\svg@tempa##1###1\@nil{\def\svg@tempb{###1}}%
1358     \svg@tempa#1\@nil%
1359   }%
1360   \def\svg@tempa{##1}%
1361 }%
1362 \svg@tempa#1-\@nil%
```

```

1363 \PackageWarning{svg-extract}{%
1364   Setting the executable%
1365   \ifx\svg@tempb\@empty\else%
1366     \space and associated options%
1367   \fi%
1368   \MessageBreak%
1369   for ImageMagick should be done with options\MessageBreak%
1370   ‘magickexe=\svg@tempa’%
1371   \ifx\svg@tempb\@empty\else%
1372     \MessageBreak and ‘magicksetting’ and/or ‘magickoperator’%
1373   \fi.\MessageBreak%
1374   Nevertheless, this was done by now%
1375   \ifx\svg@tempb\@empty\else%
1376     , whereby \MessageBreak ‘magicksetting=\svg@tempb’ was used%
1377   \fi%
1378 }%
1379 \FamilyOptions{SVG}{convert=magick}%
1380 \edef\svg@tempa{%
1381   \noexpand\FamilyOptions{SVG}{magickexe=\svg@tempa}%
1382   \ifx\svg@tempb\@empty\else%
1383     \noexpand\FamilyOptions{SVG}{magicksetting=\svg@tempb}%
1384   \fi%
1385 }%
1386 \svg@tempa%
1387 \fi%
1388 }
1389 </extract>

```

`convertformat` (opt.) Option `convertformat` controls the output format for converted files. It is set to `png` by default.

`\svgx@cnv@format`
`png` (opt.)

```

1390 (*base)
1391 \svg@dumy@key{convertformat}
1392 \svg@dumy@key[true]{png}
1393 </base>
1394 (*extract)
1395 \newcommand*\svgx@cnv@format{png}
1396 \DefineFamilyKey{SVG}{convertformat}{%
1397   \lowercase{\edef\svgx@cnv@format{#1}}%
1398   \ifx\svgx@cnv@format\@empty\else%
1399     \@svgx@cnv@runtrue%
1400   \fi%
1401   \FamilyKeyStateProcessed%
1402 }
1403 \DefineFamilyKey{SVG}{png}[true]{%
1404   \FamilySetBool{SVG}{png}{\svg@tempswa}{#1}%
1405   \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1406     \if@svg@tempswa%
1407       \svgx@ifinlist{png}{\svgx@cnv@format}{}%
1408       \edef\svgx@cnv@format{\svgx@cnv@format,png}%
1409     }%
1410     \svg@deprecated@key{png}{convertformat={\svgx@cnv@format}}%
1411   \else%
1412     \FamilyKeyStateUnknownValue%
1413   \fi%
1414 \fi%
1415 }
1416 </extract>

```

`convertdpi` (opt.) The option `convertdpi` is meant to define the used density during the conversion process. It can be set either for all designated output formats or targeted for a specific format. It’s also possible to use something like `500x300`. Given values are resolved by `\svgx@cnv@get@dpi`. It’s used like `convertdpi=300` or `convertdpi={png=600}` If the option is used for a specific or for all output formats is recognized by `\svgx@ifkeyandval`.

```

1417 (*base)
1418 \svg@dummy@key{convertdpi}
1419 \svg@dummy@key{convertdensity}
1420 (/base)
1421 (*extract)
1422 \newcommand*\svgx@cnv@dpi{}
1423 \let\svgx@cnv@dpi\relax
1424 \DefineFamilyKey{SVG}{convertdpi}{%
1425   \FamilyKeyStateUnknownValue%
1426   \svgx@ifkeyandval{#1}{%
1427     \svgx@cnv@get@dpi{##2}%
1428     \ifx\svg@tempa\relax\else%
1429       \expandafter\edef\csname svgx@cnv@dpi@##1\endcsname{\svg@tempa}%
1430       \FamilyKeyStateProcessed%
1431     \fi%
1432   }{%
1433     \svgx@cnv@get@dpi{##1}%
1434     \ifx\svg@tempa\relax\else%
1435       \edef\svgx@cnv@dpi{\svg@tempa}%
1436       \FamilyKeyStateProcessed%
1437     \fi%
1438   }%
1439 }
1440 \DefineFamilyKey{SVG}{convertdensity}{\FamilyOptions{SVG}{convertdpi=#1}}
1441 (/extract)

```

`magickexe` (opt.) Setting the command including maybe the path to **ImageMagick**. The keys `magicksetting` and `magickoperator` should be used to add optional arguments before (*Settings*) or after (*Operators*) the input file. They can either be set for all or a specific output format as like option `convertdpi`. For this `\svgx@setformatkey` is used.

```

\svgx@magick@exe
magicksetting (opt.)
\svgx@magick@set
magickoperator (opt.)
\svgx@magick@opr
1442 (*base)
1443 \svg@dummy@key{magickexe}
1444 \svg@dummy@key{magicksetting}
1445 \svg@dummy@key{magickoperator}
1446 (/base)
1447 (*extract)
1448 \newcommand*\svgx@magick@exe{}
1449 \DefineFamilyKey{SVG}{magickexe}{%
1450   \renewcommand*\svgx@magick@exe{#1}%
1451   \FamilyKeyStateProcessed%
1452 }
1453 \newcommand*\svgx@magick@set{}
1454 \DefineFamilyKey{SVG}{magicksetting}{%
1455   \svgx@setformatkey{#1}{\svgx@magick@set}%
1456   \FamilyKeyStateProcessed%
1457 }
1458 \newcommand*\svgx@magick@opr{}
1459 \DefineFamilyKey{SVG}{magickoperator}{%
1460   \svgx@setformatkey{#1}{\svgx@magick@opr}%
1461   \FamilyKeyStateProcessed%
1462 }
1463 (/extract)

```

`gsexe` (opt.) Options to set the command including maybe the path to **Ghostscript**. As **Ghostscript** needs a specific device defined for different output formats, the option `gsdevice` can be used. It can either be set for all or a specific output format just like `gsopt` in the same manner like option `convertdpi`.

```

\svgx@gs@exe
gsopt (opt.)
\svgx@gs@opt
gsdevice (opt.)
\svgx@gs@device
1464 (*base)
1465 \svg@dummy@key{gsexe}
1466 \svg@dummy@key{gsopt}
1467 \svg@dummy@key{gsdevice}
1468 (/base)
1469 (*extract)

```

```

1470 \newcommand*{svgx@gs@exe{}}
1471 \DefineFamilyKey{SVG}{gsexe}{%
1472   \renewcommand*{svgx@gs@exe{#1}}%
1473   \FamilyKeyStateProcessed%
1474 }
1475 \newcommand*{svgx@gs@opt{}}
1476 \DefineFamilyKey{SVG}{gsopt}{%
1477   \svgx@setformatkey{#1}{svgx@gs@opt}%
1478   \FamilyKeyStateProcessed%
1479 }
1480 \newcommand*{svgx@gs@device{}}
1481 \DefineFamilyKey{SVG}{gsdevice}{%
1482   \svgx@setformatkey{#1}{svgx@gs@device}%
1483   \FamilyKeyStateProcessed%
1484 }
1485 </extract>

```

C.1.3. Setting output folder

<pre> extractpath (opt.) path (opt.) extractname (opt.) name (opt.) \svgx@out@path \svgx@out@name \if@svgx@out@sec svgx@out@count (counter) </pre>	<p>The option <code>extractpath</code> controls, in which folder the results both of the extraction as well as the conversion of <i>ImageMagick</i> or <i>Ghostscript</i> will be located. With option <code>extractname</code> the name of the extracted and maybe converted file itself can be changed.</p> <pre> 1486 (*base) 1487 \svg@dummys@key{extractpath} 1488 \svg@dummys@key{path} 1489 \svg@dummys@key{extractname} 1490 \svg@dummys@key{name} 1491 </base> 1492 (*extract) 1493 \newcommand*{svgx@out@path{}} 1494 \DefineFamilyKey{SVG}{extractpath}{% 1495 \svg@sanitize@dq\svg@tempb{#1}% 1496 \FamilySetNumerical{SVG}{extractpath}{svg@tempa}{% 1497 {svgpath}{0},{svgdir}{0},% 1498 {svgsubpath}{1},{svgsubdir}{1},% 1499 {basepath}{2},{basedir}{2},{jobpath}{2},{jobdir}{2},% 1500 {basesubpath}{3},{basesubdir}{3},{jobsubpath}{3},{jobsubdir}{3}% 1501 }{\svg@tempb}% 1502 \ifx\FamilyKeyState\FamilyKeyStateProcessed% 1503 \ifcase\svg@tempa\relax% svgpath 1504 \renewcommand*{svgx@out@path{\svg@file@path}}% 1505 \or% svgsubpath 1506 \renewcommand*{svgx@out@path{\svg@file@path svg-extract}}% 1507 \or% basepath 1508 \renewcommand*{svgx@out@path{.}}% 1509 \or% basesubpath 1510 \renewcommand*{svgx@out@path{./svg-extract}}% 1511 \fi% 1512 \else% 1513 \edef\svgx@out@path{\svg@tempb}% 1514 \svg@normalize@path{\svgx@out@path}% 1515 \FamilyKeyStateProcessed% 1516 \fi% 1517 } 1518 \DefineFamilyKey{SVG}{path}{% 1519 \svg@deprecated@key[svg-extract]{path=#1}{extractpath=#1}% 1520 } 1521 \newcounter{svgx@out@count} 1522 \newcommand*{svgx@out@name{}} 1523 \newif\if@svgx@out@sec 1524 \DefineFamilyKey{SVG}{extractname}{% 1525 \svg@quotes@remove[#{1}]{\svg@tempb}% 1526 \FamilySetNumerical{SVG}{extractname}{svg@tempa}{% </pre>
--	--

```

1527     {filename}{0},{name}{0},%
1528     {filenamenumbered}{1},{namenumbered}{1},%
1529     {numberedfilename}{1},{numberedname}{1},%
1530     {numbered}{2},{section}{2},{numberedsection}{2},{sectionnumbered}{2}%
1531 }{\svg@tempb}%
1532 \@svgx@out@secfalse%
1533 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1534   \ifcase\svg@tempa\relax% filename
1535     \renewcommand*\svgx@out@name{\svg@out@name-extract}%
1536   \or% filenamenumbered
1537     \renewcommand*\svgx@out@name{\the\value{svgx@out@count}-\svg@out@name}%
1538   \or% numbered
1539     \renewcommand*\svgx@out@name{\the\value{svgx@out@count}-\svgx@out@sec}%
1540     \@svgx@out@sectrue%
1541   \fi%
1542 \else%
1543   \if@svg@quotes@found%
1544     \edef\svgx@out@name{"\svg@tempb"}%
1545   \else%
1546     \edef\svgx@out@name{\svg@tempb}%
1547   \fi%
1548   \FamilyKeyStateProcessed%
1549 \fi%
1550 }
1551 \DefineFamilyKey{SVG}{name}{%
1552   \svg@deprecated@key[svg-extract]{name=#1}{extractname=#1}%
1553 }
1554 </extract>

```

C.1.4. Options for the extraction of graphics

<pre> extractwidth (opt.) \svgx@param@width extractheight (opt.) \svgx@param@width extractdistort (opt.) extractkeepaspectratio (opt.) \svgx@param@distort extractscale (opt.) \svgx@param@scale </pre>	<p>For graphic extraction, the given settings regarding the size for inclusion can be overwritten with these options. Using <code>\relax</code> as value leads to resetting an option as unset, regardless of what was previously given. The value <code>inherit</code> means, that the actual option for including is used for extraction as well. This is the default setting.</p> <pre> 1555 (*base) 1556 \svg@dummys@key{extractwidth} 1557 \svg@dummys@key{extractheight} 1558 \svg@dummys@key{extractdistort} 1559 \svg@dummys@key{extractkeepaspectratio} 1560 \svg@dummys@key{extractscale} 1561 </base> 1562 (*extract) 1563 \newcommand*\svgx@param@width{\svg@param@width} 1564 \DefineFamilyKey{SVG}{extractwidth}{% 1565 \FamilyKeyStateUnknownValue% 1566 \svg@ifvalueisrelax{#1}{% 1567 \renewcommand*\svgx@param@width{\z@}% 1568 \FamilyKeyStateProcessed% 1569 }{% 1570 \ifstr{#1}{inherit}{% 1571 \renewcommand*\svgx@param@width{\svg@param@width}% 1572 \FamilyKeyStateProcessed% 1573 }{% 1574 \FamilySetLengthMacro{SVG}{extractwidth}{\svg@param@width}{#1}% 1575 \ifx\FamilyKeyState\FamilyKeyStateProcessed% 1576 \ifdim\svg@param@width<\z@\relax% 1577 \FamilyKeyStateUnknownValue% 1578 \fi% 1579 \fi% 1580 }% 1581 }% 1582 } </pre>
---	--

```

1583 \newcommand*{svgx@param@height}{\svg@param@height}
1584 \DefineFamilyKey{SVG}{extractheight}{%
1585   \FamilyKeyStateUnknownValue%
1586   \svg@ifvalueisrelax{#1}{%
1587     \renewcommand*{svgx@param@height}{\z@}%
1588     \FamilyKeyStateProcessed%
1589   }{%
1590     \ifstr{#1}{inherit}{%
1591       \renewcommand*{svgx@param@height}{\svg@param@height}%
1592       \FamilyKeyStateProcessed%
1593     }{%
1594       \FamilySetLengthMacro{SVG}{extractheight}{\svgx@param@height}{#1}%
1595       \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1596         \ifdim\svgx@param@height<\z@\relax%
1597           \FamilyKeyStateUnknownValue%
1598         \fi%
1599       \fi%
1600     }%
1601   }%
1602 }
1603 \newif\if@svgx@param@distort
1604 \DefineFamilyKey{SVG}{extractdistort}[true]{%
1605   \FamilyKeyStateUnknownValue%
1606   \svg@ifvalueisrelax{#1}{%
1607     \@svgx@param@distortfalse%
1608     \FamilyKeyStateProcessed%
1609   }{%
1610     \ifstr{#1}{inherit}{%
1611       \renewcommand*\if@svgx@param@distort{\if@svg@param@distort}%
1612       \FamilyKeyStateProcessed%
1613     }{%
1614       \FamilySetBool{SVG}{extractdistort}{@svgx@param@distort}{#1}%
1615     }%
1616   }%
1617 }
1618 \DefineFamilyKey{SVG}{extractkeepaspectratio}[true]{%
1619   \FamilySetBool{SVG}{extractkeepaspectratio}{@svg@tempswa}{#1}%
1620   \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1621     \if@svg@tempswa%
1622       \FamilyOptions{SVG}{extractdistort=false}%
1623     \else
1624       \FamilyOptions{SVG}{extractdistort=true}%
1625     \fi%
1626   \else%
1627     \FamilyOptions{SVG}{extractdistort=#1}%
1628   \fi%
1629 }
1630 \newcommand*{svgx@param@scale}{\svg@param@scale}
1631 \DefineFamilyKey{SVG}{extractscale}{%
1632   \FamilyKeyStateUnknownValue%
1633   \svg@ifvalueisrelax{#1}{%
1634     \renewcommand*{svgx@param@scale}{1}%
1635     \FamilyKeyStateProcessed%
1636   }{%
1637     \ifstr{#1}{inherit}{%
1638       \renewcommand*{svgx@param@scale}{\svg@param@scale}%
1639       \FamilyKeyStateProcessed%
1640     }{%
1641       \ifisdimension{#1\p@}{%
1642         \ifdim\dimexpr#1\p@\relax>\z@\relax%
1643           \renewcommand*{svgx@param@scale}{#1}%
1644           \FamilyKeyStateProcessed%
1645         \fi%
1646       }{%
1647         }%
1648     }%

```



```

1649 }
1650 </extract>

extractpretex (opt.) The similar hooks for executing code right before or after the graphic extraction.
\svgx@param@pretex
extractapptex (opt.)
\svgx@param@apptex
extractpostex (opt.)
1651 (*base)
1652 \svg@dummys@key{extractpretex}
1653 \svg@dummys@key{extractapptex}
1654 \svg@dummys@key{extractpostex}
1655 </base>
1656 (*extract)
1657 \newcommand*\svgx@param@pretex{\svg@param@pretex}
1658 \DefineFamilyKey{SVG}{extractpretex}{%
1659   \svg@ifvalueisrelax{#1}{%
1660     \let\svgx@param@pretex\relax%
1661   }{%
1662     \ifstr{#1}{inherit}{%
1663       \renewcommand*\svgx@param@pretex{\svg@param@pretex}%
1664     }{%
1665       \renewcommand*\svgx@param@pretex{#1}%
1666     }%
1667   }%
1668   \FamilyKeyStateProcessed%
1669 }
1670 \newcommand*\svgx@param@apptex{\svg@param@apptex}
1671 \DefineFamilyKey{SVG}{extractapptex}{%
1672   \svg@ifvalueisrelax{#1}{%
1673     \let\svgx@param@apptex\relax%
1674   }{%
1675     \ifstr{#1}{inherit}{%
1676       \renewcommand*\svgx@param@apptex{\svg@param@apptex}%
1677     }{%
1678       \renewcommand*\svgx@param@apptex{#1}%
1679     }%
1680   }%
1681   \FamilyKeyStateProcessed%
1682 }
1683 \DefineFamilyKey{SVG}{extractpostex}{%
1684   \svg@deprecated@key[svg-extract]{extractpostex=#1}{extractapptex=#1}%
1685 }
1686 </extract>

```

C.1.5. Miscellaneous options

`clean` (opt.) With option `clean` files generated during the extraction process can be deleted. Setting `true`
`clear` (opt.) will remove all files, `false` won't clear any file. Additionally, a specific file list of suffixes can
`\svgx@clean` be given.

```

1687 (*base)
1688 \svg@dummys@key[true]{clean}
1689 \svg@dummys@key[true]{clear}
1690 </base>
1691 (*extract)
1692 \newcommand*\svgx@clean{}
1693 \DefineFamilyKey{SVG}{clean}[true]{%
1694   \FamilySetBool{SVG}{clean}{@svg@tempswa}{#1}%
1695   \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1696     \if@svg@tempswa%
1697       \renewcommand*\svgx@clean{log,aux,dvi,out,ps,eps,pdf,\svgx@latex@ext}%
1698     \else%
1699       \renewcommand*\svgx@clean{}%
1700     \fi%
1701   \else%
1702     \renewcommand*\svgx@clean{#1}%

```

```

1703 \FamilyKeyStateProcessed%
1704 \fi%
1705 }
1706 \DefineFamilyKey{SVG}{clear}{\FamilyOptions{SVG}{clean=#1}}
1707 </extract>

```

`exclude` (opt.) If it is desired not to include but only extract graphics with package **svg-extract**, option `exclude` can be used.

```

1708 (*base)
1709 \svg@dummy@key[true]{exclude}
1710 </base>
1711 (*extract)
1712 \DefineFamilyKey{SVG}{exclude}[true]{%
1713 \FamilySetBool{SVG}{exclude}{@svg@tempswa}{#1}%
1714 \ifx\FamilyKeyState\FamilyKeyStateProcessed%
1715 \if@svg@tempswa%
1716 \renewcommand*{svg@input[2]}[%
1717 \if@svg@run\else%
1718 \PackageWarning{svg-extract}{%
1719 The image ‘#2’ was\MessageBreak%
1720 neither extracted nor included%
1721 }%
1722 \fi%
1723 }%
1724 \else%
1725 \renewcommand*{svg@input}{\svg@@input}%
1726 \fi%
1727 \fi%
1728 }
1729 </extract>

```

C.2. User commands

<code>\includesvg</code>	The parameters <code>angle</code> and <code>origin</code> are defined as pendants to the keys provided by <code>\includegraphics</code> .
<code>extract</code> (param.)	
<code>extractpreamble</code> (param.)	
<code>extractformat</code> (param.)	1730 (*extract)
<code>extractwidth</code> (param.)	1731 \newcommand*{svgx@param@angle{0}}
<code>extractheight</code> (param.)	1732 \svg@local@param@def{%
<code>extractdistort</code> (param.)	1733 \DefineFamilyKey[.param]{SVG}{extractangle}{%
<code>extractscale</code> (param.)	1734 \FamilyKeyStateUnknownValue%
<code>extractangle</code> (param.)	1735 \svg@ifvalueisrelax{#1}{%
<code>extractpretex</code> (param.)	1736 \renewcommand*{svgx@param@angle{0}}%
<code>extractapptex</code> (param.)	1737 \FamilyKeyStateProcessed%
<code>extractruns</code> (param.)	1738 }{%
<code>latexopt</code> (param.)	1739 \ifstr{#1}{inherit}{%
<code>convert</code> (param.)	1740 \renewcommand*{svgx@param@angle{svg@param@angle}}%
<code>convertformat</code> (param.)	1741 \FamilyKeyStateProcessed%
<code>convertdpi</code> (param.)	1742 }{%
<code>magicksetting</code> (param.)	1743 \ifisdimension{#1\p@}{%
<code>magickoperator</code> (param.)	1744 \renewcommand*{svgx@param@angle{#1}}%
<code>gsopt</code> (param.)	1745 \FamilyKeyStateProcessed%
<code>gsdevice</code> (param.)	1746 }{}}%
<code>clean</code> (param.)	1747 }%
<code>exclude</code> (param.)	1748 }%
<code>\includeinkscape</code>	1749 }%
<code>extract</code> (param.)	1750 }
<code>extractpreamble</code> (start)	1751 </extract>
<code>extractpreamble</code> (end)	

`extractpreamble` (start) Some dummies for package **svg**.

<code>extractpreamble</code> (end)	
<code>extractwidth</code> (param.)	1752 (*base)
<code>extractheight</code> (param.)	1753 \newcommand*{svghidepreamblestart{%
<code>extractdistort</code> (param.)	
<code>extractscale</code> (param.)	
<code>extractangle</code> (param.)	
<code>extractpretex</code> (param.)	
<code>extractapptex</code> (param.)	
<code>extractruns</code> (param.)	
<code>latexopt</code> (param.)	

```

1754 \PackageWarning{svg}{%
1755     The macro ‘\string\svghidepreamblestart’ is only meant\MessageBreak%
1756     to be used together with package ‘svg-extract’.\MessageBreak%
1757     Nevertheless, nothing will happen%
1758 }%
1759 }
1760 \newcommand*\svghidepreambleend{%
1761 \PackageWarning{svg}{%
1762     The macro ‘\string\svghidepreambleend’ is only meant\MessageBreak%
1763     to be used together with package ‘svg-extract’.\MessageBreak%
1764     Nevertheless, nothing will happen%
1765 }%
1766 }
1767 </base>

```

These two macros can be used to hide some parts of the preamble during reading the preamble of the main document.

```

1768 <*extract>
1769 \let\svghidepreamblestart\relax
1770 \let\svghidepreambleend\relax
1771 </extract>

```

C.3. Auxiliary macros

```

\svg@extract The macro \svg@extract does the actual job of both extracting and converting independent
\svgx@stream@in graphic files. Since it is necessary to run it with --shell-escape enabled, the command
\svgx@read@line raises a warning if it is not activated. Afterwards, the package is finished.
\svgx@stream@out
\if@svgx@preamble@write
1772 <*base>
1773 \newcommand*\svg@extract[1]{%
1774 </base>
1775 <*extract>
1776 \ifnum\pdf@shellescape=\@ne\relax\else%
1777 \renewcommand*\svg@extract[1]{%
1778 \if@svgx@run%
1779 \begingroup%
1780 \edef\svg@tempa{#1}%
1781 \svg@quotes@remove{\svg@tempa}%
1782 \PackageWarning{svg-extract}{%
1783     You didn’t enable ‘shell escape’ (or ‘write18’)\MessageBreak%
1784     so it wasn’t possible to run the extraction for\MessageBreak%
1785     file ‘\svg@tempa’\MessageBreak%
1786 }%
1787 \endgroup%
1788 \fi%
1789 }%
1790 \expandafter\endinput%
1791 \fi

```

If `--shell-escape` is enabled, the command is defined with its intended functionality. Some macros and an input stream as well as an output stream are necessary for this.

```

1792 \newread\svgx@stream@in
1793 \newcommand*\svgx@read@line{}
1794 \newwrite\svgx@stream@out
1795 \newif\if@svgx@preamble@write
1796 \renewcommand*\svg@extract[1]{%

```

If option `extract` is enabled...

```

1797 \if@svgx@run%

```

...the macro `\svgx@get@out@sec` is used to get the current level numbering within the document and the counter for extracted graphics is stepped. After that, a separate auxiliary \LaTeX file is created for extracting independent graphic files. The macro `\svgx@get@out@sec` is used to get the current level numbering within the document. The specified preamble is read for this task, if it exists. It is first searched in the same folder as the SVG file and if it wasn't found, in any other valid folder for SVG files.

```

1798 \if@svgx@out@sec%
1799 \svgx@get@out@sec%
1800 \fi%
1801 \stepcounter{svgx@out@count}%
1802 \begingroup%
1803 \def\svg@tempa##1.##2\@nil{%
1804 \IfArgIsEmpty{##2}{\edef\svgx@preamble{##1.\svgx@latex@ext}}{}}%
1805 }%
1806 \expandafter\svg@tempa\svgx@preamble.\@nil%
1807 \IfFileExists{\svg@file@path\svgx@preamble}{%
1808 \@svg@file@foundtrue%
1809 }{%
1810 \svg@get@path[]{\svgx@preamble}{\svg@out@path}%
1811 \def\svg@tempa####1.####2\@nil{%
1812 \edef\svgx@preamble{\svg@file@name.####2}%
1813 }%
1814 \expandafter\svg@tempa\svgx@preamble\@nil%
1815 }%
1816 \edef\svg@tempa{%
1817 \endgroup%
1818 \if@svg@file@found%
1819 \ifx\svg@file@path\@empty%
1820 \def\noexpand\svgx@preamble{.\svgx@preamble}%
1821 \else%
1822 \def\noexpand\svgx@preamble{\svg@file@path\svgx@preamble}%
1823 \fi%
1824 \fi%
1825 }%
1826 \svg@tempa%
1827 \begingroup%
1828 \endlinechar=\m@ne%
1829 \IfFileExists{\svgx@preamble}{%
1830 \PackageInfo{svg-extract}{%
1831 The preamble file '\svgx@preamble'\MessageBreak%
1832 is used for the generation of the auxiliary file\MessageBreak%
1833 '\svgx@out@name.\svgx@latex@ext'%
1834 }%

```

The catcodes for # need to be changed to prevent doubling when reading the line.

```

1835 \catcode'\#=12\relax%
1836 \immediate\openout\svgx@stream@out=\svgx@out@name.\svgx@latex@ext%
1837 \immediate\openin\svgx@stream@in=\svgx@preamble%
1838 \@svg@tempswatrue%
1839 \@svgx@preamble@writetrue%
1840 \def\svgx@read@line{%

```

The given preamble file is read line by line and written to the separate auxiliary \LaTeX file `\svgx@out@name.\svgx@latex@ext` via the output stream.

```

1841 \@whiles\if@svg@tempswa\fi{%
1842 \immediate\read\svgx@stream@in to\svgx@read@line%
1843 \ifx\svgx@read@line\@empty%
1844 \ifeof\svgx@stream@in\@svg@tempswafalse\fi%
1845 \else%

```

With `\svghidepreamblestart` and `\svghidepreambleend` it is possible for the user to omit certain parts of the preamble. Therefore the two macros `\svgx@read@preamble@till` and

\svgx@read@preamble@from are toggling the switch \if@svgx@preamble@write

```
1846         \svgx@read@preamble@till{\svghidepreamblestart}{}%  
1847         \svgx@read@preamble@from{\svghidepreambleend}{}%
```

If the desired end of the preamble (\svgx@endpreamble) was found, the readout is terminated by switching \if@svgx@tempswa to false.

```
1848         \svgx@read@preamble@till{\svgx@endpreamble}{\@svg@tempswafalse}%  
1849         \if@svgx@preamble@write%
```

During the readout process, it is searched with \svgx@documentclass for the appearance of \documentclass and \if@svgx@classfound is set to true if it was found.

```
1850         \if@svgx@classfound\else%  
1851         \expandafter\svgx@documentclass%  
1852         \svgx@read@line\documentclass\documentclass\@nil%  
1853         \fi%
```

Writing out the—maybe manipulated—read in line.

```
1854         \ifx\svgx@read@line\@empty\else%  
1855         \immediate\write\svgx@stream@out{%  
1856         \unexpanded\expandafter{\svgx@read@line}%  
1857         }%  
1858         \fi%  
1859         \fi%  
1860         \fi%  
1861     }%  
1862     \immediate\closein\svgx@stream@in%  
1863     \immediate\closeout\svgx@stream@out%  
1864     \catcode'\#=#\relax%
```

Once the separate auxiliary L^AT_EX file is written, it is read in again and its content is stored in \svg@tempa, since it is necessary to prepend some stuff to the preamble, for example a maybe not existent document class.

```
1865     \immediate\openin\svgx@stream@in=\svgx@out@name.\svgx@latex@ext%  
1866     \def\svg@tempa{}%  
1867     \loop\unless\ifeof\svgx@stream@in%  
1868     \readline\svgx@stream@in to\svgx@read@line%  
1869     \ifx\svgx@read@line\@empty\else%  
1870     \edef\svg@tempa{%  
1871     \unexpanded\expandafter{\svg@tempa}%  
1872     \unexpanded\expandafter{\svgx@read@line}^^J%  
1873     }%  
1874     \fi%  
1875     \repeat%  
1876     \immediate\closein\svgx@stream@in%  
1877 }{%
```

If a file was given that doesn't exist, a warning is issued.

```
1878     \svg@quotes@remove{\svgx@preamble}%  
1879     \ifx\svgx@preamble\@empty\else%  
1880     \PackageWarning{svg-extract}{%  
1881     The preamble file '\svgx@preamble'\MessageBreak%  
1882     does not exist%  
1883     }%  
1884     \fi%  
1885     \def\svg@tempa{}%  
1886 }{%
```

After the preamble was read in and stored in `\svg@tempa`, the separate auxiliary L^AT_EX file is written again. Some information are written right at the beginning of the file.

```

1887 \immediate\openout\svgx@stream@out=\svgx@out@name.\svgx@latex@ext%
1888 \immediate\write\svgx@stream@out{%
1889 \@percentchar\@percentchar\space This file was generated by package
1890 'svg-extract'^^J%
1891 \@percentchar\@percentchar\space from source '\jobname'^^J%
1892 \@percentchar\@percentchar\space It's intended to be compiled with
1893 '\svgx@latex@exe\ifx\svgx@latex@opt\@empty\else\space\svgx@latex@opt\fi'
1894 }%

```

With the intention of passing the correct paper dimensions, the calculating of the paper size is executed with `\AtBeginDocument` even before the document class, so that this is definitely the first thing to happen at the beginning of the document. Additionally, it is ensured that the `\special` command is definitely used with the correct paper size, when creating a DVI file.

```

1895 \immediate\write\svgx@stream@out{%
1896 \string\AtBeginDocument{\@percentchar^^J%
1897 \space\space\string\svgxsetpapersize\@percentchar^^J%
1898 \ifxetex\else\ifpdf\else%
1899 \space\space\string\AtBeginDvi{\string\special{%
1900 papersize=\string\the\string\paperwidth,%
1901 \string\the\string\paperheight%
1902 }}\@percentchar^^J%
1903 \fi\fi%
1904 }^^J%
1905 \string\PassOptionsToPackage{hidelinks}{hyperref}%
1906 }%

```

If no document class was found during reading the preamble file, then class `\article` is used.

```

1907 \ifsvgx@classfound\else%
1908 \immediate\write\svgx@stream@out{\string\documentclass{article}}%
1909 \fi%

```

And now the stored preamble.

```

1910 \ifx\svg@tempa\@empty\else%
1911 \immediate\write\svgx@stream@out{\unexpanded\expandafter{\svg@tempa}}%
1912 \fi%

```

After the given preamble was written, package **svg-extract** will be loaded in case it was forgotten.

```

1913 \immediate\write\svgx@stream@out{\string\usepackage{svg-extract}}%

```

Now all parameters relevant for the extraction are evaluated and appended.

```

1914 \def\svg@tempa##1{%
1915 \immediate\write\svgx@stream@out{\string\svgsetup{##1}}%
1916 }%
1917 \if@svg@ink@latex\else%
1918 \svg@tempa{inkscape@latex=false}%
1919 \fi%
1920 \ifdim\svgx@param@width>\z@\relax%
1921 \svg@tempa{width=\svgx@param@width}%
1922 \fi%
1923 \ifdim\svgx@param@height>\z@\relax%
1924 \svg@tempa{height=\svgx@param@height}%
1925 \fi%
1926 \if@svgx@param@distort%
1927 \svg@tempa{distort=true}%
1928 \fi%
1929 \ifdim\dimexpr\svgx@param@scale\p@\relax=\p@\relax\else%

```

```

1930     \svg@tempa{scale=\svgx@param@scale}%
1931     \fi%
1932     \def\svg@tempb{\svg@param@pretex}%
1933     \ifx\svgx@param@pretex\svg@tempb\relax%
1934     \let\svgx@param@pretex\svg@param@pretex%
1935     \fi%
1936     \ifx\svgx@param@pretex\relax\else%
1937     \svg@tempa{pretex=\unexpanded\expandafter{\svgx@param@pretex}}%
1938     \fi%
1939     \def\svg@tempb{\svg@param@apptex}%
1940     \ifx\svgx@param@apptex\svg@tempb\relax%
1941     \let\svgx@param@apptex\svg@param@apptex%
1942     \fi%
1943     \ifx\svgx@param@apptex\relax\else%
1944     \svg@tempa{apptex=\unexpanded\expandafter{\svgx@param@apptex}}%
1945     \fi%

```

Parameter `lastpage` is only considered for including PDF files with L^AT_EX support.

```

1946     \let\svg@tempa\@empty%
1947     \if@svg@ink@latex%
1948     \ifstr{\svg@ink@format}{pdf}{%
1949     \ifnum\value{svg@param@lastpage}>\z@ \relax%
1950     \edef\svg@tempa{lastpage=\the\value{svg@param@lastpage}}%
1951     \else%
1952     \ifnum\value{svg@param@lastpage}=\z@ \relax%
1953     \def\svg@tempa{lastpage=true}%
1954     \else%
1955     \def\svg@tempa{lastpage=false}%
1956     \fi%
1957     \fi%
1958     }{}%
1959     \fi%

```

The rotation angle, if given.

```

1960     \ifdim\dimexpr\svgx@param@angle\p@ \relax=\z@ \relax\else%
1961     \edef\svg@tempa{%
1962     angle=\svgx@param@angle\ifx\svg@tempa\@empty\else,\svg@tempa\fi%
1963     }%
1964     \fi%

```

As we are now at the end of the preamble and just before the beginning of the document, the paper dimension are set again to make sure, that these settings are active at the end of the preamble. Additionally, it is executed again at the very end of `\AtBeginDocument` to ensure, that no other package used this hook for manipulating the paper size.

```

1965     \ifx\svg@tempa\@empty%
1966     \def\svg@tempa{\string\svgxsetbox{#1}}%
1967     \else%
1968     \edef\svg@tempa{\noexpand\string\noexpand\svgxsetbox[\svg@tempa]{#1}}%
1969     \fi%
1970     \immediate\write\svgx@stream@out{\svg@tempa}%

```

Package `xr` is used to evaluate possible labels within the included **Inkscape** L^AT_EX file.

```

1971     \if@svg@ink@latex%
1972     \IfFileExists{xr.sty}{%
1973     \immediate\write\svgx@stream@out{%
1974     \string\usepackage{xr}^^J%
1975     \string\externaldocument{\jobname}^^J%
1976     }%
1977     }{}%
1978     \fi%
1979     \immediate\write\svgx@stream@out{%
1980     \string\begin{document}^^J%

```

```

1981     \string\pagestyle{empty}^^J%
1982     \string\svgxoutputbox\@percentchar^^J%
1983     \string\end{document}}%
1984     }%
1985     \immediate\closeout\svgx@stream@out%
1986 \endgroup%

```

After creating the separate auxiliary L^AT_EX file, the actual extraction and conversion can be done.

```

1987 \ifstr{\svgx@format\svgx@cnv@format}{-}{%
1988   \PackageWarning{svg-extract}{%
1989     Both keys 'extractformat' and 'convertformat' are\MessageBreak%
1990     empty, so nothing to do so far%
1991   }%
1992 }%

```

As the extraction maybe needs to include the main auxiliary file with `\externaldocument` provided by package `xr` it is necessary to do all related stuff after the main auxiliary file was written. This is done with `\AfterReadingMainAux` provided by package `scrfile`.

```

1993     \svg@quotes@remove{\svgx@out@path}%
1994     \svg@quotes@remove{\svgx@out@name}%

```

All generated files will be moved to the desired output folder, which is given by option `extractpath`. Therefor, this folder is created.

```

1995     \edef\svg@tempb{%
1996       \noexpand\svg@shell@mkdir{\svgx@out@path}%
1997     }%
1998     \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%

```

First of all the separate auxiliary L^AT_EX file is compiled with the detected L^AT_EX processor (`\svgx@latex@exe`) as often as defined by counter option `extractruns`.

```

1999     \edef\svg@tempb{%
2000       \noexpand\PackageInfo{svg-extract}{%
2001         Running LaTeX (\svgx@latex@exe) for graphic extraction%
2002         \ifx\svgx@latex@opt\@empty\else%
2003           \MessageBreak with added options '\svgx@latex@opt'%
2004         \fi%
2005       }%
2006     }%
2007     \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%
2008     \edef\svg@tempb{%
2009       \noexpand\ShellEscape{%
2010         \svgx@latex@exe\space\svgx@latex@opt\space%
2011         "\svgx@out@name.\svgx@latex@ext"%
2012       }%
2013     }%
2014     \loop\ifnum\value{svgx@runs}>\z@\relax%
2015       \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%
2016       \advance\c@svgx@runs\m@ne%
2017     \repeat%

```

All files requested with option `extractformat` are created with internal conversion tools supplied by most L^AT_EX 2_ε distributions if necessary.

```

2018     \def\svg@tempa##1##2##3{%
2019       \edef\svg@tempb{%
2020         \noexpand\ShellEscape{%
2021           \@nameuse{svgx@##1@exe}\space\@nameuse{svgx@##1@opt}\space%
2022           "\svgx@out@name.##2"%
2023         }%
2024       }%
2025       \AfterReadingMainAux{\PackageInfo{svg-extract}{Running ##1}}%

```



```

2026     \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%
2027   }%
2028   \@svg@tempswafalse%
2029   \ifxetex\else\ifpdf\else%
2030     \svg@tempswatruetrue%
2031   \fi\fi%
2032   \if@svg@tempswa%
2033     \svg@tempa{dvips}{dvi}{ps}%
2034     \svgx@ifinlist{eps}{\svgx@format}{\svg@tempa{pstoeeps}{ps}{eps}}{}%
2035     \svgx@ifinlist{pdf}{\svgx@format}{\svg@tempa{pstopdf}{ps}{pdf}}{}%
2036   \else%
2037     \svgx@ifinlist{eps}{\svgx@format}{\svg@tempa{pdftoeeps}{pdf}{eps}}{}%
2038     \svgx@ifinlist{ps}{\svgx@format}{\svg@tempa{pdftops}{pdf}{ps}}{}%
2039   \fi%

```

Now the desired conversion tool is invoked if requested.

```

2040     \if@svgx@cnv@run%

```

If no density was given at all, the density for PNG files is set to 300dpi by default.

```

2041     \ifx\svgx@cnv@dpi\relax%
2042     \ifx\svgx@cnv@dpi@png\@undefined%
2043     \def\svgx@cnv@dpi@png{300}%
2044     \fi%
2045     \fi%

```

The first given file type with option `extractformat` is used as source for the conversion process.

```

2046     \expandafter\svgx@cnv@get@informat\expandafter{\svgx@format}%

```

The conversion is done for each desired file type given in a list by option `convertformat`.

```

2047     \@for\svg@tempa:=\svgx@cnv@format\do{%
2048     \ifx\svg@tempa\@empty\else%
2049     \expandafter\svgx@ifinlist\expandafter{\svg@tempa}{\svgx@format}{%
2050     \PackageWarning{svg-extract}{%
2051     File type ‘\svg@tempa’ was specified for option\MessageBreak%
2052     ‘extractformat’ (\svgx@format) as well as for \MessageBreak%
2053     option ‘convertformat’ (\svgx@cnv@format) so the\MessageBreak%
2054     conversion won’t be done%
2055     }%
2056     }{%
2057     \edef\svg@tempb{%
2058     \noexpand\PackageInfo{svg-extract}{%
2059     Converting ‘\svgx@out@name.\svgx@cnv@informat’\MessageBreak%
2060     to ‘\svgx@out@name.\svg@tempa’%
2061     }%
2062     }%
2063     \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%
2064     \edef\svg@tempb{%
2065     \noexpand\ShellEscape{%
2066     \svgx@cnv@cmd{\svgx@out@name}{\svgx@cnv@informat}{\svg@tempa}%
2067     }%
2068     }%
2069     \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%
2070     }%
2071     \fi%
2072   }%
2073   \fi%

```

As both extraction and conversion are done, all files are moved to the desired output folder (`extractpath`).

```

2074     \edef\svg@tempa{\svgx@format\if@svgx@cnv@run,\svgx@cnv@format\fi}%
2075     \@for\svg@tempb:=\svg@tempa\do{%

```

```

2076     \ifx\svg@tempb\@empty\else%
2077     \edef\svg@tempb{%
2078         \noexpand\svgx@move{\svgx@out@name}{\svg@tempb}{\svgx@out@path}%
2079     }%
2080     \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%
2081     \fi%
2082 }%

```

At the very end, all unwanted auxiliary files are deleted.

```

2083     \@for\svg@tempa:=\svgx@clean\do{%
2084         \expandafter\svgx@ifinlist\expandafter{\svg@tempa}{\svg@tempb}{}%
2085         \edef\svg@tempb{%
2086             \noexpand\IfFileExists{"\svgx@out@name" . \svg@tempa}{%
2087                 \noexpand\svg@shell@rm{\svgx@out@name . \svg@tempa}%
2088             }{}%
2089         }%
2090         \expandafter\AtEndDocument\expandafter{%
2091             \expandafter\AfterReadingMainAux\expandafter{\svg@tempb}%
2092         }%
2093     }%
2094 }%
2095 }%
2096 \fi%
2097 }
2098 </extract>

```

`\svgx@get@out@sec` The macro `\svgx@get@out@sec` reads all sectioning counters in order to get the numbering of the current sectioning level. The value is stored in `\svgx@out@sec`.

```

2099 \newcommand*\svgx@out@sec{unknown}
2100 \newcommand*\svgx@get@out@sec{%
2101     \begingroup%
2102     \def\svg@tempa{}%
2103     \@for\svg@tempb:={%
2104         part,chapter,section,subsection,subsubsection,paragraph,subparagraph%
2105     }\do{%
2106         \ifx\svg@tempb\@empty\else%
2107             \scr@ifundefinedorrelax{the\svg@tempb}{}%
2108             \ifnum\value{\svg@tempb}>\z@&relax%
2109                 \edef\svg@tempa{\svg@tempb}%
2110             \fi%
2111         }%
2112     \fi%
2113 }%
2114 \edef\svg@tempb{%
2115     \endgroup%
2116     \ifx\svg@tempa\@empty\else%
2117         \def\noexpand\svgx@out@sec{\csname the\svg@tempa\endcsname}%
2118     \fi%
2119 }%
2120 \svg@tempb%
2121 }

```

`\svgx@documentclass` This delimited macro is used to find a occurrence of `\documentclass` within a read in line.
`\if@svgx@classfound` The delimiter `\documentclass` is used twice in order to ignore the possible occurrence of white space or anything else right before `\documentclass`.

```

2122 \newif\if@svgx@classfound
2123 \newcommand*\svgx@documentclass{}
2124 \def\svgx@documentclass#1\documentclass#2\documentclass#3\@nil{%
2125     \IfArgIsEmpty{#2}{}\@svgx@classfoundtrue}%
2126 }

```

`\svgx@read@preamble@till` These macros are used to skip some parts of a read in preamble file.
`\svgx@read@preamble@from`
`\svgx@read@preamble@skip`

```
2127 \newcommand*\svgx@read@preamble@till[2]{%
2128   \svgx@read@preamble@skip#1\@nil{till}{#2}%
2129 }
2130 \newcommand*\svgx@read@preamble@from[2]{%
2131   \svgx@read@preamble@skip#1\@nil{from}{#2}%
2132 }
```

In principle, the functionality is the same as for `\svgx@documentclass`.

```
2133 \newcommand*\svgx@read@preamble@skip{}
2134 \def\svgx@read@preamble@skip#1\@nil#2#3{%
```

A given token is used to create the macro `\svg@tempa` delimited by the token itself which is used twice to get any stuff right before or after the occurrence.

```
2135 \def\svg@tempa##1{%
2136   \def\svg@tempa###1##1###2##1###3\@nil{%
2137     \IfArgIsEmpty{###3}{-}{%
```

Write everything which was found right before the macro which starts hiding area to the output stream and stop writing with `\if@svgx@preamble@write`.

```
2138   \ifstr{#2}{till}{%
2139     \IfArgIsEmpty{###1}{-}{%
2140       \immediate\write\svgx@stream@out{###1}%
2141     }%
2142     \@svgx@preamble@writefalse%
2143   }{%
```

Write everything which was found right after the macro which ends the hiding area and start writing again with `\if@svgx@preamble@write`.

```
2144   \ifstr{#2}{from}{%
2145     \IfArgIsEmpty{###2}{-}{%
2146       \def\svgx@read@line{}%
2147     }{%
2148       \def\svgx@read@line{###2}%
2149     }%
2150     \@svgx@preamble@writetrue%
2151   }{-%
2152   }%
```

Additional stuff which should be done.

```
2153     #3%
2154   }%
2155 }%
2156 }
```

Creating the macro `\svg@tempa` delimited by the first argument.

```
2157 \edef\svg@tempb{\expandafter\detokenize\expandafter{#1}}%
2158 \expandafter\svg@tempa\expandafter{\svg@tempb}%
```

Calling the created macro.

```
2159 \edef\svg@tempb{%
2160   \expandafter\detokenize\expandafter{\svgx@read@line}\svg@tempb\svg@tempb%
2161 }%
2162 \expandafter\svg@tempa\svg@tempb\@nil%
2163 }
```

`\svgx@cnv@informat` The first list entry from argument (`\svgx@format`) is extracted by `\svgx@cnv@get@informat`.
`\svgx@cnv@get@informat`

```
2164 \newcommand*\svgx@cnv@informat{}
2165 \newcommand*\svgx@cnv@get@informat[1]{%
2166   \begingroup%
2167     \def\svg@tempa##1,##2\@nil{%
2168       \def\svg@tempa{##1}%
2169     }%
2170     \svg@tempa#1,\@nil%
2171   \edef\svg@tempa{%
2172     \endgroup%
2173     \def\noexpand\svgx@cnv@informat{\svg@tempa}%
2174   }%
2175   \svg@tempa%
```

If the first argument (`\svgx@format`) was empty, `\svgx@cnv@informat` is set to the a file type, which is generated anyway.

```
2176   \ifx\svgx@cnv@informat\@empty%
2177     \renewcommand*\svgx@cnv@informat{pdf}%
2178   \ifxetex\else\ifpdf\else%
2179     \renewcommand*\svgx@cnv@informat{ps}%
2180   \fi\fi%
2181 \fi%
2182 }
```

`\svgx@magick@cmd` Depending on option `convert`, one of these two macros is actually used by `\svgx@cnv@cmd`.
`\svgx@gs@cmd` For invoking the conversion process, the required platform-dependent executable is set, if nothing was set by a package option.

```
2183 \ifx\svgx@magick@exe\@empty
2184   \ifwindows
2185     \renewcommand*\svgx@magick@exe{magick}
2186   \else
2187     \renewcommand*\svgx@magick@exe{convert}
2188   \fi
2189 \fi
2190 \newcommand*\svgx@magick@cmd[3]{%
2191   \svgx@magick@exe\space%
2192   \svgx@useformatkey{svgx@cnv@dpi}{#3}{-density }%
2193   \svgx@useformatkey{svgx@magick@set}{#3}{}%
2194   "#1.#2"\space%
2195   \svgx@useformatkey{svgx@magick@opr}{#3}{}%
2196   "#1.#3"%
2197 }
```

```
2198 \ifx\svgx@gs@exe\@empty
2199   \ifwindows
2200     \renewcommand*\svgx@gs@exe{gswin64c}
2201   \else
2202     \renewcommand*\svgx@gs@exe{gs}
2203   \fi
2204 \fi
2205 \newcommand*\svgx@gs@cmd[3]{%
2206   \svgx@gs@exe\space-dSAFER -dPATCH -dNOPAUSE\space%
2207   \svgx@useformatkey{svgx@gs@device}{#3}{-sDEVICE=%}
2208   \svgx@useformatkey{svgx@cnv@dpi}{#3}{-r}%
2209   \svgx@useformatkey{svgx@gs@opt}{#3}{}%
2210   -sOutputFile="#1.#3"\space"#1.#2"%
2211 }
```

`\svgx@move` If the file doesn't exist

```
2212 \newcommand*\svgx@move[3]{%
2213   \begingroup%
```

```

2214 \IfFileExists{"#1".#2}{%
2215 \svg@shell@move{#1.#2}{#3#1.#2}%
2216 }{%
2217 \edef\svg@tempa{#2}%
2218 \@svg@tempswafalse%
2219 \expandafter\svgx@ifinlist\expandafter{\svg@tempa}{\svgx@cnv@format}{%
2220 \@svg@tempswatruetrue%
2221 \def\svg@tempb{conversion}%
2222 }{%
2223 \expandafter\svgx@ifinlist\expandafter{\svg@tempa}{pdf,ps,eps}{%
2224 \@svg@tempswatruetrue%
2225 \def\svg@tempb{extraction}%
2226 }{}%
2227 }%
2228 \if@svg@tempswa%
2229 \edef\svg@tempb{%
2230 The graphic file \svg@tempb\space failed\MessageBreak%
2231 for '#1.#2'\MessageBreak%
2232 Troubleshooting: Please check the log file how\MessageBreak%
2233 the invocation of the extraction took place and\MessageBreak%
2234 try to execute it yourself in the terminal%
2235 }%
2236 \else%
2237 \def\svg@tempb{%
2238 The extraction to format '#2' failed\MessageBreak%
2239 for '#1.#2'\MessageBreak%
2240 Only file types 'pdf,ps,eps' are supported for\MessageBreak%
2241 key 'exportformat'%
2242 }%
2243 \fi%
2244 \PackageWarning{svg-extract}{\svg@tempb}%
2245 }%
2246 \endgroup%
2247 }

```

`\svgx@ifinlist` Check, if the first argument is included in a comma-separated list in the second argument. Keep in mind that the first argument is not expanded at all, the second one exactly once.

```

2248 \newcommand*\svgx@ifinlist[2]{%
2249 \beginingroup%
2250 \def\svg@tempa##1,#1,##2\@nil{%
2251 \IfArgIsEmpty{##2}{%
2252 \aftergroup\@secondoftwo%
2253 }{%
2254 \aftergroup\@firstoftwo%
2255 }%
2256 }%
2257 \expandafter\svg@tempa\expandafter,#2,#1,\@nil%
2258 \endgroup%
2259 }

```

`\svgx@onlywindows` Do only some stuff, if Windows was detected.

```

2260 \newcommand*\svgx@onlywindows[1]{%
2261 \AfterPackage*{ifplatform}{\renewcommand*\svgx@onlywindows[1]{\ifwindows#1\fi}}

```

`\svgx@ifkeyandval` It is checked whether a key was given as $\langle key \rangle = \langle value \rangle$ or like $\langle key \rangle = \{ \langle format \rangle = \langle value \rangle \}$.

```

2262 \newcommand*\svgx@ifkeyandval[3]{%
2263 \def\svg@tempa##1==##2==##3\@nil{\ifstr{##3}{=}{#2}{#3}}%
2264 \svg@tempa#1==\@nil%
2265 }

```

`\svgx@cnv@get@dpi` This macro is used to resolve a given value to set the density for the conversion. The delimited macros `\svg@tempa` and `\svg@tempb` are defined to first crop any given suffix `dpi` and second to split two numbers at `x`, if present. Pay attention how both macros are invoked. In the end, a passed value in any of the forms `300`, `300dpi`, `300x400` or `300x400dpi` and even `300dpix400dpi` is possible. The result is stored in `\svg@tempa`.

```
2266 \newcommand*\svgx@cnv@get@dpi[1]{%
2267   \begingroup%
2268     \def\svg@tempa##1dpi##2x##3dpi##4\@nil{%
2269       \edef\svg@tempa{##1}%
```

Switch `\if@svg@tempswa` as `\iftrue` means, a valid value was found.

```
2270   \@svg@tempswafalse%
```

If only the first argument is a number and third is empty, a single number was given and there's nothing more to do. If the argument is something like `300dpix400dpi`, the third argument is the second number.

```
2271     \ifnumber{##1}{%
2272       \IfArgIsEmpty{##3}{\@svg@tempswatrue}{%
2273         \ifnumber{##3}{\edef\svg@tempa{##1x##3}}{}}%
2274       }%
2275     }{%
2276       \if@svg@tempswa\else%
2277         \expandafter\svg@tempb\svg@tempa xx\@nil%
2278       \fi%
2279     }%
```

Macro `\svg@tempb` splits at `x` and checks, if something valid like `300x400` was given. If true, the value is stored in `\svg@tempa`.

```
2280   \def\svg@tempb##1x##2x##3\@nil{%
2281     \ifstr{##3}{x}{%
2282       \@svg@tempswatrue%
2283       \IfArgIsEmpty{##1}{\@svg@tempswafalse}{%
2284         \ifnumber{##1}{\@svg@tempswafalse}%
2285       }%
2286       \IfArgIsEmpty{##2}{\@svg@tempswafalse}{%
2287         \ifnumber{##2}{\@svg@tempswafalse}%
2288       }%
2289       \if@svg@tempswa%
2290       \edef\svg@tempa{##1x##2}%
2291       \fi%
2292     }{%
2293   }%
2294   \IfArgIsEmpty{#1}{%
2295     \let\svg@tempa\@empty%
2296   }{%
2297     \lowercase{\svg@tempa#1dpi#1xdpi\@nil}%
2298     \if@svg@tempswa\else%
2299       \let\svg@tempa\relax%
2300     \fi%
2301   }%
2302   \edef\svg@tempb{%
2303     \endgroup%
2304     \ifx\svg@tempa\relax%
2305       \let\noexpand\svg@tempa\noexpand\relax%
2306     \else%
2307       \def\noexpand\svg@tempa{\svg@tempa}%
2308     \fi%
2309   }%
2310   \svg@tempb%
2311 }
```

`\svgx@setformatkey` With `\svgx@setformatkey` the—maybe output format depend—keys for the conversion tools are set. First argument contains the value given to a key, second the command sequence name of the macro, to whom the value shall be allocated.

```
2312 \newcommand*\svgx@setformatkey[2]{%
```

A key of the form $\langle key \rangle = \{ \langle format \rangle = \langle value \rangle \}$ is given. The desired output format can be accessed with `##1`, the value with `##2` within the arguments of `\svgx@ifkeyandval`.

```
2313 \svgx@ifkeyandval{#1}{%
2314 \svg@ifvalueisrelax{##2}{%
2315 \expandafter\let\csname #2@##1\endcsname\relax%
2316 }{%
2317 \@namedef{#2@##1}{##2}%
2318 }%
```

A key of the form $\langle key \rangle = \{ \langle format \rangle = \langle value \rangle \}$ is given. The value can be used with `##1`.

```
2319 }{%
2320 \svg@ifvalueisrelax{##1}{%
2321 \expandafter\let\csname #2\endcsname\relax%
2322 }{%
2323 \@namedef{#2}{##1}%
2324 }%
2325 }%
2326 }
```

The command `\svgx@useformatkey` checks, if a format specific key was defined with `\svgx@setformatkey`, whereas the format is given in the second argument. If this is not the case, the setting for all output formats is used. After that, a specific key appended with a `+` can be used to do some additional stuff.

```
2327 \newcommand*\svgx@useformatkey[3]{%
2328 \scr@ifundefinedorrelax{#1@#2}{%
2329 \scr@ifundefinedorrelax{#1}{-}{%
2330 \expandafter\ifx\csname #1\endcsname\@empty\else%
2331 #3\@nameuse{#1}\space%
2332 \fi%
2333 }%
2334 \scr@ifundefinedorrelax{#1@#2+}{-}{%
2335 \expandafter\ifx\csname #1@#2+\endcsname\@empty\else%
2336 #3\@nameuse{#1@#2+}\space%
2337 \fi%
2338 }%
2339 }{%
```

If this a format specific key was defined, it is used.

```
2340 \expandafter\ifx\csname #1@#2\endcsname\@empty\else%
2341 #3\@nameuse{#1@#2}\space%
2342 \fi%
2343 }%
2344 }
```

C.4. Commands for the separate auxiliary L^AT_EX-file

For the extraction of independent graphics, an auxiliary L^AT_EX file is needed. Within this file, the following commands are used to include the desired graphic.

`\svgxsetbox` Within the preamble of the auxiliary L^AT_EX file, the desired graphic is used to setup a box, which is used both to define the papersize as well as for the output itself. The macro `\svgx@setbox` is executed twice, the first time in the preamble and the second time at the very end of `\AtBeginDocument` if package **etoolbox** was loaded.

The switch `\if@svgx@standalone` is defined for enabling classes to implement a different behaviour for **svg-extract** in standalone mode. For example, TUD-Script-classes are using this switch.

```

2345 \newif\if@svgx@standalone
2346 \newcommand*{svgxsetbox}[2] [] {%
2347   \@svgx@standalonetrue%
2348   \svgx@setbox{#1}{#2}%
2349   \scr@ifundefinedorrelax{AtEndPreamble}{%
2350     \let\svg@tempa\@firstofone%
2351   }{%
2352     \def\svg@tempa{\AtEndPreamble}%
2353   }%
2354   \svg@tempa{\AtBeginDocument{\svgx@setbox{#1}{#2}}}%
2355 }
2356 \newcommand*{svgx@setbox}[2] {%
2357   \sbox\svg@box{\svg@input[#{1},draft=false]{#2}}%
2358   \svgxsetpapersize%
2359 }

```

`\svgxsetpapersize` This macro sets all well known length macros for defining the paper size as well as the type area to the size of `\svg@box`.

```

2360 \newcommand*{svgxsetpapersize}{%
2361   \setlength\paperwidth{\the\wd\svg@box}%

```

Due to the fact, that the lengths for stock- and mediasizes are maybe set to `\relax`, these macros are checked with `\scr@ifundefinedorrelax`.

```

2362   \scr@ifundefinedorrelax{stockwidth}{}{%
2363     \setlength\stockwidth{\paperwidth}%
2364   }%
2365   \scr@ifundefinedorrelax{mediawidth}{}{%
2366     \setlength\mediawidth{\paperwidth}%
2367   }%
2368   \setlength\textwidth{\paperwidth}%
2369   \setlength\paperheight{\the\dimexpr\ht\svg@box+\dp\svg@box\relax}%
2370   \scr@ifundefinedorrelax{stockheight}{}{%
2371     \setlength\stockheight{\paperheight}%
2372   }%
2373   \scr@ifundefinedorrelax{mediaheight}{}{%
2374     \setlength\mediaheight{\paperheight}%
2375   }%
2376   \setlength\textheight{\paperheight}%

```

Any other length regarding the layout is set to have no influence at all. Hence the document has the same size as the graphic.

```

2377   \hoffset=-1in%
2378   \oddsidemargin=\z@%
2379   \evensidemargin=\z@%
2380   \voffset=-1in%
2381   \topmargin=\z@%
2382   \headheight=\z@%
2383   \headsep=\z@%
2384   \topskip=\z@%
2385   \footskip=\z@%
2386   \marginparsep=\z@%
2387   \marginparwidth=\z@%
2388   \marginparpush=\z@%
2389 }
2390 \@onlypreamble\svgxsetpapersize

```

`\svgxoutputbox` With `\svgxoutputbox` the created box is displayed.
`\if@svgx@beamer`


```

2391 \newif\if@svgx@beamer
2392 \@ifclassloaded{beamer}{\@svgx@beamertrue}{}%
2393 \newcommand*{svgxoutputbox{%
2394   \begingroup%
2395     \setlength\parindent{\z@}%
2396     \setlength\parskip{\z@}%
2397     \setlength\parfillskip{\z@}%
2398     \if@svgx@beamer%
2399       \setbeamertemplate{navigation symbols}{}%
2400       \begin{frame}[plain]%
2401         \usebox\svg@box%
2402       \end{frame}%
2403     \else%
2404       \usebox\svg@box%
2405     \fi%
2406   \endgraf%
2407 \endgroup%
2408 }

```

D. Processing Options

Setting the default options and processing the given ones during when loading the packages.

```

2409 (*base)
2410 \FamilyExecuteOptions{SVG}{%
2411   inkscape=true,inkscapepath=basesubdir,
2412   inkscapelatex=true,inkscapearea=drawing,distort=false,%
2413   usecolor=true,usetransparent=true%
2414 }
2415 </base>
2416 (*extract)
2417 \FamilyExecuteOptions{SVG}{%
2418   extract=true,extractpath=basesubdir,%
2419   extractruns=2,extractname=namenummered,extractdistort=false,%
2420   convert=magick,convert=false,%
2421   gsdevice={png=png16m},gsdevice={jpeg=jpeg},gsdevice={jpg=jpeg},%
2422   gsdevice={tif=tiff48nc},gsdevice={tiff=tiff48nc},%
2423   gsdevice={eps=eps2write},gsdevice={ps=ps2write}%
2424 }
2425 </extract>
2426 \FamilyProcessOptions{SVG}

```

E. Macros for file access

Finally, platform dependend macros for creating directories as well as moving and deleting files are provided, if `--shell-escape` is enabled. Only then package **ifplatform** is only used in order to do not raise a warning.

```

2427 \ifnum\pdf@shellescape=\@ne\relax\else%
2428   \expandafter\endinput%
2429 \fi
2430 \RequirePackage{ifplatform}[2010/10/22]

```

```

\svg@shell@mkdir The platform dependent commands for file access.
\svg@shell@mkdir
  \svg@shell@mv 2431 \ifwindows
  \svg@shell@mv 2432   \newcommand*{svg@shell@mmkdir[1]{if not exist "#1" mkdir "#1"}
  \svg@shell@rm 2433   \newcommand*{svg@shell@mmove}
  \svg@shell@rm 2434   \newcommand*{svg@shell@mrm}{del}
  \svg@shell@rm 2435 \else
  \svg@shell@rm 2436   \newcommand*{svg@shell@mmkdir[1]{mkdir -p "#1"}

```

```

2437 \newcommand*\svg@shell@mv{mv}
2438 \newcommand*\svg@shell@rm{rm}
2439 \fi

```

A directory should only be created, if it isn't the current working directory.

```

2440 \newcommand*\svg@shell@mkdir[1]{%
2441 \begingroup%
2442 \svg@quotes@remove[#1]{\svg@tempa}%
2443 \@svg@tempswattrue%
2444 \ifstr{\svg@tempa}{.}{\@svg@tempswafalse}{%
2445 \ifstr{\svg@tempa}{.}{\@svg@tempswafalse}{%
2446 }}%
2447 \if@svg@tempswa%
2448 \ShellEscape{\svg@shell@mkdir{\svg@tempa}}%
2449 \fi%
2450 \endgroup%
2451 }

```

Commands for moving and deleting files.

```

2452 \newcommand*\svg@shell@move[2]{%
2453 \ShellEscape{\svg@shell@mv\space"#1"\space"#2"}%
2454 }
2455 \newcommand*\svg@shell@rm[1]{%
2456 \ShellEscape{\svg@shell@rm\space"#1"}%
2457 }

```

At the very end, the catcodes are restored.

```

2458 \svg@catcodecodes@restore

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described. Numbers underlined refer to the code line of the definition.

A	
apptex (opt.)	5, 311
C	
clean (opt.)	9, 1687
clear (opt.)	1687
convert (opt.)	10, 1314
convertdensity (opt.)	1417
convertdpi (opt.)	10, 1417
convertformat (opt.)	10, 1390
counters:	
svg@param@lastpage	334
svgx@out@count	1486
svgx@runs	1210
D	
distort (opt.)	5, 254
draft (opt.)	6, 348
dvipsopt (opt.)	9, 1265
E	
end (opt.)	1183
eps (opt.)	1142
exclude (opt.)	10, 1708
ext (opt.)	216
extension (opt.)	216
extract (opt.)	8, 1110
extractapptex (opt.)	9, 1651
extractdistort (opt.)	9, 1555
extractformat (opt.)	8, 1142
extractheight (opt.)	9, 1555
extractkeepaspectratio (opt.)	1555
extractname (opt.)	8, 1486
extractpath (opt.)	8, 1486
extractpostex (opt.)	1651
extractpreamble (opt.)	9, 1183
extractpreambleend (opt.)	9, 1183
extractpretex (opt.)	9, 1651
extractruns (opt.)	9, 1210
extractscale (opt.)	9, 1555
extractwidth (opt.)	9, 1555
G	
gsdevice (opt.)	11, 1464
gsexex (opt.)	11, 1464
gsopt (opt.)	11, 1464
H	
height (opt.)	5, 254
I	
\if@svg@draft	348
\if@svg@file@found	489
\if@svg@ink@run	827
\if@svg@param@distort	254
\if@svg@quotes@found	387
\if@svg@tempswa	14
\if@svg@use@transparent	32
\if@svg@use@xcolor	32
\if@svgx@beamer	2391
\if@svgx@classfound	2122
\if@svgx@cnv@run	1314
\if@svgx@out@sec	1486
\if@svgx@preamble@write	1772
\if@svgx@run	1110
\if@svgx@standalone	2345
\includeinkscape	6–7, 744 , 1730
angle (param.)	7, 785
apptex (param.)	7, 785
clean (param.)	8, 1730
convert (param.)	8, 1730
convertdpi (param.)	8, 1730
convertformat (param.)	8, 1730
distort (param.)	7, 785
draft (param.)	7, 785
exclude (param.)	8, 1730
extract (param.)	8, 1730
extractangle (param.)	8, 1730
extractapptex (param.)	8, 1730
extractdistort (param.)	8, 1730
extractformat (param.)	8, 1730
extractheight (param.)	8, 1730
extractpreamble (param.)	8, 1730
extractpretex (param.)	8, 1730
extractruns (param.)	8, 1730
extractscale (param.)	8, 1730
extractwidth (param.)	8, 1730
gsdevice (param.)	8, 1730
gsopt (param.)	8, 1730
height (param.)	7, 785
inkscapeformat (param.)	7, 785
inkscapelatex (param.)	7, 785
lastpage (param.)	7, 785
latexopt (param.)	8, 1730
magickoperator (param.)	8, 1730
magicksetting (param.)	8, 1730
origin (param.)	7, 785
pretex (param.)	7, 785
scale (param.)	7, 785
width (param.)	7, 785
\includesvg	6–7, 693 , 1730
angle (param.)	6, 728
apptex (param.)	6, 696
clean (param.)	8, 1730
convert (param.)	8, 1730
convertdpi (param.)	8, 1730
convertformat (param.)	8, 1730
distort (param.)	6, 696
draft (param.)	6, 696
exclude (param.)	8, 1730
extract (param.)	8, 1730
extractangle (param.)	7–8, 1730
extractapptex (param.)	8, 1730
extractdistort (param.)	8, 1730
extractformat (param.)	8, 1730
extractheight (param.)	8, 1730
extractpreamble (param.)	8, 1730
extractpretex (param.)	8, 1730
extractruns (param.)	8, 1730
extractscale (param.)	8, 1730
extractwidth (param.)	8, 1730

gsdevice (param.)	8, 1730	ext	216
gsopt (param.)	8, 1730	extension	216
height (param.)	6, 696	extract	8, 1110
inkscape (param.)	6, 696	extractapptex	9, 1651
inkscapearea (param.)	6, 696	extractdistort	9, 1555
inkscaledpi (param.)	6, 696	extractformat	8, 1142
inkscapeformat (param.)	6, 696	extractheight	9, 1555
inksapelatex (param.)	6, 696	extractkeepaspectratio	1555
inkscapeopt (param.)	6, 696	extractname	8, 1486
lastpage (param.)	6, 725	extractpath	8, 1486
latexopt (param.)	8, 1730	extractpostex	1651
magickoperator (param.)	8, 1730	extractpreamble	9, 1183
magicksetting (param.)	8, 1730	extractpreambleend	9, 1183
origin (param.)	6, 728	extractpretex	9, 1651
pretex (param.)	6, 696	extractruns	9, 1210
scale (param.)	6, 696	extractscale	9, 1555
svgextension (param.)	6, 696	extractwidth	9, 1555
width (param.)	6, 696	gsdevice	11, 1464
inkscape (opt.)	4, 56	gsexex	11, 1464
inkscapearea (opt.)	5, 163	gsopt	11, 1464
inkscapedensity (opt.)	177	height	5, 254
inkscapedpi (opt.)	5, 177	inkscape	4, 56
inkscapeexe (opt.)	5, 194	inkscapearea	5, 163
inkscapeformat (opt.)	5, 138	inkscapedensity	177
inkscapelatex (opt.)	5, 159	inkscapedpi	5, 177
inkscapename (opt.)	5, 223	inkscapeexe	5, 194
inkscapeopt (opt.)	5, 194	inkscapeformat	5, 138
inkscapepath (opt.)	4, 223	inkscapelatex	5, 159
K			
keepaspectratio (opt.)	254	inkscapename	5, 223
L			
lastpage (opt.)	6, 334	inkscapeopt	5, 194
latex (opt.)	159	inkscapepath	4, 223
latexexe (opt.)	9, 1227	keepaspectratio	254
latexext (opt.)	9, 1227	lastpage	6, 334
latexopt (opt.)	9, 1227	latex	159
M			
magickexe (opt.)	11, 1442	latexexe	9, 1227
magickoperator (opt.)	11, 1442	latexext	9, 1227
magicksetting (opt.)	11, 1442	latexopt	9, 1227
N			
name (opt.)	1486	magickexe	11, 1442
nottransparent (opt.)	3, 32	magickoperator	11, 1442
noxcolor (opt.)	3, 32	magicksetting	11, 1442
O			
off (opt.)	7, 136 , 1138	name	1486
on (opt.)	7, 136 , 1138	nottransparent	3, 32
options:		noxcolor	3, 32
apptex	5, 311	off	7, 136 , 1138
clean	9, 1687	on	7, 136 , 1138
clear	1687	path	1486
convert	10, 1314	pdf	1142
convertdensity	1417	pdflatex	1227
convertdpi	10, 1417	pdftepsopt	9, 1265
convertformat	10, 1390	pdftops	1265
distort	5, 254	pdftopsopt	9, 1265
draft	6, 348	png	1390
dvipsopt	9, 1265	postex	311
end	1183	preamble	1183
eps	1142	pretex	5, 311
exclude	10, 1708	pstoeptopt	9, 1265
		pstopdfopt	9, 1265
		scale	5, 254
		svgextension	5, 216
		svgpath	204
		tex	159
		usetransparent	3, 32
		usexcolor	3, 32
		width	5, 254

P

parameters:

angle-\includeinkscape	7, 785
angle-\includesvg	6, 728
apptex-\includeinkscape	7, 785
apptex-\includesvg	6, 696
clean-\includeinkscape	8, 1730
clean-\includesvg	8, 1730
convert-\includeinkscape	8, 1730
convert-\includesvg	8, 1730
convertdpi-\includeinkscape	8, 1730
convertdpi-\includesvg	8, 1730
convertformat-\includeinkscape	8, 1730
convertformat-\includesvg	8, 1730
distort-\includeinkscape	7, 785
distort-\includesvg	6, 696
draft-\includeinkscape	7, 785
draft-\includesvg	6, 696
exclude-\includeinkscape	8, 1730
exclude-\includesvg	8, 1730
extract-\includeinkscape	8, 1730
extract-\includesvg	8, 1730
extractangle-\includeinkscape	8, 1730
extractangle-\includesvg	7-8, 1730
extractapptex-\includeinkscape	8, 1730
extractapptex-\includesvg	8, 1730
extractdistort-\includeinkscape	8, 1730
extractdistort-\includesvg	8, 1730
extractformat-\includeinkscape	8, 1730
extractformat-\includesvg	8, 1730
extractheight-\includeinkscape	8, 1730
extractheight-\includesvg	8, 1730
extractpreamble-\includeinkscape	8, 1730
extractpreamble-\includesvg	8, 1730
extractpretex-\includeinkscape	8, 1730
extractpretex-\includesvg	8, 1730
extractruns-\includeinkscape	8, 1730
extractruns-\includesvg	8, 1730
extractscale-\includeinkscape	8, 1730
extractscale-\includesvg	8, 1730
extractwidth-\includeinkscape	8, 1730
extractwidth-\includesvg	8, 1730
gsdevice-\includeinkscape	8, 1730
gsdevice-\includesvg	8, 1730
gsopt-\includeinkscape	8, 1730
gsopt-\includesvg	8, 1730
height-\includeinkscape	7, 785
height-\includesvg	6, 696
inkscape-\includesvg	6, 696
inkscapearea-\includesvg	6, 696
inkscapedpi-\includesvg	6, 696
inkscapeformat-\includeinkscape	7, 785
inkscapeformat-\includesvg	6, 696
inkscapelatex-\includeinkscape	7, 785
inkscapelatex-\includesvg	6, 696
inkscapeopt-\includesvg	6, 696
lastpage-\includeinkscape	7, 785
lastpage-\includesvg	6, 725
latexopt-\includeinkscape	8, 1730
latexopt-\includesvg	8, 1730
magickoperator-\includeinkscape	8, 1730
magickoperator-\includesvg	8, 1730
magicksetting-\includeinkscape	8, 1730

magicksetting-\includesvg	8, 1730
origin-\includeinkscape	7, 785
origin-\includesvg	6, 728
pretex-\includeinkscape	7, 785
pretex-\includesvg	6, 696
scale-\includeinkscape	7, 785
scale-\includesvg	6, 696
svgextension-\includesvg	6, 696
width-\includeinkscape	7, 785
width-\includesvg	6, 696
path (opt.)	1486
pdf (opt.)	1142
pdflatex (opt.)	1227
pdftops (opt.)	9, 1265
pdftops (opt.)	1265
pdftops (opt.)	9, 1265
png (opt.)	1390
postex (opt.)	311
preamble (opt.)	1183
pretex (opt.)	5, 311
pstoeps (opt.)	9, 1265
pstopdf (opt.)	9, 1265

S

scale (opt.)	5, 254
\setsvg	679
\svg@append@input@path	411
\svg@box	14
\svg@deactivate@dq	351
\svg@deprecated@key	24
\svg@deprecated@param	805
\svg@dumy@key	1083
\svg@extension@parse	562
\svg@extension@@parse	562
\svg@extract	1772
\svg@file@base	489
\svg@file@ext	216
\svg@file@missing	597
\svg@file@name	489
\svg@file@path	489
\svg@file@suffix	489
\svg@filename@parse	525
\svg@get@lastpage	910
\svg@get@path	489
\svg@iffilenewer	643
\svg@ifvalueisrelax	478
\svg@includegraphics@file	1065
\svg@includegraphics@patched	1065
\svg@includegraphics@saved	1033
\svg@ink@area	163
\svg@ink@cmd	902
\svg@ink@dpi	177
\svg@ink@exe	194
\svg@ink@format	138
\svg@ink@latex	159
\svg@ink@mode	56
\svg@ink@opt	194
\svg@ink@run	827
\svg@input	961
\svg@input@path	681
\svg@@input	961
\svg@local@param@def	658
\svg@local@param@set	658
\svg@local@param@use	658
\svg@normalize@path	452
\svg@normalize@@path	452

convertdpi (opt.): new	1417
convertformat (opt.): new	1390
draft (opt.): new	348
dvipsopt (opt.): new	1265
end (opt.): deprecated	1183
eps (opt.): deprecated	1142
extract (opt.): new	1110
extractapptex (opt.): new	1651
extractformat (opt.): new	1142
extractheight (opt.): new	1555
extractname (opt.): new	1486
extractpath (opt.): new	1486
extractpreamble (opt.): new	1183
extractpreambleend (opt.): new	1183
extractpretex (opt.): new	1651
extractrtrns (opt.): new	1210
extractscale (opt.): new	1555
extractwidth (opt.): new	1555
gsdevice (opt.): new	1464
gsexec (opt.): new	1464
gsopt (opt.): new	1464
height (opt.): new	254
\includeinkscape: new	744
\includesvg:	
changes, especially to optional	
parameters	693
angle (param.): new	728
draft (param.): new	696
height (param.): new	696
inkscape (param.): new	696
inkscapearea (param.): new	696
inkscapedpi (param.): new	696
inkscapeformat (param.): new	696
inkscapelatex (param.): new	696
inkscapeopt (param.): new	696
lastpage (param.): new	725
origin (param.): new	728
scale (param.): new	696
inkscape (opt.): changed/extended	56
inkscapearea (opt.): new	163
inkscapedpi (opt.): new	177
inkscapeexe (opt.): new	194
inkscapeformat (opt.): new	138
inkscapelatex (opt.): new	159
inkscapename (opt.): new	223
inkscapeopt (opt.): new	194
inkscapepath (opt.): new	223
lastpage (opt.): new	334
latexexe (opt.): new	1227
latexext (opt.): new	1227
latexopt (opt.): new	1227
magickexe (opt.): new	1442
magickoperator (opt.): new	1442
magicksetting (opt.): new	1442
name (opt.):	
deprecated	1486
support of subfig removed	1486
notransparent (opt.): new	32
noxcolor (opt.): new	32
off (opt.): new	136, 1138
on (opt.): new	136, 1138
path (opt.): deprecated	1486
pdf (opt.): deprecated	1142
pdflatex (opt.): deprecated	1227
pdfstoeps (opt.): new	1265
pdftops (opt.): deprecated	1265
pdftopsopt (opt.): new	1265
png (opt.): deprecated	1390
postex (opt.): deprecated	311
preamble (opt.): deprecated	1183
pstoeps (opt.): new	1265
pstopdf (opt.): new	1265
scale (opt.): new	254
\setsvg: deprecated	679
\svghidepreambleend: new	1752
\svghidepreamblestart: new	1752
\svgpath: new	681
svgpath (opt.): deprecated	204
\svgsetup: new	679
usetransparent (opt.): new	32
usexcolor (opt.): new	32
v2.00a	
Implementation	
\svgxsetpapersize: Bug fix for	
checking stock- and mediasizes	2360
v2.00b	
Implementation	
latex (opt.): new, alternative key for	
inkscapelatex	159
tex (opt.): new, alternative key for	
inkscapelatex	159
v2.01	
General	
new option svgextension to change the	
format of files exported by Inkscape	
from svg to a custom one	2
usage of <code>\input{<tex filename>}</code> within	
Inkscape graphics locates files in all	
declared searched folders	2
Implementation	
\includesvg:	
svgextension (param.): new	696
inkscape (opt.): using <code>\trim@spaces</code>	56
\svg@append@input@path: new	411
\svg@get@path:	
using <code>\svg@set@input@path</code>	489
using <code>\trim@spaces</code>	489
\svg@set@input@path: new	411
svgextension (opt.): new due to user	
request	216
v2.02	
General	
distortion of included and extracted	
graphics supported with options	
distort (or keepaspectratio) and	
extractdistort as well as rotation	
for extractions (extractangle)	2
fixed errors with active double quotes	
from babel in path arguments	2
multiple dots within file names possible	2
package trimspaces required	2
Implementation	
distort (opt.): new	254
extractdistort (opt.): new	1555
extractname (opt.): usage of	
<code>\svg@quotes@remove</code>	1486
extractpath (opt.): usage of	
<code>\svg@sanitize@dq</code>	1486
\if@svgx@standalone : new	2345

<code>\includeinkscape:</code>	
usage of <code>\svg@extension@parse</code> ..	744
<code>extractdistort</code> (param.): new ..	1730
<code>\includesvg:</code>	
switched to <code>\svg@filename@parse</code>	693
<code>angle</code> (param.): validation of argument	728
<code>distort</code> (param.): new	696
<code>extractangle</code> (param.): new	1730
<code>extractdistort</code> (param.): new ..	1730
<code>inkscape</code> (opt.): usage of <code>\svg@sanitize@dq</code>	56
<code>inkscapepath</code> (opt.): usage of <code>\svg@sanitize@dq</code>	223
<code>keepaspectratio</code> (opt.): new	254
<code>\svg@append@input@path:</code> avoid duplicates in <code>\input@path</code>	411
<code>\svg@deactivate@dq:</code> new	351
<code>\svg@extension@parse:</code> new	562
<code>\svg@extension@@parse:</code> new	562
<code>\svg@file@missing:</code> notify svg file when missing exported files	597
<code>\svg@filename@parse:</code>	
usage of <code>\svg@extension@parse</code> ..	525
usage of <code>\svg@remove@leadingchar</code>	525
usage of <code>\svg@sanitize@dq</code>	525
<code>\svg@local@param@set:</code> reasonable value for key <code>distort</code>	658
<code>\svg@normalize@path:</code> usage of <code>\svg@deactivate@dq</code>	452
<code>\svg@quotes@remove:</code>	
calling <code>\svg@quotes@check</code>	362

usage of <code>\svg@sanitize@dq</code>	362
<code>\svg@remove@leadingchar:</code> new	395
<code>\svg@sanitize@dq:</code> new	356
<code>\svg@set@input@path:</code> usage of <code>\svg@deactivate@dq</code>	411
<code>svgextension</code> (opt.):	
usage of <code>\svg@quotes@remove</code>	216
usage of <code>\svg@remove@leadingchar</code>	216
<code>\svgpath:</code> parse argument for enclosing braces and provide if necessary ..	681
<code>\svgx@setbox:</code> new	2345
<code>\svgxsetbox:</code> late execution of <code>\svgxsetpapersize</code>	2345

v2.02a

General	
fix bug for package polyglossia which fakes babel poorly	2
Implementation	
<code>\svg@deactivate@dq:</code> bug fix for polyglossia	351

v2.02b

General	
fix bug for package tikzscale which changes <code>\includegraphics</code> globally ..	2
Implementation	
<code>\svg@patches:</code> fix bug for package tikzscale: store original definitions of <code>\picture</code> and <code>\includegraphics</code> right after loading package svg ..	1033